PHRASETRANSFORMER: SELF-ATTENTION USING LOCAL CONTEXT FOR SEMANTIC PARSING

ABSTRACT

Semantic parsing is a challenging task whose purpose is to convert a natural language utterance to machine-understandable information representation. Recently, solutions using Neural Machine Translation have achieved many promising results, especially Transformer because of the ability to learn long-range word dependencies. However, the one drawback of adapting the original Transformer to the semantic parsing is the lack of detail in expressing the information of sentences. Therefore, this work proposes a PhraseTransformer architecture that is capable of a more detailed meaning representation by learning the phrase dependencies in the sentence. The main idea is to incorporate Long Short-Term Memory (LSTM) into the Self-Attention mechanism of the original Transformer to capture more local context of phrases. Experimental results show that the proposed model captures the detailed meaning better than Transformer, raises local context awareness and achieves strong competitive performance on Geo, MSParS datasets, and leads to new state-of-the-art (SOTA) performance on Atis dataset.

1 INTRODUCTION

Semantic parsing is an important task which can be applied for many applications such as Question and Answering systems or searching systems using natural language Woods (1973); Waltz & Goodman (1977). For example, the sentence *"which state borders hawaii"* can be represented as logical form (LF) using λ-calculus syntax *"(lambda $0 e (and (state:t $0) (next_to:t $0 hawaii)))"*. There are various strategies have been developed to address the semantic parsing task such as constructing handcraft-rules Woods (1973); Waltz & Goodman (1977); Hendrix et al. (1978), using Combinatory Categorial Grammar (CCG) Zettlemoyer & Collins (2005; 2007); Kwiatkowski et al. (2011), adapting statistical machine translation method Wong & Mooney (2006; 2007) or Neural Machine Translation Dong & Lapata (2016); Jia & Liang (2016); Dong & Lapata (2018); Cao et al. (2019). The major factor of the CCG method is based on the alignments of sub-parts (lexicons or phrase) between a natural sentence and corresponding logical form and to learn how to combine these subparts best. In more detail the phrase *"borders hawaii"* is aligned to *"(next_to:t $0 hawaiiz)"* in LF. Conversely, the methods using Neural Machine Translation learn the encoder representing a sentence into a vector and decode that vector into LF. The current SOTA models are Sequence-to-Sequence using LSTM (Seq2seq) Dong & Lapata (2018); Cao et al. (2019) on Geo, Atis and Transformer Ge et al. (2019) on MSParS. The number of works using the deep learning method is increasing because of the effectiveness and a small number of handcraft features. Therefore, we concentrate on the approaches using Transformer and LSTM models to improve performance.

According to CCG methods, the semantic representation of a sentence is the combination of sub-meaning representation generated by phrases in a sentence. However, Transformer architecture

Figure 1: Pharse alignments in PhraseTransformer.

only learns the dependencies between single words without considering the local context by the phrase. Therefore, we propose a new architecture named PhraseTransformer that focuses on learning the relations of phrases in a sentence (Figure 1). To do this, we modify the Multi-head Attention Vaswani et al. (2017) by applying the self-attention mechanism into phrases instead of single words. Firstly, we use n-gram to split a sentence into phrases. Then, we use the final hidden state of LSTM architecture to represent the local context meaning of those phrases.

Our contributions are: (1) proposing a novel model based on Transformer that works effectively for semantic parsing tasks, (2) conducting experiments to confirm the awareness capacity of the model, (3) achieving competitive performance on Geo, MSParS datasets and new SOTA performance on Atis dataset.

2 RELATED WORK

As stated in Section 1, recent research results show that using the Deep Learning approach achieved promising achievements. These methods are divided into three groups:

Decoder Customization. Dong & Lapata apply the Seq2seq model to semantic parsing task and introduce Sequence-to-tree (Seq2tree) Dong & Lapata (2016) model constructing the tree structure of the LF. The authors demonstrate that the structural information in LF is lost when treating it as a sequence. Therefore, the Seq2tree model focuses on modifying the decoding method and based on bracket pairs to start a new decoding level. On the other hand, Dong & Lapata (2018) continue to introduce a new architecture Coarse-to-Fine (Coarse2Fine) based on a rough sketch of meaning to improve the structure-awareness of Seq2seq model. Similarly, Li et al. (2019) also uses the sketch meaning mechanism on BERT model Devlin et al. (2019) by two steps: classify the template of LF and fill the low-level information to that template. In our opinion, the main problem is the understanding capacity of the model because almost semantic parsers do not require generating new logical expressions but are complex in combining sub logic components. Therefore, this work focuses on change the Encoder architecture to improve the understanding capacity of the model.

Data Augmentation. There are numerous works that focus on data augmentation to improve the performance of the semantic parsing model Jia & Liang (2016); Ziai (2019); Herzig & Berant (2019). Jia & Liang propose three rules based on Synchronous Context-Free Grammar to recombine data. This step increases the size of the training data and grows the performance of the model Jia & Liang (2016). Similarly, Ziai proposes a method that automatically augments data based on the co-occurrence of words in the sentence. The author separates the training process into two phases: (1) use augmented data to train for BERT Devlin et al. (2019) and (2) fine-tuning on original data.

Weak Supervision. Some methods use semi-supervised learning for semantic parsing task such as Kočiský et al. (2016); Yin et al. (2018); Goldman et al. (2018); Cao et al. (2019; 2020). These works are promising approaches for the data-hungry problem because of the ability to extract latent information such as unpaired logical forms. In our proposed model, we aim to construct the latent representation for phrases and learn these representations via the self-attention mechanism of the Transformer. We hypothesis that complicated sentences are constructed from various phrases, so learning to represent these phrases makes the model more generalizable.

3 MODEL ARCHITECTURE

Our novel architecture (Figure 2) is based on the Encoder-Decoder of Transformer Vaswani et al. (2017). We define two models named *PhraseTransformer* to improve the encoding quality of Transformer by enhancing the architecture of Encoder while keeping the original Decoder.

Transformer Encoder (original). In Transformer Encoder architecture, the authors proposed a stack of N Identical Layer; each layer consists of two sub-layers: Multi-Head Attention layer and Position-wise Feed-Forward layer. Let set x be an input vector synthesized from the vector word embedding and positional encoding $x = [x_1, ..., x_{|S|}]$ where $|S|$ is sentence length.

In the Multi-Head Attention layer Vaswani et al. use the Linear layer to get multi-views for the inputs. This layer processes the input vector (x) and generates H distinct featured vectors (H is

Figure 2: PhraseTransformer Encoder architecture using n-gram LSTM in MultiHead Layer. In this case, n-gramLSTM layer is built with $\boldsymbol{n} = [0, 0, 2, 2, 3, 3, 4, 4]$, 2-gram, 3-gram, 4-gram models apply to every two heads from head 3 to head 8.

the number of heads) and forwards to Self-Attention layer using Scaled-Dot Product. After that, all heads are processed by Concat and Linear layers to compute the output of the Multi-Head layer.

$$\boldsymbol{q}_i, \boldsymbol{k}_i, \boldsymbol{v}_i = \boldsymbol{x}\boldsymbol{W}_i^q, \boldsymbol{x}\boldsymbol{W}_i^k, \boldsymbol{x}\boldsymbol{W}_i^v \tag{1}$$

$$\boldsymbol{head}_i = \text{Attention}(\boldsymbol{q}_i, \boldsymbol{k}_i, \boldsymbol{v}_i) \tag{2}$$

$$\boldsymbol{h}_{MulH} = [\boldsymbol{head}_1; ...; \boldsymbol{head}_H]\boldsymbol{W}^o \tag{3}$$

$$\boldsymbol{h}_{Norm} = \text{LayerNorm}(\boldsymbol{h}_{MulH} + \boldsymbol{x}) \tag{4}$$

$$\boldsymbol{h}_{out} = \text{LayerNorm}(\text{FeedForward}(\boldsymbol{h}_{Norm}) + \boldsymbol{h}_{Norm}) \tag{5}$$

where Attention is Scaled Dot-Product Attention:

$$\text{Attention}(\boldsymbol{q}_i, \boldsymbol{k}_i, \boldsymbol{v}_i) = \text{softmax}(\frac{\boldsymbol{q}_i \boldsymbol{k}_i^\mathsf{T}}{\sqrt{d_h}})\,\boldsymbol{v}_i \tag{6}$$

where d_h is dimensions per head, i is the identical index of head ($0 < i \leq H$), $\boldsymbol{W}$ is parameters, LayerNorm, FeedForward are the functions proposed by Vaswani et al. (2017).

PhraseTransformer Encoder. The Encoder is enhanced from the original model in Multi-Head Attention layer because this layer is the major factor to extract the features of inputs sequence. More detail, after H heads are generated by Linear layer, we use n-gram model to split the sentence into grams and use Bidirectional LSTM Hochreiter & Schmidhuber (1997) to extract the local context information of these grams (Figure 2). Besides, we assume that the meaning phrases are usually composed by difference length, therefore we use various n-gram models. To do this, the Phrase function is in Equation 7:

$$\text{Phrase}(\boldsymbol{s}_i) = \begin{cases} n_i\text{-gramLSTM}(\boldsymbol{s}_i) & \text{if} \quad n_i \neq 0 \\ \boldsymbol{s}_i & \text{otherwise} \end{cases} \tag{7}$$

where $\boldsymbol{s}_i$ is a sequential hidden state of a sentence of head i ($0 < i \leq H$) in Multi-Head layer; $\boldsymbol{n} \in \mathbb{N}^H$ is gram size vector for H heads; n_i is the gram size corresponding to head i; n_i-gramLSTM is a procedure that splits the sequential input into grams by n_i-gram model, and applies Bidirectional LSTM for each gram k of $\boldsymbol{s}_i$:

$$n_i\text{-gramLSTM}(\boldsymbol{s}_i) = [n_i\text{-gramLSTM}_k(\boldsymbol{s}_i)] \tag{8}$$

where n_i-gramLSTM$_k$ is the Bidirectional LSTM computed by sum of forward and backward final hidden state:

$$n_i\text{-gramLSTM}_k(\boldsymbol{s}_i) = LSTM_i^f(n_i\text{-gram}_k(\boldsymbol{s}_i)) + LSTM_i^b(n_i\text{-gram}_k(\boldsymbol{s}_i)) \tag{9}$$

where n_i-gram$_k$ is the gram index k in a sentence, n_i-gramLSTM$_k(\boldsymbol{s}_i)$ is the vector to capture local context of the gram index k. After that, the query ($\boldsymbol{q}_i$), key ($\boldsymbol{k}_i$), value ($\boldsymbol{v}_i$) matrixes (Equation 2)

are replaced by *Phrase* function:

$$\boldsymbol{q}'_i, \boldsymbol{k}'_i, \boldsymbol{v}'_i = \text{Phrase}(\boldsymbol{q}_i), \text{Phrase}(\boldsymbol{k}_i), \text{Phrase}(\boldsymbol{v}_i) \tag{10}$$

$$\boldsymbol{head}_i = \text{Attention}(\boldsymbol{q}'_i, \boldsymbol{k}'_i, \boldsymbol{v}'_i) \tag{11}$$

Residual Connection. Similar to the original Transformer architecture, we also employ a residual connection as an extension aim to effectively integrate local context features and current word information. We used $\text{sigmoid}(\sigma)$ function to adjust the rate of context ($n_i\text{-gramLSTM}_k(\boldsymbol{s}_i)$) and current word ($\boldsymbol{s}_{i,k}$) information. The hidden state $n_i\text{-gramLSTM}_k$ in Equation 8 is replaced as following:

$$n_i\text{-gramLSTM}'_k(\boldsymbol{s}_i) = \sigma(\boldsymbol{s}_{i,k}) \cdot n_i\text{-gramLSTM}_k(\boldsymbol{s}_i) + (\mathbf{1} - \sigma(\boldsymbol{s}_{i,k})) \cdot \boldsymbol{s}_{i,k} \tag{12}$$

Finally, $\boldsymbol{h}_{MulH}, \boldsymbol{h}_{Norm}, \boldsymbol{h}_{out}$ are computed similarly to Transformer architecture.

Training method is to maximize the Log-Likelihood function of the probabilities to generate the LF (y) given a sentence (x) from annotated dataset ($\mathcal{D}$):

$$\text{maximize} : \sum_{<x,y>\in\mathcal{D}} \log p_\theta\left(y|x\right) \tag{13}$$

Metric measurement. On all datasets, we compute sentence-level accuracy by using exact matching (EM) and logic matching (LM) that developed by Dong & Lapata (2018). LM metric measures the performance better than the EM method because it is probable for comparing the variant of expression. For example, the predicted LFs in different order of *and* logic: *and (oneway $0) (<(departure_time $0) ti0)* is equal to *and (<(departure_time $0) ti0) (oneway $0)* .

4 EXPERIMENTS

The purpose of experiments is to compare the performance of PhraseTransformer and extension models with the original Transformer. Besides, we explore the awareness about the phrase alignment between a sentence and the generated LF by PhraseTransformer.

4.1 DATATSETS

We conduct the experiments on three datasets Geo Zelle & Mooney (1996), Atis Dahl et al. (1994) and MSParS Duan (2019). Table 1 shows the observation of these datasets. Geo and Atis datasets are small size but more complicated in information relations than the MSParS dataset. The average length of LFs on Atis dataset (28.4) is about twice longer than that on MSParS dataset (14.7). The original MSParS dataset have large vocabulary (around 40k) because it consists of various entities name in the open domain. Therefore, we preprocess this dataset similarly to Ge et al. (2019) by replacing character "_" by " _ " and using byte-pairs-encoding (BPE) Sennrich et al. (2016) to deal with rare-word problem.

- **Geo** consists of queries about geography information of the U.S. and LFs in lambda-calculus syntax. We use the version preprocessed by Dong & Lapata (2016) by replacing all entities by numbered markers (e.g. *"new york"* → *"s0"*).
- **Atis** consists of queries about flight information and LFs in lambda-calculus syntax. We also use the version preprocessed by Dong & Lapata (2016) similar to Geo dataset.
- **MSParS** is a large-scale open domain dataset with LFs in lambda-DCS syntax Liang et al. (2011). This dataset contains 12 question types Duan (2019) such as single-relation, multi-turn-entity, etc. for Knowledge-based Question Answering system.

4.2 SETTINGS

In training processes of the MSParS and Atis datasets, to prevent overfitting, we use the *early stopping* conditioned on metrics word-level or sentence-level accuracy dev set.

Table 1: Statistics information of three datasets. The MSParS dataset is analyzed on 2 versions: *Origin* - original data, *BPE6k* - preprocessed by BPE 6000 operations. Vocabulary size and average length of source (Src) and target (Tgt) side is computed on train set.

Datatset	Total examples Train - Dev - Test	Vocab size Src	Tgt	Avg. length Src	Tgt
Geo	600 - 0 - 280	433	51	10.6	18.7
Atis	3434 - 491 - 448	120	166	7.3	28.4
MSParS (BPE6k)	63826 - 9000 - 9000	4965	5854	12.8	23.9

Hyper-parameters. Because Transformer is quite sensitive in hyper-parameters, we keep most hyper-parameters the same as Transformer-base model Vaswani et al. (2017) such as the number of layers $N = 6$ and number of heads in Multi-Head layer is $H = 8$; hidden size $d_{model} = 512$; dropout is selected in $\{0.1, 0, 3\}$; Adam optimizer with $\beta_1 = 0.9, \beta_2 = 0.998, \epsilon = 10^{-9}$. The weights of models are initialized with Xavier initialization Glorot & Bengio (2010). The embedding vectors are shared among the source-side and target-side, between the input-to-embedding layer and output-to-softmax layer in Decoder. We also retain the learning rate decay method: $lr(step) = d_{model}^{-0.5} \cdot \min(step^{-0.5}, step \cdot warmup\_steps^{-1.5})$ where $step$ is the current step number. The n-gram size for each head is selected in $\{0, 2, 3, 4\}$. The weights of Bidirectional LSTM layers in the heads using the same n-gram model (e.g. heads 3, 4) are shared. Besides, the experimental dataset sizes are quite different, therefore we use three hyper-parameter sets[1]: **Geo**: $warmup\_step = 100$ learning rate init selected from $\{\mathbf{0.05}, 0.1\}$, $batch\_size = 128$ (the batch size using number of tokens), the maximum traning steps $max\_steps = 15000$; **Atis**: $warmup\_step = 100$ learning rate init selected from $\{\mathbf{0.1}, 0.2\}$, $batch\_size = 4096$. the maximum traning steps $max\_steps = 250000$; **MSParS**: $warmup\_step = 8000$, learning rate init selected from $\{0.5, 1.0, \mathbf{2.0}\}$, $batch\_size = 8192$, the maximum traning steps $max\_steps = 250000$. On this dataset, we conducted experiments to check the number of BPE operations impacting to performance (Figure 3 and Model 4 in Table 2). Based on those results, we use the MSParS dataset preprocessed by BPE 6000 operations for all other experiments.

4.3 RESULTS AND ANALYSIS

4.3.1 PERFORMANCE

Model setting We conducted experiments to find the best gram sizes for PhraseTransformer on Atis and MSParS (Table 2) because the size of those datasets are larger than Geo that make the results are more stable. We hypothesize that performance increases when applying various gram sizes to the Atis dataset. By using various gram sizes, PhraseTransformer can see different linguistic features in various local context sizes in Multi-head layers. Besides, using LSTM to represent spans on all layers helps PhraseTransformer capture more sequential information than Transformer. On MSParS dataset, the performance is not so different when changing gram sizes (Models 1 - 4). We observe that because this dataset has diversity in object name with more than 75% words in vocabulary appearing less than 4 times in train set. One of the challenge of this dataset is to

Table 2: Sentence-level accuracy using exact matching (EM) and logic matching (LM) on two datasets Atis and MSParS using BPE 6000 or 8000 operations. The abbreviation Res. implies that we used residual connection in Equation 12.

Id	Model	gram sizes (n)	Atis		MSParS (BPE6k)		MSParS (BPE8k)	
			EM	LM	EM	LM	EM	LM
1.	PhraseTrans.	$[0; 0; 0; 0; 2; 2; 2; 2]$	87.95	88.84	84.68	85.18	-	-
2.	PhraseTrans.	$[0; 0; 0; 0; 3; 3; 3; 3]$	88.17	89.51	85.13	85.72	-	-
3.	PhraseTrans.	$[0; 0; 0; 0; 2; 2; 3; 3]$	89.06	89.96	85.04	85.39	-	-
4.	PhraseTrans.	$[0; 0; 2; 2; 3; 3; 4; 4]$	**89.51**	**90.40**	85.08	85.47	**84.60**	85.04
5.	PhraseTrans.Res.	$[0; 0; 2; 2; 3; 3; 4; 4]$	88.62	89.51	**85.72**	**86.21**	-	-

---

[1]The model using bold value is achieved a better performance than other values in our experiments.

recognize the object name and type, so capturing original word features is important. These words are usually splited into many word pieces by BPE, so the n_i-gramLSTM component lose original word information when intergrating parts of previous word. For example, the sentence *"boonie bears last movie was"* is preprocessed by BPE: *"bo@@ on@@ ie be@@ ars last movie was"* and the n_i-gramLSTM component considers similar grams *[bo@@ on@@ ie **be@@**], [on@@ ie **be@@**], [ie **be@@**]* when representing **be@@** word vector. PhraseTransformer equipped with the residual connection (Model 5) is able to avoid losing original word pieces features, thus shows better performance on MSParS.

Table 3: Evaluation results using logic matching on all datasets. The reported results on Geo are mean and standard deviation values. The values marked (*) mean that the evaluation metric is denotation match that different from others using sentence-level accuracy. This table contains two parts, the upper part shows the results of previous works and bellow part present our results. Models 4, 5 refer the Id of model in Table 2.

	Geo	Atis	MSParS
Z&C Zettlemoyer & Collins (2007)	86.1	84.6	
λ-WASP Wong & Mooney (2007)	86.6		
FUBL Kwiatkowski et al. (2011)	88.6	82.8	
TISP Zhao & Huang (2015)	**88.9**	84.2	
Seq2tree Dong & Lapata (2016)	87.1	84.6	
Seq2seq+Copy Jia & Liang (2016)	89.3*	83.3	
Coarse2Fine Dong & Lapata (2018)	88.2	87.7	
DualLearning Cao et al. (2019)		89.1	
Bert-Sketch Li et al. (2019)			84.47
Transformer Ge et al. (2019)			85.68
Transformer (ours)	86.8±0.76	87.7	86.19
PhraseTrans. (Model 4)	87.9±0.36	**90.4**	85.47
PhraseTrans.Res. (Model 5)		89.5	**86.21**

Other methods comparison We compare the performance of PhraseTransformer with the original Transformer and other methods in previous works in Table 3. The learning curve in Figure 4 also shows that PhraseTransformer beat clearly Transformer on the Geo dataset on all checkpoints. On Atis dataset, PhraseTransformer is better than Transformer on all settings of gram sizes (Table 2). Our model achieves better results on Atis, MSParS and so competitive with previous results on the Geo dataset. While our method does not use augmented datasets similarly to Jia & Liang (2016); Ge et al. (2019) or the sketch information Dong & Lapata (2018), these results show that our model learns more effectively than the others.

Figure 3: The impact of BPE preprocessing to performance of PhraseTransformer on MSParS dev set.

Figure 4: Token-level accuracy (min, max and average) of PhraseTransformer and the original Transformer on Geo test set.

4.3.2 SELF-AWARENESS

Alignment   We inspect the information learned in PhraseTransformer in Attention layers (Figure 5a). We observe that PhraseTransformer could represent attention information more clearly than Transformer. In both two models, the token *ground_transport* in LF is aligned correctly to phrase *"ground transport"* in the sentence (red alignments). In PhraseTransformer, tokens *to_city*, *from_airport* are also correctly aligned to the corresponding words *"ap0"*, *"ci0"* in the sentence (green and yellow alignments) because these word vectors probable to capture local context better than Transformer. Besides, all tokens decoded by PhraseTransformer paid the same attention to other words that is not key information, such as *"is there"*, *"into"*, *"citi"*. These evidences is positive signals show that the self-awareness of PhraseTrans better than the Transformer.

(a) Encoder-Decoder Attention.   (b) Self-Attention of PhraseTransformer Encoder.

Figure 5: Heatmap visualization of Attention. Figure a shows the difference of alignment Encoder-Decoder attention between the original Transformer (left) and PhraseTransformer (right). Considering one row, the value in each column is corresponding to the rate of the attention of token in LF to the word in the sentence. Figure b shows Self-Attention in 8 heads of the last PhraseTransformer Encoder layer. Two blue rectangles are zoomed-in separately of head 1 (not use n_gramLSTM), head 3 (use 2_gramLSTM).

Figure 5b shows the difference between heads in Self-Attention Encoder of PhraseTransformer. The self-attention in heads that do not use n_gramLSTM is more incoherent than other heads. For example, in head 1, almost words in query focus on *"ci1"* and the other words are paid attention is key information words such as *"da0"*, *"arriv"*, *"ti0"* (the green rectangles). From head 3 to 8, the attention focuses on the separated clusters, which shows that model learned the dependencies of the phrases instead of the single words. On these heads, the attentions are usually between groups important words such as *"flight"* with *"ci1 on"*, *"da0 nm0 dn0 arriv"* with *"nm0 dn0"* (the orange rectangles).

Meaning phrase   In this experiment, we explore the natural language understanding capacity of our PhraseTransformer. We use Principal Component Analysis (PCA) method to visualize the similarity of phrases in PhraseTransformer in Figure 6 by using hidden state of heads 7, 8 (the vector $[q'_7; q'_8]$ where q'_i from Equation 10). We also highlight 30 closest points (the distance using Cosine distance) to the particular phrase carrying key information such as *"round trip"*, *"from ci1 to ci0"*.

Considering two phrases *"from ci1 to ci0"* and *"from ci0 to ci1"* in Figure 6a, the phrases closest to two phrases concentrate on blue and cyan clusters. These two clusters are closest to each other but separate without overlapping. This feature helps the decoder decode different semantic components such as *(from $0 ci0) (to $ 0 ci1)* and *(from $0 ci1) (to $0 ci0)*. Figure 6b shows that the phrase *"from ci1 to ci0"* is represented by the similar vectors in various contexts. For example, this phrase in Atis data sentence 175 *"show me nonstop flight from ci1 to ci0"* has the same meaning in sentence 339 *"a flight from ci1 to ci0 arriv between ti0 and ti1"*. In Figure 6c, there are many different phrases have the same meaning that the model finds out, such as *"could i have"*, *"tell me again"*, *"find me all"* or the phrases closest to *"list the"* and *"show me all"* in Figure 6a. These phrases do not consist of query information, which is the robustness feature of human natural language, this is evidence that the model is capable of learning complicated characteristics of natural language.

(a) All phrases

(b) Phrases closest to "from ci1 to ci0"

(c) Phrases closest to "show me all"

Figure 6: Figure a draws the representing vector of phrases in Selft-Attention Layer using PCA on Atis test set. Figures b, c are zoomed-in view of the blue and red clusters. The labels are annotated for each point in two figures show the information of the phrase corresponding to point following the template *(sentence_id, pharse_position) phrase_content*.

Errors examples We present two frequent error examples that our PhraseTransformer improve Transformer (Table 4). The errors are caused by Transformer confusing the role of entities name such as *"ci2"* and *"ci0"* and missing semantic components such as *"(round_trip $0)"*.

Table 4: Examples that frequent incorrect predictions of Transformer, are improved in PhraseTransformer on the Atis test set.

Sentence	*what are the flight from ci1 to ci2 that stop in ci0.*
Gold LF	(lambda $0 e (and (flight $0) (from $0 ci1) (to $0 **ci2**) (stop $0 **ci0**))).
Transformer	(lambda $0 e (and (flight $0) (from $0 ci1) (to $0 ci0) (stop $0 ci2))).
Sentence	*give me the cheapest round trip flight from ci0 to ci1 around mn0 dn0.*
Gold LF	(argmin $0 (and (flight $0) (from $0 ci0) (to $0 ci1) (day_number $0 dn0) (month $0 mn0)) **(round_trip $0)**) (fare $0)).
Transformer	(argmin $0 (and (flight $0) (from $0 ci0) (to $0 ci1) (day_number $0 dn0) (month $0 mn0)) (fare $0)).

5 CONCLUSION

In this paper, we proposed a novel model named PhraseTransformer that can improve the performance of the Transformer in semantic parsing tasks. We enhance Transformer Encoder to improve the representing ability of the detailed meaning of a sentence based on learning the phrase dependencies. This model obtains SOTA results on the Atis dataset and achieves a competitive result with the SOTA in other datasets. We also conducted experiments to compare with Transformer and show the improvement of self-attention in PhraseTransformer architecture. In future work, we would like to extract more information about this architecture about the relationship between words or phrases and how to inject prior knowledge to improve it. We believe that this architecture can be widely applied in many problems using sequence to sequence models such as neural machine translation and abstract text summarization.

REFERENCES

Ruisheng Cao, Su Zhu, Chen Liu, Jieyu Li, and Kai Yu. Semantic parsing with dual learning. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 51–64, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1007. URL https://www.aclweb.org/anthology/P19-1007.

Ruisheng Cao, Su Zhu, Chenyu Yang, Chen Liu, Rao Ma, Yanbin Zhao, Lu Chen, and Kai Yu. Unsupervised dual paraphrasing for two-stage semantic parsing. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 6806–6817, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.608. URL https://www.aclweb.org/anthology/2020.acl-main.608.

Deborah A. Dahl, Madeleine Bates, Michael Brown, William Fisher, Kate Hunicke-Smith, David Pallett, Christine Pao, Alexander Rudnicky, and Elizabeth Shriberg. Expanding the scope of the atis task: The atis-3 corpus. In *Proceedings of the Workshop on Human Language Technology*, HLT '94, pp. 43–48, USA, 1994. Association for Computational Linguistics. ISBN 1558603573. doi: 10.3115/1075812.1075823. URL https://doi.org/10.3115/1075812.1075823.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL https://www.aclweb.org/anthology/N19-1423.

Li Dong and Mirella Lapata. Language to logical form with neural attention. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 33–43, Berlin, Germany, August 2016. Association for Computational Linguistics. doi: 10.18653/v1/P16-1004. URL https://www.aclweb.org/anthology/P16-1004.

Li Dong and Mirella Lapata. Coarse-to-fine decoding for neural semantic parsing. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 731–742, Melbourne, Australia, July 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1068. URL https://www.aclweb.org/anthology/P18-1068.

Nan Duan. Overview of the nlpcc 2019 shared task: Open domain semantic parsing. In Jie Tang, Min-Yen Kan, Dongyan Zhao, Sujian Li, and Hongying Zan (eds.), *Natural Language Processing and Chinese Computing*, pp. 811–817, Cham, 2019. Springer International Publishing. ISBN 978-3-030-32236-6.

Donglai Ge, Junhui Li, and Muhua Zhu. A transformer-based semantic parser for nlpcc-2019 shared task 2. In *CCF International Conference on Natural Language Processing and Chinese Computing*, pp. 772–781. Springer, 2019.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In Yee Whye Teh and Mike Titterington (eds.), *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, volume 9 of *Proceedings of Machine Learning Research*, pp. 249–256, Chia Laguna Resort, Sardinia, Italy, 13–15 May 2010. PMLR. URL http://proceedings.mlr.press/v9/glorot10a.html.

Omer Goldman, Veronica Latcinnik, Ehud Nave, Amir Globerson, and Jonathan Berant. Weakly supervised semantic parsing with abstract examples. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1809–1819, Melbourne, Australia, July 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1168. URL https://www.aclweb.org/anthology/P18-1168.

Gary G. Hendrix, Earl D. Sacerdoti, Daniel Sagalowicz, and Jonathan Slocum. Developing a natural language interface to complex data. *ACM Trans. Database Syst.*, 3(2):105–147, June 1978. ISSN 0362-5915. doi: 10.1145/320251.320253. URL https://doi.org/10.1145/320251.320253.

Jonathan Herzig and Jonathan Berant. Don't paraphrase, detect! rapid and effective data collection for semantic parsing. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 3810–3820, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1394. URL https://www.aclweb.org/anthology/D19-1394.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural Comput.*, 9(8): 1735–1780, November 1997. ISSN 0899-7667. doi: 10.1162/neco.1997.9.8.1735. URL https://doi.org/10.1162/neco.1997.9.8.1735.

Robin Jia and Percy Liang. Data recombination for neural semantic parsing. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 12–22, Berlin, Germany, August 2016. Association for Computational Linguistics. doi: 10.18653/v1/P16-1002. URL https://www.aclweb.org/anthology/P16-1002.

Tomáš Kočiský, Gábor Melis, Edward Grefenstette, Chris Dyer, Wang Ling, Phil Blunsom, and Karl Moritz Hermann. Semantic parsing with semi-supervised sequential autoencoders. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pp. 1078–1087, Austin, Texas, November 2016. Association for Computational Linguistics. doi: 10.18653/v1/D16-1116. URL https://www.aclweb.org/anthology/D16-1116.

Tom Kwiatkowski, Luke Zettlemoyer, Sharon Goldwater, and Mark Steedman. Lexical generalization in CCG grammar induction for semantic parsing. In *Proceedings of the 2011 Conference on Empirical Methods in Natural Language Processing*, pp. 1512–1523, Edinburgh, Scotland, UK., July 2011. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/D11-1140.

Zechang Li, Yuxuan Lai, Yuxi Xie, Yansong Feng, and Dongyan Zhao. A sketch-based system for semantic parsing. In *CCF International Conference on Natural Language Processing and Chinese Computing*, pp. 748–759. Springer, 2019.

Percy Liang, Michael Jordan, and Dan Klein. Learning dependency-based compositional semantics. In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies*, pp. 590–599, Portland, Oregon, USA, June 2011. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/P11-1060.

Rico Sennrich, Barry Haddow, and Alexandra Birch. Neural machine translation of rare words with subword units. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1715–1725, Berlin, Germany, August 2016. Association for Computational Linguistics. doi: 10.18653/v1/P16-1162. URL https://www.aclweb.org/anthology/P16-1162.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 5998–6008. Curran Associates, Inc., 2017. URL http://papers.nips.cc/paper/7181-attention-is-all-you-need.pdf.

David Waltz and Brad Goodman. Planes: A data base question-answering system. *SIGART Bull.*, (61):24, February 1977. ISSN 0163-5719. doi: 10.1145/1045283.1045288. URL https://doi.org/10.1145/1045283.1045288.

Yuk Wah Wong and Raymond Mooney. Learning for semantic parsing with statistical machine translation. In *Proceedings of the Human Language Technology Conference of the NAACL, Main Conference*, pp. 439–446, New York City, USA, June 2006. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/N06-1056.

Yuk Wah Wong and Raymond Mooney. Learning synchronous grammars for semantic parsing with lambda calculus. In *Proceedings of the 45th Annual Meeting of the Association of Computational Linguistics*, pp. 960–967, Prague, Czech Republic, June 2007. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/P07-1121.

W. A. Woods. Progress in natural language understanding: An application to lunar geology. In *Proceedings of the June 4-8, 1973, National Computer Conference and Exposition*, AFIPS '73, pp. 441–450, New York, NY, USA, 1973. Association for Computing Machinery. ISBN 9781450379168. doi: 10.1145/1499586.1499695. URL https://doi.org/10.1145/1499586.1499695.

Pengcheng Yin, Chunting Zhou, Junxian He, and Graham Neubig. StructVAE: Tree-structured latent variable models for semi-supervised semantic parsing. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 754–765, Melbourne, Australia, July 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1070. URL https://www.aclweb.org/anthology/P18-1070.

John M. Zelle and Raymond J. Mooney. Learning to parse database queries using inductive logic programming. In *Proceedings of the Thirteenth National Conference on Artificial Intelligence - Volume 2*, AAAI'96, pp. 1050–1055. AAAI Press, 1996. ISBN 026251091X.

Luke Zettlemoyer and Michael Collins. Online learning of relaxed CCG grammars for parsing to logical form. In *Proceedings of the 2007 Joint Conference on Empirical Methods in Natural Language Processing and Computational Natural Language Learning (EMNLP-CoNLL)*, pp. 678–687, Prague, Czech Republic, June 2007. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/D07-1071.

Luke S. Zettlemoyer and Michael Collins. Learning to map sentences to logical form: Structured classification with probabilistic categorial grammars. In *Proceedings of the Twenty-First Conference on Uncertainty in Artificial Intelligence*, UAI'05, pp. 658–666, Arlington, Virginia, United States, 2005. AUAI Press. ISBN 0-9749039-1-4. URL http://dl.acm.org/citation.cfm?id=3020336.3020416.

Kai Zhao and Liang Huang. Type-driven incremental semantic parsing with polymorphism. In *Proceedings of the 2015 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 1416–1421, Denver, Colorado, May–June 2015. Association for Computational Linguistics. doi: 10.3115/v1/N15-1162. URL https://www.aclweb.org/anthology/N15-1162.

Amir Ziai. Compositional pre-training for neural semantic parsing. In *Proceedings of the 3rd International Conference on Natural Language and Speech Processing*, pp. 135–141, Trento, Italy, September 2019. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/W19-7419.