Dynamics-aware Skill Generation from Behaviourally Diverse Demonstrations

Abstract

Learning from demonstrations (LfD) provides a data-efficient way for a robot to learn a task by observing humans performing the task, without the need for an explicit reward function. However, in many real-world scenarios (*e.g.*, driving a car) humans often perform the same task in different ways, motivated not only by the primary objective of the task (*e.g.*, reaching the destination safely) but also by their individual preferences (*e.g.*, different driving styles), leading to a multi-modal distribution of demonstrations. In this work, we consider an LfD problem, where the reward function for the main objective of the task is known to the learning agent; however, the individual preferences leading to the variations in the demonstrations are unknown. We show that current LfD approaches learn policies that either track a single mode or the mean of the demonstration distribution. In contrast, we propose an algorithm to learn a diverse set of policies to perform the task, capturing the different modes in the demonstrations due to the diverse preferences of the individuals. We show that we can build a parameterised solution space that captures different behaviour patterns from the demonstrations. Then, a set of policies can be generated in solution space that produce a diverse range of behaviours that go beyond the provided demonstrations.

1 Introduction

Learning from demonstrations (LfD) (Schaal, 1996) provides an alternative way to Reinforcement Learning (RL) for an agent to learn a policy by observing how humans perform similar tasks. However, in many real-world scenarios (*e.g.*, driving a car), humans often perform the same task in different ways. Their behaviours are not only influenced by the primary objective of the task (*e.g.*, reaching the destination safely) but also by their individual preferences or expertise (*e.g.*, different driving styles) (Fürnkranz & Hüllermeier, 2010; Babes et al., 2011). In other words, all the underlying policies optimise the same task reward, but each with different preference components. This leads to a multi-modal distribution of demonstrations, where each mode represents a unique behaviour.

With multi-modal demonstrations, typical LfD methods, such as Behaviour Cloning and Generative Adversarial Imitation Learning, either learn a policy that converges to one of the modes resulting in a *mode-seeking* behaviour or exhibit a *mean-seeking* behaviour by trying to average across different modes (Ke et al., 2020; Ghasemipour et al., 2020; Zhang et al., 2020). While the former will still recover a subset of solutions, the latter may cause unknown behaviour (See Fig 1). Furthermore, none of these approaches is able to learn policies that correspond to the behaviours of a wide range of individuals. Being able to learn a diverse set of policies from demonstrations is often desirable to serve the requirements of a wide range of individual users. For instance, every self-driving car can have a driving policy (selected from the diverse set of pre-trained policies) that matches the preferences of a user. Many recent works show the advantages of having a diverse set of policies, for instance, rapid damage adaptation in robotics (Kaushik et al., 2020; Chatzilygeroudis et al., 2018; Cully et al., 2015) and safe sim-to-real policy transfer in robotics (Kaushik et al., 2022).

In this work, we consider a specific setup of LfD, known as *Imitation learning from observations only* (ILfO), where the learning agent only has access to the state observations but not the corresponding actions. We address the issues of learning from the multi-modal demonstrations under this setup. Unlike most of the IL methods, our goal is not to learn *how to perform a task* (i.e., either

Figure 1: Given the demonstrations from several individuals in **A**, the mean-seeking policy produces unseen behaviour that is unsafe as shown in **B**, the mode-seeking policy only recovers one mode as shown in **C**. We propose a new framework that recovers all the possible solution modes as shown in **D**. The example is inspired from (Ke et al., 2020)

with mean-seeking or mode-seeking policy), but rather *how to perform a task in all possible ways* (i.e., multi-modal policy) as shown in Fig 1D. We assume that the agent has access to a high-fidelity simulator with a task reward function to interact with for its policy optimization, but the preference component that causes diverse behaviour remains unknown. In practice, defining a high-level task reward (sparse reward) can be straightforward, i.e., for autonomous driving, this can be the distance to a target location and the penalty for collision. However, defining the preference component is far from easy, as it may be impossible to find a mathematical expression for each individual's preferences.

As contributions, we first propose a new learning framework that solves the problem of learning from multimodal demonstrations by learning a set of policies that are capable of generating diverse behaviours from a small set of state-only (unlabelled) demonstrations. We show that our approach is capable of generating multimodal solutions beyond the provided demonstrations. In addition, we are capable of generating multimodal solutions even from single-mode demonstrations. Furthermore, we build a parameterised solution space based on the preference factors extracted from a projection function we proposed. Given this space, we show that we can map all the generated policies onto this space using our projection function. By doing so, we show that our method allows us to perform different types of *post-hoc* policy searches in the built solution space: 1) Given a (sate-only) demonstration, find the closest policy capable of generating this demonstration. 2) Search policies in the solution space that have a high/low likelihood according to the provided demonstrations (*i.e.*, similar to the provided demonstrations). 3) Find solutions that satisfy different constraints.

2 BACKGROUND

2.1 IMITATION LEARNING AS DIVERGENCE MINIMISATION

In this section, we discuss why current Imitation Learning (IL) methods are incapable of dealing with multi-modal demonstration distributions; especially, when only a small set of demonstrations is available. (Zhang et al., 2020; Ke et al., 2020; Ghasemipour et al., 2020) have shown that current the Imitation learning (IL) methods can be derived as a family of *f-divergence* minimisation methods, where the divergence of the state-action distributions of the expert $p_{\pi_{exp}}(s, a)$ and learning agent $p_{\pi_\theta}(s, a)$ is minimised using either Kullback-Lebler (KL) divergences or Jensen-Shanon (JS) divergence. As KL divergence is not symmetric, both forward KL and reverse KL are used. And depending on the choice of the divergence, the optimisation yields different results (Nowozin et al., 2016; Ke et al., 2020; Ghasemipour et al., 2020) (see Fig 2). Additional details in Appx A.2.

Figure 2: Fitting a Gaussian to a multimodal distribution (blue) by minimising the reverse-KL (A, mode-seeking) and the forward-KL (B, mean-seeking)

Behaviour cloning (Pomerleau, 1988), a supervised off-line learning approach, is one of the examples that use forward KL to optimise its policy. In practice, it either follows a mean-seeking behaviour under a stochastic policy and assumes data sampled during training are balanced or exhibits a mode-seeking pattern. As it is a supervised learning method that lacks interaction with the environment, it often requires a large amount of demonstration data in order to accurately estimate the true state-action distribution (Neu & Szepesvári, 2009).

One example of using reverse KL is *Adversarial Inverse Reinforcement Learning* (Fu et al., 2017), which recovers both the reward function and the policy by formulating IL as a min-max optimisation using *Generative Adversarial Networks* (GAN) (Goodfellow et al., 2014). Here, the generator serves as the policy network and a discriminator as the reward function. The optimised objective is the reverse KL divergence, which can be expressed in terms of entropy $\mathcal{H}$ as: $\mathbb{E}_{p_{\pi_\theta}(s,a)} \left[\log \pi_{exp}(s,a) \right] - \mathcal{H}(p_{\pi_\theta}(s,a))$. In practice, it faces additional challenges, such as the ambiguity of the reward function (Ng et al., 2000; Arora & Doshi, 2021) (i.e., many reward functions could generate the same behaviours). Thus, its policy learning counterpart, *Generative Adversarial Imitation Learning* (GAIL) (Ho & Ermon, 2016) is more frequently used. This latter optimises the JS divergence (Goodfellow et al., 2014; Ghasemipour et al., 2020; Ke et al., 2020) with the causal entropy as policy regularisation term.

Optimising the JS-divergence result in the same mode-seeking behaviour as the reverse KL (Theis et al., 2015). It further faces one of the most notorious problems of the GAN-based approach, commonly known as *mode collapse* (Srivastava et al., 2017; Bau et al., 2019), where the generator collapses to produce only a small set of data samples (partial collapse) or even a single sample (complete collapse), which disregards the multi-modal nature of the distribution. Furthermore, the adversarial optimisation scheme in GAN-based methods further imposes other challenges, such as instability in the optimisation. It is often difficult to guarantee that both the generator and the discriminator converge optimally at the same time (Radford et al., 2015). It is common to observe that the loss of the discriminator converges very quickly to zero (Arjovsky & Bottou, 2017; Xu et al., 2018) that impedes the gradient updates of the generator. It often needs a considerably large number of data and fine-tuning or additional regularization in order to stabilise the training process. The optimisation of IL methods is convex if the actions are deterministic and the demonstrations cover the complete state space (Neu & Szepesvári, 2009). In practice, it is always difficult to make sure that the demonstrations span the entire state space; instead, they just cover one of the global optima which ensures the convergence of the solution.

2.2 IMITATION LEARNING FROM OBSERVATION ONLY

To overcome the problem of learning from state-only observations, *Behavioral Cloning from Observations* (BCO) (Torabi et al., 2018) proposes a new framework, where an inverse dynamics model is learnt through interaction with the environment and a policy is learnt from state observations by using the action inferred by the inverse dynamics. However, as with most IL methods, BCO does not handle multimodal demonstrations. Similarly, ILPO (Edwards et al., 2019) learns a forward dynamics model and a latent policy to circumvent the need for the actions; however, it is only applicable to discrete action space. Latent policy learning from demonstrations has also been proposed by (Ren et al., 2020; Fujiishi et al., 2021; Wang et al., 2022). GAIfO (Torabi et al., 2019) extends GAIL to state-only observations by using a discriminator that discriminates the state transitions instead of state-action pairs from the expert. *State-alignment based Imitation Learning* (SAIL) uses state alignment to recover state sequences that are close to the demonstrations using β-VAE for local state alignment and Wasserstein distance for global state alignment. While this approach shares

some similarities with our approach (*i.e.*, state distribution matching), it is not purely a *states-only* method, as it still needs access to state-action pairs to pre-training their model. A similar approach is proposed in (Lee et al., 2019). InfoGAIL (Li et al., 2017) combines InfoGAN (Chen et al., 2016) with GAIL to capture the variations of diverse demonstrations by having interpretable latent factors. However, it is not purely observation-based and suffers in addition from the mode-collapse problem as discussed in the previous section. (Gavenski et al., 2020) shares similarities with us by using the sampling-based method to imitate unknown policies but with state-action demonstrations. The closest work is perhaps by Ghasemipour et al. (2020), where they recover a multi-modal policy from state distributions that preserves 2 solution modes using a modified reverse KL. However, the reason for this multimodality is due to the stochastic policy it uses (*i.e.*, outputs mean and variance of a Gaussian distribution). Unlike our approach, it does not allow the *post-hoc policy search* we propose, therefore, it cannot obtain a specific policy deterministically.

3 PROBLEM SETUP

Consider a finite-horizon Markov Decision Process (MDP) $\langle \mathcal{S}, \mathcal{A}, p, p_0, R, \gamma, T \rangle$, where $\mathcal{S} \subseteq \mathbb{R}^{d_s}$ and $\mathcal{A} \subseteq \mathbb{R}^{d_a}$ are the continuous *state* and *action spaces*, $p(s'|s, a)$ is the state-transition probability, s and s' are the current and the next state, a is the applied action, p_0 the initial state distribution, $\gamma \in [0, 1]$ the *discount factor*, $R : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ the *reward function*, and T the *time horizon*. We assume that this MPD has differentiable dynamics with a continuous states transition function $s_{t+1} = f_c(s_t, a_t)$, such that $d(s_t, s_{t+1}) < \delta$, with d as a distance metric, and δ a small constant.

Let $\mathbb{D} = \{\tau_0, \tau_1, \ldots, \tau_{n-1}\}$ be a set of state-trajectories (demonstrations) such that $\tau_i = (s_0^i, s_1^i, \ldots, s_{T-1}^i), s_t^i \in \mathbb{R}^{d_s}, \tau_i \in \mathbb{R}^{T \times d_s}$. The demonstration set $\mathbb{D}$ results from a set of n human policies $\{\pi_h^i(a|s)|i = 0 : n - 1\}$, where the subscript h indicates that it is a human policy, which is inaccessible for us. We hypothesise that while all human policies maximise the same task reward $R_{task}(s, a)$, each policy is constrained by a preference component. We assume that the preference component is defined as the personal preference over the state distribution, such that different individuals prefer to visit different states while solving the task. Therefore, human policies are the results of solving the following constrained optimisation problem:

$$\pi_h^i := \arg \max_\pi \mathbb{E}[(R_{task}|\pi)], \tag{1}$$

$$\text{subject to } \mathcal{D}_{KL}[p_\pi(s)||g_i(s)] < \epsilon \tag{2}$$

where $g_i(s) = p(s|\pi_h^i)$ is the state distribution preferred by the individual i, and $p_\pi(s)$ the state distribution of the learning agent. As different individuals optimise the task reward function with different preferred states, the demonstration distribution can have multiple solution modes.

Our goal is to learn a large set of policies capable of solving the same task in different ways by satisfying different preference components of the demonstrators, rather than learning a single way of solving the task (i.e., mode-seeking policy or mean-seeking policy). Thus, we propose a setup where the learning agent has access to a simulator to receive the task reward from the environment and to observe the true dynamics of the system. At the same time, it receives the demonstrations $\mathbb{D}$, where it needs to optimise its policies for the different unobserved (as it is not explicitly defined) preference components from these demonstrations. In other words, we propose to solve the objective above by combining the optimisation scheme of RL with IL that uses a divergence minimisation scheme.

4 DYNAMICS-AWARE SKILL GENERATION FROM BEHAVIOURALLY DIVERSE DEMONSTRATIONS

Our method consists of two steps: (1) latent space modelling from the demonstration, and (2) diverse policy generation on the latent space. In addition, our method allows us to perform *post-hoc solution searching* on this space in order to obtain solutions (policies) that satisfy different constraints.

To find out a large set of policies, one for each $g_i(\cdot)$ as per the KL constraint in Eq. 2, we first need to construct a latent space $\mathcal{Z}$, such that any $g_i(\cdot)$ can be mapped onto that space. Now, if we use a projection function that maps two similar $g_i(\cdot)$s closer to each other in the latent space Z, the KL constraint in Eq. 2 can be approximated using a Euclidean constraint in this space $\mathcal{Z}$. More

concretely, for some constant $\delta \in \mathbb{R}^+$, $z_i \in \mathcal{Z}$, and projection function $\text{Enc}(\cdot)$ the problem can be reformulated on the latent space $\mathcal{Z}$ as

$$\pi_i := \arg \max_{\pi} \mathbb{E}[(R_{task}|\pi)],$$
$$\text{subject to} \quad ||\text{Enc}(\tau_{\pi}) - z_i||_2 < \delta \tag{3}$$

Practically, we want to find one policy for each $z_i \in \mathcal{Z}$, optimising the objective in Eq. 3, where z_i are uniformly and densely distributed in the space $\mathcal{Z}$. In other words, we want to optimize policies for each *niche* so that the optimized policies maximise the task reward while producing state trajectories specified by its own niche only. This is a *quality-diversity optimization* problem (Cully & Demiris, 2017): finding high-quality solutions according to a cost/fitness function in a space that specifies the *behaviour* of the solutions. We solve this optimisation problem using a quality-diversity algorithm called MAP-Elites (Mouret & Clune, 2015; Vassiliades et al., 2017), where we determine the *behaviour* of the solutions as the latent preferences extracted from our projection function.

4.1 LATENT SPACE MODELLING FROM DENSITY ESTIMATION

We first model the latent factors that explain the diversity in the behaviours from the demonstrations. As mentioned in Sec. 3, we hypothesise that the diversity is caused by individual preference over the state visitations; *i.e.*, different individuals prefer visiting different regions in the state space. A similar hypothesis has also been made in previous works such as *max-margin planning* (Ratliff et al., 2006), where the reward function is recovered by matching the state-visitation frequency for every single state and the state-action feature vector. While they use single state visitation counts, we propose to estimate the *state region visitation frequencies* as latent preferences, as this gives a summary of the desired sequence of states to be visited. This implicitly captures the desired state transition for each individual under the continuous state transition function, i.e., states close in time will be in the same state region (see Sec 3).

Figure 3: Generation of the latent space from the demonstration. The state observations (A) are modelled by a GMM (B). The latent space (C) is built based on different combinations of mixture components.

Given the state distributions from the demonstrations $p(s)$ as defined in Sec 3, we use a Gaussian Mixture Model (GMM) of k mixture components to model the density as $p(s) = \sum_i^K \phi_i \mathcal{N}(s|\mu_i, \sigma_i)$, where ϕ_i is the mixture weight for each mixture component. This state density $p(s)$ models the state observations of all the demonstrations. Under the assumption of a continuous state transition, each mixture component will cover a state region in the state space. The state distribution of each individual, g_i, belongs to a subset of the entire state distribution. As a mixture component can be seen as a state region, different trajectories would have different state region visitations or assigned mixture components. Given a fitted GMM model, we can estimate the state distribution of each $g_i(s)$ given its observations by a subset of mixture components according to their corresponding posterior probability or *responsibilities* $p(k|s)$. That is, given the sequence of states, we can estimate the responsibilities $p(k|s)$ for these states using the fitted GMM, and use the corresponding mixtures to approximate its state distribution. Given the assigned mixture components $\{k_j\}$, and their assignment frequencies $\frac{f_j}{T}$(i.e., number of assignment for each component w.r.t the total number of states T) for $g_i(s)$, we can approximately define the density of $g_i(s)$ using a new GMM model composed of these mixture components as $g_i(s) \approx \sum \frac{f_j}{T} \mathcal{N}(s|\mu_{k_j}, \sigma_{k_j})$, where the assigned mixture components correspond to state region visitations, and the new mixture weight is readjusted based on their assignment frequencies $\frac{f_i}{T}$.

Now, we can define our projection function, or encoder function $\text{Enc} : \mathbb{R}^{T \times d_s} \to \mathbb{R}^{d_z}, d_z \ll (T \times d_s)$, based on the assignment of the mixture components. Given a set of states from a policy,

the GMM is used as an unsupervised clustering method to classify these states into different mixture components. There are different ways to represent this information. For instance, we can have an encoding of size K and give the frequency values of each component $[f_1, f_2, \ldots f_k]$. However, to limit the size of the encoding, we choose to take the indices of the m most frequently assigned components without explicit referring to the actual frequencies (detailed algorithm in Appx. Algo 1). The precision of the mapping depends on our choice of m as we will have information loss with a small value of m (further discussion in Appx A.5 and A.4).

Implicitly, we are defining the feature vector of a trajectory as the mixture components that are responsible for its states. The visitation frequency is explicitly taken into account by taking the top d_z most assigned mixture components in descending order. In addition, the use of GMM allows us to evaluate the likelihood of a given trajectory according to the density distribution modelled from demonstrations. For instance, given the example of Fig 4, we can evaluate whether these trajectories belong to in-distribution data or out-of-distribution based on their likelihood (of the state sequence).

Figure 4: Mixture components/clusters assignment (represented by **coloured** confidence ellipsoids of GMM) for the state distributions of 2 trajectories $\tau_1 \in \mathbb{R}^{80}$ and $\tau_2 \in \mathbb{R}^{50}$. **A.** Out-of-distribution trajectory τ_i with low average likelihood according to a fitted GMM. **B.** In-distribution trajectory τ_2 with high average likelihood.

Solution matching   We can measure the similarity of 2 trajectories by measuring their associated mixture components. As we have the analytical form of each component (*e.g.*, Gaussian with its mean and variance), we can directly measure the distance between their distributions by using measurement of our choice, such as *Bhattacharyya distance* or *KL* divergence.

4.2   MAP-ELITES (EA) AS DYNAMICS-AWARE CONDITIONAL GENERATIVE MODEL

Given $\mathcal{Z}$ as the latent space defined by the projection function, we aim to generate a solution archive $\mathcal{P}_z$ parameterised by the latent encoding z, where each entry in this archive has a unique encoding z. The goal is to generate policies and map them into this space according to encoding values for their respective $g(\cdot)$. While the latent space contains all the possible state distributions defined by the mixture components of the GMM, the solution space is constrained by the system's dynamics, as the possible solutions are subject to the system constraints that cannot generate certain state distributions. Thus, $\mathcal{P}_z \subset \mathcal{Z}$. As the solution archive is the result of filling the latent space with policies, we may use latent space interchangeably to refer to the empty solution space.

EA can be seen as an implicit state density model over states with high fitness/reward (Murphy, 2023). In our case, as EA optimises each instance of encoding, which is associated (deterministically) with a given mixture model, the generation of this space is equivalent to an implicit density modelling conditioned on the latent encodings. Thus, we refer to our method as a conditional generative model that generates policies conditioned on different encodings. The workflow is shown in Fig 5, and detailed algorithm in Appx. 2.

MAP-Elites starts with sampling N random policy parameters from a uniform distribution: $\theta_{i=0:N-1} \sim \mathcal{U}_{[a,b]}$. Then it evaluates the policies in simulation using the reward function $R_{task}(\cdot, \cdot)$, and at the same time generates the state trajectories $\tau_{i=0:N-1}$, and their corresponding encodings $z_{i=0:N-1}$. Then the policies are inserted into the closest cells in the solution archive $\mathcal{P}$. If two policies compete for the same cell, the one with a higher reward occupies the cell. Once this initialization is done, MAP-Elites randomly selects a policy from the archive, adds a small random noise (mutation) to the parameters, and evaluates the policy on the simulator for the reward, state trajectory, and the corresponding encoding. This new policy is inserted into the archive if either the corresponding cell is empty or the new policy has a higher reward; the policy is discarded otherwise.

Figure 5: Workflow of policy generation and allocation in the latent space. To initialise, the parameters of the policy (here we use a neural network) are sampled uniformly, and then the policies are executed on the simulator to get the corresponding trajectories (set of states), in order to allocate the policies into the latent space according to their encoding. Then, in a loop, policies are selected from the archive, small variations are added, and new encodings are obtained to insert them into the archive based on their reward.

The selection, variation, and insertion continue until the maximum assigned policy evaluation count is reached.

As the highest rewarding policies occupy the nearest cells in the archive, those policies produce maximally rewarding behaviour staying close to the state distribution specified in the cell. In other words, the policies in the archive essentially optimise the objective in Eq. 3 for different z_i.

Post-hoc policy search Having a set of solutions parameterised by latent encodings allows us to find solutions in a post-hoc manner that satisfy different constraints. For instance, a solution archive $\mathcal{G}$ built for a 2D navigation environment with one obstacle contains solutions for an equivalent environment $\mathcal{J}$ with two obstacles, as the latter space is more restricted, where $\mathcal{J} \subset \mathcal{G}$ (see example in Sec. 5). In addition, given a new demonstration, we can find the closest policy in our archive by finding a policy with the closest distribution distance (see Sec. 4.1) according to the encodings.

5 EXPERIMENTS

We present 3 experiments with continuous state and action spaces to show that our method is capable of generating a solution archive that optimises implicitly the density distribution from demonstrations. We propose 2 (motion) planning examples where the task is to generate a non-colliding path from two points in an end-to-end manner. The first is a 2D toy path planning environment and the second is a robotic arm motion planning environment using the Franka Emika robot with Pybullet (Coumans & Bai, 2016–2021) as the physic simulator. In both cases, we use only the XY position coordinates as the state observation. For Franka, we fixed the Z axis, as the demonstrations do not contain Z coordinates. Finally, we show a driving experiment modified on (Leurent, 2018) as a close-loop control example, using neural networks for a step-wise decision-making policy. The experiments are run 3 times. The average performance and further discussion (time, number of valid solutions vs encoding choices can be found in Appx A.4. The latent encoding is a vector of 6 dimensions defined by the top 6 most frequent mixture components responsible for the state sequence. The GMM models are trained using the same random seeds to ensure reproducibility. A discussion of model selection and reproducibility is included in Appx. A.5 and A.3.

2D path planning Here, the space of the policy parameters $\mathcal{X}$ is a subset of the state space $\mathcal{X} \subseteq \mathcal{S}$, and the action space is the state space. We can directly show that the distribution of the parameters is optimised toward the demonstrations' distribution. We use 28 non-colliding trajectories with fixed lengths that are generated artificially using *Bézier curves* as shown in Fig 6A. We use *B-spline* as the policy function, which takes 5 control points in total to generate a flexible curve. We use a GMM of 20 components for the multimodal distribution and 10 for the single-mode distributions. Under the exact same setup, we show that the parameters are optimised towards state distributions modelled by their respective GMM. As shown in Fig 6, the resulting parameters from the single-mode setup are scattered mainly in the region within single mode state distribution. While for the multi-modal setup, the parameters are scattered in both regions of the state space. This comparison is even more

noticeable after filtering out the solutions with a higher likelihood (according to their respective GMM models). We show that even though the demonstrations only cover one solution mode, our method is still capable of discovering multimodal solutions, where the unseen solutions from the demonstrations will have lower likelihood values.

Figure 6: Solution archives with the exact setup but different GMM models. **A.** Multimodal demonstration. **B.** Trajectories with GMM from **multimodal demonstration** with colour bar as their corresponding average likelihood. **C.** Parameters (control points) for policies from B shown with their colour and size re-adjusted according to their likelihood values. **D.** Trajectories from solution space build for the **single-mode demonstrations** (*i.e.*, lower regions) with their average likelihood. **E.** Parameters for the policies of Fig. D.

As VAE is commonly used as a feature encoding method as well as a (conditional) generative model, we show its capability of feature encoding and generation ability in this setup. We use the same encoding size, and trained the model for 30000 iterations (details in Sec A.3.1). As shown in Fig 7, for a small dataset, the generator suffers from partial collapse that only generates samples from certain modes and fails to produce diverse samples. The same observation occurs for the encoder, it fails to produce unique encoding values as shown in Fig. 7(B, D). While training the same model using the data generated from our solution, both its capability of reconstruction and encoding improves considerably. However, unlike our projection function, it does not provide an interpretable encoding value. And it cannot take the advantage of the simulator that is available to interact with. Another alternative method is GAN, but it does not work when a small amount of data is provided, and it suffers from the mode collapse even though a large amount of data is available (see Sec 2.1). We show this latter using trajectories from our archive in Appx A.2).

Franka arm manipulation   We use the same setup here as in the previous case, except the mixture component to model the state density increases to 25 as more data is available. We collected 140 demonstrations in real life using a motion tracker to track the movement of a pointer to draw the trajectories without considering the real dynamics of the robot. The length of demos spans between 240 and 726 time-steps. In addition, we choose different end locations in the simulator for the planning. Fig 8 shows that we can produce a diverge range of solutions with changing dynamics.

Highway driving   Here, we demonstrate that our method is capable of optimising the solution space using indirect parameterisation, where $\mathcal{X} \not\subseteq \mathcal{S}$ and $\mathcal{A} \not\subseteq \mathcal{S}$, with high-dimensional parameters (weight matrix of NN). We collected 40 demonstrations of 151 time-steps using a manual controller from the simulator. Here the observations contain both the position coordinates and the rotation angles of the vehicle, $s \in \mathbb{R}^4$, the action is the steering applied to the vehicle in order to overtake an

Figure 7: **A.** 1000 samples from VAE trained on the original demonstrations. **B.** Histogram of the predicted encodings for the corresponding demonstrations (*i.e.*, mean and variance for the isotropic Gaussian). **C.** 1000 samples from VAE trained on trajectories generated from our solution. **D** Histogram of the predicted encodings for the corresponding demonstrations. **E.** Histogram of the unique encodings from both VAEs.

Figure 8: **A.** Simulation environment. **B.** Demonstrations of various lengths collected using a motion tracker. **C.** Trajectories from the solution archive with a different end target location. **D.** Trajectories with their corresponding likelihood visualised with a colour map.

existing obstacle on the road without going off the road as shown in Fig 9A. We show the resulting behaviours when multimodal and single-mode demonstrations are used in Fig 9.

Figure 9: **A.** Demonstration. **B.** Trajectories from the multimodal solution archive with the likelihood values. **C/D.** Trajectories from the single-mode solution archives with their respective likelihood values.

Post-hoc solution search In this case, we show that we can still find valid solutions when the constraints in environment change. Here, we add another obstacle to the 2D path planning environment. By simulating the policies in this modified environment, we obtained 1738 valid trajectories as shown in Fig 10. It is also possible to obtain a set of trajectories close to a given demonstration by matching the latent encodings (see Sec. 4.1) in the solution archive (see Fig 10).

Figure 10: Post-hoc policy searching in the solution archive. **Left**: 1738 valid solutions for a new obstacle in the archive at Fig 6a. **Middle/Right**: 3 closest trajectories to a given demo with its top 6 responsible mixture components (confidence ellipsoid).

6 CONCLUSIONS

In this paper, we propose a novel framework that allows us to build a solution space where we generate a diverse range of behaviours from a small set of state-only observations. We show empirically that our method optimises all the policies in the space towards different state density constraints while optimising the task reward. With our proposed projection function that encodes state transitions into meaningful statistical encoding, we can perform a post-hoc policy search in the projected space searching for different policies. Our experimental results show that we are capable of generating multimodal solutions not only from the multimodal demonstrations as input but also from single-mode demonstrations. Where in this latter case, we can obtain only demonstration-alike trajectories by considering their respective likelihood values.

REFERENCES

Martin Arjovsky and Léon Bottou. Towards principled methods for training generative adversarial networks. *arXiv preprint arXiv:1701.04862*, 2017.

Saurabh Arora and Prashant Doshi. A survey of inverse reinforcement learning: Challenges, methods and progress. *Artificial Intelligence*, 297:103500, 2021.

Monica Babes, Vukosi Marivate, Kaushik Subramanian, and Michael L Littman. Apprenticeship learning about multiple intentions. In *Proceedings of the 28th international conference on machine learning (ICML-11)*, pp. 897–904. Citeseer, 2011.

David Bau, Jun-Yan Zhu, Jonas Wulff, William Peebles, Hendrik Strobelt, Bolei Zhou, and Antonio Torralba. Seeing what a gan cannot generate. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 4502–4511, 2019.

Konstantinos Chatzilygeroudis, Vassilis Vassiliades, and Jean-Baptiste Mouret. Reset-free trial-and-error learning for robot damage recovery. *Robotics and Autonomous Systems*, 100:236–250, 2018.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. *Advances in neural information processing systems*, 29, 2016.

Erwin Coumans and Yunfei Bai. Pybullet, a python module for physics simulation for games, robotics and machine learning. `http://pybullet.org`, 2016–2021.

Antoine Cully and Yiannis Demiris. Quality and diversity optimization: A unifying modular framework. *IEEE Transactions on Evolutionary Computation*, 22(2):245–259, 2017.

Antoine Cully, Jeff Clune, Danesh Tarapore, and Jean-Baptiste Mouret. Robots that can adapt like animals. *Nature*, 521(7553):503–507, 2015.

Ashley Edwards, Himanshu Sahni, Yannick Schroecker, and Charles Isbell. Imitating latent policies from observation. In *International conference on machine learning*, pp. 1755–1763. PMLR, 2019.

Justin Fu, Katie Luo, and Sergey Levine. Learning robust rewards with adversarial inverse reinforcement learning. *arXiv preprint arXiv:1710.11248*, 2017.

Hidehito Fujiishi, Taisuke Kobayashi, and Kenji Sugimoto. Safe and efficient imitation learning by clarification of experienced latent space. *Advanced Robotics*, 35(16):1012–1027, 2021.

Johannes Fürnkranz and Eyke Hüllermeier. Preference learning and ranking by pairwise comparison. In *Preference learning*, pp. 65–82. Springer, 2010.

Nathan Gavenski, Juarez Monteiro, Roger Granada, Felipe Meneguzzi, and Rodrigo C Barros. Imitating unknown policies via exploration. *arXiv preprint arXiv:2008.05660*, 2020.

Seyed Kamyar Seyed Ghasemipour, Richard Zemel, and Shixiang Gu. A divergence minimization perspective on imitation learning methods. In *Conference on Robot Learning*, pp. 1259–1277. PMLR, 2020.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

Jonathan Ho and Stefano Ermon. Generative adversarial imitation learning. *Advances in neural information processing systems*, 29, 2016.

Rituraj Kaushik, Pierre Desreumaux, and Jean-Baptiste Mouret. Adaptive prior selection for repertoire-based online adaptation in robotics. *Frontiers in Robotics and AI*, pp. 151, 2020.

Rituraj Kaushik, Karol Arndt, and Ville Kyrki. Safeapt: Safe simulation-to-real robot learning using diverse policies learned in simulation. *IEEE Robotics and Automation Letters*, 2022.

Liyiming Ke, Sanjiban Choudhury, Matt Barnes, Wen Sun, Gilwoo Lee, and Siddhartha Srinivasa. Imitation learning as f-divergence minimization. In *International Workshop on the Algorithmic Foundations of Robotics*, pp. 313–329. Springer, 2020.

Lisa Lee, Benjamin Eysenbach, Emilio Parisotto, Eric Xing, Sergey Levine, and Ruslan Salakhutdinov. Efficient exploration via state marginal matching. *arXiv preprint arXiv:1906.05274*, 2019.

Edouard Leurent. An environment for autonomous driving decision-making. `https://github.com/eleurent/highway-env`, 2018.

Yunzhu Li, Jiaming Song, and Stefano Ermon. Infogail: Interpretable imitation learning from visual demonstrations. *Advances in Neural Information Processing Systems*, 30, 2017.

Jean-Baptiste Mouret and Jeff Clune. Illuminating search spaces by mapping elites. *arXiv preprint arXiv:1504.04909*, 2015.

Kevin P. Murphy. *Probabilistic Machine Learning: Advanced Topics*. MIT Press, 2023. URL `probml.ai`.

Gergely Neu and Csaba Szepesvári. Training parsers by inverse reinforcement learning. *Machine learning*, 77(2):303–337, 2009.

Andrew Y Ng, Stuart Russell, et al. Algorithms for inverse reinforcement learning. In *Icml*, volume 1, pp. 2, 2000.

Sebastian Nowozin, Botond Cseke, and Ryota Tomioka. f-gan: Training generative neural samplers using variational divergence minimization. *Advances in neural information processing systems*, 29, 2016.

Dean A Pomerleau. Alvinn: An autonomous land vehicle in a neural network. *Advances in neural information processing systems*, 1, 1988.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. *arXiv preprint arXiv:1511.06434*, 2015.

Nathan D Ratliff, J Andrew Bagnell, and Martin A Zinkevich. Maximum margin planning. In *Proceedings of the 23rd international conference on Machine learning*, pp. 729–736, 2006.

Allen Z Ren, Sushant Veer, and Anirudha Majumdar. Generalization guarantees for imitation learning. *arXiv preprint arXiv:2008.01913*, 2020.

Stefan Schaal. Learning from demonstration. *Advances in neural information processing systems*, 9, 1996.

Akash Srivastava, Lazar Valkov, Chris Russell, Michael U Gutmann, and Charles Sutton. Veegan: Reducing mode collapse in gans using implicit variational learning. *Advances in neural information processing systems*, 30, 2017.

Lucas Theis, Aäron van den Oord, and Matthias Bethge. A note on the evaluation of generative models. *arXiv preprint arXiv:1511.01844*, 2015.

Faraz Torabi, Garrett Warnell, and Peter Stone. Behavioral cloning from observation. *arXiv preprint arXiv:1805.01954*, 2018.

Faraz Torabi, Garrett Warnell, and Peter Stone. Adversarial imitation learning from state-only demonstrations. In *Proceedings of the 18th International Conference on Autonomous Agents and MultiAgent Systems*, pp. 2229–2231, 2019.

Vassilis Vassiliades, Konstantinos Chatzilygeroudis, and Jean-Baptiste Mouret. Using centroidal voronoi tessellations to scale up the multidimensional archive of phenotypic elites algorithm. *IEEE Transactions on Evolutionary Computation*, 22(4):623–630, 2017.

Tianyu Wang, Nikhil Karnwal, and Nikolay Atanasov. Latent policies for adversarial imitation learning. *arXiv preprint arXiv:2206.11299*, 2022.

Tao Xu, Pengchuan Zhang, Qiuyuan Huang, Han Zhang, Zhe Gan, Xiaolei Huang, and Xiaodong He. Attngan: Fine-grained text to image generation with attentional generative adversarial networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1316–1324, 2018.

Xin Zhang, Yanhua Li, Ziming Zhang, and Zhi-Li Zhang. f-gail: Learning f-divergence for generative adversarial imitation learning. *Advances in neural information processing systems*, 33: 12805–12815, 2020.

A APPENDIX

A.1 ALGORITHMS

Algorithm 1 State region visitation frequency

1: **function** ENCODE(gmm_model, state_sequence, size_descriptor)
2:     list_components=gmm_model.predict(state_sequences) # Predict the list of mixture components responsible for each state
3:     unique_component, n_counts = **unique**(list_components)
4:     comp_indices = **top_k_components**(unique_component, n_counts, size_descriptor-1)
5:     **return** comp_indice
6: **end function**

Algorithm 2 Solution archive generation

1: **function** ARCHIVE_GENERATE(gmm_model, size_descriptor)
2:     Initialise an instance of policy π, solution archive $\mathcal{P}$, reward archive $\mathcal{R}$, number of iteration N, number of initial random samples M
3:     **while** $i \leq M$ **do**
4:         θ = uniform_sampling(0,1) # sample the parameter vectors from uniform distribution.
5:         π_θ = policy.set_parameter(π, θ)
6:         τ, r_{task} = simulate(π_θ)
7:         z = encode(gmm_model, τ, size_descriptor)
8:         $\mathcal{P}(z) \leftarrow \theta$
9:         $\mathcal{R}(z) \leftarrow r_{task}$
10:     **end while**
11:     **while** $i \leq N$ **do**
12:         θ = ramdom_solution_select($\mathcal{P}$)
13:         θ' = mutate(θ) # Gaussian noise injection to the parameters.
14:         τ, r_{task} = simulate($\pi_{\theta'}$)
15:         z = encode(gmm_model, τ, size_descriptor)
16:         **if** $\mathcal{P}(z) = \emptyset$ or $\mathcal{R}(z) < r_{task}$ **then**
17:             $\mathcal{P}(z) \leftarrow \theta'$
18:             $\mathcal{R}(z) \leftarrow r_{task}$
19:         **end if**
20:     **end while**
21:     **return** $\mathcal{P}, \mathcal{R}$
22: **end function**

A.2 KL DIVERGENCE

As KL divergence is not symmetric, the reverse KL and forward KL exhibit very different behaviours. These are also known as *Moment projection* and *Information projection* respectively.

M-projection minimises the following forward KL:

$$\pi_\theta^* = \arg\min_\theta D_{KL}\left(p_{\pi_{exp}}(s,a) \,||\, p_{\pi_\theta}(s,a)\right),$$
$$D_{KL} = \int p_{\pi_{exp}}(s,a) \log\left(\frac{p_{\pi_{exp}}(s,a)}{p_{\pi_\theta}(s,a)}\right) d(s,a) = \mathbb{E}_{p_{\pi_{exp}}(s,a)}\left[\log\left(\frac{p_{\pi_{exp}}(s,a)}{p_{\pi_\theta}(s,a)}\right)\right]. \tag{4}$$

While the I-projection minimises the following reverse KL:

$$\pi_\theta^* = \arg\min_\theta D_{RKL}\left(p_{\pi_{exp}}(s,a) \,||\, p_{\pi_\theta}(s,a)\right),$$

$$D_{RKL} = \int p_{\pi_\theta}(s,a) \log\left(\frac{p_{\pi_{exp}}(s,a)}{p_{\pi_\theta}(s,a)}\right) d(s,a) = \mathbb{E}_{p_{\pi_\theta}(s,a)}\left[\log\left(\frac{p_{\pi_{exp}}(s,a)}{p_{\pi_\theta}(s,a)}\right)\right]. \tag{5}$$

For M-projection, the difference between $p_{\pi_{exp}}(s,a)$ and $p_{\pi_\theta}(s,a)$ is weighted by $p_{\pi_{exp}}(s,a)$. Which means that when $p_{\pi_{exp}}(s,a) = 0$, the discrepancy of $p_{\pi_\theta}(s,a) > 0$ from $p_{\pi_{exp}}(s,a)$ will be ignored. Mathematically, this means that $p_{\pi_{exp}}(s,a)$ will typically over-estimate the support of $p_{\pi_\theta}(s,a)$, due to $p_{\pi_{exp}}(s,a) > 0$ whenever $p_{\pi_\theta} > 0$ to make sure KL divergence stays finite. As result, the projecting exhibits a mean-seeking, also known as moment-matching, behaviour that averages over several modes given a multimodal distribution. While it avoids the low probability assignment of the region with data (*e.g.*, the other mode of the distribution), it inevitably assigns probability mass to non-data region (Theis et al., 2015) as shown in Fig 2.

For I-projection, as difference between $p_{\pi_{exp}}(s,a)$ and $p_{\pi_\theta}(s,a)$ is weighted by $p_{\pi_\theta}(s,a)$. $p_{\pi_h}(s,a)$ will typically under-estimate the support of p_{π_θ} and concentrate on one of its modes that results in a mode-seeking behaviour. This is due to $p_{\pi_{exp}}(s,a) = 0$ whenever $p_{\pi_\theta}(s,a) = 0$ to make sure KL divergence stays finite. Using this projection is not straightforward as we might only have access to samples from the distribution rather than the data density itself (Murphy, 2023), where M-projection can be done easily by maximising the average log-likelihood with respect to the given training dataset as an equivalent way of minimising the KL.

Given the multi-mode and single-mode demonstrations of the 2D path planning environment, we proposed in Sec. 5. We show the results of Gaussian Mixture Regression (GMR) model, build on the same GMMs we used for our method (see A.4). While it performs well in the single-mode demonstrations, the result from the multimodal distribution exhibits a mean-seeking behaviour as shown in Fig 11.

Figure 11: **Left**: Prediction with 95% confidence interval from a GMR trained on multimodal demonstrations. **Middle/Left**: GMR predictions on single-mode demonstrations.

We show GAN's performance in generating trajectories for the 2D path planning environment. As GAN cannot deal with a small dataset, we trained it using the trajectories generated by our archive, which contains 3881 trajectories. The results are shown in Fig 12. The discriminator takes the entire trajectory as the input and has 3 hidden layers with 128, 32, and 8 neurons respectively. The generator takes an input of a 7-dimensional vector and uses 3 hidden layers with 128, 64, and 32 neurons respectively to generate the trajectory of the same size. The model is trained for 23000 iterations. The results are consistent with mode-seeking behaviour where it converges to one of the solution modes.

Figure 12: **A**: Samples from GAN after 3000 iterations. **B.** Samples from GAN after 15000 iterations. **C.** Samples from GAN after finished training. **D.** Training loss of the discriminator and generator during training.

Experiments	iterations	Real time	CPU time
Planning (multimodal)	10^5	3m49s $\pm$ 1m6s	13m1s $\pm$ 0m28s
Planning (upper)	10^5	2m33s $\pm$ 0m12s	11m51s $\pm$ 1m18s
Planning (lower)	10^5	2m27s $\pm$ 0m44s	12m3s $\pm$ 0m21s
Franka	10^5	6h49m $\pm$ 11m57s	6h49m $\pm$ 11m57s
Highway (multimodal)	5×10^5.	2h46m $\pm$ 4m19s	13h29m $\pm$ 36m14s
Highway (upper)	5×10^5.	1h54m $\pm$ 0m56s	12h35m $\pm$ 4m14s
Highway (lower)	5×10^5.	1h26m $\pm$ 11m57s	12h36m $\pm$ 42m9s

Table 1: Training time

A.3 EXPERIMENT SETUPS AND REPRODUCIBILITY

We train all the GMM models using *sklearn* library with a fixed random state to ensure reproducibility. The experiments were run 3 times per setup (*e.g.*, multimode and single-mode demonstrations), with 2 different types of encodings. We show the average result for single-mode demonstrations and multimodal demonstrations. As most of the experiments allow us to run parallel threads. We record both the average true elapsed time and the average CPU time, with their standard deviation. The results are shown in Table 1. For 2D path planning, we use Intel Core i7-6850K CPU @3.60GHz with 6 cores and trained our model using 12 parallel threads. For Franka, we use a single thread process with 1 CPU core of Xeon Gold 6148 @2.40GHz, and 16GB of RAM without multi-threading due to the high memory demand from the physical simulator. For the highway environment, we use 8 cores of Intel Xeon Gold 6248 @2.50GHz with 12 parallel threads and 8GB of RAM.

In the highway environment, we use neural networks with 2 hidden layers of 8 and 16 neurons respectively as policy. The total number of parameters is 201 elements. The parameters of the networks are purely optimised using random sampling and perturbation from EA without any backpropagation. As we use the exact setup from 2D path planning in the Franka environment to show the applicability of our methods in "real" applications besides the 2D path planning experiment, we only test the result in the multi-modal setup. To ensure maximum reproducibility, the solution archive is initialised with 10^4 solutions with uniformly sampled parameters from a given parameter space to minimise the advantage of a good initialisation. The parameter space for 2D path planning is defined within the range of $[-5, 5]$, while for Franka it is defined within $[0, 1]$ and for highway within $[-1, 1]$.

As we tested 2 different types of encoding, we report the performance results in the section where we discuss the impact of the size of the encoding vs the size of the solution archive in A.5.

A.3.1 SETUP FOR VAE

We use a VAE with 5 hidden layers with 256,128,64, 64,32 neurons correspondingly. Unlike our projection function, the VAE cannot handle data of different sizes, instead, it receives the full trajectory with a fixed length.

A.4 MODEL SECTION OF GMM

The model selection, *i.e.*, the number of GMM components used to model the state density distribution from the demonstration, is determined by Bayesian Information-theoretic criteria (BIC). We choose the model with lower BIC as the common practice. The GMM used for the 2D path planning environment is shown in Fig 13 using confidence ellipsoid. The GMM used for the Franka environment is shown in Fig 14. We omit the visualisation for the highway environment, as we use 4D Gaussian which cannot be visualised with confidence ellipsoid.

Figure 13: GMM models used for 2D path planning environment. **Left**: GMM confidence ellipsoid for the multimodal demonstrations. **Middle**: GMM confidence ellipsoid for the single-mode demonstrations (upper region). **Right**: GMM confidence ellipsoid for the single demonstrations (lower region).

Figure 14: GMM model for the multimodal demonstrations recorded using motion tracker.

A.5 SIZE OF THE ENCODING VS SIZE OF THE SOLUTION ARCHIVE

A.5.1 COMPARISON OF DIFFERENT ENCODINGS

We compare 2 different type of encoding: 1) Encoding with the top 6 most frequently assigned mixture component as discussed in Sec 4.1, shown in Table 2. 2) Same encoding but with an additional likelihood value added. This latter is proposed to avoid the case of having two different trajectories with the same encoding but with different likelihood values (i.e., out-of-distribution trajectories that happened to be mapped to the same encoding), shown in Table 3. In the case of the point environment, the inclusion of likelihood does not increase the size of the final solution archive. We hypothesise that this is caused by the segmentation of the solution space, as the average likelihood is low in general for all the trajectories (see the likelihood values for the trajectories in Fig 6), it worsens the uniform segmentation of the space. In reality, while different trajectories can have the assigned mixture components, their respective frequencies may rarely coincide. For instance, in Fig 4, two trajectories can have the same assigned component with low and high average likelihood respectively, but their resulting encodings are different due to the different frequency values. Thus these trajetories will not compete for the same *niche* in the solution space. While in the case of highway environment, the inclusion of the likelihood does increase the size of the descriptor as the average likelihood values span within [0, 1] (see the colour map for the trajectories in Fig 9).

Experiments	Demos's size	Encoding/GMM*	Total solutions	Valid
Planning (multimodal)	28×50	6/20	7703 ± 20	6584 ± 38
Planning (upper)	14×50	6/10	2329 ± 47	1999 ± 27
Planning (lower)	14×50	6/10	3920 ± 29	3314 ± 34
Highway (multimodal)	40×151	6/20	3900 ± 59	1009 ± 42
Highway (upper)	20×151	6/10	1657 ± 33	464 ± 16
Highway (lower)	20×151	6/10	1187 ± 14	261 ± 9

Table 2: Number of demonstrations vs archive solutions with encoding without likelihood. *Number components for the encoding / total number of mixture components.

Experiments	Demos's size	Encoding/GMM^{+*}	Total solutions	Valid
Planning (multimodal)	28×50	7/20	3810 ± 16	3554 ± 6
Planning (upper)	14×50	7/10	2685 ± 12	2415 ± 15
Planning (lower)	14×50	7/10	3761 ± 27	3270 ± 7
Franka	$140 \times$ (various)	7/25	8581 ± 24	6948 ± 48
Highway (multimodal)	40×151	7/20	4781 ± 23	1116 ± 25
Highway (upper)	20×151	7/10	1919 ± 64	515 ± 25
Highway (lower)	20×151	7/10	1237 ± 40	260 ± 11

Table 3: Number of demonstrations vs archive solutions with encoding that has likelihood as an additional dimension. $^+$Here we have 6 mixture components plus one value for the average likelihood.

A.5.2 COMPARISON OF DIFFERENT CHOICES FOR GMM

Encoding space dimensionality. Given a GMM with d_{gmm} components and an encoding size of d_z. The number of possible encodings is defined by different permutation of d_{gmm}, its size has a theoretical upper bound of $\frac{d_{gmm}!}{(d_{gmm}-d_z)!}$. In practice, its real upper bound depends on the system's dynamics, *e.g.*, it may be impossible to have a state distribution with only 2 different state regions that are far away from each other as the state transition is continuous.

As discussed, the size of the latent (encoding) space depends on the number of mixture components that represent different state region visitation and the size of the descriptor to choose. Here we show the result of using 2 different GMMs with 10 and 5 mixture components respectively that have higher BIC scores compared to the GMM with 20 components (see model selection in A.4).

For the GMM with 10 components, we keep the size of descriptor unchanged, *i.e.*, 7, while for the GMM of 5 components, we reduced it to 4 as the total number of components is reduced. The number of total solutions was reduced to 1163 trajectories with 854 valid trajectories on average for the former case. While for the latter case, the sizes are 120 total trajectories and 105 valid trajectories respectively. This is due to the fact that a lower number of mixture components will reduce the size of the latent space. The result is shown in Fig 15.

Figure 15: **Left**: Mixture component with 10 components, and the resulting solution archive with valid trajectories shown with colour map that corresponds to their respective likelihood values. **Right**: Mixture component with 5 components and the associated solution archive with valid trajectories with their respective likelihoods.