Learning NP-Hard Joint-Assignment planning using GNN: Inference on a Random Graph and Provable Auction-Fitted Q-iteration

Abstract

The present paper explores the possibility of near-optimally solving multi-robot, multi-task NP-hard scheduling problems with time-dependent rewards using a learning-based algorithm. In particular, we consider a class of robot/machine scheduling problems called the multi-robot reward collection problem (MRRC). Such MRRC problems well model ride-sharing, pickup-and-delivery, and a variety of related problems. In rep resenting the MRRC problem as a sequential decision-making problem, we observe that each state can be represented as an extension of probabilistic graphical models (PGMs), which we refer to as random PGMs. We then develop a mean-field inference method for random PGMs. We then propose (1) an order-transferable Q-function estimator and (2) an order-transferability-enabled auction to select a joint assignment in polynomial-time. These result in a reinforcement learning framework with at least $1 - 1/e$ optimality. Experimental results on solving MRRC problems highlight the near-optimality and transferability of the proposed methods. We also consider identical parallel machine scheduling problems (IPMS) and minimax multiple traveling salesman problems.

1 Introduction

Motivation Consider a set of identical robots seeking to serve a set of spatially distributed tasks. Each task is given an initial age (which then increases linearly in time). Greater rewards are given to younger tasks when service is complete according to a predetermined reward rule. Such problems prevail in operations research, e.g., dispatching drivers to transport customers or scheduling machines in a factory. Solving such highly structured NP-hard problems with the constraint of 'no possibility of two robots assigned to one task at once' using mathematical optimization schemes is infeasible or ineffective due to the expensive computational cost, especially when the problem size is large. Applying decentralized approach using multi-agent modeling frameworkLong et al. (2020); Rashid et al. (2018); Sunehag et al. (2017) is a possible way to solve a large scale problems. However, due to the impossibility of inducing consensus among agents in achieving the global objective without effective communication Fischer et al. (1985), such decentralized approaches are rarely used in industries (e.g., factories). Thus, this study focuses on centralized methods for solving MRRC.

Research Questions. Many of such NP-hard scheduling problems have time-dependent rewards. To the best of our knowledge, these problems have not yet been addressed by non-decentralized learning-based methods. Even if one can, it must also be able to simultaneously address a fundamental challenge: the number of possible robot-task pairs to be considered increases exponentially. For instance, scheduling 8 robots and 50 tasks involves 10^{13} possible joint assignments at each time-step. The main research question that the current study seeks to resolve is "how to design a computationally

effective (i.e., scalability in terms of learning and decision making) a learning based centralized decision making scheme for solving a large-scale NP-hard scheduling problems?"

Proposed method and contributions. The present paper explores the possibility of near-optimally solving multi-robot, multi-task NP-hard scheduling problems with time-dependent rewards using a learning-based algorithm. The study formulates multi-robot, multi-task NP-hard scheduling problems in a sequential decision-making framework and derives a joint scheduling policy with a theoretical performance bound under reasonable assumptions. The novelties of the current study are as follows:

- The study first observes that a state-joint assignment pair can be represented as a *random* PGM. After developing a theory of random PGM-based mean-field inference, we derive *random structure2vec*, a random PGM-based extension of structure2vec Dai et al. (2016).

- We estimate the Q-function $Q(s_k, a_k)$ using layers of *random structure2vec*, where (s_k, a_k) is the state-joint action pair. Using an interpretation of a layer of structure2vec as a Weisfeiler-Lehman kernel (as in Dai et al. (2016)), we design the estimator to possess a property we call order-transferability. This property enables transferability in problem size.

- We propose a joint assignment rule called order-transferability-enabled auction policy (OTAP) to address exponential growth in joint assignment space. We propose auction-fitted Q-iteration (AFQI) by substitution of the argmax operation of fitted Q-iteration with OTAP to train the Q-function in a scalable manner. We prove that AFQI results in a policy with polynomial-time computation that achieves at least $1 - 1/e$ performance compared with the optimal policy.

Results and Impacts. Using simulation experiments, we show that the proposed policy typically achieves 97% optimality for the multi-robot reward collection (MRRC) problem in a deterministic environment with linearly time-varying rewards. This performance is well extended to experiments with stochastic traveling times. To the best of our knowledge, this result is the first to learn a near-optimal NP-hard multi-robot/machine scheduling policy with time-dependent rewards.

2   Related studies.

Recently, Dai et al. (2017) showed that a graph neural network (GNN) called *structure2vec* Dai et al. (2016) can construct a solution for the Traveling Salesman Problem (TSP). *structure2vec* is a popular GNN derived from mean-field inference with a probabilistic graphical model (PGM). Dai et al. (2017) formulates the TSP as a Markov decision process (MDP) where a heuristically constructed PGM represents each state-next assignment pair. They employ *structure2vec* derived from the heuristic PGM to infer the Q-function, which they use to select the next assignment. While their choice of PGM was heuristic, their approach achieved near-optimality and transferability of their trained single-robot scheduling algorithm to new single-robot scheduling problems with an unseen number of tasks. However, those successes were restricted to single-robot problems except for special cases where the problem can be modeled as a variant of single-robot TSP via multiple successive journeys of a single robot Nazari et al. (2018); Kool et al. (2018).

3   Multi-Robot Reward Collection Problem

In the main text, we model a general multi robot/machine scheduling problem as a discrete-time, discrete-state (DTDS) sequential decision-making problem. In the DTDS model, time advances in fixed increments Δ, i.e., $t_k = t_0 + \Delta \times k$ where t_k is the actual time after k decision epochs have passed. For simplicity, we use k as a time index representing the kth decision epoch. In this framework, s_k denotes a state, and action a_k denotes a joint assignment of robots/machines to unfinished tasks at the kth epoch. The objective of the problem is to learn the optimum scheduling policy $\pi_\theta : s_k \rightarrow a_k$ that maximizes the reward collected or minimizes the total completion time (a.k.a. makespan minimization). Below is the formulation of MRRC. We additionally propose a continuous-time continuous-state (CTCS) problem to identical parallel machine scheduling problems (IPMS) in Appendix A and minimax multiple traveling salesman problems in Appendix B.

Figure 1: Representation of the scheduling problem using a random PGM

3.1 State

The state s_k at epoch k is represented as $(g_k, \mathcal{D}_k)$ where a graph $g_k = ((\mathcal{R}, \mathcal{T}_k), (\mathcal{E}_k^{\mathcal{TT}}, \mathcal{E}_k^{\mathcal{RT}}))$ and associated feature set $\mathcal{D}_k = (\mathcal{D}_k^{\mathcal{R}}, \mathcal{D}_k^{\mathcal{T}}, \mathcal{D}_k^{\mathcal{TT}}, \mathcal{D}_k^{\mathcal{RT}})$. The elements of graph g_k are defined as (See Figure 1):

- $\mathcal{R} = \{1, ..., M\}$ is the index set of all robots. The index i and j will be used to specifically denote robots.
- $\mathcal{T}_k = \{1, ..., N\}$ is the index set of all remaining unserved tasks at decision epoch k. The index p and q will be used to specifically denote tasks.
- $\mathcal{E}_k^{\mathcal{TT}} = \{\epsilon_{pq}^{\mathcal{TT}} | p \in \mathcal{T}_k, q \in \mathcal{T}_k\}$ is the set of all directed edges from a task in $\mathcal{T}_k$ to any task in $\mathcal{T}_k$. We consider each edge as a random variable. The task-to-task edge $\epsilon_{pq}^{\mathcal{TT}} = 1$ indicates the event that a robot that has just completed task p subsequently completes task q. We denote the probability $p(\epsilon_{pq}^{\mathcal{TT}} = 1) \in [0, 1]$ the presence probability of the edge $\epsilon_{pq}^{\mathcal{TT}}$.
- $\mathcal{E}_k^{\mathcal{RT}} = \{\epsilon_{ip}^{\mathcal{RT}} | i \in \mathcal{R}, p \in \mathcal{T}_k\}$ is the set of all directed edges from a robot in $\mathcal{R}$ to a task in $\mathcal{T}_k$. We say the robot-to-task edge $\epsilon_{ip}^{\mathcal{RT}} = 1$ indicates the event that robot i is assigned to the task p. This edge is defined deterministically depending on the joint assignment action. If robot i is assigned to task p, then $p(\epsilon_{ip}^{\mathcal{RT}}) = 1$, otherwise 0.

The element of feature set $\mathcal{D}_k$ associated with the graph g_k is defined as:

- $\mathcal{D}_k^{\mathcal{R}} = \{d_i^{\mathcal{R}} | i \in \mathcal{R}\}$ is the set of node features for the robot nodes in $\mathcal{R}$ at epoch k. In MRRC, $d_i^{\mathcal{R}}$ is defined as the location of robot i at epoch k (epoch index k is omitted).
- $\mathcal{D}_k^{\mathcal{T}} = \{d_p^{\mathcal{T}} | p \in \mathcal{T}_k\}$ is the set of node features for the task nodes in $\mathcal{T}_k$ at epoch k. In MRRC, $d_p^{\mathcal{T}}$ is defined as the age of task p at epoch k (epoch index k is omitted).
- $\mathcal{D}_k^{\mathcal{TT}} = \{d_{pq}^{\mathcal{TT}} | p \in \mathcal{T}_k, q \in \mathcal{T}_k\}$ is the set of task-task edge features at epoch k. $d_{pq}^{\mathcal{TT}}$ denotes the duration for a robot that has just completed task p to subsequently compete task q. We call this duration *task completion time*. In MRRC, a task completion time is given as a random variable (in practice, our method only requires a set of samples of random variable).
- $\mathcal{D}_k^{\mathcal{RT}} = \{d_{ip}^{\mathcal{RT}} | i \in \mathcal{R}, p \in \mathcal{T}_k\}$ is the set of robot-task edge features at epoch k. $d_{ip}^{\mathcal{RT}}$ denotes the traveling time for robot i to reach task p.

3.2 Action

An action a_k, a joint assignment at epoch k, is defined as a maximal bipartite matching of the complete bipartite graph $(\mathcal{R}, \mathcal{T}_k, \mathcal{E}_k^{\mathcal{RT}})$ composed of the robot nodes $\mathcal{R}$, the remaining task nodes $\mathcal{T}_k$, and the fully connected edges between them $\mathcal{E}_k^{\mathcal{RT}}$. That is, given the current state $s_k = (g_k, \mathcal{D}_k)$, a_k is a subset of $\mathcal{E}_k^{\mathcal{RT}}$ satisfying (1) no two robots can be assigned to the same tasks, and (ii) a robot may only remain without assignment when the number of robots exceeds the number of remaining tasks. If $\epsilon_{ip}^{\mathcal{RT}} \in a_k$, it means that robot i is assigned with task p at epoch k. For example, Figure 1 shows the case where $a_k = (\epsilon_{1,1}^{\mathcal{RT}}, \epsilon_{2,3}^{\mathcal{RT}})$. (Note, we equivalently may say this as $\epsilon_{1,1}^{\mathcal{RT}} = \epsilon_{2,3}^{\mathcal{RT}} = 1$ and 0 otherwise.) In MRRC, all robots are allowed to change their assignments at each decision epoch. (In IPMS and mTSP, only free machines/salesmen are newly assigned.)

3.3 State transition

As the joint assignment a_k is executed given the current state $s_k = (g_k, \mathcal{D}_k)$, the next state $s_{k+1} = (g_{k+1}, \mathcal{D}_{k+1})$ is determined with the updated graph g_{k+1} and features $\mathcal{D}_{k+1}$.

122 **Graph update.** When the decision epoch corresponds to the point when task p is completed, the
123 corresponding task node will be removed in the updated task nodes as $\mathcal{T}_{k+1} = \mathcal{T}_k/\{p\}$, and the
124 task-task edges and robot-task edges, $\mathcal{E}_{k+1}^{\mathcal{TT}}$ and $\mathcal{E}_{k+1}^{\mathcal{RT}}$, will be accordingly updated.

125 **Feature update.** At decision epoch $k + 1$, $\mathcal{D}_{k+1} = (\mathcal{D}_{k+1}^{\mathcal{R}}, \mathcal{D}_{k+1}^{\mathcal{T}}, \mathcal{D}_{k+1}^{\mathcal{TT}}, \mathcal{D}_{k+1}^{\mathcal{RT}})$ is determined. In
126 MRRC, task locations $\mathcal{D}_{k+1}^{\mathcal{R}} = \{d_i^{\mathcal{R}} | i \in \mathcal{R}\}$ and task ages $\mathcal{D}_{k+1}^{\mathcal{T}} = \{d_p^{\mathcal{T}} | p \in \mathcal{T}_{k+1}\}$ are updated.
127 The robot-task edge features $\mathcal{D}_{k+1}^{\mathcal{RT}}$ will be updated according to $\mathcal{D}_{k+1}^{\mathcal{R}}$ as well.

3.4 Reward and objective

129 At time 0, each task is given an initial age which increases linearly in time. A reward $r_k = r\left(d_p^{\mathcal{T}}\right)$ is
130 given when a task $p \in \mathcal{T}_k$, whose age is $d_p^{\mathcal{T}}$, is served at epoch k. We consider linear and nonlinear
131 reward functions r for MRRC. The objective is to maximize expected total collected rewards.

4 Random graph embedding: *RandStructure2Vec*

133 We observe that when task completion time is not deterministic, a scheduling problem can be
134 represented as an extension of probabilistic graphical models (PGMs), which we refer to as random
135 PGMs. This section proposes a mean-field inference method, *random struct2vec*, for random PGMs
136 to estimate the state-action value $Q(s_k, a_k)$ in solving MRRC.

4.1 Random PGM for representing a state of MRRC

138 Given random variables $\mathcal{X} = \{X_p\}$, suppose that we can factor the joint distribution $p(\mathcal{X})$ as
139 $p(\mathcal{X}) = \frac{1}{Z} \prod_i \phi_i(\mathcal{D}_i)$ where $\phi_i(\mathcal{D}_i)$ denotes a marginal distribution or conditional distribution as-
140 sociated with a set of random variables $\mathcal{D}_i$; Z is a normalizing constant. Then $\{X_p\}$ is called a
141 probabilistic graphical model (PGM). In a PGM, $\mathcal{D}_i$ is called a clique and $\phi_i(\mathcal{D}_i)$ is called the clique
142 potential for $\mathcal{D}_i$, and $\mathcal{D}_i$ is called the scope of ϕ_i. We often write simply ϕ_i, suppressing $\mathcal{D}_i$.

143 Starting from a state s_k and an action a_k, one can conduct a random experiment of "sequential
144 decision making using policy π". In this random experiment, we can denote the events 'How robots
145 serve all remaining tasks in which sequence' as *scenarios*. For example, suppose that at time-step k we
146 are given robots $\{r_1, r_2\}$, tasks $\{t_1, t_2, t_3, t_4, t_5, t_6\}$ and we follow the policy π onward. One possible
147 scenario is that robot r_1 serves tasks $\{t_1 \rightarrow t_4\}$ and robot r_2 serves tasks $\{t_3 \rightarrow t_2 \rightarrow t_5 \rightarrow t_6\}$
148 (see Figure 1). Note that the time when t_5 is served depends on the time when t_2 is served (state
149 transition is Markovian); thus the reward from t_5 depends on the reward from t_2. As shown in Figure
150 1, $\{\{t_1 \rightarrow t_4\}, \{t_3 \rightarrow t_2 \rightarrow t_5 \rightarrow t_6\}\}$ can be represented as a single instance of a Bayesian Network.
151 Since scenario realization is random, we can construct the distribution over such scenarios using
152 'random' Bayesian Network with random node $X_k = (s_k, a_k)$ and clique potential ϕ.

4.2 Mean-field inference with random PGM

154 Let $\mathcal{X} = \{X_p\}$ be the set of all random variables in the inference problem. Let $\mathcal{G}_{\mathcal{X}}$ be the set of all
155 possible PGMs on $\mathcal{X}$. Let $\mathcal{P} : \mathcal{G}_{\mathcal{X}} \mapsto [0, 1]$ be a probability measure on $\mathcal{G}_{\mathcal{X}}$. Define a random PGM
156 on $\mathcal{X}$ as $\{\mathcal{G}_{\mathcal{X}}, \mathcal{P}\}$. Note that the inference of $\{\mathcal{G}_{\mathcal{X}}, \mathcal{P}\}$ will be difficult; $|\mathcal{G}_{\mathcal{X}}|$ is too large for inferring
157 $\mathcal{P}$ even using Monte-Carlo sampling approach. To avoid this difficulty, we use the approximated
158 inference using *semi-cliques*. Suppose that we are given the set of all possible cliques on $\mathcal{X}$ as $\mathfrak{C}_{\mathcal{X}}$.
159 As a PGM will be realized according to $\mathcal{P}$, only a few of the possible cliques in $\mathfrak{C}_{\mathcal{X}}$ will be actually
160 realized as an element of the PGM and become real cliques. We call such potential clique elements
161 of $\mathfrak{C}_{\mathcal{X}}$ as *semi-cliques*. Note that if we were given $\mathcal{P}$, we could calculate the presence probability p_m
162 of the semi-clique $\mathcal{D}_m$ as $p_m = \sum_{G \in \mathcal{G}_{\mathcal{X}}} \mathcal{P}(G) \mathbf{1}_{\mathcal{D}_m \in G}$, where $\mathbf{1}$ denotes the indicator function.

163 **Mean-field inference with random PGM.** We start from a specific inference problem and state the
164 main theorem in more general way. Consider a random PGM on $\mathcal{X} = (\{H_i\}, \{X_j\})$ where H_k is
165 the latent variable corresponding to the observed variable X_k. Our goal is to infer $\{H_i\}$ given $\{X_j\}$
166 by finding $p(\{H_i\}|\{x_j\})$. In mean-field inference, we instead find a set of surrogate distributions
167 $\{q^{\{x_j\}}(H_i)\}$ for which $\{H_i\}$ are independent. Here $q^{\{x_j\}}$ means that q is a function of $\{x_j\}$).

168 We next state **Theorem 1.** in a very general manner. The statement is the same as that of mean-field
169 inference with PGM Koller & Friedman (2009) except that ours has the presence probability terms
170 $\{p_m\}$ of semi-cliques $\{\mathcal{D}_m\}$. The implication is that inference of presence probability of each
171 semi-clique is enough to conduct mean-field inference, and the inference of $\{\mathcal{G}_\mathcal{X}, \mathcal{P}\}$ is not needed.

172 **Theorem 1**. *Random PGM based mean field inference. Suppose a random PGM on $\mathcal{X} = \{X_p\}$*
173 *is given, and the presence probability $\{p_m\}$ for all semi-cliques $\mathcal{D}_m \in \mathfrak{C}_\mathcal{X}$ are known.*
174 *Then, the surrogate distribution $\{q_p(x_p)\}$ in mean-field inference is optimal only if $q_p(x_p) =$*
175 $\frac{1}{Z_p} \exp\left\{\sum_{m:X_p \in \mathcal{D}_m} p_m \mathbb{E}_{(\mathcal{D}_m - \{X_p\}) \sim q} [\ln \phi_m (\mathcal{D}_m, x_p)]\right\}$ *where Z_p is a normalizer and ϕ_m clique*
176 *potential for $\mathcal{D}_m$.*

177 For the general background and proof, see Appendix C.

178 **RandStructure2Vec.** In Dai et al. (2016), structure2vec was derived as a vector space embedding of
179 mean-field inference with PGM. For detailed background on vector space embedding, see Appendix
180 D. From **Theorem 1**, we derive *random structure2vec* as a vector-space embedding of mean-field
181 inference with random PGM. Suppose that once a PGM is realized the PGM has joint distribution
182 proportional to some factorization $\prod_p \phi(H_p|I_p) \prod_{p,q} \phi(H_p|H_q)$ (as in Dai et al. (2016)). Under
183 this assumption, we can write $\{q^{\{x_j\}}(H_i)\}$ as $\{q^{x_i}(H_i)\}$. In Dai et al. (2016), they suggest that
184 structure2vec is essentially a fixed point iteration $\tilde{\mu}_p \leftarrow \sigma(W_1 x_p + W_2 \sum_{q \neq p} \tilde{\mu}_q)$ where $\tilde{\mu}_p$ is a
185 latent vector for node p and x_p is input for node p. They show that, when we interpret $\tilde{\mu}_i$ as a vector
186 space injective embedding expressed as $\tilde{\mu}_i = \int_\mathcal{H} \phi(h_i) q^{x_i}(h_i) dh_i$ for some ϕ, structure2vec's fixed
187 point iteration is the embedding of fixed point iteration of mean-field inference with the PGM. *Lemma*
188 *1* states that we have a similar result for random PGM by including only the $\{p_{qp}\}$ information.

189 **Lemma 1**. *Structure2vec for random PGM. Assume that the presence probabilities $\{p_{qp}\}$ for all*
190 *pairwise semi-cliques $\mathcal{D}_{qp} \in \mathfrak{C}_\mathcal{X}$ are given. Then embedding the fixed point equation in Theorem 1*
191 *generates the fixed point equation $\tilde{\mu}_p \leftarrow \sigma\left(W_1 x_p + W_2 \sum_{q \neq p} p_{qp} \tilde{\mu}_q\right)$. We refer to this fixed point*
192 *iteration as random structure2vec. (The proof of Lemma 1 can be found in Appendix E.)*

193 **Remarks.** Note that inference of $\{\mathcal{G}_\mathcal{X}, \mathcal{P}\}$ is in general a difficult task. One implication of *Theorem*
194 *1* is that *we transformed a difficult inference task into a simple inference task*: inferring the presence
195 probability of each semi-clique. (See Appendix F for the algorithm that conducts this task.) In
196 addition, *Lemma 1* provides a theoretical justification to ignore the inter-dependencies among edge
197 presences when embedding a random graph using GNN. When graph edges are not explicitly given or
198 known to be random, the simplest heuristic one can use is to separately infer the presence probabilities
199 of all edges and adjust the weights of GNN's message propagation. According to *Lemma 1*, possible
200 inter-dependencies among edges would not affect the quality of such heuristic inference.

201 This section describes how the proposed method solves the MRRC problem with the newly developed
202 *random structure2vec* method. The total solution (i.e., the sequential assignments of robots/machines
203 to tasks) is found by iteratively repeating a sequential decision making. This section specifically
204 describes how to choose a joint assignment a_k given the current state $s_k = (g_k, \mathcal{D}_k)$. The procedure
205 for determining a joint assignment action is composed of (1) represent the state using a random
206 Bayesian Network, (2) estimate the Q-value using random graph embedding, and (3) select a joint
207 assignment.

4.3 Representing a state using a random PGM

209 In this section, we describe how the MRRC problem state s_k and one possible joint assignment
210 a_k can be represented as a Bayesian network. Assume H_p, the hidden random variable for task
211 p, carries information about the benefit of serving task p. Given a scenario (see section 3.1), H_p
212 depends on H_q only if q is served after p by the same robot, and H_p depends on X_p, the observed
213 features for task p. For an MRRC problem, X_p can be either a task's assignment information $d_{ip}^{\mathcal{R}\mathcal{T}}$ or
214 a task's age $d_p^\mathcal{T}$. Based on these definitions, a Bayesian Network for $\{H_p\}$ and $\{X_p\}$ is constructed
215 as $p(\{H_p\}|\{X_p\}) = \prod_p \phi(H_p|X_p) \prod_{p,q} \phi(H_p|H_q)$. This Bayesian Network corresponds to one
216 scenario; there are many possible scenarios that can be realized randomly. Since random PGM natu-
217 rally models this characteristic, according to Lemma 1, we are justified to use *random structure2vec*
218 with edge (semi-clique) presence probabilities $\{p(\epsilon_{pq}^{\mathcal{T}\mathcal{T}})\}$ from in section 2.1.

4.4 Estimating state-action value using Order trainability-enabled Q-function

We illustrate how we can estimate a Q-function for MRRC by applying *random structure2vec* to the random PGM that represents (s_k, a_k). *Lemma 1* provides the fixed point equation $\tilde{\mu}_p = \sigma\left(W_1 x_p + W_2 \sum_{j \neq k} p_{qp} \tilde{\mu}_q\right)$ to compute the embeddings $\tilde{\mu}_p$ for node task p in a random PGM. The embeddings $\tilde{\mu}_p$ for $p \in \mathcal{T}_k$ are computed in an iterative manner using *random structure2vec* as: $\tilde{\mu}_p^{(\tau+1)} = \sigma\left(W_1 x_p + W_2 \sum_{q \neq p} p_{qp} \tilde{\mu}_q^{(\tau)}\right)$. We propose a network architecture composed of two-step sequential *random structure2vec*, which is composed of *action embedding* and *value embedding*.

Action Embedding. The first *random structure2vec* layer embeds the joint assignment into the task nodes $\mathcal{T}_k = \{1, ..., n\}$. The action embedding $\tilde{\mu}_p^A$ for task node p is defined as the fixed point for the equation $\tilde{\mu}_p^A = \sigma\left(W_1^A x_p^A + W_2^A \sum_{q \neq p} p_{qp} \tilde{\mu}_q^A\right)$ where $x_p^A = d_{ip}^{\mathcal{R}\mathcal{T}}$ (distance from robot i to task p) when task p is assigned to robot i, $x_p^A = 0$ when task p is not assigned. The action node embeddings $\{\tilde{\mu}_p^A | p \in \mathcal{T}_k\}$, computed via iteration simultaneously by employing *random structure2vec*, provide sufficient information about the relative locations between robots and their assigned tasks.

Value Embedding. The second *random structure2vec* layer embeds the task ages into the task nodes. The value embedding $\tilde{\mu}_p^V$ for task node p is defined as the fixed point for the equation $\tilde{\mu}_p^V = \sigma\left(W_1^V x_p^V + W_2^V \sum_{q \neq p} p_{qp} \tilde{\mu}_q^V\right)$ where $x_p^V = (\tilde{\mu}_p^A, d_p^{\mathcal{T}})$ is the concatenation of the action embedding $\tilde{\mu}_p^A$ computed by the first layer and the task age $d_p^{\mathcal{T}}$ for node p. The resulting value node embeddings $\{\tilde{\mu}_p^V | p \in \mathcal{T}_k\}$, computed in an iterative manner, provide sufficient information about how much value is likely in the local graph around each task by the specified joint assignment.

Computing $Q_\theta(s_k, a_k)$. To derive $Q_\theta(s_k, a_k)$, we aggregate the embedding vectors for all nodes by $\tilde{\mu}^V = \sum_p \tilde{\mu}_p^V$ to obtain one global vector $\tilde{\mu}^V$ to embed the value affinity of the global graph. We then use a neural network to map $\tilde{\mu}^V$ into $Q_\theta(s_k, a_k)$. The overall pseudo-code for estimating steps is provided in Appendix G.

It is essential for the proposed inference method can estimate the state action value $Q_\theta(s_k, a_k)$ for varying graph size g_k. Let us provide the intuition related to scuh problem-size transferability. For *Action Embedding*, transferability is trivial; the inference problem is a scale-free task *locally around each node*. For *Value Embedding*, consider the ratio of robots to tasks. The overall value affinity embedding will be underestimated if this ratio in the training environment is smaller than this ratio in the testing environment; overestimated overall otherwise. The intuition is that this over/under-estimation does not matter in Q-function based policies as discussed in van Hasselt et al. (2015) as long as the *order* of Q-function value among actions are the same. That is, as long as the best assignments chosen are the same, i.e., $\arg\max_{a_k} Q(s_k, a_k) = \arg\max_{a_k} Q_\theta(s_k, a_k)$, the magnitude of imprecision $|Q(s_k, a_k) - Q_\theta(s_k, a_k)|$ does not matter. We call this property of an estimator *order-transferability* (with respect to the max operation).

4.5 Selecting a joint assignment using OTAP

With the previously introduced way to estimate $Q_\theta(s_k, a_k)$, we illustrate how to compute the joint assignment (action) a_k^*, a maximal bipartite matching in the bipartite graph $(\mathcal{R}, \mathcal{T}_k, \mathcal{E}_k^{\mathcal{R}\mathcal{T}})$, given the state $s_k = (g_k, D_k)$. Specifically, we propose the order transferability-enabled auction policy (OTAP) that constructs a joint assignment a_k through $N = \max(|\mathcal{R}|, |k|)$ iterations of *Bidding* and *Consensus* phases. This auction follows the spirit of Sequential Single Item (SSI) auctioning Koenig et al. (2006); each iteration adds one robot-task assignment to construct a full joint assignment.

Bidding-phase. In the n^{th} iteration of the bidding phase, given $\mathcal{M}_\theta^{(n-1)}$, the ordered set of $n-1$ robot-task edges in $\mathcal{E}_k^{RT}$ determined by the previous $n-1$ iterations, all the unassigned robots bid their the most preferable task to conduct. Respecting robot-task assignments determined in previous $n-1$ iterations and ignoring other unassigned robots, each unassigned robot i select the best task assignment $\epsilon_{il}^{\mathcal{R}\mathcal{T}}$ that maximizes $Q_\theta^n(s_k, \mathcal{M}_\theta^{(n-1)} \cup \{\epsilon_{ip}^{\mathcal{R}\mathcal{T}}\})$ among all unassigned tasks $p \in \mathcal{T}_k$, where Q_θ^n is the θ-parameterized network with superscript n indicating that the state action value is estimated at n^{th} iteration. Then, robot i bids $\{\epsilon_{il}^{\mathcal{R}\mathcal{T}}, Q_\theta^n(s_k, \mathcal{M}_\theta^{(n-1)} \cup \{\epsilon_{il}^{\mathcal{R}\mathcal{T}}\})\}$ to the centralized auctioneer. This bidding occurs simultaneously by all the unassigned robots at the n^{th} iteration.

268 Since the number of ignored robots varies at each iteration, transferability of Q-function inference is
269 crucial.

270 **Consensus-phase.** In the consensus phase of n^{th} iteration, the centralized auctioneer finds the bid
271 with the best bid value, say $\{\epsilon_{i^*p^*}^{\mathcal{RT}}, Q_\theta^n(s_k, \mathcal{M}_\theta^{(n-1)} \cup \{\epsilon_{i^*p^*}^{\mathcal{RT}}\})\}$ (Here i^* and p^* denote the best robot
272 task pair.) Denote $\epsilon_{i^*p^*}^{\mathcal{RT}} := m_\theta^{(n)}$. The auctioneer sets everyone's $\mathcal{M}_\theta^{(n)}$ as $\mathcal{M}_\theta^{(n)} = \mathcal{M}_\theta^{(n-1)} \cup m_\theta^{(n)}$
273 and initiate bidding phase for the remaining unassigned robots.

274 These two phases iterate until reaching $\mathcal{M}_\theta^{(N)} = \{m_\theta^{(1)}, \ldots, m_\theta^{(N)}\}$. This $\mathcal{M}_\theta^{(N)}$ is chosen as the
275 joint assignment a_k^* of N-robots at time step k. That is, $\pi_\theta(s_k) = a_k^*$. The computational complexity
276 for computing π_θ is O $(|R|\,|T|)$ and is only polynomial; see Appendix L.

4.6 Training Q-function using AFQI

278 The fitted Q-iteration (FQI) finds θ that minimizes $E_{(s_k,a_k,r_k,s_{k+1})\sim D} [Q_\theta(s_k, a_k) - [r(s_k, a_k) +$
279 $\gamma \max_a Q_\theta(s_{k+1}, a)]]$ where D denotes the distribution of training data. We propose a new rein-
280 forcement learning method, which we call *Auction-fitted Q-iteration (AFQI)*, which replaces $\max_a$
281 $Q_\theta(s_k, a)$ used in the conventional FQI with OTAP. That is, writing OTAP as π_{Q_θ}, AFQI finds θ that
282 empirically minimizes $E_{(s_k,a_k,r_k,s_{k+1})\sim D} [Q_\theta(s_k, a_k) - [r(s_k, a_k) + \gamma Q_\theta(s_{k+1}, \pi_{Q_\theta}(s_{k+1}))]]$.

5 Theoretical analysis

284 We show the proposed AFQI obtains at least $1 - 1/e$ optimality and enables computation of the joint
285 assignment in polynomial time. This result is achieved by the order-transferability of the proposed
286 Q-function estimator and its use in selecting the joint assignment.

5.1 Performance bound of OTAP

288 Recall that Q^n denotes the n-robot problem's true Q-function. In the same way as we defined $\mathcal{M}_\theta^{(N)}$
289 above, denote the joint assignment chosen by OTAP as $\{Q^n\}_{n=1}^N$ as $\mathcal{M}^{(N)} = \{m^{(1)}, \ldots, m^{(N)}\}$.

290 ***Lemma 2.*** *If the Q-function approximator has order transferability, then* $\mathcal{M}^{(N)} = \mathcal{M}_\theta^{(N)}$.

291 For any decision epoch k, let $\mathcal{M}$ denote a set of robot-task pairs (a subset of $\mathcal{E}_k^{\mathcal{RT}}$). For any robot-task
292 pair $m \in \mathcal{E}_k^{\mathcal{RT}}$, define $\Delta(m \mid \mathcal{M}) := Q^{|\mathcal{M}\cup\{m\}|}(s_k, \mathcal{M}\cup\{m\}) - Q^{|\mathcal{M}|}(s_k, \mathcal{M})$ as the the marginal
293 value (under the true Q-functions) of adding robot-task pair $m \in \mathcal{E}_k^{\mathcal{RT}}$. Lemma 2 enables us to use
294 the result discussed in Nemhauser et al. (1978) and achieve the result of Theorem 2.

295 ***Theorem 2.*** *Suppose that the Q-function approximation with the parameter value θ exhibits order*
296 *transferability. Denote $\mathcal{M}_\theta^{(N)}$ as the result of OTAP using $\{Q_\theta^n\}_{n=1}^N$ and let $\mathcal{M}^* = \text{argmax}_{a_k}$*
297 *$Q^{|a_k|}(s_k, a_k)$. If $\Delta(m \mid \mathcal{M}) \geq 0, \forall \mathcal{M} \subset \mathcal{E}_k^{RT}, \forall m \in \mathcal{E}_k^{\mathcal{RT}}$, and the marginal value of adding one*
298 *robot diminishes as the number of robots increases, i.e., $\Delta(m \mid \mathcal{M}) \leq \Delta(m \mid \mathcal{N}), \forall \mathcal{N} \subset \mathcal{M} \subset \mathcal{E}_k^{RT}$,*
299 *$\forall m \in \mathcal{E}_k^{RT}$, then the result of OTAP is at least better than $1 - 1/e$ of an optimal assignment. That is,*
300 *$Q_\theta^N(s_k, \mathcal{M}_\theta^{(N)}) \geq Q^{|\mathcal{M}^*|}(s_k, \mathcal{M}^*)(1 - 1/e)$.* See Appendix H and K for the proofs.

5.2 Performance bound of AFQI

302 AFQI seeks to find θ that minimizes $E_{(s_k,a_k,r_k,s_{k+1})\sim D} [Q_\theta(s_k, a_k) - [r(s_k, a_k) +$
303 $\gamma Q_\theta(s_{k+1}, \pi_{Q_\theta}(s_{k+1}))]]$. Here, we use OTAP, denoted as π_{Q_θ}, instead of $\max_a Q_\theta(s_k, a)$ which is
304 used in general fitted-Q iteration. As we have seen in section 5.1, OTAP replaces the *max* operation
305 with the auction algorithm with a provable performance bound compared with the *max* operation.
306 *Lemma 3* allows us to use this performance bound to obtain a performance assurance on AFQI
307 compared with FQI. We only write an abbreviated version of the statement for brevity. The formal
308 description of conditions and the proof is provided in Appendix I.

309 ***Lemma 3.*** *Kang & Kumar (2021)* Suppose that a $1 - 1/r$ approximation algorithm is substituted for
310 the max operation in FQI. Then, the corresponding new Fitted Q-iteration's performance is at least
311 $1 - 1/r$ optimal.

Corollary 1. AFQI achieves at least $1 - 1/e$ performance compared with the optimal policy.

Table 1: Performance test (50 trials of training for each case)

Reward	Environment	Baseline	Testing size : Robot (R) / Task (T)						
			2R/20T	3R/20T	3R/30T	5R/30T	5R/40T	8R/40T	8R/50T
Linear	Deterministic	Optimal	98.31 ($\pm$4.23)	97.50 ($\pm$4.71)	97.80 ($\pm$5.14)	95.35 ($\pm$5.28)	96.99 ($\pm$5.42)	96.11 ($\pm$4.56)	96.85 ($\pm$3.40)
		Ekisi et al.	99.86 ($\pm$3.24)	97.50 ($\pm$2.65)	118.33 ($\pm$2.84)	110.42 ($\pm$2.97)	105.14 ($\pm$3.78)	104.63 ($\pm$2.50)	120.16 ($\pm$3.94)
		SGA	137.3 ($\pm$5.65)	120.6 ($\pm$5.03)	129.7 ($\pm$5.54)	110.4 ($\pm$4.34)	123.0 ($\pm$4.97)	119.9 ($\pm$4.74)	119.8 ($\pm$5.84)
	Stochastic	SGA	130.9 ($\pm$4.02)	115.7 ($\pm$4.03)	122.8 ($\pm$5.21)	115.6 ($\pm$6.23)	122.3 ($\pm$4.94)	113.3 ($\pm$5.53)	115.9 ($\pm$4.08)
Nonlinear	Deterministic	SGA	111.5 ($\pm$3.71)	118.1 ($\pm$5.56)	118.0 ($\pm$5.09)	110.9 ($\pm$4.64)	118.7 ($\pm$5.23)	111.2 ($\pm$5.38)	112.6 ($\pm$5.07)
	Stochastic	SGA	110.8 ($\pm$5.17)	117.4 ($\pm$6.22)	119.7 ($\pm$4.48)	111.9 ($\pm$4.70)	120.0 ($\pm$6.38)	110.4 ($\pm$5.14)	112.4 ($\pm$5.30)

Table 2: Transferability test (linear & deterministic env, standard dev. provided in the appendix)

Training size	Testing size : Robot (R) / Task (T)						
#R/ #T	2R/20T	3R/20T	3R/30T	5R/30T	5R/40T	8R/40T	8R/50T
2R/20T	98.31 ($\pm$4.23)	93.61($\pm$4.98)	97.31 ($\pm$4.25)	92.16 ($\pm$3.49)	92.83($\pm$4.25)	90.94($\pm$3.98)	93.44 ($\pm$4.02)
3R/20T	95.98($\pm$4.75)	97.50($\pm$3.71)	96.11($\pm$3.63)	93.64($\pm$4.54)	91.75($\pm$5.71)	91.60($\pm$5.03)	92.77($\pm$4.74)
3R/30T	94.16($\pm$4.97)	96.17($\pm$4.22)	97.80($\pm$5.14)	94.79($\pm$3.53)	93.19($\pm$3.78)	93.14($\pm$4.50)	93.28($\pm$3.99)
5R/30T	97.83($\pm$3.11)	94.89($\pm$4.43)	96.43($\pm$4.23)	95.35($\pm$5.28)	93.28($\pm$4.18)	92.63($\pm$5.07)	92.40($\pm$4.10)
5R/40T	97.39($\pm$4.65)	94.69($\pm$4.01)	95.22($\pm$4.88)	93.15($\pm$5.09)	96.99($\pm$4.42)	94.96($\pm$3.94)	93.65 ($\pm$5.66)
8R/40T	95.44($\pm$4.32)	94.43($\pm$4.88)	93.48($\pm$4.37)	93.93($\pm$5.05)	96.41($\pm$3.96)	96.11($\pm$4.56)	95.24($\pm$4.44)
8R/50T	95.69($\pm$3.18)	96.68($\pm$2.81)	97.35($\pm$4.20)	94.02($\pm$2.69)	94.50($\pm$4.44)	94.86($\pm$3.26)	96.85$\pm$3.40)

Table 3: Training complexity (mean of 20 trials of training, linear & deterministic env.)

Linear & Deterministic	Testing size : Robot (R) / Task (T)						
	2R/20T	3R/20T	3R/30T	5R/30T	5R/40T	8R/40T	8R/50T
Performance with full training	98.31	97.50	97.80	95.35	96.99	96.11	96.85
Training time for 93% optimality	19261.2	61034.0	99032.7	48675.3	48217.5	45360.0	47244.2

5.3 Experiment settings

In the main text, we focus on discrete-time & discrete-state (DTDS) MRRC problems with deterministic and stochastic task completion times. For CTCS deterministic problems with real-world datasets, see IPMS (Appendix A) and mTSP (Appendix B).

Environment. Since there is no standard dataset for MRRC problems, we used the complex maze-like environment generator of Neller et al. (2010) (code provided in Appendix 10). This complex maze mimics the complex road layout of a city and random traffic, inducing nontrivial task completion times. We randomly generated a new maze for every training and testing experiment with randomly chosen initial task/robot locations. To generate the task completion times, Dijkstra's algorithm and dynamic programming were used for deterministic and stochastic environments, respectively.

In the deterministic environment, robots always succeed in their movement. In the stochastic environment, a robot makes its intended move with a certain probability. (Cells with a dot: success with 55%, every other direction with 15% each. Cells without a dot: 70% and 10%, respectively.) A task is considered served when a robot reaches it. We consider two reward rules: linearly decaying rewards $f(age) = \max\{200 - age, 0\}$ and nonlinearly decaying rewards $f(age) = \lambda^{age}$ with $\lambda = 0.99$, where age is the task age when served. The initial age of tasks are uniformly distributed.

Baselines. For deterministic environments with linear rewards, where the corresponding MRRC can be formulated as a mixed-integer linear program (MILP), we consider the following two baselines:

- *Optimal*: Gurobi Gurobi Optimization (2019), an off-the-self the optimization solver for MILP, was used to solve the problems with 60-min time limit.

- *Ekici et al.*: Ekici & Retharekar (2013), the most up-to-date heuristic for solving MRRC in the Operations Research community, was used the problems.

For stochastic environments or exponential rewards, to our knowledge, there is no literature addressing MRRC with. Thus, we construct an indirect baseline:

- *Sequential Greedy Algorithm (SGA)*: a general-purpose multi-robot task allocation algorithm called SGA Han-Lim Choi et al. (2009).

The performance measure we used is

$$\rho = \frac{\text{rewards collected by the proposed method}}{\text{reward collected by the baseline}}$$

Thus, the value of ρ greater than 100% indicates the the proposed method collects more reward than the corresponding baseline algorithm. Note that ρ against Optimal always lower than 100%.

Note that we cannot provide other reinforcement learning-based heuristics as additional baselines since, to the best of our knowledge (for the class of NP-hard multi-robot/machine scheduling problems with decaying rewards), this paper is the first to propose a reinforcement learning-based heuristic.

5.4 Performance test.

We tested the performance under four environments: deterministic/linear rewards, deterministic/nonlinear rewards, stochastic/linear rewards, stochastic/nonlinear rewards. See Table . Our method achieves near-optimality for linear/deterministic rewards with 3% fewer rewards than *optimal* on average. The standard deviation for ρ is provided in parentheses. For others, we see that the %SGA ratio for linear/deterministic is well maintained in stochastic or nonlinear environments. Due to dataset generation's dynamic programming computation complexity, we only consider 8 robots/50 tasks at maximum. We consider larger size problems in IPMS experiments discussed in Appendix A.

5.5 Transferability test.

Table 2 provides comprehensive transferability test results. The rows indicate training conditions, while the columns indicate testing conditions. The results in the diagonal cells in red (cells with the same training size and testing size) serve as baselines (direct testing). The results in the off-diagonal show the results for the transferability testing and demonstrate how the algorithms trained with different problem sizes perform well on test problems (zero-shot transfer). We can see that lower-direction transfer tests (trained with larger size problems and tested with smaller size problems) show only a small loss in performance. For upper-direction transfer tests (trained with smaller size problems and tested with larger size problems), the loss was up to 4 percent.

5.6 Scalability analysis.

For training complexity, we measured the training time required to achieve 93% optimality considering a deterministic environment with linear rewards. Table 4 shows that training time may not necessarily increase as problem size gets larger, while the performance is fairly maintained.

MRRC can be formulated as a semi-MDP (SMDP) based multi-robot planning problem (e.g., Omidshafiei et al. (2017)). This problem's complexity with R robots and T tasks and maximum H time horizon is $O((R!/T!(R-T)!)^H)$. In our proposed method, this complexity is addressed by a combination of two complexities: computational complexity and training complexity. For computational complexity of joint assignment decision at each timestep is $O(|R||T|^3)$. See Appendix L for details.

6 Concluding Remarks

In this paper, we addressed the challenge of developing a near-optimal learning-based method for solving NP-hard multi-robot/machine scheduling problems. We developed a theory of mean-field inference for scheduling problems and a corresponding theoretically justified GNN method to precisely infer the Q-function. We addressed the scalability issue of Fitted Q-Iteration methods for multi-robot/machine scheduling problems by providing a polynomial-time algorithm with a provable performance guarantee. Simulation results demonstrate the effectiveness of the our methods.

References

Agarwal, A., Jiang, N., and Kakade, S. M. Reinforcement learning: Theory and algorithms. Technical report, 2019.

Dai, H., Dai, B., and Song, L. Discriminative Embeddings of Latent Variable Models for Structured Data. 48:1–23, 2016. doi: 1603.05629.

Dai, H., Khalil, E. B., Zhang, Y., Dilkina, B., and Song, L. Learning Combinatorial Optimization Algorithms over Graphs. (Nips), 2017.

Ekici, A. and Retharekar, A. Multiple agents maximum collection problem with time dependent rewards. Computers and Industrial Engineering, 64(4):1009–1018, 2013. ISSN 03608352. doi: 10.1016/j.cie.2013.01.010. URL http://dx.doi.org/10.1016/j.cie.2013.01.010.

Fischer, M. J., Lynch, N. A., and Paterson, M. S. Impossibility of distributed consensus with one faulty process. Journal of the ACM (JACM), 32(2):374–382, 1985.

Google. Google OR-Tools, 2012. URL https://developers.google.com/optimization/.

Gurobi Optimization, L. Gurobi optimizer reference manual, 2019. URL http://www.gurobi.com.

Han-Lim Choi, Brunet, L., and How, J. Consensus-Based Decentralized Auctions for Robust Task Allocation. IEEE Transactions on Robotics, 25(4):912–926, aug 2009. ISSN 1552-3098. doi: 10.1109/TRO.2009.2022423.

Kang, H. and Kumar, P. R. 1+r-approximate policy and fitted q-iteration for problems with large action space. Unpublished working paper (http://people.tamu.edu/~hwkang/KangKumar2021A), 2021.

Koenig, S., Tovey, C., Lagoudakis, M., Markakis, V., Kempe, D., Keskinocak, P., Kleywegt, A., Meyerson, A., and Jain, S. The power of sequential single-item auctions for agent coordination. In AAAI, volume 2006, pp. 1625–1629, 2006.

Koller, D. and Friedman, N. Probabilistic graphical models : principles and techniques, page 449-453. The MIT Press, 1st edition, 2009. ISBN 9780262013192.

Kool, W., Van Hoof, H., and Welling, M. Attention, learn to solve routing problems! arXiv preprint arXiv:1803.08475, 2018.

Kurz, M. E., Askin, R. G., Kurzy, M. E., and Askiny, R. G. Heuristic scheduling of parallel machines with sequence-dependent set-up times. International Journal of Production Research, 39(16): 3747–3769, 2001. ISSN 0020-7543. doi: 10.1080/00207540110064938.

Long, Q., Zhou, Z., Gupta, A., Fang, F., Wu, Y., and Wang, X. Evolutionary population curriculum for scaling multi-agent reinforcement learning, 2020.

minmaxTSPlib. minmax multiple-tsp library. https://profs.info.uaic.ro/~mtsplib/MinMaxMTSP/, 2021.

Nazari, M., Oroojlooy, A., Snyder, L. V., and Takáč, M. Reinforcement Learning for Solving the Vehicle Routing Problem. feb 2018.

Neller, T., DeNero, J., Klein, D., Koenig, S., Yeoh, W., Zheng, X., Daniel, K., Nash, A., Dodds, Z., Carenini, G., Poole, D., and Brooks, C. Model AI Assignments. Proceedings of the Twenty-Fourth AAAI Conference on Artificial Intelligence (AAAI-10), pp. 1919–1921, 2010.

Nemhauser, G. L., Wolsey, L. A., and Fisher, M. L. An analysis of approximations for maximizing submodular set functions—i. Mathematical programming, 14(1):265–294, 1978.

Omidshafiei, S., Agha–Mohammadi, A., Amato, C., Liu, S., How, J. P., and Vian, J. Decentralized control of multi-robot partially observable Markov decision processes using belief space macro-actions. The International Journal of Robotics Research, 36(2):231–258, 2017. doi: 10.1177/0278364917692864.

Rashid, T., Samvelyan, M., de Witt, C. S., Farquhar, G., Foerster, J., and Whiteson, S. Qmix: Monotonic value function factorisation for deep multi-agent reinforcement learning, 2018.

Smola, A., Gretton, A., Song, L., and Schölkopf, B. A hilbert space embedding for distributions. In International Conference on Algorithmic Learning Theory, pp. 13–31. Springer, 2007.

Sriperumbudur, B. K., Gretton, A., Fukumizu, K., Lanckriet, G., and Schölkopf, B. Injective hilbert space embeddings of probability measures. In 21st Annual Conference on Learning Theory (COLT 2008), pp. 111–122. Omnipress, 2008.

Sunehag, P., Lever, G., Gruslys, A., Czarnecki, W. M., Zambaldi, V., Jaderberg, M., Lanctot, M., Sonnerat, N., Leibo, J. Z., Tuyls, K., and Graepel, T. Value-decomposition networks for cooperative multi-agent learning, 2017.

van Hasselt, H., Guez, A., and Silver, D. Deep Reinforcement Learning with Double Q-learning. 2015.