Simple Stochastic and Online Gradient Decent Algorithms for Pairwise Learning

Abstract

Pairwise learning refers to learning tasks where the loss function depends on a pair of instances. It instantiates many important machine learning tasks such as bipartite ranking and metric learning. A popular approach to handle streaming data in pairwise learning is an online gradient descent (OGD) algorithm, where one needs to pair the current instance with a buffering set of previous instances with a sufficiently large size and therefore suffers from a scalability issue. In this paper, we propose simple stochastic and online gradient descent methods for pairwise learning. A notable difference from the existing studies is that we only pair the current instance with the previous one in building a gradient direction, which is efficient in both the storage and computational complexity. We develop novel stability results, optimization, and generalization error bounds for both convex and nonconvex as well as both smooth and nonsmooth problems. We introduce novel techniques to decouple the dependency of models and the previous instance in both the optimization and generalization analysis. Our study resolves an open question on developing meaningful generalization bounds for OGD using a buffering set with a very small fixed size. We also extend our algorithms and stability analysis to develop differentially private SGD algorithms for pairwise learning which significantly improves the existing results.

1 Introduction

Many important learning tasks involve pairwise loss functions which are often referred to as pairwise learning. Such notable learning tasks include AUC maximization [14, 20, 26, 32, 40, 42], metric learning [4, 22, 34, 35, 38], and a minimum error entropy principle [18]. For instance, AUC maximization aims to rank positive instances above negative ones which involves a loss $f(\mathbf{w}; (x, y), (x', y')) = (1 - \mathbf{w}^\top(x - x'))_+ \mathbb{I}_{[y=1 \wedge y'=-1]}$ with $x, x' \in \mathcal{X} \subseteq \mathbb{R}^d$ and $y, y' \in \{\pm 1\}$. The aim of metric learning is to learn a distance function $h_{\mathbf{w}}(x, x') = (x - x')^\top \mathbf{w}(x - x')$ where $\mathbf{w}$ is positive semi-definite matrix in $\mathbb{R}^{d \times d}$. A typical pairwise loss can be $f(\mathbf{w}; (x, y), (x', y')) = (1 + \tau(y, y')h_{\mathbf{w}}(x, x'))_+$ where $\tau(y, y') = 1$ if $y = y'$ and -1 otherwise. While the ERM formulation for pairwise learning has been well studied theoretically using algorithmic stability [1] and U-statistics tools [10], there are considerable interests on developing and studying its online gradient descent (OGD) or stochastic gradient descent (SGD) algorithms due to their scalability in practice.

The critical issue for designing such stochastic algorithms is to construct intersecting pairs of instances for updating the model parameter upon receiving individual instances. For the offline (finite-sum) setting where the prescribed training data $S = \{z_1, \ldots, z_n\}$ is available, one natural approach is to, at each time t, randomly select a pair of instances (z_{i_t}, z_{j_t}) from $n(n-1)/2$ pairs and update $\mathbf{w}$ based on the gradient of the local error $f(\mathbf{w}_{t-1}; z_{i_t}, z_{j_t})$. The excess generalization and stability was nicely established in [25]. One popular approach [20, 33, 39, 42] is to consider the online set-

ting where the data is continuously arriving. This approach pairs the current datum $z_t = (x_t, y_t)$, which is received at time t, with all previous instances $S_{t-1} = \{z_1, \ldots, z_{t-1}\}$ and then performs the update based on the gradient of the local error $f(\mathbf{w}_{t-1}; S_{t-1}) = \frac{1}{t-1} \sum_{z \in S_{t-1}} f(\mathbf{w}_{t-1}; z_t, z)$. It requires a high gradient complexity $\mathcal{O}(t)$ (i.e. the number of computing gradients) which is expensive when t becomes large. To mitigate this potential limitation, [20, 32, 42] proposed to use a buffering set $B_{t-1} \subseteq S_{t-1}$ of size s and the local error $f(\mathbf{w}_{t-1}; B_{t-1}) = \frac{1}{s} \sum_{z \in B_{t-1}} f(\mathbf{w}_{t-1}; z_t, z)$ which reduces the gradient complexity to $\mathcal{O}(s)$. The excess generalization bound $\mathcal{O}(\frac{1}{\sqrt{s}} + \frac{1}{\sqrt{n}})$ was established in [20] using the online-to-batch conversion method [8] which is only meaningful for a very large s. In particular, this bound tends to zero only when s becomes to infinity as $n \to \infty$. It was mentioned in [20] (see the discussion at the end of Section 7 there) as an open question on how to get a meaningful bound for a fixed constant s.

In this paper, we show that optimal generalization bounds can be achieved for simple SGD and OGD algorithms for pairwise learning where, at time t, the current instance z_t is only paired with the previous instance z_{t-1}. This is equivalent to the First-In-First-Out (FIFO) buffering strategy [20, 32] while keeping the size s of the buffering set B_{t-1} to be $s = 1$, where, in this FIFO policy, the data z_t arriving at time $t > 1$ is included into the buffer by removing $\{z_1, \ldots, z_{t-2}\}$ from the buffer. In particular, our main contributions are summarized as follows.

- We propose simple SGD and OGD algorithms for pairwise learning where the t-th update of the model parameter is based on the interacting of the current instance and the previous one which has a constant gradient complexity $\mathcal{O}(1)$.

- We establish the stability results of the proposed SGD algorithms for pairwise learning and apply them to derive optimal excess generalization bounds $\mathcal{O}(1/\sqrt{n})$ for the proposed simple SGD algorithm for pairwise learning with both convex and nonconvex as well as both smooth and nonsmooth losses in the offline (finite-sum) setting where the training data of size n is given. We introduce novel techniques to decouple the dependency of the current SGD iterate with the previous instance in both the generalization and optimization error analysis, which resolves the open question in [20] on how to develop meaningful generalization bounds when a FIFO buffering set with a very small size.

- We further develop a localization version of our SGD algorithms under (ϵ, δ)-differential privacy (DP) constraints, and apply the obtained stability results to derive an optimal utility (excess generalization) bound $\tilde{\mathcal{O}}\big(1/\sqrt{n} + \sqrt{d}/n\epsilon\big)$. In contrast to the existing work [19] which requires the loss function to be smooth and an at least quadratic gradient complexity, our proposed DP algorithms only need a linear gradient complexity $\tilde{\mathcal{O}}(n)$ for smooth convex losses to achieve the optimal utility bound and can also apply to non-smooth convex losses.

The paper is organized as follows. Section 2 reviews the related work and Section 3 describes the proposed algorithms. In Section 4, we present excess generalization bounds, stability results, and optimization errors of our algorithms. Section 5 is devoted to the differentially private SGD for pairwise learning and its utility bounds. Section 6 provides experimental validation of theoretical findings. The paper is concluded in Section 7. All the main proofs are postponed to the Appendix.

2 Related Work

In this section, we briefly review the related work on SGD and online learning for pairwise learning as well as the recent work on their variants under differentially private constraints.

The work [20, 32, 33, 42] assumed the online learning setting in which a stream of i.i.d. data $\{z_1, z_2, \ldots, z_t, \ldots\}$ is continuously arriving. Upon receiving z_t at time t, it is paired with all previous instances and then the model parameter is updated based on the local error $F_t(\mathbf{w}_{t-1}) = \frac{1}{t-1} \sum_{j=1}^{t-1} f(\mathbf{w}_{t-1}; z_t, z_j)$. In particular, the work [32, 33] provided the first excess generalization bound for online learning methods by obtaining online-to-batch conversion bounds [8] using covering numbers of function classes. Kar et al. [20] significantly improved the results using the so-called symmetrization of expectations which reduce excess risk estimates to Rademacher complexities. To further reduce the expensive gradient complexity $\mathcal{O}(t)$ at a large time t, the work [20, 33, 42] proposed to use a buffering set B_{t-1} with size s instead of all previous instances. It was shown that

such OGD algorithms have an excess generalization bound $\mathcal{O}(\frac{1}{\sqrt{s}} + \frac{1}{\sqrt{n}})$ for convex and Lipschitz-continuous losses. In the offline learning setting where the training data $S = \{z_1, z_2, \ldots, z_n\}$ of size n is fixed, the work [37] considered the stochastic version of the algorithm in [20, 32] where, at time t, a random instance z_{i_t} with random index $i_t \in \{1, \ldots, n\}$ is paired with all previous instances $\{z_{i_1}, \ldots, z_{i_{t-1}}\}$. They derived stability and generalization results of such algorithms in expectation.

Lei et al. [25] considered the offline learning setting and, at time t, the algorithm there randomly picks a pair of instances (z_{i_t}, z_{j_t}) from all $\binom{n}{2}$ pairs of instances. An excess risk bound $\tilde{\mathcal{O}}(1/\sqrt{n})$ with high probability was derived for convex, Lipschitz and strongly smooth losses. Here the notation $\tilde{\mathcal{O}}(\cdot)$ means $\mathcal{O}(\cdot)$ up to some logarithmic terms. In the particular case of AUC maximization with the least square loss, [40] considered the online learning setting and reformulated the problem as a stochastic saddle point (min-max) problem which decouples the pairwise structure. From this reformulation, efficient SGD-type algorithms [27, 38] have been developed.

Recently, differentially private pairwise learning has been studied where the construction of pairs of instances follows [20, 32, 42] or all pairs are used at each iteration. In particular, Huai et al. [19] considered both online and offline learning settings and the pairs of instances at time t follow [20, 32, 42]. They provided a utility bound $\tilde{\mathcal{O}}(\sqrt{d}/(\sqrt{n}\epsilon))$ for convex and smooth loss functions. The study [37] also paired the current instance with all previous ones and showed that SGD with output perturbation for pairwise learning has a utility bound $\tilde{\mathcal{O}}(\sqrt{d}/(\sqrt{n}\epsilon))$ for nonsmooth convex losses. The work [36] showed that private gradient descent using all possible pairs can achieve a utility bound $\tilde{\mathcal{O}}(1/\sqrt{n} + \sqrt{d}/(n\epsilon))$ for strongly smooth and convex losses.

3 Proposed Algorithms for Pairwise Learning

In this section, we describe the proposed algorithms in two common learning settings for pairwise learning: offline and online learning settings. Let ρ be a probability measure defined on $\mathcal{Z} := \mathcal{X} \times \mathcal{Y}$, where $\mathcal{X}$ is an input space and $\mathcal{Y}$ is an output space. In pairwise learning, the performance of $\mathbf{w}$ is measured on a pair of instances (z, z') by a nonnegative loss function $f(\mathbf{w}; z, z')$. Denote by $[n] := \{1, 2, \ldots, n\}$ for any $n \in \mathbb{N}$.

Algorithm 1 SGD for Pairwise Learning	**Algorithm 2** OGD for Pairwise Learning
1: **Inputs:** $S = \{z_i : i \in [n]\}$ and step sizes $\{\eta_t\}$	1: **Inputs:** learning rates $\{\eta_t\}$
2: **Initialize:** $\mathbf{w}_0 \in \mathcal{W}$, let $\mathbf{w}_{-1} = \mathbf{w}_0$ and randomly select $i_0 \in [n]$	2: **Initialize:** $\mathbf{w}_0 \in \mathcal{W}$, let $\mathbf{w}_{-1} = \mathbf{w}_0$ and receiving datum z_0.
3: **for** $t = 1, 2, \ldots, T$ **do**	3: **for** $t = 1, 2, \ldots, T$ **do**
4: Randomly select $i_t \in [n]$	4: Receive a data point z_t
5: $\mathbf{w}_t = \Pi_{\mathcal{W}}\big(\mathbf{w}_{t-1} - \eta_t \nabla f(\mathbf{w}_{t-1}; z_{i_t}, z_{i_{t-1}})\big)$	5: $\mathbf{w}_t = \Pi_{\mathcal{W}}\big(\mathbf{w}_{t-1} - \eta_t \nabla f(\mathbf{w}_{t-1}; z_t, z_{t-1})\big)$
6: **Outputs:** $\bar{\mathbf{w}}_T = \sum_{j=1}^{T} \eta_j \mathbf{w}_{j-2} / \sum_{j=1}^{T} \eta_j$	6: **Outputs:** $\widetilde{\mathbf{w}}_T = \sum_{j=1}^{T} \eta_j \mathbf{w}_{j-2} / \sum_{j=1}^{T} \eta_j$

Offline Learning (Finite-Sum) Setting. The first is the finite-sum setting where the training data $S = \{z_i = (x_i, y_i) \in \mathcal{Z} : i \in [n]\}$ are drawn independently according to ρ. In this context, one aims to solve the following empirical risk minimization (ERM):

$$\mathbf{w}_S^* = \underset{\mathbf{w} \in \mathcal{W}}{\operatorname{argmin}} \Big[F_S(\mathbf{w}) := \frac{1}{n(n-1)} \sum_{i,j \in [n], i \neq j} f(\mathbf{w}; z_i, z_j) \Big]. \tag{1}$$

Our proposed algorithm to solve (1) is described in Algorithm 1. The notation $\Pi_{\mathcal{W}}(\cdot)$ there denotes the projection operator to $\mathcal{W}$. In particular, at iteration t, it randomly selects one instance z_{i_t} from the uniform distribution over $[n]$ and pairs it only with the previous instance $z_{i_{t-1}}$, and then do the gradient descent based on $\nabla f(\mathbf{w}_{t-1}; z_{i_t}, z_{i_{t-1}})$. This is in contrast to the classical SGD for pairwise learning in [20, 32, 42] where the present instance z_{i_t} is paired with all previous instances $\{z_{i_1}, z_{i_2}, \ldots, z_{i_{t-1}}\}$. Note $\mathbf{w}_{t-1}$ depends on $z_{i_{t-1}}$ and then $\nabla f(\mathbf{w}_{t-1}; z_{i_t}, z_{i_{t-1}})$ is not an unbiased estimate of $\nabla F_S(\mathbf{w}_{t-1})$. Therefore, the standard analysis of SGD does not apply. We introduce novel techniques to handle this dependency in our analysis (see more details in Section 4).

Online Learning Setting. In the online learning setting where the data $\{z_0, z_1, z_2, \ldots\}$ is assumed i.i.d. from an unknown distribution ρ on $\mathcal{Z}$, the number of iterations of an online algorithm is

128 identical to size of available data. In the same spirit to Algorithm 1, the pseudo code is given in
129 Algorithm 2. Specifically, upon receiving a datum z_t at the current time t, we pair it with z_{t-1}
130 which was revealed at the previous time $t-1$ and then perform gradient descent based on the
131 gradient $\nabla f(\mathbf{w}_{t-1}; z_t, z_{t-1})$. It aims to minimize the population risk which is defined as $F(\mathbf{w}) =$
132 $\mathbb{E}_{Z,Z'}[f(\mathbf{w}; Z, Z')]$. Here $\mathbb{E}_{Z,Z'}$ denotes the expectation with respect to (w.r.t.) $Z, Z' \sim \rho$.

133 It is worth of pointing out that online learning [17, 28, 29] in general does not require the i.i.d.
134 assumption on the data and study the regret bounds. In this paper, we mainly consider the statistical
135 performance, measured by excess generalization bounds, of the output $\widetilde{\mathbf{w}}_T$ of Algorithm 2 where
136 the streaming data $\{z_0, z_1, z_2, \ldots\}$ is i.i.d. from the population distribution ρ.

137 **Remark 1.** As discussed above, OGD for pairwise learning was proposed and studied in [20, 32]
138 where the current instance z_t is paired with a buffering set $B_t \subseteq \{z_1, \ldots, z_{t-1}\}$. However, the
139 resultant excess generalization bound is in the form of $\mathcal{O}(\frac{1}{\sqrt{s}} + \frac{1}{\sqrt{n}})$ which indicated that the buffer
140 size s needs to be large enough in order to achieve good generalization. Their analysis does not
141 apply to our case since the buffering set $B_t = \{z_{t-1}\}$ with size $s = 1$ for Algorithm 2. As we
142 show soon in Section 4, we can prove that Algorithm 2, which pairs the current instance z_t with the
143 previous instance z_{t-1}, still enjoys optimal statistical performance $\mathcal{O}(1/\sqrt{n})$.

144 **Remark 2.** The work [25] studied the stability and generalization of an SGD-type algorithm for
145 pairwise learning by randomly generating pairs of instances. Specifically, at time t, randomly gen-
146 erating a pair (z_{i_t}, z_{j_t}) from a given set of training data $S = \{z_i : i \in [n]\}$ and the subsequent
147 update is given by $\mathbf{w}_t = \mathbf{w}_{t-1} - \eta_t \nabla f(\mathbf{w}_{t-1}; z_{i_t}, z_{j_t})$. In contrast, our algorithm, i.e. Algorithm
148 1, updates the model parameter based on the pair of the current random instance and the random
149 one generated at the previous time $t-1$, i.e. $(z_{i_t}, z_{i_{t-1}})$. Furthermore, our work here significantly
150 differs from [25] in the following aspects. Firstly, the algorithm there by randomly selecting pairs
151 of instances does not work in the online learning setting while ours can seamlessly deal with the
152 streaming data as stated in Algorithm 2. Secondly, regarding the technical analysis, our algorithms
153 are more challenging to analyze than the algorithm in [25]. Indeed, $\nabla f(\mathbf{w}_{t-1}; z_{i_t}, z_{j_t})$ is an unbi-
154 ased estimate of $\nabla F_S(\mathbf{w}_{t-1})$ due to the independency between $\mathbf{w}_{t-1}$ and (i_t, j_t). Therefore, the
155 optimization error analysis of the algorithm in [25] is the same as the SGD for pointwise learning. As
156 a comparison, $\nabla f(\mathbf{w}_{t-1}; z_{i_t}, z_{i_{t-1}})$ is a biased estimate of $\nabla F_S(\mathbf{w}_{t-1})$ due to the coupling between
157 $\mathbf{w}_{t-1}$ and i_{t-1}. We introduce novel techniques to handle this coupling for both the optimization and
158 generalization analysis. Thirdly, we will soon see below that we provide generalization results for
159 nonsmooth, nonconvex losses and also use Algorithm 1 to develop novel differentially private pair-
160 wise learning algorithms while [25] focused on the smooth convex losses in the non-private setting.

4 Generalization Analysis

162 The aim for the generalization analysis of Algorithm 1 and Algorithm 2 is the same, i.e. to analyze
163 the excess generalization error $F(\mathbf{w}) - F(\mathbf{w}^*)$ of a model $\mathbf{w}$ measuring its relative behavior w.r.t.
164 the best model $\mathbf{w}^* = \arg\min_{\mathbf{w} \in \mathcal{W}} F(\mathbf{w})$.

165 For Algorithm 1 where the training data S with n datum is given beforehand, the excess general-
166 ization involves the generalization error and optimization error. Specifically, one has the following
167 error decomposition for $\bar{\mathbf{w}}_T$

$$\mathbb{E}\big[F(\bar{\mathbf{w}}_T)\big] - F(\mathbf{w}^*) = \mathbb{E}\big[F(\bar{\mathbf{w}}_T) - F_S(\bar{\mathbf{w}}_T)\big] + \mathbb{E}\big[F_S(\bar{\mathbf{w}}_T) - F_S(\mathbf{w}^*)\big]. \qquad (2)$$

168 Here, the expectation is taken w.r.t. the randomness of Algorithm 1, i.e., $\{i_t\}$ and the randomness of
169 data S which is i.i.d. from ρ on $\mathcal{Z}$. We refer to the first term $\mathbb{E}\big[F(\bar{\mathbf{w}}_T) - F_S(\bar{\mathbf{w}}_T)\big]$ as the general-
170 ization error and $\mathbb{E}\big[F_S(\bar{\mathbf{w}}_T) - F_S(\mathbf{w}^*)\big]$ as the optimization error. We will use algorithmic stability
171 to handle its generalization error in Subsection 4.2 for smooth and nonsmooth losses. The estima-
172 tion of the optimization error is given in Subsection 4.3 for both convex and nonconvex losses. For
173 Algorithm 2, there is no generalization error as the data $\{z_1, z_2, \ldots, z_T\}$ is arriving in a sequential
174 manner with T increasing all the time which does not involve the training data. The randomness of
175 Algorithm 2 is only from the i.i.d. data. Therefore, the optimization error in this setting is exactly
176 the excess generalization error $F(\widetilde{\mathbf{w}}_T) - F(\mathbf{w}^*)$ which is estimated in Subsection 4.3.

4.1 Excess Generalization Error

In this subsection, we present excess generalization error bounds of Algorithm 1 in terms of the sample size, iteration number and step size, which shows how to tune these parameters to get a model with good generalization. Our analysis requires the following assumptions.

Assumption. Let $f : \mathcal{W} \times \mathcal{Z} \times \mathcal{Z} \to \mathbb{R}^+$ and let $\|\cdot\|_2$ denote the Euclidean norm.

(A1) Assume, for any z, z' and $\mathbf{w} \in \mathcal{W}$, that $f(\cdot; z, z')$ is G-Lipschitz continuous, i.e. $|f(\mathbf{w}; z, z') - f(\mathbf{w}'; z, z')| \leq G\|\mathbf{w} - \mathbf{w}'\|_2$.

(A2) Assume, for any $z, z' \in \mathcal{Z}$, the map $\mathbf{w} \mapsto f(\mathbf{w}; z, z')$ is L-strongly smooth, i.e. $f(\mathbf{w}; z, z') - f(\mathbf{w}'; z, z') - \langle \nabla f(\mathbf{w}'; z, z'), \mathbf{w} - \mathbf{w}' \rangle \leq \frac{L}{2}\|\mathbf{w} - \mathbf{w}'\|_2^2$.

(A3) Assume, for any $z, z' \in \mathcal{Z}$, $f(\cdot; z, z')$ is α-strongly convex, i.e. $f(\mathbf{w}; z, z') - f(\mathbf{w}'; z, z') - \langle \nabla f(\mathbf{w}'; z, z'), \mathbf{w} - \mathbf{w}' \rangle \geq \frac{\alpha}{2}\|\mathbf{w} - \mathbf{w}'\|_2^2$. The case of $\alpha = 0$ is identical to the convexity.

(A4) Assume F_S satisfies the Polyak-Łojasiewicz (PL) condition with parameter $\mu > 0$, i.e., $2\mu\big(F_S(\mathbf{w}) - F_S(\mathbf{w}_S)\big) \leq \|\nabla F_S(\mathbf{w})\|_2^2$ for all $\mathbf{w} \in \mathcal{W}$.

The PL condition **(A4)** means that the suboptimality in terms of function values can be bounded by gradients [21]. Functions under the PL condition have found various applications including neural networks, matrix factorization, generalized linear models and robust regression (see, e.g., [21]).

We first study smooth and non-smooth problems for the convex case, and derive the excess generalization bounds of the order $\mathcal{O}(1/\sqrt{n})$ in both cases. We use the notation $B \asymp \tilde{B}$ if there exist constants $c_1, c_2 > 0$ such that $c_1\tilde{B} \leq B \leq c_2\tilde{B}$. The proofs are given in Section C.

Theorem 1 (Nonsmooth Problems). *Let $\mathbf{w}_{-1} = \mathbf{w}_0$ and $\{\mathbf{w}_t : t \in [T]\}$ be produced by Algorithm 1 with $\eta_t = \eta > 0$. Let $\bar{\mathbf{w}}_T = \sum_{t=1}^{T} \eta_t \mathbf{w}_{t-2} / \sum_{t=1}^{T} \eta_T$. Let (A1) and (A3) hold true with $\alpha = 0$. Then, we have*

$$\mathbb{E}_{S,\mathcal{A}}[F(\bar{\mathbf{w}}_T)] - F(\mathbf{w}^*) = \mathcal{O}\Big(\sqrt{T}\eta + \frac{T\eta}{n} + \frac{1 + T\eta^2}{T\eta}\Big). \tag{3}$$

Furthermore, selecting $T \asymp n^2$ and $\eta \asymp T^{-\frac{3}{4}}$ yields that $\mathbb{E}_{S,\mathcal{A}}[F(\bar{\mathbf{w}}_T)] - F(\mathbf{w}^*) = \mathcal{O}(1/\sqrt{n})$.

Theorem 2 (Smooth Problems). *Let (A1), (A2) and (A3) hold true with $\alpha = 0$. Let $\mathbf{w}_{-1} = \mathbf{w}_0$ and $\{\mathbf{w}_t : t \in [T]\}$ be produced by Algorithm 1 with $\eta_t = \eta \leq 2/L$. Let $\bar{\mathbf{w}}_T = \sum_{t=1}^{T} \eta_t \mathbf{w}_{t-2} / \sum_{t=1}^{T} \eta_T$. Then, there holds*

$$\mathbb{E}_{S,\mathcal{A}}[F(\bar{\mathbf{w}}_T)] - F(\mathbf{w}^*) = \mathcal{O}\Big(\frac{T\eta}{n} + \frac{1 + T\eta^2}{T\eta}\Big). \tag{4}$$

Furthermore, choosing $T \asymp n$ and $\eta \asymp T^{-\frac{1}{2}}$ implies that $\mathbb{E}_{S,\mathcal{A}}[F(\bar{\mathbf{w}}_T)] - F(\mathbf{w}^*) = \mathcal{O}(1/\sqrt{n})$.

Remark 3. Notice that the gradient complexity (i.e. the number of computing gradients) of Algorithm 1 is identical to the number of iterations T. The above results show, to get excess generalization bounds $\mathcal{O}(1/\sqrt{n})$, that Algorithm 1 requires a gradient complexity $\mathcal{O}(n^2)$ for nonsmooth problems, and $\mathcal{O}(n)$ for smooth problems. This matches the existing generalization analysis for pointwise learning [3, 16, 23]. In Appendix E, additional results are provided where we propose Algorithm 4 based on the iterative localization technique [12] in order to reduce the gradient complexity $\mathcal{O}(n^2)$ required in Theorem 1 to $\mathcal{O}(n)$ for nonsmooth problems.

Remark 4. As stated in the introduction, Algorithm 1 can be considered as a specific case of the classic pairwise learning algorithm [20] with a FIFO buffering set B_{t-1} of size $s = 1$. A key difficulty in the generalization analysis is that $\mathbf{w}_{t-1}$ depends on B_{t-1}, which rends the standard martingale analysis not applicable. Kar et al. [20] proposed to remove this coupling effect by considering $\sup_{\mathbf{w}} \big[f(\mathbf{w}; B_{t-1}) - F_S(\mathbf{w})\big]$, which is why they only derived the excess generalization error bound $\mathcal{O}(1/\sqrt{s})$. We introduce novel techniques to handle the coupling in both generalization analysis and optimization error analysis. For the generalization analysis, our strategy is to write the stability as a deterministic function of several indicator functions on whether we select the different point in neighboring datasets, and then finally consider the randomness of these indicator functions. This delay of considering expectation successfully decouples the coupling between $\mathbf{w}_{t-1}$ and B_{t-1}. For the optimization error analysis, our novelty is to observe that $f(\mathbf{w}_{t-1}; z_{i_t}, z_{i_{t-1}}) = f(\mathbf{w}_{t-2}; z_{i_t}, z_{i_{t-1}}) + \mathcal{O}(\eta_{t-1})$, which removes the decoupling since $\mathbf{w}_{t-2}$ is

now independent of both i_t and i_{t-1}. Since the additional term $\mathcal{O}(\eta_{t-1})$ here is a term of smaller magnitude, the coupling effect is removed without incurring any additional cost.

Finally, we study nonconvex pairwise learning under the PL condition. The proof is in Section C.

Theorem 3. *Let (A1), (A2) and (A4) hold true. Let $\alpha_0, B > 0$. Let $\mathbf{w}_{-1} = \mathbf{w}_0$ and $\{\mathbf{w}_j : j \in [t]\}$ be produced by Algorithm 1 with $\eta_j = 2/(\mu(j+1))$. If $\mathbb{E}_{i_{j+1}, i_{j+2}}\big[\|\nabla f(\mathbf{w}_j; z_{i_{j+1}}, z_{i_{j+2}})\|_2^2\big] \leq \alpha_0^2$ and $\sup_{z,z'} f(\mathbf{w}_j; z, z') \leq B$ for any j, then*

$$\mathbb{E}\big[F(\mathbf{w}_T)\big] - F(\mathbf{w}^*) = \mathcal{O}\Big(\frac{T^{\frac{2L}{2L+\mu}}}{n}\Big) + \mathcal{O}\big(1/(T\mu^2)\big).$$

Furthermore, choosing $T \asymp n^{\frac{2L+\mu}{4L+\mu}}\mu^{-\frac{4L+2\mu}{4L+\mu}}$ yields that $\mathbb{E}\big[F(\mathbf{w}_T)\big] - F(\mathbf{w}^*) = n^{-\frac{2L+\mu}{4L+\mu}}\mu^{-\frac{4L}{4L+\mu}}$.

Remark 5. As pointed out before, there is no generalization error for the OGD algorithm, i.e. Algorithm 2 as the i.i.d. data is given in a streaming manner and the iteration number equals the number of the available data (i.e. $t = n$). In this setting, the optimization error is identical to the excess generalization error, which will be estimated in Subsection 4.3.

4.2 Stability and Generalization Errors

We study generalization errors by algorithmic stability, which measures the sensitivity of the output of an algorithm w.r.t. the perturbation of the dataset. Below we give the definition of uniform argument stability. We say S, S' are neighboring datasets if they differ at most by a single example.

Definition 1. A (randomized) algorithm $\mathcal{A}$ for pairwise learning is called ε-uniformly argument stable if for all neighboring datasets $S, S' \in \mathcal{Z}^n$ we have $\mathbb{E}_{\mathcal{A}}[\|\mathcal{A}(S) - \mathcal{A}(S')\|_2] \leq \varepsilon$.

It is clear ε-uniform argument stability implies $G\varepsilon$-uniform stability i.e., $\sup_{z,z'} \mathbb{E}_{\mathcal{A}}[f(\mathcal{A}(S), z, z') - f(\mathcal{A}(S'), z, z')] \leq G\varepsilon$ for Lipschitz losses [7]. The connection between the uniform stability for pairwise learning and its generalization has been established in the literature [1, 31].

Lemma 1. *If an algorithm $\mathcal{A}$ for pairwise learning is ε-uniformly stable for some $\varepsilon > 0$, then we have $|\mathbb{E}_{S,\mathcal{A}}[F_S(\mathcal{A}(S)) - F(\mathcal{A}(S))]| \leq 2\varepsilon$.*

We develop uniform argument stability bound of Algorithm 1 and apply it together with Lemma 1 to establish the following generalization bounds. Theorem 4 handles nonsmooth problems, while Theorem 5 handles smooth problems. The detailed proofs for them can be found in Section A.

Theorem 4. *Let $\mathbf{w}_{-1} = \mathbf{w}_0$ and $\{\mathbf{w}_j : j \in [t]\}$ be produced by Algorithm 1 with $\eta_j = \eta$. Let (A1) and (A3) hold with $\alpha = 0$. Then, Algorithm 1 is $2\sqrt{e}G\eta\big(\sqrt{5t} + \frac{2t}{n}\big)$-uniformly argument stable and*

$$\mathbb{E}_{S,\mathcal{A}}[F(\bar{\mathbf{w}}_t) - F_S(\bar{\mathbf{w}}_t)] \leq 4\sqrt{e}G^2\eta\big(\sqrt{5t} + \frac{2t}{n}\big).$$

Theorem 5. *Let $\mathbf{w}_{-1} = \mathbf{w}_0$ and $\{\mathbf{w}_j : j \in [t]\}$ be produced by Algorithm 1 with $\eta_j = \eta \leq 2/L$. Let (A1), (A2) and (A3) hold true with $\alpha = 0$. Then, Algorithm 1 is $\frac{4G}{n}\sum_{j=1}^{t}\eta_j$-uniformly argument stable and the generalization error satisfies $\mathbb{E}_{S,\mathcal{A}}[F(\bar{\mathbf{w}}_t) - F_S(\bar{\mathbf{w}}_t)] \leq \frac{8G^2}{n}\sum_{j=1}^{t}\eta_j$.*

For Algorithm 2, there is no generalization error as the data $\{z_1, z_2, \ldots, z_T\}$ is assumed to arrive in a sequential manner with T increasing all the time which does not involve the training data.

4.3 Optimization Error

In this subsection, we establish the convergence rate, i.e. optimization error, of Algorithm 1 for convex, nonconvex and strongly convex problems. We consider both bounds in expectation and with high probability. Our analysis is based on the key observation $f(\mathbf{w}_{t-1}; z_{i_t}, z_{i_{t-1}}) = f(\mathbf{w}_{t-2}; z_{i_t}, z_{i_{t-1}}) + \mathcal{O}(\eta_{t-1})$. The proofs of results in this subsection are given in Section B.

Below we only present optimization error bounds for Algorithm 1 here in the offline (finite-sum) setting where the training data of size n, denoted by $S = \{z_1, \ldots, z_n\}$, is fixed, and the optimization error is measured by $F_S(\bar{\mathbf{w}}_t) - \inf_{\mathbf{w} \in \mathcal{W}} F_S(\mathbf{w})$. We emphasize that all our optimization error bounds hold true for Algorithm 2 in the online learning setting with exactly the same analysis where the

streaming data $\{z_1, \ldots, z_t, \ldots\}$ is assumed to be i.i.d according to the population distribution ρ, and the bounds for the optimization error in this case is given for the excess generalization error (excess population risk), i.e. $F(\widetilde{\mathbf{w}}_t) - \inf_{\mathbf{w} \in \mathcal{W}} F(\mathbf{w})$.

Theorem 6. *Let $\mathbf{w}_{-1} = \mathbf{w}_0$ and $\{\mathbf{w}_j : j \in [t]\}$ be produced by Algorithm 1. Let (A1) and (A3) hold true with $\alpha \geq 0$. Then, for any $\mathbf{w}$ independent of $\mathcal{A}$ we have the following convergence rates:*

(a) Assume f is convex, i.e. $\alpha = 0$. Then, we have

$$\mathbb{E}_{\mathcal{A}}[F_S(\bar{\mathbf{w}}_t)] - F_S(\mathbf{w}) \leq \frac{\|\mathbf{w}_0 - \mathbf{w}\|_2^2 + G^2 \sum_{j=1}^t (2\eta_j \eta_{j-1} + \eta_j^2)}{2 \sum_{j=1}^t \eta_j}. \tag{5}$$

(b) Let f be α-strongly convex with $\alpha > 0$ and $\eta_j = \frac{2}{\alpha(j+1)}$. Then, there holds $\mathbb{E}_{\mathcal{A}}[F_S(\bar{\mathbf{w}}_t)] - F_S(\mathbf{w}) = \mathcal{O}\big(G^2/(\alpha t)\big)$.

Remark 6. The above convergence rates match those in the pointwise learning [5]. Furthermore, if $\eta_j = \eta$, then Eq. (5) becomes $\mathbb{E}_{\mathcal{A}}[F_S(\bar{\mathbf{w}}_t)] - F_S(\mathbf{w}) = \mathcal{O}(1/(t\eta) + \eta)$ and one can choose $\eta \asymp 1/\sqrt{t}$ to get $\mathbb{E}_{\mathcal{A}}[F_S(\bar{\mathbf{w}}_t)] - F_S(\mathbf{w}) = \mathcal{O}(1/\sqrt{t})$. We can extend our convergence analysis to a more general update as $\mathbf{w}_t = \Pi_{\mathcal{W}}\big(\mathbf{w}_{t-1} - \frac{\eta_t}{s} \sum_{j=1}^s \nabla f(\mathbf{w}_{t-1}; z_{i_t}, z_{i_{t-j}})\big)$ for $s \in \mathbb{N}$. Indeed, one can use the observation $f(\mathbf{w}_{t-1}; z_{i_t}, z_{i_{t-s}}) = f(\mathbf{w}_{t-s-1}; z_{i_t}, z_{i_{t-s}}) + \mathcal{O}\big(\sum_{j=1}^s \eta_{t-j}\big)$ to derive the convergence rate $\mathcal{O}(\sqrt{s}/\sqrt{t})$.

Below we present high-probability bounds to understand the variation of the algorithm. We need to take conditional expectation of $f(\mathbf{w}_{2j-2}; z_{i_{2j}}, z_{i_{2j-1}})$ w.r.t. (i_{2j}, i_{2j-1}) to get $F_S(\mathbf{w}_{2j-2})$. However, there is a coupling between (i_{2j}, i_{2j-1}) and (i_{2j-1}, i_{2j-2}). Therefore, one can not directly apply concentration inequalities for martingales to handle $\sum_{j=1}^t \big(f(\mathbf{w}_{2j-2}; z_{i_{2j}}, z_{i_{2j-1}}) - F_S(\mathbf{w}_{2j-2})\big)$. We introduce a novel decoupling technique to handle this coupling. Note that the high-probability bounds match the bounds in expectation up to a constant factor.

Theorem 7. *Let $\mathbf{w}_{-1} = \mathbf{w}_0$ and $\{\mathbf{w}_j : j \in [t]\}$ be produced by Algorithm 1. Let (A1) and (A3) hold true with $\alpha \geq 0$ and $\sup_{\mathbf{w}} f(\mathbf{w}; z, z') \leq B$ for some $B > 0$. Let $\delta \in (0, 1)$.*

(a) Assume f is convex, i.e. $\alpha = 0$ and let $\bar{\mathbf{w}}_t = \sum_{j=1}^t \eta_j \mathbf{w}_{j-2} / \sum_{j=1}^t \eta_j$. Then, for any $\mathbf{w} \in \mathcal{W}$, with probability at least $1 - \delta$ the following inequality holds

$$F_S(\bar{\mathbf{w}}_t) - F_S(\mathbf{w}) \leq \frac{1}{\sum_{j=1}^t \eta_j} \Big(2B \Big(2 \sum_{j=1}^t \eta_j^2 \log(2/\delta) \Big)^{\frac{1}{2}} + \frac{1}{2} \|\mathbf{w}_1 - \mathbf{w}\|_2^2 + G^2 \sum_{j=1}^t \Big(\eta_{j-1}\eta_j + \frac{\eta_j^2}{2} \Big) \Big).$$

(b) Assume f is α-strongly convex with $\alpha > 0$ and $\eta_j = \frac{2}{\alpha(j+1)}$. Let $\bar{\mathbf{w}}_t = \sum_{j=1}^t j\mathbf{w}_{j-2} / \sum_{j=1}^t j$. Then, with probability at least $1 - \delta$, we have $F_S(\bar{\mathbf{w}}_t) - F_S(\mathbf{w}) = \mathcal{O}\big(G^2 \log(1/\delta)/(\alpha t)\big)$.

Finally, we study the convergence of Algorithm 1 associated with nonconvex functions. We first consider general smooth problems. Since we cannot find a global minimum in this setting, we measure the convergence rate in terms of gradient norms [15]. The following theorem establishes the convergence rate $\mathcal{O}(1/\sqrt{t})$ for $\min_{j=1,\ldots,t} \mathbb{E}_{\mathcal{A}}[\|\nabla F_S(\mathbf{w}_j)\|_2^2]$.

Theorem 8. *Let $\mathbf{w}_{-1} = \mathbf{w}_0$ and $\{\mathbf{w}_j : j \in [t]\}$ be produced by Algorithm 1 with $\eta_j = \eta \leq 1/(2\sqrt{L})$. Let (A2) hold true and $\mathbb{E}_{i_{j+1}, i_{j+2}}\big[\|\nabla f(\mathbf{w}_j; z_{i_{j+1}}, z_{i_{j+2}})\|_2^2\big] \leq \alpha_0^2$ for some α_0 and any j. Then,*

$$\frac{1}{t} \sum_{j=1}^t \mathbb{E}_{\mathcal{A}}\big[\|\nabla F_S(\mathbf{w}_{j-2})\|_2^2\big] \leq \frac{F_S(\mathbf{w}_0)}{t\eta} + 8L\eta\alpha_0^2.$$

Furthermore, choosing $\eta \asymp 1/\sqrt{t}$ implies that $\frac{1}{t} \sum_{j=1}^t \mathbb{E}_{\mathcal{A}}\big[\|\nabla F_S(\mathbf{w}_{j-2})\|_2^2\big] = \mathcal{O}(1/\sqrt{t})$.

We now turn to nonconvex problems under a PL condition. Theorem 9 gives convergence rates of the order $\mathcal{O}(1/t)$, which match the existing results for standard SGD in pointwise learning [21].

Theorem 9. *Assume (A2) and (A4) hold true and $\mathbb{E}_{i_{j+1}, i_{j+2}}\big[\|\nabla f(\mathbf{w}_j; z_{i_{j+1}}, z_{i_{j+2}})\|_2^2\big] \leq \alpha_0^2$ for some α_0 and any j. Let $\mathbf{w}_{-1} = \mathbf{w}_0$ and $\{\mathbf{w}_j : j \in [t]\}$ be produced by Algorithm 1 with $\eta_j = 2/(\mu(j+1))$. Then*

$$\mathbb{E}_{\mathcal{A}}[F_S(\mathbf{w}_t) - F_S(\mathbf{w}_S)] \leq \frac{32L\alpha_0^2}{\mu^2} \Big(\frac{1}{t+1} + \frac{\log(et)}{\mu t(t+1)} \Big).$$

Algorithm 3 Differentially Private Localized SGD for Pairwise Learning

---

1: **Inputs:** Dataset $S = \{z_i : i \in [n]\}$, parameters $\epsilon, \delta > 0$, and learning rate η, initial point $\mathbf{w}_0$
2: Set $K = \lceil \log_2 n \rceil$ and divide S into K disjoint subsets $\{S_1, \cdots, S_K\}$ where $|S_k| = n_k = 2^{-k} n$.
3: **for** $k = 1$ to K **do**
4:     Set $\eta_k = 4^{-k} \eta$
5:     Compute $\bar{\mathbf{w}}_k$ by Algorithm 1 based on S_k and initiated at $\mathbf{w}_{k-1}$ for $\lceil n_k \log(4/\delta) \rceil$ steps.
6:     Set $\mathbf{w}_k = \bar{\mathbf{w}}_k + \mathbf{u}_k$ where $\mathbf{u}_k \sim \mathcal{N}(0, \sigma_k^2 I_d)$ with $\sigma_k = 12 G \eta_k \log(4/\delta) \sqrt{2 \log(2.5/\delta)}/\epsilon$.
7: **Outputs:** $\mathbf{w}_K$

---

5 Application: Differentially Private SGD for Pairwise Learning

We now use Algorithm 1 and our stability analysis (i.e. Theorem 5) to develop a differentially private algorithm for pairwise learning. Let us start with the definition of differential privacy [11].

Definition 2. A (randomized) algorithm $\mathcal{A}$ is called (ϵ, δ)-differentially private (DP) if, for all neighboring datasets S, S' and for all events O in the output space of $\mathcal{A}$, one has $\mathbb{P}[\mathcal{A}(S) \in O] \leq e^\epsilon \mathbb{P}[\mathcal{A}(S') \in O] + \delta$.

Our proposed DP algorithm for pairwise learning is described in Algorithm 3 which is inspired by the iterative localization technique [12] for pointwise learning. The privacy and utility guarantees are given by the following theorem. Here D denotes the diameter of $\mathcal{W}$.

Theorem 10. *Let (A1), (A2), and (A3) hold true with $\sigma = 0$. Let $\{\mathbf{w}_k : k \in [K]\}$ be produced by Algorithm 3 with $\eta = \frac{D}{G} \min\{\frac{\log(4/\delta)}{\sqrt{n}}, \frac{\epsilon}{12 \log(4/\delta)\sqrt{2d \log(2.5/\delta)}}\} \leq \frac{2}{L}$. Then, Algorithm 3 satisfies (ϵ, δ)-DP and, with gradient complexity $\mathcal{O}(n \log(1/\delta))$, we have the utility bound that*

$$\mathbb{E}[F(\mathbf{w}_K) - F(\mathbf{w}^*)] = \mathcal{O}\Big(GD\Big(\frac{1}{\sqrt{n}} + \frac{\sqrt{d} \log^{\frac{3}{2}}(1/\delta)}{\epsilon n}\Big)\Big).$$

The main difference from the pointwise setting in [12] is that Algorithm 3 involves the coupling dependency between $\{i_t, i_{t-1}\}$ at time t in Algorithm 1 and $\{i_{t-1}, i_{t-2}\}$ at time $t-1$, which renders the direct application of the standard concentration inequalities infeasible. We propose a novel decomposition to circumvent this hurdle (see more detailed proof for Theorem 10 in Appendix D).

Remark 7. The above bound matches the lower bound given in [2] for (ϵ, δ)-differentially private pointwise learning up to a $\log(1/\delta)$ term. Our utility bound improves over the previous work [19] which has the bound $\mathcal{O}(\sqrt{d \log(1/\delta)} \log(n/\delta)/(\sqrt{n}\epsilon))$. During the preparation of this work, we notice a very recent paper [36] also studied the private version of pairwise algorithm by using the localization technique. Their algorithm establishes the optimal rate $\mathcal{O}(1/\sqrt{n} + \sqrt{d \log(1/\delta)}/(\epsilon n))$ which, however, needs an expensive gradient complexity $\mathcal{O}(n^3 \log(1/\delta))$. As a comparison, we achieve nearly optimal utility bound with linear gradient complexity $\mathcal{O}(n \log(1/\delta))$.

Remark 8. In Appendix F, we further remove the smoothness assumption (A2) required in Theorem 10 and propose a private algorithm (stated as Algorithm 5 there) that achieves the optimal rate $\mathcal{O}\big((1/\sqrt{n} + \sqrt{d \log(1/\delta)}/(\epsilon n))\big)$ with gradient complexity $\mathcal{O}(n^2 \log(1/\delta))$. Such bound improves over the previous known results with nonsmooth losses [37] where the utility bound was $\mathcal{O}(\sqrt{d \log(1/\delta)} \log(n/\delta)/(\sqrt{n}\epsilon))$.

6 Experimental Validation

We now report some preliminary experiments on AUC maximization with $f(\mathbf{w}; (x, y), (x', y')) = \ell(\mathbf{w}^\top(x - x')) \mathbb{I}_{[y=1 \wedge y'=-1]}$ where ℓ is a surrogate loss function, e.g., the hinge loss $\ell(t) = (1 - t)_+$.

The purpose of our first experiment is to compare our algorithm, i.e. Algorithm 1, against four existing algorithms for pairwise learning in terms of generalization and CPU running time on several datasets available from the LIBSVM website [9]. These algorithms are: 1) OLP [20] uses a buffer B_t updated by a variant of Reservoir sampling with replacement where the buffer size is chosen to be 200 in order to guarantee the maximum AUC score as indicated in [20]; 2) OAM$_{gra}$ [42] is

Algorithm	diabetes	german	ijcnn1	letter	mnist	usps
Ours	$.831 \pm .030$	$.793 \pm .021$	$.934 \pm .002$	$.810 \pm .007$	$.932 \pm .001$	$.926 \pm .006$
SGD_{pair} [25]	$.830 \pm .028$	$.794 \pm .023$	$.934 \pm .003$	$.811 \pm .008$	$.932 \pm .001$	$.925 \pm .006$
OLP [20]	$.825 \pm .028$	$.787 \pm .028$	$.916 \pm .003$	$.808 \pm .010$	$.927 \pm .003$	$.917 \pm .006$
OAM_{gra} [42]	$.828 \pm .026$	$.785 \pm .029$	$.930 \pm .003$	$.806 \pm .008$	$.898 \pm .002$	$.916 \pm .005$
SPAUC [24]	$.828 \pm .031$	$.799 \pm .026$	$.932 \pm .002$	$.809 \pm .008$	$.927 \pm .002$	$.923 \pm .005$

Table 1: Average AUC score $\pm$ standard deviation across multiple datasets

tailored for AUC maximization with the hinge loss which uses buffers by Reservoir sampling. The buffer size is set to be 100 for both positive and negative buffers as suggested in that paper; 3) SGD_{pair} [25] randomly pick a pair from $\binom{n}{2}$ pairs by uniform distribution; 4) SPAUC [24], where AUC maximization problem with the least square loss was reformulated as stochastic saddle point (min-max) problem. Note that SPAUC and OAM_{gra} can only apply to AUC maximization problem with the least square loss and hinge loss, respectively.

To validate the generalization ability, the surrogate loss for Algorithm 1, SGD_{pair} and OLP is chosen to be the hinge loss. Average AUC scores of different algorithms are listed in Table 1 where we can see that our algorithm yields competitive generalization performance with OAM and OLP using a large buffering set. Detailed experimental setup, data statistics and more results such as comparison with OLP and OAM with the size of the buffering set $s = 1$ are listed in Appendix G.

Figure 1: CPU running time (log scale) versus the AUC score

To fairly compare the CPU running time, we apply the following uniform setting across all algorithms: 1) $\mathcal{W}$ is an ℓ_2 ball with the same diameter; 2) the step sizes $\eta_t = \eta$ which is tuned by cross validation. We report the results in Figure 1 for the hinge loss. We can see that CPU running time for our algorithm and SGD_{pair} are similar while OLP and OAM needs more time to converge. The possible reason behind this is that they have a high gradient complexity $\mathcal{O}(s)$ at each iteration while ours is $\mathcal{O}(1)$. More results on comparison for the least square loss and for differentially private algorithms are given in Appendix G.

7 Conclusion

In this paper, we propose simple stochastic and online gradient descent algorithms for pairwise learning. The key idea is to build a gradient estimator by pairing the current instance with the previous instance, which enjoys favorable computation and storage complexity. We leverage the lens of algorithmic stability to study its generalization and apply tools in optimization theory to study its convergence rates for various problems including convex/nonconvex and smooth/nonsmooth settings. We also use our algorithms and stability analysis to develop a new DP algorithm for pairwise learning with differential privacy constraints which significantly improves the existing results. The main difference from pointwise learning in the analysis is the coupling between models and previous instances, which is handled by introducing novel decoupling techniques.

References

[1] S. Agarwal and P. Niyogi. Generalization bounds for ranking algorithms via algorithmic stability. *Journal of Machine Learning Research*, 10(Feb):441–474, 2009.

[2] R. Bassily, A. Smith, and A. Thakurta. Private empirical risk minimization: Efficient algorithms and tight error bounds. In *2014 IEEE 55th Annual Symposium on Foundations of Computer Science*, pages 464–473. IEEE, 2014.

[3] R. Bassily, V. Feldman, C. Guzmán, and K. Talwar. Stability of stochastic gradient descent on nonsmooth convex losses. *Advances in Neural Information Processing Systems*, 33, 2020.

[4] A. Bellet, A. Habrard, and M. Sebban. A survey on metric learning for feature vectors and structured data. *arXiv preprint arXiv:1306.6709*, 2013.

[5] L. Bottou, F. E. Curtis, and J. Nocedal. Optimization methods for large-scale machine learning. *SIAM Review*, 60(2):223–311, 2018.

[6] S. Boucheron, G. Lugosi, and P. Massart. *Concentration Inequalities: A Nonasymptotic Theory of Independence*. Oxford university press, 2013.

[7] O. Bousquet and A. Elisseeff. Stability and generalization. *Journal of machine learning research*, 2(Mar):499–526, 2002.

[8] N. Cesa-Bianchi, A. Conconi, and C. Gentile. On the generalization ability of on-line learning algorithms. *IEEE Transactions on Information Theory*, 50(9):2050–2057, 2004.

[9] C.-C. Chang and C.-J. Lin. LIBSVM: A library for support vector machines. *ACM Transactions on Intelligent Systems and Technology*, 2:27:1–27:27, 2011. Software available at http://www.csie.ntu.edu.tw/~cjlin/libsvm.

[10] S. Clémençon, G. Lugosi, and N. Vayatis. Ranking and empirical minimization of U-statistics. *The Annals of Statistics*, pages 844–874, 2008.

[11] C. Dwork, A. Roth, et al. The algorithmic foundations of differential privacy. *Foundations and Trends® in Theoretical Computer Science*, 9(3–4):211–407, 2014.

[12] V. Feldman, T. Koren, and K. Talwar. Private stochastic convex optimization: optimal rates in linear time. In *Proceedings of the 52nd Annual ACM SIGACT Symposium on Theory of Computing*, pages 439–449, 2020.

[13] D. J. Foster, A. Sekhari, and K. Sridharan. Uniform convergence of gradients for non-convex learning and optimization. In *Advances in Neural Information Processing Systems*, pages 8759–8770, 2018.

[14] W. Gao, R. Jin, S. Zhu, and Z.-H. Zhou. One-pass auc optimization. In *International Conference on Machine Learning*, pages 906–914, 2013.

[15] S. Ghadimi and G. Lan. Stochastic first-and zeroth-order methods for nonconvex stochastic programming. *SIAM Journal on Optimization*, 23(4):2341–2368, 2013.

[16] M. Hardt, B. Recht, and Y. Singer. Train faster, generalize better: Stability of stochastic gradient descent. In *International Conference on Machine Learning*, pages 1225–1234, 2016.

[17] E. Hazan. Introduction to online convex optimization. *Foundations and Trends® in Optimization*, 2(3-4):157–325, 2016.

[18] T. Hu, J. Fan, Q. Wu, and D.-X. Zhou. Learning theory approach to minimum error entropy criterion. *Journal of Machine Learning Research*, 14(2), 2013.

[19] M. Huai, D. Wang, C. Miao, J. Xu, and A. Zhang. Pairwise learning with differential privacy guarantees. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 694–701, 2020.

[20] P. Kar, B. Sriperumbudur, P. Jain, and H. Karnick. On the generalization ability of online learning algorithms for pairwise loss functions. In *International Conference on Machine Learning*, pages 441–449, 2013.

[21] H. Karimi, J. Nutini, and M. Schmidt. Linear convergence of gradient and proximal-gradient methods under the polyak-łojasiewicz condition. In *European Conference on Machine Learning*, pages 795–811, 2016.

[22] B. Kulis et al. Metric learning: A survey. *Foundations and Trends® in Machine Learning*, 5 (4):287–364, 2013.

[23] Y. Lei and Y. Ying. Fine-grained analysis of stability and generalization for stochastic gradient descent. In *International Conference on Machine Learning*, pages 5809–5819, 2020.

[24] Y. Lei and Y. Ying. Stochastic proximal auc maximization. *Journal of Machine Learning Research*, 22(61):1–45, 2021.

[25] Y. Lei, A. Ledent, and M. Kloft. Sharper generalization bounds for pairwise learning. In *Advances in Neural Information Processing Systems*, volume 33, pages 21236–21246, 2020.

[26] M. Liu, X. Zhang, Z. Chen, X. Wang, and T. Yang. Fast stochastic auc maximization with o (1/n)-convergence rate. In *International Conference on Machine Learning*, pages 3195–3203, 2018.

[27] M. Liu, Z. Yuan, Y. Ying, and T. Yang. Stochastic auc maximization with deep neural networks. In *International Conference on Learning Representations*, 2020.

[28] F. Orabona. A modern introduction to online learning. *arXiv preprint arXiv:1912.13213*, 2019.

[29] S. Shalev-Shwartz. Online learning and online convex optimization. *Foundations and Trends® in Machine Learning*, 4(2):107–194, 2012.

[30] S. Shalev-Shwartz, O. Shamir, N. Srebro, and K. Sridharan. Stochastic convex optimization. In *COLT*, 2009.

[31] W. Shen, Z. Yang, Y. Ying, and X. Yuan. Stability and optimization error of stochastic gradient descent for pairwise learning. *Analysis and Applications*, 18(05):887–927, 2020.

[32] Y. Wang, R. Khardon, D. Pechyony, and R. Jones. Generalization bounds for online learning algorithms with pairwise loss functions. In *Conference on Learning Theory*, volume 23, pages 13–1, 2012.

[33] Y. Wang, R. Khardon, D. Pechyony, and R. Jones. Online learning with pairwise loss functions. *arXiv preprint arXiv:1301.5332*, 2013.

[34] K. Q. Weinberger and L. K. Saul. Distance metric learning for large margin nearest neighbor classification. *Journal of Machine Learning Research*, 10:207–244, 2009.

[35] E. P. Xing, M. I. Jordan, S. J. Russell, and A. Y. Ng. Distance metric learning with application to clustering with side-information. In *Advances in Neural Information Processing Systems*, 2003.

[36] Z. Xue, S. Yang, M. Huai, and D. Wang. Differentially private pairwise learning revisited, 2021. URL https://shao3wangdi.github.io/papers/IJCAI2021_pairwise.pdf.

[37] Z. Yang, Y. Lei, S. Lyu, and Y. Ying. Stability and differential privacy of stochastic gradient descent for pairwise learning with non-smooth loss. In *International Conference on Artificial Intelligence and Statistics*, pages 2026–2034. PMLR, 2021.

[38] Y. Ying and P. Li. Distance metric learning with eigenvalue optimization. *Journal of Machine Learning Research*, 13:1–26, 2012.

[39] Y. Ying and D.-X. Zhou. Online regularized classification algorithms. *IEEE Transactions on Information Theory*, 52(11):4775–4788, 2006.

[40] Y. Ying, L. Wen, and S. Lyu. Stochastic online AUC maximization. In *Advances in Neural Information Processing Systems*, pages 451–459, 2016.

[41] T. Zhang. Data dependent concentration bounds for sequential prediction algorithms. In *Conference on Learning Theory*, pages 173–187, 2005.

[42] P. Zhao, S. C. Hoi, R. Jin, and T. Yang. Online AUC maximization. In *International Conference on Machine Learning*, pages 233–240, 2011.