Scale-invariant Bayesian Neural Networks with Connectivity Tangent Kernel

Abstract

A critical component of studying loss landscapes of neural networks is identifying generalizations and preventing overconfident predictions. In this context, flatness, which measures the perturbation resilience of pre-trained parameters for loss values, is widely recognized as an essential predictor of generalization. In formal terms, the concept of flatness has been expressed as a PAC-Bayes bound in general. It has been observed, however, that flatness (and the corresponding generalization bounds) can change arbitrarily depending on the scale of the model parameters. Despite previous attempts to solve this issue, generalization bounds are still vulnerable to function-preserving scaling transformations or are limited to impractical network structures. In this paper, we present new PAC-Bayes prior and posterior distributions invariant to scaling transformations through the *decomposition between scale and connectivity of perturbations*. In this way, the resulting generalization bound can describe the generalizability of a broader class of networks with more practical transformations, such as weight decay with batch normalization. Moreover, we show that scale-dependency issues of flatness adversely affects the uncertainty calibration of Laplace Approximation and propose a solution using our invariant posterior. With our posterior, we demonstrate effective flatness and calibration measures with low complexity while remaining invariant to practical parameter transformations, demonstrating its validity as a prediction of neural network generalization.

1 Introduction

Despite the huge success of neural networks (NNs), understanding their generalization mechanism in real-world contexts still faces several obstacles (Kendall & Gal, 2017; Ovadia et al., 2019). In particular, it is widely acknowledged but not well explained why NNs naturally generalize well and do not suffer from overfitting (Neyshabur et al., 2015b; Zhang et al., 2017; Arora et al., 2018). Recent studies on the loss landscapes of NNs seek to overcome such issues. Specifically, Hochreiter & Schmidhuber (1995) proposed a theory of flat minima (FM) which states that loss stability for parameter perturbations positively correlates with network generalizability, as empirically demonstrated by Jiang et al. (2020).

However, the FM hypothesis still has limitations, as investigated in Dinh et al. (2017); Li et al. (2018). According to Dinh et al. (2017), rescaling two successive layers can arbitrarily degrade a flatness measure while maintaining the generalizability of NNs. Meanwhile, Li et al. (2018) argued that weight decay (WD) leads to a contradiction of the FM hypothesis in practice: Although WD sharpens pre-trained NNs (i.e., decreased loss resilience), it generally improves the generalization. In short, they suggest that transformations on network parameters (e.g., re-scaling layers and WD) may lead to contradictions to the FM hypothesis. A thorough discussion on this can be found in Appendix E.

To resolve this contradiction, we investigate PAC-Bayesian prior and posterior distributions to derive a new scale-invariant generalization bound. As a result, our bound guarantees invariance for a general class of function-preserving scale transformations with a broad class of networks. Specifically, our bound is more general than existing works (Tsuzuku et al., 2020; Kwon et al., 2021), both in terms of transformations (e.g., activation-wise rescaling (Neyshabur et al., 2015a) and WD with BN (Zhang et al., 2019)) that guarantee invariance and in terms of NN architectures (e.g., ResNet (He et al., 2016) and Transformer (Vaswani et al., 2017)). Therefore, our novel generalization bound ensures no FM

contradiction for the first time, which should not occur in practical NNs, including a normalization layer such as batch normalization (BN).

Our newly defined generalization bound is derived from scale invariances of prior and posterior distributions, guaranteeing not only its scale invariance but also the scale invariance of its substance, the Kullback-Leibler (KL) divergence-based kernel. We call this kernel an empirical Connectivity Tangent Kernel (CTK), as a modification of empirical Neural Tangent Kernel (Jacot et al., 2018) with the scale-invariance property. Moreover, we define a new sharpness metric as the trace of CTK, named **Connectivity Sharpness (CS)**. We show via empirical studies that CS predicts NN generalization performance better than existing sharpness measures (Liang et al., 2019; Neyshabur et al., 2017).

In Bayesian NN regimes, we connect the contradictions of the FM hypothesis with the issue of amplifying predictive uncertainty. Then, we alleviate this issue by using a Bayesian NN based on the posterior distribution of our PAC-Bayesian analysis. We name this Bayesian NN as **Connectivity Laplace (CL)**, as it can be seen as a variation of Laplace Approximation (LA; MacKay (1992)) using a different Jacobian. Specifically, we demonstrate the major pitfalls of WD with BN in LA and show how to remedy this issue using CL.[1] We summarize our contributions as follows:

- Our novel PAC-Bayes generalization bound guarantees invariance for general function-preserving scale transformations with a broad class of networks (Sec. 2.2 and 2.3). We empirically verify this bound gives non-vacuous results for ResNet (He et al., 2016) with 11M parameters (Sec. 2.4).

- Based on our bound, we propose a low-complexity sharpness metric CS (Sec. 2.5), which empirically shows a stronger correlation with generalization error than other metrics (Sec. 4.1).

- To prevent overconfident predictions, we show how our scale-invariant Bayesian NN can be used to solve pitfalls of WD with BNs, proving its practicality (Sec. 3 and 4.2).

2 PAC-BAYES BOUND WITH SCALE-INVARIANCE

In this section, we propose a data-dependent PAC-Bayes generalization bound without scale-dependency issues. To accomplish this, we introduce our setup in Sec. 2.1, construct the scale-invariant PAC-Bayes prior and posterior in Sec. 2.2, and present the detailed bound in Sec. 2.3. Then, we demonstrate the effectiveness of this bound for ResNet-18 with CIFAR in Sec. 2.4. An efficient proxy of this bound without complex hyper-parameter optimization is provided in Sec. 2.5.

2.1 BACKGROUND

Setup and Definitions. We consider a Neural Network (NN), $f(\cdot, \cdot) : \mathbb{R}^D \times \mathbb{R}^P \to \mathbb{R}^K$, given input $x \in \mathbb{R}^D$ and network parameter $\theta \in \mathbb{R}^P$. Hereafter, for simplicity, we consider vectors as single-column matrices unless otherwise stated. We use the output of NN $f(x, \theta)$ as a prediction for input x. Let $\mathcal{S} := \{(x_n, y_n)\}_{n=1}^N$ denote the independently and identically distributed (i.i.d.) training data drawn from true data distribution $\mathcal{D}$, where $x_n \in \mathbb{R}^D$ and $y_n \in \mathbb{R}^K$ are input and output representations of n-th training instance, respectively. For simplicity, we denote concatenated input and output of all instances as $\mathcal{X} \in \mathbb{R}^{ND}$ and $\mathcal{Y} \in \mathbb{R}^{NK}$, respectively, and $f(\mathcal{X}, \theta) \in \mathbb{R}^{NK}$ as a concatenation of $\{f(x_n, \theta)\}_{n=1}^N$. Given a prior distribution of network parameters $p(\theta)$ and a likelihood function $p(\mathcal{S}|\theta) := \prod_{n=1}^N p(y_n|f(x_n, \theta))$, Bayesian inference defines posterior distribution of network parameter θ as $p(\theta|\mathcal{S}) := \frac{1}{Z(\mathcal{S})} \exp(-\mathcal{L}(\mathcal{S}, \theta))$, where $\mathcal{L}(\mathcal{S}, \theta) := -\log p(\theta) - \sum_{n=1}^N \log p(y_n|x_n, \theta)$ is training loss and $Z(\mathcal{S}) := \int p(\theta)p(\mathcal{S}|\theta)d\theta$ is the normalizing factor. For example, the likelihood function for a regression task will be Gaussian: $p(y|x, \theta) = \mathcal{N}(y|f(x, \theta), \sigma^2 \mathbf{I}_k)$ where σ is (homoscedastic) observation noise scale. For a classification task, we treat it as a one-hot regression task following Lee et al. (2019a); He et al. (2020). While we adopt this modification for theoretical tractability, Hui & Belkin (2021) showed this modification offers reasonable performance competitive to the cross-entropy loss. Details on this modification are given in Appendix C.

Laplace Approximation. In general, the exact computation for the Bayesian posterior of a network parameter is intractable. The Laplace Approximation (LA; MacKay (1992)) is proposed to approximate the posterior distribution with a Gaussian distribution defined as $p_{\text{LA}}(\psi|\mathcal{S}) \sim$

---

[1]https://github.com/to-be-updated

$\mathcal{N}(\psi|\theta^*, (\nabla_\theta^2 \mathcal{L}(\mathcal{S}, \theta^*))^{-1})$ where $\theta^* \in \mathbb{R}^P$ is a pre-trained parameter with training loss and $\nabla_\theta^2 \mathcal{L}(\mathcal{S}, \theta^*) \in \mathbb{R}^{P \times P}$ is a Hessian matrix of loss function w.r.t. parameter at θ^*.

Recent works on LA replace the Hessian matrix with (Generalized) Gauss-Newton matrix to make computation easier (Khan et al., 2019; Immer et al., 2021). With this approximation, the LA posterior of the regression problem can be represented as

$$p_{\mathrm{LA}}(\psi|\mathcal{S}) \sim \mathcal{N}(\psi|\theta^*, (\underbrace{\mathbf{I}_P/\alpha^2}_{\text{Damping}} + \underbrace{\mathbf{J}_\theta^\top \mathbf{J}_\theta/\sigma^2}_{\text{Curvature}})^{-1}) \tag{1}$$

where $\alpha, \sigma > 0$, $\mathbf{I}_P \in \mathbb{R}^{P \times P}$ is a identity matrix, and $\mathbf{J}_\theta \in \mathbb{R}^{NK \times P}$ is a concatenation of $\mathbf{J}_\theta(x, \theta^*) \in \mathbb{R}^{K \times P}$ (Jacobian of f w.r.t. θ at input x and parameter θ^*) along training input $\mathcal{X}$. Inference with LA requires a further sub-curvature approximation for modern NN architectures (e.g., ResNet (He et al., 2016) and Transformer (Vaswani et al., 2017)) because of the prohibitively large covariance matrix. This approximation includes diagonal, Kronecker-factored approximate curvature (KFAC), last-layer, and subnetwork approximation (Ritter et al., 2018; Kristiadi et al., 2020; Daxberger et al., 2021b). Meanwhile, it is well known that proper selection of prior scale α is needed to balance the dilemma between overconfidence and underfitting in LA.

PAC-Bayes bound with data-dependent prior. We consider a PAC-Bayes generalization error bound of classification task used in McAllester (1999); Perez-Ortiz et al. (2021) (especially equation (7) of Perez-Ortiz et al. (2021)). Let $\mathbb{P}$ be a PAC-Bayes prior distribution over $\mathbb{R}^P$ independent of training dataset $\mathcal{S}$, and $\mathrm{err}(\cdot, \cdot) : \mathbb{R}^{K \times K} \to [0, 1]$ be an error function defined separately from the loss function. For any constant $\delta \in (0, 1]$ and $\lambda > 0$, and any PAC-Bayes posterior distribution $\mathbb{Q}$ over $\mathbb{R}^P$, the following holds with probability at least $1 - \delta$: $\mathrm{err}_{\mathcal{D}}(\mathbb{Q}) \le \mathrm{err}_{\mathcal{S}}(\mathbb{Q}) + \sqrt{\frac{\mathrm{KL}[\mathbb{Q}\|\mathbb{P}] + \log(2\sqrt{N}/\delta)}{2N}}$ where $\mathrm{err}_{\mathcal{D}}(\mathbb{Q}) := \mathbb{E}_{(x,y) \sim \mathcal{D}, \theta \sim \mathbb{Q}}[\mathrm{err}(f(x, \theta), y)]$, $\mathrm{err}_{\mathcal{S}}(\mathbb{Q}) := \mathbb{E}_{(x,y) \sim \mathcal{S}, \theta \sim \mathbb{Q}}[\mathrm{err}(f(x, \theta), y)]$, and N denotes the cardinality of $\mathcal{S}$. That is, $\mathrm{err}_{\mathcal{D}}(\mathbb{Q})$ and $\mathrm{err}_{\mathcal{S}}(\mathbb{Q})$ are generalization error and empirical error, respectively. The only restriction on $\mathbb{P}$ here is that it cannot depend on the dataset S.

Following the recent discussion in Perez-Ortiz et al. (2021), one can construct data-dependent PAC-Bayes bounds by (i) randomly **partitioning** dataset $\mathcal{S}$ into $\mathcal{S}_{\mathbb{Q}}$ and $\mathcal{S}_{\mathbb{P}}$ so that they are independent, (ii) **pre-training** a PAC-Bayes prior distribution $\mathbb{P}_{\mathcal{D}}$ only dependent of $\mathcal{S}_{\mathbb{P}}$ (i.e., $\mathbb{P}_{\mathcal{D}}$ belongs to a PAC-Bayes prior due to the independence of $\mathcal{S}_{\mathbb{Q}}$), (iii) **fine-tuning** a PAC-Bayes posterior distribution $\mathbb{Q}$ dependent of entire dataset $\mathcal{S}$, and (iv) computing empirical error $\mathrm{err}_{\mathcal{S}_{\mathbb{Q}}}(\mathbb{Q})$ with target subset $\mathcal{S}_{\mathbb{Q}}$ (not entire dataset $\mathcal{S}$). In summary, one can modify the aforementioned original PAC-Bayes bound through a data-dependent prior $\mathbb{P}_{\mathcal{D}}$ as

$$\mathrm{err}_{\mathcal{D}}(\mathbb{Q}) \le \mathrm{err}_{\mathcal{S}_{\mathbb{Q}}}(\mathbb{Q}) + \sqrt{\frac{\mathrm{KL}[\mathbb{Q}\|\mathbb{P}_{\mathcal{D}}] + \log(2\sqrt{N_{\mathbb{Q}}}/\delta)}{2N_{\mathbb{Q}}}} \tag{2}$$

where $N_{\mathbb{Q}}$ is the cardinality of $\mathcal{S}_{\mathbb{Q}}$. We denote sets of input and output of partitioned datasets $(\mathcal{S}_{\mathbb{P}}, \mathcal{S}_{\mathbb{Q}})$ by $\mathcal{X}_{\mathbb{P}}, \mathcal{Y}_{\mathbb{P}}, \mathcal{X}_{\mathbb{Q}}, \mathcal{Y}_{\mathbb{Q}}$ for simplicity.

2.2 SCALE-INVARIANT PRIOR AND POSTERIOR FROM LINEARIZATION W.R.T. CONNECTIVITY

Our goal is to construct scale-invariant $\mathbb{P}_{\mathcal{D}}$ and $\mathbb{Q}$. To this end, we first assume a pre-trained parameter $\theta^* \in \mathbb{R}^P$ with the prior dataset $\mathcal{S}_{\mathbb{P}}$. This parameter can be attained with standard NN optimization procedures (e.g., stochastic gradient descent (SGD) with momentum). Then, we consider a linearized NN at the pre-trained parameter with an auxiliary variable $c \in \mathbb{R}^P$ as

$$g_{\theta^*}^{\mathrm{lin}}(x, c) := f(x, \theta^*) + \mathbf{J}_\theta(x, \theta^*)\mathrm{diag}(\theta^*)c \tag{3}$$

where diag is a vector-to-matrix diagonal operator. Note that equation 3 is the first-order Taylor approximation of NN with perturbation $\theta^* \odot c$ given input x and parameter θ^*: $g_{\theta^*}^{\mathrm{pert}}(x, c) := f(x, \theta^* + \theta^* \odot c) \approx g_{\theta^*}^{\mathrm{lin}}(x, c)$, where $\odot$ denotes element-wise multiplication of two vectors. Here we express the perturbation in parameter space as $\theta^* \odot c$ instead of a single variable such as $\delta \in \mathbb{R}^P$. By decomposing the scale and connectivity of perturbation, this design of linearization matches the scale of perturbation (i.e., $\theta^* \odot c$) to the scale of θ^* in a component-wise manner. Note that a similar decomposition was proposed in pruning at initialization (Lee et al., 2019c;b) to measure the importance of each connection independently of its weight. However, they only consider this form to predict the effect of each connection before pre-training.

Based on equation 3, we define a data-dependent prior ($\mathbb{P}_\mathcal{D}$) over connectivity as

$$\mathbb{P}_{\theta^*}(c) := \mathcal{N}(c \,|\, \mathbf{0}_P, \alpha^2 \mathbf{I}_p). \tag{4}$$

This distribution can be translated to a distribution over parameter by considering the distribution of perturbed parameter ($\psi := \theta^* + \theta^* \odot c$): $\mathbb{P}_{\theta^*}(\psi) := \mathcal{N}(\psi \,|\, \theta^*, \alpha^2 \mathrm{diag}(\theta^*)^2)$. We now define the PAC-Bayes posterior over connectivity $\mathbb{Q}(c)$ as follows:

$$\mathbb{Q}_{\theta^*}(c) := \mathcal{N}(c|\mu_\mathbb{Q}, \Sigma_\mathbb{Q}), \tag{5}$$

$$\mu_\mathbb{Q} := \frac{\Sigma_\mathbb{Q} \mathbf{J}_c^\top (\mathcal{Y} - f(\mathcal{X}, \theta^*))}{\sigma^2} = \frac{\Sigma_\mathbb{Q} \mathrm{diag}(\theta^*) \mathbf{J}_\theta^\top (\mathcal{Y} - f(\mathcal{X}, \theta^*))}{\sigma^2}, \tag{6}$$

$$\Sigma_\mathbb{Q} := \left(\frac{\mathbf{I}_P}{\alpha^2} + \frac{\mathbf{J}_c^\top \mathbf{J}_c}{\sigma^2} \right)^{-1} = \left(\frac{\mathbf{I}_P}{\alpha^2} + \frac{\mathrm{diag}(\theta^*) \mathbf{J}_\theta^\top \mathbf{J}_\theta \mathrm{diag}(\theta^*)}{\sigma^2} \right)^{-1} \tag{7}$$

where $\mathbf{J}_c \in NK \times P$ is a concatenation of $\mathbf{J}_c(x, \mathbf{0}_P) := \mathbf{J}_\theta(x, \theta^*)\mathrm{diag}(\theta^*) \in \mathbb{R}^{K \times P}$ (i.e., Jacobian of perturbed NN $g_{\theta^*}^{\mathrm{pert}}(x, c)$ w.r.t. c at input x and connectivity $\mathbf{0}_P$) along training input $\mathcal{X}$. Indeed, $\mathbb{Q}_{\theta^*}$ is *the posterior of Bayesian linear regression w.r.t. connectivity c.* We refer to Appendix D for detailed derivations. Again, it is equivalent to the posterior distribution over parameter $\mathbb{Q}_{\theta^*}(\psi) = \mathcal{N}\left(\psi | \theta^* + \theta^* \odot \mu_\mathbb{Q}, (\mathrm{diag}(\theta^*)^{-2}/\alpha^2 + \mathbf{J}_\theta^\top \mathbf{J}_\theta/\sigma^2)^{-1}\right)$ where $\mathrm{diag}(\theta^*)^{-2} := (\mathrm{diag}(\theta^*)^{-1})^2$ by assuming that all components of θ^* are non-zero. This assumption can be easily satisfied by considering the prior and posterior distributions of non-zero components of NNs only. Although we choose this restriction for theoretical tractability, future works can relax it to achieve diverse predictions by considering the distribution of zero coordinates.

In summary, a data-dependent PAC-Bayes bound can be computed with our PAC-Bayes distributions. The validity of this data-dependent PAC-Bayes bound is ensured as follows: our PAC-Bayes prior depends on the $\mathcal{S}_\mathbb{P}$ through θ^*, but independent to the $\mathcal{S}_\mathbb{Q}$ that measures the errors. Note that here a two-phase training (i.e., **pre-training** with $\mathcal{S}_\mathbb{P}$ and **fine-tuning** with $\mathcal{S}$) explained in Sec. 2.1 is used to attain our PAC-Bayes posterior. Similar ideas of two-phase training with linearization were proposed in the context of transfer learning in Achille et al. (2021); Maddox et al. (2021). In transfer learning, there is a distribution shift between $\mathcal{S}_\mathbb{P}$ and $\mathcal{S}_\mathbb{Q}$. Therefore, $\mathcal{S}_\mathbb{P}$ cannot be used for their fine-tuning phase in contrast to our PAC-Bayes posterior.

Now we provide an invariance property of our prior and posterior distributions w.r.t. function-preserving scale transformations as follows: The main intuition behind this proposition is that **Jacobian w.r.t. connectivity is invariant to the function-preserving scaling transformation**, i.e., $\mathbf{J}_\theta(x, \mathcal{T}(\theta^*))\mathrm{diag}(\mathcal{T}(\theta^*)) = \mathbf{J}_\theta(x, \theta^*)\mathrm{diag}(\theta^*)$. Representative cases of $\mathcal{T}$ in Proposition 2.1 are presented in Appendix E to highlight theoretical implications; these include the case of WD applied to the general network including BN.

Proposition 2.1 (Scale-invariance of PAC-Bayes prior and posterior). *Let $\mathcal{T} : \mathbb{R}^P \to \mathbb{R}^P$ is a invertible diagonal linear transformation such that $f(x, \mathcal{T}(\psi)) = f(x, \psi)$, $\forall x \in \mathbb{R}^D, \forall \psi \in \mathbb{R}^P$. Then, both PAC-Bayes prior and posterior are invariant under $\mathcal{T}$:*

$$\mathbb{P}_{\mathcal{T}(\theta^*)}(c) \stackrel{d}{=} \mathbb{P}_{\theta^*}(c), \quad \mathbb{Q}_{\mathcal{T}(\theta^*)}(c) \stackrel{d}{=} \mathbb{Q}_{\theta^*}(c).$$

Furthermore, generalization and empirical errors are also invariant to $\mathcal{T}$.

2.3 Resulting PAC-Bayes bound

Now we plug in our prior and posterior into the modified PAC-Bayes generalization error bound in equation 2. Accordingly, we obtain a novel generalization error bound, named **PAC-Bayes-CTK**, which is guaranteed to be invariant to scale transformations (hence without the contradiction of FM hypothesis mentioned in Sec. 1).

Theorem 2.2 (PAC-Bayes-CTK and its invariance). *Let us assume pre-trained parameter θ^* with data $\mathcal{S}_\mathbb{P}$. By applying $\mathbb{P}_{\theta^*}$ and $\mathbb{Q}_{\theta^*}$ to data-dependent PAC-Bayes bound (equation 2), we get*

$$\mathrm{err}_\mathcal{D}(\mathbb{Q}_{\theta^*}) \le \mathrm{err}_{\mathcal{S}_\mathbb{Q}}(\mathbb{Q}_{\theta^*}) + \sqrt{\overbrace{\underbrace{\frac{\mu_\mathbb{Q}^\top \mu_\mathbb{Q}}{4\alpha^2 N_\mathbb{Q}}}_{\textit{(average) perturbation}} + \underbrace{\sum_{i=1}^P \frac{h(\beta_i)}{4N_\mathbb{Q}}}_{\textit{sharpness}}}^{\textit{KL divergence}} + \frac{\log(2\sqrt{N_\mathbb{Q}}/\delta)}{2N_\mathbb{Q}}} \tag{8}$$

where $\{\beta_i\}_{i=1}^P$ are eigenvalues of $(\mathbf{I}_P + \frac{\alpha^2}{\sigma^2}\mathbf{J}_c^\top\mathbf{J}_c)^{-1}$ and $h(x) := x - \log(x) - 1$. **This upper bound is invariant to** $\mathcal{T}$ *for the function-preserving scale transformation by Proposition 2.1.*

Note that recent works on FM contradiction focus only on the scale-invariance of sharpness metrics: **Indeed, their generalization bounds are not invariant to scale transformations due to the scale-dependent terms** (equation (34) in Tsuzuku et al. (2020) and equation (6) in Kwon et al. (2021)). Concretely, these terms are proportional to the norm of pre-trained parameters. On the other hand, the generalization bound in Petzka et al. (2021) (Theorem 11 in their paper) only holds for single-layer NNs, whereas our bound has no restrictions for network structure. As a result, our PAC-Bayes bound is the first scale-invariant PAC-Bayes bound to the best of our knowledge.

The following corollary explains why we name PAC-Bayes bound in Theorem 2.2 PAC-Bayes-CTK.

Corollary 2.3 (Relation between CTK and PAC-Bayes-CTK). *Let us define empirical **Connectivity Tangent Kernel** (CTK) of $\mathcal{S}$ as $\mathbf{C}_\mathcal{X}^{\theta^*} := \mathbf{J}_c\mathbf{J}_c^\top = \mathbf{J}_\theta\mathrm{diag}(\theta^*)^2\mathbf{J}_\theta^\top \in \mathbb{R}^{NK \times NK}$ by removing below term. Note that empirical CTK has $T(\le NK)$ non-zero eigenvalues of $\{\lambda_i\}_{i=1}^T$, then the followings hold for $\{\beta\}_{i=1}^P$ in Theorem 2.2: (i) $\beta_i = \sigma^2/(\sigma^2 + \alpha^2\lambda_i) < 1$ for $i = 1, \ldots, T$ and (ii) $\beta_i = 1$ for $i = T + 1, \ldots, P$. Since $h(1) = 0$, this means $P - T$ terms of summation in the sharpness part of PAC-Bayes-CTK vanish to 0. Furthermore, this sharpness term of PAC-Bayes-CTK is a monotonically increasing function for each eigenvalue of empirical CTK.*

Corollary 2.3 clarifies why $\sum_{i=1}^P h(\beta_i)/4N_\mathbb{Q}$ in Theorem 2.2 is called the sharpness term of PAC-Bayes-CTK. According to Corollary 2.3, a sharp pre-trained parameter would have large CTK eigenvalues (since eigenvalues of CTK measure the sensitivity of output w.r.t. connectivity), increasing the sharpness term and the generalization gap. Finally, Proposition 2.4 shows that empirical CTK is also scale-invariant.

Proposition 2.4 (Scale-invariance of empirical CTK). *Let $\mathcal{T} : \mathbb{R}^P \to \mathbb{R}^P$ be an function-preserving scale transformation in Proposition 2.1. Then empirical CTK at parameter ψ is invariant under $\mathcal{T}$:*

$$\mathbf{C}_{xy}^{\mathcal{T}(\psi)} := \mathbf{C}_{xy}^\psi, \, \forall x, y \in \mathbb{R}^D, \forall \psi \in \mathbb{R}^P. \tag{9}$$

Remark 2.5 (Connections to empirical NTK). *The empirical CTK $\mathbf{C}_{xy}^\psi$ resembles the existing empirical Neural Tangent Kernel (NTK) at parameter ψ (Jacot et al., 2018): $\Theta_{xy}^\psi := \mathbf{J}_\theta(x, \psi)\mathbf{J}_\theta(y, \psi)^\top \in \mathbb{R}^{K \times K}$. Note that the deterministic NTK in Jacot et al. (2018) is the infinite-width limiting kernel at initialized parameters, while empirical NTK can be defined on any (finite-width) NNs. We focus on empirical kernels for finite pre-trained parameters throughout the paper, and we leave deterministic kernels defined for future studies. Comparing empirical kernels, the main difference between empirical CTK and the existing empirical NTK is in the definition of Jacobian. In CTK, Jacobian is computed w.r.t. connectivity c while the empirical NTK uses Jacobian w.r.t. parameters θ. Therefore, another PAC-Bayes bound can be derived from the linearization of $f_{\theta^*}^{\lin}(x, \delta) := f(x, \theta^*) + \mathbf{J}_\theta(x, \theta^*)\delta$. As this bound is related to the eigenvalues of $\Theta_\mathcal{X}^{\theta^*}$, we call this bound **PAC-Bayes-NTK** and provide derivations in Appendix B. Note that PAC-Bayes-NTK is scale-variant as $\Theta_{xy}^{\mathcal{T}(\psi)} \ne \Theta_{xy}^\psi$ in general.*

2.4 COMPUTING APPROXIMATE BOUND IN REAL WORLD PROBLEMS

To verify that PAC-Bayes bound in Theorem 2.2 is non-vacuous, we compute it for real-world problems. We use CIFAR-10 and 100 datasets (Krizhevsky, 2009), where the 50K training instances are randomly partitioned into $\mathcal{S}_\mathbb{P}$ of cardinality 45K and $\mathcal{S}_\mathbb{Q}$ of cardinality 5K. We refer to Appendix H for detailed experimental settings.

To compute equation 8, one needs (i) $\mu_\mathbb{Q}$-based perturbation term, (ii) $\mathbf{C}_\mathcal{X}^{\theta^*}$-based sharpness term, and (iii) samples from PAC-Bayes posterior $\mathbb{Q}_{\theta^*}$. $\mu_\mathbb{Q}$ in equation 6 can be obtained by minimizing $\arg\min_{c \in \mathbb{R}^P} L(c) = \frac{1}{2N}\|\mathcal{Y} - f(\mathcal{X}, \theta^*) - \mathbf{J}_c c\|^2 + \frac{\sigma^2}{2\alpha^2 N}c^\top c$ by first-order optimality condition. Note that this problem is a convex optimization problem w.r.t. c, since c is the parameter of the linear regression problem. We use Adam optimizer (Kingma & Ba, 2014) with a fixed learning rate 1e-4 to solve this. For the sharpness term, we apply the Lanczos algorithm to approximate the eigenspectrum of $\mathbf{C}_\mathcal{X}^{\theta^*}$ following Ghorbani et al. (2019). We use 100 Lanczos iterations based on their setting. Lastly, we estimate empirical and test errors with 8 samples of CL/LL implementation of the Randomize-Then-Optimize (RTO) framework (Bardsley et al., 2014; Matthews et al., 2017). The pseudo-code and computational complexity of RTO implementation can be found in Appendix F.

Table 1: Comparison between PAC-Bayes-CTK and PAC-Bayes-NTK for ResNet-18

CIFAR-10	PAC-Bayes-CTK				PAC-Bayes-NTK			
Parameter scale	0.5	1.0	2.0	4.0	0.5	1.0	2.0	4.0
Trace	19111 ± 442	19124 ± 448	19121 ± 447	19121 ± 441.99	87931800 ± 2273144	25909710 ± 621010	11075809 ± 206426	7662645 ± 118088
Perturbation	6.2608 ± 0.1463	5.7212 ± 0.0899	5.7717 ± 0.0782	5.8410 ± 0.0483	636.5520 ± 12.1602	564.3789 ± 7.5630	438.2133 ± 10.7265	288.2358 ± 6.3757
Sharpness	28.9262 ± 0.2066	28.9553 ± 0.2226	28.9472 ± 0.2163	28.9484 ± 0.2020	728.8004 ± 2.6895	602.1673 ± 2.7703	502.3218 ± 2.3158	441.9135 ± 2.0836
KL	17.5935 ± 0.1715	17.3383 ± 0.1537	17.3594 ± 0.1456	17.3947 ± 0.1251	682.6762 ± 4.7353	583.2731 ± 2.8812	470.2676 ± 4.3157	365.0746 ± 2.9642
Test err.	0.0482 ± 0.0012	0.0478 ± 0.0011	0.0478 ± 0.0011	0.0477 ± 0.0012	0.1300 ± 0.0053	0.0826 ± 0.0017	0.0694 ± 0.0009	0.0625 ± 0.0008
Bound	0.0921 ± 0.0004	0.0921 ± 0.0002	0.0921 ± 0.0002	0.0921 ± 0.0003	0.3900 ± 0.0061	0.3207 ± 0.0025	0.2824 ± 0.0006	0.2484 ± 0.0011
CIFAR-100	PAC-Bayes-CTK				PAC-Bayes-NTK			
Parameter scale	0.5	1.0	2.0	4.0	0.5	1.0	2.0	4.0
Trace	23350 ± 3701	23353 ± 3699	23345 ± 3702	23352 ± 3700	58305546 ± 5322605	19139020 ± 2440583	10895280 ± 1040610	9550492 ± 661609
Perturbation	14.5423 ± 0.2537	14.3154 ± 0.2403	14.0810 ± 0.1953	13.8439 ± 0.1412	620.1774 ± 6.8317	569.1593 ± 6.9407	459.1605 ± 2.8634	329.2930 ± 3.3350
Sharpness	42.5240 ± 5.2601	42.5336 ± 5.2590	42.5204 ± 5.2652	42.5319 ± 5.2561	694.4482 ± 8.6666	580.1993 ± 12.2187	519.7843 ± 7.8947	504.7443 ± 6.0965
KL	28.5331 ± 2.5076	28.4245 ± 2.5184	28.3007 ± 2.5482	28.1879 ± 2.5592	657.3128 ± 7.2148	574.6793 ± 8.9548	489.4724 ± 3.5651	417.0187 ± 3.9816
Test err.	0.2178 ± 0.0014	0.2182 ± 0.0018	0.2184 ± 0.0019	0.2186 ± 0.0021	0.4339 ± 0.0064	0.3706 ± 0.0026	0.3232 ± 0.0032	0.2837 ± 0.0013
Bound	0.2774 ± 0.0037	0.2776 ± 0.0040	0.2775 ± 0.0042	0.2775 ± 0.0042	0.6844 ± 0.0082	0.5996 ± 0.0019	0.5190 ± 0.0004	0.4480 ± 0.0025

Table 1 provides the bounds and related terms of PAC-Bayes-CTK (Theorem 2.2) and NTK (Theorem B.1). First, we found that our estimated PAC-Bayes-CTK and NTK are non-vacuous (i.e., estimated bounds are better than guessing at random) for ResNet-18 with 11M parameters. Note that deriving non-vacuous bound is challenging in PAC-Bayes analysis: only a few PAC-Bayes works (Dziugaite & Roy, 2017; Zhou et al., 2018; Perez-Ortiz et al., 2021) verified the non-vacuous property of their bounds, and other PAC-Bayes works (Foret et al., 2020; Tsuzuku et al., 2020) did not. To check the invariance property of PAC-Bayes-CTK, we scale the scale-invariant parameters in ResNet-18 (i.e., parameters preceding BN layers) for fixed constants $\{0.5, 1.0, 2.0, 4.0\}$. Due to BN layers, these transformations do not affect the function represented by NN, and the error bounds should be preserved for scale-invariant bounds. Table 1 shows that PAC-Bayes-CTK bound is stable to these transformations. On the other hand, PAC-Bayes-NTK bound is very sensitive to the parameter scale.

2.5   CONNECTIVITY SHARPNESS AND ITS EFFICIENT COMPUTATION

Now, we focus on the fact that the trace of CTK is also invariant to the parameter scale by Proposition 2.4. Unlike PAC-Bayes-CTK and NTK, traces of CTK and NTK do not require onerous hyper-parameter selection of δ, α, σ. Therefore, we simply define $\mathbf{CS}(\theta^*) := \mathrm{tr}(\mathbf{C}_{\mathcal{X}}^{\theta^*})$ as a practical sharpness measure at θ^*, named **Connectivity Sharpness** (CS) to detour the complex computation of PAC-Bayes-CTK. This metric can be easily applied to find NNs with better generalization, similar to other sharpness metrics (e.g., trace of Hessian), as shown in Jiang et al. (2020). We evaluate the detecting performance of CS in Sec. 4.1. The following corollary shows how CS can explain the generalization performance of NNs, conceptually.

Corollary 2.6 (Connectivity sharpness, Informal). *Let us assume CTK and KL divergence terms of PAC-Bayes-CTK as defined in Theorem 2.2. Then, if CS vanishes to zero or infinity, the KL divergence term of PAC-Bayes-CTK also does so.*

As traces of a matrix can be efficiently estimated by Hutchinson's method (Hutchinson, 1989), one can compute the CS *without explicitly computing the entire CTK*. We refer to Appendix F for detailed procedures of computing CS. As CS is invariant to function-preserving scale transformations by Proposition 2.4, it does not contradict the FM hypothesis.

3   BAYESIAN NNS WITH SCALE-INVARIANCE

In this section, we discuss the practical implications of our posterior distribution (equation 5) used in the PAC-Bayes analysis. To this end, we first interpret our PAC-Bayes posterior as a modified result of LA (MacKay, 1992). Then, we demonstrate that this modification improves existing LA when WD is applied to NNs with normalization layers (Proposition 3.1).

One can view the parameter space version of $\mathbb{Q}_{\theta^*}$ as a modified version of LA posterior (equation 1) by (i) substituting parameter-dependent damping $(\mathrm{diag}(\theta^*)^{-2})$ for isotropic damping and (ii) adding perturbation $\theta^* \odot \mu_{\mathbb{Q}}$ to the mean of Gaussian distribution. Here, we focus on the effect of replacing the damping term of LA in batch-normalized NNs in the presence of WD. We refer to Antoran et al. (2021; 2022) for the discussion on the effect of adding perturbation to the LA with linearized NNs.

Table 2: Correlation analysis of sharpness measures with generalization gap. We refer Sec. 4.1 for the details of sharpness measures (row) and correlation metrics for sharpness-generalization relationship (column).

	tr(**H**)	tr(**F**)	tr(Θ^{θ^*})	SO	PO	SM	PM	AS	FR	CS
τ (rank corr.)	0.706	0.679	0.703	0.490	0.436	0.473	0.636	0.755	0.649	**0.837**
network depth	0.764	0.652	**0.978**	-0.358	-0.719	0.774	0.545	0.756	0.771	**0.978**
network width	0.687	0.922	0.330	-0.533	-0.575	0.495	0.564	0.827	0.921	**0.978**
mini-batch size	0.976	0.810	**0.988**	0.859	0.893	0.909	0.750	0.829	0.685	0.905
learning rate	0.966	0.713	**1.000**	0.829	0.874	0.057	0.621	0.794	0.565	0.897
weight decay	-0.031	-0.103	0.402	0.647	0.711	0.168	0.211	0.710	0.373	**0.742**
Ψ (avg.)	0.672	0.599	0.739	0.289	0.237	0.481	0.538	0.783	0.663	**0.900**
$\mathcal{K}$ (cond. MI)	0.320	0.243	0.352	0.039	0.041	0.049	0.376	0.483	0.288	**0.539**

The main difference between the covariance terms of LA in equation 1 and equation 7 is the definition of Jacobian (i.e., parameter or connectivity) similar to the difference between empirical CTK and NTK in Remark 2.5. Therefore, we name $p_{\mathrm{CL}}(\psi|\mathcal{S}) \sim \mathcal{N}(\psi|\theta^*, \left(\mathrm{diag}(\theta^*)^{-2}/\alpha^2 + \mathbf{J}_\theta^\top \mathbf{J}_\theta/\sigma^2\right)^{-1})$ as **Connectivity Laplace (CL)** approximated posterior.

To compare CL posteriors against existing LAs, we explain how WD with BN can produce unexpected side effects. This side effect can be quantified if we consider linearized NN for LA, called Linearized Laplace (LL; Foong et al. (2019)). Assuming $\sigma^2 \ll \alpha^2$, the predictive distribution of LL and CL are

$$f_{\theta^*}^{\mathrm{lin}}(x, \psi)|p_{\mathrm{LA}}(\psi|\mathcal{S}) \sim \mathcal{N}(f(x, \theta^*), \alpha^2 \Theta_{xx}^{\theta^*} - \alpha^2 \Theta_{x\mathcal{X}}^{\theta^*} \Theta_{\mathcal{X}}^{\theta^*-1} \Theta_{\mathcal{X}x}^{\theta^*}) \tag{10}$$

$$f_{\theta^*}^{\mathrm{lin}}(x, \psi)|p_{\mathrm{CL}}(\psi|\mathcal{S}) \sim \mathcal{N}(f(x, \theta^*), \alpha^2 \mathbf{C}_{xx}^{\theta^*} - \alpha^2 \mathbf{C}_{x\mathcal{X}}^{\theta^*} \mathbf{C}_{\mathcal{X}}^{\theta^*-1} \mathbf{C}_{\mathcal{X}x}^{\theta^*}) \tag{11}$$

for any input $x \in \mathbb{R}^d$ where $\mathcal{X}$ in subscript means concatenation. We refer to Appendix G for the detailed derivations. The following proposition illustrates how WD with BN can increase the prediction uncertainty of equation 10.

Proposition 3.1 (Uncertainty amplifying effect for LL). *Let us assume that $\mathcal{W}_\gamma : \mathbb{R}^P \to \mathbb{R}^P$ is a WD on scale-invariant parameters (e.g., parameters preceding BN layers) by multiplying $\gamma < 1$ and all the non-scale-invariant parameters are fixed. Then, the predictive uncertainty of LL is amplified by $1/\gamma^2 > 1$ while the predictive uncertainty of CTK is preserved as*

$$Var_{\psi \sim p_{\mathrm{LA}}(\psi|\mathcal{S})}(f_{\mathcal{W}_\gamma(\theta^*)}^{\mathrm{lin}}(x, \psi)) = Var_{\psi \sim p_{\mathrm{LA}}(\psi|\mathcal{S})}(f_{\theta^*}^{\mathrm{lin}}(x, \psi))/\gamma^2$$

$$Var_{\psi \sim p_{\mathrm{CL}}(\psi|\mathcal{S})}(f_{\mathcal{W}_\gamma(\theta^*)}^{\mathrm{lin}}(x, \psi)) = Var_{\psi \sim p_{\mathrm{CL}}(\psi|\mathcal{S})}(f_{\theta^*}^{\mathrm{lin}}(x, \psi))$$

where $Var(\cdot)$ is variance of random variable.

Since the primal regularization effect of WD actually occurs when combined with BN as experimentally shown in Zhang et al. (2019), Proposition 3.1 describes a real-world issue. Recently, Antoran et al. (2021; 2022) observed similar pitfalls in Proposition 3.1. However, their solution requires a more complicated hyper-parameter search: *independent prior selection for each normalized parameter group*. On the other hand, CL does not increase the hyper-parameter to be optimized compared to LL. We believe this difference will make CL more attractive to practitioners.

4 EXPERIMENTS

Here we describe experiments demonstrating (i) the effectiveness of Connectivity Sharpness (CS) as a generalization measurement metric and (ii) the usefulness of Connectivity Laplace (CL) as a general-purpose Bayesian NN: **With CS and CL, we can resolve the contradiction in the FM hypothesis concerning the generalization of NNs and attain stable calibration performance for various ranges of prior scales.**

4.1 CONNECTIVITY SHARPNESS AS A GENERALIZATION MEASUREMENT METRIC

Based on the CIFAR-10 dataset, we evaluate three correlation metrics to determine whether CS is more correlated with generalization performance than existing sharpness measures: (a) Kendall's rank-correlation coefficient (τ; Kendall (1938)) (b) granulated Kendall's coefficient and their average

Table 3: Test negative log-likelihood on two UCI variants (Hernández-Lobato & Adams, 2015; Foong et al., 2019)

	Original (Hernández-Lobato & Adams, 2015)				GAP variants (Foong et al., 2019)			
	Deep Ensemble	MCDO	LL	CL	Deep Ensemble	MCDO	LL	CL
boston_housing	2.90 ± 0.03	2.63 ± 0.01	**2.85 ± 0.01**	2.88 ± 0.02	2.71 ± 0.01	2.68 ± 0.01	**2.74 ± 0.01**	2.75 ± 0.01
concrete_strength	3.06 ± 0.01	3.20 ± 0.00	3.22 ± 0.01	**3.11 ± 0.02**	4.03 ± 0.07	3.42 ± 0.00	**3.47 ± 0.01**	4.03 ± 0.02
energy_efficiency	0.74 ± 0.01	1.92 ± 0.01	2.12 ± 0.01	**0.83 ± 0.01**	0.77 ± 0.01	1.78 ± 0.01	2.02 ± 0.01	**0.90 ± 0.02**
kin8nm	-1.07 ± 0.00	-0.80 ± 0.01	-0.90 ± 0.00	**-1.07 ± 0.00**	-0.94 ± 0.00	-0.71 ± 0.00	-0.87 ± 0.00	**-0.93 ± 0.00**
naval_propulsion	-4.83 ± 0.00	-3.85 ± 0.00	-4.57 ± 0.00	**-4.76 ± 0.00**	-2.22 ± 0.33	-3.36 ± 0.01	-3.66 ± 0.11	**-3.80 ± 0.07**
power_plant	2.81 ± 0.00	2.91 ± 0.00	2.91 ± 0.00	**2.81 ± 0.00**	2.91 ± 0.00	2.97 ± 0.00	2.98 ± 0.00	**2.91 ± 0.00**
protein_structure	2.89 ± 0.00	2.96 ± 0.00	2.91 ± 0.00	**2.89 ± 0.00**	3.11 ± 0.00	3.07 ± 0.00	**3.07 ± 0.00**	3.13 ± 0.00
wine	1.21 ± 0.00	0.96 ± 0.01	**1.24 ± 0.01**	1.27 ± 0.01	1.48 ± 0.01	1.03 ± 0.00	1.45 ± 0.01	**1.43 ± 0.00**
yacht_hydrodynamics	1.26 ± 0.04	2.17 ± 0.06	**1.20 ± 0.04**	1.25 ± 0.04	1.71 ± 0.03	3.06 ± 0.02	1.78 ± 0.02	**1.74 ± 0.01**

(Ψ; Jiang et al. (2020)) (c) conditional independence test ($\mathcal{K}$; Jiang et al. (2020)). In all correlation metrics, a higher value indicates a stronger relationship between sharpness and generalization.

We compare CS to the following baseline sharpness measures: trace of Hessian ($\mathrm{tr}(\mathbf{H})$; Keskar et al. (2017)), trace of empirical Fisher ($\mathrm{tr}(\mathbf{F})$; Jastrzebski et al. (2021)), trace of empirical NTK at θ^*, Fisher-Rao (FR; Liang et al. (2019)) metric, Adaptive Sharpness (AS; Kwon et al. (2021)), and four PAC-Bayes bound based measures: Sharpness-Orig. (SO), PAC-Bayes-Orig. (PO), Sharpness-Mag. (SM), and PAC-Bayes-Mag. (PM), which are eq. (52), (49), (62), (61) in Jiang et al. (2020). We compute granulated Kendall's correlation by using five hyper-parameters (network depth, network width, learning rate, weight decay, and mini-batch size) and three options for each. Thus, we train models with $3^5 = 243$ different training configurations. We vary the depth and width of NN based on VGG-13 (Simonyan & Zisserman, 2015). Further experimental details can be found in Appendix H.

In Table 2, CS shows the best results for τ, Ψ, and $\mathcal{K}$ compared to all other sharpness measures. Additionally, granulated Kendall of CS is higher than other sharpness measures for 3 out of 5 hyperparameters and competitive with other sharpness measures for the remaining hyperparameters. The main difference between our CS and other sharpness measures is in the correlation with **weight decay** and **network width**: We found that SO and PM can capture the correlation with weight decay, and hypothesize that this is due to the weight norm term of SO and PO. As this weight norm term would interfere in capturing the sharpness-generalization correlation related to the number of parameters (i.e., width/depth), SO and PM fail to capture correlation with network width in Table 2. On the other hand, CS and AS do not suffer from such a problem. Also, it is notable that FR weakly captures this correlation despite its invariant property. For network width, we found that sharpness measures except for CS, $\mathrm{tr}(\mathbf{F})$, AS and FR fail to capture strong correlation. **In summary, only CS and AS detect clear correlations with all hyperparameters; among them, CS capture more clear correlations.**

4.2 CONNECTIVITY LAPLACE AS AN EFFICIENT GENERAL-PURPOSE BAYESIAN NN

We evaluate CL's effectiveness as a general-purpose Bayesian NN using the UCI and CIFAR datasets. We refer to Appendix H for detailed experimental settings.

UCI regression We implement full-curvature versions of LL and CL and evaluate these to the 9 UCI regression datasets (Hernández-Lobato & Adams, 2015) and its GAP-variants (Foong et al., 2019) to compare calibration performance on *in-between* uncertainty. We measure test NLL for LL/CL and 2 baselines (Deep Ensemble (Lakshminarayanan et al., 2017) and Monte-Carlo DropOut (MCDO; Gal & Ghahramani (2016))). Eight ensemble members are used in Deep Ensemble, and 32 MC samples are used in LL, CL, and MCDO. Table 3 shows that CL performs better than LL on 6 of 9 datasets. Even though LL produces better calibration results on 3 of the datasets for both settings, the performance gaps between LL and CL are not as severe as on the other 6 datasets.

Image classification. We evaluate the uncertainty calibration performance of CL on CIFAR-10 and 100. As baseline methods, we consider Deterministic network, Monte-Carlo Dropout (MCDO; (Gal & Ghahramani, 2016)), Monte-Carlo Batch Normalization (MCBN; (Teye et al., 2018)), Deep Ensemble (Lakshminarayanan et al., 2017), Batch Ensemble (Wen et al., 2020), and LL (Khan et al., 2019; Daxberger et al., 2021a). We use the Randomize-Then-Optimize (RTO) implementation of LL/CL in Appendix F. We measure negative log-likelihood (NLL), expected calibration error (ECE; Guo et al. (2017)), and Brier score (Brier.) for ensemble predictions. We also measure the area under

Table 4: Uncertainty calibration results on CIFAR-100 (Krizhevsky, 2009) for ResNet-18 (He et al., 2016)

	CIFAR-100			
	NLL ($\downarrow$)	ECE ($\downarrow$)	Brier. ($\downarrow$)	AUC ($\uparrow$)
Deterministic	1.5370 ± 0.0117	0.1115 ± 0.0017	0.3889 ± 0.0031	-
MCDO	1.4264 ± 0.0110	0.0651 ± 0.0008	0.3925 ± 0.0020	0.6907 ± 0.0121
MCBN	1.4689 ± 0.0106	0.0998 ± 0.0016	0.3750 ± 0.0028	0.7982 ± 0.0210
Batch Ensemble	1.4029 ± 0.0031	0.0842 ± 0.0005	0.3582 ± 0.0010	0.7887 ± 0.0115
Deep Ensemble	1.0110	0.0507	0.2740	0.7802
Linearized Laplace	1.1673 ± 0.0093	0.0532 ± 0.0010	0.3597 ± 0.0020	0.8066 ± 0.0120
Connectivity Laplace (Ours)	1.1307 ± 0.0042	0.0524 ± 0.0019	0.3319 ± 0.0005	0.8423 ± 0.0204

(a) NLL   (b) ECE   (c) Brier Score

Figure 1: Sensitivity to α. Expected calibration error (ECE), Negative Log-likelihood (NLL), and Brier score results on corrupted CIFAR-100 for ResNet-18. Showing the mean (line) and standard deviation (shaded area) across four different seeds.

receiver operating curve (AUC) for OOD detection, where we set the SVHN (Netzer et al., 2011) dataset as an OOD dataset.

Table 4 shows uncertainty calibration results on CIFAR-100. We refer to Appendix J for results on other settings, including CIFAR-10 and VGGNet (Simonyan & Zisserman, 2015). Except for Deep Ensemble, CL shows better results than baselines for all uncertainty calibration metrics (NLL, ECE, Brier, and AUC). Deep Ensemble performs best in 3 out of 4 metrics, but each ensemble member requires full training. LL and CL, however, require only post-hoc training on pre-trained NNs. Particularly noteworthy is that CL presents competitive results with Deep Ensemble, even with much smaller computations.

Robustness to the selection of prior scale. Figure 1 shows the uncertainty calibration results over various α values for LL, CL, and Deterministic (Det.) baseline. As mentioned in previous works (Ritter et al., 2018; Kristiadi et al., 2020), the uncertainty calibration results of LL are extremely sensitive to the selection of α. Especially, LL shows severe under-fitting for large α (i.e., small damping) regime. On the other hand, CL shows stable performance in the various ranges of α.

5   CONCLUSION

In this work, we introduced PAC-Bayes prior and posterior distributions to enhance generalization bound robustness w.r.t. parameter transformations by *decomposing* scales and connectivities. Consequently, our new generalization bound is invariant to function-preserving scale transformations. In this way, the generalization error bounds successfully resolved the contradiction in the FM hypothesis caused by the general scale transformation, which could not be resolved with the existing generalization error bounds. In line with this theoretical enhancement, our posterior distribution for PAC-Bayes analysis can also be interpreted as an improved version of Laplace Approximation without major drawbacks in the case of weight decay with BN. With potential prospective studies, our discoveries will improve the understanding of NN generalization effects, thereby reducing the theory-practice gap.

REFERENCES

Alessandro Achille, Aditya Golatkar, Avinash Ravichandran, Marzia Polito, and Stefano Soatto. Lqf: Linear quadratic fine-tuning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 15729–15739, 2021.

Javier Antoran, James Urquhart Allingham, David Janz, Erik Daxberger, Eric Nalisnick, and José Miguel Hernández-Lobato. Linearised laplace inference in networks with normalisation layers and the neural g-prior. In *Fourth Symposium on Advances in Approximate Bayesian Inference*, 2021.

Javier Antoran, David Janz, James U Allingham, Erik Daxberger, Riccardo Rb Barbano, Eric Nalisnick, and José Miguel Hernández-Lobato. Adapting the linearised laplace model evidence for modern deep learning. In *International Conference on Machine Learning*, pp. 796–821. PMLR, 2022.

Sanjeev Arora, Rong Ge, Behnam Neyshabur, and Yi Zhang. Stronger generalization bounds for deep nets via a compression approach. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 254–263. PMLR, 10–15 Jul 2018.

Johnathan M Bardsley, Antti Solonen, Heikki Haario, and Marko Laine. Randomize-then-optimize: A method for sampling from posterior distributions in nonlinear inverse problems. *SIAM Journal on Scientific Computing*, 36(4):A1895–A1910, 2014.

Christopher M. Bishop. *Pattern Recognition and Machine Learning*. Springer, 2006.

James Bradbury, Roy Frostig, Peter Hawkins, Matthew James Johnson, Chris Leary, Dougal Maclaurin, George Necula, Adam Paszke, Jake VanderPlas, Skye Wanderman-Milne, and Qiao Zhang. JAX: composable transformations of Python+NumPy programs. *github*, 2018.

Erik Daxberger, Agustinus Kristiadi, Alexander Immer, Runa Eschenhagen, Matthias Bauer, and Philipp Hennig. Laplace redux - effortless bayesian deep learning. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, 2021a.

Erik Daxberger, Eric Nalisnick, James U Allingham, Javier Antoran, and Jose Miguel Hernandez-Lobato. Bayesian deep learning via subnetwork inference. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 2510–2521. PMLR, 18–24 Jul 2021b.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Laurent Dinh, Razvan Pascanu, Samy Bengio, and Yoshua Bengio. Sharp minima can generalize for deep nets. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 1019–1028. PMLR, 06–11 Aug 2017.

Gintare Karolina Dziugaite and Daniel M. Roy. Computing nonvacuous generalization bounds for deep (stochastic) neural networks with many more parameters than training data. In *Proceedings of the 33rd Annual Conference on Uncertainty in Artificial Intelligence (UAI)*, 2017.

Andrew YK Foong, Yingzhen Li, José Miguel Hernández-Lobato, and Richard E Turner. 'in-between'uncertainty in bayesian neural networks. *arXiv preprint arXiv:1906.11537*, 2019.

Pierre Foret, Ariel Kleiner, Hossein Mobahi, and Behnam Neyshabur. Sharpness-aware minimization for efficiently improving generalization. *arXiv preprint arXiv:2010.01412*, 2020.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *international conference on machine learning*, pp. 1050–1059. PMLR, 2016.

Behrooz Ghorbani, Shankar Krishnan, and Ying Xiao. An investigation into neural net optimization via hessian eigenvalue density. In *International Conference on Machine Learning*, pp. 2232–2241. PMLR, 2019.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 1321–1330. PMLR, 06–11 Aug 2017.

Bobby He, Balaji Lakshminarayanan, and Yee Whye Teh. Bayesian deep ensembles via the neural tangent kernel. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 1010–1022. Curran Associates, Inc., 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

José Miguel Hernández-Lobato and Ryan Adams. Probabilistic backpropagation for scalable learning of bayesian neural networks. In *International conference on machine learning*, pp. 1861–1869. PMLR, 2015.

Sepp Hochreiter and Jürgen Schmidhuber. Simplifying neural nets by discovering flat minima. In G. Tesauro, D. Touretzky, and T. Leen (eds.), *Advances in Neural Information Processing Systems*, volume 7. MIT Press, 1995.

Like Hui and Mikhail Belkin. Evaluation of neural architectures trained with square loss vs cross-entropy in classification tasks. In *International Conference on Learning Representations*, 2021.

Michael F Hutchinson. A stochastic estimator of the trace of the influence matrix for laplacian smoothing splines. *Communications in Statistics-Simulation and Computation*, 18(3):1059–1076, 1989.

Alexander Immer, Maciej Korzepa, and Matthias Bauer. Improving predictions of bayesian neural nets via local linearization. In *AISTATS*, pp. 703–711, 2021.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In Francis Bach and David Blei (eds.), *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pp. 448–456, Lille, France, 07–09 Jul 2015. PMLR.

Arthur Jacot, Franck Gabriel, and Clement Hongler. Neural tangent kernel: Convergence and generalization in neural networks. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018.

Stanislaw Jastrzebski, Devansh Arpit, Oliver Astrand, Giancarlo B Kerg, Huan Wang, Caiming Xiong, Richard Socher, Kyunghyun Cho, and Krzysztof J Geras. Catastrophic fisher explosion: Early phase fisher matrix impacts generalization. In *International Conference on Machine Learning*, pp. 4772–4784. PMLR, 2021.

Yiding Jiang, Behnam Neyshabur, Hossein Mobahi, Dilip Krishnan, and Samy Bengio. Fantastic generalization measures and where to find them. In *International Conference on Learning Representations*, 2020.

Alex Kendall and Yarin Gal. What uncertainties do we need in bayesian deep learning for computer vision? In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

Maurice G Kendall. A new measure of rank correlation. *Biometrika*, 30(1/2):81–93, 1938.

Nitish Shirish Keskar, Jorge Nocedal, Ping Tak Peter Tang, Dheevatsa Mudigere, and Mikhail Smelyanskiy. On large-batch training for deep learning: Generalization gap and sharp minima. In *5th International Conference on Learning Representations, ICLR 2017*, 2017.

Mohammad Emtiyaz E Khan, Alexander Immer, Ehsan Abedi, and Maciej Korzepa. Approximate inference turns deep networks into gaussian processes. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Agustinus Kristiadi, Matthias Hein, and Philipp Hennig. Being bayesian, even just a bit, fixes overconfidence in relu networks. In *International conference on machine learning*, pp. 5436–5446. PMLR, 2020.

A Krizhevsky. Learning multiple layers of features from tiny images. *Master's thesis, University of Toronto*, 2009.

Jungmin Kwon, Jeongseop Kim, Hyunseo Park, and In Kwon Choi. Asam: Adaptive sharpness-aware minimization for scale-invariant learning of deep neural networks. *arXiv preprint arXiv:2102.11600*, 2021.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

Jaehoon Lee, Lechao Xiao, Samuel Schoenholz, Yasaman Bahri, Roman Novak, Jascha Sohl-Dickstein, and Jeffrey Pennington. Wide neural networks of any depth evolve as linear models under gradient descent. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019a.

Jaehoon Lee, Samuel Schoenholz, Jeffrey Pennington, Ben Adlam, Lechao Xiao, Roman Novak, and Jascha Sohl-Dickstein. Finite versus infinite neural networks: an empirical study. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 15156–15172. Curran Associates, Inc., 2020.

Namhoon Lee, Thalaiyasingam Ajanthan, Stephen Gould, and Philip HS Torr. A signal propagation perspective for pruning neural networks at initialization. *arXiv preprint arXiv:1906.06307*, 2019b.

Namhoon Lee, Thalaiyasingam Ajanthan, and Philip Torr. SNIP: SINGLE-SHOT NETWORK PRUNING BASED ON CONNECTION SENSITIVITY. In *International Conference on Learning Representations*, 2019c.

Hao Li, Zheng Xu, Gavin Taylor, Christoph Studer, and Tom Goldstein. Visualizing the loss landscape of neural nets. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018.

Tengyuan Liang, Tomaso Poggio, Alexander Rakhlin, and James Stokes. Fisher-rao metric, geometry, and complexity of neural networks. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pp. 888–896. PMLR, 2019.

Ekaterina Lobacheva, Maxim Kodryan, Nadezhda Chirkova, Andrey Malinin, and Dmitry P Vetrov. On the periodic behavior of neural network training with batch normalization and weight decay. *Advances in Neural Information Processing Systems*, 34:21545–21556, 2021.

Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. *arXiv preprint arXiv:1608.03983*, 2016.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019.

David J. C. MacKay. A practical bayesian framework for backpropagation networks. *Neural Comput.*, 4(3):448–472, may 1992. ISSN 0899-7667. doi: 10.1162/neco.1992.4.3.448.

Wesley Maddox, Shuai Tang, Pablo Moreno, Andrew Gordon Wilson, and Andreas Damianou. Fast adaptation with linearized neural networks. In *International Conference on Artificial Intelligence and Statistics*, pp. 2737–2745. PMLR, 2021.

Alexander G de G Matthews, Jiri Hron, Richard E Turner, and Zoubin Ghahramani. Sample-then-optimize posterior sampling for bayesian linear models. In *NIPS Workshop on Advances in Approximate Bayesian Inference*, 2017.

David A McAllester. Pac-bayesian model averaging. In *Proceedings of the twelfth annual conference on Computational learning theory*, pp. 164–170, 1999.

Raphael A Meyer, Cameron Musco, Christopher Musco, and David P Woodruff. Hutch++: Optimal stochastic trace estimation. In *Symposium on Simplicity in Algorithms (SOSA)*, pp. 142–155. SIAM, 2021.

Kevin P Murphy. *Machine learning: a probabilistic perspective*. MIT press, 2012.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y. Ng. Reading digits in natural images with unsupervised feature learning. In *NIPS Workshop on Deep Learning and Unsupervised Feature Learning 2011*, 2011.

Behnam Neyshabur, Russ R Salakhutdinov, and Nati Srebro. Path-sgd: Path-normalized optimization in deep neural networks. In C. Cortes, N. Lawrence, D. Lee, M. Sugiyama, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 28. Curran Associates, Inc., 2015a.

Behnam Neyshabur, Ryota Tomioka, and Nathan Srebro. In search of the real inductive bias: On the role of implicit regularization in deep learning. In *ICLR (Workshop)*, 2015b.

Behnam Neyshabur, Srinadh Bhojanapalli, David McAllester, and Nathan Srebro. Exploring generalization in deep learning. *arXiv preprint arXiv:1706.08947*, 2017.

Roman Novak, Jascha Sohl-Dickstein, and Samuel S Schoenholz. Fast finite width neural tangent kernel. In *International Conference on Machine Learning*, pp. 17018–17044. PMLR, 2022.

Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, D. Sculley, Sebastian Nowozin, Joshua Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

Maria Perez-Ortiz, Omar Risvaplata, John Shawe-Taylor, and Csaba Szepesvári. Tighter risk certificates for neural networks. *Journal of Machine Learning Research*, 22(227):1–40, 2021.

Henning Petzka, Michael Kamp, Linara Adilova, Cristian Sminchisescu, and Mario Boley. Relative flatness and generalization. *Advances in Neural Information Processing Systems*, 34, 2021.

Jie Ren, Peter J. Liu, Emily Fertig, Jasper Snoek, Ryan Poplin, Mark Depristo, Joshua Dillon, and Balaji Lakshminarayanan. Likelihood ratios for out-of-distribution detection. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

Hippolyt Ritter, Aleksandar Botev, and David Barber. A scalable laplace approximation for neural networks. In *International Conference on Learning Representations*, 2018.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. In *International Conference on Learning Representations*, 2015.

Mattias Teye, Hossein Azizpour, and Kevin Smith. Bayesian uncertainty estimation for batch normalized deep networks. In *International Conference on Machine Learning*, pp. 4907–4916. PMLR, 2018.

Yusuke Tsuzuku, Issei Sato, and Masashi Sugiyama. Normalized flat minima: Exploring scale invariant definition of flat minima for neural networks using PAC-Bayesian analysis. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 9636–9647. PMLR, 13–18 Jul 2020.

Joost Van Amersfoort, Lewis Smith, Yee Whye Teh, and Yarin Gal. Uncertainty estimation using a single deep deterministic neural network. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 9690–9700. PMLR, 13–18 Jul 2020.

Twan Van Laarhoven. L2 regularization versus batch and weight normalization. *arXiv preprint arXiv:1706.05350*, 2017.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Yeming Wen, Dustin Tran, and Jimmy Ba. Batchensemble: an alternative approach to efficient ensemble and lifelong learning. *arXiv preprint arXiv:2002.06715*, 2020.

M.A. Woodbury. *Inverting Modified Matrices*. Memorandum Report / Statistical Research Group, Princeton. Statistical Research Group, 1950.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires rethinking generalization, 2017.

Guodong Zhang, Chaoqi Wang, Bowen Xu, and Roger Grosse. Three mechanisms of weight decay regularization. In *International Conference on Learning Representations*, 2019.

Wenda Zhou, Victor Veitch, Morgane Austern, Ryan P Adams, and Peter Orbanz. Non-vacuous generalization bounds at the imagenet scale: a pac-bayesian compression approach. *arXiv preprint arXiv:1804.05862*, 2018.

A NOTATIONS

Table 5: Notations used in the main paper

$x_n \in \mathbb{R}^D, y_n \in \mathbb{R}^K$	$\triangleq$	training inputs/outputs
$\theta, \psi \in \mathbb{R}^P$	$\triangleq$	parameter of NNs
$f(x, \theta)$	$\triangleq$	output of NN given x, θ
$f_{\theta^*}^{\mathrm{lin}}(x, \delta)$	$\triangleq$	$f(x, \theta^*) + \mathbf{J}_\theta(x, \theta^*)\delta$ (linearization of NN w.r.t. parameter)
$g_{\theta^*}^{\mathrm{lin}}(x, c)$	$\triangleq$	$f(x, \theta^*) + \mathbf{J}_\theta(x, \theta^*)\mathrm{diag}(\theta^*)c$ (linearization of NN w.r.t. connectivity)
$f_{\theta^*}^{\mathrm{pert}}(x, \delta), g_{\theta^*}^{\mathrm{pert}}(x, c)$	$\triangleq$	Perturbed NN w.r.t. parameter/connectivity
$\mathbf{0}_d$	$\triangleq$	zero vector with dimension d
$\mathbf{I}_d$	$\triangleq$	identity matrix with dimension $d \times d$
$\mathrm{tr}(A)$	$\triangleq$	a trace (i.e., sum of diagonal elements) of matrix A
$\mathrm{diag}(v)$	$\triangleq$	a diagonal matrix whose diagonal elements correspond to v
$\mathcal{T} : \mathbb{R}^P \to \mathbb{R}^P$	$\triangleq$	a function-preserving scale transformation
$\mathcal{D}$	$\triangleq$	(true) data distribution
$\mathcal{S}$	$\triangleq$	i.i.d. sampled training dataset from $\mathcal{S}$
$\mathcal{S}_\mathbb{P}, \mathcal{S}_\mathbb{Q}$	$\triangleq$	randomly partitioned prior/posterior datasets from $\mathcal{S}$
$N, N_\mathbb{P}, N_\mathbb{Q}$	$\triangleq$	cardinality of $\mathcal{S}, \mathcal{S}_\mathbb{P}, \mathcal{S}_\mathbb{Q}$
$\mathcal{X}, \mathcal{Y}/\mathcal{X}_\mathbb{P}, \mathcal{Y}_\mathbb{P}/\mathcal{X}_\mathbb{Q}, \mathcal{Y}_\mathbb{Q}$	$\triangleq$	concatenated inputs and outputs of all instances of $\mathcal{S}/\mathcal{S}_\mathbb{P}/\mathcal{S}_\mathbb{Q}$.
$\mathbf{J}_\theta(x, \theta^*), \mathbf{J}_c(x, \theta^*) \in \mathbb{R}^{K \times P}$	$\triangleq$	Jacobian of outputs w.r.t parameter/connectivity given x, θ^*
$f(\mathcal{X}, \theta) \in \mathbb{R}^{NK \times P}$	$\triangleq$	concatenated outputs of NN along $\mathcal{X}$
$\mathbf{J}_\theta, \mathbf{J}_c \in \mathbb{R}^{NK \times P}$	$\triangleq$	concatenated Jacobian w.r.t. parameter/connectivity along $\mathcal{X}$
$\mathbb{P}_{\theta^*}(c), \mathbb{Q}_{\theta^*}(c)$	$\triangleq$	our PAC-Bayes prior/posterior
$\mathrm{err}_\mathcal{D}(\mathbb{Q}), \mathrm{err}_\mathcal{S}(\mathbb{Q})$	$\triangleq$	generalization/empirical error of PAC-Bayes posterior
α	$\triangleq$	standard deviation of our PAC-Bayes prior
σ	$\triangleq$	scale (standard deviation) of observational noise
$\mu_\mathbb{Q} \in \mathbb{R}^P, \Sigma_\mathbb{Q} \in \mathbb{R}^{P \times P}$	$\triangleq$	mean and covariance of our PAC-Bayes posterior
$\Theta_{xx'}^\psi, \mathbf{C}_{xx'}^\psi \in \mathbb{R}$	$\triangleq$	empirical NTK/CTK of NN given ψ and input pair $x, x' \in \mathbb{R}^D$
$\Theta_\mathcal{X}^\psi, \mathbf{C}_\mathcal{X}^\psi \in \mathbb{R}^{N \times N}$	$\triangleq$	empirical NTK/CTK of NN for training inputs ($\mathcal{X}$) given ψ
$\{\lambda_i\}_{i=1}^P$	$\triangleq$	eigenvalues of empirical CTK
$\{\beta_i\}_{i=1}^P$	$\triangleq$	eigenvalues of $(\mathbf{I}_P + \frac{\alpha^2}{\sigma^2}\mathbf{J}_c^\top \mathbf{J}_c)^{-1}$
$h(x)$	$\triangleq$	$x - \log(x) - 1$ (non-negative convex function w.r.t. β_i. See Fig. 2)
$(h \circ s)(x)$	$\triangleq$	non-negative concave function w.r.t. λ_i. See Fig. 2)

B PROOFS

B.1 PROOF OF PROPOSITION 2.1

Proof. Since the prior $\mathbb{P}_{\theta^*}(c)$ is independent to the parameter scale, $\mathbb{P}_{\theta^*}(c) \stackrel{d}{=} \mathbb{P}_{\mathcal{T}(\theta^*)}(c)$ is trivial. For Jacobian w.r.t. parameters, we have

$$\mathbf{J}_\theta(x, \mathcal{T}(\psi)) = \frac{\partial}{\partial \mathcal{T}(\psi)} f(x, \mathcal{T}(\psi)) = \frac{\partial}{\partial \mathcal{T}(\psi)} f(x, \psi) = \mathbf{J}_\theta(x, \psi)\mathcal{T}^{-1}$$

Then, the Jacobian of NN w.r.t. connectivity at $\mathcal{T}(\psi)$ holds

$$\mathbf{J}_\theta(x, \mathcal{T}(\psi))\mathrm{diag}(\mathcal{T}(\psi)) = \mathbf{J}_\theta(x, \psi)\mathcal{T}^{-1}\mathcal{T}\mathrm{diag}(\psi) \tag{12}$$
$$= \mathbf{J}_\theta(x, \psi)\mathrm{diag}(\psi) \tag{13}$$

where the first equality holds from the above one and the fact that $\mathcal{T}$ is a diagonal linear transformation. Therefore, the covariance of posterior is invariant to $\mathcal{T}$.

$$
\left(\frac{\mathbf{I}_P}{\alpha^2} + \frac{\text{diag}(\mathcal{T}(\theta^*))\mathbf{J}_\theta^\top(\mathcal{X},\mathcal{T}(\theta^*))\mathbf{J}_\theta(\mathcal{X},\mathcal{T}(\theta^*))\text{diag}(\mathcal{T}(\theta^*))}{\sigma^2} \right)^{-1}
$$
$$
= \left(\frac{\mathbf{I}_P}{\alpha^2} + \frac{\text{diag}(\theta^*)\mathbf{J}_\theta^\top(\mathcal{X},\theta^*)\mathbf{J}_\theta(\mathcal{X},\theta^*)\text{diag}(\theta^*)}{\sigma^2} \right)^{-1}
$$
$$
= \left(\frac{\mathbf{I}_P}{\alpha^2} + \frac{\text{diag}(\theta^*)\mathbf{J}_\theta^\top\mathbf{J}_\theta\text{diag}(\theta^*)}{\sigma^2} \right)^{-1}
$$

Moreover, the mean of posterior is also invariant to $\mathcal{T}$.

$$
\frac{\Sigma_\mathbb{Q}\text{diag}(\mathcal{T}(\theta^*))\mathbf{J}_\theta^\top(\mathcal{X},\mathcal{T}(\theta^*))\left(\mathcal{Y}-f(\mathcal{X},\mathcal{T}(\theta^*))\right)}{\sigma^2}
$$
$$
= \frac{\Sigma_\mathbb{Q}\text{diag}(\mathcal{T}(\theta^*))\mathbf{J}_\theta^\top(\mathcal{X},\mathcal{T}(\theta^*))\left(\mathcal{Y}-f(\mathcal{X},\theta^*)\right)}{\sigma^2}
$$
$$
= \frac{\Sigma_\mathbb{Q}\text{diag}(\theta^*)\mathbf{J}_\theta^\top(\mathcal{X},\theta^*)\left(\mathcal{Y}-f(\mathcal{X},\theta^*)\right)}{\sigma^2}
$$
$$
= \frac{\Sigma_\mathbb{Q}\text{diag}(\theta^*)\mathbf{J}_\theta^\top\left(\mathcal{Y}-f(\mathcal{X},\theta^*)\right)}{\sigma^2}
$$

Therefore, equation 6 and equation 7 are invariant to function-preserving scale transformations. The remaining part of the theorem is related to the definition of function-preserving scale transformation $\mathcal{T}$. For generalization error, the following holds

$$
\begin{aligned}
\text{err}_\mathcal{D}(\mathbb{Q}_{\mathcal{T}(\theta^*)}) &= \mathbb{E}_{(x,y)\sim\mathcal{D},\psi\sim\mathbb{Q}_{\mathcal{T}(\theta^*)}}[\text{err}(f(x,\psi),y)] \\
&= \mathbb{E}_{(x,y)\sim\mathcal{D},c\sim\mathbb{Q}_{\mathcal{T}(\theta^*)}}[\text{err}(g_{\theta^*}^{\text{pert}}(x,c),y)] \\
&= \mathbb{E}_{(x,y)\sim\mathcal{D},c\sim\mathbb{Q}_{\theta^*}}[\text{err}(g_{\theta^*}^{\text{pert}}(x,c),y)] \\
&= \mathbb{E}_{(x,y)\sim\mathcal{D},\psi\sim\mathbb{Q}_{\theta^*}}[\text{err}(f(x,\psi),y)] \\
&= \text{err}_\mathcal{D}(\mathbb{Q}_{\theta^*})
\end{aligned}
$$

This proof can be extended to the empirical error $\text{err}_{\mathcal{S}_\mathbb{Q}}$. $\qquad\square$

B.2 PROOF OF THEOREM 2.2

Proof. **(Construction of KL divergence)** To construct PAC-Bayes-CTK, we need to arrange KL divergence between posterior and prior as follows:

$$
\begin{aligned}
\text{KL}[\mathbb{Q}\|\mathbb{P}] &= \frac{1}{2}\left(\text{tr}\left(\Sigma_\mathbb{P}^{-1}(\Sigma_\mathbb{Q}+(\mu_\mathbb{Q}-\mu_\mathbb{P})(\mu_\mathbb{Q}-\mu_\mathbb{P})^\top)\right)+\log|\Sigma_\mathbb{P}|-\log|\Sigma_\mathbb{Q}|-P\right) \\
&= \frac{1}{2}\text{tr}(\Sigma_\mathbb{P}^{-1}(\mu_\mathbb{Q}-\mu_\mathbb{P})(\mu_\mathbb{Q}-\mu_\mathbb{P})^\top))+\frac{1}{2}\left(\text{tr}(\Sigma_\mathbb{P}^{-1}\Sigma_\mathbb{Q})+\log|\Sigma_\mathbb{P}|-\log|\Sigma_\mathbb{Q}|-P\right) \\
&= \frac{1}{2}(\mu_\mathbb{Q}-\mu_\mathbb{P})^\top\Sigma_\mathbb{P}^{-1}(\mu_\mathbb{Q}-\mu_\mathbb{P})+\frac{1}{2}\left(\text{tr}(\Sigma_\mathbb{P}^{-1}\Sigma_\mathbb{Q})-\log|\Sigma_\mathbb{P}^{-1}\Sigma_\mathbb{Q}|-P\right) \\
&= \underbrace{\frac{\mu_\mathbb{Q}^\top\mu_\mathbb{Q}}{2\alpha^2}}_{\text{perturbation}}+\underbrace{\frac{1}{2}\left(\text{tr}(\Sigma_\mathbb{P}^{-1}\Sigma_\mathbb{Q})-\log|\Sigma_\mathbb{P}^{-1}\Sigma_\mathbb{Q}|-p\right)}_{\text{sharpness}}
\end{aligned}
$$

where the first equality uses the KL divergence between two Gaussian distributions, the third equality uses trace property $(\text{tr}(AB)=\text{tr}(BA)$ and $\text{tr}(a)=a$ for scalar a), and the last equality uses the definition of PAC-Bayes prior $(\mathbb{P}_{\theta^*}(c)=\mathcal{N}(c|\mathbf{0}_P,\alpha^2\mathbf{I}_P))$. For sharpness term, we first compute the $\Sigma_\mathbb{P}^{-1}\Sigma_\mathbb{Q}$ term as

$$
\Sigma_\mathbb{P}^{-1}\Sigma_\mathbb{Q} = \left(\mathbf{I}_P+\frac{\alpha^2}{\sigma^2}\mathbf{J}_c^\top\mathbf{J}_c\right)^{-1}
$$

Since $\alpha^2, \sigma^2 > 0$ and $\mathbf{J}_c^\top \mathbf{J}_c$ is positive semi-definite, the matrix $\Sigma_{\mathbb{P}}^{-1}\Sigma_{\mathbb{Q}}$ have non-zero eigenvalues of $\{\beta_i\}_{i=1}^P$. Since a trace is the sum of eigenvalues and the log-determinant is the sum of the log of eigenvalues, we have

$$\mathrm{KL}[\mathbb{Q}\|\mathbb{P}] = \frac{\mu_{\mathbb{Q}}^\top \mu_{\mathbb{Q}}}{2\alpha^2} + \frac{1}{2}\sum_{i=1}^P (\beta_i - \log(\beta_i) - 1)$$

$$= \frac{\mu_{\mathbb{Q}}^\top \mu_{\mathbb{Q}}}{2\alpha^2} + \frac{1}{2}\sum_{i=1}^P h(\beta_i)$$

where $h(x) = x - \log(x) - 1$. By plugging this KL divergence into the equation 2, we get equation 8.

(Eigenvalues of $\Sigma_{\mathbb{P}}^{-1}\Sigma_{\mathbb{Q}}$) To show the scale-invariance of PAC-Bayes-CTK, it is sufficient to show that KL divergence posterior and prior is scale-invariant: $\frac{\log(2\sqrt{N_{\mathbb{Q}}}/\delta)}{2N_{\mathbb{Q}}}$ is independent to KL PAC-Bayes prior/posterior, and we already show the invariance property of empirical/generalization error term in Proposition 2.1. To show the invariance property of KL divergence, we consider the Connectivity Tangent Kernel (CTK) as defined in equation 2.3:

$$\mathbf{C}_{\mathcal{X}}^{\theta^*} := \mathbf{J}_c \mathbf{J}_c^\top = \mathbf{J}_\theta \mathrm{diag}(\theta^*)^2 \mathbf{J}_\theta^\top \in \mathbb{R}^{NK \times NK}.$$

Since CTK is a real-symmetric matrix, one can assume the eigenvalue decomposition of CTK as $\mathbf{C}_{\mathcal{X}}^{\theta^*} = Q\Lambda Q^\top$ where $Q \in \mathbb{R}^{NK \times NK}$ is an orthogonal matrix and $\Lambda \in \mathbb{R}^{NK \times NK}$ is a diagonal matrix. Then the following holds for $\Sigma_{\mathbb{P}}^{-1}\Sigma_{\mathbb{Q}}$

$$\Sigma_{\mathbb{P}}^{-1}\Sigma_{\mathbb{Q}} = \left(\mathbf{I}_P + \frac{\alpha^2}{\sigma^2}\mathbf{J}_c^\top \mathbf{J}_c\right)^{-1}$$

$$= \left(\mathbf{I}_P + \frac{\alpha^2}{\sigma^2}Q\Lambda Q^\top\right)^{-1}$$

$$= Q\left(\mathbf{I}_P + \frac{\alpha^2}{\sigma^2}\Lambda\right)^{-1}Q^\top$$

Therefore, eigenvalues of $\Sigma_{\mathbb{P}}^{-1}\Sigma_{\mathbb{Q}}$ are $\frac{1}{1+\alpha^2\lambda_i/\sigma^2} = \frac{\sigma^2}{\sigma^2+\alpha^2\lambda_i}$ where $\{\lambda_i\}_{i=1}^P$ are eigenvalues of CTK (and diagonal elements of Λ).

(Scale invariance of CTK) The scale-invariance property of CTK is a simple application of equation 13:

$$\mathbf{C}_{xy}^{\mathcal{T}(\psi)} = \mathbf{J}_\theta(x, \mathcal{T}(\psi))\mathrm{diag}(\mathcal{T}(\psi)^2)\mathbf{J}_\theta(y, \mathcal{T}(\psi))^\top$$

$$= \mathbf{J}_\theta(x, \psi)\mathcal{T}^{-1}\mathcal{T}\mathrm{diag}(\psi)\mathrm{diag}(\psi)\mathcal{T}\mathcal{T}^{-1}\mathbf{J}_\theta(x, \psi)^\top$$

$$= \mathbf{J}_\theta(x, \psi)\mathrm{diag}(\psi)\mathrm{diag}(\psi)\mathbf{J}_\theta(x, \psi)^\top$$

$$= \mathbf{C}_{xy}^{\psi}, \forall x, y \in \mathbb{R}^D, \forall \psi \in \mathbb{R}^P.$$

Therefore, CTK is invariant to any function-preserving scale transformation $\mathcal{T}$ and so do its eigenvalues. This guarantees the invariance of $\Sigma_{\mathbb{P}}^{-1}\Sigma_{\mathbb{Q}}$ and its eigenvalues. In summary, we showed the scale-invariance property of the sharpness term of KL divergence. Now all that remains is to show the invariance of the perturbation term. However, this is already proved in the proof of Proposition 2.1. Therefore, we show PAC-Bayes-CTK is invariant to any function-preserving scale transformation. $\square$

B.3 PROOF OF COROLLARY 2.3

Proof. In proof of Theorem 2.2, we showed that eigenvalues of $\Sigma_{\mathbb{P}}^{-1}\Sigma_{\mathbb{Q}}$ can be represented as

$$\frac{\sigma^2}{\sigma^2 + \alpha^2\lambda_i}$$

where $\{\lambda_i\}_{i=1}^P$ are eigenvalues of CTK. Now, we identify the eigenvalues of CTK. To this end, we assume the singular value decomposition (SVD) of Jacobian w.r.t. connectivity $\mathbf{J}_c \in \mathbb{R}^{NK \times P}$ as

(a) $y = h(x)$ (b) $y = (h \circ s)(x)$ where $\sigma = \alpha = 1$

Figure 2: Functions used in proofs

$\mathbf{J}_c = U\Sigma V^\top$, where $U \in \mathbb{R}^{NK \times NK}$ and $V \in \mathbb{R}^{P \times P}$ are orthogonal matrices and $\Sigma \in \mathbb{R}^{NK \times P}$ is a rectangular diagonal matrix. Then, CTK can be represented as $\mathbf{C}_{\mathcal{X}}^{\theta^*} = \mathbf{J}_c \mathbf{J}_c^\top = U\Sigma V^\top V\Sigma U^\top = U\Sigma^2 U^\top$. In summary, the column vectors of U are eigenvectors of CTK, and eigenvalues of CTK are squares of singular values of $\mathbf{J}_c$ and so $\lambda_i \geq 0, \forall i$. Therefore $\beta_i \leq 1$ for all $i = 1, \ldots, P$ for eigenvalues $\{\beta_i\}_{i=1}^{P}$ of $\Sigma_{\mathbb{P}}^{-1}\Sigma_{\mathbb{Q}}$ and equality holds for $\lambda_i = 0$. Now all that remains is to show that the sharpness term of PAC-Bayes-CTK is a monotonically increasing function on each eigenvalue of CTK. To show this, we first keep in mind that

$$s(x) := \frac{\sigma^2}{\sigma^2 + \alpha^2 x}$$

is a monotonically decreasing function for $x \geq 0$ and $h(x) := x - \log(x) - 1$ is a monotonically decreasing function for $x \in (0, 1]$. Since the sharpness term of KL divergence is

$$\sum_{i=1}^{P} \frac{h(\beta_i)}{4N_{\mathbb{Q}}} = \sum_{i=1}^{P} \frac{(h \circ s)(\lambda_i)}{4N_{\mathbb{Q}}}$$

This is a monotonically increasing function for $x \geq 0$ since $s(x) \leq 1$ for $x \geq 0$. For your information, we plot $y = h(x)$ and $y = (h \circ s)(x)$ in Figure 2.

$\square$

B.4   PROOF OF PROPOSITION 2.4

We refer to **Scale invariance of CTK** part of the proof of Theorem 2.2. This is a direct application of the scale-invariance property of Jacobian w.r.t. connectivity.

B.5   PROOF OF COROLLARY 2.6

Proof. Since CS is a trace of CTK, it is a sum of the eigenvalues of CTK. As shown in the proof of Corollary 2.3, eigenvalues of CTK are square of singular values of Jacobian w.r.t. connectivity c. Therefore, the eigenvalues of CTK are non-negative and vanish to zero if CS vanishes to zero.

$$\sum_{i=1}^{P} \lambda_i = 0 \Rightarrow \lambda_i = 0 \Rightarrow \beta_i = s(\lambda_i) = 1 \Rightarrow h(\beta_i) = 0, \quad \forall i = 1, \ldots, P$$

This means the sharpness term of KL divergence vanishes to zero. Furthermore, singular values of Jacobian w.r.t. c also vanish to zero in this case. Therefore, $\mu_{\mathbb{Q}}$ vanishes to zero, also. Similarly, if CS diverges to infinity, this means (at least) one of the eigenvalues of CTK diverges to infinity. In this case, the following holds

$$\lambda_i \to \infty \Rightarrow \beta_i = s(\lambda_i) \to 0 \Rightarrow h(\beta_i) \to \infty, \quad \forall i = 1, \ldots, P$$

Therefore, the KL divergence term of PAC-Bayes-CTK also diverges to infinity. $\square$

B.6 PROOF OF PROPOSITION 3.1

Proof. By assumption, we fixed all non-scale invariant parameters. This means we exclude these parameters in the sampling procedure of CL and LL. In terms of predictive distribution, this can be translated as

$$f_{\theta^*}^{\text{lin}}(x,\psi)|p_{\text{LA}}(\psi|\mathcal{S}) \sim \mathcal{N}(f(x,\theta^*), \alpha^2\hat{\Theta}_{xx}^{\theta^*} - \alpha^2\hat{\Theta}_{x\mathcal{X}}^{\theta^*}\hat{\Theta}\mathcal{X}^{\theta^*-1}\hat{\Theta}_{\mathcal{X}x}^{\theta^*})$$

$$f_{\theta^*}^{\text{lin}}(x,\psi)|p_{\text{CL}}(\psi|\mathcal{S}) \sim \mathcal{N}(f(x,\theta^*), \alpha^2\hat{\mathbf{C}}_{xx}^{\theta^*} - \alpha^2\hat{\mathbf{C}}_{x\mathcal{X}}^{\theta^*}\hat{\mathbf{C}}_{\mathcal{X}}^{\theta^*-1}\hat{\mathbf{C}}_{\mathcal{X}x}^{\theta^*})$$

where $\hat{\Theta}_{xx'}^\psi := \sum_{i\in\mathcal{P}} \frac{\partial f(x,\psi)}{\partial\theta_i}\frac{\partial f(x',\psi)}{\partial\theta_i}$ and $\hat{\mathbf{C}}_{xx'}^\psi := \sum_{i\in\mathcal{P}} \frac{\partial f(x,\psi)}{\partial\theta_i}\frac{\partial f(x',\psi)}{\partial\theta_i}(\psi_i)^2$ for scale-invariant parameter set $\mathcal{P}$. Thereby, we mask the gradient of the non-scale-invariant parameters as zero. Therefore, this can be arranged as follows

$$\hat{\Theta}_{xx'}^\psi = \mathbf{J}_\theta(x,\psi)\text{diag}(\mathbf{1}_\mathcal{P})\mathbf{J}_\theta(x,\psi)^\top, \quad \hat{\mathbf{C}}_{xx'}^\psi = \mathbf{J}_\theta(x,\psi)\text{diag}(\psi)\text{diag}(\mathbf{1}_\mathcal{P})\text{diag}(\psi)\mathbf{J}_\theta(x,\psi)^\top$$

where $\mathbf{1}_\mathcal{P} \in \mathbb{R}^P$ is a masking vector (i.e., one for included components and zero for excluded components). Then, the WD for scale-invariant parameters can be represented as

$$\mathcal{W}_\gamma(\psi)_i = \begin{cases} \gamma\psi_i, & \text{if} \quad \psi_i \in \mathcal{P}. \\ \psi_i, & \text{if} \quad \psi_i \notin \mathcal{P}. \end{cases}$$

Therefore, we get

$$\begin{aligned}\hat{\Theta}_{xx'}^{\mathcal{W}_\gamma(\psi)} &= \mathbf{J}_\theta(x,\mathcal{W}_\gamma(\psi))\text{diag}(\mathbf{1}_\mathcal{P})\mathbf{J}_\theta(x,\mathcal{W}_\gamma(\psi)))^\top \\ &= \mathbf{J}_\theta(x,\psi)\mathcal{W}_\gamma^{-1}\text{diag}(\mathbf{1}_\mathcal{P})\mathcal{W}_\gamma^{-1}\mathbf{J}_\theta(x,\psi)^\top \\ &= \mathbf{J}_\theta(x,\psi)\text{diag}(\mathbf{1}_\mathcal{P}/\gamma^2)\mathbf{J}_\theta(x,\psi)^\top \\ &= 1/\gamma^2\mathbf{J}_\theta(x,\psi)\text{diag}(\mathbf{1}_\mathcal{P})\mathbf{J}_\theta(x,\psi)^\top \\ &= 1/\gamma^2\hat{\Theta}_{xx'}^\psi \end{aligned}$$

for empirical NTK and

$$\begin{aligned}\hat{\mathbf{C}}_{xx'}^{\mathcal{W}_\gamma(\psi)} &= \mathbf{J}_\theta(x,\mathcal{W}_\gamma(\psi))\text{diag}(\mathcal{W}_\gamma(\psi))\text{diag}(\mathbf{1}_\mathcal{P})\text{diag}(\mathcal{W}_\gamma(\psi))\mathbf{J}_\theta(x,\mathcal{W}_\gamma(\psi)))^\top \\ &= \mathbf{J}_\theta(x,\psi)\mathcal{W}_\gamma^{-1}\mathcal{W}_\gamma\text{diag}(\psi)\text{diag}(\mathbf{1}_\mathcal{P})\text{diag}(\psi)\mathcal{W}_\gamma\mathcal{W}_\gamma^{-1}\mathbf{J}_\theta(x,\psi)^\top \\ &= \mathbf{J}_\theta(x,\psi)\text{diag}(\psi)\text{diag}(\mathbf{1}_\mathcal{P})\text{diag}(\psi)\mathbf{J}_\theta(x,\psi)^\top \\ &= \hat{\mathbf{C}}_{xx'}^\psi \end{aligned}$$

for empirical CTK. Therefore, we get

$$f_{\mathcal{W}_\gamma(\theta^*)}^{\text{lin}}(x,\psi)|p_{\text{LA}}(\psi|\mathcal{S}) \sim \mathcal{N}(f(x,\theta^*), \alpha^2/\gamma^2\hat{\Theta}_{xx}^{\theta^*} - \alpha^2/\gamma^2\hat{\Theta}_{x\mathcal{X}}^{\theta^*}\hat{\Theta}_{\mathcal{X}}^{\theta^*-1}\hat{\Theta}_{\mathcal{X}x}^{\theta^*})$$

$$f_{\mathcal{W}_\gamma(\theta^*)}^{\text{lin}}(x,\psi)|p_{\text{CL}}(\psi|\mathcal{S}) \sim \mathcal{N}(f(x,\theta^*), \alpha^2\hat{\mathbf{C}}_{xx}^{\theta^*} - \alpha^2\hat{\mathbf{C}}_{x\mathcal{X}}^{\theta^*}\hat{\mathbf{C}}_{\mathcal{X}}^{\theta^*-1}\hat{\mathbf{C}}_{\mathcal{X}x}^{\theta^*})$$

This gives us

$$\text{Var}_{\psi\sim p_{\text{LA}}(\psi|\mathcal{S})}(f_{\mathcal{W}_\gamma(\theta^*)}^{\text{lin}}(x,\psi)) = \text{Var}_{\psi\sim p_{\text{LA}}(\psi|\mathcal{S})}(f_{\theta^*}^{\text{lin}}(x,\psi))/\gamma^2$$

$$\text{Var}_{\psi\sim p_{\text{CL}}(\psi|\mathcal{S})}(f_{\mathcal{W}_\gamma(\theta^*)}^{\text{lin}}(x,\psi)) = \text{Var}_{\psi\sim p_{\text{CL}}(\psi|\mathcal{S})}(f_{\theta^*}^{\text{lin}}(x,\psi))$$

$\square$

B.7 DERIVATION OF PAC-BAYES-NTK

Theorem B.1 (PAC-Bayes-NTK). *Let us assume pre-trained parameter θ^* with data $\mathcal{S}_\mathbb{P}$. Let us assume PAC-Bayes prior and posterior as*

$$\mathbb{P}'_{\theta*}(\delta) := \mathcal{N}(\delta|\mathbf{0}_P, \alpha^2\mathbf{I}_P) \tag{14}$$

$$\mathbb{Q}'_{\theta*}(\delta) := \mathcal{N}(\delta|\mu_{\mathbb{Q}'}, \Sigma_{\mathbb{Q}'}) \tag{15}$$

$$\mu_{\mathbb{Q}'} := \frac{\Sigma_{\mathbb{Q}'}\mathbf{J}_\theta^\top(\mathcal{Y} - f(\mathcal{X},\theta^*))}{\sigma^2} \tag{16}$$

$$\Sigma_{\mathbb{Q}'} := \left(\frac{\mathbf{I}_P}{\alpha^2} + \frac{\mathbf{J}_\theta^\top\mathbf{J}_\theta}{\sigma^2}\right)^{-1} \tag{17}$$

By applying $\mathbb{P}'_{\theta^*}, \mathbb{Q}'_{\theta^*}$ to data-dependent PAC-Bayes bound (equation 2), we get

$$\text{err}_{\mathcal{D}}(\mathbb{Q}'_{\theta^*}) \leq \text{err}_{\mathcal{S}_{\mathbb{Q}'}}(\mathbb{Q}'_{\theta^*}) + \sqrt{\overbrace{\underbrace{\frac{\mu_{\mathbb{Q}'}^\top \mu_{\mathbb{Q}'}}{4\alpha^2 N_{\mathbb{Q}'}}}_{\text{(average) perturbation}} + \underbrace{\sum_{i=1}^{P} \frac{h(\beta'_i)}{4N_{\mathbb{Q}'}}}_{\text{sharpness}} + \frac{\log(2\sqrt{N_{\mathbb{Q}'}}/\delta)}{2N_{\mathbb{Q}'}}}^{\text{KL divergence}}} \qquad (18)$$

where $\{\beta'_i\}_{i=1}^{P}$ are eigenvalues of $(\mathbf{I}_P + \frac{\alpha^2}{\sigma^2}\mathbf{J}_\theta^\top \mathbf{J}_\theta)^{-1}$ and $h(x) := x - \log(x) - 1$. This upper bound is not scale-invariant in general.

Proof. The main difference between PAC-Bayes-CTK and PAC-Bayes-NTK is the definition of Jacobian: PAC-Bayes-CTK uses Jacobian w.r.t connectivity and PAC-Bayes-NTK uses Jacobian w.r.t. parameter. Therefore, **Construction of KL divergence** of proof of Theorem 2.2 is preserved except

$$\Sigma_{\mathbb{P}'}^{-1}\Sigma_{\mathbb{Q}'} = (\mathbf{I}_P + \frac{\alpha^2}{\sigma^2}\mathbf{J}_\theta^\top \mathbf{J}_\theta)^{-1}$$

and β'_i are eigenvalues of $\Sigma_{\mathbb{P}'}^{-1}\Sigma_{\mathbb{Q}'}$. Note that these eigenvalues satisfy

$$\beta'_i = \frac{\sigma^2}{\sigma^2 + \alpha^2 \lambda'_i}$$

where λ'_i are eigenvalues of NTK. $\qquad \square$

Remark B.2 (Function-preserving scale transformation to NTK)**.** *In contrast to the CTK, the scale invariance property is not applicable to the NTK due to the Jacobian w.r.t. parameter:*

$$\mathbf{J}_\theta(x, \mathcal{T}(\psi)) = \frac{\partial}{\partial \mathcal{T}(\psi)} f(x, \mathcal{T}(\psi)) = \frac{\partial}{\partial \mathcal{T}(\psi)} f(x, \psi) = \mathbf{J}_\theta(x, \psi)\mathcal{T}^{-1}$$

If we assume all parameters are scale-invariant (or equivalently masking the Jacobian for all non-scale-invariant parameters as in the proof of Proposition 3.1), the scale of NTK is proportional to the inverse scale of parameters.

B.8 Deterministic limiting kernel of CTK

Theorem B.3 (Deterministic limiting kernel of CTK)**.** *Let us assume an L-layered network with a Lipschitz activation function and NN with NTK initialization. Then the empirical CTK converges in probability to a deterministic limiting kernel $\mathbf{C}_{xy}$ as the width of layers $n_1, \ldots, n_L \to \infty$ sequentially. Furthermore, $\mathbf{C}_{xy} = \Theta_{xy}$ holds.*

Proof. The proof is a modification to proof of convergence of NTK in Jacot et al. (2018) considering NTK initialization (i.e. standard Gaussian for all parameters). We provide proof by induction. For single layer network, The CTK is summed as:

$$(\mathbf{C}_{xx'})_{kk'} = \frac{1}{n_0}\sum_{i=1}^{n_0}\sum_{j=1}^{n_1} x_i x'_i \delta_{jk}\delta_{jk'} W_{ik} W_{ik'} + \beta^2 \sum_{j=1}^{n_1} \delta_{jk}\delta_{jk'}$$
$$\to (\Theta_{xx})_{kk'}$$

since the weight is sampled from standard Gaussian distribution, whose variance is 1, and the product of two (independent) random variables converge in probability converges to the product of converged values. If we assume CTK of l-th layer is converged to NTK of l-th layer in probability, then the convergence of the $(l+1)$-th layer is also satisfied since the multiplication of two random weights, which converges to 1, is multiplied to the empirical NTK of $(l+1)$-th layer, which converges to the deterministic limiting NTK of $(l+1)$-th layer. Therefore, empirical CTK converges in probability to the deterministic limiting CTK, which is equivalent to the deterministic limiting NTK. $\qquad \square$

C DETAILS OF SQUARED LOSS FOR CLASSIFICATION TASKS

For the classification tasks in Sec. 4.2, we use the squared loss instead of the cross-entropy loss since our theoretical results are built on the squared loss. Here, we describe how we use the squared loss to mimic the cross-entropy loss. There are several works (Lee et al., 2020; Hui & Belkin, 2021) that utilized the squared loss for the classification task instead of the cross-entropy loss. Specifically, Lee et al. (2020) used

$$\mathcal{L}(\mathcal{S}, \theta) = \frac{1}{2NK} \sum_{(x_i, y_i) \in \mathcal{S}} \|f(x_i, \theta) - y_i\|^2$$

where C is the number of classes, and Hui & Belkin (2021) used

$$\ell((x, c), \theta) = \frac{1}{2K} \left(k(f_c(x, \theta) - M)^2 + \sum_{i=1, i \neq c}^{K} f_i(x, \theta)^2 \right)$$

for single data loss, where $\ell((x, c), \theta)$ is sample loss given input x, target c and parameter θ, $f_i(x, \theta) \in \mathbb{R}$ is the i-th component of $f(x, \theta) \in \mathbb{R}^K$, k and M are dataset-specific hyper-parameters.

These works used the mean for reducing the vector-valued loss into a scalar loss. However, this can be problematic when the number of classes is large. When the number of classes increases, the denominator of the mean (the number of classes) increases while the target value remains 1 (one-hot label). As a result, the scale of a gradient for the target class becomes smaller. To avoid such an unfavorable effect, we use the sum for reducing vector-valued loss into a scalar loss instead of taking the mean, i.e.,

$$\ell((x, c), \theta) = \frac{1}{2} \left((f_c(x, \theta) - 1)^2 + \sum_{i=1, i \neq c}^{K} f_i(x, \theta)^2 \right)$$

This analysis is consistent with the hyper-parameter selection in Hui & Belkin (2021). They used larger k and M as the number of classes increases (e.g., $k = 1, M = 1$ for CIFAR-10 (Krizhevsky, 2009), but $k = 15, M = 30$ for ImageNet (Deng et al., 2009)) which results in manually compensating the scale of the gradient to the target class label.

D DERIVATION OF PAC-BAYES POSTERIOR

Derivation of $\mathbb{Q}_{\theta^*}(c)$

For Bayesian linear regression, we compute the posterior of $\beta \in \mathbb{R}^P$

$$y_i = x_i \beta + \epsilon_i, \quad \text{for } i = 1 \ldots, M$$

where $\epsilon_i \sim \mathcal{N}(0, \sigma^2)$ is i.i.d. sampled and the prior of β is given as $\beta \sim \mathcal{N}(\mathbf{0}_P, \alpha^2 \mathbf{I}_P)$. By concatenating this, we get

$$\mathbf{y} = \mathbf{X}\beta + \varepsilon$$

where $\mathbf{y} \in \mathbb{R}^M, \mathbf{X} \in \mathbb{R}^{M \times p}$ are concatenation of y_i, x_i, respectively and $\varepsilon \sim \mathcal{N}(\mathbf{0}_M, \sigma^2 \mathbf{I}_M)$. It is well known (Bishop, 2006; Murphy, 2012) that the posterior of β for this problem is

$$\beta \sim \mathcal{N}(\beta | \mu, \Sigma)$$
$$\mu := \frac{\Sigma \mathbf{X}^\top y}{\sigma^2}$$
$$\Sigma := \left(\frac{\mathbf{I}_P}{\alpha^2} + \frac{\mathbf{X}^\top \mathbf{X}}{\sigma^2} \right)^{-1}.$$

Similarly, we define the Bayesian linear regression problem as

$$y_i = f(x_i, \theta^*) + \mathbf{J}_\theta(x_i, \theta^*) \text{diag}(\theta^*) c + \epsilon_i, \quad \text{for } i = 1 \ldots, NK$$

where $M = NK$ and the regression coefficient is $\beta = c$ in this case. Thus, we treat $y_i - f(x_i, \theta^*)$ as a target and $\mathbf{J}_\theta(x_i, \theta^*)\text{diag}(\theta^*)$ as an input of linear regression problem. By concatenating this, we get

$$\mathcal{Y} = f(\mathcal{X}, \theta^*) + \mathbf{J}_c c + \varepsilon \Rightarrow (\mathcal{Y} - f(\mathcal{X}, \theta^*)) = \mathbf{J}_c c + \varepsilon.$$

By plugging this into the posterior of the Bayesian linear regression problem, we get

$$\mathbb{Q}_{\theta^*}(c) := \mathcal{N}(c | \mu_\mathbb{Q}, \Sigma_\mathbb{Q})$$

$$\mu_\mathbb{Q} := \frac{\Sigma_\mathbb{Q} \mathbf{J}_c^\top (\mathcal{Y} - f(\mathcal{X}, \theta^*))}{\sigma^2} = \frac{\Sigma_\mathbb{Q} \text{diag}(\theta^*) \mathbf{J}_\theta^\top (\mathcal{Y} - f(\mathcal{X}, \theta^*))}{\sigma^2}$$

$$\Sigma_\mathbb{Q} := \left(\frac{\mathbf{I}_P}{\alpha^2} + \frac{\mathbf{J}_c^\top \mathbf{J}_c}{\sigma^2} \right)^{-1} = \left(\frac{\mathbf{I}_P}{\alpha^2} + \frac{\text{diag}(\theta^*) \mathbf{J}_\theta^\top \mathbf{J}_\theta \text{diag}(\theta^*)}{\sigma^2} \right)^{-1}$$

Derivation of $\mathbb{Q}_{\theta^*}(\psi)$ We define perturbed parameter ψ as follows

$$\psi := \theta^* + \theta^* \odot c.$$

Since ψ is affine to c, we get the distribution of ψ as

$$\mathbb{Q}_{\theta^*}(\psi) := \mathcal{N}(\psi | \mu_\mathbb{Q}^\psi, \Sigma_\mathbb{Q}^\psi)$$

$$\mu_\mathbb{Q}^\psi := \theta^* + \theta^* \odot \mu_\mathbb{Q}$$

$$\Sigma_\mathbb{Q}^\psi := \text{diag}(\theta^*) \Sigma_\mathbb{Q} \text{diag}(\theta^*) = \left(\frac{\text{diag}(\theta^*)^{-2}}{\alpha^2} + \frac{\mathbf{J}_\theta^\top \mathbf{J}_\theta}{\sigma^2} \right)^{-1}$$

E REPRESENTATIVE CASES OF FUNCTION-PRESERVING SCALING TRANSFORMATIONS

Activation-wise rescaling transformation (Tsuzuku et al., 2020; Neyshabur et al., 2015a) For NNs with positive homogeneous (e.g., ReLU) activations, following holds for $\forall x \in \mathbb{R}^d, \gamma > 0$: $f(x, \theta) = f(x, \mathcal{R}_{\gamma,l,k}(\theta))$, where rescale transformation $\mathcal{R}_{\gamma,l,k}(\cdot)$[2] is defined as

$$(\mathcal{R}_{\gamma,l,k}(\theta))_i = \begin{cases} \gamma \cdot \theta_i & \text{, if } \theta_i \in \{\text{param. subset connecting as input edges to } k\text{-th activation at } l\text{-th layer}\} \\ \theta_i / \gamma & \text{, if } \theta_i \in \{\text{param. subset connecting as output edges to } k\text{-th activation at } l\text{-th layer}\} \\ \theta_i & \text{, for } \theta_i \text{ in the other cases} \end{cases}$$

(19)

Note that $\mathcal{R}_{\gamma,l,k}(\cdot)$ is a finer-grained rescaling transformation than layer-wise rescaling transformation (i.e., common γ for all activations in layer l) discussed in Dinh et al. (2017). Dinh et al. (2017) showed that even layer-wise rescaling transformations can sharpen pre-trained solutions in terms of the trace of Hessian (i.e., contradicting the FM hypothesis). This contradiction also occurs in previous PAC-Bayes bounds (Tsuzuku et al., 2020; Kwon et al., 2021) due to the scale-dependent term.

For example, let us assume a linear NN as

$$f(x, (\theta_1, \theta_2, \theta_3, \theta_4)) = (\theta_3, \theta_4)^\top \begin{pmatrix} \theta_1 \\ \theta_2 \end{pmatrix} x = \theta_1 \theta_3 x + \theta_2 \theta_4 x$$

Then, the Jacobian of this NN would be

$$\mathbf{J}_\theta(x, \theta) = \begin{pmatrix} \theta_3 x & \theta_4 x \\ \theta_1 x & \theta_2 x \end{pmatrix}$$

From above discussion, $(0.5, 1, 2, 1) = \mathcal{R}_{2,1,1}((1, 1, 1, 1))$ would change the Jacobian while maintaining the predictions. To show this,

$$f(x, (0.5, 1, 2, 1)) = f(x, (1, 1, 1, 1)) = x + x = 2x$$

---

[2]For a simple two layer linear NN $f(x) := W_2 \sigma(W_1 x)$ with weight matrix W_1, W_2, the first case of equation 19 corresponds to k-th row of W_1 and the second case of equation 19 corresponds to k-th column of W_2.

for all $x \in \mathbb{R}$. However,

$$\mathbf{J}_\theta(x, (0.5, 1, 2, 1)) = \begin{pmatrix} 2x & x \\ 0.5x & x \end{pmatrix} \neq \begin{pmatrix} x & x \\ x & x \end{pmatrix} = \mathbf{J}_\theta(x, (1, 1, 1, 1))$$

in general. Therefore, we verified that the activation-wise rescaling transformation $\mathcal{R}_{2,1,1}$ is a valid function-preserving scale transformation.

WD with BN layers ([Ioffe & Szegedy](), 2015) For parameters $W \in \mathbb{R}^{n_l \times n_{l-1}}$ preceding BN layer,

$$\mathrm{BN}((\mathrm{diag}(\gamma)W)u) = \mathrm{BN}(Wu) \tag{20}$$

for an input $u \in \mathbb{R}^{n_{l-1}}$ and a positive vector $\gamma \in \mathbb{R}_+^{n_l}$. This implies that scaling transformations on these parameters preserve function represented by NNs for $\forall x \in \mathbb{R}^d, \gamma \in \mathbb{R}_+^{n_l}$: $f(x, \theta) = f(x, \mathcal{S}_{\gamma,l,k}(\theta))$, where scaling transformation $\mathcal{S}_{\gamma,l,k}(\cdot)$ is defined for $i = 1, \ldots, P$

$$(\mathcal{S}_{\gamma,l,k}(\theta))_i = \begin{cases} \gamma_k \cdot \theta_i & \text{, if } \theta_i \in \{\text{param. subset connecting as input edges to } k\text{-th activation at } l\text{-th layer}\} \\ \theta_i & \text{, for } \theta_i \text{ in the other cases} \end{cases} \tag{21}$$

Note that the WD ([Loshchilov & Hutter](), 2019; [Zhang et al.](), 2019) can be implemented as a realization of $\mathcal{S}_{\gamma,l,k}(\cdot)$ (e.g., $\gamma = 0.9995$ for all activations preceding BN layers). Therefore, thanks to Proposition 2.1 and Theorem 2.4, our CTK-based bound is invariant to WD applied to parameters before BN layers. We also refer to ([Van Laarhoven](), 2017; [Lobacheva et al.](), 2021) for the optimization perspective of WD with BN.

For example, let us assume a BN layer with single activation as $\mathrm{BN}(\theta x)$ where $x, \theta \in \mathbb{R}$ and batch of input is given as $0, 0, 2, 2$. Then, the Jacobian of NN would be

$$\mathbf{J}_\theta(x, \theta) = \frac{x}{|\theta|}$$

as $f(x, \theta) = \frac{\theta x}{|\theta|}$ and the denominator is detached from backpropagation computation for auto-differentiation packages (e.g., TensorFlow, Pytorch, and JAX). From the above discussion, $0.9995 = \mathcal{S}_{0.9995,1,1}(1)$ would change the Jacobian while maintaining the predictions. To show this,

$$f(x, 1) = f(x, 0.9995) = x$$

for all inputs. On the other hand,

$$\mathbf{J}_\theta(x, 0.9995) = \frac{x}{0.9995} \neq x = \mathbf{J}_\theta(x, 1).$$

Therefore, we showed that the WD with BN layer $\mathcal{S}_{0.9995,1,1}$ is a valid function-preserving scale transformation.

F   IMPLEMENTATIONS

F.1   RTO IMPLEMENTATION OF CONNECTIVITY LAPLACE

To estimate the empirical/generalization bound in Sec. 2.4 and calibrate uncertainty in Sec. 4.2, we need to sample c from the posterior $\mathbb{Q}_{\theta^*}(c)$. For this, we sample perturbations δ in connectivity space

$$\delta \sim \mathcal{N}\left(\delta | \mathbf{0}_P, \left(\frac{\mathbf{I}_P}{\alpha^2} + \frac{\mathbf{J}_c^\top \mathbf{J}_c}{\sigma^2}\right)^{-1}\right)$$

so that $c = \mu_\mathbb{Q} + \delta$ for equation 6. To sample this, we provide a novel approach to sample from LA/CL without curvature approximation. To this end, we consider the following optimization problem

$$\arg\min_c L(c) := \arg\min_c \frac{1}{2N\sigma^2}\|\mathcal{Y} - f(\mathcal{X}, \theta^*) - \mathbf{J}_c c + \varepsilon\|^2 + \frac{1}{2N\alpha^2}\|c - c_0\|_2^2$$

Algorithm 1 Connectivity Laplace RTO

Require: training data $\mathcal{S}$, pre-trained parameter θ^*, number of samples M, prior scale α, observational noise scale σ
  for $m = 1, \ldots, M$ **do**
    Sample parameter noise $c_0^m \sim \mathcal{N}(c_0|\mathbf{0}_P, \alpha^2\mathbf{I}_P)$ and label noise $\varepsilon^m \sim \mathcal{N}(\varepsilon|\mathbf{0}_{NK}, \sigma^2\mathbf{I}_{NK})$
    for $t = 1, \ldots, T$ **do**
      Randomly draw a mini-batch $\mathcal{B}$ from $\mathcal{S}$.
      Define $g_{\theta^*}^{\mathrm{lin}}(\mathcal{X}_{\mathcal{B}}, c^m) = f(\mathcal{X}_{\mathcal{B}}, \theta^*) + \mathbf{J}_\theta(\mathcal{X}_{\mathcal{B}}, \theta^*)\mathrm{diag}(\theta^*)c^m$ for mini-batch input $\mathcal{X}_{\mathcal{B}}$.
      Define $L(c^m) = \frac{1}{2|\mathcal{B}|\sigma^2}\|\mathcal{Y}_{\mathcal{B}} + \varepsilon_{\mathcal{B}}^m - g_{\theta^*}^{\mathrm{lin}}(\mathcal{X}_{\mathcal{B}}, c^m)\|_2^2 + \frac{1}{2|\mathcal{B}|\alpha^2}\|c^m - c_0^m\|_2^2$.
      Compute backpropagation of $L(c^m)$ w.r.t. connectivity c^m.
      Update c^m with SGD optimizer.
    end for
  end for
  return Samples from Connectivity Laplace $\{c^m\}_{m=1}^M$.

---

where $\varepsilon \sim \mathcal{N}(\varepsilon|\mathbf{0}_{NK}, \sigma^2\mathbf{I}_{NK})$ and $c_0 \sim \mathcal{N}(c_0|\mathbf{0}_P, \alpha^2\mathbf{I}_P)$. By first-order optimality condition, we have

$$N\nabla_c L(c) = -\frac{\mathbf{J}_c^\top(\mathcal{Y} - f(\mathcal{X}, \theta^*) - \mathbf{J}_c c^* + \varepsilon)}{\sigma^2} + \frac{c^* - c_0}{\alpha^2} = \mathbf{0}_P.$$

By arranging this w.r.t. optimizer c^*, we get

$$c^* = \left(\mathbf{J}_c^\top\mathbf{J}_c + \frac{\sigma^2}{\alpha^2}\mathbf{I}_P\right)^{-1}\left(\mathbf{J}_c^\top(\mathcal{Y} - f(\mathcal{X}, \theta^*)) + \frac{\sigma^2}{\alpha^2}c_0 + \mathbf{J}_c\varepsilon\right)$$

$$= \left(\mathbf{J}_c^\top\mathbf{J}_c + \frac{\sigma^2}{\alpha^2}\mathbf{I}_P\right)^{-1}\mathbf{J}_c^\top(\mathcal{Y} - f(\mathcal{X}, \theta^*)) + \left(\mathbf{J}_c^\top\mathbf{J}_c + \frac{\sigma^2}{\alpha^2}\mathbf{I}_P\right)^{-1}\left(\frac{\sigma^2}{\alpha^2}c_0 + \mathbf{J}_c\varepsilon\right)$$

$$= \underbrace{\left(\frac{\mathbf{I}_P}{\alpha^2} + \frac{\mathbf{J}_c^\top\mathbf{J}_c}{\sigma^2}\right)^{-1}\frac{\mathbf{J}_c^\top(\mathcal{Y} - f(\mathcal{X}, \theta^*))}{\sigma^2}}_{\text{Deterministic}} + \underbrace{\left(\frac{\mathbf{I}_P}{\alpha^2} + \frac{\mathbf{J}_c^\top\mathbf{J}_c}{\sigma^2}\right)^{-1}\left(\frac{c_0}{\alpha^2} + \frac{\mathbf{J}_c^\top\varepsilon}{\sigma^2}\right)}_{\text{Stochastic}}$$

Since both ε and c_0 are sampled from independent Gaussian distributions, we have

$$z := \left(\frac{c_0}{\alpha^2} + \frac{\mathbf{J}_c^\top\varepsilon}{\sigma^2}\right) \sim \mathcal{N}\left(z|\mathbf{0}_P, \frac{\mathbf{I}_P}{\alpha^2} + \frac{\mathbf{J}_c^\top\mathbf{J}_c}{\sigma^2}\right)$$

Therefore, optimal solution of randomized optimization problem $\arg\min_c L(c)$ is

$$c \sim \mathcal{N}\left(c\left|\left(\frac{\mathbf{I}_P}{\alpha^2} + \frac{\mathbf{J}_c^\top\mathbf{J}_c}{\sigma^2}\right)^{-1}\frac{\mathbf{J}_c^\top(\mathcal{Y} - f(\mathcal{X}, \theta^*))}{\sigma^2}, \left(\frac{\mathbf{I}_P}{\alpha^2} + \frac{\mathbf{J}_c^\top\mathbf{J}_c}{\sigma^2}\right)^{-1}\right)\right. = \mathcal{N}(c|\mu_{\mathbb{Q}}, \Sigma_{\mathbb{Q}})$$

Similarly, sampling from CL can be implemented as the following optimization problem.

$$\arg\min_c L(c) := \arg\min_c \frac{1}{2N\sigma^2}\|\mathbf{J}_c c - \varepsilon\|^2 + \frac{1}{2N\alpha^2}\|c - c_0\|_2^2$$

where $\varepsilon \sim \mathcal{N}(\varepsilon|\mathbf{0}_{NK}, \sigma^2\mathbf{I}_{NK})$ and $c_0 \sim \mathcal{N}(c_0|\mathbf{0}_P, \alpha^2\mathbf{I}_P)$. Since we sample the noise of data/perturbation and optimize the perturbation, this can be interpreted as a Randomize-Then-Optimize implementation of Laplace Approximation and Connectivity Laplace (Bardsley et al., 2014; Matthews et al., 2017). In Algorithm 1, we provide a pseudo-code for the RTO implementation of CL. Note that both time and memory complexity of computing linearized NN for mini-batch $\mathcal{B}$ is comparable to a forward propagation as shown in Novak et al. (2022) with `jax.jvp` function in JAX (Bradbury et al., 2018). Therefore, the time/memory complexity of mini-batch JVP would be $\mathcal{O}(|\mathcal{B}|LW^2)/\mathcal{O}(|\mathcal{B}|W + LW^2 + NK)$ for MLPs with width W and depth L.

Algorithm 2 Hutchison's method for computing Connectivity sharpness

---

Require: training data $\mathcal{S}$, pre-trained parameter θ^*, number of samples M
   $x_{\mathcal{B}} = 0$
   for $m = 1, \ldots, M$ **do**
      Sample $z^m \sim \mathcal{N}(\varepsilon | \mathbf{0}_{NK}, \sigma^2 \mathbf{I}_{NK})$
      for $t = 1, \ldots, T$ **do**
         Sequentially draw a mini-batch $\mathcal{B}$ from $\mathcal{S}$.
         Compute vector-Jacobian product $v_{\mathcal{B}}^m = z_{\mathcal{B}}^m \mathbf{J}_\theta(\mathcal{X}, \theta^*) \mathrm{diag}(\theta^*)$.
         Compute $x_{\mathcal{B}} = x_{\mathcal{B}} + \|v_{\mathcal{B}}^m\|_2^2 / T$
      end for
   end for
   return Estimated Connectivity Sharpness $x_{\mathcal{B}}$

F.2   COMPUTING CONNECTIVITY SHARPNESS

It is well known that empirical NTK or Jacobian is intractable in the modern architecture of NNs (e.g., ResNet (He et al., 2016) or BERT (Devlin et al., 2018)). Therefore, one might wonder how Connectivity Sharpness can be computed for these architectures. However, Connectivity Sharpness in Sec. 2.5 is defined as a trace of empirical CTK, thereby one can compute CS with Hutchison's method (Hutchinson, 1989; Meyer et al., 2021). According to Hutchison's method, trace of a matrix $A \in \mathbb{R}^{m \times m}$ is

$$\mathrm{tr}(A) = \mathrm{tr}(A\mathbf{I}_p) = \mathrm{tr}(A\mathbb{E}_z[zz^\top]) = \mathbb{E}_z[\mathrm{tr}(Azz^\top)] = \mathbb{E}_z[\mathrm{tr}(z^\top Az)] = \mathbb{E}_z[z^\top Az]$$

where $z \in \mathbb{R}^m$ is a random variable with $\mathrm{cov}(z) = \mathbf{I}_m$ (e.g., standard normal distribution or Rademacher distribution). Since $A = \mathbf{C}_{\mathcal{X}}^{\theta^*} = \mathbf{J}_c(\mathcal{X}, \mathbf{0}_p) \mathbf{J}_c(\mathcal{X}, \mathbf{0}_p)^\top \in \mathbb{R}^{NK}$ in our case, we further use mini-batch approximation to compute $z^\top Az$: (i) Sample $z_{\mathcal{B}}^m \in \mathbb{R}^{MK}$ from Rademacher distribution for mini-batch $\mathcal{M}$ with size M and (ii) compute $v_{\mathcal{B}}^m := \mathbf{J}_c(\mathcal{X}_{\mathcal{B}}, \mathbf{0}_p)^\top z_{\mathcal{B}}^m \in \mathbb{R}^P$ with Jacobian-vector product of JAX (Bradbury et al., 2018) and (iii) compute $x_{\mathcal{B}}^m = \|v_{\mathcal{B}}^m\|_2^2$. Then, the sum of $x_{\mathcal{B}}^m$ for all mini-batch in the training dataset is a Monte-Carlo approximation of CS with sample size 1. Empirically, we found that this approximation is sufficiently stable to capture the correlation between sharpness and generalization as shown in Sec. 4.1. In Algorithm 2, we provide a pseudo-code for the implementation. Note that both time and memory complexity of computing $v_{\mathcal{B}}^m$ is comparable to a backward propagation as shown in Novak et al. (2022) with `jax.vjp` function in JAX (Bradbury et al., 2018). Therefore, the time/memory complexity of mini-batch VJP would be $\mathcal{O}(|\mathcal{B}|LW^2)/\mathcal{O}(|\mathcal{B}|LW + LW^2 + NKW)$ for MLPs with width W and depth L.

G   PREDICTIVE UNCERTAINTY OF CONNECTIVITY/LINEARIZED LAPLACE

In this section, we derive predictive uncertainty of Linearized Laplace (LL) and Connectivity Laplace (CL). By matrix inversion lemma (Woodbury, 1950), the weight covariance of LL is

$$(\mathbf{I}_p/\alpha^2 + \mathbf{J}_\theta(\mathcal{X}, \theta^*)^\top \mathbf{J}_\theta(\mathcal{X}, \theta^*)/\sigma^2)^{-1} = \alpha^2 \mathbf{I}_p - \alpha^2 \mathbf{J}_\theta(\mathcal{X}, \theta^*)^\top (\frac{\sigma^2}{\alpha^2}\mathbf{I}_{Nk} + \Theta_{\mathcal{X}\mathcal{X}}^{\theta^*})^{-1} \mathbf{J}_\theta(\mathcal{X}, \theta^*).$$

Therefore, if $\sigma^2/\alpha^2 \to 0$, then the weight covariance of LL converges to

$$\alpha^2 \mathbf{I}_p - \alpha^2 \mathbf{J}_\theta(\mathcal{X}, \theta^*)^\top \Theta_{\mathcal{X}\mathcal{X}}^{\theta^* -1} \mathbf{J}_\theta(\mathcal{X}, \theta^*).$$

With this weight covariance and linearized NN, the predictive uncertainty of LL is

$$f_{\theta^*}^{\mathrm{lin}}(x, \theta)|p_{\mathrm{LA}}(\theta|\mathcal{S}) \sim \mathcal{N}(f(x, \theta^*), \alpha^2 \Theta_{xx}^{\theta^*} - \alpha^2 \Theta_{x\mathcal{X}}^{\theta^*} \Theta_{\mathcal{X}\mathcal{X}}^{\theta^* -1} \Theta_{\mathcal{X}x}^{\theta^*}).$$

Similarly, the predictive uncertainty of CL is

$$f_{\theta^*}^{\mathrm{lin}}(x, \theta)|\mathbb{Q}_{\theta^*}(\theta) \sim \mathcal{N}(f(x, \theta^*), \alpha^2 \mathbf{C}_{xx}^{\theta^*} - \alpha^2 \mathbf{C}_{x\mathcal{X}}^{\theta^*} \mathbf{C}_{\mathcal{X}\mathcal{X}}^{\theta^* -1} \mathbf{C}_{\mathcal{X}x}^{\theta^*}).$$

H   DETAILED EXPERIMENTAL SETTINGS

H.1   BOUND ESTIMATION

We pre-train ResNet-18 (He et al., 2016) with a mini-batch size of 1K on $\mathcal{S}_{\mathbb{P}}$ with SGD of initial learning rate 0.4 and momentum 0.9. We use cosine annealing for learning rate scheduling (Loshchilov & Hutter, 2016) with a warmup for the initial 10% training step. We fix $\delta = 0.1$, $\alpha = 0.1$, and $\sigma = 1.0$ to compute equation 8. These values are chosen so that the PAC-Bayes-CTK and NTK bounds fall within the non-vacuous range. We use 3 random seeds to compute the error bars. Additional results on few pre-training data with $N_{\mathbb{P}} = 5,000$ and $N_{\mathbb{Q}} = 45,000$ are presented in Appendix I.

H.2   CONNECTIVITY SHARPNESS

Table 6: Configuration of hyper-parameter

network depth	1, 2, 3
network width	32, 64, 128
learning rate	0.1, 0.032, 0.001
WD	0.0, 1e-4, 5e-4
mini-batch size	256, 1024, 4096

To verify that the CS has a better correlation with generalization performance compared to existing sharpness measures, we evaluate the three metrics: (a) Kendall's rank-correlation coefficient τ (Kendall, 1938) which considers the consistency of a sharpness measure with generalization gap (i.e., if one has higher sharpness, then so has higher generalization gap) (b) granulated Kendall's coefficient (Jiang et al., 2020) which examines Kendall's rank-correlation coefficient w.r.t. individual hyper-parameters to separately evaluate the effect of each hyper-parameter to generalization gap (c) conditional independence test (Jiang et al., 2020) which captures the causal relationship between measure and generalization.

Three metrics are compared with the following baselines: trace of Hessian ($\mathrm{tr}(\mathbf{H})$; (Keskar et al., 2017)), trace of Fisher information matrix ($\mathrm{tr}(\mathbf{F})$; (Jastrzebski et al., 2021)), trace of empirical NTK at θ^* ($\mathrm{tr}(\mathbf{\Theta}^{\theta^*})$), and four PAC-Bayes bound based measures, sharpness-orig (SO), PAC-Bayes-orig (PO), $1/\alpha'$ sharpness mag (SM), and $1/\sigma'$ PAC-Bayes mag (PM), which are eq. (52), (49), (62), (61) in Jiang et al. (2020).

For the granulated Kendall's coefficient, we use 5 hyper-parameters: network depth, network width, learning rate, WD and mini-batch size, along with 3 options for each hyper-parameters as in Table 6. We use the VGG-13 (Simonyan & Zisserman, 2015) as a base model and we adjust the depth and width of each conv block. We add BN layers after the convolution layer for each block. Specifically, the number of convolution layers of each conv block is the depth and the number of channels of convolution layers of the first conv block is the width. For the subsequent conv blocks, we follow the original VGG width multipliers ($\times 2$, $\times 4$, $\times 8$). An example with depth 1 and width 128 is depicted in Table 7.

We use an SGD optimizer with momentum of 0.9. We train each model for 200 epochs and use cosine learning rate scheduler (Loshchilov & Hutter, 2016) with 30% of initial epochs as warm-up epochs. The standard data augmentations (padding, random crop, random horizontal flip, and normalization) for CIFAR-10 are used for training data. For the analysis, we only use models with above 99% training accuracy following Jiang et al. (2020). As a result, we use 200 out of 243 trained models for our correlation analysis. For every experiment, we use 8 NVIDIA RTX 3090 GPUs.

H.3   BNN EXPERIMENTS

UCI regression We train MLP with a single hidden layer. We fix $\sigma = 1$ and choose α from {0.01, 0.1, 1, 10, 100} using log-likelihood of validation dataset since the optimal α varies for each regression dataset. We use 8 random seeds to compute the average and standard error of the test negative log-likelihoods.

Table 7: Example of network configuration with respect to the depth 1, width 128 in (Simonyan & Zisserman, 2015)-style.

ConvNet Configuration
input (224 × 224 RGB image)
Conv3-128
BN
ReLU
MaxPool
Conv3-256
BN
ReLU
MaxPool
Conv3-512
BN
ReLU
MaxPool
Conv3-1024
BN
ReLU
MaxPool
Conv3-1024
BN
ReLU
MaxPool
FC-4096
ReLU
FC-4096
ReLU
FC-1000

Image classification task We pre-train models for 200 epochs CIFAR-10/100 dataset (Krizhevsky, 2009) with ResNet-18(He et al., 2016) as mentioned in Section 2.4. We choose ensemble size M as 8 except Deep Ensemble (Lakshminarayanan et al., 2017) and Batch Ensemble (Wen et al., 2020). We use 4 ensemble members for Deep Ensemble and Batch Ensemble due to computational cost. We used 4 random seeds to compute the error bars except for Deep Ensemble, which ensembles the NNs from 4 different random seeds.

For evaluation, we define a prediction of single-member as the one-hot representation of network output with label smoothing. We select the label smoothing coefficient as 0.01 for CIFAR-10 and 0.1 for CIFAR-100. We define ensemble prediction as an averaged prediction of single-member predictions. For OOD detection, we use the variance of prediction in output space, which is competitive to recent OOD detection methods (Ren et al., 2019; Van Amersfoort et al., 2020). We use 0.01 for σ and select the best α with cross-validation. For every experiment, we used 8 NVIDIA RTX 3090 GPUs.

I ADDITIONAL RESULTS ON BOUND ESTIMATION

J ADDITIONAL RESULTS ON IMAGE CLASSIFICATION

Table 8: Results for experiments on PAC-Bayes-CTK/NTK estimation with $N_\mathbb{P} = 5,000$ and $N_\mathbb{Q} = 45,000$. We use 4 random seeds to compute error bars.

CIFAR-10	PAC-Bayes-CTK				PAC-Bayes-NTK			
Parameter scale	0.5	1.0	2.0	4.0	0.5	1.0	2.0	4.0
Trace	13041 ± 1340	13064 ± 1344	13057 ± 1344	13061 ± 1344	5413637 ± 325789	1394973 ± 90592	545037 ± 6304	488604 ± 8954
Perturbation	335.0157 ± 9.5699	338.8471 ± 9.3901	337.2096 ± 9.4698	335.8712 ± 8.3927	202.5342 ± 3.1387	315.9919 ± 2.7542	447.9744 ± 3.7511	549.3535 ± 7.6435
Sharpness	13.4824 ± 0.6300	13.4927 ± 0.6291	13.4908 ± 0.6305	13.4941 ± 0.6290	64.6953 ± 0.5463	52.5450 ± 0.5820	44.2475 ± 0.1142	42.2973 ± 0.2046
KL	174.2491 ± 5.0337	176.1699 ± 4.9428	175.3502 ± 4.9896	174.6827 ± 4.4582	133.6147 ± 1.4843	184.2685 ± 1.2386	246.1109 ± 1.8574	295.8254 ± 3.8179
Test err.	0.2375 ± 0.0017	0.2387 ± 0.0019	0.2394 ± 0.0022	0.2394 ± 0.0022	0.3133 ± 0.0030	0.2799 ± 0.0020	0.2615 ± 0.0022	0.2564 ± 0.0020
Bound	0.2771 ± 0.0015	0.2782 ± 0.0017	0.2784 ± 0.0017	0.2785 ± 0.0017	0.3359 ± 0.0025	0.3059 ± 0.0010	0.2966 ± 0.0014	0.2998 ± 0.0018
CIFAR-100	PAC-Bayes-CTK				PAC-Bayes-NTK			
Parameter scale	0.5	1.0	2.0	4.0	0.5	1.0	2.0	4.0
Trace	22168 ± 1431	22156 ± 1438	22167 ± 1426	22166 ± 1431	6557644 ± 234835	1670224 ± 57783	570114 ± 39210	505707 ± 47096
Perturbation	447.8628 ± 12.4974	447.8570 ± 8.4664	445.7568 ± 7.7510	446.9493 ± 8.0771	399.6581 ± 10.4402	622.1746 ± 27.9164	790.6263 ± 46.7006	823.0565 ± 55.5815
Sharpness	17.1074 ± 0.3992	17.1027 ± 0.4024	17.1075 ± 0.3973	17.1067 ± 0.3986	66.3580 ± 0.2726	54.1271 ± 0.2521	44.4671 ± 0.5871	42.6411 ± 0.7865
KL	232.4851 ± 6.1763	232.4799 ± 4.1645	231.4321 ± 3.7885	232.0280 ± 3.9391	233.0081 ± 5.2640	338.1509 ± 13.9632	417.5467 ± 23.0571	432.8488 ± 27.4084
Test err.	0.6507 ± 0.0033	0.6515 ± 0.0038	0.6521 ± 0.0039	0.6522 ± 0.0039	0.6992 ± 0.0050	0.6903 ± 0.0038	0.6837 ± 0.0049	0.6863 ± 0.0050
Bound	0.7098 ± 0.0035	0.7104 ± 0.0038	0.7107 ± 0.0038	0.7110 ± 0.0039	0.7110 ± 0.0027	0.6971 ± 0.0059	0.7144 ± 0.0062	0.7361 ± 0.0049

Table 9: Uncertainty calibration results on CIFAR-10 (Krizhevsky, 2009) for ResNet-18 (He et al., 2016).

	CIFAR-10			
	NLL ($\downarrow$)	ECE ($\downarrow$)	Brier. ($\downarrow$)	AUC ($\uparrow$)
Deterministic	0.3135 ± 0.0088	0.0350 ± 0.0014	0.0875 ± 0.0026	-
MCDO	0.2845 ± 0.0148	0.0157 ± 0.0012	0.1056 ± 0.0062	0.9172 ± 0.0074
MCBN	0.2922 ± 0.0074	0.0325 ± 0.0010	0.0838 ± 0.0022	0.9431 ± 0.0033
Batch Ensemble	0.2740 ± 0.0030	0.0286 ± 0.0005	0.0814 ± 0.0009	0.9376 ± 0.0036
Deep Ensemble	0.1753	0.0067	0.0594	0.8527
Linearized Laplace	0.2077 ± 0.0032	0.0180 ± 0.0009	0.0816 ± 0.0010	0.8991 ± 0.0198
Connectivity Laplace (Ours)	0.2089 ± 0.0023	0.0120 ± 0.0019	0.0720 ± 0.0011	0.9705 ± 0.0098

Table 10: Uncertainty calibration results on CIFAR-10 (Krizhevsky, 2009) for VGG-13 (Simonyan & Zisserman, 2015).

	CIFAR-10			
	NLL ($\downarrow$)	ECE ($\downarrow$)	Brier. ($\downarrow$)	AUC ($\uparrow$)
Deterministic	0.4086 ± 0.0018	0.0490 ± 0.0003	0.1147 ± 0.0005	-
MCDO	0.3889 ± 0.0049	0.0465 ± 0.0009	0.1106 ± 0.0015	0.7765 ± 0.0221
MCBN	0.3852 ± 0.0012	0.0462 ± 0.0002	0.1108 ± 0.0003	0.9051 ± 0.0065
Batch Ensemble	0.3544 ± 0.0036	0.0399 ± 0.0009	0.1064 ± 0.0012	0.9067 ± 0.0030
Deep Ensemble	0.2243	0.0121	0.0776	0.7706
Linearized Laplace	0.3366 ± 0.0013	0.0398 ± 0.0004	0.1035 ± 0.0003	0.8883 ± 0.0017
Connectivity Laplace (Ours)	0.2674 ± 0.0028	0.0234 ± 0.0011	0.0946 ± 0.0010	0.9002 ± 0.0033

Table 11: Uncertainty calibration results on CIFAR-100 (Krizhevsky, 2009) for VGG-13 (Simonyan & Zisserman, 2015).

	CIFAR-100			
	NLL ($\downarrow$)	ECE ($\downarrow$)	Brier. ($\downarrow$)	AUC ($\uparrow$)
Deterministic	1.8286 ± 0.0066	0.1544 ± 0.0010	0.4661 ± 0.0018	-
MCDO	1.7439 ± 0.0089	0.1363 ± 0.0008	0.4456 ± 0.0017	0.6424 ± 0.0099
MCBN	1.7491 ± 0.0075	0.1399 ± 0.0010	0.4488 ± 0.0015	0.7039 ± 0.0197
Batch Ensemble	1.6142 ± 0.0101	0.1077 ± 0.0020	0.4143 ± 0.0027	0.7232 ± 0.0021
Deep Ensemble	1.2006	0.0456	0.3228	0.6929
Linearized Laplace	1.5806 ± 0.0054	0.1036 ± 0.0004	0.4127 ± 0.0010	0.6893 ± 0.0221
Connectivity Laplace (Ours)	1.4073 ± 0.0039	0.0703 ± 0.0028	0.3827 ± 0.0012	0.7254 ± 0.0136

K TRANSPOSED TABLE 3

Table 12

		boston_housing	concrete_strength	energy_efficiency	kin8nm	naval_propulsion	power_plant	protein_structure	wine	yacht_hydrodynamics
Original	Deep Ensemble	2.90 ± 0.03	3.06 ± 0.01	0.74 ± 0.01	-1.07 ± 0.00	-4.83 ± 0.00	2.81 ± 0.00	2.89 ± 0.00	1.21 ± 0.00	1.26 ± 0.04
	MCDO	2.63 ± 0.01	3.20 ± 0.00	1.92 ± 0.01	-0.80 ± 0.01	-3.85 ± 0.00	2.91 ± 0.00	2.96 ± 0.00	0.96 ± 0.01	2.17 ± 0.06
	LL	**2.85 ± 0.01**	3.22 ± 0.01	2.12 ± 0.01	-0.90 ± 0.00	-4.57 ± 0.00	2.91 ± 0.00	2.91 ± 0.00	**1.24 ± 0.01**	**1.20 ± 0.04**
	CL	2.88 ± 0.02	**3.11 ± 0.02**	**0.83 ± 0.01**	**-1.07 ± 0.00**	**-4.76 ± 0.00**	**2.81 ± 0.00**	**2.89 ± 0.00**	1.27 ± 0.01	1.25 ± 0.04
GAP variants	Deep Ensemble	2.71 ± 0.01	4.03 ± 0.07	0.77 ± 0.01	-0.94 ± 0.00	-2.22 ± 0.33	2.91 ± 0.00	3.11 ± 0.00	1.48 ± 0.01	1.71 ± 0.03
	MCDO	2.68 ± 0.01	3.42 ± 0.00	1.78 ± 0.01	-0.71 ± 0.00	-3.36 ± 0.01	2.97 ± 0.00	3.07 ± 0.00	1.03 ± 0.00	3.06 ± 0.02
	LL	**2.74 ± 0.01**	**3.47 ± 0.01**	2.02 ± 0.01	-0.87 ± 0.00	-3.66 ± 0.11	2.98 ± 0.00	**3.07 ± 0.00**	1.45 ± 0.01	1.78 ± 0.02
	CL	2.75 ± 0.01	4.03 ± 0.02	0.90 ± 0.02	**-0.93 ± 0.00**	**-3.80 ± 0.07**	**2.91 ± 0.00**	3.13 ± 0.00	**1.43 ± 0.00**	**1.74 ± 0.01**