ECONOMIC HYPERPARAMETER OPTIMIZATION WITH BLENDED SEARCH STRATEGY

ABSTRACT

We study the problem of using low cost to search for hyperparameter configurations in a large search space with heterogeneous evaluation cost and model quality. We propose a blended search strategy to combine the strengths of global and local search, and prioritize them on the fly with the goal of minimizing the total cost spent in finding good configurations. Our approach demonstrates robust performance for tuning both tree-based models and deep neural networks on a large AutoML benchmark, as well as superior performance in model quality, time, and resource consumption for a production NLP model fine-tuning task.

1 INTRODUCTION

Hyperparameter optimization (HPO) of modern machine learning models is a resource-consuming task, which is unaffordable to individuals or organizations with little resource (Yang & Shami, 2020). Operating HPO in a low-cost regime has numerous benefits, such as democratizing ML techniques, enabling new applications of ML, which requires frequent low-latency tuning, and reducing the carbon footprint. It is inherently challenging due to the nature of the task: trying a large number of configurations of *heterogeneous* cost and accuracy in a large search space. The expense can accumulate from multiple sources: either a large number of individually cheap trials or a small number of expensive trials can add up the required resources.

There have been multiple attempts to address the efficiency of HPO from different perspectives. Each of them has strengths and limitations. For example, Bayesian optimization (BO) (Brochu et al., 2010), which is a class of global optimization algorithms, is used to minimize the total number of iterations to reach global optima. However, when the cost of different hyperparameter configurations is heterogeneous, vanilla BO may select a configuration that incurs unnecessarily high cost. As opposed to BO, local search (LS) methods (Wu et al., 2020) are able to control total cost by preventing very expensive trials until necessary, but they may get trapped in local optima. Multi-fidelity methods (Jamieson & Talwalkar, 2016) aim to use cheap proxies to replace some of the expensive trials and approximate the accuracy assessment, but can only be used when such proxies exist. A single search strategy is difficult to meet the generic goal of economic HPO.

In this work, we propose a blended search strategy which combines global search and local search strategy such that we can enjoy benefits from both worlds: (1) global search can ensure the convergence to the global optima when the budget is sufficient; and (2) local search methods enable a better control on the cost incurred along the search trajectory. Given a particular global and local search method, our framework, which is named as `BlendSearch`, combines them according to the following design principles. (1) Instead of sticking with a particular method for configuration selection, we consider both of the candidate search methods and decide which one to use at each round of the configuration selection. (2) We use the global search method to help decide the starting points of local search threads. (3) We use the local search method to intervene the global search method's configuration selection to avoid configurations that may incur unnecessarily large evaluation cost. (4) We prioritize search instances of both methods according to their performance and efficiency of performance improvement on the fly. Extensive empirical evaluation on the AutoML Benchmark (Gijsbers et al., 2019a) validates the robust performance of our method under different time budgets, different tasks (e.g., different ML models), and a wide variety of datasets.

(a) Loss vs. evaluation time for configs tried by each method. One point represents one config. The lower is the loss the better is the quality of the config. Longer evaluation time corresponds to larger training cost

(b) Best loss vs. optimization time per method. Colored circles – configs proposed by LS threads in our method (color change indicates thread change); diamonds – configs proposed by BO in our method

Figure 1: A typical example of the different behaviors of BO, LS and our proposed `BlendSearch` in tuning a set of 11-dim hyperparameters for XGBoost. BO is prone to selecting expensive but not necessarily good configs. LS avoids expensive configs in the beginning but is prone to getting stuck in local regions. `BlendSearch` switches between one BO and multiple LS search threads and prioritizes the more promising ones, and turns out to try more low-cost, high-quality configs.

2 BACKGROUND AND RELATED WORK

We first briefly introduce the vanilla Bayesian optimization methods and local search methods, which are among the building blocks of our method. Bayesian optimization is a class of global optimization algorithms which is suitable for optimizing expensive black-box functions. It models the probabilistic distribution of the objective conditioned on the optimization variables. Typical models include Gaussian process (Snoek et al., 2012), random forest (Hutter et al., 2011), and tree Parzen estimator (TPE) (Bergstra et al., 2011). In BO methods, an acquisition function is used to determine the next point to evaluate. Two common acquisition functions are the expected improvement (EI) (Bull, 2011) over the currently best-observed objective and upper confidence bound (UCB) (Srinivas et al., 2009). Local search methods are prevalent in the general optimization literature (Spall et al., 1992; Nesterov & Spokoiny, 2017) but less studied in the HPO literature due to the possibility of getting trapped in local optima (György & Kocsis, 2011). Recent work (Wu et al., 2020) shows that a local search method FLOW^2 can make HPO cost-effective when combined with low-cost initialization and random restart. At each iteration, it samples a pair of vectors (with opposite directions) uniformly at random from a unit sphere, the center of which is the best configuration found so far (a.k.a. incumbent) and the radius of which is the current stepsize. Expensive configurations are avoided in the beginning as each iteration proposes a configuration near the incumbent. Random restart of the local search is performed once the convergence condition is satisfied.

There are several attempts to address the limitations of vanilla BO or local search methods. BOwLS (BO with local search) (Gao et al., 2019) uses a BO model to select the starting point of a local search thread. Each local search thread is run until convergence and the BO model is updated with the start point and the converged loss. Trust region BO (Eriksson et al., 2019) fits a collection of local models and performs a principled global allocation of samples across these models via an implicit bandit approach. It is primarily designed for HPO problems with high-dimensional numerical hyperparamters. Unfortunately, all existing work that tries to combine global search with local search methods does not consider the heterogeneity of evaluation cost incurred along with the search. There are also a lot of attempts in making HPO efficient by speeding up configuration evaluation. Multi-fidelity optimizations (Klein et al., 2017; Li et al., 2017; Kandasamy et al., 2017; Falkner et al., 2018; Lu et al., 2019; Li et al., 2020) are proposed for this purpose. They usually require an additional degree of freedom in the problem called 'fidelity', to allow performance assessment on a configuration with different fidelities. There is surprisingly little prior work for generic cost-effective HPO. Gaussian process with expected improvement per second (GPEIPS) (Snoek et al., 2012) models the evaluation cost using another Gaussian process, and heuristically adds the estimated cost into the acquisition function. It does not always outperform GPEI as the acquisition function can overpenalize good but expensive configurations.

Figure 2: Framework. Among the two paths from 'Config Evaluator', path 1 goes first.

3 BLENDSEARCH

Our framework needs the following information as inputs.

- B is the total budget of cost. In this work, we measure the cost by CPU/GPU time.
- P is the input HPO problem, which has the following attributes characterizing the problem.
  - $P.\mathcal{X}$ is the search space in which each element $\mathbf{x}$ is a d-dimensional hyperparameter configuration. For a non-categorical hyperparameter dimension $i \in [d]$, if different values of $\mathbf{x}_j$ lead to heterogeneous cost and there is a known value $P.x_j^{low}$ corresponding to a low cost, it is considered as a controlled dimension. We use $P.D$ to denote such a set of controlled dimensions.
  - $P.\texttt{LossFunc}(\cdot)$ is the loss function to be minimized in terms of the configurations $\mathbf{x} \in P.\mathcal{X}$.
  - $P.\texttt{CostFunc}(\cdot)$ is the cost function that outputs the cost incurred when evaluating $\mathbf{x}$.

  The goal of an HPO algorithm is to minimize the loss $P.\texttt{LossFunc}(\mathbf{x})$ with the constraint that the total cost incurred $G(\pi) \coloneqq \sum_{\mathbf{x} \in \mathcal{I}(\pi)} P.\texttt{CostFunc}(\mathbf{x}) \leq B$, where $\mathcal{I}(\pi)$ is the search trajectory of algorithm π. Note that both $P.\texttt{LossFunc}(\mathbf{x})$ and $P.\texttt{CostFunc}(\mathbf{x})$ are black-box functions meaning that typically the analytic form is not available, and only function values can be observed. In order to distinguish the operation of querying from loss/cost function and the loss/cost observation, we use $P.\texttt{LossFunc}(\mathbf{x})$ and $P.\texttt{CostFunc}(\mathbf{x})$ to denote the former, and use $l(\mathbf{x})$ and $c(\mathbf{x})$ to denote the latter. l and c (omitting $\mathbf{x}$) are used when there is no ambiguity.
- $\mathcal{G}$ is the global search method to be used. $\mathcal{L}$ is the local search method to be used. $\mathcal{L}.\Delta$ is the largest stepsize used in local search method $\mathcal{L}$, i.e., the largest possible change on a hyperparameter value between two consecutive search steps.

The overall design of our framework is presented in Figure 2 and Algorithm 1. The key idea is to maintain a pool of search threads, one of which corresponds to global search and the others local search. The pool starts with one global search thread and gradually adds local search threads as the search goes on. Here a search thread is an instance of a global search or local search method, each with its own search trajectory. At each round, a *search thread selector* selects one of the search threads from the pool according to a priority metric that reflects the search threads' current performance and efficiency of performance improvement. The selected search thread will then be used to propose a configuration to evaluate in this round. When the selected search thread is the global search thread, a *config validator* first checks whether the proposed configuration is within the 'admissible' region for evaluation. If not, it uses a backup local search thread instead. A local search thread will be created only when the global search thread proposes a valid config and a certain *create thread condition* is met, and will be deleted once it converges. Two local search threads will be merged into one if they are close enough. The priority of each search thread is updated after each evaluation round.

For convenience, we use $\mathcal{F}$ to denote a collection of framework-level variables:

Algorithm 1 `BlendSearch`

    Inputs: HPO problem P, a global search method $\mathcal{G}$, a local search method $\mathcal{L}$, total budget B.

1: **Initialization:** Initialize $\mathcal{F}.\mathbb{S} = [S_0]$ where S_0 is an instance of $\mathcal{G}$ with initial proposal $P.\mathbf{x}^{low}$ for the controlled dimensions.

2: **while** $\mathcal{F}.c < B$ **do**

3:      $\tilde{S}, \tilde{S}_{\text{bak}} \leftarrow$ `SelectThread`$(\mathcal{F})$

4:      $(\mathbf{x}, l, c) \leftarrow$ `SearchEvaluate1Step`$(\tilde{S}, \mathcal{F}, P)$

5:      **if** $\mathbf{x}$ is `invalid` **then** $(\mathbf{x}, l, c) \leftarrow$ `SearchEvaluate1Step`$(\tilde{S}_{\text{bak}}, \mathcal{F}, P)$

6:      **if** $\mathbf{x}$ is proposed by global search & `CreateNewLSCondition` is satisfied **then**

7:          Initialize $S =$ `InitializeSearchThread`$(\mathcal{L}, P, (\mathbf{x}, l, c))$

8:          Add the new LS thread S into the pool: $\mathcal{F}.\mathbb{S} \leftarrow \mathcal{F}.\mathbb{S} + S$

9:      `DeleteAndMergeLS`$(\mathcal{F})$ ▷ Merge or delete existing LS threads when necessary

10:     Update $\mathcal{F}$.`Priority`

11:     `UpdateGSModel`$(S_0, (\mathbf{x}, l, c))$ ▷ If applicable

- $\mathcal{F}.\mathbb{S}$ is the list of search threads maintained in our framework. There is one and only one global search thread, i.e., S_0, in $\mathcal{F}.\mathbb{S}$.
- $\mathcal{F}$.`Priority` is a priority dictionary, in which the keys are the search threads in $\mathcal{F}.\mathbb{S}$, and the values are the priority of the corresponding search threads.
- Bookkeeping information of $\mathcal{F}$: $\mathcal{F}.l^*$ is the best loss achieved among all the search threads and $\mathcal{F}.c$ is the total cost consumed in our framework.
- $\mathcal{F}.\mathcal{R}$ is the 'admissible' region on the controlled dimensions of the current search, which is a hyperrectangle and can be written in the form of $\mathcal{F}.\mathcal{R} := \{[\mathcal{F}.x_i^{\min}, \mathcal{F}.x_i^{\max}]\}_{i \in D}$ with $\mathcal{F}.x_i^{\min}$ and $\mathcal{F}.x_i^{\max}$ denoting the minimum and maximum value along the i-th dimension in $\mathcal{F}.\mathcal{R}$ respectively. They are initially set as $\mathcal{F}.x_i^{\min} = \mathcal{F}.x_i^{\max} = P.x_i^{low}$ for all $i \in D$. The 'admissible' region gradually expands during the search: (1) it is expanded to cover all the points evaluated by all the search threads and all the points that are possible to be reached by the local search within one search step, as shown in line 7 of Algorithm 2; (2) it expands if a local search thread converges, as shown in line 3 of Algorithm 7 (included in Appendix A).

In the following, we explain the key steps in our algorithm.

Step 1: Search thread selector (line 3 of Alg 1). In addition to the primary search thread $\tilde{S}$, `SelectThread` also outputs a backup search thread $\tilde{S}_{\text{bak}}$ which is guaranteed to be a local search thread (it is set to be none when there is no local search thread yet in $\mathcal{F}.\mathbb{S}$). Specifically,

$$\tilde{S} = \arg\max_{S \in \mathcal{F}.\mathbb{S}} \mathcal{F}.\text{Priority}(S), \tilde{S}_{\text{bak}} = \begin{cases} \arg\max_{S \in (\mathcal{F}.\mathbb{S} \setminus S_0)} \mathcal{F}.\text{Priority}(S) & \mathcal{F}.\mathbb{S} \setminus S_0 \neq \emptyset \\ S_0 & \mathcal{F}.\mathbb{S} \setminus S_0 = \emptyset, \end{cases}$$
(1)

To explain the priority metric, we need to introduce the following search thread level variables and functions for each search thread $S \in \mathcal{F}.\mathbb{S}$.

- Bookkeeping information of S: $S.l^{\text{1st}}$ and $S.l^{\text{2nd}}$ are the best loss and second best loss achieved so far. $S.c^{\text{1st}}$ and $S.c^{\text{2nd}}$ are the total (smallest) cost taken when $S.l^{\text{1st}}$ and $S.l^{\text{2nd}}$ are achieved respectively. $S.c$ is the total cost spent in S. $S.\mathbf{x}^{\text{1st}}$ is the best configuration found so far.
- $S.s$ is the performance improvement speed of S. It is calculated as $S.s = \frac{S.l^{\text{2nd}} - S.l^{\text{1st}}}{S.c - S.c^{\text{2nd}}}$. This formula is only valid when there is at least one improvement. Otherwise, we do not have enough information to estimate the speed of improvement. We set the speed to the highest speed of all the search threads when $S.l^{\text{2nd}} = S.l^{\text{1st}}$. It is due to an implicit assumption of diminishing return: the speed of improvement decreases as more resource is spent.
- $S.x^{\min}$ and $S.x^{\max}$ are the minimum and maximum value of the i-th dimension of all hyperparameters configurations evaluated in S respectively.
- $S.\text{CostImp}(\cdot)$ is a function whose input is a target loss and output is the anticipated cost for S to generate a better loss than this target. We use the following formula to compute it, which is intuitively using the cost for improvement in the past to estimate that in the future.

$$S.\texttt{CostImp}(l) = \begin{cases} \max\left\{S.c - S.c^{\text{1st}}, S.c^{\text{1st}} - S.c^{\text{2nd}}\right\} & S.l^{\text{1st}} = l \\ \max\left\{S.c - S.c^{\text{1st}}, S.c^{\text{1st}} - S.c^{\text{2nd}}, 2\frac{S.l^{\text{1st}} - l}{S.s}\right\} & S.l^{\text{1st}} \neq l \end{cases} \qquad (2)$$

Our proposed priority metric is essentially the negative of the projected loss of S:

$$\mathcal{F}.\texttt{Priority}(S) = -(S.l^{\text{1st}} - S.s \times b) \qquad (3)$$

in which $b = \min(\max_{S \in \mathcal{F}.\mathbb{S}} S.\texttt{CostImp}(\mathcal{F}.l^*), B - \mathcal{F}.c)$. $\max_{S \in \mathcal{F}.\mathbb{S}} S.\texttt{CostImp}(\mathcal{F}.l^*)$ can be considered as the resource needed for every S to have a better performance than the currently best performance $\mathcal{F}.l^*$. Our priority metric estimates the loss of each search thread if such an amount of resource (restricted by the budget left $B - \mathcal{F}.c$) is given. By considering both the search threads' current performance and potential improvement, it provides a fair trade-off between exploiting the currently-best and exploring the potentially-better choices.

Algorithm 2 `SearchEvaluate1Step`

Inputs: HPO problem P, search thread S, and $\mathcal{F}$
1: $\mathbf{x} \leftarrow S.\texttt{ProposeConfig}()$
2: **if** $S = S_0$ (i.e., S is the global search thread) & $\mathbf{x} \notin \mathcal{F}.\mathcal{R}$ **then** $\mathbf{x} \leftarrow$ `invalid`
3: **else** $l, c \leftarrow P.\texttt{LossFunc}(\mathbf{x}), P.\texttt{CostFunc}(\mathbf{x})$ ▷ Evaluate configuration $\mathbf{x}$
4: **if** $\mathbf{x} \neq$ `invalid` **then**
5:     `BookKeeping`$(S, \mathbf{x}, l, c, \mathcal{F})$ and update speed $S.s$,
6:     $\forall i \in P.D, S.x_i^{\min} \leftarrow \min\{\mathbf{x}_i, S.x_i^{\min}\}, \mathcal{F}.x_i^{\min} \leftarrow \min\{S.x_i^{\min} - \mathcal{L}.\Delta, \mathcal{F}.x_i^{\min}\}$,
7:     $\forall i \in P.D, S.x_i^{\max} \leftarrow \max\{\mathbf{x}_i, S.x_i^{\max}\}, \mathcal{F}.x_i^{\max} \leftarrow \max\{S.x_i^{\max} + \mathcal{L}.\Delta, \mathcal{F}.x_i^{\max}\}$
8: **Outputs:** $\mathbf{x}, l, c$

Step 2: Config validator and evaluator (line 4-5 of Alg 1). Once a search thread is selected, we use the function `SearchEvaluate1Step` detailed in Algorithm 2 to propose a configuration according to its search policy (line 1 of Alg 2). If the selected search thread $\tilde{S}$ is a global search thread, we decide whether to evaluate the proposed configuration $\mathbf{x}$ depending on whether it is within the current admissible region of our framework $\mathcal{F}.\mathcal{R}$ (line 2 of Alg 2). If not, this configuration is considered to be prone to incur unnecessarily high cost and will not be evaluated at this round. In this case, the output of this round of `SearchEvaluate1Step` will be marked as `invalid`. Then a backup search thread will be used to perform another round of `SearchEvaluate1Step` (line 5 of Alg 1). The backup search thread is selected according to Eq. (1). The backup thread $\tilde{S}_{\text{bak}}$ is guaranteed to be a local search thread as long as at least one local thread exists, and is set to be the global search thread otherwise. The config validator, on the one hand, helps avoid potentially high-cost evaluation and thus avoid creating local search threads from high-cost points until necessary; on the other hand, does not make our method only stuck on local searches because the admissible region $\mathcal{F}.\mathcal{R}$ is expanding according to its definition. Note that according to the definition of $\mathcal{F}.\mathcal{R}$, only the controlled dimensions of the hyperparameter configurations are subject to validation check.

Step 3: Search thread creator, updater and cleaner (line 6-11 of Alg 1). If the newly proposed configuration is a valid configuration proposed by global search, we consider creating a new local search thread using the proposed configuration as a starting point. To make sure the newly created local search thread is relatively good, we first check whether the proposed configuration's performance is better than at least half of the existing threads' performance (specified in the `CreateNewLSCondition`). If so, a new local search thread will be initialized and added to the active search thread pool $\mathbb{S}$. In `DeleteAndMergeLS`, we check whether a local search thread has converged according to the convergence condition of the specific local search method. If it is, the search thread will be removed from $\mathbb{S}$. In addition, we also go through all the local search threads to see whether the incumbent of a LS thread is reachable in one step by another LS thread with lower loss (ref. Appendix A). If so, the former LS thread will be deleted. When applicable, the observation tuple $(\mathbf{x}, l, c)$ is used to update the model of the global search method through function `UpdateGSModel`. For example, when the global search method is a Bayesian optimization method, the model is the surrogate model of the Bayesian optimization method.

Due to page limit, detailed pseudocode for several of the straightforward functions mentioned in our framework are provided in Appendix A, including `CreateNewLSCondition`, `DeleteAndMergeLS`, `InitializeSearchThread` and `BookKeeping`.

(a) credit, loss = 1-auc   (b) KDDCup09, loss = 1-auc   (c) volkert, loss = log-loss

Figure 3: Optimization performance curve for XGBoost. Lines correspond to the mean loss over 10 folds, and shades correspond to 95% confidence intervals.

4 EXPERIMENTS

We mainly evaluate `BlendSearch` with an AutoML benchmark (Gijsbers et al., 2019b). The AutoML benchmark consists of 39 tabular datasets that represent real-world data science classification problems, and includes datasets of all sizes, of different problem domains and with various levels of difficulty. As each dataset has 10 cross-validation folds, all the results reported in this paper are averaged over the 10 folds. With this benchmark, we are able to evaluate multiple HPO methods on a large number of datasets within a manageable computational budget, for tuning three machine learning libraries: XGBoost (Chen & Guestrin, 2016), LightGBM (Ke et al., 2017) and DeepTables[1]. The first two are popular libraries based on gradient boosted trees, and the third is an easy-to-use deep learning toolkit which utilizes latest research findings for tabular data. We chose them because gradient boosted trees and deep neural networks are the most frequent winners in data science competitions. XGBoost and LightGBM are less expensive to train in general, so we first run experiments for them (Section 4.1), and then run experiments for DeepTables on the datasets where they are worse than the best known performance in the benchmark (Section 4.2). As a real application, we report an NLP model fine tuning task for a production use case in Section 4.3. Finally, in Section 4.4 we perform ablation study to investigate the effectiveness of several important components of our framework. We include the following baselines in our experiments.

- BO (Akiba et al., 2019) – the Bayesian optimization baseline. We choose a modern HPO library Optuna and use the TPE sampler because of its flexibility in handling mixed continuous and discrete space and good peformance reported in existing work (Falkner et al., 2018).
- LS (Wu et al., 2020) – the recent baseline of using local search with random restart, based on `FLOW`[2]. It is proved to be able to control cost effectively and outperform BO methods for numerical cost-related hyperparameter search.
- BOwLS (Gao et al., 2019) – the baseline of an existing approach of combining local search with BO, i.e., using BO to propose start points for local search.
- Three state-of-the-art HPO methods that use multi-fidelity optimization, including asynchronous HyperBand (Li et al., 2017; 2020), BOHB (Falkner et al., 2018), which combines BO (TPE) with Hyperband, and ASHA (Li et al., 2020), i.e., asynchronous successive halving.

4.1 TUNING XGBOOST AND LIGHTGBM

We tune a set of 9-dimensional hyperparameters (all numerical) in LightGBM and 11-dimensional hyperparameters (9 numerical and 2 categorical) in XGBoost. A detailed description of the search space can be found in Appendix B. In this experiment, we omit the multi-fidelity baseline methods because we do not find a good 'fidelity' dimension that works well in tuning LightGBM and XGBoost (ref. Section 5). We perform the evaluation on 37 out of the 39 datasets from the AutoML benchmark ('Robert' and 'Dionis' are excluded due to out-of-memory error and extremely long training time). The input budget B (in terms of CPU time) is set to be 4 hours for the 3 largest datasets among the 37 datasets, and 1 hour for the rest. For the datasets with 1 hour budget, we

---

[1]https://github.com/DataCanvasIO/DeepTables

(a) Rank   (b) Scaled loss   (c) Rank for ablation

Figure 4: Aggregated rank and scaled loss on LightGBM and XGBoost. The scaled loss is obtained by min-max scaling using the max and min loss over all time across all the methods. Sub-figure (a) & (b) share the same legend, and BS is short for `BlendSearch` in sub-figure (c).

(a) vehicle, loss = log-loss   (b) cnae, loss = log-loss   (c) Aggregated rank

Figure 5: Performance curves and aggregated rank on DeepTables.

plot performance curves for tuning XGBoost and LightGBM on 3 representative datasets of small, medium and large size in Figure 3 and Figure 7 (the latter one in Appendix B), and plot the aggregated results (in terms of rank and scaled loss) in Figure 4(a) & (b).

From the performance curves, we observe that BO tends to perform well on small datasets, e.g., 'credit' in Figure 3(a), where the 1h budget is sufficient. Under the same budget, it may perform badly on large datasets, e.g., 'volkert' in Figure 3(c), as it may try configurations which consume a very large portion of the budget at the early stage of the search. On the medium size dataset, e.g., 'KDDCup09' in Figure 3(b), the local search method is more efficient than BO in the early stage but is outperformed in the later stage. `BlendSearch` performs similarly to the better one between LS and BO in the early stage, and surpasses both of them in the later stage. We also observe that BOwLS performs similarly with LS (sometimes worse). This is because BOwLS needs to wait until a local search converges before proposing a new one. The aggregated result over all the test cases in Figure 4(a) & (b) is consistent with these observations.

Takeaway. `BlendSearch` is able to overcome the limitations of BO and LS and at the same time, inherit their advantages. By blending BO and LS, `BlendSearch` is able to outperform both on this large collection of datasets over time.

4.2 TUNING DEEPTABLES

We tune 9-dimensional hyperparameters (5 numerical and 4 categorical) in DeepTables. A detailed description of the search space and experiment setup can be found in Appendix B. In this experiment, we compare the three state-of-the-art multi-fidelity methods which are shown efficient for tuning deep neural networks and the `BlendSearch` based on each of them. The number of training epochs is used as the fidelity dimension.

Table 1: Results of Turing-NLR model fine-tuning.

method	wall-clock	GPU-hours	f1
Manual	(10-20 working hours, spanned to a few days)	40-80h	0.645
BlendSearch	**3h**	**12h**	**0.652**
ASHA-1	6h	24h	0.624
ASHA-16	6h	384h	0.640

The learning curves for tuning DeepTables are shown in Figure 5(a) & (b). It includes learning curves of one dataset with budget 1h and two datasets with budget 4h. Among the three existing multi-fidelity methods HyperBand, BOHB and ASHA, there is no consistent winner. But their performance is all significantly improved when used in our BlendSearch framework. Similar observations can be obtained from the aggregated rank of all the 6 datasets tested in Figure 5(c).

Takeaway. BlendSearch has consistent utility in leveraging existing multi-fidelity global search methods and boosting their resource efficiency by combining with local search.

4.3 NLP MODEL FINE-TUNING

This section presents an application of economic hyperparameter optimization to an NLP model fine tuning task used in a large software company. It starts from a pre-trained Turing-NLR model (Rajbhandari et al., 2020) - a large transformer based model with 24 attention heads, hidden-dimension 1024 and 340M parameters, pretrained on English Wikipedia (2,500M words) and BookCorpus (800M words), and using byte-pair encoding. This pre-trained model is then fine-tuned (Dai & Le, 2015) for use in multiple production scenarios, including sequence classification, named entity recognition and question answering. The fine-tuning procedure is performed for a dozen separate tasks, and is repeated on a regular cadence, typically every few weeks. We focus our experiment on a single sequence classification fine-tuning task where the objective is to label a document (consisting of one or more sentences) with one of five possible classes. For fine-tuning this model we introduce a classification layer with $1024 \times 5 = 5120$ additional weight parameters, randomly initialized. The dataset used for training consists of 52K labeled examples, which we split 80/20 for training/validation. The objective to maximize is the f1-score obtained on the validation set of 10.4K labeled documents. Selecting hyperparameters for fine-tuning this model has been a manual process that typically takes a data scientist a few days.

In our experiment we used a 6-dimensional search space (4 numerical and 2 categorical). A detailed description of all the hyperparameters tuned, including their ranges, can be found in Table 5 in Appendix B. We compare to ASHA and let it use 16 VMs with 4 NVIDIA Tesla V100 GPUs on each VM. We run ASHA with 16 concurrent jobs for 6 hours in wallclock time. That amounts to $4 \times 16 \times 6 = 384$ GPU hours of hardware cost. We run BlendSearch on a *single* VM of the same configuration for 3 hours, which uses 12 GPU hours in total. For comparison, we include ASHA-1 using the same single VM. The results are summarized in Table 1.

Takeaway. Not only BlendSearch finds a more accurate model than both ASHA and manual effort, it does so faster and consumes only 3% of the resources of ASHA-16.

4.4 ABLATION STUDY

To investigate the effectiveness of several important modules of our framework (colored in orange in Figure 2), we perform an ablation study in tuning XGBoost on a random subset of the datasets (13 out of 39). We show the aggregated rank of different variants of our method in Figure 4(c). Specifically, we study the following three modules of the framework. **(1) Priority metric.** 'BS-Priority:RoundRobin' uses the round-robin policy in the search thread selector. **(2) Config validator.** 'BS-w/o-ConfigValidator' skips the validity check of the proposed configuration. **(3) Create new thread condition.** In 'BS-CreateCond:Always' and 'BS-CreatCond:BestOrFirst', the following two conditions are used as the condition for creating new local search threads respectively: always create, and create a new thread only when the loss is better than all the existing search threads' loss or there is no local search thread yet.

(a) Average rank

(b) Scaled loss

Figure 6: Aggregated results on LightGBM and XGBoost. 'PurneWithSample' and 'PruneWithIter' are ASHA using sample size and iteration number as resource dimension respectively. BO and `BlendSearch` are the same as that in Figure 4.

From this ablation study, we have the following observations: (1) Making round-robin selection is worse than doing selection using our designed priority metric. Round-robin's relative performance becomes worse in the later stage of the search because it cannot avoid bad-performing search threads. (2) The config validator is also vital in our framework. (3) Overall, the conditions for creating new threads has a smaller impact on our method comparing to the other designs studied. 'Better than half' condition used by default tends to perform the best.

5 DISCUSSION

Theoretical expositions. Our search thread selection strategy, which is based on the priority metric defined in Eq. (3), follows the principle of optimism in the face of uncertainty from the multi-armed bandit literature to balance exploitation and exploration. Specifically, linear extrapolation is performed adaptively and locally to calculate the improvement speed of each search thread. The estimated future reward based on such a linear extrapolation provides a first-order upper bound of the ground truth future reward assuming each search thread has a diminishing return, i.e., the speed of improvement decreases as more resource is spent.

Multi-fidelity pruning. A multi-fidelity pruning strategy can be used in the config evaluator component. Each config, either proposed by global search or local search, uses the same schedule to increase the fidelity and check its pruning condition. For example, when ASHA is used as the pruning strategy, after each config is evaluated by a certain fidelity, it is compared with other configs already evaluated by the same fidelity, and pruned if its loss is ranked in the worst 1/ReductionFactor. If not pruned, the fidelity is multiplied by ReductionFactor.

We provide additional experiment results about multi-fidelity baselines for LightGBM and XGBoost in Figure 6. We tried two choices of fidelity dimensions with ASHA, including number of iterations and sample size (the sample size begins with 10K, so small dataests are excluded) respectively. The results show that the multi-fidelity baselines overall perform no better than BO and are significantly worse than `BlendSearch`, hence we omitted them in Figure 4.

Low-cost initialization. For the local search method used in our framework, a low-cost initialization is needed to realize its unique advantages in controlling the cost. It is implemented via setting a low-cost initial value for each of the controlled dimensions. For example, among the hyperparameters tuned in LightGBM (shown in Table 2 of Appendix B), three hyperparameters, including 'tree num', 'leaf num' and 'min child weight' have initial values corresponding to the min or max values in their range, depending on whether they have a positive or negative correlation with the evaluation cost. It does not require the loss of the initial configuration to be low. Note that only one single low-cost initial value for each controlled dimension needs to be specified as input. To ensure a fair evaluation, we use the same low-cost initial point as the starting point of all the baselines. We also perform an additional experiment, which shows that `BlendSearch` can outperform the other baselines even without low-cost initialization (ref. Figure 11 in Appendix B), though the margin is smaller.

REFERENCES

Takuya Akiba, Shotaro Sano, Toshihiko Yanase, Takeru Ohta, and Masanori Koyama. Optuna: A next-generation hyperparameter optimization framework. In *Proceedings of the 25rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2019.

James S Bergstra, Rémi Bardenet, Yoshua Bengio, and Balázs Kégl. Algorithms for hyper-parameter optimization. In *Advances in neural information processing systems*, pp. 2546–2554, 2011.

Eric Brochu, Vlad M. Cora, and Nando de Freitas. A tutorial on bayesian optimization of expensive cost functions, with application to active user modeling and hierarchical reinforcement learning. *CoRR*, abs/1012.2599, 2010.

Adam D. Bull. Convergence rates of efficient global optimization algorithms. *J. Mach. Learn. Res.*, 12:2879–2904, November 2011.

Tianqi Chen and Carlos Guestrin. Xgboost: A scalable tree boosting system. In *KDD*, 2016.

Andrew M Dai and Quoc V Le. Semi-supervised sequence learning. *Advances in neural information processing systems*, pp. 3079–3087, 2015.

David Eriksson, Michael Pearce, Jacob Gardner, Ryan D Turner, and Matthias Poloczek. Scalable global optimization via local bayesian optimization. In *Advances in Neural Information Processing Systems*, pp. 5496–5507, 2019.

Stefan Falkner, Aaron Klein, and Frank Hutter. BOHB: Robust and efficient hyperparameter optimization at scale. In *Proceedings of the 35th International Conference on Machine Learning (ICML 2018)*, 2018.

Yuzhou Gao, Tengchao Yu, and Jinglai Li. Bayesian optimization with local search. *arXiv preprint arXiv:1911.09159*, 2019.

P. Gijsbers, E. LeDell, S. Poirier, J. Thomas, B. Bischl, and J. Vanschoren. An open source automl benchmark. *arXiv preprint arXiv:1907.00909 [cs.LG]*, 2019a. URL https://arxiv.org/abs/1907.00909. Accepted at AutoML Workshop at ICML 2019.

Pieter Gijsbers, Erin LeDell, Janek Thomas, Sébastien Poirier, Bernd Bischl, and Joaquin Vanschoren. An open source automl benchmark. In *AutoML Workshop at ICML 2019*, 2019b.

András György and Levente Kocsis. Efficient multi-start strategies for local search algorithms. *Journal of Artificial Intelligence Research*, 41:407–444, 2011.

Frank Hutter, Holger H. Hoos, and Kevin Leyton-Brown. Sequential model-based optimization for general algorithm configuration. In *Learning and Intelligent Optimization*, 2011.

Kevin Jamieson and Ameet Talwalkar. Non-stochastic best arm identification and hyperparameter optimization. In *Artificial Intelligence and Statistics*, 2016.

Kirthevasan Kandasamy, Gautam Dasarathy, Jeff Schneider, and Barnabás Póczos. Multi-fidelity bayesian optimisation with continuous approximations. In *Proceedings of the 34th International Conference on Machine Learning*, pp. 1799–1808, 2017.

Guolin Ke, Qi Meng, Thomas Finley, Taifeng Wang, Wei Chen, Weidong Ma, Qiwei Ye, and Tie-Yan Liu. Lightgbm: A highly efficient gradient boosting decision tree. In *NIPS*, 2017.

Aaron Klein, Stefan Falkner, Simon Bartels, Philipp Hennig, and Frank Hutter. Fast bayesian optimization of machine learning hyperparameters on large datasets. In *Artificial Intelligence and Statistics*, pp. 528–536, 2017.

Liam Li, Kevin Jamieson, Afshin Rostamizadeh, Ekaterina Gonina, Jonathan Ben-tzur, Moritz Hardt, Benjamin Recht, and Ameet Talwalkar. A system for massively parallel hyperparameter tuning. In *Proceedings of Machine Learning and Systems*, 2020.

Lisha Li, Kevin Jamieson, Giulia DeSalvo, Afshin Rostamizadeh, and Ameet Talwalkar. Hyperband: A novel bandit-based approach to hyperparameter optimization. In *ICLR'17*, 2017.

Zhiyun Lu, Liyu Chen, Chao-Kai Chiang, and Fei Sha. Hyper-parameter tuning under a budget constraint. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI-19*, pp. 5744–5750, 2019.

Yurii Nesterov and Vladimir Spokoiny. Random gradient-free minimization of convex functions. *Foundations of Computational Mathematics*, 17(2):527–566, 2017.

Samyam Rajbhandari, Jeff Rasley, Olatunji Ruwase, and Yuxiong He. Zero: Memory optimizations toward training trillion parameter models. *arXiv preprint arXiv:1910.02054*, 2020.

Jasper Snoek, Hugo Larochelle, and Ryan P Adams. Practical bayesian optimization of machine learning algorithms. In *Advances in neural information processing systems*, pp. 2951–2959, 2012.

James C Spall et al. Multivariate stochastic approximation using a simultaneous perturbation gradient approximation. *IEEE transactions on automatic control*, 37(3):332–341, 1992.

Niranjan Srinivas, Andreas Krause, Sham M Kakade, and Matthias Seeger. Gaussian process optimization in the bandit setting: No regret and experimental design. *arXiv preprint arXiv:0912.3995*, 2009.

Qingyun Wu, Chi Wang, and Silu Huang. Cost effective optimization for cost-related hyperparameters. *arXiv preprint arXiv:2005.01571*, 2020.

Li Yang and Abdallah Shami. On hyperparameter optimization of machine learning algorithms: Theory and practice. *Neurocomputing*, 415:295 – 316, 2020.

A   MORE DETAILS ABOUT BLENDSEARCH AND EXTENSIONS

We provide detailed pseudocode of the sub-algorithms used in our framework.

Algorithm 3 `SelectThread`

Inputs: Framework-level state $\mathcal{F}$ which keeps a list of candidate search thread $\mathcal{F}.\mathbb{S}$ and a priority function $\mathcal{F}.\texttt{Priority}$.

1: $\tilde{S} = \arg\max_{S \in \mathcal{F}.\mathbb{S}} \mathcal{F}.\texttt{Priority}(S)$
2: $\tilde{S}_{\text{bak}} = \begin{cases} \arg\max_{S \in (\mathcal{F}.\mathbb{S} \setminus S_0)} \mathcal{F}.\texttt{Priority}(S) & \mathcal{F}.\mathbb{S} \setminus S_0 \neq \emptyset \\ S_0 & \mathcal{F}.\mathbb{S} \setminus S_0 = \emptyset, \end{cases}$

   Outputs: $\tilde{S}, \tilde{S}_{\text{bak}}$

Algorithm 4 `BookKeeping`

Inputs: Search thread S, one entry of observation $\mathbf{x}, l, c$ generated by S, and $\mathcal{F}$.

1: $S.c \leftarrow S.c + c$
2: **if** S is a local search thread **then** Update $\{S.x_i^{\min}\}_{i \in [d]}$, and $\{S.x_i^{\max}\}_{i \in [d]}$
3: **if** $l < S.l^{\text{1st}}$ **then**
4:     $S.l^{\text{2nd}}, S.c^{\text{2nd}} \leftarrow S.l^{\text{1st}}, S.c^{\text{1st}}; S.l^{\text{1st}}, S.c^{\text{1st}} \leftarrow l, S.c$; and $S.\mathbf{x}^{best} \leftarrow \mathbf{x}$
5:        **if** $l < \mathcal{F}.l^*$ **then** $\mathcal{F}.l^* \leftarrow l$

Algorithm 5 `InitializeSearchThread`

Inputs: Search method $\mathcal{L}$ or $\mathcal{G}$, problem P and initial point $(\mathbf{x}, l, c)$.

1: $S.\pi = \mathcal{L}.\pi$ or $\mathcal{G}.\pi$
2: Initialize bookkeeping information of S: $S.l_1 = S.l_2 = l$, $S.c^{\text{1st}} = S.c^{\text{2nd}} = S.c = c$, and $S.x_i^{\min} = S.x_i^{\max} = \mathbf{x}_i$ for $i \in P.D$

Choice of $\mathcal{L}.\Delta$ used in constructing the 'admissible' region $\mathcal{F}.\mathcal{R}$. We normalize each numeric hyperparameter into [0,1]. The setting of $\mathcal{L}.\Delta$ is decided by the local search method. For the local search method we chose, $\mathcal{L}.\Delta$ is a constant equal to the initial stepsize (fixed as 0.1).

Definition of `ReachableInOneStep` in Alg 7. We define local search thread S_1 to be reachable by S_2 if the distance between their incumbents is no larger than the maximal distance between the next proposal of S_2 and the incumbent of S_2. In the local search method we used, the incumbent is the currently best config, and the maximal distance is equal to the stepsize.

Parallelization. In the low-resource scenario which is targeted by this paper, each single trial is not resource-saturated if we spend all resources in it, so we do not recommend parallel trials in this scenario. In the case where more resources are available than the maximum which each single trial can consume, our framework can be extended by running the trials from different search threads on multiple workers. For example, if there are additional workers available, we can keep invoking the search thread selector (but skip the local search threads that have a trial running). Our design of having multiple independent local search threads naturally allows efficient asynchronous parallel trials. The design of utilizing existing global optimization methods allows existing easy-to-parallelize global optimization (such as random search or batch versions of BO) to be plugged in. The prioritization of search threads is still useful as long as the number of search threads is larger than the maximal concurrent number of trials. Since our method can be used together with ASHA, it can naturally inherit the easy-to-parallel and asynchronous resource scheduling in ASHA when used in the parallel setting.

B   MORE DETAILS ABOUT EXPERIMENTS AND ADDITIONAL RESULTS

B.1   EXPERIMENT SETUP

Settings of BO and LS. For BO, we use implementation from Optuna 2.0.0 (`https://optuna.readthedocs.io/en/stable/index.html`) with default settings for TPE sampler. For

---

Algorithm 6 `CreateNewLSCondition`

    Inputs: $l, \mathcal{F}$.
    Outputs: $|\mathcal{F}.\mathbb{S}| = 1$ or $l \leq \text{Median}(\{S.l^{\text{1st}}\}_{S \in \mathcal{F}.\mathbb{S} \setminus S_0})$

Algorithm 7 `DeleteAndMergeLS`

    Inputs: $S, \mathcal{F}$
1: **if** S.`converged()` **then**
2:      $\mathcal{F}.\mathbb{S} \leftarrow \mathcal{F}.\mathbb{S} \setminus S$,
3:      $\mathcal{F}.\mathcal{R}.x_i^{\min} \leftarrow \mathcal{F}.\mathcal{R}.x_i^{\min} - \mathcal{L}.\Delta$, and $\mathcal{F}.\mathcal{R}.x_i^{\max} \leftarrow \mathcal{F}.\mathcal{R}.x_i^{\max} + \mathcal{L}.\Delta, \forall i \in D'$
4: **else**
5:      **for** $\forall S' \in \mathcal{F}.\mathbb{S} \setminus S$ **do**
6:          **if** $S \in S'$.`ReachableInOneStep()` & $S'.l < S.l$ **then**
7:              $\mathcal{F}.\mathbb{S} \leftarrow \mathcal{F}.\mathbb{S} \setminus S$
8:              break
9:          **else if** $S' \in S$.`ReachableInOneStep()` & $S.l < S'.l$ **then** $\mathcal{F}.\mathbb{S} \leftarrow \mathcal{F}.\mathbb{S} \setminus S'$

LS, we follow the implementation guidelines from Wu et al. (2020). The local search method used is primarily designed to handle numerical hyperparameters including both continuous and integer types. Due to this reason, only global search, i.e., BO with TPE sampler, is responsible for proposing categorical values. After a local search thread is created from a particular starting point, we fix the categorical dimensions and only search for numerical dimensions in that local search thread. A local search thread S is considered to have converged (corresponding to S.`converged()` in Algorithm 7) once the stepsize of the local search thread is smaller than a lower bound introduced by Wu et al. (2020).

Experiments in tuning XGBoost and LightGBM. The XGBoost and LightGBM experiments are performed in a server with Intel Xeon E5-2690 v4 2.6GHz, and 256GB RAM. A full list of hyperparameters tuned and their ranges can be found in Table 3 and Table 2. The search space for numerical hyperparamters aligns with the search space used in (Wu et al., 2020). On the same fold, the same random seed is used for LS, BO and BS. Experiments on different folds use different random seeds.

Experiments in tuning Deeptables. The DeepTables experiments are performed in a server with the same CPU, 110GB RAM, and one Tesla P100 GPU. A full list of hyperparameters tuned and their ranges can be found in Table 4. We use the following libraries for baselines: For BOHB, we use HpBandSter 0.7.4 (`https://github.com/automl/HpBandSter`). For ASHA and asynchronous HyperBand, we use implementations from Optuna 2.0.0. In all the methods compared, including both existing methods and variants of `BlendSearch`, the number of training epochs is used as the fidelity dimension, with maximum epochs set to be 1024, reduction factor set to be 3, and minimum epochs 4. The six datasets tested in Deeptables are listed below: 'shuttle','cnae','mfeat','vehicle','phoneme', 'kc1'.

Experiments in Turing-NLR fine tuning. For ASHA, we set min and max epochs as 1 and 16, and reduction factor 4.

Result aggregation details. Aggregated rank in Figure 4(a)&(c) and 5(c) is calculated as follows: (1) per dataset per fold, the method is ranked based on the loss on validation set at each second (x-axis), starting from when there is at least one finished config evaluation in any method; (2) the rank is then averaged across datasets per fold; (3) we finally compute the average rank (line) and confidence interval (shaded area) across 10 folds. Scaled loss in Figure 4(b) is calculated similarly. Per dataset per fold, min-max scaling is applied on each method using the maximum and minimum loss along the whole performance curve across all methods.

B.2 ADDITIONAL EXPERIMENTAL RESULTS

More performance curves on LightGBM and XGBoost. The performance curves for tuning LightGBM on 3 representative datasets with an 1h budget are shown in Figure 7. We observe that the performance of LS is quite good (comparing to BO), especially on large datasets. This result is consistent with the results reported in (Wu et al., 2020), where all the hyperparameters for tuning are

Table 2: Hyperparameters tuned in LightGBM.

hyperparameter	type	range	init
tree num	int	[4, min(32768, # instance)]	4
leaf num	int	[4, min(32768, # instance)]	4
min child weight	float	[0.001, 20]	20
learning rate	float	[0.01, 0.1]	random
subsample	float	[0.6, 1.0]	random
reg alpha	float	[1e-10, 1.0]	random
reg lambda	float	[1e-10, 1.0]	random
max bin	int	[7, 1023]	random
colsample by tree	float	[0.7, 1.0]	random

Table 3: Hyperparameters tuned in XGBoost.

hyperparameter	type	range	init
tree num	int	[4, min(32768, # instance)]	4
leaf num	int	[4, min(32768, # instance)]	4
min child weight	float	[0.001, 20]	20
learning rate	float	[0.01, 0.1]	random
subsample	float	[0.6, 1.0]	random
reg alpha	float	[1e-10, 1.0]	random
reg lambda	float	[1e-10, 1.0]	random
colsample by level	float	[0.6, 1.0]	random
colsample by tree	float	[0.7, 1.0]	random
booster	categorical	{gbtree, gblinear}	gblinear
tree method	categorical	{auto, approx, hist}	random

Table 4: Hyperparameters tuned in DeepTables.

hyperparameter	type	range	init
early stopping rounds	int	[1, max(min(1.5M/# instance),150),10)]	10
batch size	int	[16, 1024]	512
dropout	float	[0, 0.5]	0.1
learning rate	float	[1e-4, 3e-2]	3e-4
dense dropout	float	[0, 0.5]	0.1
net	categorical	{DCN, dnn_nets}	random
auto discrete	boolean	{False, True}	random
apply gbm features	boolean	{False, True}	random
fixed embedding dim	boolean	{False, True}	random

Table 5: Hyperparameters tuned in Turing fine-tuning.

hyperparameter	type	range	init
learning rate	float	[1e-6, 1e-3]	random
hidden dropout probability	float	[0.05, 0.4]	random
warmup proportion	float	[0.2, 0.4]	random
batch size	categorical	{16, 32}	32
epochs	int	[1, 16]	1
learning rate scheduler	categorical	{Warmup linear decay polynomial, Warmup linear, Warmup linear decay exponential}	random

(a) blood, loss = 1 - auc   (b) numerai28.6, loss = 1 - auc   (c) Albert, loss = 1 - auc

Figure 7: Optimization performance curve for LightGBM (1h).

(a) Fashion-MNIST, loss = log-loss   (b) dilbert, loss = log-loss   (c) Covertype, loss = log-loss

Figure 8: Optimization performance curve for LightGBM (4h).

(a) Fashion-MNIST, loss = log-loss   (b) dilbert, loss = log-loss   (c) Covertype, loss = log-loss

Figure 9: Optimization performance curve for XGBoost (4h).

(a) KDDCup09

(b) Volkert

Figure 10: Search thread selection in `BlendSearch` in tuning XGBoost. In this figure, each marker corresponds to one time of search thread selection in `BlendSearch`. The diamond markers correspond to the selection of the global search thread, and the solid circle markers correspond to the selection of local search threads (different colors indicating different threads).

(a) Average rank

(b) Scaled loss

Figure 11: Aggregated rank and scaled loss on LightGBM with random initialization. The way of aggregating the rank and scaling the loss is the same as that in Figure 4.

numerical. In our experiment of XGBoost tuning, we include categorical hyperparameters. LS performs worse in this case because the introduction of categorical hyperparameters amplifies the local search method's limitation of being trapped in local optima. The observations about `BlendSearch` for LightGBM are similar to XGBoost tuning. The performance curves on the three large datasets with a 4h budget are shown in Figure 8 and 9, where similar conclusions can be drawn.

Case study. In Figure 10 we show the performance curve of three methods including LS, BO, and `BlendSearch` (BOwLS is excluded because it performs almost the same with LS on these two datasets) in tuning XGBoost on one fold of data. The markers on `BlendSearch` show the time consumed and the loss obtained when the local search thread (marked as solid circles with different colors corresponding to different local search threads) or the global search thread (marked as diamonds) is selected.

Without low-cost initialization. In this work, we use low-cost initialization for the controlled dimensions of the hyperparameters. Although such information is fairly easy to obtain, we investigate our method's robustness when no controlled dimension is provided. We test `BlendSearch` in a controlled dimension agnostic setting: there are still hyperparameters with heterogeneous cost, but the controlled dimensions and a low-cost initial point is not specified as input. In such scenarios, `BlendSearch` will use random initialization and the config validator always returns 'yes'. We compare `BlendSearch` with local search and BO under such a setting using the same random initial point. We report the results including the aggregated rank and scaled loss on LightGBM across

Figure 12: The distributions of the # of thread switches and the # of local search threads induced by the global search in `BlendSearch` for tuning XGBoost. The result is aggregated over the 34 datasets described in Section 4.1. The outliers with large # of thread switches and # of threads induced by GS (short for global search) are from very small datasets, where the number of evaluations are large.

18 datasets in Figure 11. The results show that even if `BlendSearch` is agnostic to the controlled dimensions and a random initialization is used, it is still able to outperform both the local search method and BO.