Self-Supervised Multi-Object Tracking
with Cross-Input Consistency

Abstract

In this paper, we propose a self-supervised learning procedure for training a robust multi-object tracking (MOT) model given only unlabeled video. While several self-supervisory learning signals have been proposed in prior work on single-object tracking, such as color propagation and cycle-consistency, these signals are not effective for training RNN models, which are needed to achieve accurate MOT: they yield degenerate models that, for instance, always match new detections to tracks with the closest initial detections. We propose a novel self-supervisory signal that we call cross-input consistency: we construct two distinct inputs for the same sequence of video, by hiding different information about the sequence in each input. We then compute tracks in that sequence by applying an RNN model independently on each input, and train the model to produce consistent tracks across the two inputs. We evaluate our unsupervised method on MOT17 and KITTI — remarkably, we find that, despite training only on unlabeled video, our unsupervised approach *outperforms* four supervised methods published in the last 1–2 years, including Tracktor++ [1], FAMNet [5], GSM [18], and mmMOT [29].

1 Introduction

Multi-object trackers identify all instances of a particular object type in video, and track each instance through the segment of video in which it is visible in the camera frame. Annotating training data for multi-object tracking is tedious and costly; for example, annotation of pedestrian tracks in just six minutes of video in the training set of the MOT15 Challenge [14] requires an estimated 22 hours [20] of human labeling time using LabelMe [28]. While unsupervised, heuristic detect-to-track methods [2, 4] have been proposed that group detections into tracks by estimating motion using a combination of spatial and visual cues, these methods suffer low-accuracy in scenarios with frequent occlusion where heuristics are insufficient.

Recent work has proposed applying self-supervised learning for training *single*-object tracking models on unlabeled video [24, 25]. These approaches train a model to propagate instance labels from a reference frame through the rest of a video sequence. In contrast to work on self-supervised representation learning from video, these fully unsupervised approaches do not require fine-tuning to apply the model for single-object tracking.

However, a significant limitation in prior work is that the model independently compares pairs of frames at a time. In multi-object tracking, a key challenge is robustly re-localizing tracks across potentially long occlusions, especially when an object instance is occluded by other instances of the same object type. Pairwise frame comparisons are thus insufficient for high-accuracy multi-object tracking; instead, learning recurrent features that encode the history of a track is crucial for enabling robust re-localization. However, extending prior work to learn RNN parameters is challenging. For example, Wang et al. [25] propose training using forward-backward consistency: from a patch in an

initial frame, after tracking forwards through video and then backwards to return to the initial frame, the final patch should align with the original patch. Training an RNN in this way would be ineffective as the RNN could simply memorize the features of the original patch.

To address this challenge, we propose a novel self-supervised learning method, *cross-input consistency*. We first compute object detections in each frame of unlabeled video (like unsupervised, heuristic detect-to-track methods, we assume that a robust detector is available). Then, we derive a learning signal from the unlabeled video by sampling a short sequence of contiguous frames from the video, constructing two input variations of that sequence that each hide different information about objects detected in the sequence, and training the tracker to produce consistent tracking outputs when applied independently on each of the two inputs. We propose two alternative input-hiding schemes for computing the input variations: occlusion-based hiding and visual-spatial hiding. Occlusion-based hiding eliminates information about object detections in random intermediate subsequences of frames to simulate occlusion incidents; thus, it constructs two inputs by eliminating different subsequences of detections in each input. Visual-spatial hiding applies the tracker once when only observing spatial inputs (bounding box coordinates in the video frame), and once when only observing visual inputs (pixel values inside detection boxes). After sampling a sequence of video and computing the two input variations under the chosen input-hiding scheme, we apply the tracker model independently on each input, and back-propagate a learning signal that measures the consistency between tracks computed across the two inputs. To attain high consistency, the model must accurately group detections that correspond to the same object: if the model were to instead arbitrarily group detections into tracks, then variations in the inputs would cause the tracker to produce inconsistent outputs.

To implement cross-input consistency, we adapt a now standard RNN model and tracker architecture from prior work [12]: the tracker processes each frame in sequence by matching detections in the current frame with tracks computed up to the previous frame. In prior work, this model is trained under a supervised procedure: they sample a video sequence $\langle I_0, \ldots, I_n \rangle$ and a track t in that sequence, and apply the tracker on t over the sequence. On each frame I_j, the RNN outputs a probability distribution indicating the likelihood that the prefix of a track t up to I_j matches with each detection in I_j. Prior work back-propagates the label (i.e., the correct detection of t in I_j) under cross entropy loss.

In contrast, under our method, on each training iteration, we propose to sample a sequence $\langle I_0, \ldots, I_n \rangle$ from a corpus of unlabeled video, and apply the RNN model to compute a transition matrix that specifies the probability that each detection in I_0 (rows) matches with each detection in I_n (columns). We select the sequence length n so that most objects in I_0 are still visible in I_n. Then, when applying the tracker on two input variations extracted from the sequence, we obtain two transition matrices (one for each input). We compute the dot-product similarity to measure the consistency between these matrices, and back-propagate the negative similarity as a loss function.

We evaluate our approach on the MOT17 and KITTI benchmarks against 9 baselines, including both unsupervised and supervised methods. We train our tracker model using cross-input consistency over a corpus of unlabeled video, which can be cheaply obtained. Like other unsupervised methods, we use an object detector trained on image-level bounding box annotations in COCO [17], but do not use any expensive video-level annotations. We find that, on MOT17, our approach improves both IDF1 and MOTA accuracy over the unsupervised baselines by 14% to 18%. Moreover, remarkably, our fully unsupervised approach *outperforms* five of the seven supervised methods we compared, even though these methods train on expensive video-level bounding box and track annotations.

2   Related Work

Self-supervised learning over video has been studied extensively in many contexts. Most work focuses on learning representations of video that can be applied through fine-tuning for tasks such as activity recognition, image classification, and object detection [6, 7, 9, 15, 23, 26]. More closely related to our work, several recent approaches have proposed leveraging widely available unlabeled video to directly train *single*-object tracking models, without needing fine-tuning [13, 16]. Vondrick et al. [24] train a model to colorize gray-scale video by propagating colors from a colored reference frame. The model is then applied to track objects at inference time by propagating instance IDs instead of colors. Wang et al. [25] train a model to capture correspondence by applying a cycle-consistent loss: from a patch in an initial frame, after tracking forwards through video and then backwards to return to

Figure 1: Overview of cross-input consistency. An input-hiding scheme produces two inputs, A and B, from one video sequence; these inputs contain identical information about objects detected in the first and last frames of the sequence, but vary in intermediate frames. We apply the tracker model on each input to derive two transition matrices that match detections between the first and last frames to represent tracker outputs. We then back-propagate a similarity score between the matrices that encourages the model to produce consistent outputs across both inputs.

Figure 2: Tracker model architecture. The model scores the likelihood that each detection in the current frame matches with each track.

the initial frame, the final patch should align with the original patch. As we discussed in Section 1, self-supervisory signals used in prior work such as color propagation and cycle-consistency are not effective for training RNN models, which are needed to achieve accurate MOT.

Our work is also related to unsupervised, heuristic detect-to-track multi-object tracking methods such as SORT [2] and V-IOU [4]. These methods group detections across different frames using a combination of heuristic spatial cues (e.g., Kalman filter over bounding box coordinates) and visual cues (e.g., optical flow) to track objects. Like our approach, these methods assume that a robust detector is available; however, because they rely on heuristics to group detections into tracks, they suffer low-accuracy in scenarios with frequent occlusion.

Multi-object tracking has been studied extensively in supervised settings, where methods are trained on video-level bounding box and track annotations [1, 5, 8, 12, 18, 30]. However, such annotations are expensive to hand-label, and so these methods are costly to extend to new types of video.

Other work explores using unsupervised and self-supervised learning to further improve the performance of fully supervised methods. SimpleReID [11] proposes improving the performance of one supervised method, CenterTrack [30], by training a re-identification model through unsupervised learning. However, while the model can in principle be trained only on image-level annotations through hallucinated motion techniques, their SimpleReID+CenterTrack tracking method depends on expensive video-level annotations to attain high-accuracy. In contrast, our method achieves competitive results without any video-level supervision.

3   Cross-Input Consistency

In our novel cross-input consistency method, we derive an learning signal for training an RNN tracker model through a three-step process. We assume that a corpus of unlabeled video is available, along with an object detector for the object category of interest. During pre-processing, we apply the detector on each frame of unlabeled video to compute object detections. Then, during training, we first repeatedly randomly sample a sequence of contiguous frames from the video, $\langle I_0, \ldots, I_n \rangle$,

where each I_k is a video frame. Let D_k by the detections automatically computed in I_k by the detector, and let $d_i^k = (im, x, y, w, h)$ be a detection in D_k, where (x, y, w, h) are the 4D spatial coordinates (center point and lengths) of the detection bounding box, and im is the window of I_k corresponding to that box. We apply an input-hiding scheme to select two input variations $A(D), B(D)$ for the video segment, where each variation is a modified sequence of detections in the frames, $A(D) = \langle D_0^A, \ldots, D_n^A \rangle, B(D) = \langle D_0^B, \ldots, D_n^B \rangle$. For example, some detections may be removed entirely, while others may be partially hidden. Second, we apply the tracker model independently on each input variation to derive two probabilistic tracking outputs (one per input), represented as transition matrices. Third, we compare the transition matrices with dot-product similarity to update the RNN parameters.

Figure 1 summarizes our approach.

Below, we first introduce the model architecture that we adapt from prior work in Section 3.1. We then detail our novel training procedure, including the computation of the transition matrices and dot-product loss, in Section 3.2. Finally, we propose two input-hiding schemes for selecting the input variations required by our approach in Section 4.

3.1 Background: Tracker Model

We adopt a tracker model that is similar to prior work [12]. We summarize the architecture in Figure 2. Given a video sequence $\langle I_0, \ldots, I_n \rangle$, and sets of detections $D_k = \{d_1^k, \ldots, d_{m_k}^k\}$ detected in each frame I_k, to initialize the tracking process, we create a length-1 track $t_i = \langle d_i^0 \rangle$ for each detection d_i^0 in the first video frame I_0. When processing subsequent frames, we will match the new detections with existing tracks, extending existing tracks if there is a match and initializing new tracks otherwise. Specifically, on each subsequent frame I_k, the model outputs a probability $p_{i,j}$ that each track t_i corresponds to each detection $d_j^k \in D_k$. At inference time, we formulate the problem of matching tracks with detections in I_k as a bipartite matching problem, where the cost of matching t_i with d_j^k is $1 - p_{i,j}$. We solve this problem and compute a minimum-cost matching using the Hungarian algorithm; for each pair (t_i, d_j^k) in the matching, we append d_j^k to t_i. For each detection in I_k that no track matches to, we create a new track for that detection.

The model consists of a CNN, RNN, and matcher network. Together, these components score the likelihood that the ith track, $t_i = \langle d_1, \ldots, d_m \rangle$, matches with the jth detection in I_k, d_j^k. We first apply the CNN to derive detection-level features. Given a detection $d = (im, x, y, w, h)$, the CNN inputs im resized to 64×64, and consists of 6 strided convolutional layers, with ReLU activation in the first 5 layers and linear activation in the last layer. It outputs a 64-vector, which we concatenate with the 4D spatial coordinates to derive a 68-vector detection representation $f(d)$. Then, we compute track-level features $f(t_i)$ by applying the RNN (an LSTM with 64 hidden states) over the sequence of detection-level features of detections in the track, $\langle f(d_1), \ldots, f(d_m) \rangle$. We use the output of the RNN on the last timestep as the track-level features $f(t_i)$. Finally, we apply a matching network to score the likelihood that t_i matches d_j^k. The matching network inputs the concatenation of $f(t_i)$ and $f(d_j^k)$, applies four fully-connected layers, and outputs a match score.

3.2 Training Procedure

We develop a novel self-supervised learning method for training the model parameters on unlabeled video. During training, we repeatedly sample sequences of video $\langle I_0, \ldots, I_n \rangle$. We apply one of two input-hiding schemes, which we will detail in the following section, to extract two distinct input variations $A(D)$ and $B(D)$ from a sampled video sequence, where each input is a sequence of detections. We then apply the tracker independently on $A(D)$ and $B(D)$ to derive two tracking outputs for the same video sequence. In cross-input consistency, we train the model by enforcing similarity between these two outputs.

To represent tracker outputs, we compute an $|D_0| \times |D_n| + 1$ transition matrix $M^{(0,n)}$, where $M_{i,j}^{(0,n)}, j < |D_n|$ is the probability that the track t_i matches d_j^n. We use the last column to represent tracks that are no longer visible in I_n, i.e., $M_{i,|D_n|}^{(0,n)}$ is the probability that the track t_i has exited the camera frame. When applying the model over video sequences during training, we update tracks with new detections based on the scores output by the model on intermediate frames, but do not create

167 additional tracks on frames after I_0; thus, each track t_i corresponds directly to a detection d_i^0 in I_0
168 (i.e., $t_i = \langle d_i^0, \ldots \rangle$). Thus, we can also think of $M^{(0,n)}$ as the probability that a detection in the first
169 frame d_i^0 matches a detection in the last frame d_j^n.

170 Applying the tracker on both input variations yields two transition matrices $A^{(0,n)}$ and $B^{(0,n)}$ that
171 match objects detected in I_0 with those in I_n. We train the model (CNN, RNN, and matching network)
172 to maximize the dot-product similarity between these matrices. In addition to pushing the model to
173 produce consistent outputs across both inputs, we also design our training method so that the model
174 cannot attain a high similarity score by, for example, saying that all objects visible in I_0 are no longer
175 visible in I_n.

176 In our method, it is important that the training sequence length n be chosen so that, in most sequences,
177 most (but not all) objects in I_0 are still visible in I_n, but that objects nevertheless move non-trivially
178 during the sequence (so that the tracking task is not too easy). In general, we find that setting n to
179 one-half of the average time that objects linger in the camera frame works well.

180 Below, we detail our method to compute transition matrices, and discuss dot-product similarity loss.

181 **Transition Matrix.** We propose computing a transition matrix $M^{(0,k)}$ on each frame I_k to represent
182 the tracker outputs, where $M_{i,j}^{(0,k)}$ is the probability that the track t_i matches the detection d_j^k. On
183 intermediate frames, we apply the Hungarian method on $M^{(0,k)}$ to match detections in D_k with tracks,
184 updating each track with the matched detection (if any). On the last frame I_n, we use the $M^{(0,n)}$
185 matrix produced under different inputs (denoted $A^{(0,n)}$ and $B^{(0,n)}$) to compute and back-propagate
186 a consistency score. Because we do not create new tracks after I_0 during training, $M_{i,j}^{(0,n)}$ is the
187 likelihood that d_i^0 and d_j^n match (since t_i begins with d_i^0).

188 We first construct a score matrix $S^{(0,k)}$, by computing $S_{i,j}^{(0,k)}$ as the score (any real number) output
189 by the tracker model given the track t_i and detection d_j^k. We then transform the score matrix into a
190 probability matrix to derive $M^{(0,k)}$. We could simply compute $M^{(0,k)}$ by taking softmax along rows
191 in $S^{(0,k)}$. However, computing the transition matrix in this way would allow the tracker to cheat and
192 maximize similarity between $A^{(0,n)}$ and $B^{(0,n)}$ by simply matching all detections in I_0 to a single
193 detection $d_j^n \in D_n$. Indeed, we find that in practice this yields degenerate models.

194 Thus, instead, we compute $M^{(0,k),\text{row}}$ and $M^{(0,k),\text{col}}$ by applying softmax along rows and columns,
195 respectively, and compute $M^{(0,k)} = \min(M^{(0,k),\text{row}}, M^{(0,k),\text{col}})$:

$$M_{i,j}^{\text{row}} = \frac{\exp(S_{i,j})}{\sum_k \exp(S_{i,k})} \qquad M_{i,j}^{\text{col}} = \frac{\exp(S_{i,j})}{\sum_k \exp(S_{k,j})} \qquad M_{i,j} = \min(M_{i,j}^{\text{row}}, M_{i,j}^{\text{col}}) \quad (1)$$

196 This produces a transition matrix $M^{(0,k)}$ that is almost doubly stochastic: rows and columns sum
197 to at most 1, but not necessarily exactly 1. The operation ensures that the model must match each
198 detection in I_0 to unique detections in I_n to maximize the consistency score between $A^{(0,n)}$ and
199 $B^{(0,n)}$: if two detections in I_0 are matched to the same detection in I_n, then the columnar softmax
200 would reduce those probabilities in the corresponding matrix to at most 0.5, thereby reducing any
201 dot-products involving those rows.

Dot-Product Similarity. We train the RNN tracker by computing two transition matrices $A^{(0,n)}$
and $B^{(0,n)}$ over different input variations, and then back-propagating a loss that measures the
inconsistency between the matrices. In particular, we use the dot-product to measure the similarity of
corresponding rows in the matrices. We define the loss as:

$$L = -\sum_i \log \sum_j A_{i,j}^{(0,n)} B_{i,j}^{(0,n)}$$

202 Here, L is computed by taking the logarithm of the dot product of corresponding rows in $A^{(0,n)}$
203 and $B^{(0,n)}$, averaged across rows. Note that this is equivalent to the cross-entropy loss between the
204 diagonal matrix and the matrix product of $A^{(0,n)}$ and the transpose of $B^{(0,n)}$.

205 This loss function has several desirable properties. First, the dot-product is maximized when the
206 matrices computed based on different inputs are most similar. This pushes the matching model

to learn reasonable visual and spatial tracking constraints, because arbitrarily matching tracks to detections will lead to dissimilarity. Second, the dot-product pushes each matrix to be almost doubly stochastic rather than leaving some rows and columns summing to much less than 1. The model can only produce doubly stochastic $A^{(0,n)}$ and $B^{(0,n)}$ matrices by finding unique detections in I_n for each detection in I_0.

4 Input-Hiding Schemes

In this section, we detail two alternative input-hiding schemes for selecting the two input variations, denoted $A(D) = \langle D_0^A, \ldots, D_n^A \rangle$ and $B(D) = \langle D_0^B, \ldots, D_n^B \rangle$. Recall that D is the original set of all objects detected in a video sequence $\langle I_0, \ldots, I_n \rangle$.

4.1 Occlusion-based Hiding

At a high level, occlusion-based hiding produces the variations $A(D)$ and $B(D)$ by simulating random occlusion incidents where all detections in occluded frames are eliminated from the input, i.e., if I_k is occluded for $A(D)$, then D_k^A is empty. We only occlude intermediate frames $I_k, 0 < k < n$, so that the transition matrices still compare detections in I_0 with those in I_n. When processing an occluded I_k, the tracker is forced to match all tracks to the absent column in that frame, and re-localize the tracks after the occlusion.

We first introduce two schemes that do not work in isolation, and then show that we can combine these schemes to produce input variations that result in effective training.

Only-Occlusion. For each training sequence $\langle I_0, \ldots, I_n \rangle$, Only-Occlusion randomly selects four indexes $0 < k_1 \le k_2 < k_3 \le k_4 < n$ to construct two disjoint frame subsequences $\langle I_{k_1}, \ldots, I_{k_2} \rangle$ and $\langle I_{k_3}, \ldots, I_{k_4} \rangle$. In $A(D)$, we occlude each frame I_k such that $k_1 \le k \le k_2$, and in $B(D)$, we occlude I_k if $k_3 \le k \le k_4$.

When training under Only-Occlusion, the tracker is forced to leverage track features computed through the RNN to re-localize tracks after each simulated occlusion ends. Learning to merely compare detection features across consecutive frames would yield low accuracy since features in occluded frames are not observed. Furthermore, because one tracker observes the detections and the other tracker does not, the model must make similar tracking decisions when re-localizing across occluded frames as it does when observing detections in each frame.

However, in practice, Only-Occlusion yields a model that simply memorizes detections in I_0, and computes $A^{(0,n)}$ and $B^{(0,n)}$ by comparing detections in I_n against memorized detections. This strategy yields high consistency because it is unaffected by occluded intermediate frames. Thus, to make this scheme effective, we must prevent the propagation of features directly from I_0 to I_n.

RNN Hand-off. RNN Hand-off prevents simple memorization by cutting off the propagation of RNN features through the application of two separate RNN executions. We select two indexes $0 < k_5, k_6 < n$. Instead of computing $A^{(0,n)}$ directly, we first apply the tracker on the frame sequence $\langle I_0, \ldots, I_{k_5} \rangle$ to derive a transition matrix $A^{(0,k_5)}$ that matches detections in I_0 with detections in I_{k_5}. We then independently apply the tracker on $\langle I_{k_5}, \ldots, I_n \rangle$ to derive another matrix $A^{(k_5,n)}$ that matches detections in I_{k_5} with detections in I_n. We combine these matrices through the matrix product to compute $A^{(0,n)}$: we compute $A^{(0,n)} = A^{(0,k_5)} A^{(k_5,n)}$. Similarly, we compute $B^{(0,n)} = B^{(0,k_6)} B^{(k_6,n)}$.

This scheme forces the tracker to find the same unique detection in I_{k_5} (and I_{k_6}) for two detections of the same object in I_0 and I_n in order to maximize similarity between the matrix products. However, a tracker that learns to match tracks to detections by comparing only the detection features in consecutive frames will exhibit high similarity between $A^{(0,n)}$ and $B^{(0,n)}$ under this scheme.

Combined Scheme. Only-Occlusion and RNN Hand-off have opposite advantages and drawbacks. Thus, we combine these in our occlusion-based hiding scheme. We first select the two sequences for simulated occlusion, $\langle I_{k_1}, \ldots, I_{k_2} \rangle$ and $\langle I_{k_3}, \ldots, I_{k_4} \rangle$. Then, we randomly pick k_5 and k_6 such that $k_3 \le k_5 \le k_4$ and $k_1 \le k_6 \le k_2$, i.e., the hand-off for one tracker occurs when the other tracker observes a simulated occlusion. We summarize the scheme in Figure 3.

Figure 3: Occlusion-based hiding produces input variations with different subsequences of occluded frames where all detections are hidden from the tracker. It also independently applies the tracker before and after a hand-off frame (I_4 and I_2), and merges the outputs through the matrix product.

Tracker B (Spatial)

(93, 681, 176, 103) (490, 429, 211, 140) (847, 325, 53, 37) (609, 282, 75, 48)
(950, 459, 143, 75) (740, 575, 235, 127) (458, 313, 62, 49) (899, 337, 62, 48)
(652, 333, 78, 87) (821, 335, 63, 47) (819, 336, 62, 47) (848, 325, 51, 38)

Figure 4: Visual-spatial hiding. One input includes only visual information about the detections, while the other includes only spatial bounding box coordinates.

Under this scheme, neither memorizing features in I_0 nor comparing detections solely in a pairwise frame-by-frame manner is an effective tracking strategy. Instead, the tracker must learn to leverage RNN features for re-localizing across simulated occlusion, while still ensuring the tracking decisions reflect intermediate outputs.

4.2   Visual-Spatial Hiding

Under visual-spatial hiding, we apply one tracker instance that observes only visual features and one tracker instance that observes only spatial features: in $A(D)$, we set $x = 0, y = 0, w = 0, h = 0$ for all detections, and in $B(D)$, we set $im = 0$. By encouraging similarity in the tracking outputs, each tracker learns to leverage its input features and track objects as robustly as possible.

To prevent the visual tracker from examining the background to extract an approximation of the spatial features, we do not use a recurrent unit for the visual tracker; instead, its matching network inputs visual features for detections in I_0 and for detections in I_n, and scores each pair of detections in $A^{(0,n)}$ without observing intermediate frames. We compute $B^{(0,n)}$ through the spatial tracker, which inputs 4D spatial coordinates for each detection, and processes frames with the matching network and recurrent unit. Figure 4 illustrates the training procedure.

5   Evaluation

We compare our method and nine baselines on the MOT17 [21] and KITTI [10] benchmarks.

Baselines. We compare with two unsupervised methods (SORT [2] and V-IOU [4]) and seven fully supervised methods (Tracktor++ [1], MHT-BLSTM [12], FAMNet [5], LSST [8], GSM [18], mmMOT [29], and CenterTrack [30]). Like our approach, SORT and V-IOU require an object detector, but do not train on any video-level bounding box and track annotations in the MOT17 and KITTI training sets. The fully supervised methods train on video-level annotations; Tracktor++ incorporates a core component that uses only the detector regression network, but requires video-level annotations for training a re-identification network. Results for 8 baselines are available on MOT17, and results for 4 baselines are available on KITTI.

Dataset. MOT17 [21] consists of 14 video sequences of pedestrians in a wide range of contexts, including a moving camera inside a shopping mall and a fixed, elevated view of an outdoor plaza. The dataset is split into 7 training sequences and 7 test sequences; each split includes approximately

Method	IDF1	MOTA
Occlusion (ours)	52.4	56.7
Visual-Spatial (ours)	**57.3**	**60.2**
Spatial-Only (ours)	56.5	57.8

Table 1: Ablation study on the MOT17 training set.

	Method	**IDF1**	**MOTA**	MT	ML	FP	FN	Idsw	Frag
Unsupervised Methods	Visual-Spatial (ours)	**58.3**	**56.8**	538	880	12K	231K	1K	2K
	SORT [2]	39.8	43.1	295	997	28K	288K	5K	7K
	IOU [3]	39.4	45.5	369	953	20K	282K	6K	7K
	Tracktor++ [1]	52.3	53.5	459	861	12K	248K	2K	5K
	MHT-BLSTM [12]	51.9	47.5	429	981	26K	268K	2K	3K
Supervised Methods	FAMNet [5]	48.7	52.0	450	787	14K	254K	3K	5K
	LSST [8]	62.3	54.7	480	944	26K	228K	1K	4K
	GSM [18]	57.8	56.4	523	813	14K	230K	1K	3K
	CenterTrack [30]	59.6	61.5	621	752	14K	201K	3K	5K

Table 2: Performance on the MOT17 test set. We compare methods in terms of IDF1 and MOTA, but include other non-comprehensive metrics from MOT17 as well for completeness.

Method	**HOTA**	DetA	AssA	DetRe	DetPr	AssRe	AssPr	LocA
Visual-Spatial (ours)	**62.5**	61.1	65.3	67.7	73.8	69.1	83.1	80.3
SORT [2]	42.5	44.0	41.3	47.3	73.9	42.8	83.0	80.8
FAMNet [5]	52.6	61.0	45.5	64.4	78.7	48.7	77.4	81.5
mmMOT [29]	62.1	72.3	54.0	76.2	84.9	59.0	82.4	86.6
CenterTrack [30]	73.0	75.6	71.2	80.1	84.6	73.8	89.0	86.5

Table 3: Performance on the KITTI test set (tracking cars). We show unsupervised methods, including our approach, at the top, and methods that require video-level annotations at the bottom. We use HOTA to compare methods, but include other non-comprehensive metrics from KITTI for completeness.

11 minutes of video. KITTI [10] consists of 48 video sequences captured from vehicle-mounted cameras, split into 20 for training and 28 for testing, and the objective is to track cars.

Training. The supervised baselines train on video-level bounding box and track annotations provided by MOT17 and KITTI. In contrast, our method trains only on a corpus of unlabeled video. Because video-level annotations are expensive to label, our method requires substantially less annotation time, and thus greatly reduces the effort needed to apply multi-object tracking on new datasets.

For MOT17, we collect unlabeled video from two sources: we use five hours of video from seven YouTube walking tours, and all train and test sequences from the PathTrack dataset [20] (we do not use the PathTrack ground truth annotations). For KITTI, we use both the 46 minutes of video in the KITTI dataset together with 7 hours of video from Berkeley DeepDrive [27]. We train our tracker model on an NVIDIA Tesla V100 GPU; training time varies between 4 and 24 hours depending on the input-hiding scheme. During training, we randomly select sequence lengths n between 4 and 16 frames, and apply stochastic gradient descent one sequence at a time. We apply the Adam optimizer with learning rate 0.0001, decaying to 0.00001 after plateau.

In contrast to MOT17, KITTI does not provide object detections for use by tracking methods. We extract detections from video using a YOLOv5 model trained on COCO. On MOT17, we pre-process detections with classification and regression following the pre-processing method in Tracktor++ [1].

Metrics. We use Multi-Object Tracking Accuracy (MOTA) [21] and ID F1 Score (IDF1) [22] on MOT17, and Higher Order Tracking Accuracy (HOTA) [19] for KITTI. Broadly, these comprehensive metrics measure the accuracy of inferred tracks against ground truth tracks, and penalize both when an inferred track contains a detection that doesn't match to some ground truth detection (or vice versa), and when a ground truth track is split into two or more inferred tracks (or vice versa). MOT17 and KITTI employ several other non-comprehensive metrics, many of which are used to compute MOTA, IDF1, and HOTA; we report these for completeness.

Figure 5: Output of Visual-Spatial on a portion of an MOT17 sequence. Our method tracks objects through several instances of occlusion.

Ablation Study. We first compare occlusion-based hiding and visual-spatial hiding on the MOT17 training set in Table 1. Visual-spatial hiding yields higher performance on both MOTA and IDF1 — because objects are often visible in the video for only a short duration, when training under occlusion-based hiding, the model is unable to learn to re-localize objects over simulated occlusions since the simulated occlusion must then also be short. Under Spatial-Only, we show results for visual-spatial hiding when inputting only the spatial coordinates of detections during inference (no image features).

Quantitative Results. Table 2 shows results on the MOT17 test set[1], and Table 3 shows results on the KITTI test set[2]. Metrics are automatically computed by the challenge websites. Per the challenge policies, we only submit the best method, and thus show Visual-Spatial performance.

On MOT17, our approach substantially outperforms both of the unsupervised baselines. Moreover, despite training only on unlabeled video, our method *outperforms* Tracktor++ [1], MHT-BLSTM [12], FAMNet [5], and GSM [18], even though these baselines (all of which except MHT-BLSTM were published in the last 1–2 years) are supervised methods that train on expensive video-level annotations in the MOT17 training set. Our approach is also competitive with LSST [8], yielding higher MOTA but lower IDF1. Nevertheless, CenterTrack [30] yields slightly higher accuracy on both metrics.

Similarly, on KITTI, our approach outperforms SORT [2], FAMNet [5], and mmMOT [29], but yields lower performance than CenterTrack [30].

Qualitative Results. We show qualitative results in Figure 5 and in the supplementary video.

6 Conclusion

In this paper, we have shown that a robust, fully unsupervised multi-object tracker can be trained through a novel self-supervisory learning signal, cross-input consistency, that enforces consistency in the tracking outputs across different input variations of one video sequence. Despite training only on unlabeled video, our approach outperforms four supervised trackers published in the last 1–2 years (Tracktor++ [1], FAMNet [5], GSM [18], and mmMOT [29]), which train on expensive video-level bounding box and track annotations.

Social Impact. By enabling a robust multi-object tracker to be trained given only unlabeled video, our work promises to greatly reduce the effort for users to apply multi-object tracking on new datasets without sacrificing accuracy. Thus, we believe that our novel self-supervised MOT method can open up new video analytics tasks that were previously too costly. This impact may be positive or negative depending on the nature of these tasks — however, in general, we believe that tasks with greater potential for negative impact such as surveillance and pedestrian tracking would not benefit from the reduction in annotation cost associated with our method.

---

[1]These results are taken from `https://motchallenge.net/results/MOT17/`, where our method is denoted UNS20regress. Baselines are denoted SORT17, IOU17, Tracktor++, MHT_bLSTM, FAMNet, LSST17, GSM_Tracktor, and CTTrackPub.

[2]These results are taken from `http://www.cvlibs.net/datasets/kitti/eval_tracking.php`.

References

[1] Philipp Bergmann, Tim Meinhardt, and Laura Leal-Taixe. Tracking without bells and whistles. In *IEEE International Conference on Computer Vision (ICCV)*, 2019.

[2] Alex Bewley, Zongyuan Ge, Lionel Ott, Fabio Ramos, and Ben Upcroft. Simple Online and Realtime Tracking. In *IEEE International Conference on Image Processing (ICIP)*, 2016.

[3] Erik Bochinski, Volker Eiselein, and Thomas Sikora. High-Speed Tracking-by-Detection Without Using Image Information. In *IEEE International Conference on Advanced Video and Signal Based Surveillance (AVSS)*, 2017.

[4] Erik Bochinski, Tobias Senst, and Thomas Sikora. Extending IOU Based Multi-Object Tracking by Visual Information. In *IEEE International Conference on Advanced Video and Signal Based Surveillance (AVSS)*, 2018.

[5] Peng Chu and Haibin Ling. FAMNet: Joint Learning of Feature, Affinity and Multi-dimensional Assignment for Online Multiple Object Tracking. In *IEEE International Conference on Computer Vision (ICCV)*, 2019.

[6] Carl Doersch, Abhinav Gupta, and Alexei A Efros. Unsupervised Visual Representation Learning by Context Prediction. In *IEEE International Conference on Computer Vision (ICCV)*, 2015.

[7] Carl Doersch and Andrew Zisserman. Multi-task Self-Supervised Visual Learning. In *IEEE International Conference on Computer Vision (ICCV)*, 2017.

[8] Weitao Feng, Zhihao Hu, Wei Wu, Junjie Yan, and Wanli Ouyang. Multi-object tracking with multiple cues and switcher-aware classification. *arXiv preprint arXiv:1901.06129*, 2019.

[9] Basura Fernando, Hakan Bilen, Efstratios Gavves, and Stephen Gould. Self-supervised video representation learning with odd-one-out networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, July 2017.

[10] Andreas Geiger, Philip Lenz, and Raquel Urtasun. Are we ready for autonomous driving? The KITTI Vision Benchmark Suite. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2012.

[11] Shyamgopal Karthik, Ameya Prabhu, and Vineet Gandhi. Simple unsupervised multi-object tracking. *CoRR*, abs/2006.02609, 2020.

[12] Chanho Kim, Fuxin Li, and James M. Rehg. Multi-Object Tracking with Neural Gating using Bilinear LSTM. In *European Conference on Computer Vision (ECCV)*, 2018.

[13] Zihang Lai, Erika Lu, and Weidi Xie. Mast: A memory-augmented self-supervised tracker. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.

[14] Laura Leal-Taixé, Anton Milan, Ian Reid, Stefan Roth, and Konrad Schindler. MOTChallenge 2015: Towards a Benchmark for Multi-Target Tracking. *arXiv preprint arXiv:1504.01942*, 2015.

[15] Hsin-Ying Lee, Jia-Bin Huang, Maneesh Singh, and Ming-Hsuan Yang. Unsupervised representation learning by sorting sequences. In *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, Oct 2017.

[16] Xueting Li, Sifei Liu, Shalini De Mello, Xiaolong Wang, Jan Kautz, and Ming-Hsuan Yang. Joint-task self-supervised learning for temporal correspondence. In *Advances in Neural Information Processing Systems*, volume 32, 2019.

[17] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft COCO: Common Objects in Context. In *European Conference on Computer Vision (ECCV)*, 2014.

[18] Qiankun Liu, Qi Chu, Bin Liu, and Nenghai Yu. GSM: Graph Similarity Model for Multi-Object Tracking. In *International Joint Conference on Artificial Intelligence (IJCAI)*, 2020.

[19] Jonathon Luiten, Aljosa Osep, Patrick Dendorfer, Philip Torr, Andreas Geiger, Laura Leal-Taixé, and Bastian Leibe. HOTA: A Tigher Order Metric for Evaluating Multi-Object Tracking. *International Journal of Computer Vision*, 129(2):548–578, 2021.

[20] Santiago Manen, Michael Gygli, Dengxin Dai, and Luc Van Gool. PathTrack: Fast Trajectory Annotation with Path Supervision. In *IEEE International Conference on Computer Vision (ICCV)*, 2017.

[21] Anton Milan, Laura Leal-Taixé, Ian Reid, Stefan Roth, and Konrad Schindler. MOT16: A Benchmark for Multi-Object Tracking. *arXiv preprint arXiv:1603.00831*, 2016.

[22] Ergys Ristani, Francesco Solera, Roger Zou, Rita Cucchiara, and Carlo Tomasi. Performance Measures and a Data Set for Multi-Target, Multi-Camera Tracking. In *European Conference on Computer Vision (ECCV)*, 2016.

[23] Nitish Srivastava, Elman Mansimov, and Ruslan Salakhudinov. Unsupervised Learning of Video Representations using LSTMs. In *International Conference on Machine Learning (ICML)*, 2015.

[24] Carl Vondrick, Abhinav Shrivastava, Alireza Fathi, Sergio Guadarrama, and Kevin Murphy. Tracking Emerges by Colorizing Videos. In *European Conference on Computer Vision (ECCV)*, 2018.

[25] Xiaolong Wang, Allan Jabri, and Alexei A Efros. Learning Correspondence from the Cycle-Consistency of Time. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019.

[26] Donglai Wei, Joseph J. Lim, Andrew Zisserman, and William T. Freeman. Learning and using the arrow of time. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2018.

[27] Huazhe Xu, Yang Gao, Fisher Yu, and Trevor Darrell. End-to-end learning of driving models from large-scale video datasets. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, July 2017.

[28] Jenny Yuen, Bryan Russell, Ce Liu, and Antonio Torralba. LabelMe video: Building a Video Database with Human Annotations. In *IEEE International Conference on Computer Vision (ICCV)*, 2009.

[29] Wenwei Zhang, Hui Zhou, Shuyang Sun, Zhe Wang, Jianping Shi, and Chen Change Loy. Robust multi-modality multi-object tracking. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, October 2019.

[30] Xingyi Zhou, Vladlen Koltun, and Philipp Krähenbühl. Tracking Objects as Points. In *European Conference on Computer Vision (ECCV)*, 2020.