MetaPS: Adaptive Programmatic Strategy Selection for Market Agents

Abstract

No single market strategy always wins: momentum, mean reversion, risk control, and event-driven rules can each succeed or fail as market conditions change. Rather than asking large language models to directly generate market actions, we study an executable decision paradigm where an agent selects from a library of programmatic strategies, each implemented as a code module mapping market observations to actions. We propose **MetaPS**, a simulation-guided framework for adaptive programmatic strategy selection. MetaPS rolls out candidate strategies in simulated or backtested markets, identifies states where particular strategies lead to better future outcomes, and converts these state–strategy pairs into supervised fine-tuning data. During inference, the simulator is no longer queried: MetaPS observes only the current market state and candidate strategy context, selects a suitable strategy program, and the selected program produces the final action. Experiments on multi-stock trading and a controlled goods-exchange sandbox show that MetaPS consistently improves across model scales from 0.8B to 9B parameters. It outperforms fixed-strategy baselines, direct decision-making agents, and prompted API-based LLM agents; in several settings, compact fine-tuned models even surpass stronger API models. These results demonstrate that market simulations can provide scalable and targeted supervision for learning adaptive, interpretable, and executable strategy selection.

1 Introduction

No single strategy consistently wins in financial and economic markets. Momentum rules can exploit trend continuation but fail during reversals; mean-reversion rules can benefit from overreaction but lose under persistent news shocks; risk-control rules can preserve capital during stress but miss upside in expansionary regimes. These behaviors are consistent with heavy-tailed returns, volatility clustering, and regime-dependent dynamics (Mandelbrot et al., 1963; Cont, 2001; Bouchaud et al., 2009). Market decision-making is therefore not only about designing strong strategies, but also about deciding *when each strategy should be used*.

Recent learning-based trading systems often formulate this problem as direct action prediction, mapping observations to buy, sell, hold, allocation, or exchange decisions (Ozbayoglu et al., 2020; Schulman et al., 2017; Chen et al., 2021). LLMs further allow decisions to condition on heterogeneous textual and numerical context, such as news, market summaries, and portfolio states (Liu et al., 2023; Yu et al., 2025; Xiao et al., 2024). However, direct generation entangles two separable decisions: selecting the market logic appropriate to the current state and executing the concrete action implied by that logic. This coupling can make decisions harder to audit, constrain, and reproduce.

We study a more executable paradigm: adaptive selection over programmatic strategies. The agent is given a library of strategies, each implemented as a code module that maps market observations to actions. These modules play a role similar to tools or skills in LLM agents (Yao et al., 2022; Schick et al., 2023; Patil et al., 2024; Lu et al., 2023): they expose reusable executable behavior, while the learned model serves as a meta-level selector. Instead of asking the LLM to directly invent a trade, MetaPS asks it to choose which program should control the next decision; the selected program then produces the final action through a deterministic runtime with feasibility, sizing, and risk checks.

The central challenge is supervision. Historical market data does not directly label the best strategy for each state, and the answer may depend on future outcomes. MetaPS addresses this by using market simulations and backtesting rollouts as targeted supervision. For each as-of state, it rolls out candidate strategy programs, estimates their future outcomes, mines effective state–strategy pairs, and

converts them into supervised fine-tuning data. Future outcomes are used only to construct training targets and are never shown to the model at inference time.

We propose **MetaPS** (*Meta Programmatic Selector*), a simulation-guided framework for adaptive programmatic strategy selection. MetaPS first builds a ranked candidate strategy context from the current market state, then trains an LLM router with simulation-derived labels to select a strategy program and coarse execution fields. During inference, the router observes only the as-of state and ranked strategy context, selects a suitable programmatic strategy, and delegates action generation to the selected executable module.

We evaluate MetaPS on historical multi-stock trading and a controlled goods-exchange sandbox. Across model scales from 0.8B to 9B parameters, MetaPS improves over fixed-strategy baselines, direct decision-making agents, and prompted API-based LLM agents. In several settings, compact fine-tuned MetaPS models outperform stronger API models, suggesting that targeted simulation-derived supervision can be more effective than general-purpose prompting for strategy-level market decisions.

Our contributions are threefold:

- We formulate financial and economic market decision-making as adaptive selection over executable programmatic strategies, separating strategy choice from action execution.

- We introduce **MetaPS**, a simulation-guided framework that derives supervised fine-tuning data from candidate strategy rollouts in market simulations and backtests.

- We evaluate MetaPS across stock-trading and goods-exchange environments, showing consistent gains across 0.8B–9B models over fixed-strategy, direct-agent, and API-based prompting baselines.

We provide related work in Appendix B to keep the main text focused on the method and empirical analysis.

2 Method

2.1 Problem Formulation

We study market decision making with a library of executable programmatic strategies. At step t, the environment provides an as-of observation $o_t \in \mathcal{O}$,

recent history h_t, and action space $\mathcal{A}$. Rather than mapping observations directly to actions, MetaPS assumes a strategy library

$$\mathcal{S} = \{s_1, \ldots, s_N\}, \qquad s_i : \mathcal{O} \to \mathcal{A},$$

where each s_i is an executable module that maps the current market state to a feasible action.

MetaPS learns a router over a ranked candidate subset $\mathcal{C}_t \subseteq \mathcal{S}$. Given the current observation, recent history, and candidate programs, the router predicts

$$z_t = \arg\max_{z \in \mathcal{C}_t} p_\theta(z \mid o_t, h_t, \mathcal{C}_t).$$

The selected program then produces the final action, $a_t = s_{z_t}(o_t)$. Thus, the language model decides *which program to execute*, while the executable strategy decides *which market action to take*. This factorization makes the decision process more interpretable, executable, and auditable than direct action generation.

2.2 Programmatic Strategy Library

The strategy library defines the executable decision primitives available to MetaPS. Each program follows a shared interface: it consumes an as-of market state and returns structured action fields, such as direction, target asset or resource, confidence, risk note, and coarse size. A deterministic execution layer applies feasibility, sizing, cost, and domain-specific constraints.

The concrete library is domain-specific. In the multi-stock trading environment, the library covers trend-following, reversal, news-driven, hedging, risk-control, and breakout-style strategies. In the controlled goods-exchange sandbox, the library includes producer, processor, contractor, merchant, hoarder, and balanced programs. Although the action spaces differ, the MetaPS interface is unchanged: the model selects a program identifier, and the selected executable module emits the final action.

2.3 Simulation-Guided Supervision

The key challenge is that state–strategy labels are not directly available. MetaPS constructs them through counterfactual strategy rollouts in a market simulator or historical backtester $\mathcal{M}$. For an as-of state o_t, $\mathcal{M}$ rolls out each candidate program $s_i \in \mathcal{C}_t$ from the same state snapshot. With discount

Figure 1: Overview of MetaPS. Market simulations supervise a meta-level router by rolling out executable strategy programs from the same as-of state. The resulting state–strategy winners are converted into supervised fine-tuning data. At inference time, MetaPS observes the current market state and a ranked candidate set, selects one programmatic strategy, and delegates final action generation to the selected executable program.

factor γ and horizon H, the rollout return is

$$G_i^{(H)}(o_t) = \sum_{\tau=0}^{H-1} \gamma^\tau r_{t+\tau}^{(i)},$$

where $r_{t+\tau}^{(i)}$ is the reward obtained when actions are generated by s_i during that counterfactual rollout. A training view v defines a view-specific score $q_i^v(o_t)$ from these rollout outcomes, and the corresponding target strategy is

$$z_{t,v}^\star = \arg\max_{s_i \in \mathcal{C}_t} q_i^v(o_t).$$

This produces state–strategy supervision rather than low-level action labels. The simulations are therefore a training-time source of labels, not an additional test-time input. Future rollout rewards are used only to construct labels and are not exposed in the model-facing input.

Candidate strategy context. MetaPS does not choose from an unstructured full library. We first construct a ranked candidate set using a lightweight relevance score $\rho(s_i, o_t)$ and a candidate budget B:

$$\mathcal{C}_t = \mathrm{Top}_B \{\rho(s_i, o_t)\}_{s_i \in \mathcal{S}}.$$

The score uses state phrases, strategy triggers, and missing-evidence penalties. The ranked packet is

included in the prompt, keeping the model's choice space compact while preserving interpretable program options. In the stock experiments, $N = B = 10$, so the ranked context contains the full ten-strategy library but preserves the scorer's ordering and scores. Appendix C.2 defines the ranking score, and Appendix C.3 describes the corresponding input ablations.

Training views. We construct a small set of simulation-derived training views $\mathcal{V} = \{V1, V2, V3\}$. V1 selects the short-horizon winner, V2 favors medium-horizon advantage, and V3 balances return with risk and behavioral regularization. All views share the same input and output format, but they induce different labels $z_{t,v}^\star$ through different scores $q_i^v(o_t)$. They are not a monotonic curriculum; instead, they expose MetaPS to different strategy-selection biases. Appendix C.4 gives the exact scoring definitions.

2.4 MetaPS Learning and Inference

The simulation-derived labels are converted into instruction-following examples. For state t and training view $v \in \mathcal{V}$, the model input and target text are

$$x_t = (o_t, h_t, \mathcal{C}_t), \qquad y_{t,v} = (z_{t,v}^\star, d_{t,v}, m_{t,v}),$$

Algorithm 1 MetaPS: simulation-guided programmatic strategy selection

1: **Input:** library $\mathcal{S}$, simulator $\mathcal{M}$, views $\mathcal{V}$
2: Initialize SFT dataset $\mathcal{D} \leftarrow \emptyset$
3: **for** each as-of state o_t from $\mathcal{M}$ **do**
4:      Rank programs and form $\mathcal{C}_t$
5:      **for** each $s_i \in \mathcal{C}_t$ **do**
6:          Roll out s_i and estimate $G_i^{(H)}(o_t)$
7:      **end for**
8:      **for** each view $v \in \mathcal{V}$ **do**
9:          Select label $z_{t,v}^{\star}$ using score $q_i^v(o_t)$
10:         Build instruction pair $(x_t, y_{t,v})$
11:         Add $(x_t, y_{t,v}, w_{t,v})$ to $\mathcal{D}$
12:      **end for**
13: **end for**
14: Fine-tune p_θ on $\mathcal{D}$
15: At test time, select $\hat{z}_t$ and execute $s_{\hat{z}_t}$

where $z_{t,v}^{\star}$ is the selected strategy label from Section 2.3, $d_{t,v}$ contains structured execution fields, and $m_{t,v}$ is a concise rationale. A teacher model rewrites raw rollout records into fluent rationales while preserving the selected strategy and action fields. The rewrite is based only on model-visible state information, so future rewards and counterfactual outcomes do not leak into the prompt.

Let $\mathcal{D} = \{(x_t, y_{t,v}, w_{t,v})\}$ denote the generated SFT data, where $w_{t,v}$ is an optional confidence weight derived from rollout quality. MetaPS is trained with a weighted language-model objective:

$$\mathcal{L}_{\text{sft}}(\theta) = -\sum_{(t,v)} w_{t,v} \log p_\theta(y_{t,v} \mid x_t).$$

The target text teaches the model to produce a strategy-level decision, not a raw market action. Appendix C.5 details the reward-derived weights, and Appendix C.6 gives the full response format.

At inference time, the simulator and rollout rewards are absent. MetaPS receives only the observable input $x_t = (o_t, h_t, \mathcal{C}_t)$, predicts a strategy identifier, and then calls the selected executable program:

$$\hat{z}_t = \arg\max_{z \in \mathcal{C}_t} p_\theta(z \mid x_t),$$
$$a_t = s_{\hat{z}_t}(o_t).$$

The environment applies feasibility constraints, sizing rules, costs, slippage, and domain-specific execution constraints. Outcomes are logged for evaluation; if the state is later reused for training, they may also become part of a new simulation-derived supervision set. Additional execution details are provided in Appendix C.9.

3 Experiments

The experiments test whether MetaPS improves market decisions by learning *when to switch among executable strategies*. The primary benchmark is historical multi-stock trading, where each daily decision uses an as-of market state and a ranked set of programmatic strategies. We then evaluate the same interface in a controlled goods-exchange sandbox, analyze the role of ranked strategy context, compare training objectives across model scales, and test temporal robustness with expanding-window validation. Additional diagnostics, including risk–return plots, return curves, prompt formats, and full metrics, are reported in Appendix E.

3.1 Experimental Setup

Environments. We use two environments with the same high-level strategy-selection interface.

- **Multi-stock trading** is the primary benchmark. It trains on 2022–2024 and tests on 2025, starts with \$1,000,000, and models transaction costs, slippage, and position constraints. Each daily observation is strictly as-of and includes price bars, news/event summaries, flow, portfolio state, and candidate strategies.

- **Goods-exchange sandbox** is a controlled auxiliary economy with cash, inventory, prices, production capacity, contracts, and regime notices. It uses the same strategy-selection interface but a non-financial execution space.

Full environment definitions, metric details, and execution rules are provided in Appendix D.

Programmatic strategy libraries. Training and inference use the same executable libraries. The stock library contains ten strategies, including news impulse, momentum following, mean-reversion fading, risk reset, macro rotation, and volatility breakout. In the main Ranked-Strategy setting, all ten stock strategies are visible and ranked by a lightweight signal scorer; the context therefore contains the full library while preserving relevance scores and ordering. The sandbox library contains six economic policies: producer, processor, contractor, merchant, hoarder, and balanced. In both environments, MetaPS selects *which strategy should act*; the selected program and runtime produce the final executable action. Code-level strategy details are in Appendix C.7.

Figure 2: Stock-market return comparison across baseline families on the held-out 2025 benchmark. MetaPS is compared with strategy-only baselines, non-LLM learned selectors, base/API LLM prompting, and matched-backbone Qwen routers.

Figure 3: Cumulative return trajectories on the held-out 2025 stock benchmark. The plot compares MetaPS with Qwen base models, API prompting, and a random strategy baseline over the same calendar period.

Compared systems. We compare four method families: strategy-only baselines, non-LLM learned selectors, LLM prompting baselines, and MetaPS fine-tuned routers. The non-LLM selectors include classifier, sequence, reward-ranking, and RL policy variants. LLM baselines use base Qwen or API models without SFT. Unless otherwise stated, LLM methods use the *Ranked-Strategy* context, where the as-of state is shown together with ranked strategy scores. For MetaPS, simulations are used only before training to derive state–strategy supervision; all test-time methods are evaluated from the same observable state interface.

3.2 Main Results on Stock Trading

Table 1 reports the main comparison on the held-out 2025 stock benchmark and the controlled sand-box, with Figure 2 visualizing the stock-return results. MetaPS-9B achieves the highest stock return among the main-table methods, reaching 50.29%, while MetaPS-4B obtains the highest sandbox terminal equity, reaching 31514. Matched-backbone comparisons are consistent: MetaPS improves over the Qwen-4B base router in both environments, and the 9B sandbox run increases return from 118.53% to 251.90%. Since base and fine-tuned routers share the same strategy interface, these gains indicate that supervised meta-policy learning improves strategy switching rather than changing the executable strategy space. Figure 3 further shows that the stock gain is not merely a final-day effect: MetaPS maintains a stronger cumulative-return trajectory through much of the held-out year. Additional equity, drawdown, excess-return, monthly, and quarterly diagnostics are provided in Appendix E.3.

The baselines clarify what MetaPS adds. Random and fixed strategies achieve non-trivial returns, showing that the library is useful, but their gap to MetaPS indicates that static or unguided strategy use is insufficient. Non-LLM selectors, including the retrained classifier, are competitive in some cases but remain below the learned language-based router. Prompting-only LLMs offer a complementary comparison: GPT-5.4 achieves the best stock-market Sharpe ratio and lowest drawdown, and both API models transfer to the sandbox without SFT, yet their returns remain below MetaPS in both environments. Thus, neither general-purpose prompting nor access to executable strategies alone recovers the high-return, context-dependent routing policy learned by MetaPS.

3.3 Extension to a Controlled Economic Sandbox

We further evaluate MetaPS in a controlled goods-exchange sandbox to test whether the same strategy-routing interface extends beyond historical stock trading. The sandbox contains cash, inventory, market price, and six economic regimes: expansion, shortage, processing boom, stable contract, downturn, and volatile markets. At each day, the model observes the economic state and selects one of six executable strategies: producer, processor, contractor, merchant, hoarder, or balanced. Although the environment differs from ticker-level trading, the learning problem remains unchanged: deciding when to switch among reusable programmatic strategies.

Table 1: Main results across the two evaluation environments. Stock results are reported on the held-out 2025 benchmark. The goods-exchange sandbox is a controlled auxiliary environment. Qwen and MetaPS rows report matched-backbone comparisons at 4B and 9B where available. Higher return, Sharpe, terminal equity, and winner share are better; lower maximum drawdown is better.

	Multi-stock Trading			Goods-exchange Sandbox		
Method	Return ↑	Sharpe ↑	Max DD ↓	Terminal Equity ↑	Return ↑	Winner Share ↑
Strategy-only Baselines						
Random Strategy	30.91	0.828	9.21	13401	54.84	16.2
Best Fixed Strategy	30.23	0.705	23.53	18609	115.02	38.0
Non-LLM Learned Selectors						
Strategy Classifier	35.90	0.778	16.78	26647	207.89	53.0
Sequence Selector	19.54	0.924	18.73	23872	175.84	50.0
Reward-Ranking Selector	19.64	0.275	20.87	26002	200.45	53.0
RL Q-Policy Selector	23.14	0.493	19.51	15030	73.67	41.0
LLM Prompting Baselines						
Qwen3.5-4B	25.12	0.916	16.59	23879	175.92	41.0
Qwen3.5-9B	32.69	0.762	27.30	18912	118.53	23.0
GPT-5.4-mini	14.22	0.319	11.04	23249	168.64	54.0
GPT-5.4	32.03	**1.112**	**3.05**	23554	172.16	53.0
Ours						
MetaPS-4B	45.72	0.705	12.57	**31514**	**264.14**	**59.0**
MetaPS-9B	**50.29**	0.668	15.29	30455	251.90	56.0

As shown in Table 1, MetaPS improves over the Qwen base router in this controlled setting. For 4B, it raises terminal equity from 23879 to 31514, return from 175.92% to 264.14%, and winner share from 41.0% to 59.0%; the 9B comparison shows the same trend, more than doubling base return and increasing winner share from 23.0% to 56.0%. MetaPS also achieves the best terminal equity and winner share among strategy-only, non-LLM, and API prompting baselines. We treat the sandbox as a cross-environment extension rather than primary evidence because it is synthetic, but the result suggests that MetaPS is not tied to a specific stock backtester or ticker-level action space. A compact sandbox visualization and full sandbox metrics are reported in Appendix E.6.

3.4 Strategy Behavior Analysis

Figure 4 connects the simulation-derived labels to the router's held-out behavior. The three SFT views correspond to different ways of converting rollout outcomes into supervision: V1 emphasizes short-horizon winners, V2 spreads more mass across medium-horizon active trading strategies, and V3 rebalances toward a broader but still structured label distribution. At test time, the best overall router does not sample the library uniformly. In the 2025 regime, MetaPS-9B V3 concentrates on momentum-following while retaining news impulse, mean-reversion, risk reset, and earnings drift

Figure 4: Strategy behavior under simulation-derived supervision. Left: strategy-label distributions from the three rollout-based SFT views. Right: held-out 2025 strategy-selection distribution of MetaPS-9B V3. All ten stock strategies remain available; unused strategies are discussed in Appendix E.5.

as secondary programs. This is the intended effect of simulation guidance: rollouts shape a selective meta-controller over a fixed library, rather than producing an unconstrained action generator or a uniform strategy sampler. Cross-scale strategy heatmaps and BUY/HOLD/SELL diagnostics are reported in Appendix E.5.

3.5 Effect of Strategy Context

Table 2 isolates the role of strategy context. Ranked-Strategy Context is strongest: MetaPS-9B V3 reaches 50.29% return, compared with 32.69% for Qwen3.5-9B under the same context and 30.12% for MetaPS under All-Strategies Context. API-only results show the same pattern: GPT-

Figure 5: Risk–return comparison across model scales. Hollow circles denote Qwen base models and filled circles denote the best MetaPS variants at matched scales. Arrows show that MetaPS consistently shifts the base models toward higher returns, with annotations reporting return gains in percentage points. Gray triangles indicate prompting-only API references.

Table 2: Ablation of strategy context and action-level prediction on the held-out 2025 stock benchmark. All Open rows use Qwen3.5-9B; API rows are prompting-only.

Source	Run	Target	Tuned	Ret. ↑	DD ↓
Ranked-Strategy Context					
API	GPT-5.4	Strategy	No	32.03	**3.05**
API	GPT-5.4-mini	Strategy	No	14.22	11.04
Open	Qwen3.5-9B	Strategy	No	32.69	27.30
Open	MetaPS-9B V3	Strategy	Yes	**50.29**	15.29
All-Strategies Context					
API	GPT-5.4	Strategy	No	15.49	5.88
API	GPT-5.4-mini	Strategy	No	11.69	**2.62**
Open	Qwen3.5-9B	Strategy	No	14.51	13.91
Open	MetaPS-9B	Strategy	Yes	**30.12**	16.60
Direct-Action Context					
API	GPT-5.4	Action	No	16.66	4.09
API	GPT-5.4-mini	Action	No	7.71	2.38
Open	Qwen3.5-9B	Action	No	29.30	15.14
Open	Qwen3.5-9B SFT	Action	Yes	3.14	**1.65**

Table 3: Goods-exchange sandbox objective analysis for the 9B router. Values are reported on the 100-day test split.

Run	Equity ↑	Ret. ↑	Win. ↑	Sharpe ↑	DD ↓
Base	18912	118.53	23.0	14.40	1.47
V1	**30455**	**251.90**	56.0	27.01	**0.00**
V2	28705	231.68	55.0	28.24	**0.00**
V3	30302	250.13	**57.0**	34.53	1.17

5.4 performs best with ranked strategies, while unranked or direct-action prompting is weaker. This suggests that ranked strategies provide a compact executable decision space, not merely extra text.

The Direct-Action Context shows that the gain is not due to fine-tuning alone. With the same 9B backbone and 2022–2024 training window, direct-action SFT reduces return from 29.30% to 3.14%, whereas strategy-level SFT reaches 50.29%. This supports the MetaPS design: simulation-derived supervision is more effective for learning strategy-level routing, while the selected program and runtime handle low-level execution. Appendix E.4 and Appendix E.1 provide the corresponding visualizations and full metrics.

3.6 Scaling and Objective Analysis

Figure 5, and Figure 6 show that the best training objective is not universal. V3 is strongest for 0.8B and 9B, V2 for 2B, and the serial V1→V2→V3 curriculum for 4B, indicating that V1, V2, and V3 induce different routing behaviors rather than forming a monotonic ladder. Across all tested Qwen scales, the best MetaPS variant improves over the corresponding base model: return increases by 10.18 percentage points for 0.8B, 10.48 for 2B, 20.60 for 4B, and 17.60 for 9B. The larger 4B and 9B gains are especially favorable because they also reduce maximum drawdown. Full metrics for all rows, including final value, Sharpe, drawdown, trades, win rate, and hold rate, are reported in Appendix E.2; additional heatmap and lift visualizations are in Appendix E.4.

Table 3 mirrors this objective analysis in the goods-exchange sandbox. All three MetaPS objectives substantially improve over the 9B base router, but they emphasize different properties: V1 is best by terminal equity and return, V3 is best by winner share and Sharpe, and V2 provides a middle point with zero observed drawdown. This reinforces the interpretation that the objectives encode distinct routing biases rather than a strictly ordered curriculum.

3.7 Rolling-Time Validation

The main 2025 benchmark is a fixed train/test split. To test temporal robustness, we add an expanding-window validation using the 4B router as the controlled model size. The first split trains on 2022 and tests on 2023–2025. The second trains on 2022–2023 and tests on 2024–2025. The main setting, 2022–2024 training followed by 2025 testing, is included as the third split. Because the test horizons differ in length, the table should be read within each block: it compares objectives under

Figure 6: 2025 returns across Qwen model scales under the Ranked-Strategy setting. Bars show MetaPS variants, colors denote training objectives, and stars mark the best variant at each scale.

Table 4: Rolling-time validation results of the 4B router. Each block trains on earlier years and tests on subsequent unseen years.

Objective	Return ↑	Trades	Win Rate ↑	Sharpe ↑	Max DD ↓
Train: 2022	**Test: 2023–2025**				
Base	94.74	305	81.48	**1.140**	27.23
V1	**197.46**	63	**100.00**	0.404	24.19
V2	28.11	515	58.53	0.016	**3.29**
V3	41.20	441	58.96	0.523	16.59
V1→V2	55.62	275	57.72	-0.073	10.87
V1→V2→V3	128.72	279	68.38	-0.007	26.79
Train: 2022–2023	**Test: 2024–2025**				
Base	64.46	114	86.67	**0.888**	29.59
V1	100.48	67	80.77	-0.020	**26.52**
V2	**117.49**	100	77.42	0.046	33.66
V3	87.39	95	83.78	0.293	30.08
V1→V2	113.59	86	**88.00**	0.058	32.26
V1→V2→V3	58.06	127	87.50	0.382	29.56
Train: 2022–2024	**Test: 2025**				
Base	25.12	82	32.35	0.916	16.59
V1	18.39	76	25.00	**1.016**	25.85
V2	40.69	56	28.57	0.583	28.48
V3	40.00	88	**45.00**	0.564	14.21
V1→V2	33.26	54	30.77	0.581	29.47
V1→V2→V3	**45.72**	93	26.32	0.705	**12.57**

the same train/test window. This analysis complements the single held-out 2025 benchmark by checking whether MetaPS remains useful when the training window is shortened and the test period spans different market regimes.

Table 4 refines the main 2025 conclusion by testing whether the same objective choices remain useful under shorter training windows and longer unseen horizons. With only 2022 supervision, V1 performs best over 2023–2025, suggesting that short-horizon winner imitation can identify a small number of high-conviction opportunities. After adding 2023 to training, V2 becomes strongest over 2024–2025, with the serial V1→V2 model close behind. In the shorter 2025-only test, the full serial curriculum is strongest for 4B and also has the most favorable drawdown among the 4B trained variants. Thus V3 is not uniformly better or worse; its value depends on both the market regime and the placement of the objective in the curriculum. The cumulative 2025 curve in Figure 3 complements this table by showing the within-year path for the final held-out split.

4 Conclusion

We introduced MetaPS, a framework for learning when to switch among interpretable programmatic strategies. By shifting learning from low-level market actions to strategy-level meta-control, MetaPS reuses executable strategies while adapting to changing market conditions. Results show that strategy routing is effective and supervision choice matters: ranked strategy context outperforms unranked or strategy-free prompting, supervised routing improves over base Qwen models across scales, and rolling-time validation shows that V1, V2, and V3 encode distinct behavioral biases rather than a monotonic curriculum. These findings support simulation-guided strategy selection as a practical path toward more executable, interpretable, and adaptive LLM-based market agents.

5 Limitations

MetaPS is a research framework for strategy selection, not investment advice or a deployable trading system. Our stock results are historical backtests with modeled costs, slippage, and constraints, and may not fully capture live-market risks such as liquidity shocks, latency, market impact, or distribution shift. The goods-exchange sandbox is synthetic and is used only to test whether the strategy-selection interface transfers beyond stock trading. MetaPS also depends on the coverage of its strategy library and the fidelity of its simulator, so missing strategies or biased simulations may affect the learned router. Future work should include stronger stress tests, confidence intervals, and live-market robustness checks, with any real-world use requiring human oversight, conservative risk limits, and audit logs.

References

Selim Amrouni, Aymeric Moulin, Jared Vann, Svitlana Vyetrenko, Tucker Balch, and Manuela Veloso. 2021. ABIDES-Gym: gym environments for multi-agent discrete event simulation and application to financial markets. In *Proceedings of the Second ACM International Conference on AI in Finance*, pages 1–9.

Peter Auer, Nicolo Cesa-Bianchi, and Paul Fischer. 2002. Finite-time analysis of the multiarmed bandit problem. *Machine learning*, 47(2):235–256.

Jean-Philippe Bouchaud, J Doyne Farmer, and Fabrizio Lillo. 2009. How markets slowly digest changes in supply and demand. In *Handbook of financial markets: dynamics and evolution*, pages 57–160. Elsevier.

William Brock, Josef Lakonishok, and Blake LeBaron. 1992. The profitability of technical analysis: A study of moving average and trading range breakout rules in the u.s. stock market. *The Journal of Finance*, 47(5):1731–1764.

Sébastien Bubeck, Nicolo Cesa-Bianchi, and 1 others. 2012. Regret analysis of stochastic and nonstochastic multi-armed bandit problems. *Foundations and Trends® in Machine Learning*, 5(1):1–122.

David Byrd, Maria Hybinette, and Tucker Hybinette Balch. 2020. ABIDES: Towards high-fidelity multi-agent market simulation. In *Proceedings of the 2020 ACM SIGSIM Conference on Principles of Advanced Discrete Simulation*, pages 11–22.

Lili Chen, Kevin Lu, Aravind Rajeswaran, Kimin Lee, Aditya Grover, Misha Laskin, Pieter Abbeel, Aravind Srinivas, and Igor Mordatch. 2021. Decision transformer: Reinforcement learning via sequence modeling. *Advances in neural information processing systems*, 34:15084–15097.

Prateek Chhikara, Dev Khant, Saket Aryan, Taranjeet Singh, and Deshraj Yadav. 2025. Mem0: Building production-ready ai agents with scalable long-term memory. *arXiv preprint arXiv:2504.19413*.

Rama Cont. 2001. Empirical properties of asset returns: stylized facts and statistical issues. *Quantitative finance*, 1(2):223.

Werner FM De Bondt and Richard Thaler. 1985. Does the stock market overreact? *The Journal of finance*, 40(3):793–805.

Kelvin Du, Yazhi Zhao, Rui Mao, Frank Xing, and Erik Cambria. 2025. Natural language processing in finance: A survey. *Information Fusion*, 115:102755.

Runnan Fang, Yuan Liang, Xiaobin Wang, Jialong Wu, Shuofei Qiao, Pengjun Xie, Fei Huang, Huajun Chen, and Ningyu Zhang. 2025. Memp: Exploring agent procedural memory. *arXiv preprint arXiv:2508.06433*.

J Doyne Farmer and Duncan Foley. 2009. The economy needs agent-based modelling. *Nature*, 460(7256):685–686.

Evan Gatev, William N Goetzmann, and K Geert Rouwenhorst. 2006. Pairs trading: Performance of a relative-value arbitrage rule. *The review of financial studies*, 19(3):797–827.

Campbell R Harvey, Edward Hoyle, Russell Korgaonkar, Sandy Rattray, Matthew Sargaison, and Otto Van Hemert. 2018. The impact of volatility targeting. *Available at SSRN 3175538*.

Cars H Hommes. 2006. Heterogeneous agent models in economics and finance. *Handbook of computational economics*, 2:1109–1186.

Michael Janner, Qiyang Li, and Sergey Levine. 2021. Offline reinforcement learning as one big sequence modeling problem. *Advances in neural information processing systems*, 34:1273–1286.

Narasimhan Jegadeesh and Sheridan Titman. 1993. Returns to buying winners and selling losers: Implications for stock market efficiency. *The Journal of finance*, 48(1):65–91.

Blake LeBaron. 2006. Agent-based computational finance. *Handbook of computational economics*, 2:1187–1233.

Jean Lee, Nicholas Stevens, Soyeon Caren Han, and Minseok Song. 2024. A survey of large language models in finance (finllms). *arXiv preprint arXiv:2402.02315*.

Xiao-Yang Liu, Guoxuan Wang, Hongyang Yang, and Daochen Zha. 2023. FinGPT: Democratizing internet-scale data for financial large language models. *arXiv preprint arXiv:2307.10485*.

Pan Lu, Baolin Peng, Hao Cheng, Michel Galley, Kai-Wei Chang, Ying Nian Wu, Song-Chun Zhu, and Jianfeng Gao. 2023. Chameleon: Plug-and-play compositional reasoning with large language models. *Advances in Neural Information Processing Systems*, 36:43447–43478.

Thomas Lux and Michele Marchesi. 1999. Scaling and criticality in a stochastic multi-agent model of a financial market. *Nature*, 397(6719):498–500.

Benoit Mandelbrot and 1 others. 1963. The variation of certain speculative prices. *Journal of business*, 36(4):394.

Yuqi Nie, Yaxuan Kong, Xiaowen Dong, John M Mulvey, H Vincent Poor, Qingsong Wen, and Stefan Zohren. 2024. A survey of large language models for financial applications: Progress, prospects and challenges. *arXiv preprint arXiv:2406.11903*.

Ahmet Murat Ozbayoglu, Mehmet Ugur Gudelek, and Omer Berat Sezer. 2020. Deep learning for financial applications: A survey. *Applied soft computing*, 93:106384.

Charles Packer, Vivian Fang, Shishir_G Patil, Kevin Lin, Sarah Wooders, and Joseph_E Gonzalez. 2023. Memgpt: Towards llms as operating systems.

Aaron Parisi, Yao Zhao, and Noah Fiedel. 2022. Talm: Tool augmented language models. *arXiv preprint arXiv:2205.12255*.

Joon Sung Park, Joseph O'Brien, Carrie Jun Cai, Meredith Ringel Morris, Percy Liang, and Michael S Bernstein. 2023. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th annual acm symposium on user interface software and technology*, pages 1–22.

Shishir G Patil, Huanzhi Mao, Fanjia Yan, Charlie Cheng-Jie Ji, Vishnu Suresh, Ion Stoica, and Joseph E Gonzalez. 2025. The berkeley function calling leaderboard (bfcl): From tool use to agentic evaluation of large language models. In *Forty-second International Conference on Machine Learning*.

Shishir G Patil, Tianjun Zhang, Xin Wang, and Joseph E Gonzalez. 2024. Gorilla: Large language model connected with massive apis. *Advances in Neural Information Processing Systems*, 37:126544–126565.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. 2023. Toolformer: Language models can teach themselves to use tools. *Advances in Neural Information Processing Systems*, 36:68539–68551.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.

Richard S Sutton, Andrew G Barto, and 1 others. 1998. *Reinforcement learning: An introduction*, volume 1. MIT press Cambridge.

Alexander Sasha Vezhnevets, Simon Osindero, Tom Schaul, Nicolas Heess, Max Jaderberg, David Silver, and Koray Kavukcuoglu. 2017. Feudal networks for hierarchical reinforcement learning. In *International conference on machine learning*, pages 3540–3549. PMLR.

Yijia Xiao, Edward Sun, Di Luo, and Wei Wang. 2024. TradingAgents: Multi-agents LLM financial trading framework. *arXiv preprint arXiv:2412.20138*.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R Narasimhan, and Yuan Cao. 2022. React: Synergizing reasoning and acting in language models. In *The eleventh international conference on learning representations*.

Yangyang Yu, Haohang Li, Zhi Chen, Yuechen Jiang, Yang Li, Jordan W Suchow, Denghui Zhang, and Khaldoun Khashanah. 2025. Finmem: A performance-enhanced llm trading agent with layered memory and character design. *IEEE Transactions on Big Data*.

Siyu Yuan, Kaitao Song, Jiangjie Chen, Xu Tan, Yongliang Shen, Kan Ren, Dongsheng Li, and Deqing Yang. 2025. Easytool: Enhancing llm-based agents with concise tool instruction. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 951–972.

A Appendix Overview

The appendix provides implementation and diagnostic details omitted from the main text: the ranked candidate construction, the three SFT target views, prompt formats, executable strategy snippets, environment definitions, full metrics, related work, and additional diagnostic figures.

B Related Work

Learning-based trading and strategy selection. Classical strategy families encode different market assumptions: momentum and technical rules exploit continuation (Jegadeesh and Titman, 1993; Brock et al., 1992), reversal effects motivate contrarian trading (De Bondt and Thaler, 1985), pairs trading captures relative value (Gatev et al., 2006), and volatility targeting adapts exposure to risk (Harvey et al., 2018). Learning-based systems instead often map observations directly to trades, using deep learning, reinforcement learning, or sequence modeling (Ozbayoglu et al., 2020; Sutton et al., 1998; Schulman et al., 2017; Chen et al., 2021; Janner et al., 2021). MetaPS is closest to hierarchical control and contextual bandits (Vezhnevets et al., 2017; Auer et al., 2002; Bubeck et al., 2012), but its options are executable market strategies and its router is trained from simulated strategy-outcome records.

LLM agents, tools, and skills. LLM agents commonly separate reasoning from executable tool use. ReAct links reasoning traces with actions (Yao et al., 2022); Toolformer and related tool-augmented models study external tool invocation (Schick et al., 2023; Parisi et al., 2022); and Gorilla and BFCL evaluate API/function calling (Patil et al., 2024, 2025). Modular and memory-based agents further explore tool composition and persistent procedural behavior (Lu et al., 2023; Yuan et al., 2025; Park et al., 2023; Packer et al., 2023; Chhikara et al., 2025; Fang et al., 2025). MetaPS applies this tool/skill view to markets: each tool is an executable strategy, and the LLM learns when to call it.

Financial LLM agents and market simulation. Financial LLMs have been used for financial text processing, memory-augmented trading, and multi-agent analysis (Liu et al., 2023; Yu et al., 2025; Xiao et al., 2024; Lee et al., 2024; Nie et al., 2024; Du et al., 2025). Separately, agent-based market models and simulators study heterogeneous market dynamics and trading agents (Lux and Marchesi, 1999; Hommes, 2006; LeBaron, 2006; Farmer and Foley, 2009; Byrd et al., 2020; Amrouni et al., 2021). MetaPS combines these directions by using backtesting and simulation not only for evaluation, but also to generate supervision for a router over executable strategies.

C Additional Method Details

This appendix expands the compact method description in Section 2. The main text defines the MetaPS interface and training objective; here we spell out how the ranked strategy context, simulation labels, and reward-derived weights are constructed.

C.1 Notation Map

The method uses three levels of objects. The *environment level* provides the observable state o_t, history h_t, and realized reward r_t. The *strategy level* contains executable programs $s_i \in \mathcal{S}$; each program maps the current state to an executable action. The *router level* learns $p_\theta(z \mid o_t, h_t, \mathcal{C}_t)$, where z is a strategy identifier and $\mathcal{C}_t$ is the ranked candidate set shown to the model. After the router selects z_t, the final market action is produced by the selected program, $a_t = s_{z_t}(o_t)$.

This separation is important for interpreting the equations below. Rollout returns and rewards are used to construct supervision for $z_t^\star$; they are not inserted into the model input at test time. The model-facing input remains the same for base and fine-tuned models: as-of state, recent feedback, and ranked strategy candidates.

C.2 Candidate Ranking

In the ranked-context setting, MetaPS first scores each programmatic strategy before prompting the language model. The score combines trigger overlap, textual evidence, a small prior, and missing-evidence

penalties:

$$\rho(s_i, o_t) = \alpha \cdot |\mathrm{trig}(s_i) \cap \mathrm{phrases}(o_t)|$$
$$+ \beta \cdot \mathrm{textmatch}(s_i, o_t) + b_i - p_i(o_t).$$

Here $\mathrm{trig}(s_i)$ denotes phrases associated with strategy s_i, while $\mathrm{phrases}(o_t)$ denotes phrases extracted from the current market state. The term $\mathrm{textmatch}$ captures additional lexical overlap, b_i is a small strategy prior, and $p_i(o_t)$ penalizes missing evidence. The top-K strategies under ρ form $\mathcal{C}_t$ in Section 2.3. This step is not the final policy; it only constructs a compact and interpretable strategy context for the MetaPS router.

C.3 Input Ablations

The main MetaPS setting uses a ranked top-K strategy context. We compare it with three simpler alternatives. The *all-strategies* setting exposes the entire program library without pruning. The *no-strategy* setting removes program descriptions and asks the model to produce a decision from the market state alone. The *random-strategy* baseline does not use an LLM router; it uniformly samples a program from the library and executes it. These ablations separate the value of programmatic execution from the value of learned adaptive selection.

C.4 Simulation-Derived Targets

For every as-of state, all candidate strategies in $\mathcal{C}_t$ are evaluated under the same information set. The three dataset views differ only in how they turn those simulation outcomes into a target label $z_t^\star$.

The shared pattern is

$$z_{t,v}^\star = \arg\max_{s_i \in \mathcal{C}_t} q_i^v(o_t),$$

where $v \in \{\mathrm{V1}, \mathrm{V2}, \mathrm{V3}\}$ chooses the scoring rule. The selected label is then converted into an assistant response $y_t = (z_t^\star, d_t, m_t)$, where d_t stores execution fields and m_t stores the rationale.

V1: short-horizon winner. V1 directly imitates the current short-horizon simulation winner. If $G_i^{(1)}(o_t)$ is the one-step or local rollout gain of strategy s_i, the target is

$$z_{t,\mathrm{V1}}^\star = \arg\max_{s_i \in \mathcal{C}_t} G_i^{(1)}(o_t).$$

This view favors immediate opportunities and high-conviction local actions. It is closest to a direct imitation of the best local rollout.

V2: medium-horizon advantage. V2 evaluates each candidate over multiple horizons $\mathcal{H} = \{3, 5, 10, 20\}$. For a strategy-specific horizon weight $\lambda_{i,h}$, the gross long-horizon return is

$$R_i^{\mathrm{long}}(o_t) = \sum_{h \in \mathcal{H}} \lambda_{i,h} G_i^{(h)}(o_t).$$

The implementation subtracts trading cost, risk, and turnover penalties:

$$U_i(o_t) = R_i^{\mathrm{long}}(o_t) - c_i(o_t) - q_i(o_t) - \tau_i(o_t),$$

where c_i is a transaction-cost proxy, q_i penalizes risky medium/large positions under risk phrases, and τ_i penalizes large turnover. The final score blends this utility with a strategy prior and the candidate's as-of edge:

$$B_i(o_t) = (1 - \eta)U_i(o_t) + \eta \bar{U}_i + \kappa e_i(o_t),$$

where $\bar{U}_i$ is the average utility prior for strategy s_i and $e_i(o_t)$ is the as-of candidate edge. V2 selects

$$z_{t,\mathrm{V2}}^\star = \arg\max_{s_i \in \mathcal{C}_t} B_i(o_t).$$

If the best score does not clear the trade margin, the target is converted to a hold/risk-reset decision. Thus V2 is still supervised learning, but its labels prefer strategies that remain useful beyond the next step.

V3: balanced competence. V3 does not introduce a separate reinforcement-learning objective. Instead, it constructs a balanced SFT set by choosing, for each state, between the V1 and V2 labels. Each candidate label receives a quality score

$$Q(y_t) = a(y_t) + 3\max(0, B(y_t)) + 0.08\min(w_t, 1.6),$$

where $a(y_t)$ gives a small active-action bonus, $B(y_t)$ is the V2-style long-horizon score when available, and w_t is the sample weight. The selection score then adds distribution-control terms:

$$\mathrm{Bal}(y_t) = Q(y_t) + \Delta_{\mathrm{act}} + \Delta_{\mathrm{bucket}} + \Delta_{\mathrm{strategy}},$$

where the Δ terms encourage the dataset to stay near target action, size-bucket, and strategy frequencies. Labels that exceed their target frequency are penalized. This is why V3 is best viewed as return-aware behavioral balancing rather than a pure reward maximization stage. In short, V1 asks "what wins now?", V2 asks "what remains good over several steps?", and V3 asks "which of the good labels produces a healthier training distribution?" These three views all train the same router format from Section 2.3.

Parallel and serial variants. The parallel variants train separate adapters on V1, V2, or V3 data. The serial variants continue training one adapter on the next dataset, such as V1→V2 or V1→V2→V3. Thus the serial setting tests whether the behavioral bias from one view can be refined by later views, while the parallel setting tests each view as a standalone supervision source.

C.5 Sample Weights

Simulation reward affects training through target selection and optional example weights. The SFT loss is

$$\mathcal{L}_{\mathrm{sft}} = -\sum_t w_t \log p_\theta(y_t \mid x_t).$$

For long-horizon active decisions, the implementation increases w_t with the blended score and clips it to a bounded interval. Hold decisions receive a smaller weight. In the V3 dataset, weights are recomputed from the balanced quality score and clipped again. The reward values are stored as metadata for construction and analysis; they are not inserted into the user prompt. This design keeps inference identical across base and fine-tuned models: at test time the model only sees the market state and ranked strategy context, not future reward information.

For tokenized targets $y_t = (y_{t,1}, \ldots, y_{t,L_t})$, the log-likelihood term used above expands to

$$\log p_\theta(y_t \mid x_t) = \sum_{\ell=1}^{L_t} \log p_\theta(y_{t,\ell} \mid x_t, y_{t,<\ell}).$$

Thus sample weights scale the whole assistant response for one state–strategy example, including the selected strategy identifier, execution fields, and rationale.

C.6 Instruction Format

Each SFT example is an instruction-following conversation. The user message contains the as-of state, the ranked candidate strategies, and brief strategy descriptions. The assistant message contains fixed Markdown sections: *Strategy Decision*, *Market Read*, *Why This Strategy*, *Trade Plan*, and *Risk Check*. The selected strategy and action fields are fixed before teacher rewriting, so the teacher improves rationale quality without changing the target label.

The system message used for both SFT construction and local-model inference is short and task-specific. The following boxes show the concrete input and output schema used by the router. Long market tables and news lists are abbreviated with ellipses, but the fields and Markdown sections match the data files.

SFT input prompt template

```
SYSTEM:
You are MetaPS, a strategy-routing trading agent. Read the as-of
market context, choose the best candidate strategy, and answer with
the exact Markdown sections requested. Do not use future outcomes or rewards.

USER:
# Strategy Routing Task

Choose which candidate strategy should dominate this as-of market state,
then produce the requested Markdown answer.
Use only the context below. Do not use future rewards, future prices,
or realized outcomes.

## As-Of State
- episode_id=episode-895423
- round_idx=282
- timestamp=16:00
- role_name=strategy.momentum_follow
- env_policy=strategy

## Market Windows
| ticker | price | 1d | 5d | 20d | 60d | points |
| AAPL | 153.71 | -1.04% | +1.88% | +13.63% | +1.60% | 80 |
| NVDA | 22.00 | -3.35% | -1.50% | +31.24% | +42.79% | 80 |
...

## News Context
- round=282 ... headline=No Summons For Elon Musk But Apple's Tim Cook...
- round=282 ... headline=Is the Whole Country Buying Teslas...

## Portfolio State
- cash=...
- gross_exposure=...
- net_exposure=...

## Ranked Candidate Strategies
1. strategy.risk_reset score=... trigger=risk_overheat
2. strategy.momentum_follow score=... trigger=trend_down
...
```

SFT assistant target after teacher rewrite

```
## Strategy Decision
selected_strategy: strategy.risk_reset
confidence: 0.56

## Market Read
The portfolio exhibits a heavily one-sided book. Market data shows
broad weakness, while news lacks a fresh high-conviction catalyst.

## Why This Strategy
strategy.risk_reset dominates because exposure and volatility risks
matter more than adding another directional trade. Momentum is present,
but the risk_overheat signal makes aggressive following fragile.

## Trade Plan
action: HOLD
ticker: NONE
size_bucket: none

## Risk Check
Do not add risk when constraints dominate; preserve capital before
expressing a new thesis.
```

Test-time inference input and parsed output

```
INPUT:
Same system and user template as SFT, but with the held-out 2025
as-of state. Example fields: date=2025-01-02, cash=1000000.00,
gross_exposure=0.00, net_exposure=0.0000, volatility_regime=0.1600,
visible price windows, news/event summaries, portfolio state, and
ranked candidate strategies. Future prices, realized P&L, and rollout
rewards are not included.

PARSED OUTPUT:
selected_strategy = strategy.momentum_follow
action            = BUY
ticker            = NVDA
```

```
size_bucket      = small
qty              = 289
confidence       = 0.52
```

Future rewards and realized outcomes remain metadata for dataset construction; they are not shown in the model prompt. Thus the SFT and inference inputs share the same observable information, while the SFT target additionally provides the teacher-rewritten rationale and fixed executable fields.

Table 5: Data fields used by MetaPS during SFT construction and held-out inference.

Record	Input content	Output content
SFT example	System instruction; as-of state; market windows; news context; portfolio state; ranked strategy candidates; strategy descriptions.	Teacher-rewritten Markdown rationale plus parseable fields: `selected_strategy`, `confidence`, `action`, `ticker`, and `size_bucket`. Reward and loss weight are stored only as metadata.
Inference trace	Same observable prompt schema on held-out 2025 states. No future returns, rollout rewards, or realized P&L are included.	Model-generated Markdown response, parsed into the selected strategy and execution fields. The runtime converts the size bucket to quantity and checks feasibility before execution.

C.7 Programmatic Strategy Code Flow

The codebase implements the strategy library as executable modules rather than as natural-language labels. In the stock environment, each entry in the `StockStrategySpec` registry stores a stable strategy key, category, objective, trigger condition, play description, guardrail, trigger phrases, and executor path. The roster then creates one participant per strategy, with `agent_id == role_name == selected_strategy`. This convention keeps rollout logs and SFT labels direct: there is no hidden mapping between an "agent" and a strategy.

At runtime, `StockStrategyAgent` dynamically imports the corresponding executor, e.g., `game.stock_game.strategies.momentum_follow:execute`. The executor emits a raw decision containing action, ticker, confidence, optional risk notes, and a coarse size bucket. The wrapper validates the action, normalizes `WAIT` to `HOLD`, clips invalid tickers to `HOLD`, and attaches metadata such as `selected_strategy`, `strategy_slug`, and `risk_note`. The sizing layer maps `none`/`small`/`medium`/`large` to deterministic exposure fractions of 0%, 4%, 9%, and 16%, with quantity caps of 0, 320, 800, and 1200 shares. Sell orders are further clipped by available inventory when short selling is disabled.

The goods-exchange sandbox follows the same abstraction with environment- specific programs. Its roster maps six roles to executable agents: `town_producer`, `town_processor`, `town_contractor`, `town_merchant`, `town_hoarder`, and `town_balanced`. These strategies produce, process, fill contracts, trade market discounts and premiums, stockpile inventory, or maintain balanced cash and capacity. The sandbox runtime checks inventory, production capacity, contract availability, and resource feasibility before applying the final action.

C.8 Stock Strategy Library: Meaning and Execution Logic

The ten stock strategies are executable Python modules. Below we show compact code snippets that preserve each module's decision rule and its intended market meaning. Quantity emitted by a raw strategy can be present in the strategy result, but the final evaluated quantity is determined by the shared size-bucket runtime described above.

strategy.news_impulse: trade fresh news shocks

```
def execute(obs):
    news = obs.news
    if not news:
        return HOLD("no catalyst")
    latest = news[0]
```

```
    ticker = argmax_abs(latest.impacts)
    impact = latest.impacts[ticker]
    if abs(impact) < 0.002:
        return HOLD("news impact too weak")
    direction = "BUY" if impact > 0 else "SELL"
    return {
        "action": f"{direction} {ticker}",
        "size_mode": "probe_to_medium",
        "confidence": min(abs(impact) * 30, 1.0),
        "risk_note": "abort if follow-through stalls",
    }
```

strategy.momentum_follow: ride confirmed short-term momentum

```
def execute(obs):
    best_ticker, best_momentum = None, 0.0
    for ticker, history in obs.price_history.items():
        move_3 = ret(history[-4], history[-1])
        if abs(move_3) > abs(best_momentum):
            best_ticker, best_momentum = ticker, move_3
    if best_ticker is None or abs(best_momentum) < 0.002:
        return HOLD("momentum too weak")
    direction = "BUY" if best_momentum > 0 else "SELL"
    return {
        "action": f"{direction} {best_ticker}",
        "size_mode": "scalable",
        "confidence": min(abs(best_momentum) * 20, 1.0),
        "risk_note": "pair with hedge if the book becomes one-sided",
    }
```

strategy.mean_revert_fade: fade overextended moves

```
def execute(obs):
    candidates = []
    for ticker, history in obs.price_history.items():
        sma5 = mean(history[-5:])
        deviation = (history[-1] - sma5) / sma5
        if abs(deviation) > 0.015:
            direction = "SELL" if deviation > 0 else "BUY"
            candidates.append((ticker, direction, abs(deviation)))
    if not candidates:
        return HOLD("no overextension")
    ticker, direction, stretch = select_fade_candidate(candidates)
    return {
        "action": f"{direction} {ticker}",
        "size_mode": "small_probe",
        "confidence": min(stretch / 0.05, 1.0),
        "risk_note": "avoid fading fresh catalysts without exhaustion",
    }
```

strategy.cross_asset_hedge: offset a one-sided book

```
def execute(obs):
    equity = obs.cash + obs.gross_exposure
    net_ratio = abs(obs.net_exposure) / max(equity, 1.0)
    gross_ratio = obs.gross_exposure / max(equity, 1.0)
    if not (net_ratio > 0.4 and gross_ratio > 0.2):
        return HOLD("book is balanced")
    hedge_direction = infer_hedge_direction(obs.positions)
    hedge_ticker = find_cross_asset_offset(obs.price_history, obs.positions)
    if hedge_ticker is None:
        return HOLD("no suitable hedge instrument")
    action = "SELL" if hedge_direction == "short" else "BUY"
    return {
        "action": f"{action} {hedge_ticker}",
        "size_mode": "counterbalance",
        "risk_note": "hedge legs stay subordinate to the main thesis",
    }
```

strategy.risk_reset: preserve capital under constraints

```
def execute(obs):
    equity = obs.cash + obs.gross_exposure
    vol_risk = max(0, obs.volatility_regime - 0.4) / 0.6
    liq_risk = max(0, obs.liquidity_regime - 0.4) / 0.6
```

```
    exposure_risk = obs.gross_exposure / max(equity, 1.0)
    risk = 0.4 * vol_risk + 0.3 * liq_risk + 0.3 * exposure_risk
    if risk < 0.5:
        return HOLD("risk elevated but no forced reset")
    return {
        "action": "REDUCE",
        "size_mode": "reduce",
        "confidence": 0.6 * (1.0 - 0.3 * risk),
        "risk_note": "no new positions until constraints cool",
    }
```

strategy.macro_rotation: rotate across macro and asset regimes

```
def execute(obs):
    macro_signal = news_macro_impact(obs.news)
    macro_signal += cross_asset_momentum_spread(obs.price_history)
    macro_signal += factor_risk_appetite(obs.factor_state)
    if abs(macro_signal) < 0.01:
        return HOLD("no clear cross-asset rotation")
    direction = "risk_on" if macro_signal > 0 else "risk_off"
    ticker = best_asset_for_regime(obs.price_history, direction)
    action = "BUY" if macro_signal > 0 else "SELL"
    return {
        "action": f"{action} {ticker}",
        "size_mode": "balanced",
        "confidence": min(abs(macro_signal), 1.0),
        "risk_note": "require multi-asset confirmation before scaling",
    }
```

strategy.earnings_drift: follow post-event repricing

```
def execute(obs):
    tickers = tickers_mentioned_by_recent_news(obs.news)
    candidates = []
    for ticker in tickers:
        drift = ret(obs.price_history[ticker][-3], obs.price_history[ticker][-1])
        if 0.003 < abs(drift) < 0.06:
            direction = "BUY" if drift > 0 else "SELL"
            candidates.append((ticker, direction, abs(drift)))
    if not candidates:
        return HOLD("wait for post-event drift confirmation")
    ticker, direction, strength = max(candidates, key=lambda x: x[2])
    return {
        "action": f"{direction} {ticker}",
        "size_mode": "balanced",
        "confidence": min(strength / obs.volatility_regime, 1.0),
        "risk_note": "skip broad macro noise",
    }
```

strategy.liquidity_rebate: provide liquidity in two-way markets

```
def execute(obs):
    two_way = obs.liquidity_regime > 0.4 and obs.volatility_regime < 0.5
    if not two_way or obs.news:
        return HOLD("avoid liquidity provision during catalysts")
    candidates = []
    for ticker, history in obs.price_history.items():
        mid = mean(history[-5:])
        spread = abs(history[-1] - mid) / mid
        if spread < 0.008:
            candidates.append((ticker, history[-1], mid, spread))
    if not candidates:
        return HOLD("no tight-spread instrument")
    ticker, price, mid, spread = max(candidates, key=lambda x: x[3])
    action = "BUY" if price < mid else "SELL"
    return {
        "action": f"{action} {ticker}",
        "size_mode": "liquidity",
        "confidence": 0.47,
        "risk_note": "stop when one-way news gaps appear",
    }
```

strategy.small_cap_breakout: trade high-beta style expansion

```python
def execute(obs):
    if obs.liquidity_regime < 0.3:
        return HOLD("liquidity too thin")
    candidates = []
    for ticker, history in obs.price_history.items():
        recent_high, recent_low = max(history[-6:]), min(history[-6:])
        range_pct = (recent_high - recent_low) / recent_low
        vol_expansion = recent_vol(history) / older_vol(history)
        if history[-1] > recent_high * 0.998 and range_pct > 0.01:
            candidates.append((ticker, range_pct * vol_expansion))
    if not candidates:
        return HOLD("no high-beta breakout")
    ticker, strength = max(candidates, key=lambda x: x[1])
    return {
        "action": f"BUY {ticker}",
        "size_mode": "breakout",
        "confidence": min(strength, 1.0),
        "risk_note": "cut size when breadth fades",
    }
```

strategy.volatility_breakout: trade range breaks after compression

```python
def execute(obs):
    candidates = []
    for ticker, history in obs.price_history.items():
        window = history[-20:]
        high, low, current = max(window), min(window), history[-1]
        range_width = (high - low) / low
        if range_width >= 0.005:
            continue
        if current > high * 1.002:
            candidates.append((ticker, "BUY", breakout_strength(current, high, low)))
        if current < low * 0.998:
            candidates.append((ticker, "SELL", breakout_strength(current, high, low)))
    if not candidates:
        return HOLD("no compression-breakout pattern")
    ticker, action, strength = max(candidates, key=lambda x: x[2])
    return {
        "action": f"{action} {ticker}",
        "size_mode": "breakout",
        "confidence": min(strength, 1.0),
        "risk_note": "false-break risk is high when liquidity is thin",
    }
```

C.9   Execution Details

At inference time, MetaPS only selects a strategy program and coarse execution fields. The selected program is then executed by the environment-specific runtime. In stock trading, the runtime checks ticker validity, position limits, cash constraints, transaction costs, slippage, and size-bucket rules. In the goods-exchange sandbox, it checks inventory, production capacity, order availability, and resource feasibility. This separation keeps the learned model at the strategy-selection level while ensuring that final actions remain executable under the simulator.

D   Environment Details

This section describes the two environments used in the experiments. Both are implemented through the same MetaPS interface: the environment constructs an as-of observation, the router selects a strategy program, and the selected program produces an executable action checked by the runtime.

D.1   Multi-stock Trading Environment

The stock benchmark is the primary environment. It uses daily market data and news/event context for a multi-asset universe consisting of AAPL, NVDA, SPY, QQQ, GLD, and USO. Each trading day is treated as one decision step. The main split trains on 2022–2024 and tests on 2025; the rolling validation in Section 3.7 uses earlier expanding-window splits. The portfolio starts with $1,000,000 in cash.

Observation.   At day t, the model receives only information available as of that day. The observation includes recent price bars, short- and medium-horizon return windows, news/event summaries, recent

order flow, cash and position state, and a ranked strategy context. The ranked context is built from the same ten stock strategy programs used at inference time. In the Ranked-Strategy setting, all ten stock programs are visible, ordered by the lightweight strategy scorer.

Action. The router emits a structured decision containing a selected strategy, action (BUY, SELL, or HOLD), ticker, confidence, and size bucket. The runtime converts the size bucket into a deterministic quantity and then checks cash, position limits, transaction costs, slippage, and ticker validity. This separates the learned part of the system from low-level execution mechanics.

Reward and metrics. During dataset construction, candidate strategies are rolled out under the same as-of state to construct state–strategy supervision. During evaluation, we report portfolio-level metrics: total return, final value, Sharpe ratio, maximum drawdown, trade count, win rate, and hold rate. Return is computed from final portfolio value relative to initial cash. Sharpe is computed from the sequence of daily portfolio returns, and maximum drawdown is the largest peak-to-trough portfolio decline during the test period.

D.2 Controlled Goods-exchange Sandbox

The goods-exchange sandbox is an auxiliary environment designed to test whether the MetaPS interface can be instantiated outside historical financial data. It is intentionally simpler than the stock benchmark. The state contains cash, inventory, market price, and regime signals. The available strategy programs are producer, processor, contractor, merchant, hoarder, and balanced. Each strategy maps the current economic state to a feasible inventory or market action.

The sandbox contains six regimes: expansion, shortage, processing boom, stable contract, downturn, and volatile markets. These regimes change the relative value of producing, holding inventory, accepting contracts, and selling goods. Terminal equity is cash plus inventory value and any simulator-defined asset value at the end of the episode. Winner share is the percentage of days on which the selected policy matches the best strategy under the simulator's same-day evaluation, and mean regret is the average gap to that best available strategy. Because these dynamics are synthetic, we use the sandbox as a controlled interface check rather than as the main empirical claim.

E   Additional Results and Diagnostics

E.1   Direct-Action SFT Baseline

Table 6 expands the direct-action comparison from Table **??**. The direct-action setting removes the strategy identifier from the learning target and asks the model to emit the final action fields directly. The base model produces active trades and obtains a positive return, but SFT on direct-action targets collapses most of the return while keeping the same number of executed trades. This failure mode is consistent with the motivation for MetaPS: low-level action labels are noisy and path-dependent, whereas strategy identifiers provide a more stable intermediate decision target.

Table 6: Full direct-action baseline metrics on the held-out 2025 stock benchmark.

Method	Return ↑	Sharpe ↑	Max DD ↓	Trades	Win Rate ↑	Hold Rate	Final Value ↑
Direct Action Base	29.30	0.077	15.14	50	50.0	80.0	1292956.86
Direct Action SFT	3.14	-0.139	**1.65**	50	50.0	80.0	1031418.18

E.2   Full Stock-Scale Metrics

Table 7 expands the compact return-only scale table in the main text. It reports the same 2025 Ranked-Strategy stock benchmark, but includes final value, Sharpe ratio, maximum drawdown, trade count, win rate, and hold rate for every model scale and objective.

Table 7: Full MetaPS 2025 evaluation metrics under the Top10-Ranked input setting. Return, win rate, and hold rate are percentages; final value is shown in millions of dollars.

Model	Variant	Return ↑	Final Value ↑	Sharpe ↑	Max DD ↓	Trades	Win Rate ↑	Hold Rate
MetaPS-0.8B	Base	29.90	1.30M	0.415	33.62	12	0.00	94.80
	V1	32.90	1.33M	0.536	30.98	25	0.00	90.00
	V2	36.08	1.36M	0.502	31.50	31	0.00	87.60
	V3	**40.08**	1.40M	0.560	32.04	29	42.86	88.40
	Serial V1→V2	39.54	1.40M	0.486	32.32	34	33.33	86.40
	Serial V1→V2→V3	27.85	1.28M	0.606	20.11	69	39.29	72.40
MetaPS-2B	Base	28.50	1.29M	0.494	32.29	14	100.00	94.40
	V1	28.28	1.28M	0.666	30.78	29	28.57	88.40
	V2	**38.98**	1.39M	0.459	32.33	34	33.33	86.40
	V3	36.09	1.36M	0.701	24.85	61	23.81	75.60
	Serial V1→V2	38.26	1.38M	0.474	32.69	30	0.00	88.00
	Serial V1→V2→V3	34.73	1.35M	0.601	8.60	94	30.77	62.40
MetaPS-4B	Base	25.12	1.25M	0.916	16.59	82	32.35	67.20
	V1	18.39	1.18M	1.016	25.85	76	25.00	69.60
	V2	40.69	1.41M	0.583	28.48	56	28.57	77.60
	V3	40.00	1.40M	0.564	14.21	88	45.00	64.80
	Serial V1→V2	33.26	1.33M	0.581	29.47	54	30.77	78.40
	Serial V1→V2→V3	**45.72**	1.46M	0.705	12.57	93	26.32	62.80
MetaPS-9B	Base	32.69	1.33M	0.762	27.30	43	20.00	82.80
	V1	45.39	1.45M	0.721	14.15	85	37.84	66.00
	V2	31.24	1.31M	0.690	27.53	51	25.00	79.60
	V3	**50.29**	1.50M	0.668	15.29	89	31.43	64.40
	Serial V1→V2	38.32	1.38M	0.571	26.56	45	11.11	82.00
	Serial V1→V2→V3	40.68	1.41M	0.522	26.64	48	23.53	80.80

Figure 7: Portfolio equity curves on the held-out 2025 stock benchmark. Each curve is normalized to the same initial capital and follows the daily backtester state over time.

E.3 Return-Curve Diagnostics

The main text reports aggregate return, Sharpe ratio, and maximum drawdown. Figure 7 gives the corresponding portfolio-value trajectories over the 2025 test year for the main Qwen and MetaPS variants. This view makes clear whether a method's final return comes from steady compounding, a small number of jumps, or late-period recovery.

Figure 8 expands the comparison to strategy-only, API, and Qwen baselines. Figure 9 plots the same information as return gaps relative to MetaPS-9B V3.

Figure 10 reports the paired drawdown trajectories. It complements the return curves by showing when losses occur and how long each method remains below its prior peak.

Figure 11 gives the corresponding drawdown curves for representative baselines.

Figure 12 further groups the same test year into calendar blocks. This diagnostic checks whether final performance is concentrated in one part of the year or persists across multiple market segments.

Figure 13 and Figure 14 provide complementary month-level and quarter-level views of the same trajectories.

Figure 8: Portfolio-value trajectories for MetaPS and representative baselines on the held-out 2025 stock benchmark.

Table 8: Strategy-use patterns of the best MetaPS variant at each model scale on the 2025 stock benchmark. Counts are over 250 daily decisions.

Model	Variant	Ret. ↑	Hold %	Buy	Sell	Top selected strategies
MetaPS-0.8B	V3	40.08	88.4	22	7	momentum-follow (154), macro-rotation (65), mean-revert-fade (23)
MetaPS-2B	V2	38.98	86.4	31	3	small-cap-breakout (223), mean-revert-fade (19), news-impulse (4)
MetaPS-4B	Serial V1→V2→V3	45.72	62.8	55	38	momentum-follow (196), mean-revert-fade (22), news-impulse (22)
MetaPS-9B	V3	50.29	64.4	54	35	momentum-follow (195), mean-revert-fade (23), news-impulse (19)

E.4 Additional Baseline and Ablation Figures

Figure 15 shows the risk–return positions of the same method families used in Table 1. Figure 16 visualizes the strategy-context ablation from Table ??. Figure 17 summarizes the scale-by-objective table from the main text.

E.5 Behavior and Data-Distribution Diagnostics

Table 8 reports the cross-scale behavior summary behind Figure 4. It lists the best MetaPS variant for each model size, its action counts, and its most frequently selected strategy programs.

Figure 18 gives the full ten-strategy distribution for training labels and for the best test router at each model scale. This more detailed view complements the compact main-text behavior figure by showing strategies with zero test selections.

Figure 19 reports the corresponding BUY/HOLD/SELL distributions for the best test router at each model scale. We keep this diagnostic in the appendix because action type is downstream of the main strategy-selection question.

Figure 20 shows how the three SFT data views differ before model training. Each view contains 528 examples, but the strategy and action label distributions are intentionally different. V1 is closer to short-horizon winner imitation, V2 shifts more mass toward active buy/sell labels, and V3 rebalances the distribution to avoid relying only on one aggressive behavior pattern.

Figure 9: Cumulative return gap of MetaPS-9B V3 relative to representative baselines. Positive values indicate that MetaPS-9B V3 has higher cumulative return up to that date.

Table 9: Action-label distribution of the three MetaPS SFT data views.

Data view	Samples	HOLD	BUY	SELL
V1	528	182 (34.5%)	207 (39.2%)	139 (26.3%)
V2	528	89 (16.9%)	269 (50.9%)	170 (32.2%)
V3	528	184 (34.8%)	215 (40.7%)	129 (24.4%)

E.6 Sandbox Results

Table 10 gives the fuller sandbox comparison. The results are reported to show that the same router interface can be instantiated outside the stock benchmark. We do not treat the sandbox as primary evidence because its dynamics are synthetic.

Figure 10: Drawdown curves on the held-out 2025 stock benchmark. Lower values indicate deeper declines from the running portfolio peak.

Table 10: Auxiliary controlled economic sandbox results using shared strategy-selection baselines, API prompting baselines, and 4B MetaPS routers.

Method	Terminal Equity ↑	Return (%) ↑	Winner Share ↑	Mean Regret ↓	Sharpe ↑	Max DD ↓
Strategy-only Baselines						
Random Strategy	13401	54.84	16.2	735.79	6.52	6.11
Best Fixed Strategy	18609	115.02	38.0	443.74	12.99	3.74
Non-LLM Learned Selectors						
Strategy Classifier	26647	207.89	53.0	268.37	35.14	0.00
Sequence Selector	23872	175.84	50.0	339.97	18.52	1.21
Reward-Ranking Selector	26002	200.45	53.0	251.28	27.11	0.00
RL Q-Policy Selector	15030	73.67	41.0	680.20	8.22	5.17
LLM and MetaPS Routers						
Qwen-4B Base	23879	175.92	41.0	399.45	18.25	1.21
GPT-5.4-mini	23249	168.64	54.0	236.77	25.08	0.01
GPT-5.4	23554	172.16	53.0	251.29	17.42	1.52
MetaPS-4B V1	**31514**	**264.14**	**59.0**	**186.22**	**44.21**	**0.00**
MetaPS-4B V2	27631	219.26	57.0	230.85	18.69	1.07
MetaPS-4B V3	30454	251.89	**59.0**	198.76	41.55	0.09

Figure 11: Drawdown trajectories for MetaPS and representative baselines on the held-out 2025 stock benchmark.

Figure 12: Block-level 2025 returns for the main stock benchmark. The plot breaks the full-year result into shorter calendar segments.

Figure 13: Monthly return breakdown for MetaPS and representative baselines on the 2025 stock benchmark.

Figure 14: Quarterly return comparison for MetaPS and representative baselines on the 2025 stock benchmark.

Figure 15: Risk–return comparison for strategy-only baselines, non-LLM selectors, LLM prompting baselines, and MetaPS.

Figure 16: Input-context ablation on the 2025 stock benchmark.

Figure 17: Return heatmap across Qwen model scales and MetaPS training objectives.

Figure 18: Full strategy distributions for SFT labels and best test routers across model scales. Values are percentages within each row. Zero entries indicate strategies available to the router but not selected in that held-out run.

Figure 19: Action distributions of the best MetaPS test router at each model scale on the 2025 stock benchmark.

Figure 20: Training-label distributions for the three MetaPS SFT data views. The left panel reports selected strategy labels; the right panel reports action labels.

Figure 21: Goods-exchange sandbox comparison. The same MetaPS interface is evaluated in a controlled non-stock economy, where terminal equity measures final cash and inventory value.