Haptics-based Curiosity for Sparse-Reward Tasks

Sai Rajeswar[1,2,3]*, **Cyril Ibrahim**[3]*, **Nitin Surya**[3],
Florian Golemo[1,2,3], **David Vazquez**[3], **Aaron Courville**[1,2,4], **Pedro O. Pinheiro**[3]
[3]Montréal Institute for Learning Algorithms, [2]Université de Montréal,
[3]Element AI, Montréal, [4]CIFAR Fellow

Abstract: Robots in many real-world settings have access to force/torque sensors in their gripper and tactile sensing is often necessary for tasks that involve contact-rich motion. In this work, we leverage surprise from mismatches in haptics feedback to guide exploration in hard sparse-reward reinforcement learning tasks. Our approach, Haptics-based Curiosity (HaC), learns what visible objects interactions are supposed to "feel" like. We encourage exploration by rewarding interactions where the expectation and the experience do not match. We test our approach on a range of haptics-intensive robot arm tasks (e.g. pushing objects, opening doors), which we also release as part of this work. Across multiple experiments in a simulated setting, we demonstrate that our method is able to learn these difficult tasks through sparse reward and curiosity alone. We compare our cross-modal approach to single-modality (haptics- or vision-only) approaches as well as other curiosity-based methods and find that our method performs better and is more sample-efficient.

1 Introduction

Most successes in reinforcement learning (RL) come from games [1, 2] or scenarios where the reward is strongly shaped [3, 4]. In the former, the environment is often fully observable, and the reward is dense and well-defined. In the latter, a large amount of work is required to design useful reward functions. While it may be possible to hand-craft dense reward signals for many real-world tasks, we believe that it is a worthwhile endeavor to investigate learning methods that do not require dense rewards.

Closely related to the sparse rewards problem is the issue of exploration. One reason that traditional RL agents struggle with sparse-reward problems is a lack of exploration. An agent may not obtain useful rewards without an intuitive exploration strategy when rewards are sparse. Exploration based on intrinsic curiosity comes naturally to many animals and infants (who start crawling and exploring the environment at around 9 months [5] and oftentimes even before they can crawl by using their hands and mouth to touch and probe objects). Touch is a local experience and encodes accurate geometrical information while handling objects. Experimental studies in infants has suggested that tactile and visual sensory modalities play a central role in systematic learning of tasks related to object understanding, interaction and manipulation [6, 7].

Ideally, we would like our RL agents to explore the environment in an analogous self-guided fashion to learn the dynamics and object properties, and use this knowledge to solve downstream tasks. Just as how humans utilize different sensory modalities to explore and understand the world around them, exploration in robots should be more embodied and related to a combination of vision and touch and potentially other sensor modalities. We believe that building autonomous agents that are self-driven and seek to explore via multi-modal interaction are crucial to address key issues in developmental robotics.

Recent works in RL have focused on a curiosity-driven exploration through prediction-based surprise [8, 9, 10]. In this formulation, a forward dynamics model predicts the future, and if its prediction is incorrect when compared to the real future, the agent is surprised and is thus rewarded. This encourages the agent to look for novel states while improving its visual forward model in return. However, this formulation can be practically challenging to optimize since there are many

---

*Equal contribution. Correspondence to: Sai Rajeswar<sai.rajeswar.mudumba@umontreal.ca>

5th Conference on Robot Learning (CoRL 2021), London, UK.

states that are visually dissimilar but practically irrelevant (e.g. for a pushing task, moving a robotic end-effector without touching the object creates visual novelty but contributes little to task-related knowledge). One way to constrain this search space over curious behaviors is by involving another modality like haptics.

In this work, we demonstrate that a self-guided cross-modal exploration policy can help solve sparse-reward downstream tasks that existing methods without this curiosity struggle to solve. Our method uses cross-modal consistency (mismatch between visual and haptic signal) to guide this exploration. To use self-play knowledge in downstream tasks, we relabel past experiences, providing a dense reward signal that allows modern off-policy RL methods to solve the tasks. While there are many existing methods that use artificial curiosity/intrinsic motivation, the majority of these methods either rely on strong domain knowledge (e.g. labels of state dimensions in Forestier et al. [4], a goal-picking strategy in Andrychowicz et al. [11]) or are prone to get stuck in local optima when a single meaningless stimulus creates enough surprise to capture the attention of the agent (e.g. noisy-TV experiment from [12]). Other approaches depend on unrealistic assumptions and goal conditioning [11]. Our method presents a novel approach in the family of prediction-based models [8, 13, 9] and yields better performance on a wide range of robotic manipulation tasks than purely vision-based and haptics-based approaches [8, 9]. The tasks are chosen with careful consideration—they comprise of preliminary robotic manipulations such as grasping, pushing, and pulling. In this work, we present the following contributions:

- A new curiosity method to help solve sparse-reward tasks that use cross-modal consistency (predicting one modality from another) to guide exploration. We implement it in this work as vision and touch modalities, but the formulation of our method does not require any knowledge about the underlying modalities and can thus be applied to other settings.

- We create and maintain a manipulation benchmark of simulated tasks, *MiniTouch*, inspired by Chen et al. [14], Andrychowicz et al. [11], where the robotic arm is equipped with a force/torque sensor. This allows evaluation of models' performance on different manipulation tasks that can leverage cross-modal learning.

- We validate the performance of our method on MiniTouch environment comprising of four downstream tasks. We compare purely vision-based curiosity approaches and standard off-policy RL algorithms. Our method improves both performance and sample efficiency.

2 Related Work

Intrinsic Motivation Intrinsic motivation is an inherent spontaneous tendency to be curious or to seek something novel in order to further enhance one's skill and knowledge [15, 16, 17]. This principle is shown to work well even in the absence of a well-defined goal or objective. In reinforcement learning, intrinsic motivation has been a well-researched topic [18, 19, 20, 21, 22, 23]. An intuitive way to perform intrinsic motivation is through the use of "novelty discovery". For example, incentivize the RL agent to visit unusual states or states with substantial information gain [24]. In its simplest form, this can be achieved with up-weighting mechanisms such as state visitation counts [25]. Count-based methods have also been extended to high-dimensional state spaces [26, 12, 27]. Alternative forms of intrinsic motivation include disagreement [28], empowerment [29, 30].

Exploratory intrinsic motivation can also be achieved through "curiosity" [18, 31]. In this setting, an agent is encouraged to visit states with high predictive errors [10, 8, 9] by training a forward dynamics model that predicts the future state given the current state and action. Instead of making predictions in the raw visual space, Pathak et al. [9] mapped images to a feature space where relevant information is represented via an inverse dynamics model. Burda et al. [8] demonstrate that random features are sufficient for many popular RL game benchmarks. This approach may work well with tasks that require navigation to find a reward because each unseen position of the agent in the world leads to high intrinsic reward when unseen. However, in the case of manipulative tasks, we are less interested in the robot visiting all the possible states and more interested in states where the robot interacts with other objects. In this work, we leverage multimodal inputs that encourage the agent to find novel combinations of visual and force/torque modalities.

Self-Supervised Learning via Cross-modality Exploiting multimodality to learn unsupervised representations dates back to at least 1993 [32]. Multimodal signals are naturally suitable for self-supervised learning, as information from one modality can be used to supervise learning for another

| (a) Haptics Control module | (b) Forward module |

Figure 1: **Haptics-based Curiosity Model.** (a) The input image x_t at time t is transformed into a 256-dimensional feature vector $z_t = enc(x_t)$ using a CNN encoder. The haptics decoder network predicts corresponding force/torque vector $\hat{h}_t = dec(z_t)$. The $L2$ norm between predicted haptics $\hat{h}_t$ and observed haptics h_t is used as exploration reward. (b) To stabilize training, an additional network is used to predict the forward dynamics, and the difference between predicted next latent state $\hat{z}_{t+1}$ and actual next latent state z_{t+1} is used as weighted additional term in the reward.

modality [33, 34]. Different modalities typically carry different information, e.g., visual and touch sensory modalities emerge concurrently and often in an interrelated manner during contact-rich manipulation tasks [35]. Specifically, force/torque motor signal has always been a major component in the literature of perception and control [36, 37, 38].

The most common ways to leverage multimodal signals to learn representations are through vision and language [39, 40]. Gao et al. [41], Li et al. [42] demonstrated a unified approach to learning representations for prediction tasks using visual and touch data. Chen et al. [43] learn world-models from multimodal data via a shared latent space. In robotics and interactive settings, the use of modalities such as tactile sensing [44, 45, 46] is increasingly popular for grasping, manipulation and other externally-specified tasks [47, 48]. Lee et al. [49] showed the effectiveness of self-supervised training of tactile and visual representations by demonstrating its use on a peg insertion task.

While the mentioned approaches have used multiple sensory modalities for learning better representations, in this work we demonstrate its utility for allowing agents to explore. Similar to ours, Dean et al. [50] use multimodal sensory association (i.e. audio and visual) to compute the intrinsic reward. Their curiosity-based formulation allows an agent to efficiently explore the environment in settings where audio and visual signals are governed by the same physical processes. In addition to the different nature of sensory signals, they use a discriminator that determines whether an observed multimodal pair is novel. This might not work in our case as touch is a more sparse signal and using a discriminator could lead to ambiguous outcomes.

3 Proposed Approach

The goal of our method, Haptics-Based Curiosity (HaC), is to encourage the agent to interact with objects. HaC provides a reward signal for an RL agent to explore the state space of a task that involves interacting with objects. The exploration phase is independent of the downstream task, i.e., relying solely on visual and force/torque signals, without a reward signal from the downstream task.

Similar to how people spend more time exploring stimuli that are more incongruous [7], HaC guides the agent to focus its experience on different novel cross-modal associations. We augment this intrinsic objective with a future visual state prediction objective similar to the one in Pathak et al. [9] to avoid getting stuck in undesired inactive configurations. Note that we sometimes refer to the future state prediction objective in the text as forward dynamics objective. In this work, we focus on the cross-modality between vision and touch, but the same idea could be applied to other pairs of sensory domains, such as vision and sound, or touch and acoustics.

3.1 Problem Formulation

The learning problem is formalized as a Markov decision process (MDP) defined by a tuple $\{\mathcal{S}, \mathcal{A}, \mathcal{T}, \mathcal{R}, \rho, \gamma\}$ of states, actions, transition probability, reward, initial state distribution, and discount factor. The goal is to find the optimal policy that maximizes the discounted sum of rewards, $\pi^* = \mathbb{E}_\pi[\sum_t^\infty \gamma^t r(\mathbf{s}_t, \mathbf{a}_t)]$. In our case, each state s_t in the trajectory is composed of both visual and corresponding touch features as detailed in the following section. We use soft actor-

critic policy gradients (SAC) [51] to train our policies, but in principle, our proposed approach is algorithm-agnostic. The policy π is evaluated with an estimation of the soft Q-value:

$$Q(\mathbf{s}_t, \mathbf{a}_t) \triangleq r(\mathbf{s}_t, \mathbf{a}_t) + \gamma \mathbb{E}_{\mathbf{s}_{t+1} \sim p}[V(\mathbf{s}_{t+1})] , \tag{1}$$

where $V(\mathbf{s}_t) = \mathbb{E}_{\mathbf{a}_t \sim \pi}[Q(\mathbf{s}_t, \mathbf{a}_t) - \log \pi(\mathbf{a}_t|\mathbf{s}_t)]$ is the soft value function.

3.2 Haptics-based Prediction

Our core prediction framework consists of two modules: (i) a *haptics control* module, which learns to predict expected haptic signal from the visual input, and (ii) a *forward dynamics* model, which predicts the next latent state from the current latent state and the current action (see Figure 1). Let the state of the environment $\mathbf{s}_t = (z_t, h_t)$ at time t be composed of a visual feature z_t (the encoded visual input) and a haptic signal h_t. The touch prediction model consists of a convolutional encoder $z_t = enc(x_t)$ that transforms the image x_t into a latent representation z_t and a fully-connected decoder $\hat{h}_t = dec(z_t)$ that transforms the latent into a predicted haptic signal $\hat{h}_t$. The encoder-decoder is trained with an L2 reconstruction loss, i.e. for every image x_t and force/torque sensor h_t:

$$L_{haptics} = \left\| \hat{h}_t - h_t \right\|_2 . \tag{2}$$

A high prediction error on a given image indicates that the agent has had few interactions like this. Therefore, to harness this "surprise" to guide exploration, we define the intrinsic reward at time t during exploration to be proportional to this reconstruction loss. This essentially allows the agent policy to visit under-explored configurations of the state space by encouraging interactions where the system does not know what the target object "feels" like. In addition to efficient exploration, being aware of such incongruity via touch prediction aids learning local regularities in the visual input. This in turn could assist better generalization to unseen states. An overall pipeline of the framework is shown in Figure 1a.

3.3 Regularization Through Forward Dynamics Model

We found empirically (and we demonstrate in the experiments section below) that the surprise stemming from haptic novelty was not enough to cause object-centric interaction. We postulate that by incorporating visual surprise (i.e. the mismatch between predicted forward dynamics and observed dynamics) [9], we can create an agent that seeks out visual novelty as well as haptic one and thus leads to better state space coverage. To this end, our model is augmented with a forward dynamics model (see Figure-1b) $\hat{z}_{t+1} = fdm(z_t, a_t)$ that learns to map the latent state z_t (obtained from the visual encoder enc) and action a_t at time t to the predicted latent state $\hat{z}_{t+1}$ at the next timestep. This model is also trained with L2 loss:

$$L_{fdm} = \|\hat{z}_{t+1} - z_{t+1}\|_2 = \|fdm(enc(x_t), a_t) - enc(x_{t+1})\|_2 . \tag{3}$$

The intrinsic reward is defined as the convex combination of the cross-modal prediction loss (Eq. 2) and the forward dynamics model loss (Eq. 3):

$$r_t = (1 - \lambda) \cdot L_{haptics} + \lambda \cdot L_{fdm} , \tag{4}$$

where $\lambda \in [0, 1]$ is a balancing factor. The effect of the factor λ on overall performance is studied in the ablation experiments described in Section 5.1.

3.4 Training

Learning is divided into two stages: (i) an *exploratory* step, where the agent performs free exploration following HaC, and (ii) an *adaptation* step, where the agent is tasked to solve a downstream problem, given a sparse reward.

During the exploratory step, each trajectory consists of pairs of image and force/torque features, (z_1, h_1), $(z_2, h_2),...,(z_n, h_n)$. These trajectories are used for two purposes: (i) updating the parameters of the prediction model to help shape the representations and (ii) updating the exploration policy based on the intrinsic reward r_t. Note that we use the touch features only to craft the intrinsic rewards and the input to RL agent consists of visual features alone to be comparable to the baselines. For vision-based curiosity models, Burda et al. [8] observed that encoding visual features via a random

Figure 2: **'MiniTouch' benchmark tasks** include opening a door, pushing an object to a target, grasping and lifting an object and a toy task in which object interactions are counted.

network constitute a simple and effective strategy compared to learned features. In Section 5.1, we investigate the performance of our model in both scenarios, i.e., when the features are learned vs random. The overall optimization problem at this step consists of the policy learning (driven by intrinsic reward), the touch reconstruction loss (Eq. 2), and the forward dynamics loss (Eq. 3). During the downstream adaptation step, the parameters of the policy network, the Q network and the replay buffer are retained from the exploratory phase. The objective of the down-stream task is computed as:

$$\min_{\theta} \left[-\mathbb{E}_{\pi} \left[\sum_t r_t^e \right] \right] \ , \tag{5}$$

where r_t^e in this phase is task-specific external sparse reward. In both steps, the objectives are optimized with Adam [52].

Implementation Details: The encoder is a four-layered strided CNN followed by a fully connected network. We use LeakyReLU [53] as non-linear activation in all the layers. The decoder network is a two-layered MLP that maps 256-dimensional visual features to touch vectors. For a more detailed description of the networks (SAC policy network and HaC networks, including the forward model) and hyper-parameters, please refer to the supplementary material Section 7.3.

4 Experimental Setting

Our experiments focus on a tabletop robot manipulation from raw image observations and raw force/torque sensory values, which we refer to as "touch vector". For our experiments, we use a 7-DoF Franka Emika Panda arm with a two-finger parallel gripper. Each of the fingers is equipped with a simulated force/torque sensor that measures the joint reaction force applied to it. We utilize PyBullet [54] to simulate the robot arm and haptic sensor[1].

4.1 MiniTouch Benchmark

Our proposed benchmark, MiniTouch, consists of four manipulation tasks: Playing, Pushing, Opening, Pick-up. Each of the tasks along with corresponding actions, observations, and rewards is described in detail in the Supplementary Material Section 7.1 and further illustrated in Figure 2. MiniTouch is an active repository[2] and we expect to update the benchmark with new tasks and datasets. The tasks are inspired by Yu et al. [55] but are *not* based on a proprietary simulator, feature an arm that we have access to for real-world experimentation (in follow-up work), and where the arm is equipped with a haptic sensor.

4.2 Baseline Comparisons and Metrics

For the task evaluation, we study two versions of our model: (i) HaC-Pure considering the touch vector reconstruction intrinsic reward alone, and (ii) HaC, considering the full intrinsic reward (Eq. 4). We compare with several well-known intrinsic exploration baselines based on visual features:

- **SAC**: The unmodified Soft Actor-Critic algorithm from Haarnoja et al. [51].
- **ICM**: SAC augmented with the state-of-the-art visual curiosity approach Intrinsic Curiosity Module (ICM) [12], which uses a visual prediction model to guide exploration.
- **Disagreement**: It uses model disagreement as objective for exploration [56, 28]. It leverages variance in the prediction of an ensemble of latent dynamics models as the reward.
- **RND**: Random Network Distillation [57] utilizes a randomly initialized neural network to specify an intrinsic reward for visiting unexplored states in hard exploration problems.

---

[1]Based on code from the official Franka Emika repo https://github.com/frankaemika/libfranka

[2]https://github.com/ElementAI/MiniTouch

(a) (b) (c)

HaC-Pure (ours)   HaC (ours)   ICM   Disagreement

Figure 3: **Object Interaction** To quantitatively evaluate an agent's object interaction, we consider both haptics interaction and object displacement. (a) shows the object movement evaluation (avg displacement in mm from the starting point) of our method compared with the baseline methods over training steps; (b) depicts the number of touch interactions, evaluated on the "playing" task. (c) Heat maps showing the object location at the beginning (*left*) and end (*right*) of the HaC training. The object locations are spread-out towards the end indicating interactive movement.

We built a Pytorch [58] version of these baselines based on their open source code (details in supplementary material). We use the following metrics to evaluate our method and the baseline models:

Exploration success: measures the percentage of times that the agent attained the goal state in the *exploratory* phase, i.e. with no external reward. Higher is better.
Success: denotes the percentage of times that the agent attained the goal state during the *downstream* task phase.
Episode steps: The number of steps required for each episode to succeed. This metric is an indicator of sample efficiency. The lesser the number of steps, the faster the agent's ability to succeed.
Touch-interaction: Amount of interaction the agent's fingers have with the underlying object. We measure this by computing the variance of force/torque sensory signal across the whole episode.
Object movement: The agent can resort to constantly engaging with the object unnecessarily to satisfy the objective. We, therefore, monitor the variance of door angle (for the Opening task) and the variance of object position (for the remaining tasks) over the course of training. A higher movement indicates diverse state space in addition to physical interaction.

5 Results and Discussion

HaC and baselines were trained on a Panda robot agent [54] for one million steps. In the *exploratory* phase of the training, we pre-train our method only with the curiosity-based intrinsic reward. We then progress to the *adaptation* phase. Also, note that across all tasks, HaC-Pure is based purely on cross-modal prediction, while HaC includes visual forward prediction reward in addition.

Figure 3a and 3b shows results on the basic task of playing with a single object. Since single object interaction does not have explicit goal states to evaluate, we instead measure the agent's ability to constantly engage and play with the underlying object. HaC-Pure displays four times better interaction with the underlying object when compared to SAC (see Figure 3b). Note from the plots that there is a trade-off when using HaC and HaC-Pure between constant interaction (i.e. touch interaction performance) and object movement dynamics. Collecting a variety of such interesting data during the *exploratory* phase helps the agent in terms of sample efficiency while solving the downstream tasks. Figure 9 shows similar comparison for Open-door task. In the following section, we examine the role of the forward objective term on touch interaction and possible ways to encode agent's observation in our ablation studies.

We compare HaC and HaC-Pure with SAC and state-of-the-art vision-based curiosity baselines on the remaining downstream tasks in MiniTouch. From Figure 4 it is evident that HaC and HaC-Pure perform better than SAC in all the tasks and better than the vision-based curiosity models in the majority of the tasks. Using SAC alone hinders the performance and is often unable to solve any of the three tasks. This is not surprising since the model is not motivated enough to collect diverse and useful data through interaction. We hypothesize that HaC-Pure without the visual prediction objective L_{fdm} could potentially bias the solutions towards more physical interaction, which is not necessary for every task. For instance, constant interaction in the pushing task could be seen as a hindrance as it does not let the object slide easily towards the target. Observe that ICM performs better than HaC-Pure in the pushing task, however, HaC dominates in performance by

Figure 4: **MiniTouch Evaluations**. Each row in the figure outlines the performance of the HaC variants and the baselines on a MiniTouch task. Each column marks performance on the four specified evaluation metrics over a number of training steps on the x-axis expressed in $1e^5$. The results are averaged across 5 random seeds and shaded areas represent mean ± one standard deviation while darker line represents the mean. In the majority of the tasks, HaC agents attain success in the *exploratory* phase with no external reward (see text). *Note*: We exclude the single object playing task as success in this task is equivalent to object interaction as depicted in Figure. 3.

Figure 5: **Forward Prediction weight.** Touch and Object movement evaluated on the (a) playing task and (b) Open-door task for different forward prediction weightings sampled $\sim [1, 0]$. Large weight (darker plot) favors object-movement towards the end of training, where as smaller weight improves touch-interaction. Middle value in the sweep range (*e.g.* 0.5) balances the trade-off. Note that movement is measured as distance(mm) for the Playing and angular distance for Open-door.

about 15%. Recall that the goal is not just to succeed but to help attain success in a sample efficient manner in fewer steps. The results support our hypothesis that cross-modal curiosity enables an RL agent to succeed at an early stage in training and often without any external reward. Similarly, our model outperforms on the opening task without external reward. However, HaC initially has lower success compared to RND but surpasses RND towards the end. Although HaC and HaC-Pure attain similar success in the pick-up task towards the end of the training, it is compelling to note that HaC-Pure attains faster convergence. This is because the picking task requires constant touch interaction (where HaC-Pure has an advantage), as opposed to diverse object movement.

5.1 Ablations

Forward objective and tuning Lambda Visual forward prediction L_{fdm} plays an important role when it is used in the right proportion. Our intrinsic reward is a weighted combination of cross-modal prediction and forward prediction as defined in Eq.4. Figure 5 illustrates the model behavior with different levels of emphasis on the forward loss term, with λ uniformly sampled between 0 and 1. Higher weights indicate that the future prediction dominates force/torque prediction. This leads

Metric	Pushing			Open Door			Pick-up			Playing		
	HaC	ICM+*haptics*	ICM	HaC	ICM+*haptics*	ICM	HaC	ICM+*haptics*	ICM	HaC	ICM+*haptics*	ICM
Exploration ↑	**0.403**	0.291	0.187	**0.669**	0.355	0.083	**0.063**	0.051	0.013	-	-	-
Success ↑	**0.733**	0.678	0.597	**0.983**	0.571	0.114	**0.891**	0.825	0.780	-	-	-
Episode steps ↓.	**57.84**	87.61	95.24	**23.34**	97.10	199.3	**30.54**	33.77	42.19	-	-	-
Touch-interaction ↑	**247.79**	210.11	202.66	**600.1**	287.97	43.56	980.7	**984.2**	952.3	**388.15**	267.021	63.31

Table 1: **Haptics-based future prediction** Table compares the mean evaluations for HaC and ICM+*haptics* on all the four tasks emphasizing the importance of cross-modal association(see text).

.

Figure 6: Latent feature space ablations

Figure 7: Comparing different latent space performance on *pushing* and *grasping* tasks. Features learned via haptics prediction perform better than those learned using IDF or Random.

to more object movement but lesser robot's constant touch-interaction with the underlying objects. This is useful in tasks such as Pushing. A smaller λ value leads to better inactive behavior which is handy in tasks such as grasping. In our experiments we choose an intermediate value (*e.g.* 0.5) that works best for all of our tasks.

Haptics in future prediction. The goal of this experiment is to strengthen the argument of cross-modal association. While conducting experiments, it is important to deduce information of one modality from another modality in a related manner than simply adding another modality on top of visual information. We created an additional baseline, ICM+*haptics*, where in addition to the visual prediction model we include the haptics-based future prediction model. We hypothesize ICM+*haptics* to perform better than ICM as it has additional information (haptics). The haptics-based future prediction model takes a touch vector as input and predicts the touch vector for the next time step. Table 1 compares HaC and ICM+*haptics* on MiniTouch tasks and we observe that ICM+*haptics* is better than ICM but compares below HaC. Table 4 in the supplementary compares RND based baseline.

Latent features for forward dynamics. Choosing ideal embedding space for decoding the touch vector (Figure 1a) and for predicting future state (Figure. 1b) is important. Existing approaches rely on a pretext inverse dynamics (ID) task of predicting the agent's action given its current and next states [9]. Another simple yet strong method is to use features from a random but fixed initialization of the encoder [12]. In our work, we learn the features by leveraging the self-supervised pretext task of predicting one modality from the other. Figure 6 compares (1) encoder, i.e. learned through cross-modal prediction(HaC) (2) random feature encoder(HaC-RF) (3) encoder learned through ID task (HaC-IDF). In each case, the decoder network is optimized through touch prediction. We observe that the random features variant is stable and effective on both HaC and ICM models.

6 Conclusion

Building self-seeking RL agents that can leverage cross-modal associations could be a key research direction in developmental robotics. Sense of touch is ubiquitous in human routine. Borrowing insights from how infants learn to explore out of curiosity by touching what they visually perceive, we formulated Haptics-based Curiosity (HaC) that is aimed at encouraging exploration via haptic interaction with the environment. We demonstrated in this work, that by involving additional modalities, the performance of curiosity-based systems on downstream tasks can be increased. We observed increased interaction with target objects, and presented evidence that HaC learns to solve the Mini-Touch benchmark tasks in an efficient manner while vanilla RL algorithms and vision-based curiosity formulations struggled. Force/torque sensing is widespread in the lab and industrial robots but

while there are plenty of robotic benchmarks, we believe that tactile feedback is an under-explored modality and by releasing our benchmark, we hope to enable future research in this exciting area.

Acknowledgements

We would like to sincerely thank Glen Berseth, Deepak Pathak, Edward Smith and Krishna Murthy for valuable feedback and insightful comments on the paper.

References

[1] V. Mnih, K. Kavukcuoglu, D. Silver, A. Graves, I. Antonoglou, D. Wierstra, and M. A. Riedmiller. Playing atari with deep reinforcement learning. *CoRR*, 2013.

[2] D. Silver, A. Huang, C. J. Maddison, A. Guez, L. Sifre, G. V. D. Driessche, J. Schrittwieser, I. Antonoglou, V. Panneershelvam, and M. Lanctot. Mastering the game of go with deep neural networks and tree search. *nature*, 2016.

[3] Y. Zhu, Z. Wang, J. Merel, A. A. Rusu, T. Erez, S. Cabi, T. Saran, J. Kramár, R. Hadsell, N. de Freitas, and N. Heess. Reinforcement and imitation learning for diverse visuomotor skills. *CoRR*, 2018.

[4] S. Forestier, Y. Mollard, and P. Oudeyer. Intrinsically motivated goal exploration processes with automatic curriculum learning. *CoRR*, 2017.

[5] D. Vernon, C. Hofsten, and L. Fadiga. A roadmap for cognitive development in humanoid robots. *978-3-642-16903-8*, 11, 2011.

[6] A. E and R. CH. The importance of touch in development. *Paediatr Child Health*, 2010;15(3).

[7] M. R. Connolly and L. Harris. Effects of stimulus incongruity on children's curiosity as measured by looking time and expression change. *Psychonomic Science*, 1971.

[8] Y. Burda, H. Edwards, D. Pathak, A. Storkey, T. Darrell, and A. A. Efros. Largescale study of curiosity-driven learning. *ICLR*, 2019.

[9] D. Pathak, P. Agrawal, A. Efros, and T. Darrell. Curiosity-driven exploration by self-supervised prediction. *ICML*, 2017.

[10] R. Raileanu and T. Rocktäschel. RIDE: Rewarding impact-driven exploration for procedurallygenerated environments. *ICLR*, 2020.

[11] M. Andrychowicz, F. Wolski, A. Ray, J. Schneider, R. Fong, P. Welinder, B. McGrew, J. Tobin, O. Pieter Abbeel, and W. Zaremba. Hindsight experience replay. In *NeurIPS*, 2017.

[12] Y. Burda, H. Edwards, A. Storkey, and O. Klimov. Exploration by random network distillation. *ICML*, 2019.

[13] S. H. Huang, M. Zambelli, J. Kay, M. F. Martins, Y. Tassa, P. M. Pilarski, and R. Hadsell. Learning gentle object manipulation with curiosity-driven deep reinforcement learning. *CoRR*, 2019.

[14] A. S. Chen, H. Nam, S. Nair, and C. Finn. Batch exploration with examples for scalable robotic reinforcement learning. *arXiv*, 2020.

[15] R. White. Motivation reconsidered: the concept of competence. *Psychological review*, 1959.

[16] A. G. Barto, S. Singh, and N. Chentanez. Intrinsically motivated learning of hierarchical collections of skills. In *International Conference on Development and Learning(ICDL)*, 2004.

[17] S. I. Di Domenico and R. M. Ryan. The emerging neuroscience of intrinsic motivation: A new frontier in self-determination research. *Frontiers in Human Neuroscience*, 2017.

[18] J. Schmidhuber. A possibility for implementing curiosity and boredom in model-building neural controllers. *ICSAB: From animals to animats*, 1991.

[19] P.-Y. Oudeyer, F. Kaplan, and V. V. Hafner. Intrinsic motivation systems for autonomous mental development. *IEEE transactions on evolutionary computation*, 2007.

[20] P.-Y. Oudeyer and F. Kaplan. What is intrinsic motivation? a typology of computational approaches. *Frontiers in neurorobotics*, 2009.

[21] N. Lair, C. Colas, R. P. J.-M. Dussoux, P. F. Dominey, and P.-Y. Oudeyer. Language grounding through social interactions and curiosity-driven multi-goal learni. *arXiv*, 2019.

[22] K. Marino, A. Gupta, R. Fergus, and A. Szlam. Hierarchical rl using an ensemble of proprioceptive periodic policies. *ICLR*, 2019.

[23] N. Savinov, A. Raichuk, R. Marinier, D. Vincent, M. Pollefeys, T. Lillicrap, and S. Gelly. Episodic curiosity through reachability. *aarXiv preprint arXiv:1810.02274*, 2018.

[24] R. Houthooft, X. Chen, Y. Duan, J. Schulman, F. D. Turck, and P. Abbeel. Curiosity-driven exploration in deep reinforcement learning via bayesian neural networks. *CoRR*, 2016.

[25] A. L. Strehl and M. L. Littman. An analysis of model-based interval estimation for markov decision processes. *Journal of Computer and System Sciences*, 2008.

[26] M. Bellemare, S. Srinivasan, G. Ostrovski, T. Schaul, D. Saxton, and R. Munos. Unifying count-based exploration and intrinsic motivation. *NeurIPS*, 2016.

[27] G. Ostrovski, M. G. Bellemare, A. van den Oord, and R. Munos. Count-based exploration with neural density models. *ICML*, 2017.

[28] R. Sekar, O. Rybkin, K. Daniilidis, P. Abbeel, D. Hafner, and D. Pathak. Planning to explore via self-supervised world models. In *ICML*, 2020.

[29] A. S. Klyubin, D. Polani, and D. L. Nehaniv. Empowerment: A universal agent-centric measure of control. *In 2005 IEEE Congress on Evolutionary Computation*, 2005.

[30] K. Gregor, D. J. Rezende, and D. Wierstra. Variational intrinsic control. *CoRR*, 2016.

[31] R. Dubey and T. L. Griffiths. Understanding exploration in humans and machines by formalizing the function of curiosity. *Current Opinion in Behavioral Sciences*, 2020.

[32] V. R. de Sa. Learning classification with unlabeled data. In *NeurIPS*, 1993.

[33] R. Gao, R. Feris, and K. Grauman. Learning to separate object sounds by watching unlabeled video. *ECCV*, 2018.

[34] A. Owens and A. A. Efros. Audio-visual scene analysis with self-supervised multisensory features. *ECCV*, 2018.

[35] R. Blake, K. V. Sobel, and T. W. James. Neural synergy between kinetic vision and touch. *Psychological Science*, 15:397–402, 2004.

[36] M. Kalakrishnan, L. Righetti, P. Pastor, and S. Schaal. Learning force control policies for compliant manipulation. In *IROS*, 2011.

[37] S. Levine, C. Finn, T. Darrell, and P. Abbeel. End-to-end training of deep visuomotor policies. *JMLR*, 2016.

[38] G.-H. Liu, A. Siravuru, S. Prabhakar, M. Veloso, and G. Kantor. Learning end-to-end multimodal sensor policies for autonomous navigation. In *CoRL*, 2017.

[39] N. Srivastava and R. R. Salakhutdinov. Multimodal learning with deep boltzmann machines. *NeurIPS*, 2012.

[40] Z. Gan, Y.-C. Chen, L. Li, C. Zhu, Y. Cheng, and J. J. Liu. Large-scale adversarial training for vision-and-language representation learning. In *NeurIPS*, 2020.

[41] Y. Gao, L. A. Hendricks, K. J. Kuchenbecker, and T. Darrell. Deep learning for tactile understanding from visual and haptic data. In *ICRA*, 2016.

[42] Y. Li, J.-Y. Zhu, R. Tedrake, and A. Torralba. Connecting touch and vision via cross-modal prediction. In *CVPR*, 2019.

[43] K. Chen, Y. Lee, and H. Soh. Multi-modal mutual information (mummi) training for robust self-supervised deep reinforcement learning. *ICRA*, 2021.

[44] H. van Hoof, N. Chen, M. Karl, P. van der Smagt, and J. Peters. Stable reinforcement learning with autoencoders for tactile and visual data. In *IROS*, 2016.

[45] R. Calandra, A. Owens, D. Jayaraman, J. Lin, W. Yuan, J. Malik, E. H. Adelson, and S. Levine. More than a feeling: Learning to grasp and regrasp using vision and touch. *IEEE Robotics and Automation Letters*, 2018.

[46] A. Murali, Y. Li, D. Gandhi, and A. Gupta. Learning to grasp without seeing. *International Symposium on Experimental Robotics*, 2018.

[47] L. Pape, C. M. Oddo, M. Controzzi, C. Cipriani, A. Förster, M. C. Carrozza, and J. Schmid-huber. Learning tactile skills through curious exploration. *Frontiers in Neurorobotics*, 6:6, 2012.

[48] J.-T. Lee, D. Bollegala, and S. Luo. "touching to see" and "seeing to feel": Robotic cross-modal sensory data generation for visual-tactile perception. *ICRA*, 2019.

[49] M. A. Lee, Y. Zhu, K. Srinivasan, P. Shah, S. Savarese, L. Fei-Fei, A. Garg, and J. Bohg. Making sense of vision and touch: Self-supervised learning of multimodal representations for contact-rich tasks. *ICRA*, 2019.

[50] V. Dean, S. Tulsiani, and A. Gupta. See, hear, explore: Curiosity via audio-visual association. In *NeurIPS*, 2020.

[51] T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *arXiv preprint arXiv:1801.01290*, 2018.

[52] D. P. Kingma and J. Ba. Adam: A method for stochastic optimization. In Y. Bengio and Y. LeCun, editors, *ICLR*, 2015.

[53] B. Xu, N. Wang, T. Chen, and M. Li. Empirical evaluation of rectified activations in convolu-tional network. *arxiv*, 2015.

[54] E. Coumans and Y. Bai. Pybullet, a python module for physics simulation for games, robotics and machine learning, 2016–2019.

[55] T. Yu, D. Quillen, Z. He, R. Julian, K. Hausman, C. Finn, and S. Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. *CoRR*, 2019.

[56] D. Pathak, D. Gandhi, and A. Gupta. Self-supervised exploration via disagreement. In *ICML*, 2019.

[57] Y. Burda, H. Edwards, A. J. Storkey, and O. Klimov. Exploration by random network distilla-tion. *ICLR*, 2019.

[58] A. Paszke, S. Gross, Massa, and et al. Pytorch: An imperative style, high-performance deep learning library. *NeurIPS*, 2019.

[59] V. Mnih, A. P. Badia, M. Mirza, A. Graves, T. Lillicrap, T. Harley, D. Silver, and K. Kavukcuoglu. Asynchronous methods for deep reinforcement learning. *ICML*, 2016.

Figure 8: **Haptics-based Curiosity (HaC) Overview** *Top*: An agent perceives a scene visually and anticipates the force/torque (FT) sensation of interacting with an object. *Bottom*: The object interaction leads to an unexpected FT sensation, which gives a positive reward to the policy, leading to an exploration policy that is seeking interactions that are haptically surprising. The agent's experiences gained in this way are later relabeled to become task-specific.

7   Supplementary Material

In this Supplementary Material section, we provide additional details concerning various elements which could not be elaborated on in the main paper. We begin with a detailed description of the proposed MiniTouch benchmark. We outline the action space, state space, and reward structure for each of the tasks. This is followed by a closer look into the various aspects of the haptics-control module including architectures, experimental procedures, hyper-parameters, and additional results. We include an ablation experiment at the end that investigates the usefulness larger exploration phase while solving each of the tasks.

7.1   MiniTouch Tasks

This section describes the cross-modal benchmark of simulated manipulation tasks, which we make use of and release as part of the paper. Unlike these prior simulation benchmarks, we particularly focus on providing a platform where one can use cross-modal information to solve diverse manipulation tasks. Existing benchmarks Yu et al. [55] do not include touch modality. An overview of the tasks in MiniTouch is outlined in Figure 2. These tasks are built off Pybullet [54] physics engine and contain different scene setups for each of the four tasks. The details of each of these tasks are further expanded. All the four tasks are compiled together as a "MiniTouch" benchmark suitable for evaluating interaction-based algorithms.

Playing: This environment is intended as a toy task to evaluate interaction frequency and does not feature any reward beyond interaction count. A cube is placed in a random position on a table at each episode. The agent needs to localize and interact with the cube.

Pushing: In this task, the agent needs to push an object placed randomly on a table to a target (visually indicated as a gray cube). The object position is sampled uniformly in polar coordinates around the target object (i.e. angle 0 to 360 degrees, distance 10 to 20 centimeters). The end effector's start position is sampled in the same way as the target position. In addition, the orientation of the gripper is fixed to be perpendicular to the ground all the time. The robot agent succeeds and receives a reward of +25 if the distance between the cube and the target object is less than 7 centimeters. A new episode starts if the agent succeeds. The environment also restarts if the cube is placed or pushed beyond a predefined bounding box comprising of acceptable positions on the table (*i.e.* positions that can be reached by the robot hand).

Opening: A cabinet with a door is randomly placed in reach of the agent. The goal is to find the door handle and open the door. The gripper orientation is fixed to point its fingers towards the door, parallel to the ground. For this task, the fingers are discretized to be open or closed. In addition, a fifth element is added to the action vector to control the yaw (relative rotation of the end-effector) to be able to approach the door. The robot succeeds and receives a reward of +25 when the angle of the door opening reaches thirty degrees or higher. Similar to the pushing task, a new episode starts if the agent reaches the goal.

Pick-up: In this environment, the agent needs to grasp and lift a randomly placed object. The agent's goal is to lift the object 5cm above the table. The agent receives a reward of +25 upon success. The object is placed uniformly randomly on a table. Similar to the Opening task, the end effector opening/closing is discretized, meaning when its internal continuous variable is below a threshold, the gripper closes, otherwise it remains open.

All of the tasks are implemented in the Pybullet physics engine [54], which is a free and open-source library that enables fast simulation.

7.2 Code

7.2.1 *MiniTouch* Library:

The task environment used in the experiments is packaged and released as a python library[1] that can be easily plugged into the training code. Setup instructions, code, and other details can be found in the README file included in the repository.

7.2.2 HaC and baselines:

We used the following open-source implementations for the baselines. We were able to reproduce the results from their papers before attempting to use them as baselines for our model:

ICM
https://github.com/openai/large-scale-curiosity

Disagreement:
https://github.com/danijar/dreamerv2
https://github.com/pathak22/exploration-by-disagreement

RND:
https://github.com/openai/random-network-distillation

7.3 Experimental Details

State space: The input states are a combination of visual and touch vector input. The visual input is a grayscale rendering of the scene with dimension 84×84, pre-processed similarly to Mnih et al. [59]. Image observations are captured from a static camera overlooking each scene. The touch vector input is composed of the 3-dimensional end-effector position, 2-dimensional finger position, ranging from 0 to 1, each denoting how far apart each finger is, and the 6-dimensional force/torque values. In total, the touch vector is 11-dimensional, $S \in \mathbb{R}^{11}$.
Action space: Actions are expressed as 4-dimensional continuous vectors. The first three elements describe the desired offset for the end effector at the next timestep based on its current position. The last dimension controls the relative desired distance between the two fingers at the next timestep.

Training   We use SAC [51] as the optimizer for our agent. Our training is composed of two phases as described in the main paper. (i)Exploration phase, (ii)Downstream task phase. In the exploratory phase (curiosity part) agent is trained using our intrinsic reward alone. In the task phase, network weights are seeded from the ones in the exploratory phase. We also retain the replay buffer from the exploratory phase in the downstream task phase. Duration of the exploration phase can be adjusted in the code using a hyper-parameter *stop-curiosity*. We have two hyper-parameters that change between the two phases, (i) α and (ii) the learning rate of the SAC algorithm. Details of hyper-parameters used for our experiments are outlined in Table 2 and Table 3.

---

[1]https://github.com/ElementAI/MiniTouch

SAC pretraining and training hyperparameters	
Parameter type	Value
optimizer	Adam
Visual network	Table 3
learning rate	3.10^{-5}
number of samples per minibatch	128
reward scale	100
replay buffer size	10^6
number of hidden units per layer	128
number of hidden layers (all networks)	2
activation	LeakyReLU
discount factor	0.99

Table 2: SAC parameters during pretraining and training.

(a)

(b)

Figure 9: **Object Interaction for Opening task.** (a) shows the average variance in door angle across the entire episode (note that the absolute variance is low but corresponds to successful door openings towards the end of training for HaC) and in (b), we count the number of touch interactions in the same task.

Encoder network				
Layer	Number of outputs	Kernel size	Stride	Activation function
Input x	$84 * 84 * 1$			
Convolution	20*20*32	$8 * 8$	4	LeakyReLU
Convolution	8*8*64	$4 * 4$	2	LeakyReLU
Convolution	4*4*124	$3 * 3$	1	LeakyReLU
Convolution	2*2*256	$2 * 2$	1	LeakyReLU
Fully-connected	256	1		LeakyReLU

Table 3: Visual network.

7.4 Object Interaction

As touched up in the experiments section of the main paper, Figure 9 depicts the touch interaction and door movement metrics for the Opening task. We make a similar observation to the result showed in Figure 3 for the Playing task. A higher touch-interaction need not indicate better object-movement. Agent can resort to constantly engaging with the object in a passive manner. HaC collects rich interaction data during the exploratory phase and helps the agent in terms of sample efficiency while solving the downstream tasks.

7.5 Additional Ablations

Does longer exploration help? We observe that having a longer exploratory phase of training with intrinsic reward alone usually benefits the overall performance. We can observe from Figure 4 that HaC attains decent success in the exploratory phase without any external reward on most of the tasks. This is because it encourages better associations and a larger collection of interesting configurations in the replay. The effect of the exploratory step is further studied and the results on

Metric	Pushing			Open Door			Pick-up			Playing		
	HaC	RND+*touch*	RND	HaC	RND+*touch*	RND	HaC	HaC-*RND*	RND	HaC	RND+*touch*	RND
Exploration ↑	**0.403**	0.181	0.077	**0.669**	0.564	0.380	**0.063**	0.013	0.005	-	-	-
Success ↑	**0.733**	0.710	0.582	**0.983**	0.921	0.875	**0.891**	0.593	0.450	-	-	-
Episode steps ↓.	**57.84**	55.20	97.51	**23.34**	23.54	37.92	**30.54**	52.29	89.88	-	-	-
Touch-interaction ↑	**247.79**	227.75	206.02	**600.1**	411.43	194.22	**980.7**	894.5	725.1	**388.15**	312.0	124.5

Table 4: **Random Network Distillation (RND) with touch** This table compares the mean evaluations for HaC and RND+*touch* on all the four tasks emphasizing the importance of the cross-modal association(see text). We omit measuring success and episode steps for playing task since success there is equivalent to object-interaction and has no explicit goal.

.

all of the downstream tasks with different duration of exploration are compiled in Figure 10. We depict the episode convergence steps and success rate to visualize the trend as expected.

Touch in Random Network Distillation We created an additional baseline RND+*touch* similar to touch in future prediction (ICM+*touch*) baseline. In this setting, the input to the random target network and predictor network (that predicts the outcome of target network) consists of both touch and visual feature vector concatenated. The baseline beats the vision only version by a margin for both Pushing and picking tasks as shown in the Table. 4, however for the Open-door tasks the improvement is not that significant. Although RND+*touch* is comparable with HaC for the Pushing task on the success rate, HaC has better sample efficiency as measured by episode steps. We believe this is because object movement is crucial for the pushing task compared to interaction, and prediction based techniques such as RND could be helpful in such settings.

Comparisons with Generalization to Novel shapes: It is desirable for an agent to be able to handle diverse shapes in order to be robust across arbitrary manipulation settings. We study this using an environment in which an object is sampled from a thousand procedurally generated objects. The objects are dissimilar with respect to shape and mass but are sampled from the same generative distribution. Out of 1000 different objects, 800 of them are used in the training phase, and we evaluate the agent's effectiveness on the remaining 200 unseen object shapes.

Although generalization to novel shapes is not the problem setting our method focuses on. We perform this proof of concept ablations to investigate that HaC parameters in the exploratory phase are not just reusable across different tasks with similar shapes (Eg: Playing, Pushing, and Picking), but also can help generalize when applied to distinctive shapes sampled from a similar distribution. Figure 11 shows touch interaction and object movement evaluations for a single object exploration task. We compare HaC with ICM and Disagreement baselines. . The results validate that our model generalizes to unseen object configurations.

7.6 Real world use cases:

It is possible to define safety boundaries for a robot arm (e.g. don't hit the table, don't move outside the arena boundaries) and have a robot arm autonomously and task-independently collect data for phase 1 of our method. In addition to this, we would like to point out that (a) in the pushing and pick-up tasks, only 5-10k steps are required for decent performance on the downstream task and (b) what we call a "step" is however long it takes the inverse kinematic solver to move the arm to the new end effector pose (that was generated by the policy). If many of the generated poses cluster together, that dramatically reduces runtime of the curiosity phase making it more suitable to real-world applicability. While no real robot data have been used in the experiments, our method is data agnostic. We note that the physics engine can be replaced by real-world data as there is no bias introduced in process. The networks used for the curiosity prediction task can be easily adapted, if needed, to accommodate inputs from a real robotic platform. As a next step and when restrictions are eased, we plan to implement this method on a physical system and replicate our experiments.

Figure 10: **Longer exploratory phase helps** Success and episode steps evaluations on different tasks for different lengths of *exploratory* phase. Darker shading indicates longer exploration.

Figure 11: **Generalization to novel shapes baseline comparisons**. Each column outlines Success and Episode steps for HaC, ICM, Disagreement and SAC baselines respectively. Disagreement has better generalization and reduced variance compared to ICM on the unseen categories. HaC is comparable to Disagreement on generalization performance while displaying better success and Episode steps rates.