Decentralized Gossip-Based Stochastic Bilevel Optimization over Communication Networks

Abstract

Bilevel optimization have gained growing interests, with numerous applications found in meta learning, minimax games, reinforcement learning, and nested composition optimization. This paper studies the problem of distributed bilevel optimization over a network where agents can only communicate with neighbors, including examples from multi-task, multi-agent learning and federated learning. In this paper, we propose a gossip-based distributed bilevel learning algorithm that allows networked agents to solve both the inner and outer optimization problems in a single timescale and share information via network propagation. We show that our algorithm enjoys the $\mathcal{O}(\frac{1}{K\epsilon^2})$ per-agent sample complexity for general nonconvex bilevel optimization and $\mathcal{O}(\frac{1}{K\epsilon})$ for strongly convex objective, achieving a speedup that scales linearly with the network size. The sample complexities are optimal in both ϵ and K. We test our algorithm on the examples of hyperparameter tuning and decentralized reinforcement learning. Simulated experiments confirmed that our algorithm achieves the state-of-the-art training efficiency and test accuracy.

1 Introduction

In recent years, stochastic bilevel optimization (SBO) has attracted increasing attention from the machine learning community. It has been found to provide favorable solutions in a variety of problems, such as meta learning and hyperparameter optimization (Franceschi et al., 2018; Snell et al., 2017; Bertinetto et al., 2018), composition optimization (Wang and Liu, 2016b), two-player games (Von Stackelberg and Von, 1952), reinforcement learning and imitation learning (Arora et al., 2020; Hong et al., 2020). While the majority of the above mentioned work focuses on algorithm designs in the classic centralized setting, such problems often arise in distributed/federated applications, where agents are not willing to share data but rather perform local updates and communicate with neighbors. Theories and algorithms for distributed stochastic bilevel optimization are less developed.

Consider the *decentralized* learning setting where the data are distributed over K agents $\mathcal{K} = \{1, 2, \cdots, K\}$ over a communication network. Each agent can only communicate with its neighbors. One example is federated learning which often concerns with a single-server-multi-user system, where agents communicate with a central server to cooperatively solve a task (Lan and Zhou, 2018),(Ge et al., 2018). Another example is sensor network, where sensors are fully decentralized and can only communicate with nearby neighbors (Taj and Cavallaro, 2011) .

We consider the following decentralized stochastic bilevel optimization problem,

$$\min_{x \in \mathbb{R}^{d_x}} F(x) = \left\{ \frac{1}{K} \sum_{k=1}^{K} f^k(x, y^*(x)) \right\}, \text{ s.t. } y^*(x) = \operatorname*{argmin}_{y \in \mathbb{R}^{d_y}} \left\{ \frac{1}{K} \sum_{k=1}^{K} g^k(x, y) \right\}, \quad (1)$$

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

(a) Single-Server-Multi-Agent Network

(b) Decentralized Network

Figure 1: Illustration of Distributed Network Structures. In a centralized network, the agents may work cooperatively to solve a specific task by communicating with the central server, commonly seen in federated learning.

where $f^k(x,y) = \mathbb{E}_{\zeta^k}[f^k(x,y;\zeta^k)]$ and $g^k(x,y) = \mathbb{E}_{\xi^k}[g^k(x,y;\xi^k)]$ may vary across agents. The expectations $\mathbb{E}_{\zeta^k}[\bullet]$ and $\mathbb{E}_{\xi^k}[\bullet]$ are taken with respect to the random variables ζ^k and ξ^k, with heterogeneous distributions across agents. We consider the scenario where each $g^k(x,y)$ is strongly convex in y. We denote by $F^* = \min_{x \in \mathbb{R}^{d_x}} F(x)$, $f(x,y) = \frac{1}{K}\sum_{k \in \mathcal{K}} f^k(x,y)$, and $g(x,y) = \frac{1}{K}\sum_{k \in \mathcal{K}} g^k(x,y)$ for notational convenience.

1.1 Example applications of SBO

SBO was first employed to formulate the resource allocation problem (Bracken and McGill, 1973) and has since found its application in many classic operations research settings (Cramer et al., 1994; Sobieszczanski-Sobieski and Haftka, 1997; Livne, 1999; Tu et al., 2020; Tu, 2021), and more recently in machine learning problems (Franceschi et al., 2018; Snell et al., 2017; Bertinetto et al., 2018; Wang and Liu, 2016b). In particular, we introduce two applications that have received a lot of recent attention, namely hyperparameter optimization and compositional optimization.

Hyperparameter Optimization The problem of hyper-parameter tuning (Okuno et al., 2021) often takes the following form:

$$\min_{x \in \mathbb{R}^d}\left\{\sum_{i \in \mathcal{D}_{\text{val}}} \ell_i(y^*(x))\right\}, \text{ s.t. } y^*(x) \in \operatorname*{argmin}_{y \in \mathbb{R}^{d_y}}\left\{\sum_{j \in \mathcal{D}_{\text{train}}} \ell_j(y) + \mathcal{R}(x,y)\right\}, \qquad (2)$$

where $\mathcal{D}_{\text{train}}$ and $\mathcal{D}_{\text{val}}$ are two datasets used for training and validation, respectively, $y \in \mathbb{R}^{d_y}$ is a vector of unknown parameters to optimize, $\ell_j(y)$ is a convex loss over data i, and $x \in \mathbb{R}^d$ is a vector of hyper-parameters for a strongly convex regularizer $\mathcal{R}(x,y)$. For any hyper-parameter $x \in \mathbb{R}^d$, the inner-level problem solves for the best parameter $y^*(x)$ over the training set $\mathcal{D}_{\text{train}}$ under the regularized training loss $\ell_j(y) + \mathcal{R}(x,y)$. The goal is to find the hyper-parameter $x^* \in \mathbb{R}^d$ whose corresponding best response $y^*(x)$ yields the least loss over the validation set $\mathcal{D}_{\text{val}}$. In practice, tuning continuous hyperparameters is often done by grid search which is exponentially expensive. Efficient algorithm of SBO should find optimal parameters in time polynomial to dimension, rather than exponential. When the training and validation set are distributed across nodes, the problem becomes a distributed SBO.

Compositional Optimization Let $g(x,\xi) : \mathbb{R}^d \to \mathbb{R}^{d_y}$ and $f(y,\zeta) : \mathbb{R}^{d_y} \to \mathbb{R}$ be two stochastic mappings, stochastic compositional optimization (SCO) (Wang et al., 2017a) takes the form

$$\min_{x \in \mathcal{X}} \mathbb{E}_\zeta[f(\mathbb{E}_\xi[h(x;\xi)];\zeta)].$$

SCO applies to risk management (Yang et al., 2019; Ruszczynski, 2021), machine learning (Chen et al., 2021b), and reinforcement learning (Wang et al., 2017b). SCO was identified as a special case of SBO by (Chen et al., 2021c). To see this, we take the inner optimization objective to be $g(x,y) = \mathbb{E}_\xi[(y - h(x,\xi))^2]$. Thus $y^*(x) = \operatorname{argmin}_y g(x,y)$ becomes $y^*(x) = \mathbb{E}_\xi[h(x;\xi)]$, arriving at an instance of SBO.

1.2 Challenges with Distributed SBO

Despite the recent fast development of distributed single-level optimization, a proper method for Decentralized Stochastic Bilevel Optimization (DSBO) remains illusive. The major hurdle of solving DSBO lies in the absence of explicit knowledge of $y^*(x)$, so that an unbiased gradient of $\nabla f(x, y^*(x))$ is unavailable. Recently, by applying the implicit function theorem, (Couellan and Wang, 2016; Ghadimi and Wang, 2018) showed that the gradient of non-distributed SBO can be expressed as

$$\nabla_x f(x, y^*(x)) - \nabla_{xy}^2 g(x, y^*(x))[\nabla_{yy}^2 g(x, y^*(x))]^{-1} \nabla_y f(x, y^*(x)), \tag{3}$$

providing a connection between SBO and classical stochastic optimization. Since then, various algorithms have been proposed to obtain sharp estimators for $y^*(x)$ and reduce the bias of the constructed gradients (Chen et al., 2021a; Hong et al., 2020; Ji et al., 2021; Yang et al., 2021). These techniques result in nearly tight convergence analysis and give rise to algorithms widely used in applications. However, none of the prior algorithms can be applied to the distributed setting.

Solving Problem (1) becomes challenging in the distributed setting in several aspects:

1. Even in single-agent SBO, lack of $y^*(x)$ makes outer optimization nontrivial, and estimating $y^*(x)$ requires additional stochastic approximation, weighted averaging, and sophisticated calculation.

2. Calculating outer gradient is highly nontrivial, even when we have an inner solution y. Note that

$$\frac{1}{K} \sum_{k \in \mathcal{K}} \left(\nabla_{xy}^2 g^k(x, y) [\nabla_{yy}^2 g^k(x, y)]^{-1} \nabla_y f^k(x, y) \right) \neq \nabla_{xy}^2 g(x, y) [\nabla_{yy}^2 g(x, y)]^{-1} \nabla_y f(x, y). \tag{4}$$

   In other words, even the inner problem is solved, the outer gradient requires new mechanism to estimate.

3. Now we move to SBO over distributed networks. In network learning, communication among agents can be limited by the network stucture and communication protocol, so taking a simple average across agents may require multiple rounds of communication.

Because of the above hurdles, it remains unclear how to sharply estimate the outer gradient under a distributed network. As an attempt to tackle this problem, this paper study the convergence theory and sample complexity of gossip-based algorithm. In particular, we ask two theoretical questions:

(i) How does the sample complexity of DSBO scale with the optimality gap and network size?
(ii) How is the efficiency of DSBO affected by the network structure?

In this paper, we develop a gossip-based stochastic approximation scheme where each agent solves an optimization problem collaboratively by sampling stochastic first- and second-order information using its data and making gossip communications with its neighbors. In addition, we develop novel convergence analysis techniques to characterize the convergence behavior of our algorithm. To the best of our knowledge, our work is the first to formulate DSBO mathematically and propose an algorithm with theoretical convergence guarantees. Moreover, we show that our algorithm enjoys an $\mathcal{O}(\frac{1}{K\epsilon^2})$ sample complexity for finding ϵ-stationary points for nonconvex objectives and enjoys an $\mathcal{O}(\frac{1}{K\epsilon})$ sample complexity for Polyak-Łojasiewicz (PL) functions, subsuming strongly convex optimization. These results subsume the state-of-the-art results for non-federated stochastic bilevel optimization (Chen et al., 2021c) and central-server regime (Tarzanagh et al., 2022), showing that nearly no degradation is induced by network consensus. Further, the above results suggest that our algorithm exhibits the linear speed-up effect for decentralized settings; that is, the required per-agent sample complexities decrease linearly to the number of agents.

2 Related Works

Bilevel optimization was first formulated by (Bracken and McGill, 1973) for solving resource allocation problems. Later, a class of constrained-based algorithms was proposed by (Hansen et al., 1992; Shi et al., 2005), which treats the inner-level optimality condition as constraints to the out-level problem. Recently, (Couellan and Wang, 2016) examined the finite-sum case for unconstrained strongly convex lower-lower problems and proposed a gradient-based algorithm that exhibits asymptotic convergence under certain step-sizes. For SBO, (Ghadimi and Wang, 2018) developed a double-loop algorithm and established the first known complexity results. Subsequently,

	Stochastic Bilevel Optimization					
	BSA	stocBio	ALSET	FEDNEST	This Work	
Network	Single-Agent			Central-Server		Decentralized
Samples in ζ	$\mathcal{O}(\epsilon^{-2})$	$\mathcal{O}(\epsilon^{-2})$	$\mathcal{O}(\epsilon^{-2})$	$\mathcal{O}(\epsilon^{-2})$	$\mathcal{O}(\frac{1}{K\epsilon^2})$	$\mathcal{O}(\frac{1}{K\epsilon^2} + \frac{K}{(1-\rho)^2\epsilon})$
Samples in ξ	$\mathcal{O}(\epsilon^{-3})$	$\mathcal{O}(\epsilon^{-2})$	$\mathcal{O}(\epsilon^{-2})$	$\mathcal{O}(\epsilon^{-2})$	$\mathcal{O}(\frac{1}{K\epsilon^2})$	$\mathcal{O}(\frac{1}{K\epsilon^2} + \frac{K}{(1-\rho)^2\epsilon})$

	Stochastic Compositional Optimization					
	SCGD	NASA	ALSET	FEDNEST	This Work	
Network	Single-Agent			Central-Server		Decentralized
Samples in ζ	$\mathcal{O}(\epsilon^{-4})$	$\mathcal{O}(\epsilon^{-2})$	$\mathcal{O}(\epsilon^{-2})$	$\mathcal{O}(\epsilon^{-2})$	$\mathcal{O}(\frac{1}{K\epsilon^2})$	$\mathcal{O}(\frac{1}{K\epsilon^2} + \frac{K}{(1-\rho)^2\epsilon})$
Samples in ξ	$\mathcal{O}(\epsilon^{-4})$	$\mathcal{O}(\epsilon^{-2})$	$\mathcal{O}(\epsilon^{-2})$	$\mathcal{O}(\epsilon^{-2})$	$\mathcal{O}(\frac{1}{K\epsilon^2})$	$\mathcal{O}(\frac{1}{K\epsilon^2} + \frac{K}{(1-\rho)^2\epsilon})$

Table 1: Summary of per-agent sample complexities for nonconvex stochastic bilevel and compositional optimization. $(1-\rho)$ denotes the spectral gap of the network adjacency matrix. BSA (Ghadimi and Wang, 2018), ALSET (Chen et al., 2021a), stocBio (Ji et al., 2021), FEDNEST (Tarzanagh et al., 2022), SCGD (Wang and Liu, 2016b), NASA (Ghadimi et al., 2020).

various methods have been employed to improve the sample complexity, including two-timescale stochastic approximation (Hong et al., 2020), acceleration (Chen et al., 2021a), momentum (Khanduri et al., 2021), and variance reduction (Guo et al., 2021; Ji et al., 2021; Yang et al., 2021).

Distributed optimization was developed to handle real-world large-scale datasets (Dekel et al., 2012; Feyzmahdavian et al., 2016) and graph estimation (Wang et al., 2015). Centralized and decentralized systems are two important problems that have drawn significant attention. A centralized system considers the network topology where there exists a central agent that communicates with the remaining agents (Lan and Zhou, 2018), while in a decentralized system (Gao and Huang, 2020; Koloskova et al., 2019; Lan et al., 2020; McMahan et al., 2017), each agent can only communicate with its neighbors by using gossip (Lian et al., 2017b) or gradient tracking (Pu and Nedić, 2021) communication strategies. Variance reduction approaches (Xin et al., 2020, 2021; Lian et al., 2017a) have also been applied to improve the convergence rate of decentralized optimization. Random projection schemes have been studied to handle large sets of constraints (Wang and Bertsekas, 2016; Liu et al., 2015). All of the above trials were made on vanilla stochastic optimization problems. We are the first to study the decentralized bilevel optimization problem to our knowledge. Table 1 compares this work with prior arts under different settings.

3 Problem Setup

Assumption 3.1 (Sampling Oracle $\mathcal{SO}$) *Agent k may query the sampler and receive an independent locally sampled unbiased first- and second-order information $\nabla_x f^k(x, y; \zeta^k)$, $\nabla_y f^k(x, y; \xi^k)$, $\nabla_y g^k(x, y; \xi^k)$, $\nabla_{yy}^2 g^k(x, y; \xi^k)$, and $\nabla_{xy}^2 g^k(x, y; \xi^k)$.*

Assumption 3.2 (Gossip Protocol) *The network gossip protocol is specified by a $K \times K$ symmetric matrix W with nonnegative entries. Each agent k may receive information from its neighbors, e.g., $z_j, j \in \mathcal{N}_k$, and aggregate them by a weighted sum $\sum_{j \in \mathcal{N}_k} w_{k,j} z_j$. Further, matrix W satisfies*

    (i) W is doubly stochastic such that $\sum_i w_{i,j} = 1$ and $\sum_j w_{i,j} = 1$ for all $i, j \in [K]$.

    (ii) There exists a constant $\rho \in (0, 1)$ such that $\|W - \frac{1}{K}\mathbf{1}\mathbf{1}^\top\|_2^2 = \rho$, where $\|A\|_2$ denotes the spectral norm of $A \in \mathbb{R}^{K \times K}$.

These assumptions on the adjacency matrix are crucial to ensure the convergence of decentralized algorithms, and are commonly made in the decentralized optimization literature (Lian et al., 2017b).

Assumption 3.3 (Smoothness and Convexity) *We impose the following smoothness assumptions:*

    (i) $\nabla_x f^k(x, y)$ and $\nabla_y f^k(\bullet, y)$ are L_f-Lipschitz continuous in (x, y).

    (ii) $\nabla_y g^k(x, y)$, $\nabla_{yx}^2 g^k(x, y)$, and $\nabla_{yy}^2 g^k(x, y)$ are L_g-Lipschitz continuous in (x, y).

Algorithm 1 Gossip-Based Decentralized Stochastic Bilevel Optimization

---

input: Step-sizes $\{\alpha_t\}, \{\beta_t\}, \{\gamma_t\}$, total iterations T, adjacency matrix W, smoothness constant L_g, hessian sampling parameter b
$\quad x_0^k = \mathbf{0}, y_0^k = \mathbf{0}, u_0^k = \mathbf{0}, s_0^k = \mathbf{0}, h_0^t = \mathbf{0}, v_{0,i}^k = \mu_g \mathbf{I}$ for $i = 1, 2, \cdots, b$
1: **for** $t = 0, 1, \cdots, T-1$ **do**
2: $\quad$ **for** $k = 1, \cdots, K$ **do**
3: $\qquad$ Local sampling: Query $\mathcal{SO}$ at (x_t^k, y_t^k) to obtain $\nabla_x f^k(x_t^k, y_t^k; \zeta_t^k), \nabla_y f^k(x_t^k, y_t^k; \zeta_t^k),$
$\qquad\qquad \nabla_y g^k(x_t^k, y_t^k; \xi_t^k), \nabla_{xy}^2 g^k(x_t^k, y_t^k; \xi_t^k),$ and $\{\nabla_{yy}^2 g^k(x_t^k, y_t^k; \xi_{t,i}^k)\}_{i=1}^b.$
4: $\qquad$ Outer loop update: $x_{t+1}^k = \sum_{j \in \mathcal{N}_k} w_{k,j} x_t^j - \alpha_t \left(s_t^k - u_t^k q_t^k h_t^k \right).$
5: $\qquad$ Inner loop update: $y_{t+1}^k = \sum_{j \in \mathcal{N}_k} w_{k,j} y_t^j - \gamma_t \nabla_y g^k(x_t^k, y_t^k; \xi_t^k).$
6: $\qquad$ Estimate $\nabla_x f(x_t, y_t)$: $s_{t+1}^k = (1 - \beta_t) \sum_{j \in \mathcal{N}_k} w_{k,j} s_t^j + \beta_t \nabla_x f^k(x_t^k, y_t^k; \zeta_t^k).$
7: $\qquad$ Estimate $\nabla_y f(x_t, y_t)$: $h_{t+1}^k = (1 - \beta_t) \sum_{j \in \mathcal{N}_k} w_{k,j} h_t^j + \beta_t \nabla_y f^k(x_t^k, y_t^k; \zeta_t^k).$
8: $\qquad$ Estimate $\nabla_{xy}^2 g(x_t, y_t)$: $u_{t+1}^k = (1 - \beta_t) \sum_{j \in \mathcal{N}_k} w_{k,j} u_t^j + \beta_t \nabla_{xy}^2 g^k(x_t^k, y_t^k; \xi_t^k).$
9: $\qquad$ Estimate $[\nabla_{yy}^2 g(x_t, y_t)]^{-1}$: Set $Q_{t+1,0}^k = \mathbf{I}$
10: $\qquad$ **for** $i = 1, \cdots, b$ **do**
11: $\qquad\qquad v_{t+1,i}^k = (1 - \beta_t) \sum_{j \in \mathcal{N}_k} w_{k,j} v_{t,i}^j + \beta_t \nabla_{yy}^2 g^k(x_t^k, y_t^k; \xi_{t,i}^k),$
12: $\qquad\qquad Q_{t+1,i}^k = \mathbf{I} + (\mathbf{I} - \frac{1}{L_g} v_{t+1,i}^k) Q_{t+1,i-1}^k$
13: $\qquad$ **end for**
14: $\qquad$ Set $q_{t+1}^k = \frac{1}{L_g} Q_{t+1,b}^k$
15: $\quad$ **end for**
16: **end for**
output: $\bar{x}_t = \frac{1}{K} \sum_{k \in \mathcal{K}} x_t^k$

---

140 $\quad$ *(iii) $g(x, y)$ is μ_g-strongly convex in y.*

141 We defer the detailed assumptions to Section A.1 of the supplement.

142 Here we point out that the above assumptions allow the heterogeneity between functions f^k's and
143 g^k's over the agents, and the smoothness and boundedness conditions are commonly adopted in SBO
144 (Hong et al., 2020; Chen et al., 2021a).

4 Algorithm

146 As discussed in Section 1.2, the key challenge in solving DSBO is that each agent has only access
147 to its own data but is required to construct estimators for the gradients and Hessian averaged across
148 all agents. It is particularly challenging to construct such estimators when limited by the network's
149 communication protocol.

150 To overcome this issue, we propose a gossip-based DSBO algorithm where each agent $k \in \mathcal{K}$
151 iteratively updates a solution pair (x_t^k, y_t^k) by using the combination of gossip communications and
152 weighted-average stochastic approximation, where y_t^k serves as an estimator of the best response
153 $y_t^* := y^*(\bar{x}_t)$ with $\bar{x}_t := \frac{1}{K} \sum_{k \in \mathcal{K}} x_t^k$. The full algorithm is given in Alg. 1.

154 Here we briefly explain the idea of our DSBO algorithm. Suppose agent k would like to estimate
155 $\nabla_x f(x_t^k, y_t^k)$ by s_t^k, under Alg. 1 Step 6, it would query the stochastic first-order information using
156 its own data, make gossip communications with neighbors, and update its estimators by taking the
157 weighted average among its previous estimate s_{t-1}^k, neighbors j's estimate s_{t-1}^j, and the newly
158 sampled gradient $\nabla_x f^k(x_t^k, y_t^k; \zeta_t^k)$. Roughly speaking, this procedure can be viewed as taking
159 weighted average among gradients sampled by all agents over the network, except that the effect of
160 consensus should also been taken into account.

The updates for $\nabla_y f$ and $\nabla_{xy}^2 g$ are conducted in a similar manner (Steps 7 & 8), but it takes extra
efforts to evaluate $[\nabla_{yy}^2 g]^{-1}$, due to the absence of its unbiased estimator. To be specific, we note
that $\frac{1}{K} \sum_{k \in \mathcal{K}} [\nabla_{yy}^2 g^k]^{-1} \neq [\frac{1}{K} \sum_{k \in \mathcal{K}} \nabla_{yy}^2 g^k]^{-1}$, making the unbiased estimator of the desired term
unavailable even if each agent has an unbiased estimator for $[\nabla_{yy}^2 g^k]^{-1}$. This is indeed a unique

challenge for decentralized bilevel optimization. To overcome this issue, we propose a *novel* approach that each agent k constructs b independent estimators $\{v^k_{t,j}\}^b_{j=1}$ for $\nabla^2_{yy}g(x^k_t, y^k_t)$ via consensus and stochastic approximation. We then estimate $\nabla^2_{yy}g(x^k_t, y^k_t)$ by utilizing the following approximation.

$$\left(\frac{1}{L_g}\nabla^2_{yy}g(x^k_t, y^k_t)\right)^{-1} \approx \mathbf{I} + \sum_{j=1}^b \left(\mathbf{I} - \frac{1}{L_g}\nabla^2_{yy}g(x^k_t, y^k_t)\right)^j \approx \mathbf{I} + \sum_{i=1}^b \prod_{j=1}^i \left(\mathbf{I} - \frac{1}{L_g}v^k_{t,j}\right).$$

We provide details in Steps 4 & 9.

Finally, by utilizing the estimators obtained in the above procedure, each agent would compute the gradient (3) and update the outer solution x^k_t by using the combination of gossip communication and stochastic gradient descent (Step 3). The inner loop solution y^k_t can be updated by (Step 4) in a similar way.

We highlight the following key features of our DSBO algorithm: (1) each agent would only communicate their estimates instead of the raw data in the gossip-communication process, which preserves data privacy. (2) agent k would make $\mathcal{O}(|\mathcal{N}_k|)$ communications with its neighbors in each round, which is much smaller than the total number of agents in a naive approach. (3) the algorithm is robust to contingencies in the network. If some communication channel fails, the agents can still jointly learn provided that the network is still connected. In contrast, a single-center-multi-user network would fail completely in case of a center failure.

5 Theory

In this section, we analyze the performance of our DSBO algorithm for both nonconvex and μ-PL objectives, and derive the convergence rates for both cases.

5.1 Nonconvex Objectives

We first consider the scenario where overall objective function $F(x)$ is nonconvex. For nonconvex objectives, given the total number of iterations T, we employ the step-sizes in a constant form that

$$\alpha_t = C_0\sqrt{\frac{K}{T}}, \beta_t = \gamma_t = \sqrt{\frac{K}{T}}, \text{ and } b = \Theta(\log(T)) \text{ for all } t = 0, 1, \cdots, T, \qquad (5)$$

where $C_0 > 0$ is a small constant.

Compounded effect of consensus and SBO: As discussed earlier, to derive the convergence rate of SBO under decentralized federated setting, the key step is to quantify the compounded effect between the consensus errors induced by the network structure and the biases induced by estimating gradient within (3). Distinct from the central-server or non-federated regimes, the consensus errors induced by the decentralized network structure has to be handled carefully. We conduct careful analysis to derive the contraction of consensus errors, and further show that both bias and variance of the averaged estimator diminish to zero, establishing a nontrivial convergence argument to the desired gradient and Hessian. In particular, the estimators preserve a concentration property so that their variances decrease proportionally to $1/K$, suggesting that the network consensus effect would not degrade the concentration of the generated stochastic samples. To achieve the best possible convergence rate, we carefully set the algorithm parameters, including step-sizes α_t, γ_t and averaging weights β_t, to control the above consensus errors and biases.

We provide the convergence rate of Alg. 1 in the following theorem and defer the detailed proof to Section B.7 of the supplementary material.

Theorem 5.1 *Suppose Assumptions 3.1, 3.2, and 3.3 hold. Letting $\bar{x}_t = \frac{1}{K}\sum_{k\in\mathcal{K}} x^k_t$, then*

$$\frac{1}{T}\sum_{t=0}^{T-1}\mathbb{E}[\|\nabla F(\bar{x}_t)\|^2] \leq \mathcal{O}\left(\frac{1}{\sqrt{KT}}\right) + \mathcal{O}\left(\frac{K}{T(1-\rho)^2}\right).$$

More details and proof are deferred to Section B.7 of the supplement.

Effect of consensus: In this result, the $\mathcal{O}(\frac{K}{T(1-\rho)^2})$ term represents the errors induced by consensus of network. Despite the dependency with the network structure, such term diminishes to zero in the

order of $\mathcal{O}(1/T)$, becoming a small order term when T is large. Consequently, given the network topology, the asymptotic convergence behavior of DSBO is independent of the network structure, answering the question (ii) raised in Section 1.

Linear speedup: Because each agent queries $\mathcal{O}(1)$ stochastic samples per round, clearly the required iteration and per-agent sample complexities for finding an ϵ-stationary point such that $\frac{1}{T}\sum_{t=0}^{T-1}\mathbb{E}[\|\nabla F(\bar{x}_t)\|^2] \leq \epsilon$ are both $\mathcal{O}(\frac{1}{K\epsilon^2})$. Such result implies that our algorithm achieves a linear speed-up effect proportionate to the number of agents K. In other words, in the presence of more agents, each agent needs to query fewer stochastic samples to achieve a specified accuracy. Meanwhile, our rate also matches the best-known $\mathcal{O}(1/K\epsilon^2)$ iteration and per-agent sample complexities under the decentralized vanilla stochastic gradient descent settings (Lian et al., 2018). To our knowledge, it is the first time such a result has been established for DSBO problems.

Single-center-multi-user-federated SBO: We point out that a simplified version of our algorithm solves single-center-multi-user-federated SBO, where the central server directly collects information from each agent and calculates the gradient by employing the weighted-average stochastic approximation scheme among the collected information. In such scenario, the agents no longer make gossip communication with neighbors but synchronously receives a common solution from the central server, so that the consensus effect would disappear. In Theorem D.1, we show that a variant of our algorithm can indeed achieve the same $\mathcal{O}(\frac{1}{\sqrt{KT}})$ convergence rate in this setting.

5.2 μ-PL Objectives

Next we study the case where the objective function satisfies the following μ-PL condition.

Assumption 5.2 *There exists a constant $\mu > 0$ such that the objective satisfies the PL condition:*

$$2\mu(F(x) - F^*) \leq \|\nabla F(x)\|^2.$$

Note that the class of strongly convex functions is a special case of μ-PL functions. To utilize the μ-PL property and achieve fast convergence, unlike the nonconvex case (5) where the step-sizes are set as constants depending on the total number of iterations T, we employ step-sizes in a diminishing form that

$$\alpha_t = \frac{2}{\mu(C_1 + t)}, \beta_t = \gamma_t = \frac{C_1}{C_1 + t}, \text{ and } b = \Theta(\log(T)) \text{ for } t \geq 1, \tag{6}$$

where $C_1 > 0$ is a large constant and $b =$. By following an analysis routine similar to that in the nonconvex scenario, in the next result, we derive the convergence rate of Alg. 1 for μ-PL objectives.

Theorem 5.3 *Suppose Assumptions 3.1, 3.2, and 3.3 hold and the function satisfies the μ-PL Assumption 5.2. Letting $\bar{x}_T = \frac{1}{K}\sum_{k\in\mathcal{K}} x_T^k$, then*

$$\mathbb{E}[F(\bar{x}_T)] - F^* \leq \mathcal{O}\left(\frac{1}{KT}\right) + \mathcal{O}\left(\frac{\ln T}{T^2(1-\rho)^2}\right).$$

Both iteration and per-agent sample complexities for finding an ϵ-optimal point $\mathbb{E}[F(\bar{x}_T)] - F^* \leq \epsilon$ are $\mathcal{O}(\frac{1}{K\epsilon})$.

Details and proof are deferred to Section C.2 of the supplement. This result shows that our algorithm achieves a faster convergence rate for functions satisfying the μ-PL condition in terms of both iteration and sample complexities. First, similar as the nonconvex scenario, the consensus error decays in the order of $\tilde{\mathcal{O}}(\frac{1}{T^2(1-\rho)^2})$. Dominated by $\mathcal{O}(\frac{1}{KT})$, such consensus decaying order indicates that the network structure would not affect Alg. 1's asymptotic convergence behavior under μ-PL objectives. Meanwhile, the above result implies that Alg. 1 speeds up linearly with the number of agents and matches the optimal $\mathcal{O}(1/\epsilon)$ sample complexity for single-sever vanilla strongly-convex stochastic optimization (Rakhlin et al., 2011). As a result, our algorithm achieves the *optimal* sample complexities for decentralized stochastic bilevel optimization, establishing the benchmark.

6 Numerical Experiments

In this section, we validate the practical performance of our algorithm in two examples: hyper-parameter optimization and policy evaluation in Markov Decision Processes (MDP), on artificially

| (a) | (b) |

Figure 2: (a) Empirical averaged training loss against total samples for DSBO $K = 5, 10, 20$ and DBSA $K = 5$. (b) Empirical averaged validation loss against iteration for DSBO $K = 5, 10, 20$. All figures are generated through 10 independent simulations over australia handwriting dataset.

constructed decentralized ring networks. We run the experiments on a single server desktop computer. We provide the details of federate hyper-parameter optimization and federated policy evaluation.

Hyper-parameter Optimization We consider federated hyper-parameter optimization (2) for a handwriting recognition problem over the Australia handwriting dataset (Chang and Lin, 2011) consisting of data points (w_i, z_i), where $w_i \in \mathbb{R}^{14}$ is the feature and $z_i \in \{0, 1\}$ represents whether this data point belongs to category "1" or not. In our experiment, we consider the sigmoid loss function that $l_i(z) = 1/(1 + \exp(-z))$ and a strongly convex regularizer $\mathcal{R}(x, y) = \sum_{i=1}^{d} \frac{x_i}{2} \|y_i\|^2$. We consider a ring network of K agents where each agent i preserves two neighbors $(i-1)$ and $(i+1)$ and conduct gossip communication strategy with adjacency matrix $w_{i,j} = \frac{1}{3}$ for $j \in \{i-1, i, i+1\}$.

Before testing Alg. 1, we first randomly split the dataset for training and validation, and then allocates both training and validation dataset over K agents. We then run Algorithm 1 for $T = 20000$ iterations, with $b = 200$, $\alpha_t = 0.1\sqrt{K/T}$, and $\beta_t = \gamma_t = 10\sqrt{K/T}$.

For benchmark comparison, we implement a baseline algorithm Decentralized Bilevel Stochastic Approximation (DBSA), a naive extension of the double-loop BSA algorithm (Ghadimi and Wang, 2018) in the decentralized setting, formally stated in Section E.1 of the supplementary materials.

We first consider $K = 5$, test Alg. 1 for 5×10^4 iterations, and compare its performance with DBSA. We report the validation loss against total samples in Figure 2 and observe that DSBO exhibits superior performance to DBSA. In particular, Further, we observe that our algorithm outperforms the baseline algorithm DBSA that it requires fewer samples for DSBO to achieve a certain accuracy.

To investigate the efficiency of Alg. 1 to the network structure, we test Alg. 1 over $K = 5, 10, 20$, and report the details of training and validation loss in Figure 2. Further, comparing the performances of Alg. 1 over different agents $K = 5, 10, 20$, we observe that Alg. 1 converges faster by using more agents. This observation suggests that Alg. 1 exhibits a speed-up effect by using more agents. We provide additional experiments on networks of larger size ($K = 100$) and various topologies (fully-connected and randomly-connected) in Section E.1 of the supplement.

Distributed policy evaluation for reinforcement learning We consider a multi-agent MDP problem arising in reinforcement learning. Let $\mathcal{S}$ be the state space, for any state $s \in \mathcal{S}$, we denote by $V(s)$ the value function. we consider the scenario where the value function can be approximated by a linear function such that $V(s) = \phi_s^\top x^*$, where $\phi_s \in \mathbb{R}^m$ is a feature and $x^* \in \mathbb{R}^m$ is an unknown parameter. To obtain the optimal x^*, we consider the following regularized Bellman minimization problem

$$\min_x \ F(x) = \frac{1}{2|\mathcal{S}|} \sum_{s \in \mathcal{S}} \left(\phi_s^\top x - \mathbb{E}_{s'}[r(s, s') + \gamma \phi_{s'}^\top x \mid s]\right)^2 + \frac{\lambda \|x\|^2}{2},$$

where $r(s, s')$ is the random reward incurred from transition s to s', $\gamma \in (0, 1)$ is the discount factor, λ is the coefficient for the l_2-regularizer, and the expectation is taken over all random transitions from s to s'.

In the federated learning setting, we consider a ring network of K agents. Here each agent k has access to its own data with heterogeneous random reward function r^k and can only communicate with

Figure 3: (a) Empirical averaged MSE$\|\bar{x}_t - x^*\|^2$ against total samples for DSBO $K = 5, 10, 20$ and DSGD $K = 5$. (b) Empirical averaged log-MSE $\log(\|\bar{x}_t - x^*\|^2)$ against log-iteration $\log(t)$ for DSBO $K = 5, 10, 20$. (c) 75% confidence region of log- total samples for achieving $\|\bar{x}_t - x^*\|^2 \leq \epsilon$, with varying network sizes $K = 5, 10, 20$. All figures are generated through 10 independent simulations.

its two neighbors $k + 1$ and $k - 1$. We denote by $y_s^*(x) = \phi_s^\top - \mathbb{E}_{s'}[\frac{1}{K}\sum_{k\in\mathcal{K}} r^k(s, s') + \gamma\phi_{s'}^\top x \mid s]$ where $r^k(s, s')$ is the random reward function for agent k, the above problem can be recast as a bilevel optimization problem

$$\min_{x\in\mathbb{R}^d} f(x, y^*(x)) = \frac{1}{2|\mathcal{S}|}\sum_{s\in\mathcal{S}} (y_s^*(x))^2 + \frac{\lambda\|x\|^2}{2}.$$

As pointed out by (Wang and Liu, 2016a), the above problem is λ-strongly convex.

In our experiments, we simulate an environment with state space $|\mathcal{S}| = 100$ and set the regularizer parameter $\lambda = 1$. We test the performance of Alg.1 over three setups with $K = 5, 10, 20$ and conduct 10 independent simulations for each K. We implement a baseline double-loop algorithm DSGD that first estimates $y_s^*(x_t)$ with t samples in iteration t and then optimizes the solution x_t. We defer the implementation details of the environment and above algorithms to Section E.2 of the supplement.

We first consider $K = 5$, run Alg. 1 for 10^4 iterations and compare its performance with DSGD. We plot the empirical averaged mean square error $\|\bar{x}_t - x^*\|^2$ against total samples generated by *all* agents in Figure 2. This empirical result suggests that Alg. 1 outperforms the DSGD. To investigate the convergence rate of DSBO, we compare the performance of DSBO over all three setups $K = 5, 10, 20$ and plot the trajectory of averaged log-error $\log(\|\bar{x}_t - x^*\|^2)$ averaged, with one straight line of slope -1 provided for comparison. We observe that over all four setups, the slopes of $\log(\|\bar{x}_t - x^*\|^2)$ are close to -1, matching our theoretical claim in Theorem 5.3 that Alg. 1 converges at the rate of $\mathcal{O}(1/t)$ for strongly convex objectives.

In the above experiment, we also note that Alg. 1 converges faster when using more agents. To further demonstrate the linear speedup effect, we compute the total generated samples for finding an ϵ-optimal solution $\|\bar{x}_t - x^*\|^2 \leq \epsilon$ and plot the 75% confidence region of log-sample against number of agents $K = 5, 10, 20$ in Figure 3. We observe that it takes a roughly same amount of samples to find a 10^{-6}-optimal solution despite different number of agents are involved. This suggests that the per-node sample complexity decreases linearly to K and validates the linear speedup claim in Theorem 5.3. We provide additional numerical results for other optimality level ϵ in Section E.2 of the supplementary material to further demonstrate the linear speedup effect.

7 Conclusion

In this paper, we propose a novel formulation of decentralized stochastic bilevel optimization. We develop a gossip-based stochastic approximation scheme to solve this problem in various settings. We show that our proposed algorithm finds a stationary point at a rate of $\mathcal{O}(\frac{1}{\sqrt{KT}})$ for nonconvex objectives, and converges to the optimal solution at a rate of $\mathcal{O}(\frac{1}{KT})$ for strongly convex objectives. Numerical experiments on hyper-parameter optimization and multi-agent federated MDP demonstrate the practical efficiency of our algorithm, exhibit the effect of speed-up in decentralized setting, and validate our theoretical claims. In our future work, we wish to develop algorithms that achieve lower iteration complexities and enjoy lower communication cost.

References

Sanjeev Arora, Simon Du, Sham Kakade, Yuping Luo, and Nikunj Saunshi. Provable representation learning for imitation learning via bi-level optimization. In *International Conference on Machine Learning*, pages 367–376. PMLR, 2020.

Luca Bertinetto, Joao F Henriques, Philip HS Torr, and Andrea Vedaldi. Meta-learning with differentiable closed-form solvers. *arXiv preprint arXiv:1805.08136*, 2018.

Jerome Bracken and James T McGill. Mathematical programs with optimization problems in the constraints. *Operations Research*, 21(1):37–44, 1973.

Chih-Chung Chang and Chih-Jen Lin. Libsvm: a library for support vector machines. *ACM transactions on intelligent systems and technology (TIST)*, 2(3):1–27, 2011. URL https://www.csie.ntu.edu.tw/~cjlin/libsvmtools/datasets/.

Tianyi Chen, Yuejiao Sun, and Wotao Yin. A single-timescale stochastic bilevel optimization method. *arXiv preprint arXiv:2102.04671*, 2021a.

Tianyi Chen, Yuejiao Sun, and Wotao Yin. Solving stochastic compositional optimization is nearly as easy as solving stochastic optimization. *IEEE Transactions on Signal Processing*, 69:4937–4948, 2021b.

Tianyi Chen, Yuejiao Sun, and Wotao Yin. Tighter analysis of alternating stochastic gradient method for stochastic nested problems. *arXiv preprint arXiv:2106.13781*, 2021c.

Nicolas Couellan and Wenjuan Wang. On the convergence of stochastic bi-level gradient methods. *Optimization*, 2016.

Evin J Cramer, John E Dennis, Jr, Paul D Frank, Robert Michael Lewis, and Gregory R Shubin. Problem formulation for multidisciplinary optimization. *SIAM Journal on Optimization*, 4(4): 754–776, 1994.

Ofer Dekel, Ran Gilad-Bachrach, Ohad Shamir, and Lin Xiao. Optimal distributed online prediction using mini-batches. *Journal of Machine Learning Research*, 13(1), 2012.

Hamid Reza Feyzmahdavian, Arda Aytekin, and Mikael Johansson. An asynchronous mini-batch algorithm for regularized stochastic optimization. *IEEE Transactions on Automatic Control*, 61 (12):3740–3754, 2016.

Luca Franceschi, Paolo Frasconi, Saverio Salzo, Riccardo Grazzi, and Massimiliano Pontil. Bilevel programming for hyperparameter optimization and meta-learning. In *International Conference on Machine Learning*, pages 1568–1577. PMLR, 2018.

Hongchang Gao and Heng Huang. Periodic stochastic gradient descent with momentum for decentralized training. *arXiv preprint arXiv:2008.10435*, 2020.

Jason Ge, Zhaoran Wang, Mengdi Wang, and Han Liu. Minimax-optimal privacy-preserving sparse pca in distributed systems. In *International Conference on Artificial Intelligence and Statistics*, pages 1589–1598. PMLR, 2018.

Saeed Ghadimi and Guanghui Lan. Accelerated gradient methods for nonconvex nonlinear and stochastic programming. *Mathematical Programming*, 156(1):59–99, 2016.

Saeed Ghadimi and Mengdi Wang. Approximation methods for bilevel programming. *arXiv preprint arXiv:1802.02246*, 2018.

Saeed Ghadimi, Andrzej Ruszczynski, and Mengdi Wang. A single timescale stochastic approximation method for nested stochastic optimization. *SIAM Journal on Optimization*, 30(1):960–979, 2020.

Zhishuai Guo, Quanqi Hu, Lijun Zhang, and Tianbao Yang. Randomized stochastic variance-reduced methods for multi-task stochastic bilevel optimization. *arXiv preprint arXiv:2105.02266*, 2021.

Pierre Hansen, Brigitte Jaumard, and Gilles Savard. New branch-and-bound rules for linear bilevel programming. *SIAM Journal on scientific and Statistical Computing*, 13(5):1194–1217, 1992.

Mingyi Hong, Hoi-To Wai, Zhaoran Wang, and Zhuoran Yang. A two-timescale framework for bilevel optimization: Complexity analysis and application to actor-critic. *arXiv preprint arXiv:2007.05170*, 2020.

Kaiyi Ji, Junjie Yang, and Yingbin Liang. Bilevel optimization: Convergence analysis and enhanced design. In *International Conference on Machine Learning*, pages 4882–4892. PMLR, 2021.

Prashant Khanduri, Siliang Zeng, Mingyi Hong, Hoi-To Wai, Zhaoran Wang, and Zhuoran Yang. A near-optimal algorithm for stochastic bilevel optimization via double-momentum. *Advances in Neural Information Processing Systems*, 34, 2021.

Anastasia Koloskova, Tao Lin, Sebastian U Stich, and Martin Jaggi. Decentralized deep learning with arbitrary communication compression. *arXiv preprint arXiv:1907.09356*, 2019.

Guanghui Lan and Yi Zhou. Random gradient extrapolation for distributed and stochastic optimization. *SIAM Journal on Optimization*, 28(4):2753–2782, 2018.

Guanghui Lan, Soomin Lee, and Yi Zhou. Communication-efficient algorithms for decentralized and stochastic optimization. *Mathematical Programming*, 180(1):237–284, 2020.

Xiangru Lian, Mengdi Wang, and Ji Liu. Finite-sum Composition Optimization via Variance Reduced Gradient Descent. In Aarti Singh and Jerry Zhu, editors, *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics*, volume 54 of *Proceedings of Machine Learning Research*, pages 1159–1167. PMLR, 20–22 Apr 2017a. URL https://proceedings.mlr.press/v54/lian17a.html.

Xiangru Lian, Ce Zhang, Huan Zhang, Cho-Jui Hsieh, Wei Zhang, and Ji Liu. Can decentralized algorithms outperform centralized algorithms? a case study for decentralized parallel stochastic gradient descent. *Advances in Neural Information Processing Systems*, 30, 2017b.

Xiangru Lian, Wei Zhang, Ce Zhang, and Ji Liu. Asynchronous decentralized parallel stochastic gradient descent. In *International Conference on Machine Learning*, pages 3043–3052. PMLR, 2018.

Jialin Liu, Yuantao Gu, and Mengdi Wang. Averaging random projection: A fast online solution for large-scale constrained stochastic optimization. In *2015 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 3586–3590, 2015. doi: 10.1109/ICASSP.2015.7178639.

Eli Livne. Integrated aeroservoelastic optimization: status and direction. *Journal of Aircraft*, 36(1):122–145, 1999.

Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial intelligence and statistics*, pages 1273–1282. PMLR, 2017.

Takayuki Okuno, Akiko Takeda, Akihiro Kawana, and Motokazu Watanabe. On lp-hyperparameter learning via bilevel nonsmooth optimization. *Journal of Machine Learning Research*, 22(245):1–47, 2021.

Shi Pu and Angelia Nedić. Distributed stochastic gradient tracking methods. *Mathematical Programming*, 187(1):409–457, 2021.

Alexander Rakhlin, Ohad Shamir, and Karthik Sridharan. Making gradient descent optimal for strongly convex stochastic optimization. *arXiv preprint arXiv:1109.5647*, 2011.

A. Ruszczyński and A. Shapiro. Optimization of convex risk functions. *Mathematics of Operations Research*, 31(3):433–452, 2006.

Andrzej Ruszczynski. A stochastic subgradient method for nonsmooth nonconvex multilevel composition optimization. *SIAM Journal on Control and Optimization*, 59(3):2301–2320, 2021.

Chenggen Shi, Jie Lu, and Guangquan Zhang. An extended kuhn–tucker approach for linear bilevel programming. *Applied Mathematics and Computation*, 162(1):51–63, 2005.

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. *Advances in neural information processing systems*, 30, 2017.

Jaroslaw Sobieszczanski-Sobieski and Raphael T Haftka. Multidisciplinary aerospace design optimization: survey of recent developments. *Structural optimization*, 14(1):1–23, 1997.

Murtaza Taj and Andrea Cavallaro. Distributed and decentralized multicamera tracking. *IEEE Signal Processing Magazine*, 28(3):46–58, 2011.

Davoud Ataee Tarzanagh, Mingchen Li, Christos Thrampoulidis, and Samet Oymak. Fednest: Federated bilevel, minimax, and compositional optimization. *arXiv preprint arXiv:2205.02215*, 2022.

Shenyinying Tu. *Two-Stage Decomposition Algorithms and Their Application to Optimal Power Flow Problems*. PhD thesis, Northwestern University, 2021.

Shenyinying Tu, Andreas Wächter, and Ermin Wei. A two-stage decomposition approach for ac optimal power flow. *IEEE Transactions on Power Systems*, 36(1):303–312, 2020.

Heinrich Von Stackelberg and Stackelberg Heinrich Von. *The theory of the market economy*. Oxford University Press, 1952.

M. Wang and J. Liu. Accelerating stochastic composition optimization. In *Advances In Neural Information Processing Systems*, pages 1714–1722, 2016a.

M. Wang and J. Liu. A stochastic compositional gradient method using markov samples. In *Proceedings of the 2016 Winter Simulation Conference*, pages 702–713. IEEE Press, 2016b.

M. Wang, E. X. Fang, and H. Liu. Stochastic compositional gradient descent: Algorithms for minimizing compositions of expected-value functions. *Mathematical Programming*, 161(1-2): 419–449, 2017a.

M. Wang, J. Liu, and E. X. Fang. Accelerating stochastic composition optimization. *The Journal of Machine Learning Research*, 18(1):3721–3743, 2017b.

Mengdi Wang and Dimitri P Bertsekas. Stochastic first-order methods with random constraint projection. *SIAM Journal on Optimization*, 26(1):681–717, 2016.

Xiaohan Wang, Mengdi Wang, and Yuantao Gu. A distributed tracking algorithm for reconstruction of graph signals. *IEEE Journal of Selected Topics in Signal Processing*, 9(4):728–740, 2015.

Ran Xin, Usman A Khan, and Soummya Kar. Variance-reduced decentralized stochastic optimization with accelerated convergence. *IEEE Transactions on Signal Processing*, 68:6255–6271, 2020.

Ran Xin, Usman A Khan, and Soummya Kar. An improved convergence analysis for decentralized online stochastic non-convex optimization. *IEEE Transactions on Signal Processing*, 69:1842–1858, 2021.

Junjie Yang, Kaiyi Ji, and Yingbin Liang. Provably faster algorithms for bilevel optimization. *Advances in Neural Information Processing Systems*, 34, 2021.

S. Yang, M. Wang, and E. X. Fang. Multilevel stochastic gradient methods for nested composition optimization. *SIAM Journal on Optimization*, 29(1):616–659, 2019.