A Controlled Study on Long Context Extension and Generalization in LLMs

Abstract

Broad textual understanding and in-context learning require language models that utilize full document contexts. Due to the implementation challenges associated with directly training long-context models, many methods have been proposed for extending models to handle long contexts. However, owing to differences in data and model classes, it has been challenging to compare these approaches, leading to uncertainty about how to evaluate long-context performance and whether it differs from standard evaluation. We implement a controlled protocol for extension methods with a standardized evaluation, utilizing consistent base models and extension data. Our study yields several insights into long-context behavior. First, our findings suggest that perplexity can serve as a helpful way to measure how well models perform on tasks involving longer contexts. Second, current approximate attention methods systematically underperform across long-context tasks. Finally, we confirm that exact fine-tuning based methods are generally effective within their extension range, whereas extrapolation remains challenging. All codebases, models, and checkpoints will be open-sourced, promoting transparency and facilitating further research in this critical area of AI development.

1 Introduction

The pretraining data scale of large language models (LLMs) has expanded greatly in recent years with open models trained up to 15T tokens (AI@Meta, 2024). Implementation challenges make it difficult to fully train models with longer context windows during pretraining (Liu et al., 2023a). Still, long-context windows are considered central, as they enable LLMs to perform tasks that require more extensive textual understanding, such as utilizing information from textbooks (Tanzer et al., 2024), summarizing novels (Kryściński et al., 2022), and engaging in many-shot learning (Bertsch et al., 2024; Li et al., 2023a).

As a trade-off, researchers have proposed *context extension*, where an LLM initially pretrained on standard sequences is adapted for significantly longer context lengths (Chen et al., 2023a; Peng et al., 2023; Han et al., 2023; bloc97, 2023). These methods differ in the type of attention used and in post-training adaptation techniques. They vary in complexity, training requirements, and qualitatively exhibit significantly different performance profiles.

Unfortunately, there is a relatively poor understanding of the quantitative rankings of these different methodologies. Owing to the perceived challenges of evaluation, several new metrics, such as long context perplexity (Chen et al., 2023a;b; Han et al., 2023; Hsieh et al., 2024), and retrieval accuracy (Mohtashami and Jaggi, 2023; gkamradt, 2023) have been introduced (Bai et al., 2023; An et al., 2023). However, the differences in long-context extension procedures make it hard to calibrate these metrics while controlling for other factors.

In this work, we implement a controlled protocol for context extension. The aim is to compare context extension while removing spurious factors that impact LLM ability.

Modeling: We standardize on the same base models for comparison. Different base models behave significantly differently, making it challenging to draw general conclusions. For instance, past work evaluates LM-Infinite (Han et al., 2023) on LongBench (Bai et al., 2023) using different base models (Xiao et al., 2024; Lu et al., 2024). We use five distinct open-weight base models with varying sizes and model families to validate the transferability of our findings from smaller to larger models.

Extensions: We implement various context extension methods within the same framework. We use a standardized recipe to eliminate potential gains from tailored hyperparameters. We also fix each method's post-training data, utilizing an identical and open-sourced training corpus (Fu et al., 2024; Chen et al., 2023b).

Metrics: We look at both intrinsic metrics, such as perplexity, and extrinsic properties, such as downstream task performance (Hsieh et al., 2024; gkamradt, 2023; Bai et al., 2023). We consider metrics within the extension length as well as an extrapolation to longer contexts.

Our study identifies several takeaways for future research. First, while there have been suggestions that we need new ways to measure performance, our findings show that perplexity does align with how well models perform to some extent on various tasks in our controlled studies. Though some newer attention methods don't show this pattern as clearly, we generally found that when models got better at predicting text, they also got better at most other tasks we tested them on.

Second, we find relatively poor results for approximate attention methods. While they can handle longer length contexts, there generally is a trade-off in terms of accuracy for most of our benchmarks. Exact frozen methods also tend to degrade model performance, showing high sensitivity to hyperparameters and often failing with a general training recipe.

Finally, continual fine-tuning with exact attention generally works well, particularly within the extended context length. Specifically, Dynamic NTK (emozilla, 2023) works best among these methods. Extrapolation to longer lengths remains a challenging problem. The aggregated results across various base models further support the broader applicability of our findings.

2 RELATED WORK

Long Context Methods   We divide extension methods into three broad classes: exact attention, approximate attention, and context compression. Exact attention methods augment the parameterization of attention. Position interpolation (PI) (Chen et al., 2023a), NTK-aware (bloc97, 2023), Dynamic NTK (emozilla, 2023), YaRN (Peng et al., 2023), and CLEX (Chen et al., 2024), all based on RoPE (Su et al., 2021), design position embeddings for length extension. These methods may be applied with fine-tuning or to frozen models. Other exact attention methods focus on training-time improvements, such as contrastive training (Tworkowski et al., 2023). Approximate attention methods uses structured attention approximations to minimize the computational cost of length growth. Chen et al. (2023b) uses LoRA (Hu et al., 2021) and a specialized local attention mechanism to reduce further the computational overhead of further fine-tuning with long context. Other approaches break the text into chunks and utilize a well-designed "chunk representation" to retrieve relevant chunks for attention (Mohtashami and Jaggi, 2023; Xiao et al., 2024; Lu et al., 2024). LM-Infinite and StreamLLM (Han et al., 2023; Xiao et al., 2023) retain only a few tokens from the beginning of the text and a local window to keep the attention window within the pretrained length. Xu et al. (2024) focuses on using retrievers to retrieve relevant blocks from long documents. Finally, context compression methods, which we do not explore in this work, reduce length extension to length compression via a summarization step (Jiang et al., 2023; Li et al., 2023b).

Long Context Evaluation Benchmarks   The Long Range Arena (LRA) (Tay et al., 2020) is an early efforts evaluating the proficiency of processing long contexts. Since then, a growing number of benchmarks have emerged, including LongBench (Bai et al., 2023), LEval (An et al., 2023), and LooGLE (Li et al., 2023c). These benchmarks are a mixture of diverse downstream tasks explicitly tailored to assess the capabilities of LLMs in understanding and generating lengthy contexts. Among these benchmarks, LongBench stands out for its inclusion of diverse sequences with varying lengths, distributions, patterns, languages, and domains, enabling a comprehensive, nuanced evaluation. In addition to evaluating LLMs' performance on downstream NLP tasks, there is another line of benchmarks that specifically focuses on assessing particular aspects of long context processing ability Liu et al. (2023b); Hsieh et al. (2024). For instance, Mohtashami and Jaggi (2023) propose the passkey retrieval task to challenge a language model to accurately locate and retrieve a simple passkey (a five-digit random number) in a long context sequence. Similarly, the Needle in a Haystack (gkamradt, 2023) test requires the model to accurately recite the information from a specified sentence(the "needle"). However, most existing works mainly focus on evaluating mainstream commercial models (e.g. GPT-4 and Claude), open-source base models, or just perform individual evaluations of a few long context methods. There is a lack of comprehensive, yet controlled evaluation on long-context extension techniques themselves.

3 CONTEXT EXTENSION METHODS

3.1 BACKGROUND: ATTENTION AND ROPE

The bottleneck in long context modeling in Transformers is attention. Attention is defined over C embeddings $\mathbf{X} = [\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_C]^\top \in \mathbb{R}^{C \times d}$ where d is the model dimension. Learned weight matrices $\mathbf{W}_v \in \mathbb{R}^{d \times d_k}$, $\mathbf{W}_q \in \mathbb{R}^{d \times d_k}$, and $\mathbf{W}_k \in \mathbb{R}^{d \times d_k}$ are used to transform these inputs where d_k is the projected hidden dimension. The attention mechanism itself computes the attention matrix and applies it to produce a weighted sum of the value vectors:

$$\text{Attention}(\mathbf{Q}, \mathbf{K}, \mathbf{V}) = \mathbf{A}\mathbf{V} = \text{softmax}\left(\frac{\mathbf{Q}\mathbf{K}^\top}{\sqrt{d_k}}\right)\mathbf{V}. \tag{1}$$

Basic attention was originally defined with: $\mathbf{Q} = \mathbf{X}\mathbf{W}_q, \mathbf{K} = \mathbf{X}\mathbf{W}_k, \mathbf{V} = \mathbf{X}\mathbf{W}_v$. However, this approach does not directly encode the relative position of keys and values.

Rotary Position Embeddings (RoPE) (Su et al., 2024) encode positional information by applying a phase rotation to each element of the embedding vectors. Formally, we define a transformation $\mathbf{f}$:

$$\mathbf{f}_\mathbf{W}(\mathbf{x}_i, \boldsymbol{\theta}) = \mathbf{R}(\boldsymbol{\theta}, i)\mathbf{W}^\top \mathbf{x}_i \tag{2}$$

Here $\mathbf{x}_i \in \mathbb{R}^{d_k}$ is an embedding for position i, $\mathbf{W}$ is a projection matrix, and $\boldsymbol{\theta} \in \mathbb{R}^{d_k/2}$ is a frequency basis. The function is defined based on the rotary position matrix:

$$\mathbf{R}(\boldsymbol{\theta}, i) = \begin{pmatrix} \cos i\theta_1 & -\sin i\theta_1 & \cdots & 0 & 0 \\ \sin i\theta_1 & \cos i\theta_1 & \cdots & 0 & 0 \\ \vdots & & & & \\ 0 & 0 & \cdots & \cos i\theta_{\frac{d_k}{2}} & -\sin i\theta_{\frac{d_k}{2}} \\ 0 & 0 & \cdots & \sin i\theta_{\frac{d_k}{2}} & \cos i\theta_{\frac{d_k}{2}} \end{pmatrix} \tag{3}$$

Due to the arrangement of frequencies, this matrix has the property that $\mathbf{R}(\boldsymbol{\theta}, n - m) = \mathbf{R}(\boldsymbol{\theta}, m)^\top \mathbf{R}(\boldsymbol{\theta}, n)$ by Ptolemy's identity. We redefine the query-key product between two positions m and n as,

$$\mathbf{q}_m^\top \mathbf{k}_n = \mathbf{f}_{\mathbf{W}_q}(\mathbf{x}_m, \boldsymbol{\theta})^\top \mathbf{f}_{\mathbf{W}_k}(\mathbf{x}_n, \boldsymbol{\theta}) \tag{4}$$

$$= \left(\mathbf{R}(\boldsymbol{\theta}, m)\mathbf{W}_q^\top \mathbf{x}_m\right)^\top \left(\mathbf{R}(\boldsymbol{\theta}, n)\mathbf{W}_k^\top \mathbf{x}_n\right) \tag{5}$$

$$= \mathbf{x}_m^\top \mathbf{W}_q \mathbf{R}(\boldsymbol{\theta}, n - m)\mathbf{W}_k^\top \mathbf{x}_n \tag{6}$$

In this way, the relative positional information $n - m$ is implicitly injected into the query and key product, thus the attention score.

The standard RoPE transformation, $f_\mathbf{W}(x_i, \boldsymbol{\theta})$, sets the components $\theta_j = b^{-\frac{2j}{d_k}}$ with base $b = 10000$.

3.2 ADJUSTING THE FREQUENCY OF ROPE FOR LONG CONTEXT EXTENSION

We consider four methods for performing length extension on RoPE embeddings: Position Interpolation (PI) (Chen et al., 2023a), NTK-RoPE (emozilla, 2023), YaRN (Peng et al., 2023) and CLEX (Chen et al., 2024). In this section our goal is to extend a method trained to extend position embeddings for context length C to length $C' >> C$. The methods in this section perform this extension by scaling the frequencies with the *base scaling vector* $\boldsymbol{\alpha} \in \mathbb{R}^{\frac{d_k}{2}}$:

$$\mathbf{f}_\mathbf{W}(x_i) = \mathbf{f}(x_i, \boldsymbol{\alpha} \odot \boldsymbol{\theta}). \tag{7}$$

Linear Position Interpolation (PI) decreases the frequencies of the basis functions so that more tokens fit within each period. PI is implemented by setting the components of the base scaling vector to

$$\alpha_j^{\text{PI}} = \frac{C}{C'} = \frac{1}{t}. \tag{8}$$

where $t = \frac{C'}{C}$ is target length ratio. PI has been integrated into many open-source models such as LLaMA2-7B-32K (Together.AI, 2023), Vicuna-7B-v1.5 (Chiang et al., 2023), and LongAlpaca (Chen et al., 2023b).

Neural Tangent Kernel Interpolation RoPE (NTK-RoPE) builds on linear position interpolation by introducing a per-dimension scaling factor. Inspired by findings from the NTK literature that show that high-frequency features are difficult for MLPs to learn, NTK-RoPE preserves high-frequency features while extending the period of low-frequency features. This is accomplished via a dimension-dependent base scaling vector $\boldsymbol{\alpha}$:

$$\alpha_j^{\text{NTK-RoPE}} = \kappa^{-\frac{2j}{d_k}}, \tag{9}$$

where $\kappa = (t)^{\frac{d_k}{d_k - 2}}$ so that the lowest frequency is scaled to match PI and the highest frequency remains the same as in RoPE.

An extension to this approach, Dynamic NTK-RoPE suggests that instead of fixing scaling based on a set ratio s for all examples during inference, the formula should adapt to the current context length for a specific example. We followed the set up of Fu et al. (2024) for Dynamic NTK-RoPE. More details can be found in the Appendix 7.5.

YaRN, another RoPE extension method, uses "NTK-by-parts" interpolation strategies across different dimensions of the embedding space and introduces a temperature factor to adjust the attention distribution for long inputs.

$$\alpha_j^{\text{YaRN}} = ((1 - \gamma_j)\frac{1}{t} + \gamma_j)/\sqrt{T} \tag{10}$$

We use a ramp vector $\boldsymbol{\gamma}$ to determine the interpolation between the $\frac{1}{t}$ and the original frequency base. The interpolation gating is set based on the frequency for the dimension j. More details about this ramp function can be found in the Appendix 7.3.

Other methods such as **CLEX** Chen et al. (2024) models the scaling vectors as a dynamical system, with the goal of learning target-length dependent scaling vectors.

3.3 ADJUSTING ATTENTION FOR CONTEXT EXTENSION

An alternative approach is to modify the attention function itself. Approaches to handling longer contexts fall into two main categories: approximate attention and attention modification. In approximate attention, instead of computing the full attention matrix, methods select a subset of positions to attend to. In attention modification, the approach incorporates additional information through retrieval or other mechanisms. We examine four established methods across these categories: sparse attention, sliding window attention, and retrieval attention.

LongLoRA (Chen et al., 2023b) avoids computing attention ranges over C' by only computing the block-diagonl part of attention. Formally, given a sequence length of C', LongLoRA divides it into M blocks of size B, resulting in a sparse attention matrix $\mathbf{A} \in \mathbb{R}^{C' \times C'}$ with a block-diagonal structure:

$$\mathbf{A} = \begin{bmatrix} \mathbf{A}_1 & \mathbf{0} & \cdots & \mathbf{0} \\ \mathbf{0} & \mathbf{A}_2 & \cdots & \mathbf{0} \\ \vdots & \vdots & \ddots & \vdots \\ \mathbf{0} & \mathbf{0} & \cdots & \mathbf{A}_M \end{bmatrix} \tag{11}$$

where $\mathbf{A}_i \in \mathbb{R}^{B \times B}$ is the attention matrix for the i-th block. In addition, they shift the blocks for half of the heads enabling the information flow between groups via shifting. Notably, while they employ local attention during the fine-tuning phase, full attention is still adopted during the inference stage.

Landmark Attention (Mohtashami and Jaggi, 2023) addresses the challenge of attending over long sequences by breaking the input sequence into chunks and using trainable "landmark" tokens to summarize these chunks. The attention process is carried out in two stages. Given a sequence of C' embeddings, divided into M chunks, each of length B, the first step is to compute global attention between the query vectors $\mathbf{Q} \in \mathbb{R}^{C' \times d_k}$ (corresponding to all input embedding) and the

landmark vectors $\mathbf{L} \in \mathbb{R}^{M \times d_k}$ (which represent the chunks). From this global attention, a set of n-most attended-to chunks is selected for further processing. Next, a local attention mechanism is applied within each of the selected chunks. For the n-th selected chunk, the key matrix for the chunk is denoted as $\mathbf{K}_n \in \mathbb{R}^{B \times d_k}$ and $\mathbf{Q}_n \in \mathbb{R}^{B \times d_k}$. The attention matrices are then computed as follows:

$$\mathbf{A}^1 = \text{softmax}\left(\frac{\mathbf{Q}\mathbf{L}^T}{\sqrt{d_k}}\right) \in \mathbb{R}^{C' \times M}, \mathbf{A}^{2,n} = \text{softmax}\left(\frac{\mathbf{Q}_n\mathbf{K}_n^T}{\sqrt{d_k}}\right) \in \mathbb{R}^{B \times B}, \tag{12}$$

The final attention for each embedding is a combination of these two attention. This method efficiently scales attention mechanisms for long sequences by focusing on landmark tokens that summarize large parts of the sequence, followed by local attention within the relevant chunks.

LM-Infinite (Han et al., 2023) (a.k.a., Sliding Window Attention) maintains a sliding local window of size M along with a fixed global memory of G positions at the starting point of the given embedding. Given C' embeddings, attention is computed over the M embeddings in its local window and G embeddings in global memory. LM-Infinite replaces relative positional information $n - m$ with $\min(n - m, C)$ while computing the query and key product in Eq 4. Altogether, LM-Infinite reduces the complexity from $\mathcal{O}((C')^2)$ to $\mathcal{O}(C'(M + G))$ without the need to scale positional encoding.

Self-Extend (Jin et al., 2024) maps the unseen positions in extended context length C' to positions within the pretraining context length C to avoid training. For each embeddings, Self-Extend chooses closest M embeddings and any embeddings beyond are divided into multiple groups. Each group contains N embeddings. When performing query-key product between two positions m and n in Equation 4, the relative positional information $n - m$ is replaced by r which is computed by scaling $n - m$ w.r.t M and N:

$$r = \begin{cases} n - m, & n - m \leq M, \\ M + \left\lfloor \frac{n-m}{N} \right\rfloor - \left\lfloor \frac{M}{N} \right\rfloor, & n - m > M. \end{cases} \tag{13}$$

where $\lfloor \cdot \rfloor$ denotes the floor division. The maximum extended context length C' is $(C - M) \cdot N + M$.

4 LONG-CONTEXT EXTENSION PROTOCOL

Base Model All models start from an identical base checkpoint. We choose to use five different base models LLaMA2-7B(Touvron et al., 2023), Phi-2(Javaheripi et al., 2023), LLaMA3-7B, LLaMA3-13B, LLaMA3-70B Dubey et al. (2024)as base models for context extension experiments, to verify whether the trends and analyses we observed are consistent across different base models, thereby avoiding potential over-generalization. **Note that in our main findings, we only report results with LLaMA2-7B base model** to maintain conciseness and avoid redundancy as we find most of general findings from LLaMA2-7B can be transferred to all other models. Results from other models are provided in Appendix 7.4.

Fine-Tuning We sample 1B tokens from a long-context data mixture following Fu et al. (2024). The data details are reported in Appendix 7.6. We focus on extending the context window from 4k to 32k since most benchmarks require contexts under 32k. We maintain a fixed training recipe to ensure consistency across all models (Chen et al., 2023b). We follow existing practices by keeping an exponential moving average (EMA) of model weights with a constant decay, a linear learning rate warm-up and zero weight decay. Most training hyperparameters are based on (Fu et al., 2024), with the learning rate set to 2×10^{-5}. Our experiments are done on 8 NVIDIA A100 GPUs.

For LongLora, we fine-tune the weights of the LoRA adapter with trainable embedding and normalization, then merge these trainable weights with the LLaMA2 base model for evaluation. For Landmark Attention, the training context length is set to 512, with a block size of 64. For CLEX, we set the max scale factor to 32 and use the SiLU activation function.

We reuse the original scale factor to maintain consistency for NTK, YaRN, and Position Interpolation methods. However, this base factor significantly degrades continual fine-tuned models, particularly causing performance deterioration in shorter sequences. Therefore, we conduct a grid search to determine a better scale factor for different input lengths for NTK-RoPE method. Based on our findings, we follow and improve upon Fu et al. (2024) to set the scale factor for NTK-RoPE method. The scale factor and its relationship with perplexity are reported in the Appendix 7.8. Please refer to the Appendix 7.5 for detailed hyperparameter setups.

Table 1: Overview of results across different extension types.

Attention Mechanisms		Model	PPL	Needle	Mshots	LongB	RULER
	Frozen	NTK-F	14.52	18.8	64.5	25.54	0.72
Exact Attention	Fine-Tuned	PI	5.95	42.1	**75.5**	33.48	57.66
		YaRN	5.93	46.7	75.0	33.45	36.95
		CLEX	5.82	71.1	74.0	33.48	52.17
		NTK-32K	**5.79**	**83.7**	71.0	**35.32**	59.42
		NTK-64K	5.93	69.1	73.0	34.30	**60.03**
Modified. Attention	Modified. Attention	LM-Infinite	6.71	23.9	61.5	25.84	12.34
		Self-Extend	6.11	25.8	72.0	33.62	29.50
	Approxi. Attention	LongLora	9.89	20.3	55.5	23.30	3.53
		Landmark	8.13	50.9	50.0	28.19	13.56

Metrics We consider two sets of intrinsic metrics. The first is based on *perplexity*. We use the book corpus PG19 (Rae et al., 2019) and the Proof-pile dataset (Azerbayev et al., 2023) to evaluate the long sequence language modeling performances. Following Press et al. (2022), all perplexity evaluations are calculated using a sliding window with a window size of 256.

The second is based on *retrieval*. We focus on the needle in the haystack task (gkamradt, 2023)(NIAH). NIAH involves identifying a specific, relevant piece of information (the "needle") within a large set of irrelevant data (the "haystack"). This task is commonly used to test the precision and recall capabilities of LLMs in scenarios where the relevant data is sparse and surrounded by a significant amount of noise. Additionally, we evaluate with RULER (Hsieh et al., 2024). RULER enhances the standard NIAH test by incorporating variations with different types and quantities of needles with new task categories, such as multi-hop tracing and aggregation.

For extrinsic metrics, we consider a collection of tasks. LongBench (Bai et al., 2023) is a family of bilingual, multitask evaluations for long-context understanding widely used in measuring the long-context abilities of LLMs (Jin et al., 2024; Xiao et al., 2024; Lu et al., 2024). LongBench includes single-document question answering, multi-document QA, summarization, few-shot learning, and code completion. We follow Bai et al. (2023) to evaluate the models on 32k context window sizes by truncating the prompt from the middle when the task length exceeds a designated context window size. We also consider the ManyShots tasks, where the long-context model will be given several examples as prompts. We use the Trec News (Li and Roth, 2002) dataset for this task.

5 EXPERIMENTAL RESULTS AND ANALYSIS

5.1 RESULT OVERVIEW

Table 1 overviews the results across both types of evaluation. The main result demonstrate that fine-tuned exact attention methods for long contexts, such as NTK-32K and YARN, consistently outperform approximate attention methods by a significant margin. This suggests that trading accuracy for speed in approximate attention methods can result in a loss of important reasoning capabilities, particularly for retrieval-based tasks. The performance disparity highlights the importance of exact attention in maintaining high accuracy over extended contexts, emphasizing the need for careful consideration of attention type in model design for long-context tasks. We now consider each type of result in more detail.

5.2 INTRINSIC TASKS

Perplexity Table 2 shows perplexity scores across length. We see that continuous fine-tuning methods like PI, YaRN, and LongLora effectively keep low perplexity scores within the pre-training context length. However, when the context length exceeds perplexity scores escalate once the context surpasses the pre-trained window. Only NTK and CLEX can generalize to unseen sequence length in both pretraining and continual finetuning. Additionally, we find that exact attention maintains better perplexity than LoRA, which may reduce LongLora's ability. We also note that results on both PG19 and Proof-file gave nearly consistent conclusions.

Table 2: Perplexity of different methods on PG 19 and Proof-file. NTK-32K and NTK-64K refer to NTK-Dynamic, which requires finetuning. Len refers to the longest-length examples seen at training or fine-tuning. Ex refers to the exact attention. All results are produced by our experiments.

Model Details			Eval Length					
Len	Ex	Methods	2k	4k	8k	16k	32k	64k
PG19								
Frozen 4k	✓	LLaMA2	**6.61**	**6.30**	-	-	-	-
4k		LM-Infinite	**6.61**	**6.30**	6.25	6.45	6.71	8.49
4k	✓	NTK-Frozen	**6.61**	**6.30**	6.82	7.94	14.52	-
4k		Self-Extend	**6.61**	6.32	6.15	6.07	6.11	7.15
32k	✓	PI	6.88	6.52	6.27	6.08	5.95	-
32k	✓	NTK-32K	6.63	6.32	**6.09**	**5.92**	**5.79**	**5.76**
Finetuned 32k	✓	YaRN	6.70	6.39	6.16	6.01	5.93	-
32k	✓	CLEX	6.85	6.62	6.14	5.93	5.82	5.79
32k		LongLora	12.80	11.52	10.70	10.18	9.89	-
32k		Landmark	8.15	8.14	8.14	8.11	8.13	8.15
64k	✓	NTK-64K	6.83	6.49	6.25	6.07	5.93	5.85
Proof-file								
Frozen 4k	✓	LLaMA2	3.34	3.04	-	-	-	-
4k		LM-Infinite	3.34	3.04	2.94	3.02	3.11	3.12
4k	✓	NTK-Frozen	3.34	3.04	2.91	3.09	4.06	12.65
4k		Self-Extend	3.35	3.06	2.88	2.78	2.75	2.90
32k	✓	PI	3.34	3.03	2.83	2.68	2.58	-
32k	✓	NTK-32K	**3.27**	**2.98**	**2.78**	**2.64**	**2.54**	**2.48**
Finetuned 32k	✓	YaRN	3.29	3.00	2.81	2.68	2.59	106.38
32k	✓	CLEX	3.37	3.10	2.80	2.65	2.55	**2.48**
32k		LongLora	5.97	5.10	4.58	4.27	4.13	-
32k		Landmark	4.51	4.50	4.48	4.49	4.49	4.49
64k	✓	NTK-64K	3.33	3.03	2.83	2.69	2.58	2.51

Table 3: RULER evaluation at lengths from 4k to 64k. Score is computed by averaging the accuracy of 13 tasks. Train Len refers to the longest-length examples seen at continuous finetuning.

	Models	Train Len	4k	8k	16k	32k	64k	128k
Frozen	LLaMA2	4k	80.94	-	-	-	-	-
	LM-Infinite	4k	81.05	30.01	18.02	12.34	10.56	-
	NTK-Frozen	4k	81.14	44.45	14.79	0.72	0.91	-
	Self-Extend	4k	65.03	50.73	44.02	29.50	9.34	-
Finetuned	PI	32k	84.56	76.04	69.64	57.66	0.00	-
	NTK-32K	32k	86.58	**77.75**	**70.01**	59.42	46.26	29.91
	YaRN	32k	79.12	65.60	54.21	36.95	0.00	-
	CLEX	32k	50.18	63.93	64.35	52.17	30.61	-
	LongLora	32k	10.58	6.37	3.67	3.53	0.00	-
	Landmark	32k	22.37	17.52	16.31	13.56	14.15	-
	NTK-64K	64k	**86.60**	76.34	69.56	**60.03**	**49.31**	**40.09**

Needle-in-the-haystack NIAH results are shown in Figure 1. Continuous finetuning approaches such as NTK, PI, and YaRN have successfully retrieved the "needle" within the pretraining length. Yet, only the NTK and CLEX method can retrieve the needle beyond the pretraining length, aligning with the perplexity results. The performance of the Exact Attention Method generally surpasses that of the Approximate Attention Methods. LM-Infinite and Landmark Excel are only within the local

Figure 1: Needle in a Haystack evaluation. Green squares indicates a high retrieval success rate, the white dashed line denotes the longest length examples seen at training or finetuning, and the Y-axis represents the distance to the retrieved target.

window, and they struggle to retrieve the intermediate text accurately. Regarding the Dynamic NTK method, NTK-F exhibits weak generalization when not trained. When trained on the same amount of data(1B), NTK-32K outperforms NTK-64K. When trained on 2B tokens, NTK-64K demonstrated a significant performance improvement, details are in Appendix 7.7.

RULER We test all models on 13 tasks from the four RULER (Hsieh et al., 2024). Each model is evaluated with 500 examples for lengths of 4k, 8k, 16k, 32k, 64k and 128k. Results are compared with the Llama2-7B baseline in Table 3. We observed a similar trend as in the NIHK task, NTK has the minimal performance degration w.r.t the increase of length beyond pretrained or finetuned length. NTK-32k maintained relatively good performance compared to other methods finetuned with a length cap of 32k. Performance of models on different length and breakdown by 13 subtasks can be found in Appendix 7.11.

5.3 EXTRINSIC TASKS

LongBench The evaluation results of most methods on LongBench are presented in Table 4, and results on all methods are presented in Appendix 7.10. Both LM-Infinite and Landmark Attention exhibit significant performance degradation compared to the base model. In contrast, the NTK, PI, and YaRN methods have successfully maintained their performance at 32k, demonstrating comparable results among these methods. This suggests that PI and YaRN perform similarly in downstream tasks, while the NTK family of models remains stable.

Notably, the LongLoRA method, which utilizes LoRA, also experiences a performance decline relative to the base checkpoint, LLaMA2. We argue that this may be due to the sensitivity of the training procedures for LongLoRA, and we acknowledge this in our limitation discussion section.

Furthermore, the overall performance on LongBench has not shown significant improvement over LLaMA2.We hypothesize that this is due to the average length of LongBench test data (approximately 7.5k) being considerably shorter than the 32k context window of the long-context methods.

Table 4: LongBench results. N-32 and N-64 refer to NTK finetuned on 32K and 64K context lengths respectively. SE refers to Self-Extend. YN refers to YaRN. CX refers to CLEX. LLR refers to LongLora. Len refers to average length of the datasets. Train Len refers to the longest length examples seen at training or finetuning. Eval Len refers to the maximum length of the input prompt. ✓refers to whether the method is exact attention.

| | | | Frozen | | | | | Finetuned | | | | |
	Len	Base ✓	N-F ✓	SE	PI ✓	N-32 ✓	YN ✓	CX	LLR	Land ✓	N-64
Train Len		4k	4k	4K	32k	32k	32k	32k	32k	32k	64k
Eval Len		4k	32k	32K	32k	32k	32k	32k	32k	32k	32k
NQA	18k	21.09	3.88	23.49	23.02	23.73	19.82	24.19	12.07	12.47	**24.31**
QAP	4k	26.94	26.79	28.75	25.85	**27.50**	26.98	23.36	20.15	19.06	24.97
MQA	5k	32.42	29.82	32.66	35.10	38.22	37.11	40.83	24.50	21.86	**40.60**
HQA	9k	31.23	32.10	37.63	36.98	**41.56**	38.60	35.59	27.41	33.66	41.47
WQA	5k	25.75	22.34	30.70	29.38	**31.58**	30.63	28.24	21.46	24.94	28.62
MSQ	11k	10.55	8.84	15.73	16.80	17.41	**22.08**	17.12	11.46	11.41	18.24
GR	9k	17.32	17.87	13.15	25.61	**28.27**	20.98	24.68	24.05	17.20	24.37
QSM	11k	21.28	15.35	20.20	21.19	21.52	20.66	21.55	17.66	18.83	**21.65**
MWS	2k	3.44	9.30	1.50	10.55	22.13	8.91	16.96	21.19	19.43	**25.02**
TRE	5k	66.00	67.50	69.00	**71.00**	69.00	69.00	67.50	50.00	49.00	69.00
TQA	8k	87.89	18.69	88.44	88.55	88.86	**89.63**	89.36	12.28	74.75	88.65
SMS	6k	41.70	32.46	43.76	**43.35**	42.21	44.25	43.02	13.45	40.38	41.59
PSC	11k	2.10	2.67	0.00	1.50	2.68	1.05	2.50	**4.57**	0.64	2.09
PSR	9k	**9.00**	3.77	4.50	4.50	4.62	3.79	8.50	3.50	2.50	6.50
LCC	1k	**68.22**	63.64	68.47	55.05	56.78	54.06	49.45	57.12	56.70	52.04
REP	4k	**61.73**	53.69	59.99	47.26	49.09	47.60	42.84	51.92	48.23	39.68
Avg.	7k	32.92	25.54	33.62	33.48	**35.32**	33.45	33.48	23.30	28.19	34.30

Figure 2: Perplexity and averaged downstream task accuracy for NIAH, LongBench and RULER.

6 ADDITIONAL ANALYSIS

Perplexity and Downstream Tasks While prior work (Sun et al., 2021; An et al., 2023) suggests that perplexity may not reliably predict long-range task performance, our analysis in Figure 2 reveals to some extent perplexity might be reliable. We observe a general correlation between perplexity and model performance across tasks. However, we also observed that approximate attention methods, including LongLora and Landmark on RULER, show minor deviations but maintain a roughly linear relationship. We hypothesize that this apparent discrepancy with previous findings may stem from their less controlled experimental conditions and noisier datasets.

Context extension hurts in the short term and gains in the long term While context extension seems to improve perplexity, in Table 4, we do not notice a significant gain in performance. We hypothesize that while this dataset contains long tasks, the average length is much shorter than 32K. These methods seem to improve the ability to model language over the long term but hurt in the short term. To understand this better we compute the averaged negative likelihood of each position of

Figure 3: (Left) Performance of different context extension methods across model sizes. (Right) Average negative log-likelihood of different models by context position.

YaRN, LLaMa2, and NTK-32K per position (with LLaMa2 seeing just tokens every 4k chunks) in Figure 3(Left). Additionally, we evaluated these methods on short tasks from standard benchmarks and found that extension methods exhibited a slight decrease in performance on short-text tasks compared to the base model, as shown in Appendix Table 11. This aligns with our observations in Figure 3(Right), which analyzes the average negative log-likelihood across different context positions.

General Discoveries across Model Sizes   Our analysis across LLaMA3-7b, 13b, and 70b base models reveals several key patterns. Non-extension methods like NTK-Frozen and Self-Extend demonstrate improved performance on intrinsic tasks such as Needle-in-a-Haystack at larger scales, while maintaining consistent performance rankings across model sizes. Although continual fine-tuning methods still outperform non-extension approaches within their extension range, the correlation between perplexity and downstream task performance remains robust. These findings, shown in Figure 3(Left), validate our conclusions about long-context capabilities across model scales and provide deeper insights into the relationship between model scaling and context extension.

NTK Generalizes Beyond 32k   In Figure 1, we observe that NTK-32K successfully generalizes to unseen sequence lengths beyond 32k in both Needle-in-the-Haystack and RULER tasks, performing on par with NTK-64K. In contrast, NTK-F demonstrates generalization up to 8k but fails to extend further. This suggests that while NTK methods may possess the capability to generalize to longer unseen sequences, their effectiveness is contingent upon conditions such as continual fine-tuning.

We find that up until 4K they all improve as expected with LLaMa2 having the best NLL. After 4K they all fluctuate in average, but we see a clear separation with Yarn and NTK taking into account the long context. At extremely long context NTK remains a strong model whereas Yarn becomes reverts to a similar performance as LLaMa2.

7   LIMITATIONS AND CONCLUSION

Our study has several limitations. The experiments are confined to context extensions up to 32k tokens, and behavior patterns may vary at longer extensions. Additionally, our standardized training protocol with fixed hyperparameters might disproportionately affect certain models' performance. Furthermore, our perplexity findings may be specific to our experimental settings and may not generalize to models beyond our test scope.

In this paper, we use a standardized approach to assess the performance of various long-context methods in LLMs. Our study underscores the role of perplexity as a crucial, performance indicator at length and highlights the trade-offs inherent in different attention mechanisms. We analyze the strengths and weaknesses of various approaches, providing valuable insights for future research. All our resources, including codebases, models, and checkpoints, will be open-sourced upon acceptance, fostering future advancements in this pivotal area of AI research.

REPRODUCIBILITY STATEMENT

To ensure the reproducibility of our work on evaluating context extension of LLMs, we have taken the following steps: (1) We provide detailed descriptions of our model architectures, training procedures, and hyperparameters in the methodology section of our paper; (2) Our code, including scripts for data preprocessing, model training, and evaluation, will be available in a public GitHub repository; (3) We have used standard, publicly available datasets for both training and evaluation, which are clearly referenced in our paper; (4) For context extension method, we provide a step-by-step explanation in the main text; (5) Finetuned model checkpoints will be available for download in the huggingface hub. By following the instructions in the future repository and using the provided resources, other researchers should be able to replicate our experiments and verify our results.

ETHICS STATEMENT

We acknowledge that we have read the Code of Ethics and adhere to the Code of Ethics.

REFERENCES

AI@Meta. Llama 3 model card. 2024. URL `https://github.com/meta-llama/llama3/blob/main/MODEL_CARD.md`.

Hao Liu, Matei Zaharia, and Pieter Abbeel. Ring attention with blockwise transformers for near-infinite context. In *NeurIPS 2023 Foundation Models for Decision Making Workshop*, 2023a. URL `https://openreview.net/forum?id=fXugVDtCQO`.

Garrett Tanzer, Mirac Suzgun, Eline Visser, Dan Jurafsky, and Luke Melas-Kyriazi. A benchmark for learning to translate a new language from one grammar book. In *The Twelfth International Conference on Learning Representations*, 2024. URL `https://openreview.net/forum?id=tbVWug9f2h`.

Wojciech Kryściński, Nazneen Rajani, Divyansh Agarwal, Caiming Xiong, and Dragomir Radev. Booksum: A collection of datasets for long-form narrative summarization. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 6536–6558, 2022.

Amanda Bertsch, Maor Ivgi, Uri Alon, Jonathan Berant, Matthew R Gormley, and Graham Neubig. In-context learning with long-context models: An in-depth exploration. *arXiv preprint arXiv:2405.00200*, 2024.

Mukai Li, Shansan Gong, Jiangtao Feng, Yiheng Xu, Jun Zhang, Zhiyong Wu, and Lingpeng Kong. In-context learning with many demonstration examples. *arXiv preprint arXiv:2302.04931*, 2023a.

Shouyuan Chen, Sherman Wong, Liangjian Chen, and Yuandong Tian. Extending context window of large language models via positional interpolation, 2023a.

Bowen Peng, Jeffrey Quesnelle, Honglu Fan, and Enrico Shippole. Yarn: Efficient context window extension of large language models, 2023.

Chi Han, Qifan Wang, Wenhan Xiong, Yu Chen, Heng Ji, and Sinong Wang. Lm-infinite: Simple on-the-fly length generalization for large language models, 2023.

bloc97. NTK-Aware Scaled RoPE allows LLaMA models to have extended (8k+) context size without any fine-tuning and minimal perplexity degradation, 2023. URL `https://www.reddit.com/r/LocalLLaMA/comments/14lz7j5/ntkaware_scaled_rope_allows_llama_models_to_have/`.

Yukang Chen, Shengju Qian, Haotian Tang, Xin Lai, Zhijian Liu, Song Han, and Jiaya Jia. Longlora: Efficient fine-tuning of long-context large language models, 2023b.

Cheng-Ping Hsieh, Simeng Sun, Samuel Kriman, Shantanu Acharya, Dima Rekesh, Fei Jia, Yang Zhang, and Boris Ginsburg. Ruler: What's the real context size of your long-context language models?, 2024.

Amirkeivan Mohtashami and Martin Jaggi. Landmark attention: Random-access infinite context length for transformers, 2023.

gkamradt. Needle in a haystack - pressure testing llms, 2023. URL https://github.com/gkamradt/LLMTest_NeedleInAHaystack.

Yushi Bai, Xin Lv, Jiajie Zhang, Hongchang Lyu, Jiankai Tang, Zhidian Huang, Zhengxiao Du, Xiao Liu, Aohan Zeng, Lei Hou, Yuxiao Dong, Jie Tang, and Juanzi Li. Longbench: A bilingual, multitask benchmark for long context understanding, 2023.

Chenxin An, Shansan Gong, Ming Zhong, Xingjian Zhao, Mukai Li, Jun Zhang, Lingpeng Kong, and Xipeng Qiu. L-eval: Instituting standardized evaluation for long context language models, 2023.

Chaojun Xiao, Pengle Zhang, Xu Han, Guangxuan Xiao, Yankai Lin, Zhengyan Zhang, Zhiyuan Liu, Song Han, and Maosong Sun. Infllm: Unveiling the intrinsic capacity of llms for understanding extremely long sequences with training-free memory. *arXiv preprint arXiv:2402.04617*, 2024.

Yi Lu, Xin Zhou, Wei He, Jun Zhao, Tao Ji, Tao Gui, Qi Zhang, and Xuanjing Huang. Longheads: Multi-head attention is secretly a long context processor. *arXiv preprint arXiv:2402.10685*, 2024.

Yao Fu, Rameswar Panda, Xinyao Niu, Xiang Yue, Hannaneh Hajishirzi, Yoon Kim, and Hao Peng. Data engineering for scaling language models to 128k context, 2024.

emozilla. Dynamically Scaled RoPE further increases performance of long context LLaMA with zero fine-tuning, 2023. URL https://www.reddit.com/r/LocalLLaMA/comments/14mrgpr/dynamically_scaled_rope_further_increases/.

Guanzheng Chen, Xin Li, Zaiqiao Meng, Shangsong Liang, and Lidong Bing. Clex: Continuous length extrapolation for large language models, 2024. URL https://arxiv.org/abs/2310.16450.

Jianlin Su, Yu Lu, Shengfeng Pan, Bo Wen, and Yunfeng Liu. Roformer: Enhanced transformer with rotary position embedding. *Cornell University - arXiv,Cornell University - arXiv*, Apr 2021.

Szymon Tworkowski, Konrad Staniszewski, Mikołaj Pacek, Yuhuai Wu, Henryk Michalewski, and Piotr Miłoś. Focused transformer: Contrastive training for context scaling, 2023.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. *CoRR*, abs/2106.09685, 2021. URL https://arxiv.org/abs/2106.09685.

Guangxuan Xiao, Yuandong Tian, Beidi Chen, Song Han, and Mike Lewis. Efficient streaming language models with attention sinks, 2023.

Peng Xu, Wei Ping, Xianchao Wu, Lawrence McAfee, Chen Zhu, Zihan Liu, Sandeep Subramanian, Evelina Bakhturina, Mohammad Shoeybi, and Bryan Catanzaro. Retrieval meets long context large language models, 2024.

Huiqiang Jiang, Qianhui Wu, Xufang Luo, Dongsheng Li, Chin-Yew Lin, Yuqing Yang, and Lili Qiu. Longllmlingua: Accelerating and enhancing llms in long context scenarios via prompt compression, 2023.

Yucheng Li, Bo Dong, Chenghua Lin, and Frank Guerin. Compressing context to enhance inference efficiency of large language models, 2023b.

Yi Tay, Mostafa Dehghani, Samira Abnar, Yikang Shen, Dara Bahri, Philip Pham, Jinfeng Rao, Liu Yang, Sebastian Ruder, and Donald Metzler. Long range arena: A benchmark for efficient transformers, 2020.

Jiaqi Li, Mengmeng Wang, Zilong Zheng, and Muhan Zhang. Loogle: Can long-context language models understand long contexts?, 2023c.

Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. Lost in the middle: How language models use long contexts, 2023b.

Jianlin Su, Murtadha Ahmed, Yu Lu, Shengfeng Pan, Wen Bo, and Yunfeng Liu. Roformer: Enhanced transformer with rotary position embedding. *Neurocomputing*, 568:127063, 2024.

Together.AI. Llama-2-7b-32k-instruct — and fine-tuning for llama-2 models with together api, 2023. URL https://www.together.ai/blog/llama-2-7b-32k-instruct.

Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E. Gonzalez, Ion Stoica, and Eric P. Xing. Vicuna: An open-source chatbot impressing gpt-4 with 90%* chatgpt quality, March 2023. URL https://lmsys.org/blog/2023-03-30-vicuna/.

Hongye Jin, Xiaotian Han, Jingfeng Yang, Zhimeng Jiang, Zirui Liu, Chia-Yuan Chang, Huiyuan Chen, and Xia Hu. Llm maybe longlm: Self-extend llm context window without tuning, 2024.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. Llama 2: Open foundation and fine-tuned chat models, 2023.

Mojan Javaheripi, Sébastien Bubeck, Marah Abdin, Jyoti Aneja, Sebastien Bubeck, Caio César Teodoro Mendes, Weizhu Chen, Allie Del Giorno, Ronen Eldan, Sivakanth Gopi, Suriya Gunasekar, Mojan Javaheripi, Piero Kauffmann, Yin Tat Lee, Yuanzhi Li, Anh Nguyen, Gustavo de Rosa, Olli Saarikivi, Adil Salim, Shital Shah, Michael Santacroce, Harkirat Singh Behl, Adam Taumann Kalai, Xin Wang, Rachel Ward, Philipp Witte, Cyril Zhang, and Yi Zhang. Phi-2: The surprising power of small language models, 2023.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Jack W. Rae, Anna Potapenko, Siddhant M. Jayakumar, and Timothy P. Lillicrap. Compressive transformers for long-range sequence modelling, 2019.

Zhangir Azerbayev, Bartosz Piotrowski, Hailey Schoelkopf, Edward W. Ayers, Dragomir Radev, and Jeremy Avigad. Proofnet: Autoformalizing and formally proving undergraduate-level mathematics, 2023.

Ofir Press, Noah Smith, and Mike Lewis. Train short, test long: Attention with linear biases enables input length extrapolation. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=R8sQPpGCv0.

Xin Li and Dan Roth. Learning question classifiers. In *Proceedings of the 19th international conference on Computational linguistics -*, Jan 2002. doi: 10.3115/1072228.1072378. URL http://dx.doi.org/10.3115/1072228.1072378.

Simeng Sun, Kalpesh Krishna, Andrew Mattarella-Micke, and Mohit Iyyer. Do long-range language models actually use long-range context?, 2021.

Daria Soboleva, Faisal Al-Khateeb, Robert Myers, Jacob R Steeves, Joel Hestness, and Nolan Dey. SlimPajama: A 627B token cleaned and deduplicated version of RedPajama. https://www.cerebras.net/blog/slimpajama-a-627b-token-cleaned-and-deduplicated-version-of-redpajama, 6 2023. URL https://huggingface.co/datasets/cerebras/SlimPajama-627B.

APPENDIX

7.1 REBUTTAL FIGURES

Figure 4: Needle in a Haystack evaluation with different sizes of models. Green squares indicates a high retrieval success rate, the white dashed line denotes the longest length examples seen at training or finetuning, and the Y-axis represents the distance to the retrieved target.

Figure 5: Perplexity and averaged downstream task accuracy for NIAH, LongBench and RULER.

7.2 REBUTTAL TABLES

Note that the perplexity is evaluated on Proof-file. Llama2-13b and Llama2-70b is evaluated on 4k context length for perplexity, Longbench and RULER.

Table 5: Overview of 13b models results across different extension types.

Attention Mechanisms		Model	PPL	Needle	LongB	RULER
Exact Attention	Frozen	Llama2-13b(4k)	2.90	17.00	33.84	86.35
		NTK-F	3.31	43.00	31.87	2.30
		Self-Extend	2.65	53.50	33.69	30.23
	Fine-Tuned	PI	2.46	45.00	37.45	55.95
		NTK-32K	2.44	82.20	38.41	58.38
		YaRN	2.46	44.20	34.03	44.79
		CLEX	2.43	78.90	35.89	52.76

Table 6: Overview of 70b models results across different extension types.

Attention Mechanisms		Model	PPL	Needle	LongB	RULER
Exact Attention	Frozen	Llama2-70b(4k)	2.66	14.70	34.00	93.67
		NTK-F	3.25	30.90	32.40	11.39
		Self-Extend	2.43	32.60	29.10	31.94
	Fine-Tuned	PI	2.26	49.80	42.44	77.98
		NTK-32K	2.25	90.50	41.51	76.97

Table 7: Overview of 7b, 13b, and 70b models results across different extension types.

Model	Method	PPL	Needle	LongB	RULER
Llama2-7b	Base (4k)	3.04	8.40	32.92	80.94
	NTK-Frozen	4.06	18.80	25.54	0.72
	Self-Extend	2.75	25.80	33.62	29.50
	PI	2.58	42.10	33.48	57.66
	NTK-32k	2.54	83.70	35.32	59.42
	YaRN	2.59	46.70	33.45	36.95
	CLEX	2.55	71.10	33.48	52.17
Llama2-13b	Base (4k)	2.90	17.00	33.84	86.35
	NTK-Frozen	3.31	43.00	31.87	2.30
	Self-Extend	2.65	53.50	33.69	30.23
	PI	2.46	45.00	37.45	55.95
	NTK-32k	2.44	82.20	38.41	58.38
	YaRN	2.46	44.20	34.03	44.79
	CLEX	2.43	78.90	35.89	52.76
Llama2-70b	Base (4k)	2.66	14.70	34.00	93.67
	NTK-Frozen	3.25	30.90	32.40	11.39
	Self-Extend	2.43	32.60	29.10	31.94
	PI	2.26	49.80	42.44	77.98
	NTK-32k	2.25	90.50	41.51	76.97

Many-shot In-Context Learning with Trec News We evaluate TREC News (Li and Roth, 2002) with 1 to 1000 in-context examples. In general, performance improves with more examples in Figure **??**. Exact Attention methods show significant gains from 10 to 50 examples (+44.0%), with slower growth from 50 to 100 examples (+5.7%). Approximate Attention methods consistently underperform. Performance gains align with model perplexity; NTK-Frozen excels with fewer examples but underperforms with more.

Table 8: Model Performance on short Tasks. HS refers to Hellaswag, TQA refers to TruthfulQA and WG refers to WinoGrande.

Methods	ARC-c	ARC-e	HS	MMLU	TQA	WG	Avg.
Llama2-7b	52.73	81.31	78.96	42.09	38.97	74.43	61.42
LM-Infinite	52.56	81.36	78.95	42.09	38.96	74.11	61.34
Self-Extend	52.56	81.31	78.94	42.07	38.97	74.43	61.38
NTK-Frozen	52.73	81.31	78.96	42.09	38.97	74.43	61.42
PI	51.11	81.14	77.44	37.19	38.03	71.74	59.44
NTK-32k	49.15	80.22	74.48	35.25	38.13	72.61	58.31
NTK-64k	46.08	78.32	70.68	34.27	39.08	70.24	56.45
YaRN	53.41	81.82	78.47	41.06	38.63	74.43	61.30
CLEX	50.60	81.27	76.06	37.54	36.10	64.72	57.72
LongLora	46.67	78.58	67.08	26.29	37.61	55.25	51.91

Table 9: Perlexity and Downstream Tasks Correlations and Interpretations.

Task	Kendall's Tau	p-value	Interpretation
Needle	-0.7191	0.0041	Statistically significant ($p < 0.01$).
Mshots	-0.4944	0.0482	Borderline significant ($p \approx 0.05$).
LongB	-0.6136	0.0149	Statistically significant ($p < 0.05$).
RULER	-0.7191	0.0041	Statistically significant ($p < 0.01$).

Short-context Tasks We analyzed performance on short tasks from the Open LLM Leaderboard[1] to validate our hypothesis regarding context length impact. Results are shown in Figure 11. Our analysis revealed three key findings: (1) long-context extension methods generally show minor performance degradation on short-text tasks compared to the base model, with NTK-Frozen outperforming NTK-RoPE, (2) continuous fine-tuning methods demonstrate more significant short-text performance reduction, suggesting a trade-off between long and short context capabilities, and (3) these results corroborate the negative log-likelihood patterns observed in Figure 3.

7.3 DETAILS OF YARN EXTENSION METHOD

YaRN, another RoPE extension method, uses "NTK-by-parts" interpolation strategies across different dimensions of the embedding space and introduces a temperature factor to adjust the attention distribution for long inputs.

$$\alpha_j^{\text{YaRN}} = ((1 - \gamma_j)\frac{1}{t} + \gamma_j)/\sqrt{T} \tag{14}$$

We use a ramp vector $\boldsymbol{\gamma}$ to determine the interpolation between the $\frac{1}{t}$ and the original frequency base. The interpolation gating is set based on the frequency for the dimension j.

$$\gamma_j = \begin{cases} 0, & \text{if } \theta_j < p, \\ 1, & \text{if } \theta_j > q, \\ \frac{\theta_j - p}{q - p}, & \text{otherwise.} \end{cases} \tag{15}$$

The values of p, q, T can be tuned as needed.

7.4 LLAMA-3 AND PHI-2 FOR CONTEXT EXTENSION

We use other open-weight models, LLaMA-3-8B (AI@Meta, 2024) base and Phi-2-base (Javaheripi et al., 2023) as the base point for context extension, to verify whether the trends and analyses we observed are consistent across different base models. Using an identical training recipe, we re-train and re-evaluate seven models with Llama-3-8B base and Phi-2-base.

---

[1]https://huggingface.co/spaces/open-llm-leaderboard-old/open_llm_leaderboard

Table 10: Efficiency analysis for different sequence lengths (4k, 8k, 16k, 32k). The prefill time(Pre) cost represents the time required to generate the first token. The decoding speed(Dec) (seconds / per token) is averaged over 100 token inferences at each sequence length. Memory consumption corresponds to the peak GPU memory usage during inference. All methods, except for LM-Infinite and Landmark, utilize Flash-Attention 2 for enhanced computational efficiency.

Method	4k			8k			16k			32k		
	Pre (s)	Dec (s)	Mem (GB)	Pre (s)	Dec (s)	Mem (GB)	Pre (s)	Dec (s)	Mem (GB)	Pre (s)	Dec (s)	Mem (GB)
Llama2	1.15	0.03	17.13	1.51	0.06	21.61	2.41	0.11	30.59	4.63	0.21	48.55
NTK-F	1.16	0.04	17.13	1.56	0.05	21.61	2.39	0.06	30.59	4.69	0.09	48.55
PI	1.15	0.03	22.05	1.54	0.03	26.54	2.43	0.05	35.51	4.74	0.08	53.47
NTK-32k	1.17	0.04	17.11	1.56	0.04	21.60	2.42	0.06	30.58	4.75	0.09	48.53
YaRN	1.23	0.03	18.05	1.53	0.03	22.54	2.43	0.05	31.51	4.80	0.08	49.47
CLEX	1.16	0.05	17.16	6.99	0.07	21.74	7.68	0.11	30.92	10.06	0.18	49.28
LM-Infinite	1.56	0.05	17.23	3.34	0.07	25.47	5.82	0.11	38.60	11.58	0.18	65.61
Self-Extend	1.24	0.05	17.23	1.63	0.07	21.81	2.63	0.13	30.98	4.97	0.22	49.32
LongLora	1.16	0.05	17.16	1.65	0.05	21.65	2.60	0.05	30.62	5.07	0.08	48.58
Landmark	8.62	0.08	18.77	17.65	0.08	22.97	36.47	0.09	31.22	77.77	0.09	47.74

Table 11: Short-Text Task Performance

Methods	ARC-c	ARC-e	Hellaswag	MMLU	TruthfulQA	WinoGrande	Average
Llama2-7b-base	0.5273	0.8131	0.7896	0.4209	0.3897	0.7443	0.6142
LM-Infinite	0.5256	0.8136	0.7895	0.4209	0.3896	0.7411	0.6134
Self-Extend	0.5256	0.8131	0.7894	0.4207	0.3897	0.7443	0.6138
NTK-Frozen-hf	0.5273	0.8131	0.7896	0.4209	0.3897	0.7443	0.6142
PI	0.5111	0.8114	0.7744	0.3719	0.3803	0.7174	0.5944
NTK-32k	0.4915	0.8022	0.7448	0.3525	0.3813	0.7261	0.5831
NTK-64k	0.4608	0.7832	0.7068	0.3427	0.3908	0.7024	0.5645
YaRN	0.5341	0.8182	0.7847	0.4106	0.3863	0.7443	0.6130
CLEX	0.5060	0.8127	0.7606	0.3754	0.3610	0.6472	0.5772
LongLora	0.4667	0.7858	0.6708	0.2629	0.3761	0.5525	0.5191

7.4.1 PERPLEXITY ON PROOF-FILE OF LLAMA-3 AND PHI-2

We evaluate the perplexity of LLaMA-3-8B base in Table 12 and Phi-2-base in Table 13. Consistent with our observations on LLaMA-2-7B, continuous fine-tuning methods like PI and YaRN effectively maintain low perplexity scores within the pre-training context length. However, perplexity scores escalate once the context length exceeds the pre-trained window. Notably, only NTK and CLEX could generalize to unseen sequence lengths during both pre-training and continual fine-tuning.

Table 12: Perplexity results of different methods on Proof-file with LLaMA-3-8B base. Len refers to the longest-length examples seen at training or fine-tuning. Ex refers to the exact attention. All results are produced by our experiments.

Model Details			Eval Length					
Len	Ex	Methods	2k	4k	8k	16k	32k	64k
Frozen								
8k	✓	LLaMA-3	**2.98**	**2.72**	**2.54**	31.11	318	-
8k	✓	NTK-Frozen	**2.98**	**2.72**	**2.54**	2.48	3.80	8.69
8k		Self-Extend	**2.98**	**2.72**	**2.54**	**2.43**	2.36	2.62
Finetuned								
32k	✓	PI	3.13	2.83	2.63	2.49	2.39	38.77
32k	✓	NTK-32K	3.05	2.76	2.57	**2.43**	**2.34**	**2.28**
32k	✓	YaRN	3.16	2.86	2.66	2.52	2.43	4989
32k	✓	CLEX	3.30	2.89	2.64	2.47	2.38	2.39

7.4.2 RULER OF LLAMA-3 AND PHI-2

We test all models on all 13 diverse tasks for LLaMA-3-8B and 12 tasks (except QA-2) for Phi-2 from the four Ruler Hsieh et al. (2024) categories in Table 14 and Table 15. Consistently, NTK-32k

Table 13: Perplexity results of different methods on Proof-file with Phi-2-base. Len refers to the longest-length examples seen at training or fine-tuning. Ex refers to the exact attention. All results are produced by our experiments.

Model Details				Eval Length					
	Len	Ex	Methods	2k	4k	8k	16k	32k	64k
Frozen	2k	✓	Phi-2-base	**4.02**	25.72	175.05	-	-	-
	2k	✓	NTK-Frozen	**4.02**	3.73	4.07	5.49	12.58	36.68
	2k		Self-Extend	4.08	**3.70**	**3.48**	3.42	3.48	3.73
Finetuned	32k	✓	PI	7.53	6.75	6.25	5.97	5.83	45.00
	32k	✓	NTK-32K	4.24	3.81	3.51	**3.32**	**3.18**	**3.20**
	32k	✓	CLEX	5.53	4.32	3.78	3.51	3.42	3.60
	64k	✓	NTK-64K	4.63	4.14	3.82	3.61	3.47	3.38

maintains relatively strong performance compared to other methods fine-tuned with a length cap of 32k and showing a slight drop in performance at 64k. The only exception is Self-Extend on LLaMA-3-8B, which benefits from a larger pretraining length of 8192. Self-Extend demonstrates superior performance on LLaMA-3 compared to LLaMA-2 and Phi-2, with performance approaching that of CLEX and PI.

Table 14: RULER evaluation on seven methods with LLaMA-3-8B. Performance of models evaluated at length from 8k to 64k. Each score is computed by averaging the accuracy of 13 tasks. Train Len refers to the longest-length examples seen at continuous finetuning.

	Models	Train Len	4k	8k	16k	32k	64k
Frozen	LLaMA-3	8k	93.63	91.16	0.06	0.01	0.05
	NTK-Frozen	8k	93.63	91.15	6.86	1.98	0.02
	Self-Extend	8k	92.73	84.11	78.78	71.40	38.79
Finetuned	PI	32k	91.60	88.56	86.99	73.14	0.02
	NTK-32K	32k	**93.68**	**91.67**	**91.12**	**86.04**	**65.42**
	YaRN	32k	92.51	90.59	88.07	68.69	0.06
	CLEX	32k	89.65	87.35	87.89	69.27	39.81

Table 15: RULER evaluation on seven methods with Phi-2-base. Performance of models evaluated at length from 2k to 64k. Each score is computed by averaging the accuracy of 12 tasks. Train Len refers to the longest-length examples seen at continuous finetuning.

	Models	Train Len	2k	4k	8k	16k	32k	64k
Frozen	Phi-2-base	2k	83.73	-	-	-	-	-
	NTK-Frozen	2k	**83.98**	52.95	18.09	4.07	0.06	0.00
	Self-Extend	2k	68.55	50.82	36.65	22.00	7.83	2.32
Finetuned	PI	32k	25.51	23.19	16.88	14.99	4.78	0.00
	NTK-32K	32k	81.18	66.90	52.57	**46.53**	**32.06**	12.84
	CLEX	32k	75.33	**72.66**	**53.56**	46.23	25.46	13.03
	NTK-64K	64k	78.73	59.87	47.56	41.87	25.66	**17.69**

7.5 IMPLEMENTATION DETAILS

7.5.1 TRAINING

To maintain consistency across all models, we use a fixed training protocol (Chen et al., 2023b). We adopt standard practices by applying an exponential moving average (EMA) to the model weights with a constant decay rate. Most training hyperparameters are based on (Fu et al., 2024), including a learning rate of 2×10^{-5}. We implement a linear warm-up for the learning rate and set the weight decay to zero, utilizing 8 NVIDIA A100 GPUs. We present the hyperparameter settings for different methods on LLaMA-2-7B, LLaMA-3-8B, and Phi-2 during the training stage in Table 16.

LLaMA-2 For LongLora, we fine-tune the LoRA adapter weights along with trainable embeddings and normalization, subsequently integrating these trained weights into the LLaMA2 base model for evaluation. For Landmark Attention, the training context length is 512, with a block size of 64. For YaRN, we set beta fast to 32, beta slow to 1, and α to 8.0. For CLEX, we set the max scale factor to 32 and use the SiLU activation function. For NTK-RoPE, given the maximum observed length during training or inference, C_{test}, and the scaling hyperparameter s, we follow Fu et al. (2024) in replacing t with $s \cdot \frac{\max(C', C_{\text{test}})}{C} - (s-1)$, and set the hyperparameter s to $\frac{C'}{2C}$ during both training and inference. We set s to 4.0 for NTK-32k and s to 8.0 for NTK-64k. For LM-infinite, we set the global memory $G = 10$ and the local window $M = 4096$.

LLaMA-3 For YaRN, we set beta fast to 32, beta slow to 1, and α to 4.0. For CLEX, we set the max scale factor to 16 and use the SiLU activation function. For NTK-RoPE, we set s to 2.0.

Phi-2 For CLEX, we set the max scale factor to 64 and use the tanh activation function. For NTK-RoPE, we set s to 8.0 for NTK-32k and 16.0 for NTK-64k.

Table 16: Hyperparameters for Different Long Sequence Methods in Training.

Models	Methods	Train Len	Train Tokens	α	bsz	lr
LLaMA-2	PI	32k	1B	8.0	32	2e-5
	NTK-32K	32k	1B	29.0	32	2e-5
	YaRN	32k	1B	8.0	32	2e-5
	LongLora	32k	1B	8.0	32	2e-5
	Landmark	32k	1B	-	32	2e-5
	NTK-64K	64k	1B	57.0	32	2e-5
	NTK-64K-2B	64k	2B	57.0	32	2e-5
LLaMA-3	PI	32k	1B	4.0	32	2e-5
	NTK-32K	32k	1B	7.0	32	2e-5
	YaRN	32k	1B	4.0	32	2e-5
Phi-2	PI	32k	1B	16.0	32	2e-5
	NTK-32K	32k	1B	121.0	32	2e-5
	NTK-64K	64k	1B	497.0	32	2e-5

7.5.2 INFERENCE

For all methods on all base models, we show the hyperparameter settings and present the α used for different length ranges during inference in Table 17.

LLaMA-2 For Landmark Attention, the training context length is set to 512, with a block size of 64. For Self-Extend, we set the local window size M for neighbor tokens to 1024 and the group size N to 64. For NTK-RoPE, we replace t with $s \cdot \frac{\max(C', C_{\text{test}})}{C} - (s-1)$ and set s to 4.0 for NTK-32k and 8.0 for NTK-64k.

LLaMA-3 For Self-Extend, we set the local window size M for neighbor tokens to 2048 and the group size N to 32. For NTK-RoPE, we set s to 2.0 for NTK-frozen and 4.0 NTK-32k.

Phi-2   For Self-Extend, we set the local window size M for neighbor tokens to 512 and the group size N to 128. For NTK-RoPE, we set s to 2.0 for NTK-frozen, 8.0 for NTK-32k, and 16.0 for NTK-64k.

Table 17: Hyperparameters for the Scale Factor α Different Long-context Methods in Inference.

Models	Methods	4k	8k	16k	32k	64k
LLaMA-2	NTK-Frozen	1.0	3.0	7.0	15.0	31.0
	PI	8.0	8.0	8.0	8.0	8.0
	NTK-32K	29.0	29.0	29.0	29.0	61.0
	YaRN	8.0	8.0	8.0	8.0	8.0
	LongLora	8.0	8.0	8.0	8.0	8.0
	NTK-64K	57.0	57.0	57.0	57.0	57.0
LLaMA-3	NTK-Frozen	1.0	1.0	3.0	7.0	15.0
	PI	4.0	4.0	4.0	4.0	4.0
	NTK-32K	13.0	13.0	13.0	13.0	29.0
	YaRN	4.0	4.0	4.0	4.0	4.0
Phi-2	NTK-Frozen	3.0	7.0	15.0	31.0	63.0
	PI	16.0	16.0	16.0	16.0	16.0
	NTK-32K	121	121	121	121	249
	NTK-64K	497	497	497	497	497

7.6   TRAINING DATA CONSTRUCTION

We sample 1B tokens from a long-context data mixture following Fu et al. (2024). We use the SlimPajama (Soboleva et al., 2023) dataset for continuous finetuning. This dataset serves as an open-source replication of the LLaMA (Touvron et al., 2023) pretraining data mixture. It comprises 82% web data (sourced 67% from CommonCrawl and 15% from C4), 4.5% code data (Github), 4.5% Wikipedia content, 4.5% books, 2.5% Arxiv papers, and 2.0% StackExchange content. We use per-source length-upsampling to sample 1B tokens from the datasets, which increases the portion of long sequences while keeping the domain mixture the same. We packed all sampled data into chunks of the corresponding training length, regardless of document boundaries, following common practiceTouvron et al. (2023); Fu et al. (2024).

7.7   LONGER MODEL NEEDS MORE TRAINING TOKENS

We observe that the performance of NTK-64K is not as good as NTK-32K. Consequently, we further sample 2B tokens from a long-context data mixture from Fu et al. (2024) for training and evaluate the model on the "Needle in A Haystack" task, as shown in Figure 6. Our NTK-64K model demonstrates a significant performance improvement when trained with more tokens, indicating that longer models require more tokens for effective training.

Figure 6: Needle in a Haystack evaluation. "NTK-64-2B" represents the NTK-64K model trained with 2B tokens. Green squares indicates a high retrieval success rate, the white dashed line denotes the longest length examples seen at training or finetuning, and the Y-axis represents the distance to the retrieved target.

7.8 RoPE Scale Factor for Dynamic NTK

We observe that the scale factor significantly degrades NTK-Dynamic models, particularly causing performance deterioration in shorter sequences. Therefore, we conduct a grid search to determine a better scale factor for different input lengths. The scale factor and its relationship with perplexity on PG19 are reported in Table 18.

Table 18: The scale factor and its relationship with perplexity on PG19. We only use the first 2 documents of PG19 to calculate the perplexity.

Models	Scale Factor	4k	8k	16k	32k	64k
NTK-Frozen	1	**7.65**	118.82	NaN	NaN	NaN
	3	8.19	**7.99**	57.15	386.02	NaN
	7	9.39	9.26	**9.61**	72.62	486.13
	15	11.53	12.04	12.98	**20.15**	180.59
	31	16.18	20.66	26.67	40.06	**69.01**
	63	30.22	48.78	69.89	89.75	118.59
NTK-32K	1	12.64	NaN	NaN	NaN	NaN
	5	7.84	7.638	10.36	NaN	NaN
	13	**7.686**	7.459	7.25	8.35	NaN
	29	7.689	**7.457**	**7.24**	**6.82**	9.11
	61	7.8	7.565	7.34	6.91	**6.63**
	125	7.99	7.774	7.57	7.13	6.83
NTK-64K	1	19.16	NaN	NaN	NaN	NaN
	9	8.02	7.79	7.63	22.6	NaN
	25	**7.89**	**7.65**	**7.443**	7.04	14.02
	57	7.922	7.67	7.44	**7.01**	**6.75**
	121	8.016	7.75	7.51	7.06	6.77

7.9 LongLora Validation

To validate our LongLora Chen et al. (2023b) implementation, we reproduce their Llama-2-7b-longlora-32k model following LongLora's training data and training recipe. We evaluate the perplexity for the corresponding length on PG19 and Proof-file in Table 19.

Table 19: Perplexity results of LongLora reported and our reproduction on PG 19 and Proof-file.

Method	2k	4k	8k	16k	32k
PG19					
Llama-2-7b-longlora-32k	8.29	7.83	7.54	7.35	7.22
Our Reproduction	8.10	7.69	7.43	7.28	7.32
Proof-file					
Llama-2-7b-longlora-32k	3.35	3.01	2.78	2.61	2.50
Our Reproduction	3.33	3.01	2.80	2.67	2.61

7.10 LongBench Results

The evaluation results of all methods on LongBench are presented in Table 20.

Table 20: LongBench results. N-32 and N-64 refer to NTK finetuned on 32K and 64K context lengths respectively. Inf refers to LM-Infinite. SE refers to Self-Extend. LLR refers to LongLora. AvgLen refers to average length of the datasets. Train Len refers to the longest length examples seen at training or finetuning. Eval Len refers to the maximum length of the input prompt. ✓refers to whether the method is exact attention.

Exact	AvgLen	Frozen				Finetuned						
		Base	Inf	N-F	SE	PI	N-32	YaRN	CLEX	LLR	Land	N-64
		✓			✓	✓	✓	✓			✓	
Train Len		4k	4k	4k	4K	32k	32k	32k	32k	32k	32k	64k
Eval Len		4k	32k	32k	32K	32k	32k	32k	32k	32k	32k	32k
NQA	**18,409**	21.09	10.39	3.88	23.49	23.02	23.73	19.82	24.19	12.07	12.47	**24.31**
QAPR	3,619	26.94	22.58	26.79	28.75	25.85	**27.50**	26.98	23.36	20.15	19.06	24.97
MFQA	4,559	32.42	26.19	29.82	32.66	35.10	38.22	37.11	40.83	24.50	21.86	**40.60**
HPQA	9,151	31.23	16.13	32.10	37.63	36.98	**41.56**	38.60	35.59	27.41	33.66	41.47
WMQA	4,887	25.75	20.64	22.34	30.70	29.38	**31.58**	30.63	28.24	21.46	24.94	28.62
MSQ	11,214	10.55	5.26	8.84	15.73	16.80	17.41	**22.08**	17.12	11.46	11.41	18.24
GR	8,734	17.32	13.43	17.87	13.15	25.61	**28.27**	20.98	24.68	24.05	17.20	24.37
QMSM	10,614	21.28	6.10	15.35	20.20	21.19	21.52	20.66	21.55	17.66	18.83	**21.65**
MNWS	2,113	3.44	3.63	9.30	1.50	10.55	22.13	8.91	16.96	21.19	19.43	**25.02**
TREC	5,177	66.00	61.00	67.50	69.00	**71.00**	69.00	69.00	67.50	50.00	49.00	69.00
TRVQA	8,209	87.89	81.40	18.69	88.44	88.55	88.86	**89.63**	89.36	12.28	74.75	88.65
SMSM	6,258	41.70	15.07	32.46	43.76	**43.35**	42.21	44.25	43.02	13.45	40.38	41.59
PSC	11,141	2.10	1.62	2.67	0.00	1.50	2.68	1.05	2.50	**4.57**	0.64	2.09
PSR	9,289	**9.00**	4.00	3.77	4.50	4.50	4.62	3.79	8.50	3.50	2.50	6.50
LCC	1,235	**68.22**	67.68	63.64	68.47	55.05	56.78	54.06	49.45	57.12	56.70	52.04
REPO	4,206	**61.73**	58.27	53.69	59.99	47.26	49.09	47.60	42.84	51.92	48.23	39.68
Average	7,425	32.92	25.84	25.54	33.62	33.48	**35.32**	33.45	33.48	23.30	28.19	34.30

7.11 RULER SUBTASKS RESULT

The performance of models on different lengths and breakdowns by 13 subtasks are reported in Table 21(RULER on 4k), Table 22(RULER on 8k), Table 23(RULER on 16k), Table 24(RULER on 32k) and Table 25(RULER on 64k).

Table 21: Ruler results on 4k context length. N-32 and N-64 refer to NTK finetuned on 32K and 64K context lengths respectively. Inf refers to LM-Infinite. SE refers to Self-Extend. LLR refers to LongLora. Train Len refers to the longest length examples seen at training or finetuning. Eval Len refers to the maximum length of the input prompt. ✓refers to whether the method is exact attention.

Exact	Frozen				Finetuned						
	Base	Inf	N-F	SE	PI	N-32	YaRN	CLEX	LLR	Land	N-64
	✓			✓	✓	✓	✓	✓			✓
Train Len	4k	4k	4k	4k	32k	32k	32k	32k	32k	32k	64k
Eval Len	4k	4k	4k	4k	4k	4k	4k	4k	4k	4k	4k
NIAH_S1	100.00	100.00	100.00	100.00	98.00	100.00	99.60	100.00	0.00	49.00	100.00
NIAH_S2	100.00	100.00	100.00	100.00	99.80	100.00	88.60	100.00	0.00	20.60	100.00
NIAH_S3	99.20	95.80	98.80	89.80	99.80	94.20	53.00	89.60	0.00	10.00	97.20
NIAH_M1	99.20	98.80	99.20	79.00	99.20	99.20	62.60	95.80	0.00	10.60	98.00
NIAH_M2	88.00	88.00	88.20	26.00	95.40	97.40	14.00	83.20	0.00	6.80	97.00
NIAH_M3	61.40	62.00	61.60	14.40	78.00	68.20	8.20	53.80	0.00	1.20	84.80
NIAH_MV	83.55	90.45	86.60	82.10	95.45	96.40	50.25	95.10	0.05	10.80	96.15
NIAH_MQ	95.45	96.15	96.00	90.70	96.95	97.00	62.00	96.20	0.00	5.35	98.25
VT	57.72	58.56	56.48	8.92	96.64	98.16	25.68	85.72	0.00	2.92	97.00
CWE	78.20	75.90	78.20	73.56	81.38	80.86	58.78	82.60	64.70	23.16	74.26
FWE	84.33	84.20	84.93	80.07	58.40	85.53	26.20	52.60	18.53	84.93	81.40
QA_1	62.20	60.40	62.40	60.60	57.80	62.40	60.20	55.80	26.20	37.20	55.80
QA_2	43.00	43.40	42.40	40.20	42.40	46.20	43.20	38.20	28.00	28.20	46.00
Avg.	80.94	81.05	81.14	65.03	84.56	86.58	50.18	79.12	10.58	22.37	86.60

Table 22: Ruler results on 8k context length.

Exact		Frozen						Finetuned			
	Base	Inf	N-F	SE	PI	N-32	YaRN	CLEX	LLR	Land	N-64
	✓		✓		✓	✓	✓	✓			✓
Train Len	4k	4k	4k	4k	32k	32k	32k	32k	32k	32k	64k
Eval Len	4k	4k	4k	4k	4k	4k	4k	4k	4k	4k	4k
NIAH_S1	-	46.00	61.60	100.00	99.00	99.80	100.00	100.00	0.00	46.00	100.00
NIAH_S2	-	36.60	59.40	98.80	100.00	100.00	99.40	100.00	0.00	7.20	100.00
NIAH_S3	-	20.80	51.00	88.60	99.20	94.20	96.00	97.80	0.00	3.80	99.20
NIAH_M1	-	27.80	46.00	69.40	98.00	94.20	86.60	90.20	0.00	7.60	95.20
NIAH_M2	-	4.40	11.00	8.20	91.60	86.20	60.60	66.00	0.00	1.60	86.60
NIAH_M3	-	2.60	4.00	3.20	48.40	52.20	34.60	11.80	0.00	0.00	47.40
NIAH_MV	-	30.35	41.35	52.95	65.50	85.95	70.40	61.25	0.00	6.25	84.75
NIAH_MQ	-	30.15	50.40	78.70	93.25	95.20	92.45	86.95	0.00	3.35	94.95
VT	-	4.88	69.88	1.48	91.20	96.16	77.52	48.16	0.00	3.08	94.36
CWE	-	65.08	40.30	30.82	45.66	45.76	44.72	32.72	18.92	22.08	40.80
FWE	-	56.73	64.87	59.00	65.07	70.13	10.53	45.40	16.73	76.60	54.13
QA_1	-	35.80	44.40	31.00	50.80	49.20	43.20	48.20	22.80	25.00	50.20
QA_2	-	29.00	33.60	37.40	40.80	41.80	36.80	42.60	24.40	25.20	44.80
Avg.	-	30.01	44.45	50.73	76.04	77.75	65.60	63.93	6.37	17.52	76.34

Table 23: Ruler results on 16k context length.

Exact		Frozen						Finetuned			
	Base	Inf	N-F	SE	PI	N-32	YaRN	CLEX	LLR	Land	N-64
	✓		✓		✓	✓	✓	✓			✓
Train Len	4k	4k	4k	4k	32k	32k	32k	32k	32k	32k	64k
Eval Len	4k	4k	4k	4k	4k	4k	4k	4k	4k	4k	4k
NIAH_S1	-	21.00	14.20	99.80	97.20	99.40	100.00	99.80	0.00	42.40	99.80
NIAH_S2	-	17.00	17.40	93.40	100.00	100.00	99.20	100.00	0.20	6.80	100.00
NIAH_S3	-	11.60	8.20	77.00	99.60	98.60	89.60	99.60	0.00	3.60	100.00
NIAH_M1	-	15.80	9.20	60.00	97.80	93.20	83.40	89.40	0.00	5.60	90.80
NIAH_M2	-	0.00	0.60	3.80	82.80	79.80	19.60	72.00	0.00	0.80	67.60
NIAH_M3	-	1.00	0.00	1.80	34.20	18.20	7.40	15.00	0.00	0.00	29.60
NIAH_MV	-	8.40	6.90	38.85	77.55	81.95	58.75	62.40	0.00	4.80	83.50
NIAH_MQ	-	8.85	7.95	59.30	90.95	86.20	85.15	81.60	0.00	2.75	90.35
VT	-	6.56	11.28	1.16	68.84	83.56	47.12	48.16	0.00	2.52	88.68
CWE	-	19.94	28.36	17.80	27.26	26.32	23.72	28.60	0.62	11.90	21.20
FWE	-	77.13	25.80	59.80	47.93	61.73	10.13	57.33	12.93	81.60	51.73
QA_1	-	22.80	36.40	28.00	46.00	45.20	43.20	49.20	13.20	23.00	45.00
QA_2	-	24.20	26.00	31.60	35.20	36.00	37.40	33.40	20.80	26.20	36.00
Avg.	-	18.02	14.79	44.02	69.64	70.01	54.21	64.35	3.67	16.31	69.56

Table 24: Ruler results on 32k context length.

Exact	Base	Frozen			Finetuned						
		Inf	N-F	SE	PI	N-32	YaRN	CLEX	LLR	Land	N-64
	✓		✓		✓	✓	✓	✓			✓
Train Len	4k	4k	4k	4k	32k	32k	32k	32k	32k	32k	64k
Eval Len	4k	4k	4k	4k	4k	4k	4k	4k	4k	4k	4k
NIAH_S1	-	7.80	0.00	83.00	97.20	99.00	85.80	85.60	0.00	33.80	100.00
NIAH_S2	-	7.00	0.00	68.40	99.00	100.00	81.00	94.00	0.00	3.20	99.20
NIAH_S3	-	6.40	0.00	42.80	97.00	99.40	62.40	97.20	0.00	2.60	96.40
NIAH_M1	-	8.80	0.00	29.40	93.40	90.80	63.20	78.40	0.00	5.40	82.60
NIAH_M2	-	0.00	0.00	2.40	48.80	39.40	6.40	40.40	0.00	0.20	36.60
NIAH_M3	-	0.00	0.00	1.40	5.80	8.60	1.20	8.00	0.00	0.00	7.20
NIAH_MV	-	3.75	0.00	24.65	61.30	68.20	37.95	60.75	0.00	2.80	82.20
NIAH_MQ	-	2.05	0.00	20.35	68.65	78.25	46.95	67.80	0.05	2.35	85.80
VT	-	2.08	0.00	2.32	56.68	43.28	22.00	30.08	0.00	2.52	71.28
CWE	-	4.48	0.02	17.46	26.72	11.78	11.38	22.70	13.26	3.68	7.34
FWE	-	72.67	2.93	46.73	31.00	64.53	15.13	34.67	13.93	72.47	51.53
QA_1	-	20.20	5.20	20.60	33.40	34.40	23.00	28.00	6.00	22.60	27.00
QA_2	-	25.20	1.20	24.00	30.60	34.80	24.00	30.60	12.60	24.60	33.20
Avg.	-	12.34	0.72	29.50	57.66	59.42	36.95	52.17	3.53	13.56	60.03

Table 25: Ruler results on 64k context length.

Exact	Base	Frozen			Finetuned						
		Inf	N-F	SE	PI	N-32	YaRN	CLEX	LLR	Land	N-64
	✓		✓		✓	✓	✓	✓			✓
Train Len	4k	4k	4k	4k	32k	32k	32k	32k	32k	32k	64k
Eval Len	4k	4k	4k	4k	4k	4k	4k	4k	4k	4k	4k
NIAH_S1	-	3.20	0.00	71.80	0.00	83.60	0.00	40.60	0.00	40.00	98.00
NIAH_S2	-	3.80	0.00	0.20	0.00	95.60	0.00	68.80	0.00	3.00	98.00
NIAH_S3	-	5.40	0.00	0.00	0.00	95.40	0.00	70.40	0.00	3.00	95.80
NIAH_M1	-	5.40	0.00	0.00	0.00	76.80	0.00	55.40	0.00	5.20	67.20
NIAH_M2	-	0.00	0.00	2.60	0.00	15.20	0.00	15.80	0.00	0.00	25.80
NIAH_M3	-	0.00	0.00	0.20	0.00	1.20	0.00	1.00	0.00	0.00	4.00
NIAH_MV	-	4.45	0.00	0.20	0.00	51.70	0.00	36.40	0.00	3.70	51.20
NIAH_MQ	-	4.45	0.00	0.05	0.00	56.60	0.00	43.50	0.00	2.45	65.40
VT	-	1.28	0.00	12.20	0.00	34.28	0.00	0.00	0.00	2.40	41.48
CWE	-	0.76	0.00	6.85	0.00	6.58	0.00	9.72	0.00	1.70	7.88
FWE	-	72.20	11.47	26.47	0.00	25.27	0.00	11.73	0.00	82.67	27.73
QA_1	-	16.20	0.20	0.80	0.00	30.80	0.00	25.60	0.00	19.60	29.20
QA_2	-	20.20	0.20	0.00	0.00	28.40	0.00	19.00	0.00	20.20	29.40
Avg.	-	10.56	0.91	9.34	0.00	46.26	0.00	30.61	0.00	14.15	49.31