Sliced Iterative Normalizing Flows

Abstract

We develop an iterative (greedy) deep learning algorithm which is able to transform an arbitrary probability distribution function (PDF) into the target PDF. The model is based on iterative Optimal Transport of a series of 1D slices, matching on each slice the marginal PDF to the target. As special cases of this algorithm, we introduce two Sliced Iterative Normalizing Flows (SINF), which map from the data to the latent space (GIS) and vice versa (SIG). We show that SIG is able to generate high quality samples that match the GAN benchmarks. GIS obtains better results on small dataset density estimation tasks compared to the density trained NFs. SINF approach deviates significantly from the current DL paradigm, as it is greedy and does not use concepts such as mini-batching, stochastic gradient descent and gradient back-propagation through deep layers.

1. Introduction

Latent variable generative models such as Normalizing Flows (NFs) (Rezende & Mohamed, 2015; Dinh et al., 2014; 2016; Kingma & Dhariwal, 2018), Variational AutoEncoders (VAEs) (Kingma & Welling, 2013; Rezende et al., 2014) and Generative Adversarial Networks (GANs) (Goodfellow et al., 2014; Radford et al., 2015) aim to model the distribution $p(x)$ of high-dimensional input data x by introducing a mapping from a latent variable z to x, where z is assumed to follow a given prior distribution $\pi(z)$. These models usually parameterize the mapping using neural networks, and the training of these models typically consists of minimizing a dissimilarity measure between the model distribution and the target distribution.

In this work we adopt a different approach to build the map from latent variable z to data x. We approach this problem from the Optimal Transport (OT) point of view. OT studies

[1]Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

Preliminary work. Under review by INNF+ 2021. Do not distribute.

whether the transport maps exist between two probability distributions, and if they do, how to construct the map to minimize the transport cost. We propose to decompose the high dimensional problem into a succession of 1D transport problems, where the OT solution is known. The mapping is iteratively augmented, and it has a NF structure that allows explicit density estimation and efficient sampling. We name the algorithm Sliced Iterative Normalizing Flow (SINF). Our objective function is inspired by the Wasserstein distance, which is defined as the minimal transport cost and has been widely used in the loss functions of generative models (Arjovsky & Bottou, 2017; Tolstikhin et al., 2017). We propose a new metric, max K-sliced Wasserstein distance, which enables the algorithm to scale well to high dimensions.

2. Background

The p-Wasserstein distance, $p \in [1, \infty)$, between two probability distributions p_1 and p_2 is defined as:

$$W_p(p_1, p_2) = \inf_{\gamma \in \Pi(p_1, p_2)} \left(\mathbb{E}_{(x,y) \sim \gamma} \left[\|x - y\|^p \right] \right)^{\frac{1}{p}}, \quad (1)$$

where $\Pi(p_1, p_2)$ is the set of all possible joint distributions $\gamma(x, y)$ with marginalized distributions p_1 and p_2. In 1D the Wasserstein distance has a closed form solution via Cumulative Distribution Functions (CDFs), but this evaluation is intractable in high dimension. An alternative metric, the Sliced p-Wasserstein Distance (SWD), is defined as:

$$SW_p(p_1, p_2) = \left(\int_{\mathbb{S}^{d-1}} W_p^p(\mathcal{R}p_1(\cdot, \theta), \mathcal{R}p_2(\cdot, \theta)) d\theta \right)^{\frac{1}{p}}, \quad (2)$$

where $\mathbb{S}^{d-1}$ denotes the unit sphere $\theta_1^2 + \cdots \theta_n^2 = 1$ in $\mathbb{R}^d$, $d\theta$ is the normalized uniform measure on $\mathbb{S}^{d-1}$, and $\mathcal{R}$ denotes the Radon transform. The definition of Radon transform can be found in the appendix. For a given θ, the function $(\mathcal{R}p)(\cdot, \theta) : \mathbb{R} \to \mathbb{R}$ is essentially the slice (or projection) of $p(x)$ on axis θ.

The SWD can be calculated by approximating the high dimensional integral with Monte Carlo samples. However, in high dimensions a large number of projections is required to accurately estimate SWD. This motivates to use the max-

imum Sliced p-Wasserstein Distance (max SWD):

$$\max\text{-}SW_p(p_1, p_2) = \max_{\theta \in \mathbb{S}^{d-1}} W_p(\mathcal{R}p_1(\cdot, \theta), \mathcal{R}p_2(\cdot, \theta)), \tag{3}$$

which is the maximum of the Wasserstein distance of the 1D marginalized distributions of all possible directions.

3. Sliced Iterative Normalizing Flows

We consider the general problem of building a NF that maps an arbitrary PDF $p_1(x)$ to another arbitrary PDF $p_2(x)$ of the same dimensionality. We firstly introduce our objective function in Section 3.1. The general SINF algorithm is presented in Section 3.2. We then consider the special cases of p_1 and p_2 being standard Normal distributions in Section 3.3 and Section 3.4, respectively.

3.1. Maximum K-sliced Wasserstein distance

We generalize the idea of maximum SWD and propose maximum K-Sliced p-Wasserstein Distance (max K-SWD):

$$\max\text{-}K\text{-}SW_p(p_1, p_2) = \max_{\{\theta_1, \cdots, \theta_K\} \text{ orthonormal}}$$

$$\left(\frac{1}{K} \sum_{k=1}^{K} W_p^p((\mathcal{R}p_1)(\cdot, \theta_k), (\mathcal{R}p_2)(\cdot, \theta_k)) \right)^{\frac{1}{p}}. \tag{4}$$

In this work we fix $p = 2$. The max K-SWD defines K orthogonal axes $\{\theta_1, \cdots, \theta_K\}$ where the marginal distributions of p_1 and p_2 are most different, providing a natural choice for performing 1D marginal matching in our algorithm (see Section 3.2). The proof that max K-SWD is a proper distance and the details of its estimation are provided in the appendix.

3.2. Proposed SINF algorithm

The SINF algorithm is based on iteratively matching the 1D marginalized distribution of p_1 to p_2. This is motivated by the inverse Radon Transform (see Appendix) and Cramér-Wold theorem, which suggest that matching the high dimensional distributions is equivalent to matching the 1D slices on all possible directions, decomposing the high dimensional problem into a series of 1D problems. Given a set of i.i.d. samples X drawn from p_1, in each iteration, a set of 1D marginal transformations $\{\Psi_k\}_{k=1}^{K}$ [1] ($K \le d$ where d is the dimensionality of the dataset) are applied to the samples on orthogonal axes $\{\theta_k\}_{k=1}^{K}$ to match the 1D marginalized PDF of p_2 along those axes. Let $A = [\theta_1, \cdots, \theta_K]$ be the weight matrix ($A^T A = I_K$), the transformation at iteration

---

[1]**Notation definition**: In this paper we use l, k, j and m to represent different iterations of the algorithm, different axes θ_k, different gradient descent iterations of max K-SWD calculation (see Algorithm 2), and different knots in the spline functions of 1D transformation, respectively.

Algorithm 1 Sliced Iterative Normalizing Flow

Input: $\{x_i \sim p_1\}_{i=1}^{N}$, $\{y_i \sim p_2\}_{i=1}^{N}$, K, number of iteration L_{iter}
for $l = 1$ **to** L_{iter} **do**
   $A_l = \max \text{ K-SWD}(x_i, y_i, K)$
   for $k = 1$ **to** K **do**
      $\theta_k = A_l[:, k]$
      Compute $\hat{x}_i = \theta_k \cdot x_i$ and $\hat{y}_i = \theta_k \cdot y_i$ for each i
      $\tilde{x}_m = \text{quantiles}(\text{PDF}(\hat{x}_i))$
      $\tilde{y}_m = \text{quantiles}(\text{PDF}(\hat{y}_i))$
      $\psi_{l,k} = \text{RationalQuadraticSpline}(\tilde{x}_m, \tilde{y}_m)$
   end for
   $\boldsymbol{\Psi}_l = [\Psi_{l1}, \cdots, \Psi_{lK}]$
   Update $x_i = x_i - A_l A_l^T x_i + A_l \boldsymbol{\Psi}_l(A_l^T x_i)$
end for

---

l of samples X_l can be written as

$$X_{l+1} = A_l \boldsymbol{\Psi}_l(A_l^T X_l) + X_l^{\perp}, \tag{5}$$

where $X_l^{\perp} = X_l - A_l A_l^T X_l$. $\boldsymbol{\Psi}_l = [\Psi_{l1}, \cdots, \Psi_{lK}]^T$ is the marginal mapping of each dimension of $A_l^T X_l$, and its components are required to be monotonic and differentiable. The Inverse and Jacobian determinant of transformation 5 can be easily evaluated (see appendix).

The weight matrix A_l and the marginal transformations $\boldsymbol{\Psi}_l$ are determined by iteratively minimizing the max K-SWD (Equation 4) between the transformed p_1 and p_2. Specifically, we propose to iteratively solving for the orthogonal axes $\{\theta_1, \cdots, \theta_K\}$ in max K-SWD, and then apply 1D marginal matching on those axes to minimize max K-SWD.

Let $p_{1,l}$ be the transformed p_1 at iteration l. The kth component of $\boldsymbol{\Psi}_l$, $\Psi_{l,k}$, maps the 1D marginalized PDF of $p_{1,l}$ to p_2 and has an OT solution:

$$\Psi_{l,k}(x) = F_k^{-1}(G_{l,k}(x)), \tag{6}$$

where $G_{l,k}(x) = \int_{-\infty}^{x} (\mathcal{R}p_{1,l})(t, \theta_k) dt$ and $F_k(x) = \int_{-\infty}^{x} (\mathcal{R}p_2)(t, \theta_k) dt$ are the CDFs of $p_{1,l}$ and p_2 on axis θ_k, respectively. The CDFs can be estimated using the quantiles of the samples (in SIG Section 3.3), or using Kernel Density Estimation (KDE, in GIS Section 3.4). Equation 6 is monotonic and therefore invertible. We choose to parametrize it with monotonic rational quadratic splines (Gregory & Delbourgo, 1982; Durkan et al., 2019). Details about the splines are shown in the appendix.

The proposed algorithm iteratively minimizes the max K-SWD between the transformed p_1 and p_2. The orthonormal vectors $\{\theta_1, \cdots, \theta_K\}$ specify K axes along which the marginalized PDF between $p_{1,l}$ and p_2 are most different, thus maximizes the gain at each iteration and improves the efficiency of the algorithm. The model is able to converge with two orders of magnitude fewer iterations than

Table 1. FID scores on different datasets (lower is better). The errors are generally smaller than the differences.

	Method	MNIST	Fashion	CIFAR-10	CelebA
iterative	SWF	225.1	207.6	-	-
	SIG ($T=1$) (this work)	**4.5**	**13.7**	66.5	37.3
adversarial training	Flow-GAN (ADV)	155.6	216.9	71.1	-
	WGAN	6.7	21.5	**55.2**	41.3
	WGAN GP	20.3	24.5	55.8	**30.0**
	Best default GAN	~ 10	~ 32	~ 70	~ 48
AE based	SWAE(Wu et al., 2019)	-	-	107.9	48.9
	SWAE(Kolouri et al., 2018)	29.8	74.3	141.9	53.9
	CWAE	23.6	57.1	120.0	49.7
	PAE	-	28.0	-	49.2
	two-stage VAE	12.6	29.3	96.1	44.4

Table 2. Comparison between SIG and GIS

Model	SIG	GIS
Initial PDF p_1	Gaussian	p_{data}
Final PDF p_2	p_{data}	Gaussian
Training	Iteratively maps Gaussian to p_{data}	Iteratively maps p_{data} to Gaussian
NF structure	Yes	Yes
Advantage	Good samples	Good density estimation

random axes, and it also leads to better sample quality. This is because as the dimensionality d grows, the number of slices $(\mathcal{R}p)(\cdot, \theta)$ required to approximate $p(x)$ using inverse Radon formula scales as L^{d-1} (Kolouri et al., 2015), where L is the number of slices needed to approximate a similar smooth 2D distribution. Therefore, if θ are randomly chosen, it takes a large number of iterations to converge in high dimensions due to the curse of dimensionality. Our objective function reduces the curse of dimensionality in high dimensions by identifying the most relevant directions.

Unlike KL-divergence which is invariant under flow transformations, max K-SWD is different in data space and in latent space. Therefore the direction of building the flow model is of key importance. In the next two sections we discuss two different ways of building the flow, which are good at sample generation and density estimation, respectively.

3.3. Sliced Iterative Generator (SIG)

For Sliced Iterative Generator (SIG) p_1 is a standard Normal distribution, and p_2 is the target distribution. The model iteratively maps the Normal distribution to the target distribution using 1D slice transformations. Specifically, one firstly draw a set of samples from the standard Normal dis-

tribution, and then iteratively updates the samples following Equation 5. SIG directly minimizes the max K-SWD between the generated distribution and the target distribution, and is able to generate high quality samples.

3.4. Gaussianizing Iterative Slicing (GIS)

For Gaussianizing Iterative Slicing (GIS) p_1 is the target distribution and p_2 is a standard Normal distribution. The model iteratively Gaussianizes the target distribution, and the mapping is learned in the reverse direction of SIG. In GIS the max K-SWD between latent data and the Normal distribution is minimized, thus the model performs well in density estimation, even though its objective is not $p(x)$. A comparison between SIG and GIS is shown in Table 2.

4. Experiments

4.1. Density estimation $p(x)$ of small datasets

We perform density estimation with GIS on four UCI datasets (Lichman et al., 2013) and BSDS300 (Martin et al., 2001). The data preprocessing of UCI datasets and BSDS300 follows Papamakarios et al. (2017). We vary the size of the training set N_{train} from 10^2 to 10^5 to test the model performance on a wide range of dataset size. In Figure 1 we compare GIS to other NF models GF (Meng et al., 2020), FFJORD (Grathwohl et al., 2018), MAF (Papamakarios et al., 2017) and RQ-NSF (AR)(Durkan et al., 2019), as well as KDE. Some non-GIS NF models collapsed during training or used more memory than our GPU, and are not shown in the plot. The results in Figure 1 show that GIS is more stable compared to other NFs and outperforms them on small training sets. This highlights that GIS is less sensitive to hyper-parameter optimization and achieves good performance out of the box. Training time varies with data size, but is generally lower than other NFs on small datasets.

(a) POWER (6D)

(b) GAS (8D)

(c) HEPMASS (21D)

(d) MINIBOONE (43D)

(e) BSDS300 (63D)

Figure 1. Density estimation versus training set size. The legend in panel (a) applies to other panels as well. Higher is better: at 100-1000 training size GIS has the best performance in all cases.

4.2. Generative modeling of images

We evaluate SIG as a generative model of images using the following 4 datasets: MNIST (LeCun et al., 1998), Fashion-MNIST (Xiao et al., 2017), CIFAR-10 (Krizhevsky et al., 2009) and Celeb-A (Liu et al., 2015). In Figure 2 we show samples of these four datasets. For MNIST, Fashion-MNIST and CelebA dataset we show samples from the model with reduced temperature $T = 0.85$ (i.e., sampling from a Gaussian distribution with standard deviation $T = 0.85$ in latent space), which slightly improves the sample quality (Parmar et al., 2018; Kingma & Dhariwal, 2018). We report the final FID score (calculated using temperature T=1) in Table 1, where we compare our results with similar algorithms SWF (Liutkus et al., 2018) and Flow-Gan (ADV) (Grover et al., 2018). We also list the FID scores of some other generative models for comparison, including models using slice-based distance SWAEs (Wu et al., 2019; Kolouri et al., 2018) and CWAE (Knop et al., 2018), Wasserstein GAN models (Arjovsky et al., 2017; Gulrajani et al., 2017), and other GANs and AE-based models PAE (Böhm & Seljak, 2020) and two-stage VAE (Dai & Wipf, 2019; Xiao et al., 2019). We notice that previous iterative algorithms were unable to produce good samples on high dimensional image datasets.

(a) MNIST (T=0.85)

(b) Fashion-MNIST (T=0.85)

(c) CIFAR-10 (T=1)

(d) CelebA (T=0.85)

Figure 2. Random samples from SIG.

In contrast, SIG obtains the best FID scores on MNIST and Fashion-MNIST, while on CIFAR-10 and CelebA it also outperforms similar algorithms and AE-based models, and gets comparable results with GANs.

5. Conclusions

We introduce sliced iterative normalizing flow (SINF) that iteratively transforms data distribution to a Gaussian (GIS) or the other way around (SIG) using OT. To the best of our knowledge, SIG is the first greedy deep learning algorithm that is competitive with the SOTA generators in high dimensions, while GIS achieves comparable results on density estimation with current NF models, but is more stable, faster to train, and achieves higher $p(x)$ when trained on small training sets even though it does not train on $p(x)$. SINF has very few hyperparameters, and is very insensitive to their choice. SINF is related to several previous models, which is discussed in Appendix. SINF has deep neural network architecture, but its approach deviates significantly from the current Deep Learning paradigm, as it does not use concepts such as mini-batching, stochastic gradient descent and gradient back-propagation through deep layers. SINF is an existence proof that greedy Deep Learning without these ingredients can be SOTA for modern high dimensional ML applications. SINF may be of particular interest in applications where robustness, insensitivity to hyperparameters, small data size, and speed are of primary importance.

References

Arjovsky, M. and Bottou, L. Towards principled methods for training generative adversarial networks. *arXiv preprint arXiv:1701.04862*, 2017.

Arjovsky, M., Chintala, S., and Bottou, L. Wasserstein gan. *arXiv preprint arXiv:1701.07875*, 2017.

Böhm, V. and Seljak, U. Probabilistic auto-encoder. *arXiv preprint arXiv:2006.05479*, 2020.

Chen, S. S. and Gopinath, R. A. Gaussianization. In *Advances in neural information processing systems*, pp. 423–429, 2001.

Choi, H., Jang, E., and Alemi, A. A. Waic, but why? generative ensembles for robust anomaly detection. *arXiv preprint arXiv:1810.01392*, 2018.

Cramér, H. and Wold, H. Some theorems on distribution functions. *Journal of the London Mathematical Society*, 1(4):290–294, 1936.

Dai, B. and Wipf, D. Diagnosing and enhancing vae models. *arXiv preprint arXiv:1903.05789*, 2019.

Deshpande, I., Zhang, Z., and Schwing, A. G. Generative modeling using the sliced wasserstein distance. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3483–3491, 2018.

Deshpande, I., Hu, Y.-T., Sun, R., Pyrros, A., Siddiqui, N., Koyejo, S., Zhao, Z., Forsyth, D., and Schwing, A. G. Max-sliced wasserstein distance and its use for gans. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 10648–10656, 2019.

Dinh, L., Krueger, D., and Bengio, Y. Nice: Non-linear independent components estimation. *arXiv preprint arXiv:1410.8516*, 2014.

Dinh, L., Sohl-Dickstein, J., and Bengio, S. Density estimation using real nvp. *arXiv preprint arXiv:1605.08803*, 2016.

Durkan, C., Bekasov, A., Murray, I., and Papamakarios, G. Neural spline flows. In *Advances in Neural Information Processing Systems*, pp. 7509–7520, 2019.

Goodfellow, I., Pouget-Abadie, J., Mirza, M., Xu, B., Warde-Farley, D., Ozair, S., Courville, A., and Bengio, Y. Generative adversarial nets. In *Advances in neural information processing systems*, pp. 2672–2680, 2014.

Grathwohl, W., Chen, R. T., Bettencourt, J., Sutskever, I., and Duvenaud, D. Ffjord: Free-form continuous dynamics for scalable reversible generative models. *arXiv preprint arXiv:1810.01367*, 2018.

Gregory, J. and Delbourgo, R. Piecewise rational quadratic interpolation to monotonic data. *IMA Journal of Numerical Analysis*, 2(2):123–130, 1982.

Grover, A., Dhar, M., and Ermon, S. Flow-gan: Combining maximum likelihood and adversarial learning in generative models. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Gulrajani, I., Ahmed, F., Arjovsky, M., Dumoulin, V., and Courville, A. C. Improved training of wasserstein gans. In *Advances in neural information processing systems*, pp. 5767–5777, 2017.

Helgason, S. *Integral geometry and Radon transforms*. Springer Science & Business Media, 2010.

Kingma, D. P. and Dhariwal, P. Glow: Generative flow with invertible 1x1 convolutions. In *Advances in Neural Information Processing Systems*, pp. 10215–10224, 2018.

Kingma, D. P. and Welling, M. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Knop, S., Tabor, J., Spurek, P., Podolak, I., Mazur, M., and Jastrzębski, S. Cramer-wold autoencoder. *arXiv preprint arXiv:1805.09235*, 2018.

Kolouri, S., Park, S. R., and Rohde, G. K. The radon cumulative distribution transform and its application to image classification. *IEEE transactions on image processing*, 25(2):920–934, 2015.

Kolouri, S., Pope, P. E., Martin, C. E., and Rohde, G. K. Sliced-wasserstein autoencoder: An embarrassingly simple generative model. *arXiv preprint arXiv:1804.01947*, 2018.

Kolouri, S., Nadjahi, K., Simsekli, U., Badeau, R., and Rohde, G. Generalized sliced wasserstein distances. In *Advances in Neural Information Processing Systems*, pp. 261–272, 2019.

Krizhevsky, A., Hinton, G., et al. Learning multiple layers of features from tiny images. 2009.

Lake, B. M., Salakhutdinov, R., and Tenenbaum, J. B. Human-level concept learning through probabilistic program induction. *Science*, 350(6266):1332–1338, 2015.

Laparra, V., Camps-Valls, G., and Malo, J. Iterative gaussianization: from ica to random rotations. *IEEE transactions on neural networks*, 22(4):537–549, 2011.

LeCun, Y., Bottou, L., Bengio, Y., and Haffner, P. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Lichman, M. et al. Uci machine learning repository, 2013.

Liu, Z., Luo, P., Wang, X., and Tang, X. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, December 2015.

Liutkus, A., Şimşekli, U., Majewski, S., Durmus, A., and Stöter, F.-R. Sliced-wasserstein flows: Nonparametric generative modeling via optimal transport and diffusions. *arXiv preprint arXiv:1806.08141*, 2018.

Martin, D., Fowlkes, C., Tal, D., and Malik, J. A database of human segmented natural images and its application to evaluating segmentation algorithms and measuring ecological statistics. In *Proceedings Eighth IEEE International Conference on Computer Vision. ICCV 2001*, volume 2, pp. 416–423. IEEE, 2001.

Meng, C., Ke, Y., Zhang, J., Zhang, M., Zhong, W., and Ma, P. Large-scale optimal transport map estimation using projection pursuit. In *Advances in Neural Information Processing Systems 32*. 2019.

Meng, C., Song, Y., Song, J., and Ermon, S. Gaussianization flows. *arXiv preprint arXiv:2003.01941*, 2020.

Nadjahi, K., Durmus, A., Chizat, L., Kolouri, S., Shahrampour, S., and Simsekli, U. Statistical and topological properties of sliced probability divergences. *Advances in Neural Information Processing Systems*, 33, 2020.

Nalisnick, E., Matsukawa, A., Teh, Y. W., Gorur, D., and Lakshminarayanan, B. Do deep generative models know what they don't know? *arXiv preprint arXiv:1810.09136*, 2018.

Nguyen, K., Ho, N., Pham, T., and Bui, H. Distributional sliced-wasserstein and applications to generative modeling. *arXiv preprint arXiv:2002.07367*, 2020a.

Nguyen, K., Nguyen, S., Ho, N., Pham, T., and Bui, H. Improving relational regularized autoencoders with spherical sliced fused gromov wasserstein. *arXiv preprint arXiv:2010.01787*, 2020b.

Papamakarios, G., Pavlakou, T., and Murray, I. Masked autoregressive flow for density estimation. In *Advances in Neural Information Processing Systems*, pp. 2338–2347, 2017.

Parmar, N., Vaswani, A., Uszkoreit, J., Kaiser, Ł., Shazeer, N., Ku, A., and Tran, D. Image transformer. *arXiv preprint arXiv:1802.05751*, 2018.

Pitié, F., Kokaram, A. C., and Dahyot, R. Automated colour grading using colour distribution transfer. *Computer Vision and Image Understanding*, 107(1-2):123–137, 2007.

Radford, A., Metz, L., and Chintala, S. Unsupervised representation learning with deep convolutional generative adversarial networks. *arXiv preprint arXiv:1511.06434*, 2015.

Ren, J., Liu, P. J., Fertig, E., Snoek, J., Poplin, R., Depristo, M., Dillon, J., and Lakshminarayanan, B. Likelihood ratios for out-of-distribution detection. In *Advances in Neural Information Processing Systems*, pp. 14680–14691, 2019.

Rezende, D. J. and Mohamed, S. Variational inference with normalizing flows. *arXiv preprint arXiv:1505.05770*, 2015.

Rezende, D. J., Mohamed, S., and Wierstra, D. Stochastic backpropagation and approximate inference in deep generative models. *arXiv preprint arXiv:1401.4082*, 2014.

Salimans, T., Karpathy, A., Chen, X., and Kingma, D. P. Pixelcnn++: Improving the pixelcnn with discretized logistic mixture likelihood and other modifications. *arXiv preprint arXiv:1701.05517*, 2017.

Tagare, H. D. Notes on optimization on stiefel manifolds. In *Technical report, Technical report*. Yale University, 2011.

Tolstikhin, I., Bousquet, O., Gelly, S., and Schoelkopf, B. Wasserstein auto-encoders. *arXiv preprint arXiv:1711.01558*, 2017.

Wu, J., Huang, Z., Acharya, D., Li, W., Thoma, J., Paudel, D. P., and Gool, L. V. Sliced wasserstein generative models. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3713–3722, 2019.

Xiao, H., Rasul, K., and Vollgraf, R. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms, 2017.

Xiao, Z., Yan, Q., Chen, Y., and Amit, Y. Generative latent flow: A framework for non-adversarial image generation. *arXiv preprint arXiv:1905.10485*, 2019.

Xiao, Z., Yan, Q., and Amit, Y. Likelihood regret: An out-of-distribution detection score for variational auto-encoder. *arXiv preprint arXiv:2003.02977*, 2020.

A. Radon transform

Let $\mathbb{L}^1(X)$ be the space of absolute integrable functions on X. The Radon transform $\mathcal{R} : \mathbb{L}^1(\mathbb{R}^d) \to \mathbb{L}^1(\mathbb{R} \times \mathbb{S}^{d-1})$ is defined as

$$(\mathcal{R}p)(t, \theta) = \int_{\mathbb{R}^d} p(x)\delta(t - \langle x, \theta \rangle)dx, \qquad (7)$$

where $\mathbb{S}^{d-1}$ denotes the unit sphere $\theta_1^2 + \cdots \theta_n^2 = 1$ in $\mathbb{R}^d$, $\delta(\cdot)$ is the Dirac delta function, and $\langle \cdot, \cdot \rangle$ is the standard inner product in $\mathbb{R}^d$. For a given θ, the function $(\mathcal{R}p)(\cdot, \theta) : \mathbb{R} \to \mathbb{R}$ is essentially the slice (or projection) of $p(x)$ on axis θ.

Note that the Radon transform $\mathcal{R}$ is invertible. Its inverse, also known as the filtered back-projection formula, is given by (Helgason, 2010; Kolouri et al., 2019)

$$\mathcal{R}^{-1}((\mathcal{R}p)(t, \theta))(x) = \int_{\mathbb{S}^{n-1}} ((\mathcal{R}p)(\cdot, \theta) * h)(\langle x, \theta \rangle)d\theta, \qquad (8)$$

where $*$ is the convolution operator, and the convolution kernel h has the Fourier transform $\hat{h}(k) = c|k|^{d-1}$. The inverse Radon transform provides a practical way to reconstruct the original function $p(x)$ using its 1D slices $(\mathcal{R}p)(\cdot, \theta)$, and is widely used in medical imaging. This inverse formula implies that if the 1D slices of two functions are the same in all axes, these two functions are identical. This is also known as Carmér-Wold theorem (Cramér & Wold, 1936).

B. max K-SWD

The optimization in max K-SWD is performed under the constraints that $\{\theta_1, \cdots, \theta_K\}$ are orthonormal vectors, or equivalently, $A^T A = I_K$ where $A = [\theta_1, \cdots, \theta_K]$ is the matrix whose i-th column vector is θ_i. Mathematically, the set of all possible A matrices is called Stiefel Manifold $V_K(\mathbb{R}^d) = \{A \in \mathbb{R}^{d \times K} : A^T A = I_K\}$. As suggested by Tagare (2011), the optimization of matrix A can be performed by doing gradient ascent on the Stiefel Manifold:

$$A_{(j+1)} = \left(I_d + \frac{\tau}{2}B_{(j)}\right)^{-1}\left(I_d - \frac{\tau}{2}B_{(j)}\right)A_{(j)}, \qquad (9)$$

where $A_{(j)}$ is the weight matrix at gradient descent iteration j (which is different from the iteration l of the algorithm), τ is the learning rate, which is determined by backtracking line search, $B = GA^T - AG^T$, and G is the negative gradient matrix $G = [-\frac{\partial \mathcal{F}}{\partial A_{p,q}}] \in \mathbb{R}^{d \times K}$. Equation 9 has the properties that $A_{(j+1)} \in V_K(\mathbb{R}^d)$, and that the tangent vector $\frac{dA_{(j+1)}}{d\tau}|_{\tau=0}$ is the projection of gradient $[\frac{\partial \mathcal{F}}{\partial A_{p,q}}]$ onto $T_{A_{(j)}}(V_K(\mathbb{R}^d))$ (the tangent space of $V_K(\mathbb{R}^d)$ at $A_{(j)}$) under the canonical inner product (Tagare, 2011).

However, Equation 9 requires the inversion of a $d \times d$ matrix, which is computationally expensive in high dimensions.

Algorithm 2 max K-SWD

Input: $\{x_i \sim p_1\}_{i=1}^N$, $\{y_i \sim p_2\}_{i=1}^N$, K, order p, max iteration J_{maxiter}
Randomly initialize $A \in V_K(\mathbb{R}^d)$
for $j = 1$ to J_{maxiter} **do**
  Initialize $D = 0$
  for $k = 1$ to K **do**
    $\theta_k = A[:, k]$
    Compute $\hat{x}_i = \theta_k \cdot x_i$ and $\hat{y}_i = \theta_k \cdot y_i$ for each i
    Sort $\hat{x}_i$ and $\hat{x}_j$ in ascending order s.t. $\hat{x}_{i[n]} \leq \hat{x}_{i[n+1]}$ and $\hat{y}_{j[n]} \leq \hat{y}_{j[n+1]}$
    $D = D + \frac{1}{KN}\sum_{i=1}^N |\hat{x}_{i[n]} - \hat{y}_{j[n]}|^p$
  end for
  $G = [-\frac{\partial D}{\partial A_{i,j}}]$, $U = [G, A]$, $V = [A, -G]$
  Determine learning rate τ with backtracking line search
  $A = A - \tau U(I_{2K} + \frac{\tau}{2}V^T U)^{-1}V^T A$
  if A has converged **then**
    Early stop
  end if
end for
Output: $D^{\frac{1}{p}} \approx \max\text{-}K\text{-}SW_p$, $A \approx [\theta_1, \cdots, \theta_K]$

The matrix inversion can be simplified using the Sherman-Morrison-Woodbury formula, which results in the following equation (Tagare, 2011):

$$A_{(j+1)} = A_{(j)} - \tau U_{(j)}(I_{2K} + \frac{\tau}{2}V_{(j)}^T U_{(j)})^{-1}V_{(j)}^T A_{(j)}, \qquad (10)$$

where $U = [G, A]$ (the concatenation of columns of G and W) and $V = [A, -G]$. Equation 10 only involves the inversion of a $2K \times 2K$ matrix, where K is the number of axes to apply marginal transformation in each iteration. For high dimensional data (e.g. images), we use a relatively small K to avoid the inversion of large matrices. A large K leads to faster training, but one would converge to similar results with a small K using more iterations.

The procedure for estimating max K-SWD and A is summarized in Algorithm 2.

Proposition 1. *Let $P_p(\Omega)$ be the set of Borel probability measures with finite p'th moment on metric space (Ω, d). The maximum K-sliced p-Wasserstein distance is a metric over $P_p(\Omega)$.*

Proof. We firstly prove the triangle inequality. Let μ_1, μ_2 and μ_3 be probability measures in $P_p(\Omega)$ with probability density function p_1, p_2 and p_3, respectively. Let $\{\theta_1^*, \cdots, \theta_K^*\} = \arg\max_{\{\theta_1, \cdots, \theta_K\}\text{ orthonormal}}$

$\left(\frac{1}{K}\sum_{k=1}^{K}W_p^p((\mathcal{R}p_1)(\cdot,\theta_k),(\mathcal{R}p_3)(\cdot,\theta_k))\right)^{\frac{1}{p}}$; then

$$\text{max-}K\text{-}SW_p(p_1,p_3)$$
$$=\max_{\{\theta_1,\cdots,\theta_K\}\text{ orthonormal}}$$
$$\left(\frac{1}{K}\sum_{k=1}^{K}W_p^p((\mathcal{R}p_1)(\cdot,\theta_k),(\mathcal{R}p_3)(\cdot,\theta_k))\right)^{\frac{1}{p}}$$
$$=\left(\frac{1}{K}\sum_{k=1}^{K}W_p^p((\mathcal{R}p_1)(\cdot,\theta_k^*),(\mathcal{R}p_3)(\cdot,\theta_k^*))\right)^{\frac{1}{p}}$$
$$\leq\left(\frac{1}{K}\sum_{k=1}^{K}[W_p((\mathcal{R}p_1)(\cdot,\theta_k^*),(\mathcal{R}p_2)(\cdot,\theta_k^*))\right.$$
$$\left.+W_p((\mathcal{R}p_2)(\cdot,\theta_k^*),(\mathcal{R}p_3)(\cdot,\theta_k^*))]^p\right)^{\frac{1}{p}}$$
$$\leq\left(\frac{1}{K}\sum_{k=1}^{K}W_p^p((\mathcal{R}p_1)(\cdot,\theta_k^*),(\mathcal{R}p_2)(\cdot,\theta_k^*))\right)^{\frac{1}{p}} \quad (11)$$
$$+\left(\frac{1}{K}\sum_{k=1}^{K}W_p^p((\mathcal{R}p_2)(\cdot,\theta_k^*),(\mathcal{R}p_3)(\cdot,\theta_k^*))\right)^{\frac{1}{p}}$$
$$\leq\max_{\{\theta_1,\cdots,\theta_K\}\text{ orthonormal}}$$
$$\left(\frac{1}{K}\sum_{k=1}^{K}W_p^p((\mathcal{R}p_1)(\cdot,\theta_k),(\mathcal{R}p_2)(\cdot,\theta_k))\right)^{\frac{1}{p}}$$
$$+\max_{\{\theta_1,\cdots,\theta_K\}\text{ orthonormal}}$$
$$\left(\frac{1}{K}\sum_{k=1}^{K}W_p^p((\mathcal{R}p_2)(\cdot,\theta_k),(\mathcal{R}p_3)(\cdot,\theta_k))\right)^{\frac{1}{p}}$$
$$=\text{max-}K\text{-}SW_p(p_1,p_2)+\text{max-}K\text{-}SW_p(p_2,p_3),$$

where the first inequality comes from the triangle inequality of Wasserstein distance, and the second inequality follows Minkowski inequality. Therefore $\text{max-}K\text{-}SW_p$ satisfies the triangle inequality.

Now we prove the identity of indiscernibles. For any probability measures μ_1 and μ_2 in $P_p(\Omega)$ with probability density function p_1 and p_2, let
$\hat{\theta}=\arg\max_{\theta\in\mathbb{S}^{d-1}}W_p((\mathcal{R}p_1)(\cdot,\theta),(\mathcal{R}p_2)(\cdot,\theta))$, and
$\{\theta_1^*,\cdots,\theta_K^*\}=\arg\max_{\{\theta_1,\cdots,\theta_K\}\text{ orthonormal}}$

$\left(\frac{1}{K}\sum_{k=1}^{K}W_p^p((\mathcal{R}p_1)(\cdot,\theta_k),(\mathcal{R}p_2)(\cdot,\theta_k))\right)^{\frac{1}{p}}$, we have

$$\text{max-}K\text{-}SW_p(p_1,p_2)$$
$$=\left(\frac{1}{K}\sum_{k=1}^{K}W_p^p((\mathcal{R}p_1)(\cdot,\theta_k^*),(\mathcal{R}p_2)(\cdot,\theta_k^*))\right)^{\frac{1}{p}}$$
$$\leq\left(\frac{1}{K}\sum_{k=1}^{K}W_p^p((\mathcal{R}p_1)(\cdot,\hat{\theta}),(\mathcal{R}p_2)(\cdot,\hat{\theta}))\right)^{\frac{1}{p}} \quad (12)$$
$$=W_p((\mathcal{R}p_1)(\cdot,\hat{\theta}),(\mathcal{R}p_2)(\cdot,\hat{\theta}))$$
$$=\text{max-}SW_p(p_1,p_2).$$

On the other hand, let $\{\hat{\theta},\tilde{\theta}_2,\cdots,\tilde{\theta}_K\}$ be a set of orthonormal vectors in $\mathbb{S}^{d-1}$ where the first element is $\hat{\theta}$, we have

$$\text{max-}K\text{-}SW_p(p_1,p_2)$$
$$=\left(\frac{1}{K}\sum_{k=1}^{K}W_p^p((\mathcal{R}p_1)(\cdot,\theta_k^*),(\mathcal{R}p_2)(\cdot,\theta_k^*))\right)^{\frac{1}{p}}$$
$$\geq\left(\frac{1}{K}W_p^p((\mathcal{R}p_1)(\cdot,\hat{\theta}),(\mathcal{R}p_2)(\cdot,\hat{\theta}))\right.$$
$$\left.+\frac{1}{K}\sum_{k=2}^{K}W_p^p((\mathcal{R}p_1)(\cdot,\tilde{\theta}_k),(\mathcal{R}p_2)(\cdot,\tilde{\theta}_k))\right)^{\frac{1}{p}} \quad (13)$$
$$\geq\left(\frac{1}{K}W_p^p((\mathcal{R}p_1)(\cdot,\hat{\theta}),(\mathcal{R}p_2)(\cdot,\hat{\theta}))\right)^{\frac{1}{p}}$$
$$=(\frac{1}{K})^{\frac{1}{p}}\text{max-}SW_p(p_1,p_2).$$

Therefore we have $(\frac{1}{K})^{\frac{1}{p}}\text{max-}SW_p(p_1,p_2)\leq$ $\text{max-}K\text{-}SW_p(p_1,p_2)\leq\text{max-}SW_p(p_1,p_2)$. Thus $\text{max-}K\text{-}SW_p(p_1,p_2)=0\Leftrightarrow\text{max-}SW_p(p_1,p_2)=0\Leftrightarrow\mu_1=\mu_2$, where we use the non-negativity and identity of indiscernibles of $\text{max-}SW_p$.

Finally, the symmetry of $\text{max-}K\text{-}SW_p$ can be proven using the fact that p-Wasserstein distance is symmetric:

$$\text{max-}K\text{-}SW_p(p_1,p_2)$$
$$=\left(\frac{1}{K}\sum_{k=1}^{K}W_p^p((\mathcal{R}p_1)(\cdot,\theta_k^*),(\mathcal{R}p_2)(\cdot,\theta_k^*))\right)^{\frac{1}{p}}$$
$$=\left(\frac{1}{K}\sum_{k=1}^{K}W_p^p((\mathcal{R}p_2)(\cdot,\theta_k^*),(\mathcal{R}p_1)(\cdot,\theta_k^*))\right)^{\frac{1}{p}} \quad (14)$$
$$=\text{max-}K\text{-}SW_p(p_2,p_1).$$

$\square$

C. More details of SINF

C.1. Inverse and Jacobian determinant

The SINF transformation of Equation 5 can be easily inverted:

$$X_l = A_l \Psi_l^{-1}(A_l^T X_{l+1}) + X_l^\perp, \qquad (15)$$

where $X_l^\perp = X_l - A_l A_l^T X_l = X_{l+1} - A_l A_l^T X_{l+1}$. The Jacobian determinant of the transformation is also efficient to calculate:

$$\det\left(\frac{\partial X_{l+1}}{\partial X_l}\right) = \prod_{k=1}^{K} \frac{d\Psi_{lk}(x)}{dx}. \qquad (16)$$

Proof of Equation 16. Let $\{\theta_1, \cdots, \theta_K, \cdots, \theta_d\}$ be a set of orthonormal basis in $\mathcal{R}^d$ where the first K vectors are $\theta_1, \cdots, \theta_K$, respectively. Let $R_l = [\theta_1, \cdots, \theta_d]$ be an orthogonal matrix whose i-th column vector is θ_i, $U_l = [\theta_{K+1}, \cdots, \theta_d]$. Since $A_l = [\theta_1, \cdots, \theta_K]$, we have $R_l = [A_l, U_l]$ (the concatenation of columns of A and U). Let $\mathbf{I}^{d-K} = [\mathrm{id}_1, \cdots, \mathrm{id}_{d-K}]^T$ be a marginal transformation that consists of $d - K$ 1D identity transformation, $\hat{\Psi}_l = \begin{bmatrix} \Psi_l \\ \mathbf{I}^{d-K} \end{bmatrix}$, we have

$$
\begin{aligned}
X_{l+1} &= A_l \Psi_l(A_l^T X_l) + X_l - A_l A_l^T X_l \\
&= A_l \Psi_l(A_l^T X_l) + R_l R_l^T X_l - A_l A_l^T X_l \\
&= A_l \Psi_l(A_l^T X_l) + [A_l, U_l] \begin{bmatrix} A_l^T \\ U_l^T \end{bmatrix} X_l - A_l A_l^T X_l \\
&= A_l \Psi_l(A_l^T X_l) + U_l U_l^T X_l \\
&= A_l \Psi_l(A_l^T X_l) + U_l \mathbf{I}^{d-K}(U_l^T X_l) \\
&= [A_l, U_l] \begin{bmatrix} \Psi_l \\ I^{d-K} \end{bmatrix} ([A_l, U_l]^T X_l) \\
&= R_l \hat{\Psi}_l(R_l^T X_l).
\end{aligned}
\qquad (17)
$$

Since R_l is an orthogonal matrix with determinant ± 1, and the Jacobian of the marginal transformation $\hat{\Psi}_l$ is diagonal, the Jacobian determinant of the above equation can be written as

$$
\begin{aligned}
\det\left(\frac{\partial X_{l+1}}{\partial X_l}\right) &= \prod_{k=1}^{K} \frac{d\Psi_{lk}(x)}{dx} \cdot \prod_{k=1}^{d-K} \frac{d(\mathrm{id}_k(x))}{dx} \\
&= \prod_{k=1}^{K} \frac{d\Psi_{lk}(x)}{dx}.
\end{aligned}
\qquad (18)
$$

$\square$

C.2. Objective

At iteration l, the objective of SINF can be written as:

$$\mathcal{F}_l = \min_{\{\Psi_{l1}, \cdots, \Psi_{lK}\}} \max_{\{\theta_{l1}, \cdots, \theta_{lK}\} \text{ orthonormal}}$$

$$\left(\frac{1}{K} \sum_{k=1}^{K} W_p^p(\Psi_{lk}((\mathcal{R}p_{1,l})(\cdot, \theta_{lk})), (\mathcal{R}p_2)(\cdot, \theta_{lk})) \right)^{\frac{1}{p}}. \quad (19)$$

The algorithm firstly optimize θ_{lk} to maximize the objective, with Ψ_{lk} fixed to identical transformations (equivalent to Equation 4). Then the axes θ_{lk} are fixed and the objective is minimized with marginal matching Ψ_l. The samples are updated, and this process repeats until convergence.

C.3. Monotonic Rational Quadratic Spline

Monotonic Rational Quadratic Splines (Gregory & Delbourgo, 1982; Durkan et al., 2019) approximate the function in each bin with the quotient of two quadratic polynomials. They are monotonic, continuously differentiable, and can be inverted analytically. The splines are parametrized by the coordinates and derivatives of M knots: $\{(x_m, y_m, y'_m)\}_{m=1}^{M}$, with $x_{m+1} > x_m$, $y_{m+1} > y_m$ and $y'_m > 0$. Given these parameters, the function in bin m can be written as (Durkan et al., 2019)

$$y = y_m + (y_{m+1} - y_m) \frac{s_m \xi^2 + y'_m \xi(1-\xi)}{s_m + \sigma_m \xi(1-\xi)}, \qquad (20)$$

where $s_m = (y_{m+1} - y_m)/(x_{m+1} - x_m)$, $\sigma_m = y'_{m+1} + y'_m - 2s_m$ and $\xi = (x - x_m)/(x_{m+1} - x_m)$. The derivative is given by

$$\frac{dy}{dx} = \frac{s_m^2[y'_{m+1}\xi^2 + 2s_m\xi(1-\xi) + y'_m(1-\xi)^2]}{[s_m + \sigma_m \xi(1-\xi)]^2}. \qquad (21)$$

Finally, the inverse can be calculated with

$$x = x_m + (x_{m+1} - x_m)\frac{2c}{-b - \sqrt{b^2 - 4ac}}, \qquad (22)$$

where $a = (s_m - y'_m) + \zeta\sigma_m$, $b = y'_m - \zeta\sigma_m$, $c = -s_m\zeta$ and $\zeta = (y - y_m)/(y_{m+1} - y_m)$. The derivation of these formula can be found in Appendix A of Durkan et al. (2019).

In our algorithm the coordinates of the knots are determined by the quantiles of the marginalized PDF (see Algorithm 1). The derivative y'_m ($1 < m < M$) is determined by fitting a local quadratic polynomial to the neighboring knots (x_{m-1}, y_{m-1}), (x_m, y_m), and (x_{m+1}, y_{m+1}):

$$y'_m = \frac{s_{m-1}(x_{m+1} - x_m) + s_m(x_m - x_{m-1})}{x_{m+1} - x_{m-1}}. \qquad (23)$$

The function outside $[x_1, x_M]$ is linearly extrapolated with slopes y'_1 and y'_M. In SIG, y'_1 and y'_M are fixed to 1, while in GIS they are fitted to the samples that fall outside $[x_1, x_M]$.

Figure 3. Illustration of the patch-based approach with $S = 4$, $p = 2$ and $q = 2$. At each iteration, different patches are modeled separately. The patches are randomly shifted in each iteration assuming periodic boundaries.

Figure 4. Illustration of the hierarchical modeling of an $S = 8$ image. The patch size starts from $q = 8$ and gradually decreases to $q = 2$.

We use $M = 400$ knots in SIG to interpolate each $\Psi_{l,k}$, while in GIS we set $M = \min(\sqrt{N_{\text{train}}}, 200)$. The performance is insensitive to these choices, as long as M is large enough to fully characterize the 1D transformation $\Psi_{l,k}$.

C.4. Patch-based hierarchical approach for SIG

Generally speaking, the neighboring pixels in images have stronger correlations than pixels that are far apart. This fact has been taken advantage by convolutional neural networks, which outperform Fully Connected Neural Networks (FCNNs) and have become standard building blocks in computer vision tasks. Like FCNNs, vanilla SIG and GIS make no assumption about the structure of the data and cannot model high dimensional images very well. Recently, Meng et al. (2020) proposed a patch-based approach, providing a different way to improve the modeling of the local correlations for NF models. The patch-based approach decomposes an $S \times S$ image into $p \times p$ patches, with $q \times q$ neighboring pixels in each patch ($S = pq$). In each iteration the marginalized distribution of each patch is modeled separately without considering the correlations between different patches. This approach effectively reduces the dimensionality from S^2 to q^2, at the cost of ignoring the long range correlations.

To reduce the effects of ignoring long range correlations,

we propose a hierarchical model. In SIG, we start from modeling the entire images, which corresponds to $q = S$ and $p = 1$. After some iterations the samples show correct structures, indicating the long range correlations have been modeled well. We then gradually decrease the patch size q until $q = 2$, which allows us to gradually focus on the smaller scales. Assuming a periodic boundary condition, we let the patches randomly shift in each iteration. If the patch size q does not divide S, we set $p = \lfloor S/q \rfloor$ and the rest of the pixels are kept unchanged.

C.5. Regularization of GIS

We add regularization to GIS for density estimation tasks to further improve the performance and reduce overfitting. The regularization is added in the following two aspects: 1) The weight matrix W_l is regularized by limiting the maximum number of iteration J_{maxiter} (see Algorithm 2). We set $J_{\text{maxiter}} = N/d$, where N is the number of training data and d is the dimensionality. Thus for very small datasets ($N/d \to 1$) the axes of marginal transformation are almost random. This has no effect on datasets of regular size. 2) The CDFs in Equation 6 are estimated using KDE, and the 1D marginal transformation is regularized with:

$$\tilde{\psi}_{l,k}(x) = (1 - \alpha)\psi_{l,k}(x) + \alpha x, \qquad (24)$$

where $\alpha \in [0, 1)$ is the regularization parameter. $\tilde{\psi}_{l,k}$ is the regularized transformation. As α increases, the performance improves, but more iterations are needed to converge. Thus α controls the trade-off between performance and speed.

D. Related work

Iterative normalizing flow models called RBIG (Chen & Gopinath, 2001; Laparra et al., 2011) are simplified versions of GIS, as they are based on a succession of rotations followed by 1D marginal Gaussianizations. Iterative Distribution Transfer (IDT) (Pitié et al., 2007) is a similar algorithm but does not require the base distribution to be a Gaussian. These models do not scale well to high dimensions because they do not have a good way of choosing the axes, and they are not competitive against modern NFs trained on $p(x)$ (Meng et al., 2020). Meng et al. (2019) use a similar algorithm Projection Pursuit Monge Map (PPMM) to construct OT maps. They propose to find the most informative axis using Projection Pursuit (PP) in each iteration, and show that PPMM works well in low-dimensional bottleneck settings ($d = 8$). However, it has yet to be proven that PPMM scales to high dimensions, considering that PP scales as $\mathcal{O}(d^3)$. A DL, non-iterative version of these models is Gaussianization Flow (GF) (Meng et al., 2020), which trains on $p(x)$ and achieves good density estimation results in low dimensions, but does not have good sampling properties in high dimensions. RBIG, GIS and GF have similar

architectures but are trained differently. We compare their density estimation results in Section 4.1.

Another iterative generative model is Sliced Wasserstein Flow (SWF) (Liutkus et al., 2018). Similar to SIG, SWF tries to minimize the SWD between the distributions of samples and the data, and transforms this problem into solving a d dimensional PDE. The PDE is solved iteratively by doing a gradient flow in the Wasserstein space, and they show SWF works well for low dimensional bottleneck features. However, in each iteration the algorithm requires evaluating an integral over the d dimensional unit sphere approximated with Monte Carlo integration, which does not scale well to high dimensions. Another difference with SIG is that SWF does not have a flow structure, cannot be inverted, and does not provide the likelihood. We compare the sample qualities between SWF and SIG in Section 4.2.

SWD, max SWD and other slice-based distance (e.g. Cramér-Wold distance) have been widely used in training generative models (Deshpande et al., 2018; 2019; Wu et al., 2019; Kolouri et al., 2018; Knop et al., 2018; Nguyen et al., 2020b;a; Nadjahi et al., 2020). Wu et al. (2019) propose a differentiable SWD block composed of a rotation followed by marginalized Gaussianizations, but unlike RBIG, the rotation matrix is trained in an end-to-end DL fashion. They propose Sliced Wasserstein AutoEncoder (SWAE) by adding SWD blocks to an AE to regularize the latent variables, and show that its sample quality outperforms VAE and AE + RBIG. Nguyen et al. (2020b;a) generalize the max-sliced approach using parametrized distributions over projection axes. Nguyen et al. (2020b) propose Mixture Spherical Sliced Fused Gromov Wasserstein (MSSFG), which samples the slice axes around a few informative directions following Von Mises-Fisher distribution. They apply MSSFG to training Deterministic Relational regularized AutoEncoder (DRAE) and name it mixture spherical DRAE (ms-DRAE). Nguyen et al. (2020a) go further and propose Distributional Sliced Wasserstein distance (DSW), which tries to find the optimal axes distribution by parametrizing it with a neural network. They apply DSW to the training of GANs, and we will refer to their model as DSWGAN in this paper. We compare the sample qualities between SWAE, ms-DRAE, DSWGAN and SIG in Section 4.2.

Grover et al. (2018) propose Flow-GAN using a NF as the generator of a GAN, so the model can perform likelihood evaluation, and allows both maximum likelihood and adversarial training. Similar to our work they find that adversarial training gives good samples but poor $p(x)$, while training by maximum likelihood results in bad samples. Similar to SIG, the adversarial version of Flow-GAN minimizes the Wasserstein distance between samples and data, and has a NF structure. We compare their samples in Section 4.2.

Figure 5. Gaussian noise (first column), Fashion-MNIST (top panel) and CelebA (bottom) samples at different iterations.

Figure 6. Middle: interpolations between CelebA samples from SIG. Left and right: the corresponding nearest training data.

E. Other experiments

E.1. Density estimation of full datasets

We perform density estimation with GIS on four UCI datasets (Lichman et al., 2013) and BSDS300 (Martin et al., 2001), as well as image datasets MNIST (LeCun et al., 1998) and Fashion-MNIST (Xiao et al., 2017). The data preprocessing of UCI datasets and BSDS300 follows Papamakarios et al. (2017). In Table 3 we compare our results with RBIG (Laparra et al., 2011) and GF (Meng et al., 2020). The former can be seen as GIS with random axes to apply 1D gaussianization, while the latter can be seen as training non-iterative GIS with MLE training on $p(x)$. We also list other NF models Real NVP (Dinh et al., 2016), Glow (Kingma & Dhariwal, 2018), FFJORD (Grathwohl et al., 2018), MAF (Papamakarios et al., 2017) and RQ-NSF (AR)(Durkan et al., 2019) for comparison.

We observe that RBIG performs significantly worse than current SOTA. GIS outperforms RBIG and is the first iterative algorithm that achieves comparable performance compared to maximum likelihood models. This is even more impressive given that GIS is not trained on $p(x)$, yet it outperforms GF on $p(x)$ on GAS, BSDS300 and Fashion-MNIST.

E.2. More samples from SIG

In Figure 5 we show the SIG samples at different iterations. In Figure 6 we display interpolations between SIG samples, and the nearest training data, to verify we are not memorizing the training data.

Table 3. Negative test log-likelihood for tabular datasets measured in nats, and image datasets measured in bits/dim (lower is better).

	Method	POWER	GAS	HEPMASS	MINIBOONE	BSDS300	MNIST	Fashion
iterative	RBIG	1.02	0.05	24.59	25.41	-115.96	1.71	4.46
	GIS (this work)	-0.32	-10.30	19.00	14.26	-155.75	1.34	3.22
maximum likelihood	GF	-0.57	-10.13	17.59	10.32	-152.82	1.29	3.35
	Real NVP	-0.17	-8.33	18.71	13.55	-153.28	1.06	2.85
	Glow	-0.17	-8.15	18.92	11.35	-155.07	1.05	2.95
	FFJORD	-0.46	-8.59	14.92	10.43	-157.40	0.99	-
	MAF	-0.30	-10.08	17.39	11.68	-156.36	1.89	-
	RQ-NSF (AR)	-0.66	-13.09	14.01	9.22	-157.31	-	-

Table 4. OoD detection accuracy quantified by the AUROC of data $p(x)$ trained on Fashion-MNIST.

Method	MNIST	OMNIGLOT
SIG (this work)	**0.980**	**0.993**
GIS (this work)	0.824	0.891
PixelCNN++	0.089	-
IWAE	0.423	0.568

Figure 7. Fashion-MNIST samples before (left panel) and after SIG improvement (right panel). Top: SWF. Middle: Flow-GAN (ADV). Bottom: MAF.

E.3. Out of Distribution (OoD) detection

OoD detection with generative models has recently attracted a lot of attention, since the $\log p$ estimates of NF and VAE have been shown to be poor OoD detectors: different generative models can assign higher probabilities to OoD data than to In Distribution (InD) training data (Nalisnick et al., 2018). One combination of datasets for which this has been observed is Fashion-MNIST and MNIST, where a model trained on the former assigns higher density to the latter.

SINF does not train on the likelihood $p(x)$, which is an advantage for OoD. Likelihood is sensitive to the smallest variance directions (Ren et al., 2019): for example, a zero variance pixel leads to an infinite $p(x)$, and noise must be added to regularize it. But zero variance directions contain little or no information on the global structure of the image. SINF objective is more sensitive to the meaningful global structures that can separate between OoD and InD. Because the patch based approach ignores the long range correlations and results in bad OoD, we use vanilla SINF without patch based approach. We train the models on F-MNIST, and then evaluate anomaly detection on test data of MNIST and OMNIGLOT (Lake et al., 2015). In Table 4 we compare our results to maximum likelihood $p(x)$ models PixelCNN++(Salimans et al., 2017; Ren et al., 2019), and IWAE (Choi et al., 2018). Other models that perform well include VIB and WAIC (Choi et al., 2018), which achieve 0.941, 0.943 and 0.766, 0.796, for MNIST

and OMNIGLOT, respectively (below our SIG results). For the MNIST case Ren et al. (2019) obtained 0.996 using the likelihood ratio between the model and its perturbed version, but they require fine-tuning on some additional OoD dataset, which may not be available in OoD applications. Lower dimensional latent space PAE (Böhm & Seljak, 2020) achieves 0.997 and 0.981 for MNIST and OMNIGLOT, respectively, while VAE based likelihood regret (Xiao et al., 2020) achieves 0.988 on MNIST, but requires additional (expensive) processing.

E.4. Improving the samples of other generative models

Since SIG is able to transform any base distribution to the target distribution, it can also be used as a "Plug-and-Play" tool to improve the samples of other generative models. To demonstrate this, we train SWF, Flow-GAN(ADV) and MAF(5) on Fashion-MNIST with the default architectures in their papers, and then we apply 240 SIG iterations (30% of the total number of iterations in Section 4.2) to improve the sample quality. In Figure 7 we compare the samples before and after SIG improvement. Their FID scores improve from 207.6, 216.9 and 81.2 to 23.9, 21.2 and 16.6, respectively. These results can be further improved by adding more SIG iterations.