Improved Imaging by Invex Regularizers
with Global Optima Guarantees

Abstract

Image reconstruction enhanced by regularizers, e.g., to enforce sparsity, low rank or smoothness priors on images, has many successful applications in vision tasks such as computer photography, biomedical and spectral imaging. It has been well accepted that non-convex regularizers normally perform better than convex ones in terms of the reconstruction quality. But their convergence analysis is only established to a critical point, rather than the global optima. To mitigate the loss of guarantees for global optima, we propose to apply the concept of *invexity* and provide the first list of proved invex regularizers for improving image reconstruction. Moreover, we establish convergence guarantees to global optima for various advanced image reconstruction techniques after being improved by such invex regularization. To the best of our knowledge, this is the first practical work applying invex regularization to improve imaging with global optima guarantees. To demonstrate the effectiveness of invex regularization, numerical experiments are conducted for various imaging tasks using benchmark datasets.

1 Introduction

Image reconstruction (restoration) enhanced by regularizers has a wide application in vision tasks such as computed tomography [1, 2], optical imaging [3, 4], magnetic resonance imaging [5, 6], computer photography [7, 8], biomedical and spectral imaging [9, 10]. In general, an image reconstruction task can be formulated as the solution of the following optimization problem:

$$\underset{\boldsymbol{x} \in \mathbb{R}^n}{\text{minimize}} \quad F(\boldsymbol{x}) = f(\boldsymbol{x}) + g(\boldsymbol{x}). \tag{1}$$

Here $f(\boldsymbol{x})$ models a data fidelity term, which usually corresponds to an error loss for image reconstruction, and is assumed to be differentiable. The other function $g(\boldsymbol{x})$ acts as a regularizer which can be non-smooth. It imposes image priors such as sparsity, low rank or smoothness [11]. The use of an appropriate regularizer plays an important role in obtaining robust reconstruction results.

Convex regularization has been popular in the last decade [11, 12, 13, 14, 15], because it can result in guaranteed global optima. The most well-known examples include the ℓ_1-norm and nuclear norm, which are the continuous and convex surrogates of the ℓ_0-pseudo norm and rank, respectively [16]. Although convex regularizers have demonstrated their success in signal/image processing, biomedical informatics and computer vision applications [13, 17, 18, 19], they are suboptimal in many cases, as they promote sparsity and low rank only under very limited conditions (more measurements from the scene are needed [20, 21]). To address such limitations, non-convex regularizers have been proposed. For instance, several interpolations between the ℓ_0-pseudonorm and the ℓ_1-norm have been explored including the ℓ_p-quasinorms (where $0 < p < 1$) [22], Capped-ℓ_1 penalty [23], Log-Sum Penalty [20], Minimax Concave Penalty [24], Geman Penalty [25]. However, these non-convex regularizers unfortunately come with the price of losing global optima guarantees.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Table 1: Comparison between the assumptions made in this work for $f(\boldsymbol{x})$, and $g(\boldsymbol{x})$ to be optimized in Eq. (1) and the most common/successful assumptions in the state-of-the-art.

Method name	Assumption	Global optimizer
IRLS [33, 34]	special f and g	No
General descent [35, 36]	Kurdyka-Łojasiewicz	No
GIST [37]	nonconvex f, $g = g_1 - g_2$, g_1, g_2 convex	No
iPiano [38]	nonconvex f, convex g	No
Proposed	convex f, invex g	**Yes**

Image reconstruction methods based on Eq. (1) include model-based approaches that directly solve Eq. (1) using well-established optimization techniques, e.g., proximal operators and gradient descent rules [26, 27, 28], learning-based approaches that train an inference neural network [29, 30], as well as hybrid approaches that draw links between iterative signal processing algorithms and the layer-wise neural network architectures [31, 32]. Many of these exploit non-convex assumptions over $f(\boldsymbol{x})$ and/or $g(\boldsymbol{x})$, for which we present a summary of some commonly used or successful ones in Table 1. The table includes algorithms like the iterative reweighted least squares (IRLS) [33, 34], where the regularizer is a composition between the one-dimensional ℓ_p-quasinorm and the trace of a matrix. In [35, 36], the objective function $F(\boldsymbol{x})$ is assumed to form a semi-algebraic or tame optimization problem solved by gradient descent algorithms. In [37], the regularizer $g(\boldsymbol{x})$ is assumed to be the subtraction of two convex functions, and the general iterative shrinkage and thresholding (GIST) algorithm is proposed to optimize $F(\boldsymbol{x})$. Lastly, [38] assumes non-convex $f(\boldsymbol{x})$ but convex $g(\boldsymbol{x})$ and proposes the inertial proximal (iPiano) algorithm for optimization.

For algorithms with the convexity assumptions removed, e.g., those in Table 1, their convergence analysis unfortunately can only be established for a critical point. Ideally, we always prefer algorithms that can find the optimal solution for the target problem. One way to mitigate the loss of guarantees for global optima is by revisiting the concept of *invexity* which was first introduced by Hanson [39], Craven and Glover [40] in the 1980s. What makes this class of functions special is that, for any point where the derivative of a function vanishes (stationary point), it is a global minimizer of the function. Convexity is a special case of invexity. Since 1990s, a lot of mathematical implications for invex functions have been developed, but with the lack of practical applications [41]. Examples of the few successful works implementing the invexity theory include [42, 43, 44]. To the best of our knowledge, there is no existing work on the application of invex regularization for imaging.

In this paper, we focus on image reconstruction problems formulated in the form of Eq. (1), where the data fidelity term $f(\boldsymbol{x})$ is based on the ℓ_2-norm and an invex regularizer $g(\boldsymbol{x})$ is used. Most invex theory research lacks clarity on how to benefit practical applications, and this does not encourage the practitioners to exploit the invex property [41]. We aim at filling this gap by providing for the first time concrete and useful invex optimization formulations for imaging applications.

Specifically, we make the following contribution:

- Provide the first list of regularizers with proved invexity that fits optimization problems for imaging applications.

- Establish convergence guarantees to global optima for three types of advanced image reconstruction techniques enhanced by invex reguarlizers.

- Empirically demonstrate the effectiveness of invex regularization for various imaging tasks.

2 Preliminaries

Throughout this paper, we use boldface lowercase and uppercase letters for vectors and matrices, respectively. The i-th entry of a vector $\boldsymbol{w}$, is $\boldsymbol{w}[i]$. For vectors, $\|\boldsymbol{w}\|_p$ is the ℓ_p-norm. An open ball is defined as $B(\boldsymbol{x}; r) = \{\boldsymbol{y} \in \mathbb{R}^n : \|\boldsymbol{y} - \boldsymbol{x}\|_2 < r\}$. The operation $\mathrm{conv}(\mathcal{A})$ represents the convex hull of the set $\mathcal{A}$, and the operation $\mathrm{sign}(w)$ returns the sign of w. We use $\sigma_i(\boldsymbol{W})$ to denote the i-th singular value of $\boldsymbol{W}$ assumed in descending order.

We present several concepts needed for the development of this paper starting with the definition of a locally Lipschitz continuous function.

Definition 1 (Locally Lipschitz Continuity). A function $f : \mathbb{R}^n \to \mathbb{R}$ is locally Lipschitz continuous at a point $\boldsymbol{x} \in \mathbb{R}^n$ if there exist scalars $K > 0$ and $\epsilon > 0$ such that

$$|f(\boldsymbol{y}) - f(\boldsymbol{z})| \leq K\|\boldsymbol{y} - \boldsymbol{z}\|_2, \tag{2}$$

for all $\boldsymbol{y}, \boldsymbol{z} \in B(\boldsymbol{x}, \epsilon)$.

Since the ordinary directional derivative being the most important tool in optimization does not necessarily exist for locally Lipschitz continuous functions, it is required to introduce the concept of subdifferential [45] which is calculated in practice as follows.

Theorem 1 (Subdifferential). [45, Theorem 3.9] Let $f : \mathbb{R}^n \to \mathbb{R}$ be a locally Lipschitz continuous function at $\boldsymbol{x} \in \mathbb{R}^n$, and define $\Omega_f = \{\boldsymbol{x} \in \mathbb{R}^n | \text{ f is not differentiable at the point } \boldsymbol{x}\}$. Then the subdifferential of f is given by

$$\partial f(\boldsymbol{x}) = \text{ conv } \left(\{\boldsymbol{\zeta} \in \mathbb{R}^n | \text{ exists } (\boldsymbol{x}_i) \in \mathbb{R}^n \setminus \Omega_f \text{ such that } \boldsymbol{x}_i \to \boldsymbol{x} \text{ and } \nabla f(\boldsymbol{x}_i) \to \boldsymbol{\zeta}\}\right). \tag{3}$$

The notion of subdifferential is given for locally Lipschitz continuous functions because it is always nonempty [45, Theorem 3.3]. Based on these, the concept of invex function is presented as follows.

Definition 2 (Invexity). Let $f : \mathbb{R}^n \to \mathbb{R}$ be locally Lipschitz; then f is invex if there exists a function $\eta : \mathbb{R}^n \times \mathbb{R}^n \to \mathbb{R}^n$ such that

$$f(\boldsymbol{x}) - f(\boldsymbol{y}) \geq \boldsymbol{\zeta}^T \eta(\boldsymbol{x}, \boldsymbol{y}), \tag{4}$$

$\forall \boldsymbol{x}, \boldsymbol{y} \in \mathbb{R}^n, \forall \boldsymbol{\zeta} \in \partial f(\boldsymbol{y})$.

It is well known that a convex function simply satisfies this definition for $\eta(\boldsymbol{x}, \boldsymbol{y}) = \boldsymbol{x} - \boldsymbol{y}$.

The following classical theorem [46, Theorem 4.33] makes connection between an invex function and its well-known optimum property that supports the motivation of designing invex regularizers.

Theorem 2 (Invex Optimality). [46, Theorem 4.33]) Let $f : \mathbb{R}^n \to \mathbb{R}$ be locally Lipschitz. Then the following statements are equivalent.

1. f is invex.

2. Every point $\boldsymbol{y} \in \mathbb{R}^n$ that satisfies $\boldsymbol{0} \in \partial f(\boldsymbol{y})$ is a global minimizer of f.

3. Definition 2 is satisfied for $\eta : \mathbb{R}^n \times \mathbb{R}^n \to \mathbb{R}^n$ given by

$$\eta(\boldsymbol{x}, \boldsymbol{y}) = \begin{cases} \boldsymbol{0} & f(\boldsymbol{x}) \geq f(\boldsymbol{y}), \\ \frac{f(\boldsymbol{x}) - f(\boldsymbol{y})}{\|\boldsymbol{\zeta}_{\boldsymbol{y}}^*\|_2^2} \boldsymbol{\zeta}_{\boldsymbol{y}}^* & \text{otherwise,} \end{cases} \tag{5}$$

where $\boldsymbol{\zeta}_{\boldsymbol{y}}^*$ is an element in $\partial f(\boldsymbol{y})$ of minimum norm.

3 Invex Functions

We start this section by firstly presenting five examples of invex functions that are useful for imaging applications. Four of these have been labelled as non-convex in existing works. This is the first time that they are formally proved to be invex functions. We prove their invexity by showing they satisfy Statement 2 of Theorem 2 (see proof in supplementary material).

Lemma 1 (Invex Functions). All of the following functions are invex:

$$g(\boldsymbol{x}) = \sum_{i=1}^{n} \left(|\boldsymbol{x}[i]| + \epsilon\right)^p, \text{ for } p \in (0, 1) \text{ and } \epsilon \geq (p(1-p))^{\frac{1}{2-p}}, \tag{6}$$

$$g(\boldsymbol{x}) = \sum_{i=1}^{n} \log(1 + |\boldsymbol{x}[i]|), \tag{7}$$

$$g(\boldsymbol{x}) = \sum_{i=1}^{n} \frac{|\boldsymbol{x}[i]|}{2 + 2|\boldsymbol{x}[i]|}, \tag{8}$$

$$g(\boldsymbol{x}) = \sum_{i=1}^{n} \frac{\boldsymbol{x}^2[i]}{1 + \boldsymbol{x}^2[i]}, \tag{9}$$

$$g(\boldsymbol{x}) = \sum_{i=1}^{n} \log(1 + |\boldsymbol{x}[i]|) - \frac{|\boldsymbol{x}[i]|}{2 + 2|\boldsymbol{x}[i]|}. \tag{10}$$

Table 2 summarizes their applications. Specifically, Eq. (6) is known as quasinorm, and has attracted a lot of attention because it has resulted in theoretical improvements for matrix completion and compressive sensing [22, 47]. The analysis on the quasinorms is valid with and without the constant ϵ. We prefer to add ϵ in order to formally satisfy the Lipschitz continuity in Definition 1. Eqs. (7) and (8) enhance the convex ℓ_1-norm regularizer, and they have significantly improved image denoising [48]. Eq. (9) has been used as the loss function to improve support vector classification [49].

Table 2: List of invex functions studied in this work.

Reference	Invex function	Application
[22, 33, 50, 51]	Eq. (6)	Matrix completion
[20, 37, 52, 53]	Eq. (7)	Enhancing compressive sensing
[48, 54, 55]	Eq. (8)	Image denoising
[49]	Eq. (9)	Support vector classification
Proposed	Eq. (10)	Compressive sensing

We propose the last function in Eq. (10) by the subtraction between Eq. (7) and Eq. (8). This design is motivated by the optimization framework in [37] where the regularization term is assumed to be the subtraction of two convex functions (see GIST in Table 1). This has been found to be highly successful in imaging applications (see the survey [53]). But until now there is no evidence that this subtraction produces another convex function (if exists) potentially useful in imaging applications. Therefore, we propose this example to show that at least this is possible in the invex case.

Additionally, we present another way of constructing an invex function in the following lemma. It establishes that an invex function $f : \mathbb{R}^m \to \mathbb{R}$ composed with an affine mapping $\boldsymbol{Hx} - \boldsymbol{b}$ for $\boldsymbol{H} \in \mathbb{R}^{m \times n}$, $\boldsymbol{x} \in \mathbb{R}^n$ and $\boldsymbol{b} \in \mathbb{R}^m$, is also invex if $\boldsymbol{H}$ has full row rank.

Lemma 2 (Affine Invex Construction). Let $f : \mathbb{R}^m \to \mathbb{R}$ be a continuously differentiable invex function, $\boldsymbol{H} \in \mathbb{R}^{m \times n}$ have full row rank, and $\boldsymbol{b} \in \mathbb{R}^m$ be a vector. Then the function $h(\boldsymbol{x}) = f(\boldsymbol{Hx} - \boldsymbol{b})$ is invex.

Similar to Lemma 1, it is proved by showing that the composed function satisfies Statement 2 of Theorem 2 (see proof in supplementary material). Eq. (9) is an example of such an invex construction that satisfies the continuously differentiable assumption in Lemma 2. This is easily verified in the proof of Lemma 1. A practical implication of Lemma 2 for imaging applications appears when we want to solve linear system of equations (e.g. [49]). We demonstrate an application of this kind of invex construction in Section 4.2.2 to improve a widely used image reconstruction framework.

4 Invex Imaging Examples, Algorithms and Convergence Analysis

In this section, we demonstrate the use of invex regularizers to improve some advanced imaging methodologies. To benefit both practitioners and theory development, we present practical invex imaging algorithms and prove their convergence guarantees to global optima which was only possible for convex functions.

4.1 Image Denoising

Image denoising plays a critical role in modern signal processing systems since images are inevitably contaminated by noise during acquisition, compression, and transmission, leading to distortion and loss of image information [56]. Plenty of denoising methods exist, originating from a wide range of disciplines such as probability theory, statistics, partial differential equations, linear and nonlinear filtering, spectral and multiresolution analysis, also classical machine learning and deep learning [57, 58, 56]. All these methods rely on some explicit or implicit assumptions about the true (noise-free) signal in order to separate it properly from the random noise.

One of the most successful assumptions is that a signal can be well approximated by a linear combination of few basis elements in a transform domain [59, 60]. Under this assumption, a denoising method can be implemented as a two-step procedure: i) to obtain high-magnitude transform coefficients that convey mostly the true-signal energy, ii) to discard the transform coefficients which are mainly due to noise. Typical choices for the first step are the wavelet, cosine transforms, and

principal component analysis (PCA) [59, 60, 61]. The second step is seen as a filtering procedure that is formally modelled as a proximal optimization problem [62]

$$\text{Prox}_g(\boldsymbol{u}) = \underset{\boldsymbol{x} \in \mathbb{R}^n}{\arg\min} \left(g(\boldsymbol{x}) + \frac{1}{2}\|\boldsymbol{x} - \boldsymbol{u}\|_2^2 \right), \tag{11}$$

where $g(\boldsymbol{x})$ acts as a regularization term, and $\boldsymbol{u}$ represents the noisy transform coefficients. In fact, the usefulness of Eq. (11) is not just limited to denoising, but other imaging problems like computer tomography [63], optical imaging [64], biomedical and spectral imaging [65]. In general, global optima guarantees in Eq. (11) is restricted to convex $g(\boldsymbol{x})$, e.g., ℓ_1-norm.

We improve this important proximal operator by incorporating invex regularizers. Specifically, using those invex functions $g(\boldsymbol{x})$ as listed in Table 2, global minimization is achieved in Eq. (11). The result is presented in the following theorem:

Theorem 3 (Invex Proximal). Consider the optimization problem in Eq. (11) for all functions in Table 2. Then the following holds:

1. The function $h(\boldsymbol{x}) = g(\boldsymbol{x}) + \frac{1}{2}\|\boldsymbol{x} - \boldsymbol{u}\|_2^2$ is convex (therefore invex).

2. The resolvent operator of the proximal is $(\mathbf{I} + \partial g)^{-1}$ and it is treated as a singleton because it always maps to a global optimizer.

It is classically known that the sum of two invex functions is not necessarily invex in general [46]. Therefore, presenting examples like above, where the sum of $f(\boldsymbol{x})$ and $g(\boldsymbol{x})$ is invex, is important to both invexity and imaging communities. We present the proof of Theorem 3 and provide the solution to Eq. (11) for each function in Table 2 in supplementary material.

4.2 Image Compressive Sensing

Image *compressive sensing* has been extensively exploited in areas such as microscopy, holography, optical imaging and spectroscopy [66, 67, 68]. It is an inverse problem that aims at recovering a signal $\boldsymbol{x} \in \mathbb{R}^n$ from its measurement data vector in the form of $\boldsymbol{b} = \boldsymbol{H}\boldsymbol{x}$, where $\boldsymbol{x}$ is k-sparse ($k \ll n$ non-zero elements) and $\boldsymbol{H} \in \mathbb{R}^{m \times n}$ is a unitary matrix ($m < n$). It enables to recover $\boldsymbol{x}$ using much lesser samples than what are predicted by the Nyquist criterion [69]. The task formulation is

$$\underset{\boldsymbol{x} \in \mathbb{R}^n}{\text{minimize}} \ f(\boldsymbol{x}) + \lambda g(\boldsymbol{x}) = \frac{1}{2}\|\boldsymbol{H}\boldsymbol{x} - \boldsymbol{b}\|_2^2 + \lambda g(\boldsymbol{x}), \tag{12}$$

where $\lambda \in (0, 1]$ is a typical choice in practice. When the regularizer $g(\boldsymbol{x})$ takes the convex form of ℓ_1-norm, and when the sampling matrix $\boldsymbol{H}$ satisfies the *restricted isometry property* (RIP) for any k-sparse vector $\boldsymbol{x} \in \mathbb{R}^n$, i.e., $(1 - \delta_{2k})\|\boldsymbol{x}\|_2^2 \leq \|\boldsymbol{H}\boldsymbol{x}\|_2^2 \leq (1 + \delta_{2k})\|\boldsymbol{x}\|_2^2$ for $\delta_{2k} < \frac{1}{3}$ [70, Theorem 6.9], it has been proved that $\boldsymbol{x}$ can be exactly recovered by solving Eq. (12) [71].

We are interested in invex regularizers. It has been proved that, when $g(\boldsymbol{x})$ takes the particular invex form in Eq. (6), $\boldsymbol{x}$ can be exactly recovered by solving Eq. (12) [47]. Below we further generalize this result to all the invex functions as listed in Table 2. The generalized result is presented in Theorem 4.

Theorem 4 (Invex Image Compressive Sensing). Assume $\boldsymbol{H}\boldsymbol{x} = \boldsymbol{b}$, where $\boldsymbol{x} \in \mathbb{R}^n$ is k-sparse, the unitary matrix $\boldsymbol{H} \in \mathbb{R}^{m \times n}$ ($m < n$) satisfies the RIP condition for any k-sparse vector, and $\boldsymbol{b} \in \mathbb{R}^m$ is a noiseless measurement vector. If $g(\boldsymbol{x})$ in Eq. (12) takes the form of the functions in Table 2, then the following holds:

1. The objective function $\frac{1}{2}\|\boldsymbol{H}\boldsymbol{x} - \boldsymbol{b}\|_2^2 + \lambda g(\boldsymbol{x})$ is invex.

2. $\boldsymbol{x}$ can be exactly recovered by solving Eq. (12) i.e. only global optimizers exist. When $g(\boldsymbol{x})$ takes the form of Eq. (9), extra mild conditions on $\boldsymbol{x}$ are needed.

The result is important to invex community. We present another proved form of function sum that can result in an invex function, i.e., the sum of $g(\boldsymbol{x})$ and the ℓ_2-norm composed with the affine mapping $\boldsymbol{H}\boldsymbol{x} - \boldsymbol{b}$. The complete proof is provided in supplementary material.

Next, we present different algorithms to solve Eq. (12) using invex $g(\boldsymbol{x})$ as in Table 2. We select a few of the most important and successful image reconstruction techniques to start from, and develop their invex extensions. Taking advantage of the invex property, we prove convergence to global minimizers for each extended algorithm, which is unexplored up to date.

Algorithm 1 Accelerated Proximal Gradient

1: **input**: Tolerance constant $\epsilon \in (0,1)$, initial point $\boldsymbol{x}^{(0)}$, and number of iterations T.
2: **initialize**: $\boldsymbol{x}^{(1)} = \boldsymbol{x}^{(0)} = \boldsymbol{z}^{(0)}, r_1 = 1, r_0 = 0, \alpha_1, \alpha_2 < \frac{1}{L}$, and $\lambda \in (0,1]$
3: **for** $t = 1$ to T **do**
4:      $\boldsymbol{y}^{(t)} = \boldsymbol{x}^{(t)} + \frac{r_{t-1}}{r_t}(\boldsymbol{z}^{(t)} - \boldsymbol{x}^{(t)}) + \frac{r_{t-1}-1}{r_t}(\boldsymbol{x}^{(t)} - \boldsymbol{x}^{(t-1)})$
5:      $\boldsymbol{z}^{(t+1)} = \text{prox}_{\alpha_2\lambda g}(\boldsymbol{y}^{(t)} - \alpha_2\nabla f(\boldsymbol{y}^{(t)}))$
6:      $\boldsymbol{v}^{(t+1)} = \text{prox}_{\alpha_1\lambda g}(\boldsymbol{x}^{(t)} - \alpha_1\nabla f(\boldsymbol{x}^{(t)}))$
7:      $r_{t+1} = \frac{\sqrt{4(r_t)^2+1}+1}{2}$
8:      $\boldsymbol{x}^{(t+1)} = \begin{cases} \boldsymbol{z}^{(t+1)}, & \text{if } f(\boldsymbol{z}^{(t+1)}) + \lambda g(\boldsymbol{z}^{(t+1)}) \leq f(\boldsymbol{v}^{(t+1)}) + \lambda g(\boldsymbol{v}^{(t+1)}) \\ \boldsymbol{v}^{(t+1)}, & \text{otherwise} \end{cases}$
9: **end for**
10: **return**: $\boldsymbol{x}^{(T)}$

4.2.1 Accelerated Proximal Gradient Algorithm

The accelerated proximal gradient (APG) method [72] has been shown to be effective solving Eq. (12), achieving better imaging quality in less iterations than its predecessors [13, 36, 37, 38, 73], and been frequently used by recent imaging works [55, 74, 75, 76]. Its convergence to global optima is only guaranteed for convex loss [72]. For non-convex cases, convergence to a critical point has been stated [72]. Its pseudo-code for solving Eq. (12) is provided in Algorithm 1.

Taking advantage that the loss function $f(\boldsymbol{x}) + \lambda g(\boldsymbol{x})$ in Eq. (12) is invex, and the uniqueness result in Theorem 3, we formally extend APG in the following lemma stating that the sequence $\{\boldsymbol{x}^{(t+1)}\}$ generated by Algorithm 1 converges to a global minimizer of Eq. (12).

Lemma 3 (Invex APG). Under the setup of Theorem 4 and using $L = \sigma_1\left(\boldsymbol{H}^T\boldsymbol{H}\right)$ (maximum singular value), the sequence $\{\boldsymbol{x}^{(t)}\}_{t=0}^{T-1}$ generated by Algorithm 1 converges to a global minimizer.

To prove Lemma 3, we apply the Statement 2 of Theorem 2 to Eq. (12) and the unicity of the proximal operators for functions in Table 2. The complete proof is provided in supplementary material.

4.2.2 Plug-and-play with Deep Denoiser Prior

Plug-and-play (PnP) is a powerful framework for regularizing imaging inverse problems [65] and has gained popularity in a range of applications in the context of imaging inverse problems [29, 65, 77, 78, 79]. It replaces the proximal operator in an iterative algorithm with an image denoiser, which does not necessarily have a corresponding regularization objective. This implies that the effectiveness of PnP goes beyond standard proximal algorithms such as primal-dual splitting [80, 81, 82]. It has guarantees to a fixed point only when convex objective functions are employed [81].

To apply the PnP framework, we modify Algorithm 1 by replacing the proximal operator (Line 6 in its pseudo-code) with a neural network based denoiser Noise2Void [58], resulting in

$$\boldsymbol{v}^{(t+1)} = \text{Noise2Void}\left(\boldsymbol{x}^{(t)} - \alpha_1\nabla f\left(\boldsymbol{x}^{(t)}\right)\right). \tag{13}$$

The complete pseudo-code is presented in supplemental material. Its output is a close estimation to the solution of Eq. (12) [81]. The benefit of using this denoiser is that it does not require clean target images in order to be trained. We present the following convergence result for this modified algorithm under the assumption of $f(\boldsymbol{x})$ in Eq. (12) being invex which is a generalization of [81] (restricted to convex functions only).

Lemma 4 (Invex Plug-and-play). Assume $f(\boldsymbol{x})$ in Eq. (12) is invex with Lipschitz continuous gradient, and a denoiser $d : \mathbb{R}^n \to \mathbb{R}$. Under the setup of Theorem 4 and some mild conditions on d, the sequence $\{\boldsymbol{x}^{(t)}\}_{t=0}^{T}$ generated by Algorithm 2 satisfies

$$\frac{1}{T}\sum_{t=1}^{T}\left\|\boldsymbol{x}^{(t)} - d\left(\boldsymbol{x}^{(t)} - \alpha_1\nabla f\left(\boldsymbol{x}^{(t)}\right)\right)\right\|_2^2 \leq \frac{2}{T}\left(\frac{1+\kappa}{1-\kappa}\right)\left\|\boldsymbol{x}^{(0)} - \boldsymbol{x}^*\right\|_2^2, \tag{14}$$

for any $\boldsymbol{x}^* = d(\boldsymbol{x}^* - \alpha_1\nabla f(\boldsymbol{x}^*))$ (fixed point) and for some $\kappa \in (0,1)$.

Eq. (14) guarantees that the sequence $\left\{\boldsymbol{x}^{(t)}\right\}_{t=0}^{T}$ is arbitrarily close to the set of fixed points of $d(\cdot)$ which can be considered as a close estimation to the solution of Eq. (12) [81]. Its proof is provided in the supplementary material. As an example, Eq. (9) satisfies the assumption required in Lemma 4.

4.2.3 Unrolling

The *unrolling* or *unfolding* framework is another imaging strategy for solving Eq. (12). It offers a systematic connection between iterative algorithms used in signal processing and the neural networks [31, 32, 83]. Unrolled neural networks become popular due to their potential in developing efficient and high-performing network architectures from reasonably sized training sets [84, 85]. A folded version of the proximal gradient algorithm is presented in Algorithm 2. Particularly, existing works [86, 87] have shown that the efficiency of Algorithm 2 can be improved by simulating a recurrent neural network so that its layers mimic the iterations in Line 4 of Algorithm 2. Specifically, each $\boldsymbol{x}^{(t+1)}$ constitutes one linear operation which models a layer of the network, followed by a proximal operation that models the activation function. Thus, one forms a deep network by mapping each iteration to a network layer and stacking the layers together to learn $\boldsymbol{H}, \alpha_t$, and $\boldsymbol{x}^{(t)}$ for all t which is equivalent to executing an iteration of Algorithm 2 multiple times. Their study was conducted only for $g(\boldsymbol{x})$ in the form of ℓ_1-norm.

Algorithm 2 Folded Proximal Gradient Algorithm

1: **input**: initial point $\boldsymbol{x}^{(0)}$, number of iterations T
2: **initialize**: $\alpha_t < \frac{2}{L+2}$, and $\lambda \in (0, 1]$
3: **for** $t = 0$ to T **do**
4: $\quad \boldsymbol{x}^{(t+1)} = \text{prox}_{\alpha_t \lambda g}(\boldsymbol{x}^{(t)} - \alpha_t \boldsymbol{H}^T(\boldsymbol{H}\boldsymbol{x}^{(t)} - \boldsymbol{b}))$
5: **end for**
6: **return:** $\boldsymbol{x}^{(T)}$

Convergence guarantees to global optima for Algorithm 2 has been established in [13], but it is restricted to convex objective functions. Therefore, due to the success and importance of unrolling we aim to extend the global optima guarantees of Algorithm 2 to invex objectives, and present the results in the following lemma:

Lemma 5 (Invex Unrolling). Under the setup of Theorem 4 and using $L = \sigma_1\left(\boldsymbol{H}^T\boldsymbol{H}\right)$ (maximum singular value) and $\alpha_t < \frac{2}{L+2}$, the sequence $\left\{\boldsymbol{x}^{(t)}\right\}_{t=0}^{T-1}$ generated by Algorithm 2 converges to a global minimizer.

The key to proving Lemma 5 relies on the uniqueness result of the proximal operator for invex functions in Table 2 as stated in Theorem 3. The proof is presented in supplementary material. Such results confirm that the invex unrolled network of Algorithm 2, which uses the proximal operators of invex mappings as the activation functions, can reach the optimal solution during training.

5 Experiments and Results

We conduct various experiments to study the performance of those invex regularizers as listed in Table 2 in non-ideal conditions. We compare them against the state-of-the-art methods originally developed for convex regularizers (ℓ_1-norm) ensuring global optima. When neural network training is involved, we take a total of 900 images which are randomly divided into a training set of 800 images, a validation set of 55 images, and a test set of 45 images. For all the experiments, the images are scaled into the range between 0 and 1. For the invex regularizer in Eq. (6), we vary the value of p.

5.1 Image Compressive Sensing Experiments

The DIV2K dataset for super-resolution [88], the McMaster [89], kodak datasets [90], the Berkeley Segmentation Data Set (BSDS 500) [91], Tampere Images (TID2013) [92] and the Color BSD68 dataset [93] are used. We assess signal reconstruction by averaging the peak-signal-to-noise-ratio (PSNR) in dB over the testing image set. We consider additive white Gaussian noise in the measurements data vector with three different levels of SNR (Signal-to-Noise Ratio) = 20, 30, and ∞

265 (noiseless case). For Algorithm 1 and its plug-and-play variant, the parameters λ, α_1, and α_2 were
266 chosen to be the best for each analyzed function determined by cross validation, and the initial point
267 $x^{(0)}$ was the blurred image b.

Table 3: Performance comparison where the best and least efficient among invex functions is highlighted in boldface and underscore, respectively.

Experiment 1, $p = 0.5$ for Eq. (6)						
SNR	m/n	**Eq. (6)**	Eq. (7)	Eq. (8)	Eq. (9)	Eq. (10)	ℓ_1-norm FISTA
∞	-	33.40	31.25	31.93	30.00	32.65	29.97
20dB	-	24.60	22.83	23.39	22.00	23.98	21.80
30dB	-	27.61	26.56	26.90	26.00	27.25	24.91
Experiment 2, $p = 0.8$ for Eq. (6)						
SNR	m/n	**Eq. (6)**	Eq. (7)	Eq. (8)	Eq. (9)	Eq. (10)	ℓ_1-norm
∞	-	34.51	32.37	33.06	31.40	33.76	31.10
20dB	-	25.55	23.92	24.44	23.00	24.98	22.95
30dB	-	28.30	26.87	27.33	26.05	27.80	26.00
Experiment 3, $p = 0.7$ for Eq. (6)						
SNR	m/n	**Eq. (6)**	Eq. (7)	Eq. (8)	Eq. (9)	Eq. (10)	ℓ_1-norm LISTA
	0.2	31.32	29.20	29.87	28.56	30.58	27.95
∞	0.4	36.10	33.50	34.34	32.75	35.20	32.01
	0.6	44.27	38.71	40.45	36.24	42.27	35.82
	0.2	26.00	24.45	24.94	23.97	25.01	23.52
20dB	0.4	32.67	30.64	31.32	30.02	32.29	29.43
	0.6	34.38	33.00	33.28	32.94	33.64	32.60
	0.2	27.65	26.20	26.66	25.75	27.15	25.32
30dB	0.4	34.33	31.89	32.66	31.02	33.47	30.46
	0.6	39.95	36.57	37.63	35.00	38.75	34.63
Denoising Experiment, $p = 0.5$ for Eq. (6)						
-	-	**Eq. (6)**	Eq. (8)	Eq. (10)	-	Noise2Void	ℓ_1-norm BM3D
-	-	49.40	43.85	46.46	-	39.43	41.52

268 **Experiment 1** studies the effect of different invex regularizers under Algorithm 1. A deconvolution
269 problem is studied to formulate Eq. (12) which is an important problem in signal processing due to
270 imperfect artefacts in physical setups such as mismatch, calibration errors, and loss of contrast [94].
271 To compare, the used state-of-the-art method that employs convex regularization to ensure global
272 optima is the fast iterative shrinkage-thresholding algorithm (FISTA) [13]. To model this problem, all
273 pixels of the testing set are fixed to 256×256 pixels. The images went through a Gaussian blur of size
274 9×9 and standard deviation 4, followed by an additive zero-mean white Gaussian noise. The sensing
275 matrix H is built as $H = RW$, where R represents the blur operator over the images and W is the
276 inverse of a three stage Haar wavelet transform. This experiment is extremely ill-conditioned, where
277 the condition number of $H^T H$ is significantly higher than 1. This means that in practice the RIP
278 condition is not guaranteed. To achieve a fair comparison, the number of iterations was fixed for all
279 functions as $T = 800$. The deconvolution problem follows a compressive sensing setup because the
280 Gaussian filter remove high frequency information of the input image. Therefore, the ratio $\frac{m}{n}$ is not
281 computed.

282 **Experiment 2** studies the invex regularizers under the plug-and-play modification of Algorithm 1 as
283 described in Section 4.2.2 [1] [58]. The same deconvolution problem as in Experiment 1 is used. The
284 interesting aspect of this scenario is that Algorithm 1 has a proximal step in Line 5 that allows to
285 compare between regularizers (invex and convex) while using neural networks. Noise2Void is trained
286 by randomly extracting patches of size 64×64 pixels from the training images where zero-mean
287 white Gaussian noise was added for $SNR = 20, 30$dB. Data augmentation on the training dataset is
288 used, by rotating each image three times by 90 and also added all mirrored versions. The learning
289 rate is fixed as 0.0004. The ratio $\frac{m}{n}$ is not computed.

290 **Experiment 3** compares the invex regularizers but under the unrolling framework as described in
291 Section 4.2.3. The gold standard convex regularization to compare with is the learned iterative
292 shrinkage and thresholding algorithm (LISTA) [87]. We follow the existing setting in [86] [2]. For
293 the training stage we extract 10000 patches $b \in \mathbb{R}^{16 \times 16}$ at random positions of each image, with all

---

[1] We used Noise2Void implementation at `https://github.com/juglab/n2v`
[2] We used the implementation from [86] at `https://github.com/VITA-Group/LISTA-CPSS`

means removed. We then learn a dictionary $\boldsymbol{D} \in \mathbb{R}^{256 \times 512}$ from the extracted patches, using the same strategy as in [86]. Gaussian i.i.d sensing matrices $\boldsymbol{\Phi} \in \mathbb{R}^{m \times 256}$ are created from the standard Gaussian distribution, $\boldsymbol{\Phi}[i, j] \sim \mathcal{N}(0, 1/m)$ and then normalize its columns to have the unit ℓ_2-norm, where m is selected such that $\frac{m}{256} = 0.2, 0.4, 0.6$. The matrix $\boldsymbol{H}$ is built as $\boldsymbol{H} = \boldsymbol{\Phi D}$ with $T = 16$ (number of layers). We follow the same two-step strategy in [86] to train a recurrent neural network. First, perform a layer-wise pre-training solving Eq. (12) for each extracted patch $\boldsymbol{b}$ by fixing $\boldsymbol{H} = \boldsymbol{D}$. Second, append a learnable fully-connected layer at the end of the network structure, initialized by $\boldsymbol{D}$. Then, perform an end-to-end training solving Eq. (12) where $\boldsymbol{H}$ in this case is learnt by updating the initial matrix $\boldsymbol{D}$. For each testing image, we divide it into non-overlapping 16×16 patches. When $g(\boldsymbol{x})$ is the the ℓ_1-norm, we recover [86].

Table 3 confirms performance improvement by using invex regularizers over the ℓ_1-norm. The best result is obtained with Eq. (6) (highlighted in boldface), and as expected from the proof of Theorem 4, Eq. (9) is the least efficient (highlight with an underscore). Table 3 and theoretical results in Section 4 revive the potential of exploring invex theory in practical applications.

5.2 Image Denoising Experiment

The image dataset (40 in total) used for this experiment comes from a neutron image formation phenomenon[3]. These type of images contain the neutron attenuation properties of the object which helps analyze material structure. Performance is assessed by averaging along all the images the experimental SNR in dB given by $SNR = 20 \log \left(\frac{\|\boldsymbol{z}\|_2}{\|\hat{\boldsymbol{z}} - \boldsymbol{z}\|_2} \right)$, where $\boldsymbol{z}$ and $\hat{\boldsymbol{z}}$ stand for the noisy and the denoised image, respectively. Taking advantage of results observed from Table 3, we compare the top three regularizers in Eqs. (6), (8), and (10) with two state-of-the-art denoising techniques including the block-matching and 3-D filtering (BM3D) [59] using ℓ_1-norm regularizer and the deep learning technique Noise2Void [58]. We follow the two-step denoising procedure described in Section 4.1. In the first step, the transform domain is built using PCA as in [61]. To build this transform we extract patches of 16×16 from the noisy image that are then used to adaptively construct a tight frame (nearly orthogonal matrix) tailored to the given noisy data [4]. We report in supplemental material the algorithm used for the invex regularizers to denoise these images.

Results are summarized in the end of Table 3. The best is obtained with Eq. (6) while Eq. (10) is the least efficient. Since we are analyzing all the regularizers under non-ideal scenarios due to noise, such results show the effectiveness of invex regularizers. Examples of denoised images obtained by Eqs. (6), (8), (10), BM3D, and Noise2Void are illustrated in the supplementary material.

6 Discussion and Conclusion

Application advancement of invex theory has paused for decades due to the lack of practical examples, which has caused a significantly reduced interest in invexity research. To address this issue, we present for the first time a list of invex regularizers for image reconstruction applications, and formulate corresponding optimization problems. Particularly, for image compressive sensing, we improve three advanced imaging techniques using the listed functions in Table 2 as invex regularizers. We present their solution algorithms and develop theoretical guarantees on their convergence to global minimum. We also conducted various image compressive sensing and denoising experiments to demonstrate the effectiveness of invex regularizers under practical scenarios that are non-ideal with noisy data observed and RIP condition not guaranteed. Significant benefit of using invex regularizers have been proved from both theoretical and empirical aspects. In fact, Table 3 and theoretical results in Section 4 revive the potential of exploring invex theory in practical applications.

Broader Impact

We believe that the presented mathematical and empirical analysis over the studied regularizers has the potential to unlock the benefits of invexity for further applications in signal and image processing. This may be an enabler to improve downstream tasks like deep learning for imaging, and to provide more robust image reconstruction algorithms.

---

[3]Acquired with the ISIS Neutron and Moun Source system at Harwell Science and Innovation Campus.

[4]We used implementation at `https://www.math.hkust.edu.hk/~jfcai/`.

References

[1] Emil Y Sidky, Jakob H Jørgensen, and Xiaochuan Pan. Convex optimization problem prototyping for image reconstruction in computed tomography with the chambolle–pock algorithm. *Physics in Medicine & Biology*, 57(10):3065, 2012.

[2] Haibo Zhang, Linqi Hai, Jiaojiao Kou, Yuqing Hou, Xiaowei He, Mingquan Zhou, and Guohua Geng. OPK_SNCA: Optimized prior knowledge via sparse non-convex approach for cone-beam x-ray luminescence computed tomography imaging. *Computer Methods and Programs in Biomedicine*, page 106645, 2022.

[3] Tim Meinhardt, Michael Moller, Caner Hazirbas, and Daniel Cremers. Learning proximal operators: Using denoising networks for regularizing inverse imaging problems. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 1781–1790, 2017.

[4] Manya V Afonso, José M Bioucas-Dias, and Mário AT Figueiredo. Fast image recovery using variable splitting and constrained optimization. *IEEE transactions on image processing*, 19(9):2345–2356, 2010.

[5] Matthias J Ehrhardt and Marta M Betcke. Multicontrast mri reconstruction with structure-guided total variation. *SIAM Journal on Imaging Sciences*, 9(3):1084–1106, 2016.

[6] Jeffrey A Fessler. Optimization methods for magnetic resonance image reconstruction: Key models and optimization algorithms. *IEEE signal processing magazine*, 37(1):33–40, 2020.

[7] Seyyed Reza Miri Rostami, Samuel Pinilla, Igor Shevkunov, Vladimir Katkovnik, and Karen Egiazarian. Power-balanced hybrid optics boosted design for achromatic extended depth-of-field imaging via optimized mixed OTF. *Applied Optics*, 60(30):9365–9378, 2021.

[8] Felix Heide, Mushfiqur Rouf, Matthias B Hullin, Bjorn Labitzke, Wolfgang Heidrich, and Andreas Kolb. High-quality computational imaging through simple lenses. *ACM Transactions on Graphics (TOG)*, 32(5):1–14, 2013.

[9] Lizhi Wang, Chen Sun, Ying Fu, Min H Kim, and Hua Huang. Hyperspectral image reconstruction using a deep spatial-spectral prior. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8032–8041, 2019.

[10] Cishen Zhang and Ifat-Al Baqee. Parallel magnetic resonance imaging reconstruction by convex optimization. In *Third International Conference on Innovative Computing Technology (INTECH 2013)*, pages 473–478. IEEE, 2013.

[11] Vishal Monga. *Handbook of Convex Optimization Methods in Imaging Science*, volume 1. Springer, 2017.

[12] Yuli Sun, Hao Chen, Jinxu Tao, and Lin Lei. Computed tomography image reconstruction from few views via log-norm total variation minimization. *Digital Signal Processing*, 88:172–181, 2019.

[13] Amir Beck and Marc Teboulle. A fast iterative shrinkage-thresholding algorithm for linear inverse problems. *SIAM journal on imaging sciences*, 2(1):183–202, 2009.

[14] Yunsong Liu, Zhifang Zhan, Jian-Feng Cai, Di Guo, Zhong Chen, and Xiaobo Qu. Projected iterative soft-thresholding algorithm for tight frames in compressed sensing magnetic resonance imaging. *IEEE transactions on medical imaging*, 35(9):2130–2140, 2016.

[15] Fernando Soldevila, P Clemente, Enrique Tajahuerce, N Uribe-Patarroyo, Pedro Andrés, and Jesús Lancis. Computational imaging with a balanced detector. *Scientific Reports*, 6(1):1–10, 2016.

[16] Yun Fu. *Low-rank and sparse modeling for visual analysis*. Springer, 2014.

[17] Shirish Krishnaj Shevade and S Sathiya Keerthi. A simple and efficient algorithm for gene selection using sparse logistic regression. *Bioinformatics*, 19(17):2246–2253, 2003.

[18] John Wright, Allen Y Yang, Arvind Ganesh, S Shankar Sastry, and Yi Ma. Robust face recognition via sparse representation. *IEEE transactions on pattern analysis and machine intelligence*, 31(2):210–227, 2008.

[19] Jieping Ye and Jun Liu. Sparse methods for biomedical data. *ACM Sigkdd Explorations Newsletter*, 14(1):4–15, 2012.

[20] Emmanuel J Candes, Michael B Wakin, and Stephen P Boyd. Enhancing sparsity by reweighted ℓ_1 minimization. *Journal of Fourier analysis and applications*, 14(5):877–905, 2008.

[21] Tong Zhang. Analysis of multi-stage convex relaxation for sparse regularization. *Journal of Machine Learning Research*, 11(3), 2010.

[22] Goran Marjanovic and Victor Solo. On ℓ_q optimization and matrix completion. *IEEE Transactions on signal processing*, 60(11):5714–5724, 2012.

[23] Zhihua Zhang, James T Kwok, and Dit-Yan Yeung. Surrogate maximization/minimization algorithms and extensions. *Machine Learning*, 69(1):1–33, 2007.

[24] Cun-Hui Zhang. Nearly unbiased variable selection under minimax concave penalty. *The Annals of statistics*, 38(2):894–942, 2010.

[25] Donald Geman and Chengda Yang. Nonlinear image recovery with half-quadratic regularization. *IEEE transactions on Image Processing*, 4(7):932–946, 1995.

[26] Amir Beck. *First-order methods in optimization*. SIAM, 2017.

[27] Jikai Jin, Bohang Zhang, Haiyang Wang, and Liwei Wang. Non-convex distributionally robust optimization: Non-asymptotic analysis. *Advances in Neural Information Processing Systems*, 34, 2021.

[28] Stefano Sarao Mannelli and Pierfrancesco Urbani. Analytical study of momentum-based acceleration methods in paradigmatic high-dimensional non-convex problems. *Advances in Neural Information Processing Systems*, 34, 2021.

[29] Kai Zhang, Yawei Li, Wangmeng Zuo, Lei Zhang, Luc Van Gool, and Radu Timofte. Plug-and-play image restoration with deep denoiser prior. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2021.

[30] Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep learning*. MIT press, 2016.

[31] Samuel Pinilla, Kumar Vijay Mishra, Igor Shevkunov, Mojtaba Soltanalian, Vladimir Katkovnik, and Karen Egiazarian. Unfolding-aided bootstrapped phase retrieval in optical imaging. *arXiv preprint arXiv:2203.01695*, 2022.

[32] Vishal Monga, Yuelong Li, and Yonina C Eldar. Algorithm unrolling: Interpretable, efficient deep learning for signal and image processing. *IEEE Signal Processing Magazine*, 38(2):18–44, 2021.

[33] Karthik Mohan and Maryam Fazel. Iterative reweighted algorithms for matrix rank minimization. *The Journal of Machine Learning Research*, 13(1):3441–3473, 2012.

[34] Peter Ochs, Alexey Dosovitskiy, Thomas Brox, and Thomas Pock. On iteratively reweighted algorithms for nonsmooth nonconvex optimization in computer vision. *SIAM Journal on Imaging Sciences*, 8(1):331–372, 2015.

[35] Hedy Attouch, Jérôme Bolte, and Benar Fux Svaiter. Convergence of descent methods for semi-algebraic and tame problems: proximal algorithms, forward–backward splitting, and regularized gauss–seidel methods. *Mathematical Programming*, 137(1):91–129, 2013.

[36] Pierre Frankel, Guillaume Garrigos, and Juan Peypouquet. Splitting methods with variable metric for kurdyka–łojasiewicz functions and general convergence rates. *Journal of Optimization Theory and Applications*, 165(3):874–900, 2015.

[37] Pinghua Gong, Changshui Zhang, Zhaosong Lu, Jianhua Huang, and Jieping Ye. A general iterative shrinkage and thresholding algorithm for non-convex regularized optimization problems. In *international conference on machine learning*, pages 37–45. PMLR, 2013.

[38] Peter Ochs, Yunjin Chen, Thomas Brox, and Thomas Pock. ipiano: Inertial proximal algorithm for nonconvex optimization. *SIAM Journal on Imaging Sciences*, 7(2):1388–1419, 2014.

[39] Morgan A Hanson. On sufficiency of the kuhn-tucker conditions. *Journal of Mathematical analysis and applications*, 80(2):545–550, 1981.

[40] Bruce D Craven and Barney M Glover. Invex functions and duality. *Journal of the Australian Mathematical Society*, 39(1):1–20, 1985.

[41] Constantin Zălinescu. A critical view on invexity. *Journal of Optimization Theory and Applications*, 162(3):695–704, 2014.

[42] Adarsh Barik and Jean Honorio. Fair sparse regression with clustering: An invex relaxation for a combinatorial problem. *Advances in Neural Information Processing Systems*, 34, 2021.

[43] Mujahid Syed, Panos Pardalos, and Jose Principe. Invexity of the minimum error entropy criterion. *IEEE Signal Processing Letters*, 20(12):1159–1162, 2013.

[44] Badong Chen, Lei Xing, Haiquan Zhao, Nanning Zheng, José C Prı, et al. Generalized correntropy for robust adaptive filtering. *IEEE Transactions on Signal Processing*, 64(13):3376–3387, 2016.

[45] Adil Bagirov, Napsu Karmitsa, and Marko M Mäkelä. *Introduction to Nonsmooth Optimization: theory, practice and software*. Springer, 2014.

[46] Shashi K Mishra and Giorgio Giorgi. *Invexity and optimization*, volume 88. Springer Science & Business Media, 2008.

[47] Rui Wu and Di-Rong Chen. The improved bounds of restricted isometry constant for recovery via ℓ_p-minimization. *IEEE transactions on information theory*, 59(9):6142–6147, 2013.

[48] Yongjun Wu, Guangjun Gao, and Can Cui. Improved wavelet denoising by non-convex sparse regularization under double wavelet domains. *IEEE Access*, 7:30659–30671, 2019.

[49] Zhenxun Zhuang, Ashok Cutkosky, and Francesco Orabona. Surrogate losses for online learning of stepsizes in stochastic non-convex optimization. In *International Conference on Machine Learning*, pages 7664–7672. PMLR, 2019.

[50] Haibo Zhang, Guohua Geng, Shunli Zhang, Kang Li, Cheng Liu, Yuqing Hou, and Xiaowei He. Sparse non-convex ℓ_p regularization for cone-beam x-ray luminescence computed tomography. *Journal of Modern Optics*, 65(20):2278–2289, 2018.

[51] Fan Lin, Yingpin Chen, Lingzhi Wang, Yuqun Chen, Wei Zhu, and Fei Yu. An efficient image reconstruction framework using total variation regularization with ℓ_p-quasinorm and group gradient sparsity. *Information*, 10(3):115, 2019.

[52] Quanming Yao and James Kwok. Efficient learning with a family of nonconvex regularizers by redistributing nonconvexity. In *International Conference on Machine Learning*, pages 2645–2654. PMLR, 2016.

[53] Fei Wen, Lei Chu, Peilin Liu, and Robert C Qiu. A survey on nonconvex regularization-based sparse and low-rank recovery in signal processing, statistics, and machine learning. *IEEE Access*, 6:69883–69906, 2018.

[54] Zhanxuan Hu, Feiping Nie, Rong Wang, and Xuelong Li. Low rank regularization: A review. *Neural Networks*, 136:218–232, 2021.

[55] Weina Wang and Yunmei Chen. An accelerated smoothing gradient method for nonconvex nonsmooth minimization in image processing. *Journal of Scientific Computing*, 90(1):1–28, 2022.

[56] Linwei Fan, Fan Zhang, Hui Fan, and Caiming Zhang. Brief review of image denoising techniques. *Visual Computing for Industry, Biomedicine, and Art*, 2(1):1–12, 2019.

[57] Mona Mahmoudi and Guillermo Sapiro. Fast image and video denoising via nonlocal means of similar neighborhoods. *IEEE signal processing letters*, 12(12):839–842, 2005.

[58] Alexander Krull, Tim-Oliver Buchholz, and Florian Jug. Noise2void-learning denoising from single noisy images. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2129–2137, 2019.

[59] Kostadin Dabov, Alessandro Foi, Vladimir Katkovnik, and Karen Egiazarian. Image denoising by sparse 3-d transform-domain collaborative filtering. *IEEE Transactions on image processing*, 16(8):2080–2095, 2007.

[60] Michael Elad and Michal Aharon. Image denoising via sparse and redundant representations over learned dictionaries. *IEEE Transactions on Image processing*, 15(12):3736–3745, 2006.

[61] Jian-Feng Cai, Hui Ji, Zuowei Shen, and Gui-Bo Ye. Data-driven tight frame construction and image denoising. *Applied and Computational Harmonic Analysis*, 37(1):89–105, 2014.

[62] Neal Parikh and Stephen Boyd. Proximal algorithms. *Foundations and Trends in optimization*, 1(3):127–239, 2014.

[63] Jakob S Jørgensen, Evelina Ametova, Genoveva Burca, Gemma Fardell, Evangelos Papoutsellis, Edoardo Pasca, Kris Thielemans, Martin Turner, Ryan Warr, William RB Lionheart, et al. Core imaging library-part i: a versatile python framework for tomographic imaging. *Philosophical Transactions of the Royal Society A*, 379(2204):20200192, 2021.

[64] Yu Sun, Shiqi Xu, Yunzhe Li, Lei Tian, Brendt Wohlberg, and Ulugbek S Kamilov. Regularized fourier ptychography using an online plug-and-play algorithm. In *ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 7665–7669. IEEE, 2019.

[65] Yu Sun, Brendt Wohlberg, and Ulugbek S Kamilov. An online plug-and-play algorithm for regularized image reconstruction. *IEEE Transactions on Computational Imaging*, 5(3):395–408, 2019.

[66] Gonzalo R Arce, David J Brady, Lawrence Carin, Henry Arguello, and David S Kittle. Compressive coded aperture spectral imaging: An introduction. *IEEE Signal Processing Magazine*, 31(1):105–115, 2013.

[67] Andrés Jerez, Samuel Pinilla, and Henry Arguello. Fast target detection via template matching in compressive phase retrieval. *IEEE Transactions on Computational Imaging*, 6:934–944, 2020.

[68] Andrés Guerrero, Samuel Pinilla, and Henry Arguello. Phase recovery guarantees from designed coded diffraction patterns in optical imaging. *IEEE Transactions on Image Processing*, 29:5687–5697, 2020.

[69] Emmanuel J Candès and Michael B Wakin. An introduction to compressive sampling. *IEEE signal processing magazine*, 25(2):21–30, 2008.

[70] Simon Foucart and Holger Rauhut. *A Mathematical Introduction to Compressive Sensing*. 2013.

[71] Emmanuel J Candès, Justin Romberg, and Terence Tao. Robust uncertainty principles: Exact signal reconstruction from highly incomplete frequency information. *IEEE Transactions on information theory*, 52(2):489–509, 2006.

[72] Huan Li and Zhouchen Lin. Accelerated proximal gradient methods for nonconvex programming. *Advances in neural information processing systems*, 28, 2015.

[73] Radu Ioan Boţ, Ernö Robert Csetnek, and Szilárd Csaba László. An inertial forward–backward algorithm for the minimization of the sum of two nonconvex functions. *EURO Journal on Computational Optimization*, 4(1):3–25, 2016.

[74] Trang C Mai, Hien Quoc Ngo, and Le-Nam Tran. Energy-efficient power allocation in cell-free massive mimo with zero-forcing: First order methods. *Physical Communication*, 51:101540, 2022.

[75] Jingxin Zhang, Donghua Zhou, Maoyin Chen, and Xia Hong. Continual learning for multimode dynamic process monitoring with applications to an ultra-supercritical thermal power plant. *IEEE transactions on Automation Science and Engineering*, 2022.

[76] Zhili Ge, Xin Zhang, and Zhongming Wu. A fast proximal iteratively reweighted nuclear norm algorithm for nonconvex low-rank matrix minimization problems. *Applied Numerical Mathematics*, 2022.

[77] Kaixuan Wei, Angelica Aviles-Rivero, Jingwei Liang, Ying Fu, Hua Huang, and Carola-Bibiane Schönlieb. TFPNP: Tuning-free plug-and-play proximal algorithms with applications to inverse imaging problems. *Journal of Machine Learning Research*, 23(16):1–48, 2022.

[78] Ulugbek S Kamilov, Charles A Bouman, Gregery T Buzzard, and Brendt Wohlberg. Plug-and-play methods for integrating physical and learned models in computational imaging. *arXiv preprint arXiv:2203.17061*, 2022.

[79] Yuyang Hu, Jiaming Liu, Xiaojian Xu, and Ulugbek S Kamilov. Monotonically convergent regularization by denoising. *arXiv preprint arXiv:2202.04961*, 2022.

[80] Shunsuke Ono. Primal-dual plug-and-play image restoration. *IEEE Signal Processing Letters*, 24(8):1108–1112, 2017.

[81] Ulugbek S Kamilov, Hassan Mansour, and Brendt Wohlberg. A plug-and-play priors approach for solving nonlinear imaging inverse problems. *IEEE Signal Processing Letters*, 24(12):1872–1876, 2017.

[82] Zhiyuan Zha, Bihan Wen, Xin Yuan, Jiantao Zhou, and Ce Zhu. Simultaneous nonlocal low-rank and deep priors for poisson denoising. In *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 2320–2324. IEEE, 2022.

[83] Qiyu Hu, Yunlong Cai, Qingjiang Shi, Kaidi Xu, Guanding Yu, and Zhi Ding. Iterative algorithm induced deep-unfolding neural networks: Precoding design for multiuser mimo systems. *IEEE Transactions on Wireless Communications*, 20(2):1394–1410, 2020.

[84] Arindam Chowdhury, Gunjan Verma, Chirag Rao, Ananthram Swami, and Santiago Segarra. Unfolding wmmse using graph neural networks for efficient power allocation. *IEEE Transactions on Wireless Communications*, 20(9):6004–6017, 2021.

[85] Naveed Naimipour, Shahin Khobahi, and Mojtaba Soltanalian. UPR: A model-driven architecture for deep phase retrieval. In *Asilomar Conference on Signals, Systems, and Computers*, pages 205–209, 2020.

[86] Xiaohan Chen, Jialin Liu, Zhangyang Wang, and Wotao Yin. Theoretical linear convergence of unfolded ista and its practical weights and thresholds. *Advances in Neural Information Processing Systems*, 31, 2018.

[87] Jialin Liu and Xiaohan Chen. Alista: Analytic weights are as good as learned weights in lista. In *International Conference on Learning Representations (ICLR)*, 2019.

[88] Eirikur Agustsson and Radu Timofte. Ntire 2017 challenge on single image super-resolution: Dataset and study. In *Proceedings of the IEEE conference on computer vision and pattern recognition workshops*, pages 126–135, 2017.

[89] Lei Zhang, Xiaolin Wu, Antoni Buades, and Xin Li. Color demosaicking by local directional interpolation and nonlocal adaptive thresholding. *Journal of Electronic imaging*, 20(2):023016, 2011.

[90] Kodak image dataset. `http://r0k.us/graphics/kodak/`. Accessed: 2022-05-05.

[91] D. Martin, C. Fowlkes, D. Tal, and J. Malik. A database of human segmented natural images and its application to evaluating segmentation algorithms and measuring ecological statistics. In *Proc. 8th Int'l Conf. Computer Vision*, volume 2, pages 416–423, July 2001.

[92] Nikolay Ponomarenko, Oleg Ieremeiev, Vladimir Lukin, Karen Egiazarian, Lina Jin, Jaakko Astola, Benoit Vozel, Kacem Chehdi, Marco Carli, Federica Battisti, et al. Color image database TID2013: Peculiarities and preliminary results. In *European workshop on visual information processing (EUVIP)*, pages 106–111. IEEE, 2013.

[93] David Martin, Charless Fowlkes, Doron Tal, and Jitendra Malik. A database of human segmented natural images and its application to evaluating segmentation algorithms and measuring ecological statistics. In *Proceedings Eighth IEEE International Conference on Computer Vision. ICCV 2001*, volume 2, pages 416–423. IEEE, 2001.

[94] Li-Hao Yeh, Jonathan Dong, Jingshan Zhong, Lei Tian, Michael Chen, Gongguo Tang, Mahdi Soltanolkotabi, and Laura Waller. Experimental robustness of fourier ptychography phase retrieval algorithms. *Optics Express*, 23(26):33214–33240, 2015.

[95] Rémi Gribonval and Morten Nielsen. Highly sparse representations from dictionaries are unique and independent of the sparseness measure. *Applied and Computational Harmonic Analysis*, 22(3):335–355, 2007.

[96] Joseph Woodworth and Rick Chartrand. Compressed sensing recovery via nonconvex shrinkage penalties. *Inverse Problems*, 32(7):075004, 2016.

[97] Heinz H Bauschke, Patrick L Combettes, et al. *Convex analysis and monotone operator theory in Hilbert spaces*, volume 408. Springer, 2011.