Tourism Mining: Aligning Sentiment–Topic Representations of Sentence Transformer Embeddings for Tourism Opinion Mining

Abstract

We introduce **TourCSE**, a Sentence Transformer tailored for tourism opinion mining leveraging training data derived from topic modeling applied to customer reviews. It enables efficient identification of key aspects in large-scale exploratory analyses.

Beyond topic modeling, we investigate other strategies, including Low-Rank Adaptation, dropout augmentation, sentiment sampling, and negative filtering. Our experiments demonstrate that fine-tuning with domain-specific topics combined with negative filtering substantially improves the alignment between topics and their associated sentiment. Furthermore, when topic information is unavailable, sentiment sampling alone with negative filtering further boosts the model's sensitivity to sentiment without degrading topic alignment. Finally, we reveal annotation issues concerning the NEUTRAL sentiment category in SemEval datasets.

1 Introduction

When social tourism researchers seek to analyze customer opinions, a fundamental question arises: *Which dimensions of the hospitality experience are most relevant to extract?* The challenge is that, in most cases, social researchers do not have pre-defined annotation schemes, as their ground truth depends on their individual expertise and research objectives (Schofield et al., 2025). This limitation reduces the applicability of supervised learning approaches (Grimmer et al., 2021). In contrast, unsupervised approaches, although less accurate, offer a compelling alternative by allowing the labeling scheme to emerge directly from the data. Yet despite their potential, systematic reviews of tourism opinion mining from both computer science (Ameur et al., 2023) and tourism fields (Mehraliyev et al., 2022) highlight a persistent gap: the lack of unsupervised methods specifically tailored for tourism opinion mining in large-scale

Figure 1: We categorize sentence embeddings into three groups: GENERAL, OPINION MINING, and TOURISM MINING. GENERAL embeddings are typically biased toward the sentence subject (Nikolaev and Padó, 2023; Ghafouri et al., 2024), whereas OPINION MINING embeddings tend to discard it (Kim et al., 2024). To overcome these limitations, we introduce TourCSE, which reorganizes the embedding space to capture both topic and sentiment specific to tourism reviews.

analyses involving millions of customer reviews. Although Large Language Models (LLMs) show promise for opinion mining, they currently face significant scalability issues. As Li et al. (2025) notes, classifying 10,000 documents with GPT-4o takes 9 hours and costs about $65. For social scientists, these time and financial constraints pose significant limitations, especially when testing hypotheses that may ultimately be rejected.

As an alternative approach, Ghafouri et al. (2024) emphasize the promising application of Sentence Transformers (Reimers and Gurevych, 2019) for social media opinion mining.[1] These models

---

[1] Sentence Transformers have been employed by Sánchez-Franco and Rey-Moreno (2022) to examine the reasons behind tourism destination choices, and by Introne (2023) to measure opinions regarding climate change.

generate embeddings and enable pairwise comparisons between N sentences and T topics, with linear complexity $O(N + T)$.[2] They also support thematic grouping through clustering frameworks such as BERTopic (Grootendorst, 2022). However, as illustrated in Figure 1, embedding representations from general-purpose and opinion mining models are insufficiently tailored to capturing tourism topics and sentiments. Therefore, using data-driven approaches, we reorganize the embedding space to better align domain-specific tourism topics and sentiments (Section 2). Our contributions can be summarized as follows:[3]

- Demonstrating the relevance of **TourCSE** (Section 4.3 and 4.4), we pave the way for further development on domain-specific opinion-mining Sentence Transformers

- Our ablation study (Sections 4.1 and 4.2) shows that topic model pseudo-labeling with negative filtering aligns domain-specific topics and sentiments, while sentiment sampling introduces sentiment awareness without affecting topic alignment

Also, we position our work in light of the Venkit et al. (2023) critical sentiment analysis survey by:

- Ensuring transparency in sentiment labeling and clearly defining the targeted application scope to avoid unintended biases[4]

- Drawing on linguistic research (Kamoen et al., 2015) and survey definitions (Liu, 2020), we highlight annotation issues in the NEUTRAL category of SemEval datasets

2 Proposed Approach : TourCSE

In this section, we present **TourCSE** (**Tour**ism **C**ontrastive **S**entence **E**mbeddings), our method to develop a Sentence Transformer for tourism opinion mining. Similarly to other contrastive learning frameworks, we require training data pairs, some that share thematic elements (positive samples) and others that differ (negative samples). For positive sampling, we introduce a novel topic modeling

Figure 2: UMAP visualization of Word2Vec representations of sample aspects extracted from HotelRec (Antognini and Faltings, 2020). Aspects related to bedding are highlighted in red.

approach, **SWET**[2] (**S**imple **W**ord **E**mbeddings-based **T**ourism **T**opic Model). For negative samples, we demonstrated that simple negative filtering using GISTEmbed (Solatorio, 2024) significantly improves the alignment between domain topics and sentiment representations. The implemented pipeline is illustrated in Figure 4.

2.1 Topic Modeling : SWET[2]

SWET[2] is our topic model designed to find and extract topics for tourism opinion mining.

2.1.1 Topic Identification

Following the recommendations of Laureate et al. (2023) for topic model development, we propose an approach specifically designed for tourism customer reviews.[5] First, we employ part-of-speech tagging to extract the most frequent nouns, as these correspond to aspects evaluated by customers (Hu and Liu, 2004). Then, to capture semantic relationships between aspects and extract thematic information, we train Word2Vec embeddings on tourism reviews (Mikolov et al., 2013). The aspect embeddings visualization in Figure 2 reveals a natural clustering tendency, suggesting the feasibility of grouping them thematically.

2.1.2 Label Assignment

We present our method for assigning previously extracted topics to each review and propose a solution for incorporating sentiment.

Topic Assignment. Firstly, to extract both implicit and explicit aspects in an unsupervised

---

[2]In contrast, Cross-Encoder architectures, while more accurate, combine inputs such as "text [SEP] label" and have a complexity of $O(N \times T)$ (Shu et al., 2022).

[3]The code is available at https://anonymous.4open.science/r/TourCSE-8372/README.md

[4]Responding to Venkit et al. (2023) ethics sheet, App. E

[5]See Appendix D.1 for their recommendations.

●●○○○○
Cheap but not totally dreadful accommodation.

For what it is (a hostel) it was not too bad. It has the basics, like linen, towels, a common room and kitchen. Staff is friendly and helpful and reception is open 24hrs, which is convenient for late arrivals.
Great transport links to all over London, with New Cross station on one side and New Cross Gate on the other, both within 5min walking distance.
And I met some interesting folk in the hostel.
Not a bad place to stay if you're on a small budget.

Figure 3: A TripAdvisor review. Kamoen et al. (2015) note that indirect positives, such as "*not too bad*", should not be treated as positive sentiment.

manner, we implemented CAt (Tulkens and van Cranenburgh, 2020). An embarrassingly simple method that relies exclusively on the tourism domain `Word2Vec` embeddings (Mikolov et al., 2013) and an extracted set of aspects, which have already been introduced in the previous Section 2.1.1.[6]

Sentiment Assignment. We aim to remain as faithful as possible to the sentiment expressed by customers, while minimizing potential biases introduced by subjective interpretation. To this end, we adopt star ratings as a coarse proxy for sentiment polarity. An example of TripAdvisor reviews and their star ratings is shown in Figure 3.

The Sentiment Problem. Although this approximation does not capture cases of mixed sentiment within a single review, it provides a practical alternative to supervised models, which struggle with aspect-level sentiment granularity (Xing et al., 2020). Moreover, while LLMs perform well on explicit aspect-based sentiment extraction, they exhibit limitations when dealing with more subjective sentiment interpretation and implicit aspects (Zhang et al., 2024). Additionally, general sentiment analysis tools such as VADER (Hutto and Gilbert, 2014) tend to introduce bias because sentiment is inherently context-sensitive (Rebora, 2023). A simple example: a review stating *"Hotel near to Eiffel Tower"* might be classified as POSITIVE in tourism context, but in practice, general sentiment analysis models trained on social media classify this sentence as NEUTRAL.[7] For examples of various sentiment definitions see the critical survey of Venkit et al. (2023).

---

[6]Background on CAt and the evaluation of our reimplementation are provided in Appendix C. Example code is available in Appendix F.

[7]cardiffnlp/twitter-roberta-base-sentiment-latest

2.2 Guided Contrastive Fine-Tuning

2.2.1 Training Objective

Following state-of-the-art Sentence Transformers models (Wang et al., 2024; Li et al., 2023), we use InfoNCE (van den Oord et al., 2019).

$$\mathcal{L} = \frac{e^{cosim(q_i,p_i)/\tau}}{e^{cosim(q_i,p_i)/\tau} + \sum_{j \in B} e^{cosim(q_i,n_j)/\tau}} \quad (1)$$

The objective is to minimize the distance between the embeddings of positive pairs (q_i, p_i), and maximize the distance between negative pairs (q_i, n_j), selected from the batch sample B, using cosine similarity ($cosim$). The parameter τ controls the temperature, allowing adjustment of the scale of cosine similarity.

2.2.2 Negative Sampling

The most common approach for negative sampling involves selecting negatives randomly within the batch (Wang et al., 2024). However, this can lead to false negatives due to the presence of multiple topics within a review. For instance, a review describing a *"small bathroom"* might be incorrectly paired as negative with a review containing a *"dirty shower"*. Although these reviews differ semantically, both express negative sentiment about the same topic BATHROOM. To address this, we adopt GISTEmbed (Solatorio, 2024).[8] This method refines the fine-tuning process by discarding negative samples that exhibit high similarity to the anchor and its corresponding positive pair within the batch. It enhances training signals while reducing the dependency on large batch sizes.

2.3 Parameter-Efficient Fine-Tuning

Previous studies suggest that integrating adapter modules into transformer layers mitigates the risk of catastrophic forgetting during the fine-tuning process (Ghafouri et al., 2024; Schopf et al., 2023). To evaluate this hypothesis, we apply LoRA (Hu et al., 2022) with a rank of 32.

3 Experimental Settings

3.1 Datasets

We focus on the hotel and restaurant domains due to their importance in the tourism sector. For the

---

[8]See sbert.net for documentation.

Figure 4: **TourCSE.** We mine positive sampling using Topic Modeling (**SWET**[2]) by selecting sentences that share the same sentiment and topic (a, p) through our annotation process. Then, we treat other sentences in the batch (n_1, n_2, n_3, n_4) as negatives. In this case, n_3 and n_4 share the same topic (BATHROOM) and sentiment (NEGATIVE) as anchor a but differ in their specific aspects (BATHROOM & TOILET). To address negatives highly similar to a like n_3 and n_4, we introduce **Guided Contrastive Fine-Tuning** (Solatorio, 2024). This method leverages a guidance model to ignore negative pairs (a, n_i) with higher similarity to the current positive pair (a, p) in the batch training.

training process in **TourCSE**, we select large publicly available datasets avoiding data contamination caused by possible overlap between the training and test sets. For evaluation, we use English-annotated datasets that follow established ABSA terminology (Zhang et al., 2023).

3.1.1 Training Dataset

We select two publicly available TripAdvisor datasets, each corresponding to a specific domain:

- **SixTripAdvisorDatasets** for the restaurant domain (Botana et al., 2022)[9]

- **HotelRec** for the hotel domain (Antognini and Faltings, 2020)[10]

Both datasets include sentiment metadata derived from star ratings ranging from 1 to 5. To ensure a balanced distribution, we sampled 100,000 English-language reviews per dataset, with equal representation of 20,000 reviews for each rating.

3.1.2 Evaluation Dataset

We select three annotated datasets: Rest14 (Pontiki et al., 2014), Rest16 (Pontiki et al., 2016), and HotelOATS (Chebolu et al., 2024). These datasets provide sentence-level topics with their associated sentiments. We retain the full train and test splits from each dataset.

Issue with Neutral Annotation. We observed inconsistencies in the annotation of

NEUTRAL sentiment, providing some examples from Rest16. As noted in linguistic studies, indirect negative expressions such as *"Food was okay"* or *"Service was decent"*, currently labeled as NEUTRAL, may in fact convey a negative opinion expressed politely (Kamoen et al., 2015). Similarly, a sentence like *"Plan on waiting 30–70 minutes"* was also annotated as NEUTRAL. However, this example should be categorized as NOT OPINIONATED, since it does not express any sentiment (Liu, 2020). They also misannotated unambiguous NEUTRAL sentences, such as "*Food was mediocre*". To better align the dataset with our research goals, we removed all sentences with NEUTRAL aspect from the evaluation set in our main experiments.[11]

3.2 Detail of Downstream Tasks

3.2.1 Topic Retrieved

We evaluated our embeddings by retrieving topic-sentiment pairs using a single-query approach, simulating real-world scenarios (Wang et al., 2023a). The retrieved topics are as follows:

- **Restaurant**: FOOD, SERVICE, DRINKS, LOCATION, AMBIANCE, PRICE

- **Hotel:** ROOMS, AMENITIES, FACILITIES, SERVICE, LOCATION, FOOD & DRINKS

To incorporate sentiment, we use the sentiment words *excellent* for positive polarity and *terrible*

---

[9]https://zenodo.org/records/6583422
[10]https://github.com/Diego999/HotelRec

[11]Discard NEUTRAL is a common practice, as shown in previous work (Nguyen et al., 2023) but it has not been explicitly justified. Additional results are provided in Appendix B.2.

for negative polarity. Queries are constructed in the format "{sentiment} {topic}". For example, "*excellent food*" retrieves positive opinions about food, while "*terrible food*" retrieves negative ones. Retrieval is performed based on cosine similarity between the query and sentence embeddings.

3.2.2 Evaluation Metric

Following Booking.com (Wang et al., 2023a), we adopt the macro-averaged precision score from Scikit-Learn as the evaluation metric (Pedregosa et al., 2011).

3.3 Model Selected

Following `StanceSBERT` (Ghafouri et al., 2024), we selected `all-mpnet-base-v2` as the base model for domain adaptation because it offers a strong trade-off between model size and performance on MTEB (Muennighoff et al., 2023). It has been trained on a large-scale corpus, with details about the training data. As a guided model in the **Guided Contrastive Fine-Tuning** step, we use a copy of the selected model `all-mpnet-base-v2`.

4 Results

4.1 Number of Topics

As positive sampling generation is based on Topic Modeling, we aim to evaluate the impact of topic number, denoted as K. Since there is no universally optimal method to determine the ideal number of topics, we test six different values: 10, 50, 100, 150, 200, and 250. The fine-tuning is performed with Guided Contrastive Fine-Tuning and LoRA and results are presented in Figure 5. Our analysis shows that **TourCSE consistently outperforms the base model across all values of** K. However, increasing the number of topics does not necessarily lead to better performance. Instead, for HotelOATS and Rest16, the optimal K is 10, beyond which performance declines and then stabilizes.[12] Overall, using topic models does not reduce the performance of the base models and performs similarly or better than sentiment sampling (see Section 4.2), **indicating that any selection of** K **superior to 10 yields reliable results.**

---

[12]This limitation likely stems from the annotation scheme itself. A more flexible or nuanced scheme may be better suited for real-world settings, potentially improving performance for larger values of K. See the Limitations section for further discussion.

4.2 Ablation Study

We aim to evaluate the impact of different modules in **TourCSE**, specifically **Guided Contrastive Fine-Tuning** (GCFT) and **LoRA**. Additionally, we compare the effect of our positive sampling, refereed as Topic Modeling, with two others possible strategies:

- **Dropout**: Following `SimCSE` (Gao et al., 2021), this strategy generates positive pairs by using the same sentence twice, applying dropout within layers as a form of data augmentation.

- **Sentiment**: Following `SentiCSE` (Kim et al., 2024), this approach selects positive pairs based solely on sentiment, ignoring specific aspect mentioned in the sentence.

	HotelOATS	Rest16	Rest14	Avg.
all-mpnet-base-v2	38.72	43.98	53.94	45.55
Dropout	20.25	24.47	31.78	25.50
Δ w/o LoRA	-2.34	-4.08	-3.58	-3.33
Sentiment	44.01	47.82	58.65	50.16
Δ w/o GCFT	-21.87	-23.98	-26.17	-24.01
Δ w/o LoRA	-0.51	-0.70	-1.33	-0.85
Δ w/o LoRA & GCFT	-21.99	-22.55	-23.23	-22.59
Topic Modeling $k = 10$	**45.75**	51.59	62.38	53.24
Δ w/o GCFT	-4.56	-5.30	**+0.86**	-3.00
Δ w/o LoRA	-0.13	**+0.78**	-0.16	**+0.16**
Δ w/o LoRA & GCFT	-19.11	-9.91	-10.93	-13.32

Table 1: Ablation study of different positive and negative sampling strategies and the impact of LoRA. Overall, topic modeling sampling yields the best results. However, sentiment sampling with GCFT remains a strong alternative.

The ablation study presented in Table 1 demonstrates that **topic modeling with LoRA, GCFT, or both significantly outperforms all other configurations**. The inclusion of GCFT has a more noticeable positive impact on Sentiment sampling, **positioning it as a strong alternative when only sentiment information is available**. In contrast, Dropout sampling consistently underperforms, with or without LoRA, indicating its negative impact on performance as a positive sampling strategy. The small performance gap between models with and without LoRA in Topic Modeling configuration suggests that negative filtering plays a greater role in training. In general, these findings suggest that **a simple data-centric approach is sufficient to adapt sentence representations to both domain topics and sentiment**.

Figure 5: Macro Average Precision scores for different values of K during positive pair generation. Fine-tuning is performed using Guided Contrastive Fine-Tuning and LoRA. The cross markers represent the score of the base model `all-mpnet-base-v2`. The horizontal dashed line indicates the score obtained with randomly sampled positive pairs sharing the same sentiment, as discussed in Section 4.2. Overall, topic mining achieves better performance than both the base model and, with the right choice of K, the sentiment-only strategy.

4.3 Model Comparison

We compare **TourCSE** with other Sentence Transformers models, including a variety of architectures, training data, and objective loss, to assess the usefulness of our fine-tuning approach :

- **General Sentence Embeddings** trained on large-scale, multi-domain data, including `all-MiniLM-L6-v2`, `all-MiniLM-L12-v2`, `all-mpnet-base-v2`, the E5 series (Microsoft) (Wang et al., 2024, 2023b), GTE (Alibaba) (Li et al., 2023), and T5-XXL (Google) (Ni et al., 2021b,a).

- **Opinion Mining Sentence Embeddings**, including `SentiCSE` (Kim et al., 2024) and `StanceSBERT` (Ghafouri et al., 2024).[13]

- **Tourism Mining Sentence Embeddings**, including `Word2Vec` (Mikolov et al., 2013), `FastText` (Bojanowski et al., 2017), and `TourBERT` (Arefeva and Egger, 2022).[14]

The results in Table 2 show that **TourCSE** consistently outperforms models with comparable

---

[13]`SentiCSE` is a RoBERTa fine-tuning model, and `StanceSBERT` is an all-mpnet-base-v2 fine-tuning model. The objective loss and training data are discussed in Section 5.1.

[14]`TourBERT` is a BERT model fine-tuned on tourism data using MLM objective. `Word2Vec` and `FastText` were trained on the same dataset as TourCSE.

	HotelOATS	Rest16	Rest14	Avg.
General Sentence Embeddings				
all-MiniLM-L6-v2	30.73	34.46	45.38	36.86
all-MiniLM-L12-v2	33.61	36.20	47.71	39.17
all-mpnet-base-v2	38.72	43.98	53.94	45.55
E5-small-v2	34.26	37.34	54.14	41.91
E5-base-v2	35.43	40.96	56.57	44.32
E5-large-v2	34.29	38.32	53.52	42.04
E5-Mistral-7B-Instruct	31.87	36.88	47.48	38.74
GTE-base-v1.5	36.75	40.13	56.50	44.46
GTE-large-v1.5	39.78	44.01	57.69	47.16
GTE-ModernBERT	42.18	49.48	**67.32**	52.99
ST5-XXL	43.70	47.20	67.20	52.70
GTR-T5-XXL	31.30	40.16	50.13	40.53
Opinion Mining Sentence Embeddings				
SentiCSE	31.27	34.29	45.37	36.98
StanceSBERT	37.00	37.53	49.65	41.39
Tourism Mining Sentence Embeddings				
Word2Vec$_{CBOW}$	31.58	31.73	40.73	34.68
Word2Vec$_{SG}$	29.78	32.86	41.26	34.63
FastText$_{CBOW}$	30.23	28.93	38.27	32.48
FastText$_{SG}$	28.19	32.10	39.63	33.31
TourBERT	18.68	20.72	30.10	19.26
TourCSE $K = 10$	**45.75**	**51.59**	62.38	**53.24**

Table 2: Performance comparison of different sentence embedding models across datasets, using Macro Average Precision. Best results are shown in **bold**, and best of each categories is underlined. Overall, **TourCSE** outperforms both general and opinion mining models.

backbones, such as E5 (BERT), GTE (Transformers++), SentiCSE (RoBERTa), and StanceSBERT (MPNet), underlining the effectiveness of our training data for domain adaptation. **TourCSE** achieves the highest scores on HotelOATS (45.75) and Rest16 (51.59), ranks third on Rest14 (62.38), and achieves the highest average score (53.24). In contrast, models like GTE-ModernBERT and LLMs such as ST5-XXL also demonstrate strong performance, with GTE-ModernBERT leading on Rest14 (67.32) and securing second place for the average score (52.99).[15] Surprisingly, opinion mining sentence embeddings do not show any improvement over general sentence embeddings. In particular, StanceSBERT performs worse than its base model, all-mpnet-base-v2. Similarly, TourBERT performs worse than Word2Vec, highlighting the limitations of domain adaptation through MLM (Gururangan et al., 2020) for learning sentence representations, despite Arefeva and Egger (2022) reporting improved sentence representations for tourism reviews. These findings underscore the **importance of incorporating domain-specific topics and sentiment into contrastive objective training**.

---

[15]Replacing all-mpnet-base-v2 with GTE-ModernBERT may offer a promising way to improve performance without relying on larger models.

Figure 6: BERTopic visualization (Grootendorst, 2022) for `all-mpnet-base-v2` (left) and `TourCSE` (K = 250) (right), based on sampled reviews from the HotelRec dataset. The top row shows the distribution of POSITIVE (★★★★★, ★★★★☆), NEGATIVE (★★☆☆☆, ★☆☆☆☆), and **NEUTRAL** (★★★☆☆) reviews. The bottom row displays topic clusters obtained using K-Means (20 clusters). Overall, `TourCSE` demonstrates better sentiment separation in the top row and more coherent, domain-specific topic clusters in the bottom row, as highlighted by the appearance of topics such as GREAT LOVELY STAY and ROOM DIRTY SMOKING.

4.4 Embeddings Visualization

BERTopic Compatibility. Figure 6 illustrates how TourCSE integrates with BERTopic (Grootendorst, 2022), providing an interpretable embeddings visualization that supports both clustering and keyword extraction. BERTopic is the framework used by Sánchez-Franco and Rey-Moreno (2022) to analyze tourism reviews.

Ambiguous Sentiment. To analyze how TourCSE handles ambiguous sentiment expressions, we constructed pseudo-sentences of the form "*hotel was ...*", where "..." represents opinion expressions. We examined how indirect positives (e.g., "*not bad*"), indirect negatives (e.g., "*not great*"), and conflicting sentiments (different sentiments separated by "*but*") are positioned relative to anchor opinions "*great*" (positive), "*bad*" (negative), and "*okay*" (neutral). The visualization is shown in Figure 7. Positive expressions cluster near "*great*", while negative expressions and indirect negatives appear closer to "*bad*". Conflicting sentiment expressions appear near positive or neutral regions. Interestingly, the indirect positive is positioned nearer to the

sentiment word "*okay*". This aligns with Kamoen et al. (2015), **who found that indirect positives like "*not bad*" should not be treated as positive**.

Figure 7: UMAP of TourCSE embeddings for pseudo-opinion sentences "hotel was ...". Cosine similarity to the nearest sentiment anchor is shown. Sentiment expressions are coherently organized

5 Related Work

In this section, we compare **TourCSE** against various approaches for incorporating sentiment into embeddings and generating pseudo-labels, situating our work within the existing literature.

5.1 Sentiment-Aware Sentence Embeddings

As illustrated in Figure 1, general-purpose sentence embeddings fail to encode sentiment information effectively, partly because of their bias toward subject (Nikolaev and Padó, 2023), which limits their usefulness for opinion mining tasks (Ghafouri et al., 2024). To address this, SentiCSE (Kim et al., 2024) employs contrastive learning with positive and negative sentence pairs constructed based on sentiment polarity, which are mined using Senti-WordNet (Baccianella et al., 2010). StanceSBERT (Ghafouri et al., 2024) combines contrastive and triplet loss, uses LoRA to mitigate catastrophic forgetting, and employs its own algorithm to mine negatives. However, as shown in our ablation study (Section 4.2), LoRA has a negligible impact compared to the importance of the training data, and GISTEmbed (Solatorio, 2024) is sufficient to improve negative sample quality. Also, SentiCSE does not incorporate any notion of aspect or topic structure in its training data, while StanceSBERT relies on metadata from debate forum topics, which do not align with tourism-related topics. The problem is that both approaches claim general effectiveness in opinion mining. **In contrast, our approach explicitly specifies domain scopes and addresses this by mining topics directly from customer reviews.** Furthermore, unlike SentiCSE and StanceSBERT, our method requires only positive examples for training. Sentiment-aware sentence embedding models are summarized in Appendix Table 6.

5.2 Pseudo-Labeling for Sentiment Analysis

Previous studies have explored pseudo-labeling methods that explicitly retrieve aspect–sentiment pairs for training sentiment analysis models. Shu et al. (2022) introduces the Review Natural Language Inference (RNLI) dataset, constructed using Double Propagation algorithm (Qiu et al., 2011) to extract aspects, with sentiment labels assigned via an opinion lexicon (Liu, 2004). Similarly, Noisy ABSA Pre-Training (NAPT) (Vacareanu et al., 2024) adopts a fully dictionary-based approach: frequent nouns are extracted as candidate aspects, and adjectives are identified using the same opinion lexicon. They generate aspect–opinion pairs, combine them into pseudo-sentences like `"aspect is opinion"` (e.g., "*pizza is good*"), and validate links using a Natural Language Inference model.[16] However, both approaches are tailored to the e-commerce domain and lack topic-level abstraction and aspect extraction beyond the main subject. For example, in "*hotel located near the Eiffel Tower*" relying only on the explicit aspect "*hotel*" misses the implicit sentiment about the "*location*". Pseudo-labeling strategies are summarized in Appendix Table 7.

6 Conclusion

We present TourCSE, a Sentence Transformer model specifically designed for opinion mining in the tourism sector, enabling scalable analysis of millions of reviews. We empirically demonstrate the promising use of topic models as a pseudo-labeling approach, combined with negative filtering, to align domain-specific topics and sentiment in embeddings. We hope our results, which highlight the underperformance of general opinion mining sentence embedding models, encourage further development of domain-specific opinion mining Sentence Transformers. Further direct research directions include:

- Mining training data with TourCSE to train more robust ABSA models (de Souza P. Moreira et al., 2025; Nguyen et al., 2023).

- Leveraging TourCSE as a retrieval component within RAG pipelines for opinion summarization (Nayeem and Rafiei, 2025)

- Assisting experts in corpus exploration by integrating TourCSE with BERTopic, as illustrated in Figure 6 (Sánchez-Franco and Rey-Moreno, 2022)

- Re-annotating the NEUTRAL category (Kamoen et al., 2015; Liu, 2020) to more thoroughly benchmark supervise SLMs and LLMs in ABSA, and to verify claims about their ability to handle ambiguous sentiment

Limitations

As a limitation, we remember that **TourCSE** was developed solely for tourism opinion mining.

---

[16]For instance, RNLI is used to train a cross-encoder (BART), while NAPT train a Seq2Seq model (T5).

Nevertheless, we aim to provide guidance for practitioners on developing and evaluating topics and sentiments with Sentence Transformers in their own domains.

The Domain Scope of SWET². Recent work has highlighted the limitations of general LLM-based topic models (Pham et al., 2024; Lam et al., 2024), particularly their difficulty in extracting informative topics when the document collection originates from a single, specific domain (Li et al., 2025). To address this limitation, we developed **SWET²** specifically for tourism reviews.

Recommendation: Practitioners who wish to align sentiment embeddings in their own domain may rely on existing topic models, such as LDA (Blei et al., 2003) or TopicGPT (Pham et al., 2024), although better results can be expected when the topic model is adapted to the target domain. See Appendix D.1 for a discussion of the research agenda on topic model development.

The K Parameters. Issues with traditional automated evaluation metrics helping select K are now well documented (Hoyle et al., 2021; Chang et al., 2009; Doogan and Buntine, 2021; Shadrova, 2021). Although recent methods such as TopicGPT (Pham et al., 2024) use LLMs to automatically set K, the resulting topics still require expert refinement (Choi et al., 2024; Schofield et al., 2025), and they are not necessarily more informative than those extracted by traditional methods such as LDA (Li et al., 2025).

Recommendation: Practitioners should empirically test multiple values of K as it is inherently dependent on their task and domain, and refine the extracted topics manually whenever possible.[17] Alternatively, as shown in our ablation study (Section 4.2), practitioners can rely solely on sentiment-based sampling (opinion datasets often include sentiment indicators such as star ratings) combined with GISTEmbed negative filtering (Solatorio, 2024) to improve sentiment-related

representations without degrading topic alignment.

The Ground Truth Subjectivity. As noted by Grimmer et al. (2022), the primary goal of unsupervised methods is not to reproduce an existing ground truth, but to enable new interpretations through exploratory analysis. In our study, we evaluated only a limited set of predefined topics. By contrast, Booking.com uses a much more fine-grained taxonomy with 239 distinct topics to train a Sentence Transformer in a supervised manner (Wang et al., 2023a).

Recommendation: Unsupervised Sentence Transformers should not be used to extract preconceived topics envisioned by experts. Rather, their goal is to explore embeddings through visualization (as shown in Figure 6) to assist experts in defining topic sets, which can then guide the development of supervised methods or LLM-based analyses. Evaluation without a defined ground truth remains an active research area (Li et al., 2024, 2025; Hoyle et al., 2025), and further research should verify whether these approaches are applicable to domain-specific opinion mining.

Ethical Considerations

Considering the work of Venkit et al. (2023), we respond to the ethics sheet for sentiment analysis systems, provided in Appendix E. We acknowledge potential biases in training data, which may influence the outputs of our system, and we strive to mitigate them through **careful dataset selection** and a **well-defined application scope**. The datasets used in our study may contain identifiable information; however, we are not responsible for such content, as the data is publicly available and originates from previous research. Generative AI was used solely for rephrasing, improving grammar, and providing coding assistance.

Acknowledgments

References

Asma Ameur, Sana Hamdi, and Sadok Ben Yahia. 2023. Sentiment analysis for hotel reviews: A systematic literature review. *ACM Comput. Surv.*, 56(2).

Diego Antognini and Boi Faltings. 2020. HotelRec: a novel very large-scale hotel recommendation dataset. In *Proceedings of the Twelfth Language Resources and Evaluation Conference*, pages 4917–4923, Marseille, France. European Language Resources Association.

---

[17]For assisting in the selection of K, Stammbach et al. (2023) explored the use of LLMs, reporting promising results when the LLM was prompted with a related hypothesis to test (e.g., "Which dimensions of the hospitality experience are most relevant to extract?"). However, they explicitly acknowledge in their limitations that "*The optimal number of topics is a vague concept, dependent on a practitioner's goals and the data under study*".

Erik Arakelyan, Zhaoqi Liu, and Isabelle Augenstein. 2024. Semantic sensitivities and inconsistent predictions: Measuring the fragility of NLI models. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 432–444, St. Julian's, Malta. Association for Computational Linguistics.

Veronika Arefeva and Roman Egger. 2022. When bert started traveling: Tourbert—a natural language processing model for the travel industry. *Digital*, 2(4):546–559.

Stefano Baccianella, Andrea Esuli, and Fabrizio Sebastiani. 2010. SentiWordNet 3.0: An enhanced lexical resource for sentiment analysis and opinion mining. In *Proceedings of the Seventh International Conference on Language Resources and Evaluation (LREC'10)*, Valletta, Malta. European Language Resources Association (ELRA).

Steven Bird and Edward Loper. 2004. NLTK: The natural language toolkit. In *Proceedings of the ACL Interactive Poster and Demonstration Sessions*, pages 214–217, Barcelona, Spain. Association for Computational Linguistics.

David M. Blei, Andrew Y. Ng, and Michael I. Jordan. 2003. Latent dirichlet allocation. *J. Mach. Learn. Res.*, 3(null):993–1022.

Piotr Bojanowski, Edouard Grave, Armand Joulin, and Tomas Mikolov. 2017. Enriching word vectors with subword information. *Transactions of the association for computational linguistics*, 5:135–146.

Iñigo López-Riobóo Botana, Verónica Bolón-Canedo, Bertha Guijarro-Berdiñas, and Amparo Alonso-Betanzos. 2022. Explain and conquer: Personalised text-based reviews to achieve transparency. *Preprint*, arXiv:2205.01759.

Jonathan Chang, Sean Gerrish, Chong Wang, Jordan Boyd-Graber, and David Blei. 2009. Reading tea leaves: How humans interpret topic models. *Advances in neural information processing systems*, 22.

Siva Uday Sampreeth Chebolu, Franck Dernoncourt, Nedim Lipka, and Thamar Solorio. 2024. OATS: A challenge dataset for opinion aspect target sentiment joint detection for aspect-based sentiment analysis. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 12336–12347, Torino, Italia. ELRA and ICCL.

Alexander Choi, Syeda Sabrina Akter, J.p. Singh, and Antonios Anastasopoulos. 2024. The LLM effect: Are humans truly using LLMs, or are they being influenced by them instead? In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 22032–22054, Miami, Florida, USA. Association for Computational Linguistics.

Gabriel de Souza P. Moreira, Radek Osmulski, Mengyao Xu, Ronay Ak, Benedikt Schifferer, and Even Oldridge. 2025. Nv-retriever: Improving text embedding models with effective hard-negative mining. *Preprint*, arXiv:2407.15831.

Caitlin Doogan and Wray Buntine. 2021. Topic model or topic twaddle? re-evaluating semantic interpretability measures. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 3824–3848, Online.

Gayatree Ganu, Noemie Elhadad, and Amélie Marian. 2009. Beyond the stars: Improving rating predictions using review text content. In *WebDB*, volume 9, pages 1–6.

Tianyu Gao, Xingcheng Yao, and Danqi Chen. 2021. SimCSE: Simple contrastive learning of sentence embeddings. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 6894–6910, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Aitor García-Pablos, Montse Cuadros, and German Rigau. 2018. W2vlda: almost unsupervised system for aspect based sentiment analysis. *Expert Systems with Applications*, 91:127–137.

Vahid Ghafouri, Jose Such, Guillermo Suarez-Tangil, and 1 others. 2024. I love pineapple on pizza!= i hate pineapple on pizza: Stance-aware sentence transformers for opinion mining. In *Empirical Methods in Natural Language Processing*.

Justin Grimmer, Margaret E Roberts, and Brandon M Stewart. 2021. Machine learning for social science: An agnostic approach. *Annual Review of Political Science*, 24(1):395–419.

Justin Grimmer, Margaret E Roberts, and Brandon M Stewart. 2022. *Text as data: A new framework for machine learning and the social sciences*. Princeton University Press.

Maarten Grootendorst. 2022. Bertopic: Neural topic modeling with a class-based tf-idf procedure. *Preprint*, arXiv:2203.05794.

Suchin Gururangan, Ana Marasović, Swabha Swayamdipta, Kyle Lo, Iz Beltagy, Doug Downey, and Noah A Smith. 2020. Don't stop pretraining: Adapt language models to domains and tasks. *arXiv preprint arXiv:2004.10964*.

Ruidan He, Wee Sun Lee, Hwee Tou Ng, and Daniel Dahlmeier. 2017. An unsupervised neural attention model for aspect extraction. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, Vancouver, Canada. Association for Computational Linguistics.

Alexander Hoyle, Pranav Goel, Andrew Hian-Cheong, Denis Peskov, Jordan Boyd-Graber, and Philip Resnik. 2021. Is automated topic model evaluation broken? the incoherence of coherence. In *Advances in Neural Information Processing Systems*, volume 34, pages 2018–2033. Curran Associates, Inc.

Alexander Miserlis Hoyle, Lorena Calvo-Bartolomé, Jordan Lee Boyd-Graber, and Philip Resnik. 2025. ProxAnn: Use-oriented evaluations of topic models and document clustering. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15872–15897, Vienna, Austria. Association for Computational Linguistics.

Alexander Miserlis Hoyle, Rupak Sarkar, Pranav Goel, and Philip Resnik. 2022. Are neural topic models broken? In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 5321–5344, Abu Dhabi, United Arab Emirates.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*.

Minqing Hu and Bing Liu. 2004. Mining and summarizing customer reviews. In *Proceedings of the Tenth ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '04, page 168–177, New York, NY, USA. Association for Computing Machinery.

C. J. Hutto and Eric E. Gilbert. 2014. VADER: A parsimonious rule-based model for sentiment analysis of social media text. In *Proceedings of the Eighth International Conference on Weblogs and Social Media (ICWSM-14)*, Ann Arbor, MI.

Joshua Introne. 2023. Measuring belief dynamics on twitter. In *Proceedings of the International AAAI Conference on Web and Social Media*, volume 17, pages 387–398.

Naomi Kamoen, Maria B.J. Mos, and Willem F.S. Dekker (Robbin). 2015. A hotel that is not bad isn't good. the effects of valence framing and expectation in online reviews on text, reviewer and product appreciation. *Journal of Pragmatics*, 75:28–43.

Jaemin Kim, Yohan Na, Kangmin Kim, Sang-Rak Lee, and Dong-Kyu Chae. 2024. SentiCSE: A sentiment-aware contrastive sentence embedding framework with sentiment-guided textual similarity. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 14693–14704, Torino, Italia. ELRA and ICCL.

Michelle S Lam, Janice Teoh, James A Landay, Jeffrey Heer, and Michael S Bernstein. 2024. Concept induction: Analyzing unstructured text with high-level concepts using lloom. In *Proceedings of the 2024 CHI Conference on Human Factors in Computing Systems*, pages 1–28.

Caitlin Doogan Poet Laureate, Wray Buntine, and Henry Linger. 2023. A systematic review of the use of topic models for short text social media analysis. *Artificial Intelligence Review*, 56(12):14223–14255.

Zehan Li, Xin Zhang, Yanzhao Zhang, Dingkun Long, Pengjun Xie, and Meishan Zhang. 2023. Towards general text embeddings with multi-stage contrastive learning. *Preprint*, arXiv:2308.03281.

Zongxia Li, Lorena Calvo-Bartolomé, Alexander Hoyle, Paiheng Xu, Alden Dima, Juan Francisco Fung, and Jordan Boyd-Graber. 2025. Large language models struggle to describe the haystack without human help: Human-in-the-loop evaluation of llms. *Preprint*, arXiv:2502.14748.

Zongxia Li, Andrew Mao, Daniel Stephens, Pranav Goel, Emily Walpole, Alden Dima, Juan Fung, and Jordan Boyd-Graber. 2024. Improving the TENOR of labeling: Re-evaluating topic models for content analysis. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 840–859, St. Julian's, Malta. Association for Computational Linguistics.

Weng Marc Lim. 2024. What is qualitative research? an overview and guidelines. *Australasian Marketing Journal*, page 14413582241264619.

Bing Liu. 2004. Opinion lexicon. Accessed: 2025-06-24.

Bing Liu. 2020. *Sentiment analysis*, 2 edition. Studies in Natural Language Processing. Cambridge University Press, Cambridge, England.

Ling Luo, Xiang Ao, Yan Song, Jinyao Li, Xiaopeng Yang, Qing He, and Dong Yu. 2019. Unsupervised neural aspect extraction with sememes. In *IJCAI*, pages 5123–5129.

Tingting Ma, Jin-Ge Yao, Chin-Yew Lin, and Tiejun Zhao. 2021. Issues with entailment-based zero-shot text classification. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 2: Short Papers)*, pages 786–796, Online. Association for Computational Linguistics.

Fuad Mehraliyev, Irene Cheng Chu Chan, and Andrei Petrovich Kirilenko. 2022. Sentiment analysis in hospitality and tourism: a thematic and methodological review. *International Journal of Contemporary Hospitality Management*, 34(1):46–77.

Tomas Mikolov, Kai Chen, Gregory S. Corrado, and Jeffrey Dean. 2013. Efficient estimation of word representations in vector space. In *International Conference on Learning Representations*.

Christopher Mitcheltree, Skyler Wharton, and Avneesh Saluja. 2018. Using aspect extraction approaches to generate review summaries and user profiles. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 3 (Industry Papers)*, pages 68–75, New Orleans - Louisiana. Association for Computational Linguistics.

Niklas Muennighoff, Nouamane Tazi, Loic Magne, and Nils Reimers. 2023. MTEB: Massive text embedding benchmark. In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, pages 2014–2037, Dubrovnik, Croatia.

Mir Tafseer Nayeem and Davood Rafiei. 2025. OpinioRAG: Towards generating user-centric opinion highlights from large-scale online reviews. In *Second Conference on Language Modeling*.

Thi-Nhung Nguyen, Hoang Ngo, Kiem-Hieu Nguyen, and Tuan-Dung Cao. 2023. A self-enhancement multitask framework for unsupervised aspect category detection. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 8043–8054, Singapore. Association for Computational Linguistics.

Jianmo Ni, Chen Qu, Jing Lu, Zhuyun Dai, Gustavo Hernández Ábrego, Ji Ma, Vincent Y. Zhao, Yi Luan, Keith B. Hall, Ming-Wei Chang, and Yinfei Yang. 2021a. Large dual encoders are generalizable retrievers. *Preprint*, arXiv:2112.07899.

Jianmo Ni, Gustavo Hernández Ábrego, Noah Constant, Ji Ma, Keith B. Hall, Daniel Cer, and Yinfei Yang. 2021b. Sentence-t5: Scalable sentence encoders from pre-trained text-to-text models. *Preprint*, arXiv:2108.08877.

Dmitry Nikolaev and Sebastian Padó. 2023. Representation biases in sentence transformers. In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, pages 3701–3716, Dubrovnik, Croatia.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. 2011. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830.

Chau Minh Pham, Alexander Hoyle, Simeng Sun, Philip Resnik, and Mohit Iyyer. 2024. TopicGPT: A prompt-based topic modeling framework. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 2956–2984, Mexico City, Mexico. Association for Computational Linguistics.

Maria Pontiki, Dimitris Galanis, Haris Papageorgiou, Ion Androutsopoulos, Suresh Manandhar, Mohammad AL-Smadi, Mahmoud Al-Ayyoub, Yanyan Zhao, Bing Qin, Orphée De Clercq, Véronique Hoste, Marianna Apidianaki, Xavier Tannier, Natalia Loukachevitch, Evgeniy Kotelnikov, Nuria Bel, Salud María Jiménez-Zafra, and Gülşen Eryiğit. 2016. SemEval-2016 task 5: Aspect based sentiment analysis. In *Proceedings of the 10th International Workshop on Semantic Evaluation (SemEval-2016)*, pages 19–30, San Diego, California.

Maria Pontiki, Dimitris Galanis, John Pavlopoulos, Harris Papageorgiou, Ion Androutsopoulos, and Suresh Manandhar. 2014. SemEval-2014 task 4: Aspect based sentiment analysis. In *Proceedings of the 8th International Workshop on Semantic Evaluation (SemEval 2014)*, pages 27–35, Dublin, Ireland.

Guang Qiu, Bing Liu, Jiajun Bu, and Chun Chen. 2011. Opinion word expansion and target extraction through double propagation. *Computational linguistics*, 37(1):9–27.

Simone Rebora. 2023. Sentiment analysis in literary studies. a critical survey. *DHQ: Digital Humanities Quarterly*, 17(3).

Radim Řehůřek and Petr Sojka. 2010. Software Framework for Topic Modelling with Large Corpora. In *Proceedings of the LREC 2010 Workshop on New Challenges for NLP Frameworks*, pages 45–50, Valletta, Malta. ELRA. http://is.muni.cz/publication/884893/en.

Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3982–3992, Hong Kong, China.

Anna Rogers. 2021. Changing the world by changing the data. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 2182–2194, Online.

Manuel J Sánchez-Franco and Manuel Rey-Moreno. 2022. Do travelers' reviews depend on the destination? an analysis in coastal and urban peer-to-peer lodgings. *Psychology & marketing*, 39(2):441–459.

Alexandra Schofield, Siqi Wu, Theo Bayard de Volo, Tatsuki Kuze, Alfredo Gomez, and Sharifa Sultana. 2025. "my very subjective human interpretation": Domain expert perspectives on navigating the text analysis loop for topic models. *Proceedings of the ACM on Human-Computer Interaction*, 9(1):1–30.

Tim Schopf, Dennis Schneider, and Florian Matthes. 2023. Efficient domain adaptation of sentence embeddings using adapters. In *Recent Advances in Natural Language Processing*.

Anna Shadrova. 2021. Topic models do not model topics: epistemological remarks and steps towards best practices. *Journal of Data Mining & Digital Humanities*, 2021:4.

Tian Shi, Liuqing Li, Ping Wang, and Chandan K Reddy. 2021. A simple and effective self-supervised contrastive learning framework for aspect detection. In *Proceedings of the AAAI conference on artificial intelligence*, volume 35, pages 13815–13824.

Lei Shu, Hu Xu, Bing Liu, and Jiahua Chen. 2022. Zero-shot aspect-based sentiment analysis. *Preprint*, arXiv:2202.01924.

Aivin V. Solatorio. 2024. Gistembed: Guided in-sample selection of training negatives for text embedding fine-tuning. *Preprint*, arXiv:2402.16829.

Dominik Stammbach, Vilém Zouhar, Alexander Hoyle, Mrinmaya Sachan, and Elliott Ash. 2023. Revisiting automated topic model evaluation with large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 9348–9357, Singapore.

Stéphan Tulkens and Andreas van Cranenburgh. 2020. Embarrassingly simple unsupervised aspect extraction. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 3182–3187.

Robert Vacareanu, Siddharth Varia, Kishaloy Halder, Shuai Wang, Giovanni Paolini, Neha Anna John, Miguel Ballesteros, and Smaranda Muresan. 2024. A weak supervision approach for few-shot aspect based sentiment analysis. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2734–2752, St. Julian's, Malta.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. 2019. Representation learning with contrastive predictive coding. *Preprint*, arXiv:1807.03748.

Pranav Venkit, Mukund Srinath, Sanjana Gautam, Saranya Venkatraman, Vipul Gupta, Rebecca Passonneau, and Shomir Wilson. 2023. The sentiment problem: A critical survey towards deconstructing sentiment analysis. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 13743–13763, Singapore.

Fengjun Wang, Moran Beladev, Ofri Kleinfeld, Elina Frayerman, Tal Shachar, Eran Fainman, Karen Lastmann Assaraf, Sarai Mizrachi, and Benjamin Wang. 2023a. Text2Topic: Multi-label text classification system for efficient topic detection in user generated content with zero-shot capabilities. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 93–103, Singapore.

Liang Wang, Nan Yang, Xiaolong Huang, Binxing Jiao, Linjun Yang, Daxin Jiang, Rangan Majumder, and Furu Wei. 2024. Text embeddings by weakly-supervised contrastive pre-training. *Preprint*, arXiv:2212.03533.

Liang Wang, Nan Yang, Xiaolong Huang, Linjun Yang, Rangan Majumder, and Furu Wei. 2023b. Improving text embeddings with large language models. *arXiv preprint arXiv:2401.00368*.

Xiaoyu Xing, Zhijing Jin, Di Jin, Bingning Wang, Qi Zhang, and Xuanjing Huang. 2020. Tasty burgers, soggy fries: Probing aspect robustness in aspect-based sentiment analysis. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 3594–3605, Online. Association for Computational Linguistics.

Wenxuan Zhang, Yue Deng, Bing Liu, Sinno Pan, and Lidong Bing. 2024. Sentiment analysis in the era of large language models: A reality check. In *Findings of the Association for Computational Linguistics: NAACL 2024*, pages 3881–3906, Mexico City, Mexico.

Wenxuan Zhang, Xin Li, Yang Deng, Lidong Bing, and Wai Lam. 2023. A survey on aspect-based sentiment analysis: Tasks, methods, and challenges. *IEEE Trans. on Knowl. and Data Eng.*, 35(11):11019–11038.

A Implementation Details

A.1 SWET[2]

We tokenize the text and remove stopwords. Then, we extract the 1000 most frequent common nouns, considering them as explicit aspects in our corpus. This process is implemented using the NLTK library (Bird and Loper, 2004). Next, we train two Word2Vec models on each training corpus using Skip-Gram with negative sampling with Gensim (Řehůřek and Sojka, 2010). We perform hierarchical clustering on the cosine similarity matrix of aspect vectors to extract topics, setting the desired number of clusters as the threshold.

A.2 Positive Sampling

Label Assignment is conducted at the sentence level, resulting in approximately 300,000 positive pairs per domain. Generation is performed by coupling each sentence with a random sentence that shares the same topics and sentiment.

A.3 Guided Contrastive Fine-Tuning

We train all models with a batch size of 128, using one positive and 127 negative pairs per step. Training runs for 3 epochs with AdamW, a learning rate of 5×10^{-5}, no warm-up, and a temperature τ of 20. Using GistEmbed loss and LoRA on a single H100 GPU, training completes in 30 minutes.

B   Additional Experiments

B.1   Aspect Category Detection

We evaluate aspect extraction using queries constructed solely on the {aspect} without sentiment words. An ablation study on different values of K is provided in Figure 8 and a model comparison is shown in Table 3.

Figure 8: Macro Average Precision score for different values of K during the generation of positives sampling. Overall, randomly sampling by sentiment does not show any improvement in topic extraction, while SWET[2] improves or at least does not degrade performance.

	HotelOATS	Rest16	Rest14	Avg.
General Sentence Embeddings				
all-MiniLM-L6-v2	58.28	62.94	80.86	67.36
all-MiniLM-L12-v2	59.87	63.15	81.16	68.06
all-mpnet-base-v2	59.16	61.11	80.74	67.00
E5-small-v2	52.53	50.60	72.96	58.70
E5-base-v2	51.66	56.61	76.35	61.54
E5-large-v2	49.91	51.55	74.17	58.54
E5-Mistral-7B-Instruct	59.40	**68.31**	84.12	70.61
GTE-base-v1.5	55.82	59.17	78.11	64.37
GTE-large-v1.5	57.27	58.53	80.03	65.28
GTE-ModernBERT	54.03	64.60	82.49	67.04
ST5-XXL	56.05	58.19	76.14	63.46
GTR-T5-XXL	52.57	60.10	78.27	63.65
Opinion Mining Sentence Embeddings				
SentiCSE	39.47	35.66	49.23	41.45
StanceSBERT	44.96	40.26	57.54	47.59
Tourism Mining Sentence Embeddings				
Word2Vec$_{CBOW}$	62.73	63.18	72.83	66.25
Word2Vec$_{SG}$	60.27	65.23	76.46	67.32
FastText$_{CBOW}$	59.73	55.15	71.26	62.05
FastText$_{SG}$	59.93	61.40	74.89	65.41
TourBERT	29.70	32.13	44.86	35.56
TourCSE $K = 10$	**62.80**	66.21	**84.54**	**71.18**

Table 3: Performance comparison of different sentence embedding models across datasets, using Macro Average Precision. Overall, **TourCSE** outperforms both general and opinion mining models.

B.2   Aspect Category Sentiment Analysis (Neutral)

We added the NEUTRAL sentiment and extracted it using queries of the form "okay {aspect}". An ablation study on different values of K is provided in Figure 9 and a model comparison is shown in Table 4.

Figure 9: Macro Average Precision scores for different values of K during positive sample generation. Overall, we observe results consistent with those obtained without the neutral sentiment, as described in Section 4.1.

	HotelOATS	Rest16	Rest14	Avg.
General Sentence Embeddings				
all-MiniLM-L6-v2	21.05	23.39	31.27	25.24
all-MiniLM-L12-v2	23.42	24.95	32.86	27.08
all-mpnet-base-v2	26.80	29.90	37.17	31.29
E5-small-v2	23.81	26.28	37.86	29.32
E5-base-v2	24.70	30.05	40.10	31.62
E5-large-v2	24.17	29.18	39.21	30.85
E5-Mistral-7B-Instruct	23.00	27.53	33.84	28.12
GTE-base-v1.5	26.05	31.22	42.62	33.30
GTE-large-v1.5	27.61	33.74	42.78	34.71
GTE-ModernBERT	29.67	**36.99**	**49.06**	38.57
ST5-XXL	**31.04**	36.56	48.29	**38.63**
GTR-T5-XXL	22.26	29.21	35.53	29.00
Opinion Mining Sentence Embeddings				
SentiCSE	21.07	22.87	30.89	24.94
StanceSBERT	24.59	25.03	33.96	27.86
Tourism Mining Sentence Embeddings				
Word2Vec$_{CBOW}$	22.45	23.64	28.59	24.89
Word2Vec$_{SG}$	21.46	24.44	28.96	24.95
FastText$_{CBOW}$	21.54	21.92	26.74	23.40
FastText$_{SG}$	20.56	24.08	27.82	24.15
TourBERT	12.73	14.67	21.13	16.18
TourCSE $K = 10$	31.02	36.19	43.45	36.89

Table 4: Performance comparison of different sentence embedding models across datasets, using Macro Average Precision. Overall, **TourCSE** is slightly outperformed by the general-purpose model.

C CAt

C.1 Background

Between 2018 and 2020, several studies aimed to improve implicit aspect extraction using neural network architectures based on Word2Vec features (He et al., 2017; García-Pablos et al., 2018; Luo et al., 2019). Tulkens and van Cranenburgh (2020) argued that such architectures are unnecessary, showing that relying solely on Word2Vec embeddings achieve competitive results. Their method is based on two main concepts:

- Incorporating an attention mechanism to assign higher weights to tokens that are more similar to the most frequent aspect embeddings.

- Computing cosine similarity between the mean weighted token embeddings of a sentence and a target topic embedding.

Initially, CAt uses word embeddings of label names (e.g., *food*) as the target. In contrast, we use cluster centroids derived from identified topics (Figure 2, e.g., *food, pastries, breakfast*).

C.2 Is CAt Outdated?

Although improvements in unsupervised implicit aspect extraction have been reported for pipelines using pseudo-labeling to train transformer-based language models (Nguyen et al., 2023; Shi et al., 2021), direct comparisons with CAt are not entirely fair. CAt can generalize beyond annotated aspects in evaluation because Word2Vec embeddings naturally group semantically related words into thematic clusters (see Figure 2). In contrast, pseudo-labeling pipelines from related work are over-optimized to extract only the aspects present in the evaluation set. Furthermore, since CAt was not evaluated using pseudo-labeling, it remains unclear whether these newer pipelines (somewhat complex and less reproducible) truly outperform a basic Word2Vec clustering approach.

C.3 Reimplementation

We compare our reimplementation of CAt with the results reported by Tulkens and van Cranenburgh (2020) and ABAE (He et al., 2017). Additionally, we evaluate a state-of-the-art Natural Language Inference (NLI) model [18] using the template "this

---

[18] https://huggingface.co/MoritzLaurer/DeBERTa-v3-base-mnli-fever-anli

Figure 10: Boxplot of token similarities. The top 5 tokens with the highest variance are related to the topic FOOD, while the bottom 5 tokens exhibit low variance and are not informative for any specific aspect.

Method	FOOD	STAFF	AMBIANCE
ABAE	82.8	**75.7**	74.0
Mean*	86.2 / 85.6	66.9 / 67.5	71.3 / 57.4
Softmax*	86.5 / 88.1	71.1 / 69.3	68.6 / 66.4
RBF*	86.2 / 92.1	67.3 / 78.8	70.9 / 76.6
CosineVar	88.4	72.2	**76.8**
DeBERTa$_{NLI}$	**89.1**	67.8	68.9

Table 5: F1-macro scores on the **CitySearch** dataset. For Mean, Softmax, and RBF, scores are reported as "ours / Tulkens and van Cranenburgh (2020)". Differences may stem from Word2Vec hyperparameter settings and the candidate aspect sets.

review discusses [ASPECT]". We follow the original experimental setup, tuning hyperparameters on the SemEval datasets (Pontiki et al., 2014, 2016) and evaluating performance on CitySearch (Ganu et al., 2009). Furthermore, we introduce a novel attention mechanism, **CosineVar**, detailed in Appendix F.2. As illustrated in Figure 10, the intuition behind CosineVar is that aspect-relevant tokens, such as *mushrooms*, tend to have high similarity with their corresponding candidate aspect (e.g., *FOOD*) and low similarity with others (e.g., *STAFF*). In contrast, non-aspect tokens generally exhibit relatively uniform similarity across all candidate aspect terms. Results are reported in Table 5. Overall, we find that NLI models do not outperform Word2Vec embeddings on the topics STAFF and AMBIANCE[19]. Furthermore, no single method consistently achieves the best performance across all aspects. Nevertheless, our proposed **CosVAR** attention mechanism outperforms our implementations of SoftMax, Mean, and RBF attention. Importantly, CosVAR requires only the candidate aspect

---

[19] See (Ma et al., 2021; Arakelyan et al., 2024), which empirically show that NLI models are sensitive to slight changes.

set as a hyperparameter, unlike RBF, which also depends on tuning a gamma value.

D Other Related Work

D.1 Social Media Analysis

Laureate et al. (2023) highlight that LDA (Blei et al., 2003) remains the most widely used method for social media analysis. They also provide guidance for further topic modeling development:

- Topic modeling developers should have familiarity with how topics are interpreted and the epistemologies and methodologies that guide interpretation. This understanding will inform the design of topic models, the choice of performance measures, and the validation of new evaluation metrics.

- Topic model research should, in many cases, not aim to target a broad range of settings but instead focus on a well-defined set of applications, datasets, and established interpretation protocols.

- Application-driven design and/or demonstrative case studies should be adopted. This includes the clear specification of use cases.

D.2 Tourism Opinion Mining

In tourism review opinion mining, methods typically rely on lightweight supervised or unsupervised approaches that prioritize scalability.

D.2.1 Academia

Similar to Laureate et al. (2023), Mehraliyev et al. (2022) note that scholars predominantly use LDA (Blei et al., 2003) to analyze tourism reviews due to the lack of available training data. Interestingly, Sánchez-Franco and Rey-Moreno (2022) extract aspects using BERTopic (Grootendorst, 2022) with `all-MiniLM-L6-v2` to study travelers' destination choices between coastal and urban locations. Their approach is motivated by the computational efficiency and interpretability provided by Sentence Transformer embeddings.

D.2.2 Industry

Airbnb (Mitcheltree et al., 2018) applies ABAE, a neural topic model based on Word2Vec embeddings (He et al., 2017), to analyze customer reviews. However, they find that simple k-means

clustering with ABAE does not significantly improve the identification of common aspects, consistent with Hoyle et al. (2022), who report that neural topic models are less stable and do not consistently outperform traditional algorithmic methods. Booking.com (Wang et al., 2023a) uses Sentence Transformers trained in a supervised manner with an annotation scheme based on user search behavior. This approach is motivated by the desire to avoid reliance on prompt engineering while ensuring scalability.

E Ethics Sheet

Q1: What is the framework and definition of sentiment utilized? We adopt the definition proposed by Liu (2020):

> *"A subjective statement, view, attitude, emotion, or appraisal about an entity or an aspect of an entity from an opinion holder."*

Q2: What framework is employed for sentiment analysis in the measurement of sentiment? Sentiment is modeled using a regression scale (1–5), aligned with user star ratings, and evaluated as a binary classification: `positive` or `negative`.

Q3: Will this study be made available for public use in measuring sentiment in NLP? Yes.

- **Q3.1: Is the training dataset publicly available without access restrictions?** Yes. All datasets used for training, visualization, and evaluation are publicly released.

- **Q3.2: Is the model algorithm publicly available without access restrictions?** Yes. The algorithm is openly accessible.

Q4: Is this system primarily designed for users outside the field of NLP? Yes. This research is intended to support transdisciplinary investigation.

Q5: What are the specific use cases for this system? The primary use case is content analysis of tourism reviews (Lim, 2024). Applications beyond this domain may introduce biases or yield misleading interpretations.

Q6: Who are the intended users of this system? The system targets social scientists aiming

to analyze and interpret the meanings conveyed in tourism-related reviews.

Q7: Were tests conducted to identify explicit and implicit biases in sentiment analysis models, particularly regarding sociodemographic factors? No, such bias evaluations were not performed.

Q8: Were experts from interdisciplinary fields involved in discussing the use and evaluation of sentiment analysis models in social applications? Yes, though further work is required to benchmark our approach against traditional content analysis methods (Lim, 2024).

Q9: Did the study consider potential cultural or contextual variations in sentiment interpretation? No. Sentiment was treated as directly inferred from the reviewer's star rating, without accounting for cultural variation in expression.

Q10: Were any measures implemented to mitigate potential biases in the model? Yes. We used star ratings as sentiment proxies and trained models on domain-specific data, whose biases are more interpretable than those of deep learning models (Rogers, 2021).

Model	Objective Loss	Positive Sampling	Negative Sampling
SentiCSE	Contrastive	Sentiment	Sentiment
StanceSBERT	Contrastive & Triplet	Sentiment & Topic	Sentiment & Topic & Filtering
TourCSE	**InfoNCE**	Sentiment & Topic	**Random & In-Batch Filtering**

Table 6: Comparison of contrastive learning methods for sentiment-aware sentence embeddings. We report the loss function and the strategies used for constructing positive and negative pairs. `Filtering` refers to the use of a Sentence Transformer to discard sentences based on a similarity threshold. Overall, **the creation of the TourCSE training data is simpler, as it requires only positive samples.**

Method	Training Data	Pseudo-Labels		Domain
		Aspect	**Sentiment**	
RNLI	Amazon Reviews	Double Propagation	Opinion Lexicon	E-Commerce*
NAPT	Amazon / Yelp Reviews	Frequent Nouns	Opinion Lexicon	E-Commerce*
SentiCSE	Movie Reviews	-	SentiWordNet	Agnostic*
StanceSBERT	Kialo (Debate Forums)	Metadata (Subject)	Metadata (Pro/Con)	Social Media*
TourCSE	**TripAdvisor Reviews**	**Topic Modeling**	**Star Ratings**	**Tourism**

Table 7: Overview of pseudo-labeling strategies. *Domain is not explicitly addressed in these studies but is inferred from the training data and methods. In contrast, **TourCSE is specifically tailored for tourism reviews by retrieving domain-specific topics**.

F   Algorithm & Code

F.1   CAt: Code

```python
from cat_aspect_extraction import CAt, RBFAttention  # for using the model
from reach import Reach  # for loading word embeddings

# Load in-domain word embeddings and create a CAt instance
r = Reach.load("path/to/embeddings", unk_word="UNK")
cat = CAt(r)

# Initialize candidate aspects
candidates = [
    "food",
    "service",
    "ambiance",
    "price",
    "location",
    "experience"
]

for aspect in candidates:
    cat.add_candidate(aspect)

# Add topics
cat.add_topic("food", ["taste", "flavor", "quality", "portion", "menu", "dish", "cuisine", "ingredient"])
cat.add_topic("service", ["staff", "waiter", "waitress", "service", "server", "host", "manager", "bartender"])
cat.add_topic("ambiance", ["atmosphere", "decor", "interior", "design", "lighting", "music", "noise", "vibe"])

# Compute topic score
sentence = "The food was great !".split()  # tokenize your sentence
cat.get_scores(sentence, attention=RBFAttention())
# Output: [('food', 1), ('service', 0.5), ('ambiance', 0.0)]
```

F.2   CosineVar : Algorithm

Given a matrix $S \in R^{n \times d}$ of sentence token input vectors and a matrix $C \in R^{m \times d}$ of candidate aspect vectors, we first compute the cosine similarity matrix $Z \in R^{n \times m}$, where each entry is:

$$Z_{ij} = \cos(\vec{s}_i, \vec{c}_j)$$

For each input vector $\vec{s}_i$, we compute the variance of its cosine similarities with all candidate vectors:

$$\text{var}_i = \text{Var}(Z_{i1}, Z_{i2}, \ldots, Z_{im})$$

The attention weights are then obtained by normalizing these variances:

$$\alpha_i = \frac{\text{var}_i}{\sum_{k=1}^{n} \text{var}_k}$$

The final attention vector $\alpha \in R^{1 \times n}$ reflects the relative variability of each input vector's similarity to the candidates.

Topic	Pos.	Neg.	Neu.
LOCATION	1119	48	18
FACILITIES	280	105	18
ROOMS	835	328	42
ROOM AMENITIES	219	110	8
SERVICE	1044	181	16
FOOD & DRINKS	350	82	17

Table 8: Distribution of sentiment polarity (positive, negative, neutral) by topic in the HotelOATS dataset.

Topic	Pos.	Neg.	Neu.
AMBIENCE	217	32	17
FOOD	730	213	58
LOCATION	32	1	8
DRINKS	95	17	2
SERVICE	261	269	19

Table 9: Distribution of sentiment polarity (positive, negative, neutral) by topic in the Rest16 dataset.

Topic	Pos.	Neg.	Neu.
AMBIENCE	314	112	86
FOOD	1113	260	193
SERVICE	410	252	61
PRICE	212	123	28

Table 10: Distribution of sentiment polarity (positive, negative, neutral) by topic in the Rest14 dataset.

Figure 11: Top 20 most frequent aspects extracted from HotelRec (Hotel Domain)

Figure 12: Top 20 most frequent aspects extracted from SixTripAdvisor (Restaurant Domain)

Figure 13: Distribution of extracted topics from HotelRec (Hotel Domain) for different values of K.

Figure 14: Distribution of extracted topics from SixTripAdvisor (Restaurant Domain) for different values of K.

Figure 15: UMAP projections of sentence embeddings from the HotelOATS datasets (Hotel Domain)

Figure 16: UMAP projections of sentence embeddings from the Rest16 and Rest14 datasets (Restaurant Domain)