Can LLMs Rank Candidates with Missing Sensitive Attributes Fairly?

Abstract

Large language models (LLMs) are increasingly deployed in high-stakes ranking systems used for hiring, lending, and scholarship allocation, raising concerns about fairness, accountability, and ethical use. These challenges are exacerbated in ranking settings where sensitive demographic attributes are unavailable due to legal, ethical, or practical constraints. Inferring such attributes may introduce harm by violating consent requirements, misrepresenting individuals, and reinforcing structural inequities. This work thus investigates the timely question: How is LLM-based fair re-ranking impacted when demographic information is missing? In this context, we study three alternate strategies: (1) inferring sensitive attributes using traditional third-party services prior to ranking, (2) directly prompting LLMs to produce fair rankings without explicit mention of attribute inference, and (3) employing a chain-of-thought approach in which LLMs are first prompted to infer attributes and thereafter to perform fairness-aware re-ranking. We compare these strategies across multiple datasets using established group-fairness metrics for ranking. Our experiments demonstrate that LLMs match the accuracy of leading third-party services in demographic inference. Moreover, LLMs can embed fairness objectives into rankings even without explicitly inferring sensitive attributes, revealing a new design space for fairness interventions that avoids direct demographic labeling. Lastly, few-shot prompting is found to be crucial for striking the desired balance between fairness and utility. We conclude by discussing the ethical and governance implications of deploying LLMs for fairness-critical ranking tasks. While LLMs offer flexibility under demographic uncertainty, their capacity for implicit inference also raises significant risks if adopted without transparency, evaluation, and institutional oversight. *To support reproducibility and scrutiny, we release our source code and experimental artifacts*[1].

Fair Ranking, Group-fairness metrics, LLM, Inference, Fairness Intervention

1 Introduction

Background. In recent times, AI tools have been increasingly utilized in the context of decision-making processes, becoming integral to a wide range of critical applications—from scholarship and grant decisions to job hiring—that profoundly affect humans Kim et al. (2024). Such applications involve the allocation of resources in a ranked order, where the position implies relevance or priority Qin et al. (2024). As with any transformative technology impacting society, these AI-driven advances have sparked scrutiny regarding potential risks with algorithmic fairness and bias Elliott (2024). Biases often emerge when decisions (e.g., ranking candidates for a job position) correlate with sensitive attributes such as sex or race.

While traditional AI-algorithms for incorporating fairness in rankings have been well explored Zehlike and Castillo (2020), the emergence of large language models (LLMs) demonstrating ever-increasing capabilities raises the question of whether, and if so, how LLMs could be applied for fair ranking Sun et al. (2023a;b). This issue warrants particular attention, as organizations are increasingly seeking to capitalize on recent

---

[1] https://anonymous.4open.science/r/Hidden-FaiReRTabLLM-8C73/

technological advances such as LLMs across their business tasks in pursuit of perceived productivity gains. Hence, examining the appropriateness, effectiveness, and potential harms is crucial.

Further, as empirical investigations into fairness for ranking-based decision-making have shown, progress is hindered by the limited availability of sensitive demographic attributes (e.g., sex, race, or age) needed for incorporating fairness constraints Singh et al. (2021). In practice, such attributes may be missing for multiple reasons: legal restrictions on collecting sensitive information, individuals' rights to safeguard their privacy, or practical issues such as incomplete or noisy data Council of the European Union (2016). This creates a difficult tension: fairness-aware algorithms generally require access to sensitive demographic data to measure and mitigate disparities, yet these very attributes are often unavailable in real-world systems. We do not advocate demographic inference as a deployment strategy. Instead, we audit how LLM-based ranking pipelines behave under demographic uncertainty, including when demographic signals are inferred, implicit, or absent, and we surface the resulting fairness and governance risks.

State-of-Art and Their Limitations. To address the lack of demographic data, prior work has studied the inference of these sensitive attributes using custom inference systems and the resulting impact on ranking fairness Ghosh et al. (2021; 2023); Olulana et al. (2024). This line of work highlights a shared element among most pipelines: attribute inference serves as the first step, enabling re-ranking methods to adjust exposure or relevance in a way that mitigates group-level disparities. Nonetheless, reliance on inference introduces new sources of bias and error, raising questions as to whether LLMs can perform this combined task of demographic attribute inference and fairness-aware re-ranking as effectively than traditional systems, or if they can be leveraged for fair re-ranking while bypassing explicit inference. Although LLMs have been used for re-ranking tasks Sun et al. (2023b), there is limited work that explores fairness in this context. Gao et al. (2025) consider fairness-aware reranking in special-case settings where sensitive attributes are assumed to be known and correct, and additional user information is available to the reranking model. This motivates the following research questions in the more practical context:

RQ1 (External inference): When sensitive demographic data are unavailable, should traditional third-party demographic inference services remain the default for recovering these attributes before LLM-based re-ranking?

RQ2 (LLM inference): Could LLMs themselves be leveraged to directly infer sensitive attributes, thereby reducing dependence on external inference services in fairness-aware LLM-based re-ranking frameworks?

RQ3 (Pipeline design): When using LLMs for fairness-aware re-ranking under demographic uncertainty, should attribute inference be treated as a separate preprocessing step, or integrated with ranking in an end-to-end approach, and if so, should inference be implicit or guided through chain-of-thought reasoning?

RQ4 (Role of demonstrations): How does the inclusion of few-shot exemplars influence the effectiveness of fairness-aware LLM-based re-ranking across different pipeline designs, LLM models, and datasets?

Our Approach. To explore these open research questions, we explore the role of LLMs in promoting fairness within ranking systems when ground-truth demographic data are unavailable. We assume the standard setting where the input list has items or candidates (e.g., scholarship applicants) pre-sorted by some utility criterion (e.g., relevance or performance on the task at hand). In this work, we investigate how various design choices for deploying LLMs impact both fairness and utility outcomes, specifically either by leveraging external demographic signals, by providing only implicit guidance, or by directing the model through explicit reasoning. We intentionally employ a fixed prompt structure across experiments, without task-specific prompt optimization. This design choice allows us to study baseline LLM behavior under demographic uncertainty and to isolate the effects of different fairness intervention strategies, rather than maximizing performance through generic prompt tuning.

While recent works explored the use of LLMs for the demographic attribute inference subtask, this is the first study to comprehensively evaluate LLM-based strategies for fairness-aware ranking when demographic information is missing.

Our contributions can be summarized as follows:

- **Novel problem framing.** We introduce and formalize the task of LLM-based fairness-aware re-ranking under demographic uncertainty, a research question largely unexplored in the literature. In doing so, we propose and evaluate a family of design choices, including the use of chain-of-thought prompting, that collectively define how LLMs can be leveraged for this task.
- **Interaction with external demographic inference services.** We analyze how fairness outcomes change when LLM-based ranking methods rely on demographic inference from third-party services. Our results show that fairness-aware re-ranking is highly sensitive to inference quality: low-accuracy services can substantially degrade fairness outcomes, while high-accuracy services yield improvements only under favorable conditions.
- **Auditing LLM demographic inference capacity.** We explore if LLMs themselves can infer sensitive demographic attributes; and show that LLMs can perform demographic inference comparably to third-party services, underscoring that sensitive attributes may be recoverable even when intentionally withheld.
- **Fairness without explicit inference.** We find that certain LLM-based re-ranking strategies can improve group outcomes even without explicit access to sensitive attributes, in some cases approaching the performance of methods that rely on ground-truth demographic data. This suggests a design space for fairness interventions that avoids direct demographic labeling, while raising new questions about transparency and governance.
- **Role of few-shot alignment.** We show that carefully constructed ranking examples empower LLMs to adapt their behavior to align with specific fairness goals, while concurrently improving robustness against errors in demographic inference.

What this work is NOT. Our goal is not to position LLMs as replacements for dedicated fair-ranking algorithms, nor to claim that they outperform purpose-built methods when sensitive attributes are available and usable. Instead, we examine the promises and perils of LLM-based re-ranking in real-world settings where sensitive information may be unavailable and its potential impact on fairness toward individuals in decision-making contexts. This focus is motivated by the fact that LLMs are already being deployed in decision pipelines where classical fairness mechanisms are often bypassed or infeasible to apply.

2 Related Work

Fair Ranking Approaches. Fairness has been incorporated into traditional ranking pipelines through two primary approaches: by introducing fairness constraints directly into the learning objective of the ranking model Zehlike et al. (2022a;b), or by post-processing the model's ranked output list through re-ranking Geyik et al. (2019); Singh and Joachims (2018). However, despite the growing adoption of LLMs for decision-making tasks and the increasing likelihood that companies may leverage them for fairness-aware ranking applications, this area remains largely underexplored.

LLMs and Fairness Assessment. Most work on fairness in LLM-based ranking has centered on evaluating the fairness of model outputs, rather than harnessing LLMs as proactive agents for promoting fairness in downstream ranking tasks Wang et al. (2024); Liu et al. (2025); Xu et al. (2023). Other studies evaluating fairness in LLMs include investigations into hiring biases specifically, such as discrimination against candidates with disabilities observed in ChatGPT Glazko et al. (2024), demonstration of the amplification of stereotypical biases Kotek et al. (2023) or socioeconomic biases Arzaghi et al. (2024) by LLMs.

Fairness with Missing Demographic Information. Research on fair ranking presumes access to sensitive demographic information to audit or enforce fairness constraints Zehlike and Castillo (2020); Kotek et al. (2023); Glazko et al. (2024), including in fairness evaluations involving LLMs Wang et al. (2024). Yet, in real-world scenarios, such information may be unavailable due to privacy concerns, legal restrictions, or incomplete data, raising the need for the design of new strategies that do not rely on the availability of sensitive attributes European Union (2000); U.S. Equal Employment Opportunity Commission (EEOC) (2025). Research on fairness-aware ranking with uncertainty in demographic attributes is in its infancy. Olulana et al. Olulana et al. (2024), and Ghosh et al. Ghosh et al. (2021) suggest using only highly accurate traditional inference methods; however, both works focused on traditional, non-LLM methods. To our knowledge, no

Figure 1: Proposed Framework for LLM-Based Fair Reranking with Sensitive Attributes.

work has has addressed *the research question of uncertain demographic attributes in the context of LLM-based rankings*—the topic of our current work.

Demographic Inference Using LLMs. Prior work has studied demographic inference by LLMs as a standalone task or as a tool for bias analysis AlNuaimi et al. (2024). For example, demographic attributes are inferred to analyze sexism or persona construction in LLM outputs Magnossão de Paula et al. (2025), or are perturbed to examine how non-clinical demographic cues influence downstream decisions such as clinical reasoning Gourabathina et al. (2025). A recent survey systematizes fairness approaches under incomplete demographic information across machine learning settings Wang et al. (2025), but does not address ranking-specific fairness nor the role of LLMs in re-ranking under demographic uncertainty. In contrast, our work focuses on fair re-ranking when sensitive attributes are unavailable and empirically studies how different LLM-based pipeline designs affect fairness and utility.

3 Preliminaries

3.1 Fairness-Related Concepts

A sensitive attribute is an individual's characteristic, such as race, sex, gender or age, that is commonly treated as protected under legal and regulatory frameworks and raises heightened concerns around fairness, privacy and consent U.S. Equal Employment Opportunity Commission (EEOC) (2025); European Union (2000). All candidates whose attribute values correspond to the same demographic value a_i fall into the same group, g_k. Each candidate i is also associated with a performance score $s_i \in \mathbb{R}$, representing its relevance with respect to the ranking task.

Fairness has been defined in various ways across the literature depending on the context and application Pitoura et al. (2022). In ranking scenarios, common fairness objectives include discounted cumulative fairness Yang and Stoyanovich (2017), fairness of exposure Singh and Joachims (2018), and equity of attention Biega et al. (2018). In this work, we focus on group fairness, ensuring that individuals belonging to a certain group are treated fairly relative to those belonging to another group Zehlike and Castillo (2020). In our experimental study, we measure the fairness achieved in a ranking with group fairness evaluation metrics such as fairness of exposure and discounted cumulative fairness. See the definition of these metrics in Appendix 5.1.

3.2 The Fair Re-Ranking Task

A ranking model can be trained to jointly optimize performance (here referred to as 'utility'; see note in Appendix A.2) and fairness objectives Zehlike and Castillo (2020). Alternatively, when a utility-optimized model is already available, fairness can be incorporated post hoc by applying a fair re-ranking method to its ranked output, without modifying the underlying model Zehlike et al. (2017); Geyik et al. (2019).

Problem Definition. Let a ranked list of n candidates be denoted as $C = \{(x_i, s_i)\}_{i=1}^n$, where x_i represents the feature vector of candidate i and s_i its utility or relevance score. The initial ranking is: $\tau_0 = \text{argsort}_\downarrow(s_i)$, that is, the permutation induced by sorting candidates in descending order of utility. Each candidate i is additionally associated with a demographic attribute $a_i \in \mathcal{A}$ with an unknown value. The objective of fair

re-ranking is to produce a modified ranking τ over the same candidate set C that balances utility and fairness with respect to the demographic attribute a_i, according to fairness criterion F Geyik et al. (2019); Zehlike et al. (2017); Singh and Joachims (2018).

As foundation, fair re-ranking can be formalized as an optimization problem,Singh and Joachims (2018) where the optimal permutation, τ^* is defined as

$$\tau^* = \arg \max_{\tau \in S_n} \left[\alpha \, U(\tau; s) - \beta \, \mathcal{L}_{\text{fair}}(\tau; a) \right], \tag{1}$$

where S_n denotes the set of all permutations over n candidates, $U(\tau; s)$ is a utility metric (e.g., NDCG), $\mathcal{L}_{\text{fair}}(\tau; a)$ quantifies fairness loss (e.g., exposure disparity or NDKL), and $\alpha, \beta \geq 0$ control the trade-off between utility and fairness.

In practice, a_i may be missing, making group membership uncertain. Prior work has addressed this by inferring sensitive attributes via third-party services and subsequently applying traditional fair re-ranking methods to the augmented data Ghosh et al. (2021), introducing additional assumptions through the inference step.

3.3 Missing Demographic Attributes and Inference

Demographic inference services use other candidate characteristics, like names, email addresses, or photos, to infer demographic information like a person's gender, age, or race. With several such services available, for our experiments, we select three popular methods for gender inference and two for race inference.

For gender inference, we use: (1) **Behind The Name (BTN)**[2] utilizes the etymology and historical usage of names, allowing users to input either a first name or a full name, with data drawn from national statistics agencies across various regions. (2) **Gender API (GAPI)**[3] also supports name-based gender inference using the first name or full name. It can enhance accuracy with additional inputs such as email address, location (country, IP address, browser), and publicly available governmental and social media data. (3) **Namsor (NMS)** [4], on the other hand, relies on both the first and last name and boasts extensive global coverage across languages, scripts, and regions. Its model is trained on a diverse dataset of 1.3 million names compiled from baby name statistics, reflecting a wide range of countries, languages, and ethnic backgrounds. For race inference we reuse two race/ethnicity inference setups from the pipeline proposed by Ghosh et al. (2021) to infer those sensitive attributes from full names. (1) **EthCNN** is a character-level convolutional neural network proposed by Kim (2014). (2) **Ethnicolr** is a publicly available library by Chintalapati et al. (2018) (although inspired by Hofstra et al. (2020)), which provides pretrained name-based race/ethnicity classifiers. These models use neural architectures to capture the relationship between character sequences in personal names and racial/ethnic categories. Table 3 shows the inference accuracies for each dataset used in our experiments against the external inference services (ETCNN and Etnicolr).

Gender vs. Sex. Henceforth we opt to use the term 'sex' instead of 'gender' for the reasons explained in Appendix A.3.

4 Proposed Framework: LLM-Based Fair Reranking w/ Missing Sensitive Attributes

In this section, we introduce three alternative methodologies for leveraging LLMs to achieve fair re-ranking in scenarios where the sensitive demographic attributes are missing. Each of the three proposed methodologies correspond to a similarly structured two-stage pipeline consisting of (i) data preparation followed by (ii) fair re-ranking.

4.1 Two-Stage LLM Fair Reranking Framework

We now describe the core component of two-stage pipeline referenced above shared by the three alternate strategies. The first stage prepares the inputs required for fairness-aware re-ranking, while the second stage

---

[2]https://https://www.behindthename.com/
[3]https://gender-api.com/
[4]https://namsor.app/

of the pipeline operationalizes the fair re-ranking problem defined in Section 3. This overall structure is illustrated in Fig. 1.

4.1.1 Data Preparation Stage

Since LLMs are designed to process natural language inputs Vaswani et al. (2017), the main goal of the first stage is to transform the structured tabular input data into a textual format consumable by LLM models. Building on recent methods from the literature, we employ the "List Template" serialization method introduced by Hegselmann et al. (2023) for this task. In this approach, each data row in the input list is systematically converted into a structured list of column names paired with their corresponding values. Lists candidates are indexed to enhance readability and help the LLM delineate individual records.

For the strategy where explicit inferencing is explored, this stage may additionally include demographic attribute inference. Because group fairness relies on knowledge of the group membership of the candidates, one approach employs third-party inference services to estimate missing sensitive attributes based on available features For example, sex may be inferred from a candidate's name and nationality.

4.1.2 Fair Reranking Stage

By the end of the first stage, the sensitive demographic attributes either remain missing or inferred (some potentially incorrectly), and the data is serialized. In the second stage, we use an LLM as the re-ranking mechanism. Specifically, we use a unified prompt-based instruction template to guide the model toward fairness-aware reordering. The final output is a re-ranked list that aims to balance utility and fairness.

Our *prompt design,* used in all three approaches, is a multi-layered template-based approach to guide toward generating fair and well-structured ranked outputs. At its core, the prompt consists of a fairness instruction along with the serialized input list to turn it into a fair ranking. In few-shot settings, example input-output pairs of utility-ranked lists (input) and their corresponding fairly re-ranked ordering (output) are incorporated to demonstrate the desired behavior. The prompt template includes five core components:

1. *Pre-Prompt:* This is the task context, defining the LLM's role and goals (e.g., ranking officer, loan officer). It is included as a system prompt for instruction-tuned models like `Llama-Instruct`.

2. *Fairness Instruction:* The fairness instruction is a statement that provides details on the attribute to be considered by the LLM when incorporating fairness (e.g., sex, race):

   ```
   Re-rank the following list to incorporate fairness with respect to {attribute}.
   ```

   We deliberately do not instantiate a specific fairness definition, allowing us to evaluate how LLMs respond to a notion of fairness as a basic signal.

3. *Serialized Input List:* Depending on the strategy, the input may include names, scores, and optionally the inferred sensitive attributes.

4. *Few-Shot Examples:* Example rankings are formatted as lists of n candidates, where the input is sorted by utility and the output reflects fair re-ranking generated using a standard fair ranking algorithm such as DetConstSort Geyik et al. (2019). Only examples yielding high fairness scores (based on exposure ratio) are utilized, ensuring quality guidance.

5. *Post-Prompt:* This final component guides the LLM in structuring its output in the expected format.

Building on this representation, we construct the input prompt p based on its components as:

$$p = P\,[\,\oplus\,\mathcal{S}\,] \oplus T \oplus \texttt{TabSerialize}(C, a) \oplus O, \tag{2}$$

(a) Approach 1 (EXP): LLM Fair Re-Ranking Using Attribute Inference via Third-Party Service

(b) Approach 2 (IMP*): LLM-Based Fair Re-Ranking without Sensitive Attribute Inferencing

(c) Approach 3 (CoT): CoT-FairRank

Figure 2: Proposed approaches for LLM-based fair re-ranking with missing sensitive attributes

where $\oplus$ denotes concatenation, P is the pre-prompt, $\mathcal{S}$ represents optional exemplar shots, T is the fairness instruction, `TabSerialize()` denotes the table-to-text serialization of the data C with attributes a,[5] and O is the post-prompt.

4.2 Approach 1: LLM Fair ReRanking Using Attribute Inference via Third-Party Service

This approach, seen in Fig. 2a, conditions the LLM's re-ranking stage on externally inferred sensitive attributes obtained during data preparation. A structured prompt example is shown in Fig. 15 (Appendix Section A.11).

Data Preparation Stage. Missing sensitive attribute values are estimated using *traditional demographic inference services,* such as, Behind-the-Name, Gender-API, etc (see Section 3.3),

We evaluate three widely used name-based sex inference services, which, as we show in Section 5, exhibit differing levels of errors. We represent the inferred demographic attribute for a candidate i as $\tilde{a}_i = g(x_i)$, and the list of inferred attributes for all candidates in C is denoted $\tilde{a}$. These inferred attributes are incorporated into the serialized representation defined in Section 4.1. The resulting prompt is therefore expressed in terms of $\tilde{a}$ rather than ground-truth value attributes:

$$p = P\left[\oplus\mathcal{S}\right] \oplus T \oplus \texttt{TabSerialize}(C, \tilde{a}) \oplus O. \tag{3}$$

Fair Reranking Stage The LLM receives the serialized list augmented with inferred attributes and utility scores. The prompt explicitly discloses that demographic attributes were inferred rather than ground-truth (see Fig. 15). Optionally, we include in the prompt few-shot examples (shots) consisting of names, ground-truth attributes, and corresponding scores. The examples are presented as input-output pairs, illustrating representative instances of typical inputs alongside their corresponding outputs.

---

[5]Note that the demographic attribute vector is a, the individual attribute values are a_i and the inferred demographic attribute vector is represented as $\tilde{a}$

Baselines		Approach 1 (EXP)		Approaches 2 (IMP*) & 3 (CoT)	
Initial	ranked by ground-truth scores	GT	using ground-truth sens. attribute	IMP	(App #2) zero-shot
		GAPI	with Gender API	IMP-P	(App #2) sens. attr. present in shots
DCS	ranked by DetConstSort	BTN	with Behind the Name	IMP-A	(App #2) sens. attr. absent in shots
		NMS	with Namsor	CoT	(App #3) chain-of-thought
		ETHCNN	with EthCNN		
		Ethnicolr	with Ethnicolr		

Table 1: Fair ranking strategies, including baselines. Legend: EXP: Explicit-FairRank, IMP*: Implicit-FairRank, CoT: CoT-FairRank.

4.3 Approach 2: LLM-Based Fair ReRanking without Sensitive Attribute Inferencing

This approach, seen in Fig. 2b does not rely on support from external cues or explicit demographic inference instruction. Instead, it requires the LLM to perform such inference implicitly in order to incorporate fairness. A structured prompt example is illustrated in Fig. 16 (Appendix).

Data Preparation Stage. We convert the input table to a serialized list without performing demographic inference (Fig. 2b). The attributes in their serialized format are thus: ID, name, and the score. Hence $\tilde{a}$ is absent in p (see Eq. 2).

Fair Reranking Stage The LLM receives only IDs, names, and utility scores, requiring it to rely on internal signals to perform fairness-aware re-ranking (Fig. 2b). Prompts do not reference demographic attributes or inference. We consider *two few-shot variants*. IMPLICIT-A, where the sensitive attributes are absent from the examples and IMPLICIT-P, where ground-truth attributes are present in the examples. These variants assess performance under fully unassisted conditions versus settings where examples implicitly convey the role of demographic information in fair re-ranking.

4.4 Approach 3: Chain-of-Thought Inferencing and Fair ReRanking via LLM

This approach, depicted in Fig. 2c, assesses whether instructing the LLM explicitly to first infer the missing attributes and then to use those results for fair re-ranking improves fairness outcomes. To model this, we utilize Least-to-Most Zhou et al. (2023), an enhanced form of the Chain-of-Thought style of prompting. An example prompt is illustrated in Fig. 17.

Data Preparation Stage Same as in Approach 2.

Fair Reranking Stage. In the fair re-ranking stage, the LLM is explicitly guided to perform a structured multi-step reasoning process in a chain-of-thought format (illustrated in Fig. 17 from Appendix A.8). First, it is instructed to infer the sensitive attribute from the candidates' names. Thereafter, it is instructed to utilize these inferred attributes to conduct fairness-aware re-ranking. The initial input (in the first step) includes only names and utility scores. In the second step, the LLM-inferred attributes are explicitly reintroduced into the input to perform the final re-ranking step.

5 Design of our Experimental Study

Datasets. We select ranking datasets in which measured fairness is low under standard ranking procedures, making them appropriate for evaluating fairness-aware re-ranking under demographic uncertainty. We utilize four datasets, each containing sensitive attributes such as sex or race:

- STARTUP FOUNDERS: This dataset is derived from publicly available records of U.S. startup founders who raised Series A funding, compiled from Crunchbase. We use the aggregated Series A funding amounts as reference scores for ranking founders. In this dataset, race is used as the sensitive attribute and is modeled as a multivalued attribute with four categories.[6]

- (W)NBA: This dataset captures performance statistics from elite basketball players across the NBA and WNBA. We use the all-time career points up to 2017 as the reference scores.

- BOSTONMARATHON: Collected from the 2017 Boston Marathon, this dataset provides stage-wise performance data for runners across sex categories. We use the 'Official Time' column for our reference scores. Times are normalized such that the longest time is given the lowest score to have an appropriate relevance-ordered ranking set [7].

- COMPAS: This dataset originates from a public investigation into recidivism risk assessments used in the U.S. justice system involving the COMPAS algorithm Larson et al. (2016). We use the recidivism (*likelihood to re-offend*) scores as reference scores.

We also examine whether fairness-aware re-ranking strategies that perform well for one sensitive attribute (e.g., sex) exhibit similar behavior when applied to a different attribute (e.g., race), across distinct datasets (Appendix **??**).

Dataset Preparation. Each data set is split into 80% for *curating the few-shot examples* (detailed below) and 20% for *testing*. To identify the disadvantaged group, we plot skew graphs (Section 5.1) and observe which group exhibits lower representation at the top. For test set generation, we sample, from the test split, 10 subsets of candidates each to account for variance, ensuring that the relative skews in group representation mirrors that of the original test set (Section 5.1). To best understand the effect of re-ranking, each group defined by the sensitive attribute is equally represented in the subsets. Specifically, in the gender-based experiments, there are 25 female and 25 male instances, while in the race-based experiments, each racial group contains 25 instances.

Creating Example Shots. Using the 80% portion of the datasets, we sample four distinct subsets and apply the fairness-aware re-ranking algorithm, DetConstSort Geyik et al. (2019) to each. This process yields fairly re-ranked sets, which we use as few-shot examples in our experiments. To ensure that the shots are expressive, we constrain the average exposure ratio to be close to 1 (Section 5.1).

Comparative Fair Ranking Baseline Methods. We evaluate our approach against two traditional baselines. The first baseline corresponds to the original utility-based rankings, allowing us to assess the trade-off between utility and fairness introduced by our method. The second baseline employs DetConstSort Geyik et al. (2019), a widely-used fairness-oriented re-ranking algorithm based on traditional machine learning techniques, to generate fairer rankings. Additionally, for our first LLM-based strategy (Approach 1), we include an extra set of baselines where the re-ranking is guided by ground-truth demographic attributes to benchmark the performance of inference-based fairness adjustments.

LLMs used as Backbone Models. We experiment with three LLMs selected for their diversity and relevance to the task (Table 2), namely, open-source models—DeepSeek and LLaMA—and proprietary model, Gemini. DeepSeek and LLaMA were accessed using paid production-grade services; while we experimented with both the freely available version and the paid API access of Gemini. We use few-shot prompting as a reproducible, model-agnostic means of controlling model behavior across backbones and versions.

Third-Party Attribute Inference and Treatment of Unknowns. We experiment with three popular services for inferring missing demographic attributes (see Section 3.3). In our study, we experiment with the sensitive attribute being inferred given a person's name as inherent component of Approach 1 (Section 4.2). Each inference service returns candidates whose sensitive attribute could not be determined with a degree of certainty above a threshold, hereby referred to as 'unknowns'. We addressed this by following

---

[6]We recognize that representing race as a fixed set of categories is inherently limited and may obscure social, cultural, and individual complexity.

[7]https://www.kaggle.com/datasets/rojour/boston-results?resource=&select=marathon_results_2017.csv

Model (shorthand)	Official model name	Access method
Gemini	`gemini-2.0-flash-thinking-exp-01-21`	Gemini API (free)
	`gemini-3-flash-preview`	Gemini API (paid)
DeepSeek	`deepseek-chat` (DeepSeek-V3)	Paid API (also available for free via
	`DeepSeek-V3.2` (used for race-based experiments)	Hugging Face)
LLaMA	`Llama-3-8B-Instruct`	Hugging Face transformers (open-source)

Table 2: Large language models used in our experiments, including shorthand references, official model names, and access modalities.

the steps in Olulana et al Olulana et al. (2024) for the gender experiments. Table 1 collects all strategies and their abbreviated names used in this paper, including baselines. For the race inference, we exclude candidates labeled as unknown from the analysis. We adopt this strategy to avoid introducing an additional heterogeneous group whose composition and size depend on inference confidence and may correlate with race itself. Treating unknowns as a separate group in the race setting could confound fairness evaluation and obscure interpretation of race-based disparities. We therefore restrict the race experiments to candidates with confidently inferred race labels. We note the exclusion of candidates with unknown race as a limitation of this part of the study.

5.1 Evaluation Metrics

To assess fair rankings, we use three fairness metrics—two based on representational parity (Skew and NDKL) and one on exposure ratio—and a standard utility metric.

5.1.1 Skew Geyik et al. (2019).

Skew quantifies the relative visibility of a demographic group within the top prefix of a ranking. For a given group $g \in G$, the skew at position k in a ranking τ is computed as:

$$Skew@k(\tau)_g = \frac{p_{\tau@k,g}}{p_{C,g}}, \tag{4}$$

where $p_{\tau@k,g}$ is the share of group g in the top k ranked candidates, and $p_{C,g}$ is the group's proportion across the full candidate set C.

5.1.2 NDKL Geyik et al. (2019).

The Normalized Discounted Kullback-Leibler divergence measures the divergence between the group distribution in the top k results and that of the entire candidate set C, with a logarithmic discount applied to account for position relevance:

$$NDKL@k(\tau) = \frac{1}{Z} \sum_{i=1}^{k} \frac{1}{\log_2(i+1)} d_{KL}(P_{\tau@k}||P_C), \tag{5}$$

where $d_{KL}(P_{\tau@k}||P_C)$ is the KL-divergence between group distributions in the top-k candidates and the full set C and $Z = \sum_{i=1}^{k} \frac{1}{\log_2(i+1)}$ is a normalization constant.

Average Exposure Ratio (AveExpR CI-95) Singh and Joachims (2019).

The Average Exposure Ratio quantifies fairness in terms of visibility by comparing the average exposure allocated to the disadvantaged group against that received by the advantaged group in a given ranking τ:

$$Average\ Exposure\ Ratio(\tau) = \frac{Average\ Exposure(\tau, dis)}{Average\ Exposure(\tau, adv)}, \tag{6}$$

Here, the average exposure for any group g is computed as:

$$Average\ Exposure(\tau, g) = \frac{1}{|a|} \sum_{a_i \in g} Exposure(\tau, a_i),$$

where individual exposure is determined by position-based visibility:

$$Exposure(\tau, a_i) = \frac{1}{\log_2(\tau(a_i) + 1)}.$$

In our evaluation, we average this ratio across 10 independent runs (that is, 10 individual test sets) and report 95% confidence intervals. A ratio of 1.0 indicates equitable exposure, with values below or above signifying under- or over-exposure of the disadvantaged group, respectively.

5.1.3 Normalized Discounted Cumulative Gain (NDCG) Järvelin and Kekäläinen (2002).

NDCG, a standard metric for quantifying ranking quality based on candidate relevance, is defined as:

$$NDCG@k(\tau) = \frac{1}{Z} \sum_{i=1}^{k} \frac{s_i}{\log_2(i + 1)}, \tag{7}$$

where s_i is the relevance score assigned to the candidate at position i and Z is a normalization factor ensuring the metric ranges from 0 to 1. A perfect ranking (where the highest-relevance candidates appear first) yields NDCG = 1.

6 Experimental Study: Results and Analysis

In this section, we analyze LLM-based fairness-aware re-ranking across four settings: demographic inference from names (§6.1), fair ranking with ground-truth attributes (§6.2), re-ranking under missing demographic information (§6.3), and the impact of few-shot examples on integrated inference and re-ranking (§6.4).

6.1 Capability of LLMs for Demographic Attribute Inference

Given that fair re-ranking inherently relies on access to the group membership of each candidate, we first study the *accuracy of the sensitive attribute inference* that serves as a core component of our fair re-ranking methods. For this, we evaluate how accurately LLMs infer sensitive attributes, and compare this with the performance of the third-party attribute inference services (**RQ1 & RQ2**)[8]. LLM-based attribute inference is a core component of our CoT-FairRank strategy (Approach 3), while third-party inference services are utilized by EXP[9] (Approach 1). IMP performs ranking without attribute inference, and is thus discussed later in Section 6.3. While name-based demographic inference risks reproducing cultural and linguistic biases, these methods have prevalence in real-world systems. Our goal is not to endorse these practices, but instead to evaluate how commonly deployed inference tools interact with fairness-aware re-ranking in practice and to surface their limitations and risks. ***Note that for each dataset, we conduct a memorization test to ensure that inference results by the LLMs are not due to memorization*** *(see Appendix A.10).*

Table 3 reports the inference accuracy yielded by third party inference services and by the inference step in CoT-FairRank for each LLM backbone model—on the test sets of the three benchmark datasets. The wide variation in demographic inference accuracies provides a robust foundation for evaluating performance across different tools with varying capabilities in demographic inference.

Except on Boston Marathon, the LLMs consistently maintain inference performance at or above the average inference service. Notably, Gemini demonstrates competitive accuracy, achieving results that are on par with those of the most highly accurate third-party inference services across all three datasets. Overall, our results show that LLMs are solid alternatives to medium and lower quality demographic inference services, providing a partial answer to **RQ2**.

---

[8]Additional results on RQ1 will be presented in Section 6.3.

[9]The names of the inference services are also used to refer to the LLM-based methods that employed them as third-party inference components.

| | | Dataset and Sensitive Attribute | | | |
	Inference Method	Startup Founders (race)	Boston Marathon (sex)	(W)NBA (sex)	COMPAS (sex)
Third-party services (Approach 1)	Gender API	–	98%	96%	99%
	Behind The Name	–	76%	75%	84%
	Namsor	–	40%	41%	40%
	EthCNN	40%	–	–	–
	Ethnicolr	37%	–	–	–
LLMs (Approach 3, 0-shot)	Gemini	73%	98%	100%	94%
	DeepSeek	55%	56%	77%	88%
	Llama	57%	63%	79%	93%

Table 3: Inference accuracy across datasets used in the experiments. Race inference is evaluated on the Startup Founders dataset, while gender inference is evaluated on the Boston Marathon, (W)NBA, and COMPAS datasets. Third-party services correspond to Approach 1 (EXP), while LLM-based inference corresponds to Approach 3 (CoT-FairRank); sensitive attribute corresponding to each dataset.

6.2 Fair Re-Ranking Capabilities of LLMs (No Shots, No Attribute Inferencing)

Next, we investigate the viability of LLMs as re-ranking models. To isolate this capability from their demographic inference performance, we conduct the evaluation using ground-truth demographic attributes. While this does not address any specific research question, it provides an important foundation for employing LLMs in the fair re-ranking task. Specifically, we use race for the Startup Founders dataset and sex for the Boston Marathon, (W)NBA, and COMPAS datasets.

Fig. 3 show the and NDKL and NDCG obtained by the different LLMs for the Startup Founders and Boston Marathon datasets when ranking is performed with access to the ground-truth demographic attributes. Across both datasets, we observe a consistent reduction in NDKL values relative to the Initial ranking, indicating improved fairness, except for Llama on the Startup Founders dataset, where the fairness metric slightly worsens. Gemini consistently outperforms the baseline fairness re-ranking algorithm (DCS) in terms of NDKL. DeepSeek performs competitively with DCS and in some cases surpasses it, particularly on the Boston Marathon dataset. Llama also improves fairness relative to the Initial ranking, although its performance remains inferior to the DCS baseline for the Boston Marathon dataset.

In terms of utility, measured by NDCG, the scores remain largely stable across models, indicating that fairness improvements generally do not come at a substantial cost to ranking quality. The only notable change occurs for Gemini on the Startup Founders dataset, where NDCG increases and outperforms the DCS baseline. Interestingly, in this case Gemini achieves both improved fairness (lower NDKL) and higher utility (higher NDCG) compared to DCS, whereas a fairness–utility trade-off might typically be expected.

These results demonstrate the LLMs' promising capacity for fair re-ranking. However, the observed inconsistencies motivate exploration of additional approaches to determine whether the performance of these LLM-based solutions can match or exceed the baseline traditional algorithm. In the following sections, we focus on the results obtained from DeepSeek and Gemini, as these models consistently demonstrated to outperform Llama.

6.3 Fair LLM-Based Re-Ranking Strategies with Uncertain Demographic Attributes (No Shots)

We evaluate fairness-aware re-ranking under demographic uncertainty by comparing a traditional baseline, DetConstSort (DCS), with zero-shot variants of the LLM-based approaches introduced in Section 4. We compute NDKLs and NDCGs on all four datasets. Fig. 4 shows NDKL (top) and NDCG (bottom) obtained on the STARTUP FOUNDERS dataset; using Gemini (two left-most columns) and DeepSeek (two right-most columns) as backbones. In this Section, we present results for the STARTUP FOUNDERS dataset, and present results for other datasets in the Appendix.

Figure 3: Fairness metrics—NDKL (left) and NDCG (right)—for LLM-based fair reranking methods evaluated across datasets.

Plots showing NDKL and NDCG metrics for LLM-based fair reranking methods across datasets.

Figure 4: Fairness (NDKL) and Utility (NDCG) for LLM-based reranking on the STARTUPFOUNDERS dataset.

The Approach 1 (EXP third-party services-based) results are ordered based on the quality of the third-party attribute inference services used, namely, from most (GAPI) to least accurate (NMSOR). Across all settings, the LLM-based approaches (GT, GAPI, IMP, and CoT-FairRank) achieve lower representation disparity (NDKL) than DCS, except when external demographic inference is highly inaccurate (BTN, NMSOR). All variants improve over the Initial ranking, even without exemplar guidance, indicating that LLMs can exhibit fairness-aware behavior without task-specific tuning. In addition, we observe that:

- *Approach 1 (EXP).* When inferred sensitive attributes are accurate or have low error rates (e.g., via GAPI; see Section 5), fairness improves relative to the initial ranking, as reflected by lower NDKL values. In contrast, higher inference error rates (e.g., with NMSOR) degrade fairness, leading to worse NDKL outcomes; the same pattern is observed for AveExpR (see Section A.1 in Appendix). This degradation arises because misclassified attributes misguide the re-ranking process, causing the fairness objective to be optimized with respect to incorrect groups. Accordingly, in addressing **RQ1**, external demographic inference services are effective only when their predictions are sufficiently accurate; otherwise, they risk undermining fairness rather than improving it.
- *Approach 2 (IMP).* We observe consistent improvements in NDKL relative to the Initial ranking, with performance exceeding the traditional fair re-ranking algorithm (DCS) and, under conditions of perfect (100%) inference accuracy, matching that of Approach 1. For AveExpR (Section A.1 in Appendix), IMP likewise improves upon the Initial ranking and reaches parity with Approach 1 when inference is error-free. In addressing **RQ3**, these results indicate that LLMs can, in some settings, effectively act as the inference mechanism within fair re-ranking pipelines.
- *Approach 3 (CoT).* This approach yields further improvements in NDKL over both the Initial ranking and DCS. For AveExpR (Section A.1 in Appendix), we also observe consistent gains relative to Initial, reinforcing the advantage of designs that leverage LLMs for inference and thereby providing additional support for **RQ3**. Notably, CoT consistently outperforms IMP, suggesting that within end-to-end LLM frameworks, chain-of-thought reasoning is the preferred strategy.

Figure 5: Fairness (NDKL and Average Exposure) and Utility (NDCG) metrics for fair reranking results varying the number of shots using Gemini on STARTUP FOUNDERS dataset.

Figure 6: Fairness (NDKL and Average Exposure) and Utility (NDCG) metrics for fair reranking results varying the number of shots using DeepSeek on STARTUP FOUNDERS dataset.

In sum, LLM-based approaches are promising: fairness improves upon Initial's, while utility remains relatively stable.

6.4 Effect of Shots on Fair LLM-Based Re-Ranking Strategies With Uncertain Demographic Attributes

Next, we investigate how the inclusion of few-shot examplars of fairly ranked lists affects the outcomes of LLM-based re-ranking, i.e., whether they improve the model's ability to balance fairness with utility (**RQ4**). As a side objective, we study the extent to which providing shots can counteract various error levels of the inferred demographic information.

We report results for Gemini and DeepSeek on the STARTUP FOUNDERS (Figs. 5, 6) and BOSTONMARATHON (Figs. 7, 8) dataset in this section; [10] results for additional datasets are provided in the Appendix (Figures 12, 13 and 14). For third-party inference services with high accuracy (Approach 1), adding exemplar shots consistently brings the results closer to those of the fair re-ranking baseline, DCS. When inference error is negligible (GT, GAPI), few-shot prompting yields NDKL values comparable to DCS. In contrast, when inference quality is poor (NMSOR), the fairness signal conveyed in the few-shot examples cannot be adequately leveraged due to the (lack of) accuracy in demographic inference, thus not yielding a clear improvement on re-ranking effectiveness. Approaches IMP-A, IMP-P, and CoT-FairRank also benefit from exemplar shots, with CoT-FairRank achieving DCS-level fairness using fewer examples. Overall, these results show that few-shot prompting can enable LLM-based re-ranking to match dedicated fairness algorithms while largely preserving utility, addressing **RQ4**.

6.5 Comparison of Alternate Backbone LLMs for Fair Re-Ranking

In this section, we examine the impact of different LLM backbone models (Gemini, DeepSeek, and Llama) on the effectiveness and stability of LLM-based fair re-ranking, and in particular, the CoT-FairRank, IMP-A, and IMP-P approaches. These models operate without external inference services, representing scenarios where LLMs receive no assistance regarding demographic attributes. This analysis directly builds upon our investigation of **RQ4**, showing how backbone choice directly impacts fairness–utility outcomes under

---

[10]Similar results are reflected on the other datasets. See Appendix - (Figures 12, 13 and 14)

Figure 7: Fairness (NDKL and Average Exposure) and Utility (NDCG) metrics for fair reranking results varying the number of shots using Gemini on BOSTON MARATHON dataset.

Figure 8: Fairness (NDKL and Average Exposure) and Utility (NDCG) metrics for fair reranking results varying the number of shots using DeepSeek on STARTUP FOUNDERS dataset.

demographic uncertainty. Fig. 9 and, from Appendix A.9, Figures 18 and 19 respectively present the results of CoT-FairRank, IMP-A and IMP-P, evaluated across three LLMs. Across the three strategies, Gemini and DeepSeek perform comparably, with the inclusion of shots consistently reducing variability and improving effectiveness. Notably, DeepSeek reaches stability and near-optimal results after about the third shot, while Gemini follows closely with nearly indistinguishable performance. In contrast, Llama fails to improve fairness relative to the initial baseline.

7 Discussion

Here, we reflect on our findings, clarify our contributions, and discuss key implications, opportunities, and limitations.

Empirical Findings Under Demographic Uncertainty. This work examined whether LLMs can support fairness-aware re-ranking when sensitive demographic attributes are missing, uncertain, or unavailable. Across a range of experimental settings, we observed that despite these scenarios, LLM-based re-ranking strategies can improve fairness outcomes, as measured by exposure- and representation-based metrics, while largely preserving ranking utility. The effectiveness of different strategies however varies substantially depending on how demographic signals are incorporated.

Figure 9: Fairness (NDKL) and Utility (NDCG) for CoT-FairRank across LLMs with shots varying from 0 to 5 on BOSTONMARATHON.

Explicit vs. Implicit Use of Demographic Attributes. A key empirical distinction explored in this work concerns whether fairness improvements require explicit demographic inference. While strategies that rely on accurate demographic inference can mitigate *allocative harms* (exposure disparity), they introduce significant *representation harms* through misgendering and essentialism (for a taxonomy of sociotechnical harms, we refer the reader to Shelby et al. (2023)). Their performance degrades sharply when inference error is high. In contrast, we find that certain LLM-based re-ranking strategies can improve fairness outcomes even without explicitly inferring the sensitive attributes. This result highlights an important design space in which fairness-aware behavior emerges from the model's internal reasoning rather than from explicit demographic labeling.

Procedural and Distributive Fairness Considerations. Our evaluation focuses on distributive fairness outcomes, measured through established group-based metrics. The strategies in our study that avoid explicit demographic inference can circumvent mislabeling risks. Yet, they raise procedural fairness questions regarding how fairness is achieved and what information is used in the decision-making process. We do not claim to resolve these normative questions. Instead, we view our results as providing empirical evidence that can inform broader debates about procedural fairness, transparency, and accountability in ranking systems.

Legal, Ethical, and Governance Implications. The ability to improve fairness without explicitly inferring sensitive attributes has important legal and ethical implications. In many real-world settings, the collection or inference of demographic attributes is constrained by privacy regulations or anti-discrimination law. Our findings suggest that LLM-based re-ranking may, in some cases, enable fairness interventions that operate under such constraints. However, this possibility also underscores the need for careful governance, as LLMs may implicitly rely on demographic signals in ways that are difficult to audit or explain. Human oversight and institutional safeguards remain essential.

Scope and Limitations. Our contribution is intentionally scoped to an empirical investigation of fairness-aware re-ranking under demographic uncertainty. We do not claim algorithmic optimality, nor do we advocate for the deployment of LLM-based ranking systems in high-stakes settings without meaningful human involvement and accountability. We do not attempt to resolve broader societal questions concerning the legitimacy of demographic inference, the role of human judgment, or long-term social impacts. Addressing these issues requires interdisciplinary engagement beyond the scope of this work and represents an important direction for future research.

8 Conclusion

This paper examined the possibilities and risks of using LLMs as backbone technologies for fairness-aware re-ranking in settings where sensitive attributes may be missing or uncertain. By evaluating multiple LLM-based re-ranking strategies, we showed that LLMs can support fairness improvements under demographic uncertainty, both when demographic attributes are inferred and, in some cases, even when explicit inference is avoided altogether.

Ethical Considerations Statement

Privacy and Ethical Considerations of Demographic Inference. While demographic attributes are often unavailable due to privacy protections or legal constraints, we acknowledge that the ability of LLMs to infer such attributes raises the very same concerns. Our results should not be interpreted as endorsing demographic inference; rather, the fact that LLMs can accurately infer undisclosed attributes highlights a significant privacy risk, particularly when individuals have intentionally chosen not to disclose sensitive information. Accordingly, our findings motivate caution and underscore the importance of fairness-aware ranking approaches that avoid explicit demographic labeling, alongside stronger governance and safeguards against misuse.

Utilization and Access to Tools, Models, and Data Sets. All components used in this study—including datasets, AI models, and inference tools—were obtained from publicly accessible sources. Our use of these tools was limited to controlled experimental analysis for research purposes only and does not constitute deployment, profiling, or decision-making about real individuals. While some of the experiments in this paper examine the ability of language models or third-party services to infer demographic attributes from names, this inference is studied as an object of analysis rather than as a recommended practice. We do not endorse the use of demographic inference in operational systems, without appropriate legal basis, consent, or institutional safeguards.

Importantly, a central contribution of this work is to demonstrate that fairness-aware re-ranking can, in some cases, be achieved without explicitly inferring or conditioning on sensitive attributes. This finding directly responds to legal, ethical, and policy constraints that restrict demographic inference and motivates alternative fairness interventions that operate under such constraints.

For reference, the licensing terms for the inference tools can be found at the following URLs: **GenderAPI**, gender-api.com/en/terms-of-use; **Behind The Name**, behindthename.com/info; **Namsor**: namsor.app/terms-and-conditions. All source code we produced and experimental artifacts of our experimental study will be made available on *github*.

Broader Impact Statement. While our research investigates whether LLMs can fairly rank candidates when sensitive attributes are missing, we emphasize that relying on imperfect demographic inference tools is generally unadvisable. Fairness is highly contextual, varying based on the specific task, model, and dataset. Therefore, practitioners should continuously evaluate the fairness of ranking systems and carefully consider if substituting true demographic information with inferred data might lead to unintended negative consequences.

Researcher Positionality. Our backgrounds in computer and data science fundamentally shape the lens through which we investigate research questions and design or evaluate computational methods addressing fairness challenges. This perspective informs how we critically engage with the societal implications arising from the integration of digital technologies. We do acknowledge that social scientists and perspectives by other researchers on these critical societal issues is imperative to ensure that potential harm to individuals in our society is avoided to the greatest extend possible.

Generative AI Usage Statement

No Generative AI tools were used in the creation of the figures or text in this work. AI-based tools were employed only for subsequent light grammatical proof-reading of this manuscript. The conceptual development and intellectual contributions of this work are solely those of the authors, and were conducted independently of LLMs.

References

Khaled AlNuaimi, Gautier Marti, Mathieu Ravaut, Abdulla AlKetbi, Andreas Henschel, and Raed Jaradat. 2024. Enriching Datasets with Demographics through Large Language Models: What's in a Name? *arXiv preprint arXiv:2409.11491* (2024).

Mina Arzaghi, Florian Carichon, and Golnoosh Farnadi. 2024. Understanding intrinsic socioeconomic biases in large language models. In *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, Vol. 7. 49–60.

Asia J. Biega, Krishna P. Gummadi, and Gerhard Weikum. 2018. Equity of Attention: Amortizing Individual Fairness in Rankings. In *Proceedings of the 41st International ACM SIGIR Conference*. 405–414.

Rajashekar Chintalapati, Suriyan Laohaprapanon, and Gaurav Sood. 2018. Predicting race and ethnicity from the sequence of characters in a name. *arXiv preprint arXiv:1805.02109* (2018).

Council of the European Union. 2016. Regulation (EU) 2016/679 of the European Parliament and of the Council.

Hannah Devinney, Jenny Björklund, and Henrik Björklund. 2022. Theories of "Gender" in NLP Bias Research. In *Proceedings of the 2022 ACM Conference on Fairness, Accountability, and Transparency* (Seoul, Republic of Korea) *(FAccT '22)*. Association for Computing Machinery, New York, NY, USA, 2083–2102. doi:10.1145/3531146.3534627

Mark T. Elliott. 2024. Schools of AI in the Public Sector: Fairness and Accountability Concerns. In *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, Vol. 7. 11–13.

European Union. 2000. EU Equality Directives (2000/43/EC, 2000/78/EC, 2006/54/EC). https://eur-lex.europa.eu

Jingtong Gao, Bo Chen, Xiangyu Zhao, Weiwen Liu, Xiangyang Li, Yichao Wang, Wanyu Wang, Huifeng Guo, and Ruiming Tang. 2025. Llm4rerank: Llm-based auto-reranking framework for recommendations. In *Proceedings of the ACM on Web Conference 2025*. 228–239.

Sahin Cem Geyik, Stuart Ambler, and Krishnaram Kenthapadi. 2019. Fairness-Aware Ranking in Search and Recommendation Systems. In *Proceedings of the 25th ACM SIGKDD Conference*. 2221–2231.

Avijit Ghosh, Rohan Dutt, and Christo Wilson. 2021. When Fair Ranking Meets Uncertain Inference. In *Proceedings of the 44th ACM SIGIR Conference*. 1033–1043.

Avijit Ghosh, Pablo Kvitca, and Christo Wilson. 2023. When fair classification meets noisy protected attributes. In *Proceedings of the 2023 AAAI/ACM Conference on AI, Ethics, and Society*. 679–690.

Ksenia Glazko, Yasmeen Mohammed, Ben Kosa, Varshini Potluri, and Jennifer Mankoff. 2024. Identifying and Improving Disability Bias in GPT-Based Resume Screening. In *Proceedings of the ACM Conference on Fairness, Accountability, and Transparency*. 687–700.

A. Gourabathina, W. Gerych, E. Pan, and M. Ghassemi. 2025. The Medium Is the Message: How Non-Clinical Information Shapes Clinical Decisions in LLMs. In *Proceedings of the 2025 ACM Conference on Fairness, Accountability, and Transparency*. ACM, 1805–1828.

Zach Harned and Hanna Wallach. 2019. Stretching human laws to apply to machines: The dangers of a" colorblind" computer. *Fla. St. UL Rev.* 47 (2019), 617.

Stefan Hegselmann, Alberto Buendia, Henk Lang, Mayank Agrawal, Xiaoqian Jiang, and David Sontag. 2023. TabLLM: Few-Shot Classification of Tabular Data with Large Language Models. In *International Conference on Artificial Intelligence and Statistics*. 5549–5581.

Bas Hofstra, Vivek V Kulkarni, Sebastian Munoz-Najar Galvez, Bryan He, Dan Jurafsky, and Daniel A McFarland. 2020. The diversity–innovation paradox in science. *Proceedings of the National Academy of Sciences* 117, 17 (2020), 9284–9291.

Kalervo Järvelin and Jaana Kekäläinen. 2002. Cumulated Gain-Based Evaluation of IR Techniques. *ACM Transactions on Information Systems* 20, 4 (2002), 422–446.

Yoon Kim. 2014. Convolutional neural networks for sentence classification. *arXiv preprint arXiv:1408.5882* (2014).

Yubin Kim, Chanwoo Park, Hyewon Jeong, Yik S Chan, Xuhai Xu, Daniel McDuff, Hyeonhoon Lee, Marzyeh Ghassemi, Cynthia Breazeal, and Hae W Park. 2024. Mdagents: An adaptive collaboration of llms for medical decision-making. *Advances in Neural Information Processing Systems* 37 (2024), 79410–79452.

Hadas Kotek, Rikker Dockum, and David Sun. 2023. Gender bias and stereotypes in large language models. In *Proceedings of the ACM collective intelligence conference*. 12–24.

Jeff Larson, Surya Mattu, Lauren Kirchner, and Julia Angwin. 2016. How we analyzed the COMPAS Recidivism Algorithm. https://www.propublica.org/article/how-we-analyzed-the-compas-recidivism-algorithm

Wei Liu, Baisong Liu, Jiangcheng Qin, Xueyuan Zhang, Weiming Huang, and Yangyang Wang. 2025. Fairness identification of large language models in recommendation. *Scientific Reports* 15, 1 (2025), 5516.

Jeffrey W. Lockhart, Molly M. King, and Christin Munsch. 2023. Name-based demographic inference and the unequal distribution of misrecognition. *Nature Human Behaviour* 7, 7 (July 2023), 1084–1095. doi:10.1038/s41562-023-01587-9

A. F. Magnossão de Paula, J. S. Culpepper, A. Moffat, S. Pathiyan Cherumanal, F. Scholer, and J. Trippas. 2025. The Effects of Demographic Instructions on LLM Personas. In *Proceedings of the 48th International ACM SIGIR Conference on Research and Development in Information Retrieval*. ACM, 3045–3049.

Harsha Nori, Nicholas King, Scott Mayer McKinney, Dean Carignan, and Eric Horvitz. 2023. Capabilities of gpt-4 on medical challenge problems. *arXiv preprint arXiv:2303.13375* (2023).

Oluseun Olulana, Kathleen Cachel, Fabricio Murai, and Elke Rundensteiner. 2024. Hidden or Inferred: Fair Learning-to-Rank with Unknown Demographics. 7 (2024), 1088–1099.

Evaggelia Pitoura, Kostas Stefanidis, and Georgia Koutrika. 2022. Fairness in Rankings and Recommendations: An Overview. *The VLDB Journal* (2022).

Zhen Qin, Rolf Jagerman, Kai Hui, Honglei Zhuang, Junru Wu, Le Yan, Jiaming Shen, Tianqi Liu, Jialu Liu, Donald Metzler, et al. 2024. Large Language Models are Effective Text Rankers with Pairwise Ranking Prompting. In *Findings of the Association for Computational Linguistics: NAACL 2024*. 1504–1518.

Renee Shelby, Shalaleh Rismani, Kathryn Henne, AJung Moon, Negar Rostamzadeh, Paul Nicholas, N'Mah Yilla-Akbari, Jess Gallegos, Andrew Smart, Emilio Garcia, and Gurleen Virk. 2023. Sociotechnical Harms of Algorithmic Systems: Scoping a Taxonomy for Harm Reduction. In *Proceedings of the 2023 AAAI/ACM Conference on AI, Ethics, and Society* (Montréal, QC, Canada) *(AIES '23)*. Association for Computing Machinery, New York, NY, USA, 723–741. doi:10.1145/3600211.3604673

Ashudeep Singh and Thorsten Joachims. 2018. Fairness of Exposure in Rankings. *Proceedings of the ACM SIGKDD Conference* (2018), 2219–2228.

Ashudeep Singh and Thorsten Joachims. 2019. Policy learning for fairness in ranking. *Advances in neural information processing systems* 32 (2019).

Ashudeep Singh, David Kempe, and Thorsten Joachims. 2021. Fairness in ranking under uncertainty. *Advances in Neural Information Processing Systems* 34 (2021), 11896–11908.

Weiwei Sun, Zheng Chen, Xinyu Ma, Lingyong Yan, Shuaiqiang Wang, Pengjie Ren, Zhumin Chen, Dawei Yin, and Zhaochun Ren. 2023a. Instruction distillation makes large language models efficient zero-shot rankers. *arXiv preprint arXiv:2311.01555* (2023).

Weiwei Sun, Lingyong Yan, Xinyu Ma, Shuaiqiang Wang, Pengjie Ren, Zhumin Chen, Dawei Yin, and Zhaochun Ren. 2023b. Is ChatGPT good at search? investigating large language models as re-ranking agents. *arXiv preprint arXiv:2304.09542* (2023).

U.S. Equal Employment Opportunity Commission (EEOC). 2025. Who is protected from employment discrimination? https://www.eeoc.gov/employers/small-business/3-who-protected-employment-discrimination. Accessed: Jan 19, 2025.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan Gomez, Lukasz Kaiser, and Illia Polosukhin. 2017. Attention Is All You Need. *Advances in Neural Information Processing Systems* 30 (2017).

Yiming Wang, Xiaoyu Wu, Hsin-Tien Wu, Zhixiang Tao, and Yunjun Fang. 2024. Do Large Language Models Rank Fairly? *arXiv preprint arXiv:2404.03192* (2024).

Zichong Wang, Zhipeng Yin, Roland HC Yap, and Wenbin Zhang. 2025. Ai fairness beyond complete demographics: Current achievements and future directions. *arXiv preprint arXiv:2511.13525* (2025).

Hilde Weerts, Raphaële Xenidis, Fabien Tarissan, Henrik Palmer Olsen, and Mykola Pechenizkiy. 2024. The Neutrality Fallacy: When Algorithmic Fairness Interventions are (Not) Positive Action. In *Proceedings of the 2024 ACM Conference on Fairness, Accountability, and Transparency* (Rio de Janeiro, Brazil) *(FAccT '24)*. Association for Computing Machinery, New York, NY, USA, 2060–2070. doi:10.1145/3630106.3659025

Chen Xu, Wenjie Wang, Yuxin Li, Liang Pang, Jun Xu, and Tat-Seng Chua. 2023. A study of implicit ranking unfairness in large language models. *arXiv preprint arXiv:2311.07054* (2023).

Ke Yang and Julia Stoyanovich. 2017. Measuring fairness in ranked outputs. In *Proceedings of the 29th international conference on scientific and statistical database management*. 1–6.

Meike Zehlike, Francesco Bonchi, Carlos Castillo, Sara Hajian, Mohamed Megahed, and Ricardo Baeza-Yates. 2017. Fa* ir: A fair top-k ranking algorithm. In *Proceedings of the 2017 ACM on Conference on Information and Knowledge Management*. 1569–1578.

Meike Zehlike and Carlos Castillo. 2020. Reducing disparate exposure in ranking: A learning to rank approach. In *Proceedings of the web conference 2020*. 2849–2855.

Meike Zehlike, Ke Yang, and Julia Stoyanovich. 2022a. Fairness in ranking, part i: Score-based ranking. *Comput. Surveys* 55, 6 (2022), 1–36.

Meike Zehlike, Ke Yang, and Julia Stoyanovich. 2022b. Fairness in ranking, part ii: Learning-to-rank and recommender systems. *Comput. Surveys* 55, 6 (2022), 1–41.

Denny Zhou, Nathanael Schärli, Le Hou, Jason Wei, Nathan Scales, Xuezhi Wang, Dale Schuurmans, Claire Cui, Olivier Bousquet, Quoc V Le, and Ed H. Chi. 2023. Least-to-Most Prompting Enables Complex Reasoning in Large Language Models. In *The Eleventh International Conference on Learning Representations*. https://openreview.net/forum?id=WZH7099tgfM