# ELLA: Exploration through Learned Language Abstraction

## Abstract

Building agents capable of understanding language instructions is critical to effective and robust human-AI collaboration. Recent work focuses on training these agents via reinforcement learning in environments with synthetic language; however, instructions often define long-horizon, sparse-reward tasks, and learning policies requires many episodes of experience. We introduce ELLA: Exploration through Learned Language Abstraction, a reward shaping approach that correlates high-level instructions with simpler low-level instructions to enrich the sparse rewards afforded by the environment. ELLA has two key elements: 1) A termination classifier that identifies when agents complete low-level instructions, and 2) A relevance classifier that correlates low-level instructions with success on high-level tasks. We learn the termination classifier offline from pairs of instructions and terminal states. Notably, in departure from prior work in language and abstraction, we learn the relevance classifier online, *without* relying on an explicit decomposition of high-level instructions to low-level instructions. On a suite of complex BabyAI [11] environments with varying instruction complexities and reward sparsity, ELLA shows a significant gain in sample efficiency across several environments compared to competitive language-based reward shaping and no-shaping methods.

## 1 Introduction

A long-standing goal for robotics and embodied agents is to build systems that can perform tasks specified in natural language [1, 8, 20, 25, 38, 41, 42]. Central to the promise of language is its ability to cleanly specify complex, multi-step instructions. Instructions like *make a cup of coffee* define long-horizon tasks as *abstractions* over lower-level components—simple instructions like *pick up a cup* or *turn on the coffee maker*. The key to natural and seamless human-AI collaboration is in finding a way to leverage these abstractions with the goal of amplifying the sample efficiency and generalization potential of our autonomous agents.

One way to do this is through the lens of *instruction following*, which can be framed in several ways. One common framing—and the one we use in this work—is via reinforcement learning (RL): an agent is given a start state, a language instruction, and a corresponding reward function to optimize that usually denotes termination [20, 30]. While RL can be a useful framing, such approaches are often not sample efficient [11, 20]. Especially in the case of complex, highly compositional language instructions, RL agents can fail to make progress quickly—or at all. There are several reasons for poor performance in these settings; paramount is that in many environments, these instructions are tied to sparse reward functions that only provide signal upon completion of the high-level task, which drastically hurts sample efficiency. For example, seeing reward for *make a cup of coffee* would require already having turned on the coffee maker, which could itself be a difficult task. Such "bottleneck" states, which have zero intermediate reward, complicate exploration and learning [29, 39].

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Figure 1: In this example, an expert provides examples of when low-level *go to* tasks are and are not solved, and the agent trains a termination classifier. During policy learning, the agent rewards itself for completing *go to* subtasks—specifically, those which are relevant to its current high-level task. It stores successful experiences to learn to correlate low-level *go to* tasks with high-level *put next* tasks.

Our goal is to improve sample efficiency for instruction following agents operating in sparse reward settings. Driving our approach is using the principle of *abstraction*—the fact that complex instructions entail simpler ones—to guide exploration. Consider our coffee example; we would like to guide the agent to explore in a structured fashion, learning low-level behaviors first (*pick up a cup*, *turn on the coffee machine*) and building up to solving the high-level task. To do this, we frame our problem via *reward shaping*, the general technique of supplying auxiliary rewards to guide learning [31, 35].

Our approach, Exploration through Learned Language Abstraction (ELLA) provides intermediate rewards to an agent for completing relevant low-level behaviors as it tries to solve a complex, sparse reward task. Notably, our approach 1) learns to identify the low-level primitives helpful for a high-level language task *online*, and 2) does not require a strict hierarchical decomposition of language instructions to these primitives. Rather, ELLA uses low-level instructions to support agents performing complex tasks, bonusing agents as they complete *relevant* behaviors. In contrast to prior work [3, 23] that assumes strict contracts over instruction decomposition, our contract is simple and general. This prior work assumes each high-level task is comprised of exact series of low-level policies—an assumption that is only possible when the full set of primitives is known ahead of time, and fails when new actions or further exploration is necessary.

In order to bonus agents as they complete relevant subtasks, ELLA assumes access to a set of low-level language instructions and their corresponding termination states, similar to the data assumed in prior work [6]. While collecting this data for complex tasks may require time and effort (and even then, may require many more examples to generalize from), assuming annotations for low-level instructions is more tractable. Humans can quickly annotate instructions like *pick up the cup* or *open the cupboard*, or even build tools for generating such examples. Looking to prior work, this becomes increasingly apparent [5, 22, 25, 43]; low-level instructions are used to simplify the problem of interpreting high-level instructions, through a variety of mechanisms. In our case, these low-level instructions provide the basis for reward shaping.

We empirically validate our abstraction-based reward shaping framework on a series of tasks via the BabyAI platform [11]. We compare against a standard RL baseline as well as to a strong language-based reward shaping approach [17], and find that our method leads to substantial gains in sample efficiency across a variety of instruction following tasks.

## 2   Related Work

We build on a large body of work that studies language in the context of reinforcement learning (RL) [27] with a focus on methods for instruction following, leveraging hierarchy, and reward shaping.

**Instruction Following.** Instruction following focuses on the automated execution of language commands in simulated or real environments [1, 16, 26, 41, 44]. We focus on the RL setting [11, 30], where agents learn language-conditioned policies in a Markov decision process (MDP).

Even simple instruction following problems are difficult to learn [28], which has made 2D environments important test-beds for new learning methods [3, 11, 46]. Such environments, which are procedurally-generated, are useful because they decouple exploration from the problem of perception, and demand policies that do not overfit to narrow regions in the state space [10, 13].

We use BabyAI [11] as the platform for our tasks. BabyAI's language is synthetic, similar to prior work examining RL for instruction following at scale [20, 21]. These environments are scalable starting points for new instruction following approaches, since deep RL remains sample-inefficient but has the potential to flexibly deal with complex environments [21]. Simplified environments also make investigating concepts such as language abstraction possible, and these concepts can generalize to real human-AI interactions [25, 43]. We describe our experimental setup in Section 5.

**Hierarchical and Language-Structured Policies.** A large body of work in hierarchical RL studies temporal abstractions of MDPs, where policies are designed or learned at multiple levels of hierarchy [40]. Recent works have made the connection to language: for example, high-level policies can act over the space of low-level instructions [23]. Other hierarchical language techniques include learning models that predict symbolic representations of reward functions at different granularities [5, 24], and compositional approaches like policy sketches [3] and modular control [15], methods that explicitly decompose high-level instructions into sequences of predefined low-level instructions, or subtasks.

In this work, we use language hierarchically, but *without* the strict decomposition assumption made by prior work: we do not assume high-level tasks are composed of an exact series of low-level tasks. Without this assumption, it is infeasible to use explicitly modular approaches [3, 5, 15]. A further distinguishing factor of our method relative to prior work is that we do not require high-level task decompositions be provided *a priori*. We expand on these features in Section 3.

**Language and Reward Shaping.** Reward shaping is a general technique for supplying auxiliary rewards in order to guide an agent's learning process. Certain types of reward transformations, such as potential-based rewards, do not change the optimal policy but can impact sample efficiency [31]. Prior work has applied reward shaping to language-based instruction following settings. Goyal et al. [17] train a classification network on (trajectory, language) data to predict if a trajectory (parameterized by action frequencies) matches a language description, and evaluate the network at every time step to form a potential-based reward shaping function. They evaluate their method on Montezuma's Revenge, which is a complex task, but with a static, deterministic layout that does not speak to the generalization potential of such methods. Relatedly, Waytowich et al. [45] use a narration-based approach, where high-level tasks are explicitly broken down into low-level tasks as narrations. Finally, Misra et al. [30] use a shaping function based on spatial distance to goals specified in language, but require the location of the goal to be known. In this work, we use the same high level principle—language can yield useful intermediate rewards—but do not make the restrictive assumptions of prior work about the environment or the way tasks are structured.

**Other Forms of Guidance.** Several other methods exist for improving the sample efficiency of RL in sparse reward settings. These methods are orthogonal to our approach, but we see potential for combining these methods with ours. One popular technique is hindsight experience replay (HER), in which failed trajectories are stored in a replay buffer and relabeled with new goals that get nonzero reward [4]. Jiang et al. [23] extend the method to hierarchical language settings, assuming a mapping from states to corresponding goals. Cideron et al. [12] learn this mapping alongside policy training using the environment reward as supervision. Another technique for improving sample efficiency is through intrinsic motivation [9, 32, 34, 36]. In general, these methods instantiate reward shaping to incentivize accessing novel, diverse, or unpredictable parts of the state space via intrinsic rewards, and they can be extended to language-conditioned settings as well [14]. In Appendix D, we evaluate the performance of RIDE [34], an intrinsic motivation method that rewards actions that cause significant changes to the state, and discuss potential synergies with ELLA.

## 3 Problem Statement

We consider an augmented MDP $\mathcal{M}$ defined by the tuple $(\mathcal{S}, \mathcal{A}, T, R, \mathcal{G}, \gamma)$ where $\mathcal{S}, \mathcal{A}, T$, and $\gamma$ are standard. $\mathcal{A}$ consists of primitive actions—in the BabyAI tasks, these are navigation primitives

123  (forward, pick up, etc.). $\mathcal{G}$ is a set of language instructions, from which a high-level task instruction
124  $g$ is drawn, and $R : \mathcal{S} \times \mathcal{A} \times \mathcal{G} \rightarrow [0, 1]$ represents the state-action reward given some $g$. Via RL, we
125  wish to find some policy $\pi : \mathcal{S} \times \mathcal{G} \rightarrow \mathcal{A}$ that maximizes the expected discounted return.

126  We specifically consider cases where $\mathcal{M}$ has a finite horizon $H$ and $R$ is sparse with respect to
127  goal-completion, making exploration difficult. Our aim is to construct a reward transformation
128  $R \rightarrow R'$ which is policy invariant with respect to the original MDP (i.e. an optimal policy for
129  $\mathcal{M}' = (\mathcal{S}, \mathcal{A}, T, R', g, \gamma)$ is also optimal in $\mathcal{M}$ and vice versa), and which provides the agent strong
130  supervisory signal that leads to sample-efficient exploration.

131  We assume access to a set of low-level instructions $\mathcal{G}_\ell$ such that every $g \in \mathcal{G}$ *is supported by* some
132  $g_\ell \in \mathcal{G}_\ell$. Note that we do not require that high-level tasks fully factorize into low-level tasks. To
133  clarify the distinction, say that $\mathcal{G}_\ell$ consists of *go to "x"* instructions: *go to the red ball*, *go to the*
134  *blue ball*, etc. The instruction *go to the red ball and then go to the blue ball* can be fully factorized
135  into low-level tasks in $\mathcal{G}_\ell$. On the other hand, the instruction *put the red ball next to the green key* is
136  supported by *go to the red ball*, but it also requires picking up and putting down the ball—actions not
137  covered by $\mathcal{G}_\ell$. Our framing permits exploration using a mixture of low-level instructions *as well as*
138  primitive actions in $\mathcal{A}$ (such as pick up and put down).

139  We assume that examples of the corresponding termination states of instructions in $\mathcal{G}_\ell$ are easy to
140  obtain—via a human expert or automation. This is reasonable for simple low-level tasks like the *go*
141  *to* tasks in Figure 1. However, it is less feasible in domains where data collection is costly and the
142  environment is hard to simulate; we address this further in Section 7.

143  The environments in our experiments are partially observable, so we use recurrent networks that
144  ingest sequences of observations $(o_1, o_2, ..., o_t)$ rather than a single state $s_t$ [19]. Though our notation
145  describes the fully observable setting, the extension to the partially observable case is straightforward.

## 4  ELLA

147  We present ELLA, our reward shaping framework for guiding exploration using learned language
148  abstractions. Figure 1 provides a graphical overview of ELLA. Our approach rewards an agent when
149  it has completed low-level tasks that support a given high level task. To do this, it predicts 1) when a
150  low-level task *terminates* and 2) when a low-level task is *relevant*. Section 4.1 describes our low-level
151  termination classifier. Section 4.2 describes our relevance classifier, and how we learn it online during
152  RL. Finally, Section 4.3 provides the details of our reward shaping scheme, which bonuses the agent
153  for exploring states that satisfy relevant low-level tasks.

### 4.1  Learning the Low-Level Termination Classifier

155  We train a binary termination classifier $h^\phi : \mathcal{S} \times \mathcal{G}_\ell \rightarrow \{0, 1\}$ parameterized by $\phi$ to predict if a
156  low-level task $g_\ell \in \mathcal{G}_\ell$ terminates in a particular state $s \in \mathcal{S}$. We assume access to $\mathcal{G}_\ell$ as well as
157  positive and negative examples of low-level task termination states. This dataset could be provided by
158  a human annotator or created automatically; while providing demonstrations of high-level tasks (e.g.,
159  *make a cup of coffee*) across varied environments is costly, doing so for low-level tasks (e.g., *pick up*
160  *the mug*, *open the cupboard*) which are shorter, simpler, and more generalizable, is more feasible. To
161  represent $h^\phi$, we use an adapted version of the architecture in [11] which merges state and language
162  representations using feature-wise linear modulation (FiLM) [33].

### 4.2  Learning the Relevance Classifier

164  Our reward shaping approach also needs to evaluate relevance of a low-level instruction in addition
165  to being able to classify termination. The relevance mapping from $\mathcal{G}$ to $\mathcal{P}(\mathcal{G}_\ell)$ (the power set of $\mathcal{G}_\ell$)
166  is initially unknown to the agent. We refer to the output of this mapping as a decomposition of $g$, but
167  note again that it need not be a *strict* decomposition. We propose that this mapping is represented
168  by a separate binary relevance classifier $f^\rho : \mathcal{G} \times \mathcal{G}_\ell \rightarrow \{0, 1\}$ learned during policy training from a
169  dataset of decompositions $\mathcal{D}$ collected online. The output of $f^\rho$ indicates whether a particular $g_\ell \in \mathcal{G}_\ell$
170  is relevant to some $g \in \mathcal{G}$. We use a Siamese network to represent $f^\rho$.

171  **Training the Relevance Classifier.** Suppose $\mathcal{D}$ already contains key-value pairs $(g, \mathbb{S})$ where $g \in \mathcal{G}$
172  and $\mathbb{S} \in \mathcal{P}(\mathcal{G}_\ell)$. Each $\mathbb{S}$ is an estimate of the oracle decomposition $\bar{\mathbb{S}}$ of a particular $g$. For every $g$ in

---

**Algorithm 1** Reward Shaping via ELLA

---

**Input:** Initial policy parameters $\theta_0$, relevance classifier parameters $\rho_0$, update rate $n$, low-level bonus $\lambda$, and RL optimizer OPTIMIZE
Initialize $\mathcal{D} \leftarrow \{(g : \mathcal{G}_\ell) \text{ for all } g \text{ in } \mathcal{G}\}$
**for** $k = 0, 1, \ldots$ **do**
  Collect trajectories $\mathcal{D}_k$ using $\pi_k^\theta$.
  **for** $\tau \in \mathcal{D}_k$ **do**
    Set $N \leftarrow$ length of $\tau$
    Set $(r'_{1:N}, \hat{\mathbb{S}}) \leftarrow$ SHAPE$(\tau)$
    **if** $U(\tau) > 0$ **then**
      Set $r'_N \leftarrow$ NEUTRALIZE$(r'_{1:N})$
      Set $\mathcal{D}[g] \leftarrow$ UPDATEDECOMP$(\mathcal{D}, \hat{\mathbb{S}})$
    Update $\theta_{k+1} \leftarrow$ OPTIMIZE$(r'_{1:N})$.
  **if** $k$ is a multiple of $n$ **then**
    Update $\rho_{k+1}$ by sampling positive and negative examples from $\mathcal{D}$ and optimizing cross entropy loss.

**function** SHAPE$(\tau)$
  Set $\hat{\mathbb{S}} \leftarrow \emptyset$
  **for** $g_\ell \in \mathcal{G}_\ell$ **do**
    **for** $g, (s_t, r_t) \in \tau$ **do**
      **if** $h^\phi(s_t, g_\ell) = 1$ and $g_\ell \notin \hat{\mathbb{S}}$ **then**
        Update $\hat{\mathbb{S}} \leftarrow \hat{\mathbb{S}} \cup \{g_\ell\}$
        **if** $f^\rho(g, g_\ell) = 1$ **then**
          Set $r'_t = r_t + \lambda$
  **return** $(r'_{1:N}, \hat{\mathbb{S}})$

**function** NEUTRALIZE$(r'_{1:N})$
  Set $T_{\mathbb{S}} \leftarrow \{t \mid 1 \leq t \leq N, r'_t > 0\}$
  **return** $r'_N - \sum_{t \in T_{\mathbb{S}}} \gamma^{t-N} \lambda$

**function** UPDATEDECOMP$(\mathcal{D}, \hat{\mathbb{S}})$
  Set $\mathbb{S} \leftarrow \mathcal{D}[g]$
  **return** $\mathbb{S} \cap \hat{\mathbb{S}}$ (or $\hat{\mathbb{S}}$ if $\mathbb{S} \cap \hat{\mathbb{S}} = \emptyset$)

---

$\mathcal{D}$, we enumerate negative examples of relevant subtasks from $\mathcal{G}_\ell \setminus \mathbb{S}$ and accordingly oversample positive examples from $\mathbb{S}$; we then optimize a cross entropy objective on this balanced dataset.

**Collecting Relevance Data Online.** We describe any trajectory that solves the high-level task as *successful*, regardless of whether they do so optimally, and any other trajectories as *unsuccessful*. For every successful trajectory of some $g$ we encounter during RL training, we record the low-level instructions which terminated. That is, we relabel the steps in the trajectory and use $h^\phi$ to determine which low-level instructions were completed (if any), yielding an estimate $\hat{\mathbb{S}}$ of the true decomposition $\bar{\mathbb{S}}$. If $\mathcal{D}$ already contains an estimate $\mathbb{S}$ for $g$, we simply deduplicate the multiple decomposition estimates by intersecting $\mathbb{S}$ and $\hat{\mathbb{S}}$. As the agent completes more successful trajectories, decompositions in $\mathcal{D}$ are more likely to get revisited.

**Intuition for Deduplication.** Intuitively, this method for deduplication denoises run-specific experiences, and distills the estimate $\mathbb{S}$ in $\mathcal{D}$ for a given $g$ to only those $g_\ell$ that are shared among multiple successful runs of $g$. Consider $g = $ *put the red ball next to the blue box*; successful runs early in training could highlight *go to the red ball* along with irrelevant *go to* low-level instructions. As $\pi^\theta$ improves, so do the decomposition estimates. Later runs may highlight only *go to the red ball*. Taking the intersection would yield only *go to the red ball* as our final estimate $\mathbb{S}$. This approach also helps to deal with false positives of $h^\phi$ by effectively boosting the estimate across runs. If deduplication produces a null intersection, which may happen due to false negatives of $h^\phi$, we err on the side of using the latest estimate. If we assume $h^\phi$ has perfect accuracy, the intersection will never be null, and the continual intersections will reflect the set of completed $g_\ell$ common to all successful runs of $g$. For an initialization conducive to deduplication and that provides $\pi^\theta$ strong incentive to complete low-level tasks from the beginning of training, we initialize $f^\rho$ to predict that $\mathbb{S} = \mathcal{G}_\ell$ for all $g$.

## 4.3 Shaping Rewards

We now describe the shaped reward function $R'$ which relies on $h^\phi$ and $f^\rho$. $R'$ provides a bonus $\lambda$ whenever a relevant low-level task terminates. We do this by relabeling the current $(s_t, a_t, r_t, s_{t+1})$ with every $g_\ell$ and using $h^\phi$ to predict low-level task termination, and $f^\rho$ to predict relevance.

Critically, we do not want the shaping transformation from $R \rightarrow R'$ to be vulnerable to the agent getting "distracted" by the shaped reward (reward hacking), as in Randløv and Alstrøm [35] where an agent learns to ride a bicycle in a circle around a goal repeatedly accruing reward. To this end, we cap the bonus per low-level instruction per episode to $\lambda$ to prevent cycles. More generally, we want $R'$ to be *policy invariant* with respect to $\mathcal{M}$: it should not introduce any new optimal policies, and it should retain all the optimal policies from $\mathcal{M}$. Policy invariance is a useful property [31]: we do not want to reward a suboptimal trajectory (such as one that repeatedly completes a low-level instruction) more than an optimal trajectory in $\mathcal{M}$, and policy invariance guarantees this.

| Low-Level Task | Example |
|---|---|
| GoTo-Room [G1] | *Go to a red ball* |
| GoTo-Maze [G2] | *Go to a red ball* |
| Open-Maze [O2] | *Open the green door* |
| Pick-Maze [P2] | *Pick up the blue box* |

| High-Level Task | Example | $\mathcal{G}_\ell$ |
|---|---|---|
| PutNext-Room | *Put the red ball next to the green key* | G1 |
| PutNext-Maze | *Put the red ball next to the green key* | G2 |
| Unlock-Maze | *Open the green door* | P2 |
| Open&Pick-Maze | *Open the yellow door and pick up the blue box* | O2, G2 |
| Combo-Maze | *Put next, open, pick* | G2 |
| Sequence-Maze | *Pick up a purple key and then put the grey box next to the yellow box* | G2 |

Figure 2: Sample Instructions for our low- and high-level tasks.

We establish two desiderata for $R'$ [7]: (a) The reward transformation should be policy invariant with respect to $\mathcal{M}$ for states from which the task is solvable, and (b) $R'$ should improve sample efficiency by encouraging subtask-based exploration. To satisfy our desiderata, we choose $R'$ such that successful trajectories get the same return under $\mathcal{M}$ and $\mathcal{M}'$, and that unsuccessful trajectories get lower returns under $\mathcal{M}'$ than trajectories optimal in $\mathcal{M}$. We will describe and intuitively justify each of these choices with respect to (a) and (b).

**Neutralization in Successful Trajectories.** We neutralize shaped reward in successful trajectories—that is, subtract the shaped reward at the final time step—so that successful trajectories gets the same return under both $R'$ and $R$.

More specifically, let $U(\tau) := \sum_{t=1}^{N} \gamma^t R(s_t, a_t)$, the cumulative discounted return under $R$ of a successful trajectory $\tau$. Let $U'(\tau)$ be likewise defined for $R'$. If $\tau$ has $N$ steps, the sparse reward under $R$ is $U(\tau) = \gamma^N r_N$. Under $R'$, if $T_{\mathbb{S}}$ is the set of the time steps at which a $\lambda$ bonus is applied, we set $r'_N$ to $r_N - \sum_{t \in T_{\mathbb{S}}} \gamma^{t-N} \lambda$. This is the value required to neutralize the intermediate rewards, such that $U'(\tau) = \gamma^N r_N = U(\tau)$. (Note that we cap the bonus per time step to $\lambda$—if multiple low-level language instructions terminate at a single state, only a bonus of $\lambda$ is applied.)

Theoretically, we could apply neutralization to *all* trajectories, not just successful ones, and we would satisfy property (a) [18]. However, this is harmful to property (b), because unsuccessful trajectories would result in zero return: a negative reward at the last time step would negate the subtask rewards, hurting boosts in sample efficiency.

**Tuning $\lambda$ to Limit Return in Unsuccessful Trajectories.** Any successful trajectory gets the same return under $R'$ as under $R$ because of neutralization. By choosing $\lambda$ carefully, we can additionally satisfy the property that any unsuccessful trajectory gets a lower return under $R'$ than any trajectory selected by an optimal policy $\pi_{\mathcal{M}}^*$ in $\mathcal{M}$.

To achieve this, we need $\lambda$ to be sufficiently small. Assume that a trajectory $\tau$ selected by $\pi_{\mathcal{M}}^*$ takes no longer than $M$ time steps to solve any $g$. In the worst case, $M = H$, and $U(\tau)$ would be $\gamma^H r_H$. If $T_{\mathbb{S}}$ is the set of the time steps at which $R'$ provides $\lambda$ bonuses, $U'(\tau)$ would be $\lambda \sum_{t \in T_{\mathbb{S}}} \gamma^t$. We can upper bound $\sum_{t \in T_{\mathbb{S}}} \gamma^t$ with $|\mathcal{G}_\ell|$. Then, the following inequality is sufficient for maintaining (a):

$$\lambda < \frac{\gamma^H r_H}{|\mathcal{G}_\ell|}, \tag{1}$$

where $r_H$ is the value of a sparse reward if it were attained at time step $H$. We provide a more thorough justification of this choice of $\lambda$ in Appendix F. Note that $\lambda$ and the sparse reward can be both scaled by a constant if $\lambda$ is otherwise too small to propagate as a reward.

An important feature of our work is the realization that we can make this bound less conservative through minimal knowledge about the optimal policy and the environment (e.g., knowledge about the expected task horizon $M$, or a tighter estimate of the number of subtasks available in an environment instance). Such reasoning yields a feasible range of values for $\lambda$, and these can empirically lead to faster learning (Section 6.1). At a minimum, reasoning over the value of $\lambda$ using via (1) provides a generalizable way to incorporate this technique across a variety of different settings in future work.

We summarize our shaping procedure in Algorithm 1, with an expanded version in Appendix C.

Figure 3: Average reward for ELLA and baselines in six environments, with error regions to indicate standard deviation over three random seeds. Example rollouts in the PUTNEXT-ROOM environment and UNLOCK-MAZE environment illustrate the final policy learned via ELLA, where the agent completes relevant low-level subtasks in order to solve the high-level task.

## 5  Experiments

**Experimental Setup.** We run our experiments in BabyAI [11], a grid world platform for instruction following, where an agent has a limited range of view and receives goal instructions such as *go to the red ball* or *open a blue door*. Grid worlds can consist of multiple rooms connected by a closed/locked door (e.g., the UNLOCK-MAZE environment in Figure 3). The action space $\mathcal{A}$ consists of several navigation primitives (forward, pickup, etc.). Every task instance includes randomly placed distractor objects that agents can interact with. Rewards in BabyAI are sparse: agents receive a reward of $1 - 0.9\frac{t}{H}$ where $t$ is the time step upon succeeding at the high-level goal. If the goal is not reached, the reward is 0. By default, all rewards are scaled up by a constant factor of 20.

We evaluate our reward shaping framework using Proximal Policy Optimization (PPO) [37], but note that ELLA is agnostic to the RL algorithm used. We compare to PPO without shaping, as well as to LEARN, a prior method on language-based reward shaping [17] that provides rewards based on the predicted relevance of action frequencies in the current trajectory to the current instruction.

We focus on several high- and low-level tasks. Figure 2 describes each task with examples. ROOM levels consist of a single $7 \times 7$ grid, while MAZE levels contain two such rooms, connected by a door; agents may need to open and pass through the door multiple times to complete the task. In the UNLOCK environment, the door is "locked," requiring the agent to hold a key of the same color as the door before opening it, introducing significant bottleneck states [29, 39]. Our six high-level tasks differ on three axes: *sparsity* of the high-level task, *similarity* of the low- and high-level tasks, and *compositionality* of the tasks in $\mathcal{G}$—the number of $g_\ell \in \mathcal{G}_\ell$ relevant to some $g$. We use these axes to frame our understanding of how ELLA performs in different situations.

We used a combination of NVIDIA Titan and Tesla T4 GPUs to train our models. We ran 3 seeds for each of the 3 methods in each environment, with runs taking 1 to 6 days.

**Results.** Figure 3 presents learning curves for ELLA, LEARN, and PPO (without shaping) across the six environments. We explain our results in the context of the three axes described above.

*1. How does ELLA perform on tasks of varying sparsity?*

In both single room (PUTNEXT-ROOM) and two room (PUTNEXT-MAZE) environments, ELLA induces gains in sample efficiency, using GOTO as $\mathcal{G}_\ell$. Relative gains are larger for the bigger environment because reward signals are more spatially sparse and so spatial subgoals—visiting relevant objects—help the agent navigate.

Figure 4: Average reward in PUTNEXT-ROOM for various values of $\lambda$. Smaller values are more conservative but potentially less helpful than larger values. $\lambda = 0$ indicates no shaping; for this case, we show an error region over three random seeds.

Figure 5: Two metrics to analyze ELLA's performance over an RL run are the average number of low-level instructions per high-level instruction in $\mathcal{D}$ and the accuracy of the relevance classifier $f^\rho$ on a balanced validation set. For PUTNEXT-MAZE, $f^\rho$ improves as decomposition estimates get less noisy. For the challenging SEQUENCE-MAZE task, ELLA still incentivizes subtask completion, but the decomposition estimates are noisy and $f^\rho$ is less accurate.

Another degree of sparsity comes from bottleneck states: for example, in the UNLOCK environment, the agent must pick up a key of the corresponding color (the bottleneck) before it can successfully open a colored door and see reward. Without shaping, random exploration rarely passes such bottlenecks. However, in this experiment, ELLA rewards picking up keys, via the PICK low-level instruction, quickly learning to correlate picking up keys of the correct color with successfully unlocking doors, allowing agents to navigate these bottlenecks and improving sample efficiency.

*2. How does ELLA perform when the low-level tasks are similar to the high-level task?*

In the COMBO environment, tasks consist of multiple types of instructions such as *put the red ball next to the green box*, *open the green door*, and *pick up the blue box*. The latter instructions require minimal exploration beyond "going to" the object in question. That is, the low-level task GOTO is more similar to this high-level task set than in the other environments such as PUTNEXT. As a result, in the COMBO environment, ELLA does not increase in sample efficiency. However, it notably does not perform *worse* than baselines: the exploration it encourages is not harmful, but is simply not helpful. This is expected as subtasks are relatively similar to many high-level tasks, and achieving them is about as difficult as exploring the correct subtasks.

*3. How does ELLA perform when the high-level tasks are compositional and diverse?*

We test ELLA on OPENANDPICKUP using *two* low-level instruction families, OPEN and GOTO. The instruction *open the yellow door and pick up the blue box* abstracts over *go to the yellow door*, *open the yellow door*, and *go to the blue box*. Although learning the relevance classifier becomes harder with more compositional instructions, the boost in sample efficiency provided by ELLA remains.

Similarly, SEQUENCE has a combinatorially-large number of compositional instructions: it requires two of *put next*, *open*, and *pick up* in the correct order. It has over 1.5 million instructions compared to the other high-level tasks with 300 to 1500 instructions. Although the exploration problem is very difficult, we see marginal gains from ELLA; we discuss this further in Section 7.

# 6   Analyzing ELLA

In this section, we analyze two aspects of ELLA's performance: the effect of different choices for the low-level reward hyperparameter (Section 6.1), and the performance of the relevance classifier over an RL run (Section 6.2).

## 6.1   Effect of the Low-Level Task Reward

A critical hyperparameter that needs to be controlled for is the magnitude of the low-level reward $\lambda$. Instead of using ad hoc methods for tuning this value, Section 4.3 provides guidelines for choosing a reasonable range for this value. To summarize, we want to pick $\lambda$ small enough that any unsuccessful trajectory—such as one that only completes subtasks and never finishes the high-level task—does not

receive greater return than an optimal trajectory. We find that values of $\lambda$ that egregiously violate policy invariance lead to unstable learning. In this section, we observe this effect in PUTNEXT-ROOM, by evaluating various values of $\lambda$ determined using the multi-tier assumptions alluded to in Section 4.3. With no knowledge of the environment or the expert policy, the loosest bounds for $M$ and $|T_{\mathbb{S}}|$ ($H$ and $|\mathcal{G}_\ell|$ respectively), as in (1) give us a value of $\lambda = 0.015$. With the minimal assumption that the expert policy solves the task in under 100 steps, we arrive at $\lambda = 0.05$. For 40 steps, we arrive at $\lambda = 0.25$. Figure 4 compares learning curves for $\lambda$—the smallest being more conservative and not having a great effect on sample efficiency, the middle values illustrating the value of rewarding relevant subtasks, and the largest values illustrating how low-level task rewards can "distract" the agent from the high-level task. In the run where $\lambda = 10$, the agent does not learn the task at all. The results in Section 5 use $\lambda = 0.25$ for PUTNEXT-ROOM, PUTNEXT, UNLOCK, and COMBO, and use $\lambda = 0.5$ for OPEN&PICK and SEQUENCE (which have longer horizons $H$).

### 6.2 Progress of the Relevance Classifier

The online relevance dataset and classifier provide transparency into the type of guidance that ELLA provides. Figure 5 focuses on PUTNEXT-MAZE and SEQUENCE-MAZE, and shows two metrics: the average number of subtasks per high-level instruction in $\mathcal{D}$, which we expect to decrease as decomposition estimates improve; and the validation accuracy of $f^\rho$ in classifying a balanced oracle set of subtask decompositions, which we expect to increase if ELLA learns language abstractions.

For PUTNEXT-MAZE, the number of subtasks per high-level instruction decreases and the relevance classifier becomes very accurate. This happens as, from Figure 3, the policy improves in terms of average return. For the SEQUENCE-MAZE task, ELLA has marginal gains in performance compared to baselines (Figure 3). This is likely due to ELLA incentivizing general subtask completion, evidenced by the growing average length of the decompositions. However, the large number of diverse language instructions makes it difficult to estimate good decompositions via our deduplication method, and so it is difficult to learn $f^\rho$ online and offer the most targeted low-level task bonuses.

## 7 Discussion

We introduce ELLA, a reward shaping approach for guiding exploration based on the principle of abstraction in language. Our approach incentivizes low-level behaviors without assuming a strict hierarchy between high- and low-level language, and learns to identify relevant abstractions online.

As noted in Section 2, several other methods exist for addressing sample inefficiency in sparse reward settings. While we focus on using language as the basis for reward shaping, intrinsic rewards can also be based on the dynamics of the environment. For example, RIDE [34] provides rewards for actions that produce significant changes to the state. In Appendix D, we discuss how ELLA can synergize with such methods to reward different aspects of exploration.

**Limitations and Future Work.** Our framework requires termination states for each low-level instruction. This assumption is similar to that made by Jiang et al. [23] and Waytowich et al. [45], and is weaker than the assumption made by the LEARN baseline of Goyal et al. [17], where full demonstrations are required. Even so, training accurate termination classifiers can require many examples—in this work, we used 15K positive and negative pairs for each low-level task. In Appendix E, we provide an ablation on the data budget for the termination classifier. Our approach is less feasible in domains where collecting examples of low-level terminating conditions is costly.

Highly compositional and diverse instructions, as in the SEQUENCE-MAZE environment, remain a challenge. Additional data augmentation (e.g., GECA [2]) on the online relevance dataset could potentially improve performance on these large instruction sets. More sophisticated relevance classifiers may also prove helpful: rather than our current method of storing decompositions, we could maintain a belief distribution over whether a particular pair of high- and low-level instructions are relevant conditioned on trajectories the RL algorithm has observed so far.

Our approach showed strong performance in several sparse reward task settings with high- and low-level synthetic language. Extensions to the case of natural language could model a broad spectrum of abstraction, beyond two tiers.

## References

[1] P. Anderson, Q. Wu, D. Teney, J. Bruce, M. Johnson, N. Sünderhauf, I. Reid, S. Gould, and A. van den Hengel. Vision-and-language navigation: Interpreting visually-grounded navigation instructions in real environments. In *Computer Vision and Pattern Recognition (CVPR)*, 2018.

[2] J. Andreas. Good-enough compositional data augmentation. In *Association for Computational Linguistics (ACL)*, 2020.

[3] J. Andreas, D. Klein, and S. Levine. Modular multitask reinforcement learning with policy sketches. In *International Conference on Machine Learning (ICML)*, 2017.

[4] M. Andrychowicz, F. Wolski, A. Ray, J. Schneider, R. Fong, P. Welinder, B. McGrew, J. Tobin, P. Abbeel, and W. Zaremba. Hindsight experience replay. *arXiv preprint arXiv:1707.01495*, 2017.

[5] D. Arumugam, S. Karamcheti, N. Gopalan, L. L. S. Wong, and S. Tellex. Accurately and efficiently interpreting human-robot instructions of varying granularities. In *Robotics: Science and Systems (RSS)*, 2017.

[6] D. Bahdanau, F. Hill, J. Leike, E. Hughes, S. A. Hosseini, P. Kohli, and E. Grefenstette. Learning to understand goal specifications by modelling reward. In *International Conference on Learning Representations (ICLR)*, 2019.

[7] P. Behboudian, Y. Satsangi, M. E. Taylor, A. Harutyunyan, and M. Bowling. Useful policy invariant shaping from arbitrary advice. *arXiv preprint arXiv:2011.01297*, 2020.

[8] Y. Bisk, A. Holtzman, J. Thomason, J. Andreas, Y. Bengio, J. Chai, M. Lapata, A. Lazaridou, J. May, A. Nisnevich, N. Pinto, and J. Turian. Experience grounds language. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2020.

[9] Y. Burda, H. Edwards, D. Pathak, A. Storkey, T. Darrell, and A. A. Efros. Large-scale study of curiosity-driven learning. In *International Conference on Learning Representations (ICLR)*, 2019.

[10] A. Campero, R. Raileanu, H. Küttler, J. B. Tenenbaum, T. Rocktäschel, and E. Grefenstette. Learning with AMIGo: Adversarially motivated intrinsic goals. *arXiv preprint arXiv:2006.12122*, 2020.

[11] M. Chevalier-Boisvert, D. Bahdanau, S. Lahlou, L. Willems, C. Saharia, T. H. Nguyen, and Y. Bengio. Babyai: A platform to study the sample efficiency of grounded language learning. In *International Conference on Learning Representations (ICLR)*, 2019.

[12] G. Cideron, M. Seurin, F. Strub, and O. Pietquin. Self-educated language agent with hindsight experience replay for instruction following. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[13] K. Cobbe, C. Hesse, J. Hilton, and J. Schulman. Leveraging procedural generation to benchmark reinforcement learning. In *International Conference on Machine Learning (ICML)*, 2020.

[14] C. Colas, T. Karch, N. Lair, J.-M. Dussoux, C. Moulin-Frier, P. F. Dominey, and P.-Y. Oudeyer. Language as a cognitive tool to imagine goals in curiosity driven exploration. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[15] A. Das, G. Gkioxari, S. Lee, D. Parikh, and D. Batra. Neural modular control for embodied question answering. In *Conference on Robot Learning (CORL)*, 2018.

[16] J. Fu, A. Korattikara, S. Levine, and S. Guadarrama. From language to goals: Inverse reinforcement learning for vision-based instruction following. In *International Conference on Learning Representations (ICLR)*, 2019.

[17] P. Goyal, S. Niekum, and R. J. Mooney. Using natural language for reward shaping in reinforcement learning. In *International Joint Conference on Artificial Intelligence (IJCAI)*, 2019.

[18] M. Grzes. Reward shaping in episodic reinforcement learning. In *International Conference on Autonomous Agents and Multiagent Systems (AAMAS)*, 2017.

[19] M. Hausknecht and P. Stone. Deep recurrent Q-learning for partially observable mdps. *arXiv preprint arXiv:1507.06527*, 2015.

[20] K. M. Hermann, F. Hill, S. Green, F. Wang, R. Faulkner, H. Soyer, D. Szepesvari, W. Czarnecki, M. Jaderberg, D. Teplyashin, M. Wainwright, C. Apps, D. Hassabis, and P. Blunsom. Grounded language learning in a simulated 3d world. *arXiv preprint arXiv:1706.06551*, 2017.

[21] F. Hill, S. Mokra, N. Wong, and T. Harley. Human instruction-following with deep reinforcement learning via transfer-learning from text. *arXiv preprint arXiv:2005.09382*, 2020.

[22] R. Jia and P. Liang. Data recombination for neural semantic parsing. In *Association for Computational Linguistics (ACL)*, 2016.

[23] Y. Jiang, S. S. Gu, K. P. Murphy, and C. Finn. Language as an abstraction for hierarchical deep reinforcement learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[24] S. Karamcheti, E. C. Williams, D. Arumugam, M. Rhee, N. Gopalan, L. L. S. Wong, and S. Tellex. A tale of two draggns: A hybrid approach for interpreting action-oriented and goal-oriented instructions. In *First Workshop on Language Grounding for Robotics @ ACL*, 2017.

[25] S. Karamcheti, D. Sadigh, and P. Liang. Learning adaptive language interfaces through decomposition. In *EMNLP Workshop for Interactive and Executable Semantic Parsing (IntEx-SemPar)*, 2020.

[26] T. Kollar, S. Tellex, D. Roy, and N. Roy. Toward understanding natural language directions. In *Human-Robot Interaction*, pages 259–266, 2010.

[27] J. Luketina, N. Nardelli, G. Farquhar, J. Foerster, J. Andreas, E. Grefenstette, S. Whiteson, and T. Rocktäschel. A survey of reinforcement learning informed by natural language. In *International Joint Conference on Artificial Intelligence (IJCAI)*, 2019.

[28] C. Lynch and P. Sermanet. Grounding language in play. *arXiv preprint arXiv:2005.07648*, 2020.

[29] A. McGovern and A. G. Barto. Automatic discovery of subgoals in reinforcement learning using diverse density. In *International Conference on Machine Learning (ICML)*, 2001.

[30] D. K. Misra, J. Langford, and Y. Artzi. Mapping instructions and visual observations to actions with reinforcement learning. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2017.

[31] A. Y. Ng, D. Harada, and S. Russell. Policy invariance under reward transformations: Theory and application to reward shaping. In *International Conference on Machine Learning (ICML)*, volume 99, pages 278–287, 1999.

[32] D. Pathak, P. Agrawal, A. A. Efros, and T. Darrell. Curiosity-driven exploration by self-supervised prediction. In *Computer Vision and Pattern Recognition (CVPR)*, pages 16–17, 2017.

[33] E. Perez, F. Strub, H. D. Vries, V. Dumoulin, and A. C. Courville. Film: Visual reasoning with a general conditioning layer. In *Association for the Advancement of Artificial Intelligence (AAAI)*, 2018.

[34] R. Raileanu and T. Rocktäschel. Ride: Rewarding impact-driven exploration for procedurally-generated environments. In *International Conference on Learning Representations (ICLR)*, 2020.

[35] J. Randløv and P. Alstrøm. Learning to drive a bicycle using reinforcement learning and shaping. In *International Conference on Machine Learning (ICML)*, 1998.

[36] J. Schmidhuber. Adaptive confidence and adaptive curiosity. Technical report, Institut fur Informatik, Technische Universitat Munchen, Arcisstr. 21, 800 Munchen 2, 1991.

[37] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

[38] M. Shridhar, J. Thomason, D. Gordon, Y. Bisk, W. Han, R. Mottaghi, L. Zettlemoyer, and D. Fox. Alfred: A benchmark for interpreting grounded instructions for everyday tasks. In *Computer Vision and Pattern Recognition (CVPR)*, 2020.

[39] M. Stolle and D. Precup. Learning options in reinforcement learning. In *Proceedings of the 5th International Symposium on Abstraction, Reformulation and Approximation*, 2002.

[40] R. S. Sutton, D. Precup, and S. Singh. Between mdps and semi-mdps: A framework for temporal abstraction in reinforcement learning. *Articial intelligence*, 112:181–211, 1999.

[41] S. Tellex, T. Kollar, S. Dickerson, M. R. Walter, A. G. Banerjee, S. J. Teller, and N. Roy. Understanding natural language commands for robotic navigation and mobile manipulation. In *Association for the Advancement of Artificial Intelligence (AAAI)*, 2011.

[42] J. Thomason, S. Zhang, R. J. Mooney, and P. Stone. Learning to interpret natural language commands through human-robot dialog. In *International Joint Conference on Artificial Intelligence (IJCAI)*, 2015.

[43] S. I. Wang, S. Ginn, P. Liang, and C. D. Manning. Naturalizing a programming language via interactive learning. In *Association for Computational Linguistics (ACL)*, 2017.

[44] X. E. Wang, Q. Huang, A. Celikyilmaz, J. Gao, D. Shen, Y.-F. Wang, W. Y. Wang, and L. Zhang. Reinforced cross-modal matching and self-supervised imitation learning for vision-language navigation. In *Computer Vision and Pattern Recognition (CVPR)*, 2019.

[45] N. Waytowich, S. L. Barton, V. Lawhern, and G. Warnell. A narration-based reward shaping approach using grounded natural language commands. In *International Conference on Machine Learning (ICML)*, 2019.

[46] H. Yu, H. Zhang, and W. Xu. A deep compositional framework for human-like language acquisition in virtual environment. *arXiv preprint arXiv:1703.09831*, 2017.