Towards Reasoning-Aware Explainable VQA

Abstract

The domain of joint vision-language understanding, especially in the context of reasoning in Visual Question Answering (VQA) models, has garnered significant attention in the recent past. While most of the existing VQA models focus on improving the accuracy of VQA, the way models arrive at an answer is often-times a black box. As a step towards making the VQA task more explainable and interpretable, our method is built upon the SOTA VQA framework [1] by augmenting it with an end-to-end explanation generation module. In this paper, we investigate two network architectures, including LSTM and Transformer decoder, as the explanation generator. Our method generates human-readable explanations while maintaining SOTA VQA accuracy on the GQA-REX (77.49%) and VQA-E (71.48%) datasets. Approximately 65.16% of the generated explanations are ap-proved to be valid by humans. Roughly 60.5% of the generated explanations are valid and lead to the correct answers.

1 Introduction

Problems involving joint vision-language understanding are gaining more attention in both Computer Vision (CV) and Natural Language Processing (NLP) communities. In recent years, complex reasoning problems in the vision-language domain have been in the spotlight. Based on the classic Visual Question Answering (VQA), reasoning has been highly involved. In [2, 3, 4], a model needs to reason over spatial and arithmetic relationships within an image-question pair. [5] incorporates spatial-temporal reasoning and domain-specific knowledge. A more challenging set-ting such as [6, 7] requires the capability to make use of external knowledge to perform reasoning in the vision and language domain.

Q: Is the stovelight on?   **GT Ans:** Yes
M1, **M2**, **M3**: Yes
C: There is a stove and a bunch of knives
E: The space under the hood is brighter than the surrounding area.

Figure 1: A VQA example shows the importance of an explanation that leads to the correct answer.

Benefiting from the large-scale pre-trained models in both single modality and multi-modality, we witness impressive improvements in VQA accuracy [8, 9, 10, 11] in both the stock setting and its variants. However, we barely pay attention to how a model reaches an answer given an image-question pair. Let's take a look at Figure 1 as an illustrative example. The ground-truth answer to the question is straightforward and information from the image is sufficient to answer the question. There are three different types of VQA models: **Model type 1** predicts the correct answer without any evidence on how to achieve it. **Model type 2** answers the question correctly and provides a caption that summarizes the image. Unfortunately, the caption fails to unveil the reasoning chain

Submitted to 2022 Trustworthy and Socially Responsible Machine Learning (TSRML 2022). Do not distribute.

behind predicting the correct answer to the question. **Model type 3** successfully generates a logically self-contained explanation which corresponds to the correct answer. Both **Model type 1** and **Model type 2** cover most of the SOTA VQA models. Surprisingly, very few models exist that are similar to **Model type 3**. Motivated by examples like in Figure 1, we investigate the following two open topics in this paper: (i) whether a VQA model can generate a human-readable explanation while maintaining the VQA accuracy; (ii) how good are the generated explanations and how to evaluate them? Our contribution is two-fold:

- We present easy to implement methods on top of a SOTA VQA framework which maintains VQA accuracy while generating human-readable textual explanations.

- We show both quantitative experimental results and human-studies of the proposed explainable VQA method. Our experiments illustrate the urgency of proposing new metrics to evaluate the predicted explanations in vision-language reasoning problems such as VQA.

2   Related Work

Reasoning in VQA   VQA [4] and its variants, as an end-to-end task, have been well explored, and various models have kept achieving higher performance along the way. Built on top of the original setting, complex reasoning tasks are heavily involved. [4, 12] introduces arithmetic reasoning into the setting. [3, 13, 2] highlight the importance of fine spatial reasoning in the VQA problem. While the above datasets limit the reasoning domain within the image, [6, 14] propose a visual language task that requires external knowledge, sometimes even domain-specific knowledge, to answer the question. In [15], the emphasis is on the logical entailment problem. Recent methods such as [8, 9, 10] take advantage of the unprecedented amount of vision-language data and large size of models, achieving SOTA performances on the above VQA datasets. As the reasoning problem in VQA is becoming more and more complicated, it is urgent to have an interpretable way to analyze and diagnose the model and measure its reliability.

Explainable VQA and Metrics   Very few among the SOTA VQA works study the explainability of the models, especially in the era of big data and big model. [16] is one of the standard datasets that focuses on explainability. A similarity score between the question and image caption is computed to check for question-relevant captions. The caption is then used to generate an explanation that is relevant to the question-answer pair. [17, 18] use attributes and captions of the image to provide a naive version of the explanation to the answer. Some works [19, 11] make use of textual knowledge from external sources to improve the interpretability of the model. But such external knowledge oftentimes cannot provide direct evidence to the answer. The neural-symbolic framework [20] is also applied in the VQA domain since it is naturally more interpretable than the pure deep learning based methods. Recently, more works [21, 22] have been proposed for enhancing the explainability of the VQA problem using either natural or synthetic data. Another topic that is not well-studied in explainable VQA is the evaluation of explanations. In [16, 22], conventional NLP metrics such as ROUGE, BLEU scores are used to measure the quality of the generated explanation. Different from [16], [21] doesn't use a caption as the explanation, instead it uses tokens representing a bounding box in the image to replace key parts in the scene graph.

3   Methodology

In this section, we describe our method in detail. Please refer to Figure 2 for an overview of the model flow and architecture. The proposed method consists of two major components, (i) coarse-to-fine visual language reasoning for VQA and (ii) explanation generation module.

3.1   Extracting Features and Predicates

A pre-trained Faster-RCNN model[23] is used to extract features for each Region of Interest (RoI) in the image I. The image features as denoted as f_I. Similarly, a Faster-RCNN model is also used to extract objects and attributes, which form the image predicates. We generate the Glove embedding[24] for each word in the set of image predicates, denoted as p_I. The words in the question Q are also encoded using Glove embeddings. The question embeddings are then passed through

Figure 2: An overview of coarse-to-fine VQA with explanation generation.

a GRU to extract sequential features f_Q. Together with this, question predicates are extracted by passing the question through a stop words filter. The stop words not only consist of words from NLTK[25], but also includes those words in questions that occur less frequently (threshold=10). Each question predicate is then encoded with Glove embedding. Question predicates are denoted as p_Q.

3.2 Coarse-to-Fine Reasoning for VQA

VQA can be generally formulated as $(I, Q) \rightarrow \mathbf{a}$, where $a \in \mathcal{A}$ and $\mathcal{A}$ is the set of answers. Usually, the answer set $\mathcal{A}$ is filtered by a frequency threshold from the annotated answers. The coarse-to-fine reasoning framework can be formalized as :

$$
\begin{aligned}
\mathbf{a}^* &= arg \max_a \mathbf{CFR}_\theta(\mathbf{a}|f_I, p_I, f_Q, p_Q) \\
&= arg \max_a \mathbf{SR}(\mathbf{a}|\mathbf{IF}(f_I, p_I, f_Q, p_Q), \mathbf{MM}(f_I, p_I, f_Q, p_Q))
\end{aligned}
\tag{1}
$$

where $\mathbf{CFR}_\theta$ is an end-to-end module with learnable parameter θ. It consists of three different modules, including an information filtering module $\mathbf{IF}$, a multimodal learning module $\mathbf{MM}$, followed by a semantic reasoning module $\mathbf{SR}$.

Information Filtering The extracted features may be noisy and have incorrect information as they are extracted from pre-trained models. This module helps remove unnecessary information and aids in understanding the importance of RoIs in images for each question.

Multimodal Learning Bilinear Attention Networks are used to learn features at both coarse-grained and fine-grained levels. The coarse-grained module works with image and question features and predicates and produces a joint representation at the coarse-grained level. The fine-grained module learns the correlation of the filtered image and question information and learns a joint representation at the fine-grained level.

Semantic Reasoning This module learns selective information from both the coarse-grained and fine-grained module outputs. The joint embedding from this module is then fed into a multi-layer perceptron to perform answer prediction and to the explanation module for explanation generation.

3.3 Explanation Generation

The joint embedding from the semantic reasoning module is used to train an explanation generator with ground-truth explanations as supervision. The VQA backbone is augmented with the explanation generation module. Two architectures are evaluated for explanation generation: (i) Long Short-Term Memory (LSTM), (ii) Transformer Decoder. The LSTM architecture used consists of 2 layers, with an input dimension of 768. The Transformer Decoder architecture has an input dimension of 768, and consists of 8 attention heads. In both cases, the input is a joint embedding and is trained using ground-truth explanations from the dataset (discussed in the following section) using cross-entropy loss for each word. Suppose we have an explanation $\mathbf{E} = (w_1, ..., w_i, .., w_l)$, where $w_i \in \mathbb{V}$, the vocabulary and l is the length of the explanation. The explanation can therefore be represented as a sequence of one-hot encoded vectors. The loss function is therefore given by:

$$L_{expl} = -\frac{1}{l \cdot |\mathbb{V}|} \cdot \sum_{i=1}^{l} \sum_{k=1}^{|\mathbb{V}|} y_{i,k} \cdot \log(p(w_{i,k})) \tag{2}$$

where $y_{i,k}$ is the one-hot vector for the i^{th} word in the ground-truth explanation and $p(w_{i,k})$ is the probability of the k^{th} word in $\mathbb{V}$ at the i^{th} time step. We also make use of the teacher enforcing to train the explanation module with auto-regressive cross-entropy loss.

4 Experiments

4.1 Datasets and Evaluation

Figure 3: Examples from (a) GQA-REX dataset, (b) VQA-E dataset.

As discussed in section 2, there are a limited number of datasets that come with annotated explanations along with answers. Owing to the large dataset size, we perform our experiments on the **GQA-REX** and **VQA-E** datasets, although they have their own set of limitations. In this section, we measure the accuracy of the predicted answer and the quality of the generated explanation. To evaluate the predicted answer, we use the **VQA score** as the metric. Unfortunately, we don't have accurate metrics for explanation evaluation. Therefore, we report qualitative results from a **human-study** as well as quantitative results using conventional NLP metrics such as **ROUGE** and **BLEU**.

GQA-REX contains explanations for almost 98% of the samples in the GQA-balanced dataset. It contains around 1.04M question-answer (QA) pairs spanning across 82k images, with annotated explanations (1 explanation per QA pair). However, the explanations are consistent with the reasoning framework proposed in [21] and are therefore not completely in human-readable form (Refer Figure 3(a)). Although the explanations can be converted to human readable form using information from scene graphs, there are instances of grammatical inaccuracy.

VQA-E contains explanations for around 40% of the QA pairs in the VQA2.0 dataset (1 explanation per QA pair). The explanations are generated by comparing the similarity scores between the caption candidates and the ground-truth question-answer pair. It is, therefore not surprising that the explanations seem more like captions of the image which contains the answer. Figure 3(b) illustrates a couple of examples from the VQA-E dataset.

4.2 VQA Experimental Results

Dataset	Expl. Model	α	VQA score
VQA-E[16]	N/A	N/A	71.48
	LSTM	0.25	71.36
	LSTM	0.50	**71.55**
	LSTM	0.75	71.53
	LSTM	1.0	71.32
	Transformer	0.50	71.46
GQA-REX[21]	N/A	N/A	77.49
	LSTM	0.25	75.08
	LSTM	0.50	77.16
	LSTM	1.0	**77.33**
	Transformer	0.50	77.06

Table 1: VQA scores of the predicted answers from our method on VQA-E and GQA-REX validation datasets.

We use the CFRF[1] model as the backbone and augment it with an explanation module based on (i) LSTM, (ii) Transformer Decoder. The baseline model is trained without any explanations as supervision. Since our goal is to generate explanations while maintaining the VQA performance, we incorporate both the loss for VQA answer and the supervision from the ground-truth explanation. In order to investigate the impact from two different training signals, we design the loss function for the end-to-end training as follows: $L = \alpha L_{ans} + (1 - \alpha)L_{expl}$, where L_{ans} is the cross-entropy loss

162 between the predicted answer and the ground truth answer, L_{expl} is the loss function of the explana-
163 tion module, as represented by Equation 2, and $\alpha \in [0, 1]$ is the balance factor. As shown in Table 1,
164 our methods successfully maintain the VQA scores while generating textual explanations.

4.3 Results of Generated Explanations

Quantitative Results   We use the explanations generated by the CFRF+LSTM model, correspond-
167 ing to $\alpha = 0.75$ (Refer Table 1). The results of BLEU-1 and ROUGE scores are presented. Note that
168 ROUGE scores are F1 scores. As shown in Table 2, although our method outperforms the baseline,
169 the absolute scores are not satisfied.

Dataset	Model	BLEU-1	ROUGE-1	ROUGE-2	ROUGE-L
VQA-E val	Baseline[16]	0.268	-	-	0.249
	CFRF+LSTM	0.33	0.364	0.117	0.325

Table 2: Quantitative evaluation of the generated explanation on VQA-E validation set.

170 As mentioned in section 2, in the VQA domain, there is no standard common practice to quantitatively
171 evaluate generated explanations. Although both VQA-E and GQA-REX suggest using conventional
172 NLP metrics such as ROUGE and BLEU scores to evaluate the explanation, it is not ideal. These
173 metrics are particularly designed for string matching in the form of overlapping n-grams. Figure 4
174 illustrates why such metrics are practically unreliable.

Figure 4: Problem with using string matching metrics to evaluate generated explanations in VQA.

175 In Figure 4(a), our model predicts the correct answer. However, according to the string matching
176 metrics, the quality of the explanation is bad. In fact, interestingly, both the generated explanation
177 and ground-truth explanation in Figure 4(a) are annotated as valid by human annotators. On the
178 other hand, the generated explanation in Figure 4(b) is almost identical to the ground truth, and
179 both of them are approved by human subjects as valid explanations for the answer. In Figure 4(c),
180 even though the predicted explanation is wrong, the string matching score is very high. Because the
181 keywords are those related to the colors. These examples lead to such a conclusion: we need to find a
182 more reliable metric to evaluate the explanation in VQA problem.

Human Study Setup   Since no mature quantitative metrics are available, we introduce humans into
184 the loop. We conduct a human subject study using Amazon Mechanical Turk (AMT). The goal of our
185 subject study is to evaluate the quality of the explanation by human annotation. One example of the
186 human intelligence task (HIT) is shown in Figure 5:

Figure 5: An example of the HIT in the human study.

187 Given an image-question pair from the VQA-E validation set, we design two questions for the
188 annotators. Both questions are the same, asking whether an explanation leads to the answer. But the
189 contexts are different. In the first question, both explanation and answer are generated by our model.
190 In the second question, we provide a ground-truth explanation and answer. The subjects have the
191 same four options to choose from in both cases. They are: (i) Yes; (ii) No, but contains the answer;

Context	Yes	No, but contains the Ans.	No	Not determined
predicted [total]	56.46%	9.02%	34.12%	0.4%
predicted [unique]	65.16 %	2.01%	32.8%	0.03%
ground-truth [total]	83.90%	5.12%	10.98%	0%
ground-truth [unique]	93.12%	0.57%	6.31%	0%

Table 3: Statistics of the raw human annotation data. It contains 4735 unique examples from the VQA-E validation set. Each job is distributed to 3 different annotators to eliminate potential bias.

(iii) No; (iv) Not determined. Annotators have no idea which context is the ground truth. Specifically, option (ii) "No, but contains the answer" means the explanation contains a sub-string that matches the predicted answer, however, the explanation does not lead to the answer. Option (iv) "Not determined" means the explanation leads to the answers, but the reasoning chain may be contradictory.

Human Approved Results We randomly select 4735 unique image-question pairs from the VQA-E validation set for the human study. Each image-question pair makes up one HIT with the same setting as in Figure 5. In order to eliminate individual bias, we assign each HIT to three different workers. Therefore, in total, we have received $4735 \times 3 = 14205$ responses from 111 subjects. The raw distribution of subject annotations for all the 14205 responses (predicted [total] and ground-truth [total]) are shown in Table 3. From the total set of responses, questions for which there is no consensus among the three annotators (all three responses are different) are discarded (869 out of 4735). Following this, we calculate the vote using mode, i.e. majority vote for the unique HITs. Among the 3866 unique HITs, **65.16%** of the generated explanations leads to the predicted answers, while 2.01% of them contain the answers but make no sense. 32.8% of the generated explanations fail to make connections with the predicted answers. On the other hand, 93.12% of the ground-truth explanations successfully lead to the ground-truth answers. According to [16], because the ground-truth explanations are selected by comparing the similarity between the question-ground-truth-answer pair and the caption candidates, most of them are valid.

	Predicted		Ground-truth	
	Valid Expl.	Invalid Expl.	Valid Expl.	Invalid Expl.
Correct Ans.	**56.39%**	23.77%	93.11%	6.88%
Wrong Ans.	8.77%	11.05%	-	-

Table 4: Ratio of valid/invalid explanation based on the correctness of the predicted answer.

Besides raw annotations, we provide a more straightforward result, as shown in Table 4. Among the 3866 unique HITs, we find that in 56.39% of the cases, our model can predict both the correct answer as well as generate valid explanations. 23.77% of the explanation is not valid although the predicted answers are correct. It may either not make any sense or contain the answer in it, albeit without any significant meaning. Only in 8.77% of the cases, our model generates a good explanation but leads to a wrong answer. On the other hand, we also observe that 6.88% of the ground-truth explanations are not reasonable. Therefore, our model is able to answer question correctly and also generate valid explanations approximately **60.5%** of the time.

5 Conclusion and Future Work

We explore the task of Explainable Visual Question Answering (Explainable-VQA). We leverage the Coarse-to-Fine reasoning framework as the VQA backbone and augment it with an explanation generation module using two architectures: LSTM and Transformer Decoder. Our model generates an explanation along with an answer while also maintaining close to SOTA VQA performance. We conduct both objective experiments and a human study to evaluate the generated explanation, pointing out the urgency of proposing new metrics for explainable VQA.

Future Work We plan to improve the quality of generated explanations as well as leverage them to increase VQA accuracy. We urge for proper metrics to evaluate explanations in the VQA problem.

Acknowledgement We thank Nguyen et al., the authors of [1] for providing us with the features and predicates for the VQA 2.0 dataset, and helping with answering all queries in a timely manner.

References

[1] Binh X Nguyen, Tuong Do, Huy Tran, Erman Tjiputra, Quang D Tran, and Anh Nguyen. Coarse-to-fine reasoning for visual question answering. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4558–4566, 2022.

[2] Ranjay Krishna, Yuke Zhu, Oliver Groth, Justin Johnson, Kenji Hata, Joshua Kravitz, Stephanie Chen, Yannis Kalantidis, Li-Jia Li, David A Shamma, Michael Bernstein, and Li Fei-Fei. Visual genome: Connecting language and vision using crowdsourced dense image annotations. 2016.

[3] Drew A Hudson and Christopher D Manning. Gqa: A new dataset for real-world visual reasoning and compositional question answering. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 6700–6709, 2019.

[4] Stanislaw Antol, Aishwarya Agrawal, Jiasen Lu, Margaret Mitchell, Dhruv Batra, C Lawrence Zitnick, and Devi Parikh. Vqa: Visual question answering. In *Proceedings of the IEEE international conference on computer vision*, pages 2425–2433, 2015.

[5] Rowan Zellers, Yonatan Bisk, Ali Farhadi, and Yejin Choi. From recognition to cognition: Visual commonsense reasoning. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

[6] Peng Wang, Qi Wu, Chunhua Shen, Anthony Dick, and Anton Van Den Hengel. Fvqa: Fact-based visual question answering. *IEEE transactions on pattern analysis and machine intelligence*, 40(10):2413–2427, 2017.

[7] Kenneth Marino, Mohammad Rastegari, Ali Farhadi, and Roozbeh Mottaghi. Ok-vqa: A visual question answering benchmark requiring external knowledge. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019.

[8] Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katie Millican, Malcolm Reynolds, et al. Flamingo: a visual language model for few-shot learning. *arXiv preprint arXiv:2204.14198*, 2022.

[9] Zelin Zhao, Karan Samel, Binghong Chen, et al. Proto: Program-guided transformer for program-guided tasks. *Advances in Neural Information Processing Systems*, 34:17021–17036, 2021.

[10] Wenhui Wang, Hangbo Bao, Li Dong, Johan Bjorck, Zhiliang Peng, Qiang Liu, Kriti Aggarwal, Owais Khan Mohammed, Saksham Singhal, Subhojit Som, et al. Image as a foreign language: Beit pretraining for all vision and vision-language tasks. *arXiv preprint arXiv:2208.10442*, 2022.

[11] Feng Gao, Qing Ping, Govind Thattai, Aishwarya Reganti, Ying Nian Wu, and Prem Natarajan. A thousand words are worth more than a picture: Natural language-centric outside-knowledge visual question answering. *arXiv preprint arXiv:2201.05299*, 2022.

[12] Yash Goyal, Tejas Khot, Douglas Summers-Stay, Dhruv Batra, and Devi Parikh. Making the v in vqa matter: Elevating the role of image understanding in visual question answering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 6904–6913, 2017.

[13] Justin Johnson, Bharath Hariharan, Laurens Van Der Maaten, Li Fei-Fei, C Lawrence Zitnick, and Ross Girshick. Clevr: A diagnostic dataset for compositional language and elementary visual reasoning. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2901–2910, 2017.

[14] Kenneth Marino, Mohammad Rastegari, Ali Farhadi, and Roozbeh Mottaghi. Ok-vqa: A visual question answering benchmark requiring external knowledge. In *Proceedings of the IEEE/cvf conference on computer vision and pattern recognition*, pages 3195–3204, 2019.

[15] Alane Suhr, Stephanie Zhou, Ally Zhang, Iris Zhang, Huajun Bai, and Yoav Artzi. A corpus for reasoning about natural language grounded in photographs. *arXiv preprint arXiv:1811.00491*, 2018.

[16] Qing Li, Qingyi Tao, Shafiq Joty, Jianfei Cai, and Jiebo Luo. Vqa-e: Explaining, elaborating, and enhancing your answers for visual questions. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 552–567, 2018.

[17] Qing Li, Jianlong Fu, Dongfei Yu, Tao Mei, and Jiebo Luo. Tell-and-answer: Towards explainable visual question answering using attributes and captions. *arXiv preprint arXiv:1801.09041*, 2018.

[18] Jialin Wu, Zeyuan Hu, and Raymond J Mooney. Generating question relevant captions to aid visual question answering. *arXiv preprint arXiv:1906.00513*, 2019.

[19] Jialin Wu, Liyan Chen, and Raymond J Mooney. Improving vqa and its explanations by comparing competing explanations. *arXiv preprint arXiv:2006.15631*, 2020.

[20] Weixin Liang, Feiyang Niu, Aishwarya Reganti, Govind Thattai, and Gokhan Tur. Lrta: a transparent neural-symbolic reasoning framework with modular supervision for visual question answering. *arXiv preprint arXiv:2011.10731*, 2020.

[21] Shi Chen and Qi Zhao. Rex: Reasoning-aware and grounded explanation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15586–15595, 2022.

[22] Leonard Salewski, A Koepke, Hendrik Lensch, and Zeynep Akata. Clevr-x: A visual reasoning dataset for natural language explanations. In *International Workshop on Extending Explainable AI Beyond Deep Models and Classifiers*, pages 69–88. Springer, 2022.

[23] Peter Anderson, Xiaodong He, Chris Buehler, Damien Teney, Mark Johnson, Stephen Gould, and Lei Zhang. Bottom-up and top-down attention for image captioning and visual question answering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 6077–6086, 2018.

[24] Jeffrey Pennington, Richard Socher, and Christopher D Manning. Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pages 1532–1543, 2014.

[25] Edward Loper and Steven Bird. Nltk: The natural language toolkit. *arXiv preprint cs/0205028*, 2002.

Appendix for
Towards Reasoning-Aware Explainable VQA

Anonymous Author(s)
Affiliation
Address
`email`

(a)

(b)

Figure 1: (a) 3 examples for incorrectly predicted answer but correct explanation. (b) 3 examples for incorrectly predicted answer and incorrect explanation.

Q: What type of plant is this?
GT Ans: broccoli
GT Expl: a broccoli plant in the ground near other plant life

Pred Ans: broccoli
Pred Expl: a close up of a broccoli plant with leaves

Q: What sport is being performed?
GT Ans: skateboarding
GT Expl: a person that is doing a skateboarding trick

Pred Ans: skateboarding
Pred Expl: a man is doing a trick on a skateboard

Q: Is the horse walking on a trail?
GT Ans: no
GT Expl: a man is riding a horse on the beach

Pred Ans: no
Pred Expl: a man is riding a horse on the beach

Q: Is this in the forest?
GT Ans: yes
GT Expl: a blue bird is sitting in the branch of a tree

Pred Ans: yes
Pred Expl: a bird is perched on the branch of a tree

Q: Who is in the car?
GT Ans: cat
GT Expl: a cat is sitting in a car near the dash

Pred Ans: cat
Pred Expl: a cat is sitting in the driver 's seat of a car

Q: Is this building really tall?
GT Ans: yes
GT Expl: there is a very tall tower that has a clock on it

Pred Ans: yes
Pred Expl: a tall tower with a clock on the top of it

Q: What color is the bed sheet?
GT Ans: white
GT Expl: there is a bed with white sheets and pillows layer on it

Pred Ans: white
Pred Expl: a bed with a white comforter and pillows on it

Q: Is the bird sitting?
GT Ans: yes
GT Expl: a blue bird is sitting on a tree branch

Pred Ans: yes
Pred Expl: a bird is sitting on the branch of a tree

Q: Is it cold?
GT Ans: yes
GT Expl: a man in skis is standing in a snowy area

Pred Ans: yes
Pred Expl: a man is standing in the snow with skis and ski poles

Figure 2: 9 examples for correctly predicted answer and correct explanation.

Q: What game is he playing?
GT Ans: baseball
GT Expl: a baseball player is swinging a bat and some grass

Pred Ans: baseball
Pred Expl: a baseball player is swinging his bat

Q: Is this stop sign red?
GT Ans: yes
GT Expl: a red stop sign sitting on top of a wooden post.

Pred Ans: yes
Pred Expl: a red stop sign sitting in the middle of a road

Q:What color is the animal?
GT Ans: black
GT Expl: a black bear is standing outdoors in the wild.

Pred Ans: black
Pred Expl: a black bear is walking around in the woods

Q: How many trains are there?
GT Ans: 2
GT Expl: two trains are on tracks in a commuter strain station with people standing on the platform between them.
Pred Ans: 2
Pred Expl: two trains are parked on the tracks at a station

Q: Where is the kite?
GT Ans: sky
GT Expl: a man sitting in a field flying a kite in the blue sky.

Pred Ans: sky
Pred Expl: a man is flying a kite in the sky high

Q: What type of numbers are used?
GT Ans: roman numerals
GT Expl: a clock tower with roman numerals and a sun dial.

Pred Ans: roman numerals
Pred Expl: a clock on a building with roman numerals and a clock

Q: What color is the bus?
GT Ans: red
GT Expl: a red bus parked in front of a building near a street.

Pred Ans: red
Pred Expl: a red and white bus parked in front of a building

Q: Is the kite lifting in the wind?
GT Ans: yes
GT Expl: folks flying a kite in the water of a nice beach.
Pred Ans: yes
Pred Expl: a kite flying in the sky over a body of water

Q: How many sinks are there?
GT Ans: 2
GT Expl: modern bathroom with two sinks a toilet and a shower.

Pred Ans: 2
Pred Expl: a bathroom with two sinks and a mirror above it

Figure 3: 9 examples for correctly predicted answer and correct explanation.

Q: What colors are the dining plates?
GT Ans: blue and white
GT Expl: two slices of pizza are on a blue and white plate on a coffee table.
Pred Ans: blue and white
Pred Expl: a pizza sitting on top of a white plate covered in cheese and veggies

Q: What is the bottom cat doing?
GT Ans: sitting
GT Expl: a cat that is sitting on some steps.
Pred Ans: sitting
Pred Expl: a black and white cat is sitting in a black and white photo

Q: Which room is this?
GT Ans: bathroom
GT Expl: a bathroom which has a telephone, sink and mirror.
Pred Ans: bathroom
Pred Expl: a cat is sitting in a bathroom sink and is looking out into the distance

Q: What type of meat appears on the sandwich?
GT Ans: chicken
GT Expl: a chicken sandwich and fries on a table.
Pred Ans: chicken
Pred Expl: a chicken sandwich with onions and onions on a plate

Q: What color is the bench?
GT Ans: green
GT Expl: an old green wood bench on a porch with a white railing.
Pred Ans: green
Pred Expl: a man sitting on a park bench next to a green field

Q: What sport is being played?
GT Ans: tennis
GT Expl: a tennis player with a racket on a court
Pred Ans: tennis
Pred Expl: a tennis player is swinging his racket on the court

Q: What mode of transportation is this?
GT Ans: bus
GT Expl: a bus is riding down the street with passengers.
Pred Ans: bus
Pred Expl: a bus is parked in the parking lot while a passenger boards

Q: What color are the boats?
GT Ans: blue
GT Expl: several small blue boats side by side out in the open.
Pred Ans: blue
Pred Expl: a couple of small boats are on the blue water

Q: What kind of animal is pictured?
GT Ans: giraffe
GT Expl: a very large giraffe that is standing in the woods

Pred Ans: giraffe

Pred Expl: a giraffe is standing in the grass near a fence

Figure 4: 9 examples for correctly predicted answer but incorrect explanation.