Revisiting Realistic Test-Time Training: Sequential Inference and Adaptation by Anchored Clustering

Abstract

Deploying models on target domain data subject to distribution shift requires adaptation. Test-time training (TTT) emerges as a solution to this adaptation under a realistic scenario where access to full source domain data is not available and instant inference on target domain is required. Despite many efforts into TTT, there is a confusion over the experimental settings, thus leading to unfair comparisons. In this work, we first revisit TTT assumptions and categorize TTT protocols by two key factors. Among the multiple protocols, we adopt a realistic sequential test-time training (sTTT) protocol, under which we further develop a *test-time anchored clustering (TTAC)* approach to enable stronger test-time feature learning. TTAC discovers clusters in both source and target domain and match the target clusters to the source ones to improve generalization. Pseudo label filtering and iterative updating are developed to improve the effectiveness and efficiency of anchored clustering. We demonstrate that under all TTT protocols TTAC consistently outperforms the state-of-the-art methods on five TTT datasets. We hope this work will provide a fair benchmarking of TTT methods and future research should be compared within respective protocols.

1 Introduction

The recent success in deep learning is attributed to the availability of large labeled data [14, 39] and the assumption of i.i.d. between training and test datasets. Such assumptions could be violated when test data features a drastic difference from the training data, e.g. training on synthetic images and test on real ones, and this is often referred to as domain shift [21, 2]. To tackle this issue, domain adaptation (DA) [31] emerges and the labeled training data and unlabeled testing data are often referred to as source and target data/domains respectively.

The existing DA works either require the access to both source and target domain data during training [4] or training on multiple domains simultaneously [38]. The former approach renders the methods restrictive to limited scenarios where source domain data is always available during adaptation while the latter ones are computationally more expensive. To alleviate the reliance on source domain data, which may be inaccessible due to privacy issues or storage overhead, source-free domain adaptation (SFDA) emerges which handles DA on target data without access to source data [18, 15, 36, 34, 19]. SFDA is often achieved through self-training [18], self-supervised learning [19] or introducing prior knowledge [18] and it requires multiple training epochs on the full target data to allow convergence. Despite easing the dependence on source data, SFDA has major drawbacks in a more realistic domain adaptation scenario where test data arrives in a stream and inference or prediction must be taken instantly, and this setting is often referred to as test-time training (TTT) or adaptation (TTA) [26, 30, 12, 19]. Despite the attractive feature of adaption at time test, we notice a confusion of what defines a test-time training and as a result comparing apples

and oranges happens frequently in the community. In this work, we first categorize TTT by two key factors after summarizing various definitions made in existing works. First, under a realistic TTT setting, test samples are sequentially streamed and prediction must be made instantly upon the arrival of a new test sample. More specifically, the prediction of test sample X_T, arriving at time stamp T, should not be affected by any subsequent samples, $\{X_t\}_{t=T+1\cdots\infty}$. Throughout this work, We refer to the sequential streaming as **one-pass adaptation** protocol and any other protocols violating this assumption are called **multi-pass adaptation** (model may be updated on all test data for multiple epochs before inference). Second, we notice some recent works must **modify source domain training loss**, e.g. by introducing additional self-supervised branch, to allow more effective TTT [26, 19]. This will introduce additional overhead in the deployment of TTT because re-training on some source dataset, e.g. ImageNet, is computationally expensive. In this work, we aim to tackle on the most realistic and challenging TTT protocol, i.e. one-pass test time training with no modifications to training objective. This setting is similar to TTA proposed in [30] except for not restricting access to a light-weight information from the source domain. Given the objective of TTT being efficient adaptation at time-time, this assumption is computationally efficient and improves TTT performance substantially. We name this new TTT protocol as **sequential test time training (sTTT)**.

We propose two techniques to enable efficient and accurate sTTT. i) We are inspired by the recent progresses in unsupervised domain adaptation [27] that encourages testing samples to form clusters in the feature space. However, separately learning to cluster in the target domain without regularization from source domain does not guarantee improved adaptation [27]. To overcome this challenge, we identify clusters in both the source and target domains through a mixture of Gaussians with each component Gaussian corresponding to one category. Provided with the category-wise statistics from source domain as anchors, we match the target domain clusters to the anchors by minimizing the KL-Divergence as the training objective for sTTT. Therefore, we name the proposed method *test-time anchored clustering (TTAC)*. Since test samples are sequentially streamed, we develop an exponential moving averaging strategy to update the target domain cluster statistics to allow gradient-based optimization. ii) Each component Gaussian in the target domain is updated by the test sample features that are assigned to the corresponding category. Thus, incorrect assignments (pseudo labels) will harm the estimation of component Gaussian. To tackle this issue, we are inspired by the correlation between network's stability and confidence and pseudo label accuracy [16, 23], and propose to filter out potential incorrect pseudo labels. Component Gaussians are then updated by the samples that have passed the filtering. To exploit the filtered out samples, we incorporate a global feature alignment [19] objective. We also demonstrate TTAC is compatible with existing TTT techniques, e.g. contrastive learning branch [19], if source training loss is allowed to be modified. The contributions of this work are summarized as below.

- In light of the confusions within TTT works, we provide a categorization of TTT protocols by two key factors. Comparison of TTT methods is now fair within each category.
- We adopt a realistic TTT setting, namely sTTT. To improve test-time feature learning, we propose TTAC by matching the statistics of the target clusters to the source ones. The target statistics are updated through moving averaging with filtered pseudo labels.
- The proposed method is complementary to existing TTT method and is demonstrated on five TTT datasets, achieving the state-of-the-art performance under all categories of TTT protocols.

2   Related Work

Unsupervised Domain Adaptation. Domain adaptation aims to improve model generalization when source and target data are not drawn i.i.d. When target data are unlabeled, UDA [4, 28] learns domain invariant feature representations on both source and target domains to improve generalization. Follow-up works improve DA by minimizing a divergence [5, 24, 37], adversarial training [10] or discovering cluster structures in the target data [27]. Apart from formulating DA within a task-specific model, re-weighting has been adopted for domain adaptation by selectively up-weighting conducive samples in the source domain [13, 35]. Despite the efforts in UDA, it is inevitable to access the source domain data which may be not accessible due to privacy issues, storage overhead, etc. Deploying DA in more realistic scenarios has inspired research into source-free domain adaptation and test-time training/adaptation.

Source-Free Domain Adaptation. Without the access to source data, source-free domain adaptation (SFDA) develops domain adaptation through self-training [18, 15, 12], self-supervised training [19] or clustering in the target domain [36]. It has been demonstrated that SFDA performs well on seminal domain adaptation datasets even compared against UDA methods [27]. Nevertheless, SFDA still requires access to all testing data and training must be carried out iteratively on the testing data. In a more realistic DA scenario where inference and adaptation must be implemented simultaneously, SFDA will no longer be effective. Moreover, some statistical information on the source domain does not pose privacy issues and can be exploited to further improve adaptation on target data.

Test-Time Training. Collecting enough samples from target domain and adapt models in an offline manner restricts the application to adapting to static target domain. To allow fast and online adaptation, test-time training (TTT) [26, 32] or adaptation (TTA) [30] emerges. Despite many recent works claiming to be test-time training, we notice a severe confusion over the definition of TTT. In particular, whether training objective must be modified [26, 19] and whether sequential inference on target domain data is possible [30, 12]. Therefore, to reflect the key challenges in TTT, we define a setting called sequential test-time training (sTTT) which neither modifies the training objective nor violates sequential inference. Under the more clear definition, some existing works, e.g. TTT [26] and TTT++ [19] is more likely to be categorized into SFDA. Several existing works [30, 12] can be adapted to the sTTT protocol. Tent [30] proposed to adjust affine parameters in the batchnorm layers to adapt to target domain data. The high TTA efficiency inevitably leads to limited performance gain on the target domain. T3A [12] further proposed to update classifier prototype through pseudo labeling. Despite being efficient, updating classifier prototype alone does not affect feature representation for the target domain. Target feature may not form clusters at all when the distribution mismatch between source and target is large enough. In this work we propose to simultaneously cluster on the target domain and match target clusters to source domain classes, namely anchored clustering. To further constrain feature update, we introduce additional global feature alignment and pseudo label filtering. Through the introduced anchored clustering, we achieve test-time training of more network parameters and achieve the state-of-the-art performance.

3 Methodology

In this section we first introduce the anchored clustering objective for test-time training through pseudo labeling and then describe an efficient iterative updating strategy. An overview of the proposed pipeline is illustrated in Fig. 1.

Figure 1: Overview of TTAC pipeline. i) In the source domain, we calculate category-wise and global statistics as anchors. ii) In the testing stage, samples are sequentially streamed and pushed into a fixed-length queue. Clusters in target domain are identified through anchored clustering with pseudo label filtering. Target clusters are then matched to the anchors in source domain to achieve test-time training.

3.1 Anchored Clustering for Test-Time Training

Discovering cluster structures in the target domain has been demonstrated effective for unsupervised domain adaptation [27] and we develop an anchored clustering on the test data aloneWe first use a mixture of Gaussians to model the clusters in the target domain, here each component Gaussian represents one discovered cluster. We further use the distributions of each category in the source domain as anchors for the target distribution to match against. In this way, test data features can simultaneously form clusters and the clusters are associated with source domain categories, resulting in improved generalization to target domain. Formally, we first write the mixture of Gaussians in the source and target domains $p_s(x) = \sum_k \alpha_k \mathcal{N}(\mu_{sk}, \Sigma_{sk})$, $p_t(x) = \sum_k \beta_k \mathcal{N}(\mu_{tk}, \Sigma_{tk})$, where $\{\mu_k \in \mathbb{R}^d, \Sigma_k \in \mathbb{R}^{d \times d}\}$ represent one cluster in the source/target domain and d is the dimension of feature embedding.

Anchored clustering can be achieved by matching the above two distributions and one may directly minimize the KL-Divergence between the two distribution. Nevertheless, this is non-trivial because the KL-Divergence between two mixture of Gaussians has no closed-form solution which prohibits efficient gradient-based optimization. Despite some approximations exist [9], without knowing the semantic labels for each Gaussian component, even a good match between two mixture of Gaussians does not guarantee target clusters are aligned to the correct source ones and this will severely harm the performance of test-time training. In light of these challenges, we propose a category-wise alignment. Specifically, we allocate the same number of clusters in both source and target domains and each target cluster is assigned to one source cluster. We can then minimize the KL-Divergence between each pair of clusters as in Eq. 1.

$$
\begin{aligned}
\mathcal{L}_{ac} &= \sum_k D_{KL}(\mathcal{N}(\mu_{sk}, \Sigma_{sk}) || \mathcal{N}(\mu_{tk}, \Sigma_{tk})) \\
&= \sum_k -H(\mathcal{N}(\mu_{sk}, \Sigma_{sk})) + H(\mathcal{N}(\mu_{sk}, \Sigma_{sk}), \mathcal{N}(\mu_{tk}, \Sigma_{tk}))
\end{aligned}
\tag{1}
$$

The KL-Divergence can be further decomposed into the entropy $H(\mathcal{N}(\mu_{sk}, \Sigma_{sk}))$ and cross-entropy $H(\mathcal{N}(\mu_{sk}, \Sigma_{sk}), \mathcal{N}(\mu_{tk}, \Sigma_{tk}))$. It is commonly true that the source reference distribution $P_s(x)$ is fixed thus the entropy term is a constant C and only the cross-entropy term is to be optimized. Given the closed-form solution to the KL-Divergence between two Gaussian distributions, we now write the anchored clustering objective as,

$$
\mathcal{L}_{ac} = \sum_k \{\log \sqrt{2\pi^d |\Sigma_{tk}|} + \frac{1}{2}(\mu_{tk} - \mu_{sk})^\top \Sigma_{tk}^{-1}(\mu_{tk} - \mu_{sk}) + tr(\Sigma_{tk}^{-1}\Sigma_{sk})\} + C
\tag{2}
$$

The source cluster parameters can be estimated in an offline manner. These information will not cause any privacy leakage and only introduces a small computation and storage overheads. In the next section, we elaborate clustering in the target domain.

3.2 Clustering through Pseudo Labeling

In order to test-time train network with anchored clustering loss, one must obtain target cluster parameters $\{\mu_{tk}, \Sigma_{tk}\}$. For a minibatch of target test samples $\mathcal{B}^t = \{x_i\}_{i=1 \ldots N_B}$ at timestamp t, we first denote the predicted posterior as $P^t = softmax(h(f(x_i))) \in [0,1]^{B \times K}$ where $softmax(\cdot)$, $h(\cdot)$ and $f(\cdot)$ respectively denote a standard softmax function, the classifier head and backbone network. The pseudo labels are obtained via $\hat{y}_i = \arg\max_k P_{ik}^t$. Given the predicted pseudo labels we could estimate the mean and covariance for each component Gaussian with the pseudo labeled testing samples. However, pseudo labels are always subject to model's discrimination ability. The error rate for pseudo labels is often high when the domain shift between source and target is large, directly updating the component Gaussian is subject to erroneous pseudo labels, a.k.a. confirmation bias [1]. To reduce the impact of incorrect pseudo labels, we first adopt a light-weight temporal consistency (TC) pseudo label filtering approach. Compared to co-teaching [6] or meta-learning [17] based methods, this light-weight method does not introduce additional computation overhead and is therefore more suitable for test-time training. Specifically, to alleviate the impact from the noisy predictions, we calculate the temporal exponential moving averaging posteriors $\widetilde{P}^t \in [0,1]^{N \times K}$ as below,

$$\widetilde{P}_i^t = (1 - \xi) * \widetilde{P}_i^{t-1} + \xi * P_i^t \quad , \quad s.t. \quad \widetilde{P}_i^0 = P_i^0 \tag{3}$$

The temporal consistency filtering is realized as in Eq. 4 where τ_{TC} is a threshold determining the maximally allowed difference in the most probable prediction over time. If the posterior deviate from historical value too much, it will be excluded from target domain clustering.

$$F_i^{TC} = \mathbb{1}((P_{i\hat{k}}^t - \widetilde{P}_{i\hat{k}}^{t-1}) > \tau_{TC}), \quad s.t. \quad \hat{k} = \arg\max_k(P_{ik}^t) \tag{4}$$

Due to the sequential inference, test samples without enough historical predictions may still pass the TC filtering. So, we further introduce an additional pseudo label filter directly based on the posterior probability as,

$$F_i^{PP} = \mathbb{1}(\widetilde{P}_{i\hat{k}}^t > \tau_{PP}) \tag{5}$$

By filtering out potential incorrect pseudo labels, we update the component Gaussian only with the leftover target samples as below.

$$\mu_{tk} = \frac{\sum_i F_i^{TC} F_i^{PP} \mathbb{1}(\hat{y}_i = k) f(x_i)}{\sum_i F_i^{TC} F_i^{PP} \mathbb{1}(\hat{y}_i = k)}, \quad \Sigma_{tk} = \frac{\sum_i F_i^{TC} F_i^{PP} \mathbb{1}(\hat{y}_i = k)(f(x_i) - \mu_{tk})^\top (f(x_i) - \mu_{tk})}{\sum_i F_i^{TC} F_i^{PP} \mathbb{1}(\hat{y}_i = k)} \tag{6}$$

3.3 Global Feature Alignment

As discussed above, test samples that do not pass the filtering will not contribute to the estimation of target clusters. Hence, anchored clustering may not reach its full potential without the filtered test samples. To exploit all available test samples, we propose to align global target data distribution to the source one. We define the global feature distribution of the source data as $\hat{p}_s(x) = \mathcal{N}(\mu_s, \Sigma_s)$ and the target data as $\hat{p}_t(x) = \mathcal{N}(\mu_t, \Sigma_t)$. To align two distributions, we again minimize the KL-Divergence as,

$$\mathcal{L}_{ga} = D_{KL}(\hat{p}_s(x) || \hat{p}_t(x)) \tag{7}$$

Similar idea has appeared in [19] which directly matches the moments between source and target domains [37] by minimizing the F-norm for the mean and covariance, i.e. $||\mu_t - \mu_s||_2^2 + ||\Sigma_t - \Sigma_s||_F^2$. However, designed for matching complex distributions represented as drawn samples, central moment discrepancy [37] requires summing infinite central moment discrepancies and the ratios between different order moments are hard to estimate. For matching two parameterized Gaussian distributions KL-Divergence is more convenient with good explanation from a probabilistic point of view. Finally, we add a small constant to the diagonal of Σ for both source and target domains to increase the condition number for better numerical stability.

3.4 Efficient Iterative Updating

Despite the distribution for source data can be trivially estimated from all available training data in a totally offline manner, estimating the distribution for target domain data is not equally trivial, in particular under the sTTT protocol. In a related research [19], a dynamic queue of test data features are preserved to dynamically estimate the statistics, which will introduce additional memory footprint [19]. To alleviate the memory cost we propose to iteratively update the running statistics for Gaussian distribution. Formally, we define t-th test minibatch as $\mathcal{B}^t = \{x_i\}_{i=1\cdots N_B}$. Denoting the running mean and covariance at step t as μ^t and Σ^t, we present the rules to update the mean and covariance in Eq. 8. More detailed derivations and update rules for per cluster statistics are deferred to the Appendix.

$$\mu^t = \mu^{t-1} + \delta^t, \quad \Sigma^t = \Sigma^{t-1} + a^t \sum_{x_i \in \mathcal{B}} \{(f(x_i) - \mu^{t-1})^\top (f(x_i) - \mu^{t-1}) - \Sigma^{t-1}\} - \delta^{t\top} \delta^t$$

$$\delta^t = a^t \sum_{x_i \in \mathcal{B}} (f(x_i) - \mu^{t-1}), \quad N^t = N^{t-1} + |\mathcal{B}^t|, \quad a^t = \frac{1}{N^t}, \tag{8}$$

Additionally, N^t grows larger overtime. New test samples will have smaller contribution to the update of target domain statistics when N^t is large enough. As a result, the gradient calculated from current minibatch will vanish. To alleviate this issue, we impose a clip on the value of α^t as below. As such, the gradient can maintain a minimal scale even if N^t is very large.

$$a^t = \begin{cases} \frac{1}{N^t} & N^t < N_{clip} \\ \frac{1}{N_{clip}} & others \end{cases} \qquad (9)$$

3.5 TTAC Training Algorithm

We summarize the training algorithm for the TTAC in Algo. 1. For effective clustering in target domain, we allocate a fixed length memory space, denoted as $\mathcal{C} \in \mathcal{R}^{N_C \times H \times W \times 3}$, to store the recent testing samples. In the sTTT protocol, we first make instant prediction on each testing sample, and only update the model when N_B testing samples are accumulated. TTAC can be efficiently implemented, e.g. with two devices, one is for continuous inference and another is for model updating.

Algorithm 1: Test-Time Anchored Clustering Training Algorithm

---

input :A new testing sample batch $\mathcal{B}^t = \{x_i\}_{i=1...N_B}$.
Update the testing sample queue $\mathcal{C}$.
$\mathcal{C}^t = \mathcal{C}^t \setminus \mathcal{B}^{t-N_C/N_B}, \quad \mathcal{C}^t = \mathcal{C}^t \bigcup \mathcal{B}^t$
for 1 **to** N_{itr} **do**
    for *minibatch* $\{x_k^t\}_{k=1}^N$ *in* $\mathcal{C}^t$ **do**
        # Obtain the predicted posterior and pseudo labels
        $P_i^t = softmax(h(f(x_i^t))), \quad \hat{y}_i^t = \arg\max_k(P_{ik}^t)$
        # Calculate the global and per-cluster running mean and covariance by Eq. 8
        $\mu^t, \quad \Sigma^t, \quad \{\mu_k^t\}, \quad \{\Sigma_k^t\}$
        # Optimize the combined loss by Eq. 2 and Eq. 7
        $\mathcal{L} = \mathcal{L}_{ac} + \lambda\mathcal{L}_{ga}$
        update network f to minimize $\mathcal{L}$

---

4 Experiment

In this section, we first compare various existing methods based on the two key factors. Evaluation is then carried out on five test-time training datasets. We then ablate the components of TTAC. Further analysis on the cumulative performance, qualitative insights, etc. are provided at the end.

4.1 Datasets

We evaluate on 5 test-time training datasets and report the classification error rate (%) throughout the experiment section. To evaluate the test-time training efficacy on corrupted target images, we use **CIFAR10-C/CIFAR100-C** [8], each consisting of 10/100 classes with 50,000 training samples of clean data and 10,000 corrupted test samples. We further evaluate test-time training on hard target domain samples with **CIFAR10.1** [22], which contains around 2,000 difficult testing images sampled over years of research on the original CIFAR-10 dataset. To demonstrate the ability to do test-time training for synthetic data to real data transfer we further use **VisDA-C** [20], which is a challenging large-scale synthetic-to-real object classification dataset, consisting of 12 classes, 152,397 synthetic training images and 55,388 real testing images. Finally, to evaluate test-time training on 3D point cloud data, we choose **ModelNet40-C** [25], which consists of 15 common and realistic corruptions of point cloud data, with 9,843 training samples and 2,468 test samples.

4.2 Experiment Settings

Hyperparameters. We use the ResNet-50 [7] for image datasets and the DGCNN [33] on ModelNet40-C. We optimize the backbone network $f(\cdot)$ by SGD with momentum on all datasets. On CIFAR10-C/CIFAR100-C and CIFAR10.1, we set BS = 256 and LR = 0.01, 0.0001, 0.01 respectively. On VisDA-C we set BS = 128 and LR = 0.0001, and on ModelNet40-C we set BS = 64 and LR = 0.001. More details of hyperparameters can be found in the Appendix.

Test-Time Training Protocols. We categorize test-time training based on two key factors. First, whether the training objective must be changed during training on the source domain, we use Y and N

to indicate if training objective is allowed to be changed or not respectively. Second, whether testing data is sequentially streamed and predicted, we use O to indicate a sequential **O**ne-pass inference and M to indicate non-sequential inference, a.k.a. **M**ulti-pass inference. With the above criteria, we summarize 4 test-time training protocols, namely N-O, Y-O, N-M and Y-M, and the strength of the assumption increases from the first to the last protocols. Ours sTTT setting makes the weakest assumption, i.e. N-O. Existing methods are categorized by the four TTT protocols, we notice that some methods can operate under multiple protocols

Competing Methods. We compare the following test-time training methods. Direct testing (**TEST**) without adaptation simply do inference on target domain with source domain model. Test-time training (**TTT-R**) [26] jointly trains the rotation-based self-supervised task and the classification task in the source domain, and then only train the rotation-based self-supervised task in the streaming test samples and make the predictions instantly. The default method is classified into the Y-M protocol. Test-time normalization (**BN**) [11] moving average updates the batch normalization statistics by streamed data. The default method follows N-M protocol and can be adapted to N-O protocol. Test-time entropy minimization (**TENT**) [30] updates the parameters of all batch normalization by minimizing the entropy of the model predictions in the streaming data. By default, TENT follows the N-O protocol and can be adapted to N-M protocol. Test-time classifier adjustment (**T3A**) [12] computes target prototype representation for each category using streamed data and make predictions with updated prototypes. T3A follows the N-O protocol by default. Source Hypothesis Transfer (**SHOT**) [18] freezes the linear classification head and trains the target-specific feature extraction module by exploiting balanced category assumption and self-supervised pseudo-labeling in the target domain. SHOT by default follows the N-M protocol and we adapt it to N-O protocol. **TTT++** [19] aligns source domain feature distribution, whose statistics are calculated offline, and target domain feature distribution by minimizing the F-norm between the mean covariance. TTT++ follows the Y-M protocol and we adapt it to N-O (removing contrastive learning branch) and Y-O protocols. Finally, we present our own approach, **TTAC**, which only requires a single pass on the target domain and does not have to modify the source training objective. We further modify TTAC for Y-O, N-M and Y-M protocols, for Y-O and Y-M we incorporate an additional contrastive learning branch [19]. We could further combine TTAC with additional diversity loss and entropy minimization loss introduced in SHOT [18], denoted as TTAC+SHOT.

4.3 Test-Time Training on Corrupted Target Domain

We present the test-time training results on CIFAR10C/100C and ModelNet40C datasets in Tab. 1. We make the following observations from the results.

sTTT (N-O) Protocol. We first analyze the results under the proposed sTTT (N-O) protocol. Our method outperforms all competing ones by a large margin, e.g. 3% improvement is observed on both CIFAR10-C and CIFAR100-C from the previous best (TTT++). We further combine TTAC with the class balance assumption made in SHOT (TTAC+SHOT). With the stronger assumptions out method can further improve upon TTAC alone, in particular on ModelNet40-C dataset. This result demonstrates TTAC's compatibility with existing methods.

Alternative Protocols. We further compare different methods under N-M, Y-O and Y-M protocols. Under the Y-O protocol, TTT++ [19] modifies the source domain training objective by incorporating a contrastive learning branch [3]. To compare with TTT++, we also include the contrastive branch and observe a clear improvement on both CIFAR10-C and CIFAR100-C datasets. More TTT methods can be adapted to the N-M protocol which allows training on the whole target domain data multiple epochs. Specifically, we compared with BN, TENT and SHOT. With TTAC alone we observe substantial improvement on all three datasets and TTAC can be further combined with SHOT demonstrating additional improvement. Finally, under the Y-M protocol, we demonstrate very strong performance compared to TTT-R and TTT++. It is also worth noting that TTAC under the N-O protocol can already yield results close to TTT++ under the Y-M protocol, suggesting the strong test-time training ability of TTAC even under the most challenging TTT protocol.

4.4 Additional Datasets

TTT on Hard Samples. CIFAR10.1 contains roughly 2,000 new test images that were re-sampled after the research on original CIFAR-10 dataset, which consists of some hard samples and reflects the normal domain shift in our life. The results in Table. 2 demonstrate our method is better able to adapt to the normal domain shift.

Table 1: Comparison under different TTT protocols. Y/N indicates modifying source domain training objective or not. O/M indicate one pass or multiple passes test-time training. C10-C, C100-C and MN40-C refer to CIFAR10-C, CIFAR100-C and ModelNet40-C datasets respectively. All numbers indicate error rate in percentage.

Method	TTT Protocol	Assum. Strength	C10-C	C100-C	MN40-C
TEST	-	-	29.15	60.34	34.62
BN [11]	N-O	Weak	15.49	43.38	26.53
TENT [30]	N-O	Weak	14.27	40.72	26.38
T3A [12]	N-O	Weak	15.44	42.72	24.57
SHOT [18]	N-O	Weak	13.95	39.10	19.71
TTT++ [19]	N-O	Weak	13.69	40.32	-
TTAC (Ours)	N-O	Weak	**10.94**	36.64	22.30
TTAC+SHOT (Ours)	N-O	Weak	10.99	**36.39**	**19.21**
TTT++ [19]	Y-O	Medium	13.00	35.23	-
TTAC (Ours)	Y-O	Medium	**10.69**	**34.82**	-
BN [11]	N-M	Medium	15.70	43.30	26.49
TENT [30]	N-M	Medium	12.60	36.30	21.23
SHOT [18]	N-M	Medium	14.70	38.10	15.99
TTAC (Ours)	N-M	Medium	**9.42**	33.55	16.77
TTAC+SHOT (Ours)	N-M	Medium	9.54	**32.89**	**15.04**
TTT-R [26]	Y-M	Strong	14.30	40.40	-
TTT++ [19]	Y-M	Strong	9.80	34.10	-
TTAC (Ours)	Y-M	Strong	**8.52**	**30.57**	-

TTT on Synthetic to Real Adaptation. VisDA-C is a large-scale benchmark of synthetic-to-real object classification dataset. The setting of training on a synthetic dataset and testing on real data fits well with the real application scenario. On this dataset, we conduct experiments with our method under the N-O, Y-O and Y-M protocols and other methods under respective protocols, results are presented in Table. 4. We make the following observations. First, our method (TTAC Y-O) outperforms all methods except TTT++ under the Y-M protocol. This suggests TTAC is able to be deployed in the realistic test-time training protocol. Moreover, if training on the whole target data is allowed, TTAC (Y-M) further beats TTT++ by a large margin, suggesting the effectiveness of TTAC under a wide range of TTT protocols.

Table 2: Test-time training on CIFAR10.1.

TEST	BN	TTT-R	TENT	SHOT	TTT++	TTAC
12.1	14.1	11.0	13.4	11.1	9.5	**9.2**

Table 3: Source-free sTTT on CIFAR10-C.

TEST	BN	TENT	T3A	SHOT	TTAC	TTAC+SHOT
29.15	15.49	14.27	15.44	13.95	13.74	**13.35**

Table 4: Test-time training on VisDA. The numbers for competing methods are inherited from [19].

Method	Plane	Bcycl	Bus	Car	Horse	Knife	Mcycl	Person	Plant	Sktbrd	Train	Truck	Per-class
TEST	56.52	88.71	62.77	30.56	81.88	99.03	17.53	95.85	51.66	77.86	20.44	99.51	65.19
BN (N-M) [11]	44.38	56.98	33.24	55.28	37.45	66.60	16.55	59.02	43.55	60.72	31.07	82.98	48.99
TENT (N-M) [30]	13.43	77.98	20.17	48.15	21.72	82.45	12.37	35.78	21.06	76.41	34.11	98.93	45.21
SHOT (N-M) [18]	5.73	**13.64**	23.33	42.69	7.93	86.99	19.17	19.97	11.63	11.09	15.06	**43.26**	25.04
TFA (N-M) [19]	28.25	32.03	33.67	64.77	20.49	56.63	22.52	36.30	24.84	35.20	25.31	64.24	37.02
TTT++ (Y-M) [19]	4.13	26.20	21.60	**31.70**	7.43	83.30	7.83	21.10	7.03	**7.73**	**6.91**	51.40	23.03
TTAC (N-O)	18.54	40.20	35.84	63.11	23.83	39.61	15.51	41.35	22.97	46.56	25.24	67.81	36.71
TTAC (Y-O)	7.19	29.99	22.52	56.58	8.14	18.41	8.25	22.28	10.18	23.98	13.55	67.02	24.01
TTAC (Y-M)	**2.74**	17.73	**18.91**	43.12	**5.54**	12.24	**4.66**	15.90	**4.77**	10.78	9.75	62.45	**17.38**

4.5 Ablation Study

We conduct ablation study on CIFAR10-C dataset for individual components, including anchored clustering, pseudo label filtering, global feature alignment and finally the compatibility with contrastive branch [19]. For anchored clustering alone, we use all testing samples to update cluster statistics. For pseudo label filtering alone, we implement as predicting pseudo labels followed by filtering, then pseudo labels are used for self-training. We make the following observations from Tab. 5. Under both N-O and N-M protocols, introducing anchored clustering or pseudo label filtering alone improves over the baseline, e.g. under N-O $29.15\% \rightarrow 14.32\%$ for anchored clustering and $29.15\% \rightarrow 15.00\%$ for pseudo label filtering. When anchored clustering is combined with pseudo label filtering, we observe a significant boost in performance. This is due to more accurate estimation of category-wise

(a) Test-time cumulative error (b) TTT++ Feature (c) TTAC Feature

Figure 2: (a) Comparison of test-time cumulative error under one-pass protocol. (b) T-SNE visualization of TTT++ feature embedding. (c) T-SNE visualization of TTAC feature embedding.

cluster in the target domain and this reflects matching directly in the feature space may be better than minimizing cross-entropy with pseudo labels. We further evaluate aligning global features alone with KL-Divergence. This achieves relatively good performance and obviously outperforms the L2 distance alignment adopted in [19]. Finally, we combine all three components and the full model yields the best performance. When contrast learning branch is included, TTAC achieves even better results.

Table 5: Ablation study for individual components on CIFAR10-C dataset.

TTT Protocol	-			N-O			Y-O			N-M			Y-M
Anchored Cluster.	-	✓	-	✓	-	✓	✓	✓	✓	-	-	✓	✓
Pseudo Label Filter.	-	-	✓	✓	-	✓	✓	-	✓	-	-	✓	✓
Global Feat. Align.	-	-	-	-	KLD	KLD	KLD	-	-	L2 Dist.[19]	KLD	KLD	KLD
Contrast. Branch [19]	-	-	-	-	-	-	✓	-	-	-	-	-	✓
Avg Acc	29.15	14.32	15.00	11.33	11.72	10.94	10.69	11.11	10.01	11.87	10.8	9.42	8.52

4.6 Additional Analysis

Cumulative performance under sTTT. We illustrate the cumulative error under the sTTT protocol in Fig. 2 (a). For both datasets TTAC outperforms competing methods from the early stage of test-time training. The advantage is consistent throughout the TTT procedure.

TSNE Visualization of TTAC features. We provide qualitative results for test-time training by visualizing the adapted features through T-SNE [29]. In Fig. 2 (b) and Fig. 2 (c), we compared the features learned by TTT++ [19] and TTAC (Ours). We observe a better separation between classes by TTAC, implying an improved classification accuracy.

Source-Free Test-Time Training. TTT aims to adapt model to target domain data by doing simultaneous training and sequential inference. It has been demonstrated some light-weight information, e.g. statistics, from source domain will greatly improve the efficacy of TTT. Nevertheless, under a more strict scenario where source domain information is strictly blind, TTAC can still exploit classifier prototypes to facilitate anchored clustering. Specifically, we normalize the category-wise weight vector with the norm of corresponding target domain cluster center as prototypes. Then, we build source domain mixture of Gaussians by taking prototypes as mean with a fixed covariance matrix. The results on CIFAR10-C are presented in Tab. 3. It is clear that even without any statistical information from source domain, TTAC still outperforms all competing methods.

5 Conclusion

Test-time training (TTT) tackles the realistic challenges of deploying domain adaptation on-the-fly. In this work, we are first motivated by the confused evaluation protocols for TTT and propose two key criteria, namely modifying source training objective and sequential inference, to further categorize existing methods into four TTT protocols. Under the most realistic protocol, i.e. sequential test-time training (sTTT), we develop a test-time anchored clustering (TTAC) approach to align target domain features to the source ones. Unlike batchnorm and classifier prototype updates, anchored clustering allows all network parameters to be trainable, thus demonstrating stronger test-time training ability. We further propose pseudo label filtering and an iterative update method to improve anchored clustering and save memory footprint respectively. Experiments on five datasets verified the effectiveness of TTAC under sTTT as well as other TTT protocols.

References

[1] Eric Arazo, Diego Ortego, Paul Albert, Noel E O'Connor, and Kevin McGuinness. Pseudo-labeling and confirmation bias in deep semi-supervised learning. In *2020 International Joint Conference on Neural Networks (IJCNN)*, pages 1–8. IEEE, 2020.

[2] Shai Ben-David, John Blitzer, Koby Crammer, Alex Kulesza, Fernando Pereira, and Jennifer Wortman Vaughan. A theory of learning from different domains. *Machine learning*, 2010.

[3] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pages 1597–1607. PMLR, 2020.

[4] Yaroslav Ganin and Victor Lempitsky. Unsupervised domain adaptation by backpropagation. In *International conference on machine learning*. PMLR, 2015.

[5] Arthur Gretton, Karsten M Borgwardt, Malte J Rasch, Bernhard Schölkopf, and Alexander Smola. A kernel two-sample test. *The Journal of Machine Learning Research*, 13(1):723–773, 2012.

[6] Bo Han, Quanming Yao, Xingrui Yu, Gang Niu, Miao Xu, Weihua Hu, Ivor Tsang, and Masashi Sugiyama. Co-teaching: Robust training of deep neural networks with extremely noisy labels. *Advances in neural information processing systems*, 31, 2018.

[7] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[8] Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. In *International Conference on Learning Representations*, 2019.

[9] John R Hershey and Peder A Olsen. Approximating the kullback leibler divergence between gaussian mixture models. In *2007 IEEE International Conference on Acoustics, Speech and Signal Processing-ICASSP'07*, volume 4, pages IV–317. IEEE, 2007.

[10] Judy Hoffman, Eric Tzeng, Taesung Park, Jun-Yan Zhu, Phillip Isola, Kate Saenko, Alexei Efros, and Trevor Darrell. Cycada: Cycle-consistent adversarial domain adaptation. In *International conference on machine learning*, pages 1989–1998. PMLR, 2018.

[11] Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International conference on machine learning*, 2015.

[12] Yusuke Iwasawa and Yutaka Matsuo. Test-time classifier adjustment module for model-agnostic domain generalization. In *Advances in Neural Information Processing Systems*, volume 34, 2021.

[13] Jing Jiang and ChengXiang Zhai. Instance weighting for domain adaptation in nlp. ACL, 2007.

[14] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 25, 2012.

[15] Jogendra Nath Kundu, Naveen Venkat, R Venkatesh Babu, et al. Universal source-free domain adaptation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2020.

[16] Dong-Hyun Lee et al. Pseudo-label: The simple and efficient semi-supervised learning method for deep neural networks. In *Workshop on challenges in representation learning, ICML*, volume 3, page 896, 2013.

[17] Junnan Li, Yongkang Wong, Qi Zhao, and Mohan S Kankanhalli. Learning to learn from noisy labeled data. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 5051–5059, 2019.

[18] Jian Liang, Dapeng Hu, and Jiashi Feng. Do we really need to access the source data? Source hypothesis transfer for unsupervised domain adaptation. In *Proceedings of the 37th International Conference on Machine Learning*, 2020.

[19] Yuejiang Liu, Parth Kothari, Bastien van Delft, Baptiste Bellot-Gurlet, Taylor Mordan, and Alexandre Alahi. Ttt++: When does self-supervised test-time training fail or thrive? In *Advances in Neural Information Processing Systems*, volume 34, 2021.

[20] Xingchao Peng, Ben Usman, Neela Kaushik, Judy Hoffman, Dequan Wang, and Kate Saenko. Visda: The visual domain adaptation challenge, 2017.

[21] Joaquin Quiñonero-Candela, Masashi Sugiyama, Anton Schwaighofer, and Neil D Lawrence. *Dataset shift in machine learning*. Mit Press, 2008.

[22] Benjamin Recht, Rebecca Roelofs, Ludwig Schmidt, and Vaishaal Shankar. Do ImageNet classifiers generalize to ImageNet? In Kamalika Chaudhuri and Ruslan Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 5389–5400. PMLR, 09–15 Jun 2019.

[23] Kihyuk Sohn, David Berthelot, Nicholas Carlini, Zizhao Zhang, Han Zhang, Colin A Raffel, Ekin Dogus Cubuk, Alexey Kurakin, and Chun-Liang Li. Fixmatch: Simplifying semi-supervised learning with consistency and confidence. *Advances in Neural Information Processing Systems*, 33:596–608, 2020.

[24] Baochen Sun and Kate Saenko. Deep coral: Correlation alignment for deep domain adaptation. In *European conference on computer vision*, pages 443–450. Springer, 2016.

[25] Jiachen Sun, Qingzhao Zhang, Bhavya Kailkhura, Zhiding Yu, Chaowei Xiao, and Z. Morley Mao. Benchmarking robustness of 3d point cloud recognition against common corruptions, 2022.

[26] Yu Sun, Xiaolong Wang, Zhuang Liu, John Miller, Alexei Efros, and Moritz Hardt. Test-time training with self-supervision for generalization under distribution shifts. In *International Conference on Machine Learning*, 2020.

[27] Hui Tang, Ke Chen, and Kui Jia. Unsupervised domain adaptation via structurally regularized deep clustering. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 8725–8735, 2020.

[28] Eric Tzeng, Judy Hoffman, Ning Zhang, Kate Saenko, and Trevor Darrell. Deep domain confusion: Maximizing for domain invariance. *arXiv preprint arXiv:1412.3474*, 2014.

[29] Laurens Van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(11), 2008.

[30] Dequan Wang, Evan Shelhamer, Shaoteng Liu, Bruno Olshausen, and Trevor Darrell. Tent: Fully test-time adaptation by entropy minimization. In *International Conference on Learning Representations*, 2021.

[31] Mei Wang and Weihong Deng. Deep visual domain adaptation: A survey. *Neurocomputing*, 312:135–153, 2018.

[32] Qin Wang, Olga Fink, Luc Van Gool, and Dengxin Dai. Continual test-time domain adaptation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2022.

[33] Yue Wang, Yongbin Sun, Ziwei Liu, Sanjay E Sarma, Michael M Bronstein, and Justin M Solomon. Dynamic graph cnn for learning on point clouds. *Acm Transactions On Graphics (tog)*, 38(5):1–12, 2019.

[34] Haifeng Xia, Handong Zhao, and Zhengming Ding. Adaptive adversarial network for source-free domain adaptation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9010–9019, 2021.

[35] Hongliang Yan, Yukang Ding, Peihua Li, Qilong Wang, Yong Xu, and Wangmeng Zuo. Mind the class weight bias: Weighted maximum mean discrepancy for unsupervised domain adaptation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2272–2281, 2017.

[36] Shiqi Yang, Yaxing Wang, Joost van de Weijer, Luis Herranz, and Shangling Jui. Generalized source-free domain adaptation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 8978–8987, 2021.

[37] Werner Zellinger, Thomas Grubinger, Edwin Lughofer, Thomas Natschläger, and Susanne Saminger-Platz. Central moment discrepancy (cmd) for domain-invariant representation learning. In *International Conference on Learning Representations*, 2016.

[38] Kaiyang Zhou, Ziwei Liu, Yu Qiao, Tao Xiang, and Chen Change Loy. Domain generalization: A survey. *arXiv e-prints*, pages arXiv–2103, 2021.

[39] Zhi-Hua Zhou. A brief introduction to weakly supervised learning. *National science review*, 5(1):44–53, 2018.