Geometry reveals an instructive role of retinal waves as biologically plausible pre-training signals

Editors: List of editors' names

Abstract

Prior to the onset of vision, neurons in the developing mammalian retina spontaneously fire in correlated activity patterns known as retinal waves. Experimental evidence suggests retinal waves strongly influence sensory representations before the visual experience. We aim to elucidate the computational role of retinal waves by using them as pre-training signals for neural networks. We consider simulated activity patterns generated by a model retina as well as real activity patterns observed experimentally in a developing mouse retina. We show that pre-training a classifier with a biologically plausible Hebbian learning rule on both simulated and real wave patterns improves the separability of the network's internal representations. In particular, the pre-trained networks achieve higher classification accuracy and exhibit internal representations with higher manifold capacity when compared to networks with randomly shuffled synaptic weights.

Keywords: retinal waves, development, vision, representation, geometry, manifold, classification, biologically plausible, pre-training

1. Introduction

How the brain learns to solve visual object recognition is still unknown. Evidence suggests that sensory representations of distinct objects in the early visual system are tangled together and gradually untangle as they are transformed and re-mapped in a feedforward manner along the ventral stream (DiCarlo et al., 2012). However, we do not know the precise mechanism by which the brain learns the appropriate sequence of mappings to sufficiently separate objects for recognition in higher visual areas.

Interestingly, many key aspects of visual function are well-established before the visual experience, such as topographic maps, orientation selectivity, and ocular dominance (Espinosa and Stryker, 2012), suggesting external stimuli are not necessary for the initial development of the visual system, and axon targeting can largely be learned by internally generated signals such as spontaneous neural activity and molecular guidance cues. Both have been implicated in establishing retinal axonal projections, though their relative importance is unknown (Feller and Kerschensteiner, 2020). Here, we focus on spontaneous activity in the form of retinal waves, correlated patterns of propagating, wave-like activity that occur in the absence of light responses among groups of retinal ganglion cells (RGCs) early in mammalian development (Arroyo and Feller, 2016). Experimental and computational evidence suggests that retinal waves instruct the formation of retinotopic maps, enabling RGC axons to reach their targets in the superior colliculus and lateral geniculate nucleus before the eyes even open (Cang et al., 2005; Chandrasekaran et al., 2005; Huberman et al., 2006; Markowitz et al., 2012; Hunt et al., 2012).

Our computational work predicts that the spatiotemporal properties of retinal waves can instruct synaptic projections to higher visual areas such that object representations

become more linearly separable. Using a simple feedforward network trained to classify MNIST digits (Raghavan and Thomson, 2019), we demonstrate that training the input layer weights on retinal wave patterns with a biologically plausible Hebbian learning rule prior to training the classifier layer on MNIST improves the linear separability of the network's internal representations as well as the classifier accuracy. To do this, we turn to the framework of manifold geometry, in which the collective response of neurons in the network to different presentations of a particular object comprises an "object manifold" (Chung and Abbott, 2021). In particular, we examine three metrics that describe the object manifold geometry — capacity, dimension, and radius (Chung et al., 2018) — and show that the object manifolds in the networks pre-trained with both simulated and experimentally obtained retinal wave patterns are more easily separable than those in control networks whose weights are random permutations of the pre-trained network weights. This suggests that the spatial structure learned from retinal waves (in the absence of the task data) is relevant for visual object recognition and implies an instructive role for retinal waves prior to the visual experience.

2. Results

Figure 1: Classification accuracy of SVM on network representations (n=3 per network). Error bars represent one standard deviation above/below the mean.

We consider feedforward networks consisting of an input layer, a linear layer with pre-trained weights (the receptive fields), an random (untrained) hidden linear layer, and a support vector machine (SVM) as the classifier/output layer (Section 4). Only the SVM layer is trained on the MNIST data, such that it learns to classify the network's internal representations of the digits. We present results for four networks: "Pre-trained (sim.)", a network with receptive fields pre-trained on simulated retinal waves, "Pre-trained (real)"; a network with receptive fields pre-trained on real retinal wave data (Appendix A); and "Scrambled (sim.)" and "Scrambled (real)", networks in which each receptive field is the

result of randomly permuting the pixels of its corresponding receptive field in "Pre-trained (sim.)" and "Pre-trained (real)", respectively. We find that classification accuracy is higher for pre-trained networks relative to their scrambled counterparts (Fig. 1).

Figure 2: Geometry of hidden layer representations for each MNIST digit manifold. Error bars represent one standard deviation above/below the mean.

We next analyze three manifold properties of the networks' internal representations: capacity, defined as the maximum number of manifolds that can be linearly separated using random binary labels divided by the dimension of the representation; dimension, the spread of anchor points (which define the optimal separating hyperplane between two perceptual manifolds) along the manifold axes; and radius, the variance of anchor points normalized by the average distance between manifold centers. The lower the dimension and radius of the object manifolds, the more linearly separable they are, yielding higher classification capacity and therefore higher accuracy (Chung et al., 2018). We show that the internal representations of pre-trained networks generally exhibit higher capacity, lower dimension, and lower radius relative to those of their scrambled counterparts (Fig. 2).

3. Discussion

Our results show that pre-training with both simulated and real retinal waves yields receptive fields with spatial structure favorable for separation and classification of object manifolds. Because we are comparing to scrambled networks, whose receptive fields share the same pixel distribution as the pre-trained networks but lack their spatial structure, these results suggest that learning the spatial structure in retinal wave patterns, as opposed to just the overall distribution, is relevant for object recognition. We note another trend that manifold dimension decreases from the input layer to the hidden layer for all networks while radius increases, suggesting that dimension as opposed to radius is the primary driver of the increase in capacity from the input layer to the hidden layer. Finally, we find that networks trained on simulated waves exhibit higher accuracy and more favorable manifold properties compared to networks trained on real retinal waves. We suspect this is because the real data contains considerably more noise and is less local in its spatial structure, which may lower performance on the relatively simple MNIST dataset. A more natural task, like classifying objects in natural images, may favor the network pre-trained on real waves.

4. Methods

The model architecture considered is a four layer feed-forward network consisting of a 3200-unit input layer of retinal ganglion cells randomly placed on a square grid, a 400-unit hidden layer, a 100-unit hidden layer, and a 1 unit classifier/output layer. Only the weights between the input layer and first hidden layer are pre-trained, following the procedure described in Raghavan and Thomson (2019), where simulated retinal waves are propagated across the input layer to train the weights (receptive fields) to the first hidden layer units by a winner-take-all Hebbian learning rule. The MNIST data is pre-processed by binarizing the pixel values and projecting them onto the input layer units. After pre-training, the network is trained by freezing the input and hidden layer weights as is, doing a forward pass of the projected MNIST data through the second hidden layer, and training the classifier layer, a support vector machine, on the 100-dimensional second hidden layer output representations of the data. Manifold analysis is done for the second hidden layer output representations of each digit class according to the procedure described in Chung et al. (2018). The code for pre-processing, pre-training, MNIST training, and manifold analysis is publicly available in Jupyter notebooks at https://github.com/ligeralde/wave_manifold.

References

David A. Arroyo and Marla B. Feller. Spatiotemporal Features of Retinal Waves Instruct the Wiring of the Visual Circuitry. *Frontiers in Neural Circuits*, 10:54, July 2016. ISSN 1662-5110. doi: 10.3389/fncir.2016.00054. URL https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4960261/.

Jianhua Cang, René C. Rentería, Megumi Kaneko, Xiaorong Liu, David R. Copenhagen, and Michael P. Stryker. Development of precise maps in visual cortex requires patterned spontaneous activity in the retina. *Neuron*, 48(5):797–809, December 2005. ISSN 0896-6273. doi: 10.1016/j.neuron.2005.09.015.

Anand R. Chandrasekaran, Daniel T. Plas, Ernesto Gonzalez, and Michael C. Crair. Evidence for an instructive role of retinal activity in retinotopic map refinement in the superior colliculus of the mouse. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, 25(29):6929–6938, July 2005. ISSN 1529-2401. doi: 10.1523/JNEUROSCI.1470-05.2005.

SueYeon Chung and L. F. Abbott. Neural population geometry: An approach for understanding biological and artificial neural networks. *Current Opinion in Neurobiology*, 70:137–144, October 2021. ISSN 09594388. doi: 10.1016/j.conb.2021.10.010. URL http://arxiv.org/abs/2104.07059. arXiv: 2104.07059.

SueYeon Chung, Daniel D. Lee, and Haim Sompolinsky. Classification and Geometry of General Perceptual Manifolds. *Physical Review X*, 8(3):031003, July 2018. ISSN 2160-3308. doi: 10.1103/PhysRevX.8.031003. URL https://link.aps.org/doi/10.1103/PhysRevX.8.031003.

James J. DiCarlo, Davide Zoccolan, and Nicole C. Rust. How Does the Brain Solve Visual Object Recognition? *Neuron*, 73(3):415–434, February 2012. ISSN 0896-6273. doi: 10.1016/j.neuron.2012.01.010. URL https://www.sciencedirect.com/science/article/pii/S089662731200092X.

J. Sebastian Espinosa and Michael P. Stryker. Development and Plasticity of the Primary Visual Cortex. *Neuron*, 75(2):230–249, July 2012. ISSN 08966273. doi: 10.1016/j.neuron.2012.06.009. URL https://linkinghub.elsevier.com/retrieve/pii/S0896627312005697.

M. B. Feller and D. Kerschensteiner. Chapter 16 - Retinal waves and their role in visual system development. In John Rubenstein, Pasko Rakic, Bin Chen, Kenneth Y. Kwan, Hollis T. Cline, and Jessica Cardin, editors, *Synapse Development and Maturation*, pages 367–382. Academic Press, January 2020. ISBN 978-0-12-823672-7. doi: 10.1016/B978-0-12-823672-7.00016-8. URL https://www.sciencedirect.com/science/article/pii/B9780128236727000168.

Peiran Gao, Eric Trautmann, Byron Yu, Gopal Santhanam, Stephen Ryu, Krishna Shenoy, and Surya Ganguli. A theory of multineuronal dimensionality, dynamics and measurement. preprint, Neuroscience, November 2017. URL http://biorxiv.org/lookup/doi/10.1101/214262.

Andrew D. Huberman, Colenso M. Speer, and Barbara Chapman. Spontaneous Retinal Activity Mediates Development of Ocular Dominance Columns and Binocular Receptive Fields in V1. *Neuron*, 52(2):247–254, October 2006. ISSN 0896-6273. doi: 10.1016/j. neuron.2006.07.028. URL https://www.cell.com/neuron/abstract/S0896-6273(06)00625-8. Publisher: Elsevier.

Jonathan J. Hunt, Michael Ibbotson, and Geoffrey J. Goodhill. Sparse Coding on the Spot: Spontaneous Retinal Waves Suffice for Orientation Selectivity. *Neural Computation*, 24 (9):2422–2433, September 2012. ISSN 0899-7667. doi: 10.1162/NECO_a_00333. URL https://doi.org/10.1162/NECO_a_00333.

Jeffrey Markowitz, Yongqiang Cao, and Stephen Grossberg. From Retinal Waves to Activity-Dependent Retinogeniculate Map Development. *PLOS ONE*, 7(2):e31553, February 2012. ISSN 1932-6203. doi: 10.1371/journal.pone.0031553. URL https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0031553. Publisher: Public Library of Science.

Guruprasad Raghavan and Matt Thomson. Neural networks grown and self-organized by noise, June 2019. URL http://arxiv.org/abs/1906.01039. Number: arXiv:1906.01039 arXiv:1906.01039 [nlin, q-bio].

Appendix A. In vitro retinal wave data preparation

Mice aged postnatal day 8-11 (P8-P11) were deeply anesthetized with isoflurane inhalation and euthanized by decapitation. Eyes were immediately enucleated and retinas were dissected at room temperature under infrared illumination in oxygenated (95% O_2/5% CO_2) artificial cerebrospinal fluid (ACSF) (in mM, 119 NaCl, 2.5 KCl, 1.3 $MgCl_2$, 1 K_2HPO_4, 26.2 $NaHCO_3$, 11 D-glucose, and 2.5 $CaCl_2$). Cuts along the chloride fissure were made prior to isolating the retina from the retinal pigmented epithelium. These cuts were made to precisely orient retinas. Isolated retinas were mounted whole on filter paper with the photoreceptor layer side down, and transferred in a recording chamber of a microscope for subsequent imaging. The whole-mount retinas were continuously perfused (3 mL/min) with oxygenated ACSF media at 32-34°C for the duration of the experiment. The retina from the other eye was kept in the dark at room temperature in ACSF media bubbled with 95% O_2, 5% CO_2 until use (maximum 8 h).

Retinas of C57B6 mice used for two-photon calcium imaging were mounted over white filter paper (Watman) and bolus loaded with either the green calcium dye Calbrtye 520 AM or the red calcium dye Calbryte 590 AM. Two-photon fluorescence measurements were obtained with a modified movable objective microscope (MOM) (Sutter instruments, Novator, CA) and made using a Nikon 16×, 0.80 NA, N16×LWD-PF objective (Nikon, Tokyo, Japan). Two-photon excitation of calcium dyes was evoked with an ultrafast pulsed laser (Chameleon Ultra II; Coherent, Santa Clara, CA) tuned to 920 nm for green dyes and GFP or 1040 nm for red dyes. The microscope system was controlled by ScanImage software (www.scanimage.org). Retinal waves were imaged with the field of view set to 850um×850um and the scan parameters were [pixels/line×lines/frame (frame rate in Hz)]:

[128×128 (5.92 Hz)], at 1 ms/line. The same field of view was imaged until at least 50 retinal waves had propagated through it for a total of 18,000 images.

To ensure a sufficient number of pre-training steps, the original set of 18,000 images was augmented by appending 3 rotations of the images to the data (90°, 180°, and 270°), for a total of 72,000 images. The images were then mean-pooled with a block size of 4, and the pixel intensities were projected onto the retina as binary values as described above in Section 4.

Appendix B. Receptive fields of pre-trained and shuffled networks

(*a*) Pre-trained   (*b*) Scrambled   (*c*) Pre-trained   (*d*) Scrambled
(sim. waves)   (sim. waves)   (real waves)   (real waves)

Figure 3: Receptive fields have spatial structure that resembles that of the retinal waves used in pre-training. Each scrambled receptive field is a random permutation of the pixels in the corresponding pre-trained receptive field.

Appendix C. Participation ratio of data and hidden layer representations

Participation ratio (PR) captures effective dimensionality, i.e., how the data variance is distributed along the principal axes of the data (Gao et al., 2017). The maximum value of PR is the number of features in the data, which signifies that there is equal variance in all principal axes. The minimum value is one, which signifies that all the variance is concentrated along one principal axis. We measure the PR for 100-dimensional Gaussian random projections of the MNIST data (as projected onto the model retina) and for each of the networks' hidden layer representation of the data and find that the pre-trained networks dramatically reduce the effective dimensionality of the data. The scrambled networks reduce the effective dimensionality even more, however given the lower performance and less favorable manifold properties Section 2, we suspect they reduce the dimensionality at the expense of meaningful sources of variance.

Figure 4: Participation ratio captures effective dimensionality. Error bars represent one standard deviation above/below the mean.