Minimax-Optimal Multi-Agent RL in Zero-Sum Markov Games With a Generative Model

Abstract

This paper is concerned with two-player zero-sum Markov games — arguably the most basic setting in multi-agent reinforcement learning — with the goal of learning a Nash equilibrium (NE) sample-optimally. All prior results suffer from at least one of the two obstacles: the curse of multiple agents and the barrier of long horizon, regardless of the sampling protocol in use. We take a first step towards settling this problem, assuming access to a flexible sampling mechanism: the generative model. Focusing on non-stationary finite-horizon Markov games, we develop a learning algorithm and an adaptive sampling scheme that leverage the optimism principle in adversarial learning (particularly the Follow-the-Regularized-Leader (FTRL) method), with a delicate design of bonus terms that ensure certain decomposability under the FTRL dynamics. Our algorithm learns an ε-approximate Markov NE policy using

$$\widetilde{O}\left(\frac{H^4 S(A+B)}{\varepsilon^2}\right)$$

samples, where S is the number of states, H is the horizon, and A (resp. B) is the number of actions for the max-player (resp. min-player). This is nearly unimprovable in a minimax sense. Along the way, we derive a refined regret bound for FTRL that makes explicit the role of variance-type quantities.

1 Introduction

The thriving field of multi-agent reinforcement learning (MARL) studies how a group of interacting agents make decisions autonomously in a shared dynamic environment [79]. The recent developments in game playing [65, 9], self-driving vehicles [57], and multi-robot control [46] are prime examples of MARL in action. In practice, there is no shortage of situations where the agents involved have conflict of interest, and they have to act competitively in order to promote their own benefits (possibly at the expense of one another). Scenarios of this kind are frequently modeled via Markov games (MGs) [58, 42], a framework that has been a fruitful playground to formalize and stimulate the studies of competitive MARL.

In view of the irreconcilable competition between individual players, solutions of competitive MARL normally take the form of certain equilibrium strategy profiles, which are perhaps best epitomized by the concept of Nash equilibrium (NE). In a Nash equilibrium, no gain can be realized through a unilateral change, and hence no player has incentives to deviate from her current strategy/policy (assuming no coordination between players). A myriad of research has been conducted surrounding NEs, which spans various aspects like existence, learnability, computational hardness, and algorithm design, among others [58, 19, 11, 52, 51, 21, 42, 27, 49, 32].

Sample efficiency in zero-sum Markov games. One critical challenge impacting modern MARL applications is data efficiency. The players involved often have minimal knowledge about how the environment responds to their actions, and have to learn the dynamics and preferable actions by probing the unknown environment. For MARL to expand into applications with enormous dimensionality and long planning horizon, the learning algorithms must manage to make efficient use of the collected data.

Nevertheless, how to learn NEs with optimal sample complexity remains by and large unsettled, even when it comes to the most basic setting — two-player zero-sum Markov games. In what follows, let us review two representative algorithms developed on this front under two drastically different sampling protocols, and discuss the shortfalls of these cutting-edge results. To facilitate precise comparisons, our discussion concentrates on zero-sum Markov games involving two players, where S is the number of states, H indicates the horizon or effective horizon, and A and B denote respectively the number of actions for the max-player and the min-player.

- *Model-based methods under either a generative model or online exploration.* Assuming access to a generative model (so that one can sample arbitrary state-action combinations), Zhang et al. [78] investigated a natural model-based algorithm, which performs planning (e.g., value iteration) on an empirical MG derived from samples produced by the generative model. Focusing on *stationary* discounted infinite-horizon MGs, their algorithm finds an ε-approximate NE with no more than

$$\widetilde{O}\left(\frac{H^3 SAB}{\varepsilon^2}\right) \text{ samples.} \tag{1}$$

  In parallel, Liu et al. [43] studied *non-stationary* finite-horizon MGs with online exploration, and obtained similar sample complexity bounds, i.e.,

$$\widetilde{O}\left(\frac{H^4 SAB}{\varepsilon^2}\right) \text{ samples} \qquad \text{or} \qquad \widetilde{O}\left(\frac{H^3 SAB}{\varepsilon^2}\right) \text{ episodes} \tag{2}$$

  for learning ε-approximate NEs. While these bounds achieve minimax-optimal dependency on the horizon H, a major drawback emerges commonly referred to as the curse of multiple agents; namely, these results scale proportionally with the total number of *joint actions* (i.e., AB), a quantity that blows up exponentially with the number of players.

- *V-learning for online exploration settings.* Focusing on online exploration settings, Bai et al. [5], Jin et al. [30] proposed an algorithm called V-learning that leverages the advances in online adversarial learning (e.g., adversarial bandits) to circumvent the curse of multiple agents. This algorithm provably yields an ε-approximate NE in non-stationary finite-horizon MGs using

$$\widetilde{O}\left(\frac{H^6 S(A+B)}{\varepsilon^2}\right) \text{ samples} \qquad \text{or} \qquad \widetilde{O}\left(\frac{H^5 S(A+B)}{\varepsilon^2}\right) \text{ episodes,} \tag{3}$$

  which effectively brings down the sample size scaling (2) from AB (i.e., the number of joint actions) to $A + B$ (i.e., the sum of individual actions). It is worth pointing out, however, that this theory appears sub-optimal in terms of the horizon dependency, as it is a factor of H^2 above the minimax lower bound.

The above results represent the most advanced sample complexity theory thus far for learning NEs in two-player zero-sum MGs. In summary, these state-of-the-art results — irrespective of the sampling mechanism in use — fall short of overcoming at least one of the two major hurdles: (i) the *curse of multiple agents*, and (ii) the *barrier of long horizon*. A natural question to pose is:

> **Question:** *can we learn Nash equilibria in a two-player zero-sum Markov game in a sample-optimal and computation-efficient fashion?*

To settle this question favorably, both of the above-mentioned hurdles need to be crossed simultaneously.

Main contributions. Recognizing that the above question remains open regardless of the sampling scheme in use, this paper takes a first step towards solving it assuming access to the most flexible sampling protocol: the generative model (or simulator). In sharp contrast to the single-agent

case where uniform sampling of all state-action pairs suffices [2, 37], the multi-agent scenario requires one to take samples intelligently and adaptively, a crucial step to avoid inefficient use of data (otherwise one cannot hope to break the curse of multiple agents). With the aim of computing an ε-approximate NE in a *non-stationary* finite-horizon two-player zero-sum MG, we come up with a learning algorithm (accompanied by an adaptive sampling strategy) that accomplishes this goal with no more than

$$\widetilde{O}\left(\frac{H^4 S(A+B)}{\varepsilon^2}\right) \text{ samples} \tag{4}$$

drawn from the generative model. Encouragingly, this sample complexity bound matches the minimax lower limit (up to a logarithmic factor). Our sample complexity theory is valid for the full ε-range (i.e., any $\varepsilon \in (0, H]$); this unveils that no burn-in cost whatsoever is needed for our algorithm to achieve sample optimality, which lends itself well to sample-hungry applications.

The proposed algorithm is inspired by two key algorithmic ideas in RL and bandit literature: (1) optimism in the face of uncertainty (by leveraging upper confidence bounds (UCBs) in value estimation), and (2) online and adversarial learning (particularly the Follow-the-Regularized-Leader (FTRL) algorithm). Note that the optimal design of bonus terms — typically based on certain data-driven variance estimates — is substantially more challenging than the single-agent case, as it requires intricate adaptation in response to the policy changes of one another as well as compatibility with the FTRL dynamics. Two points are worth emphasizing (which will be made precise later on):

- The efficacy of FTRL in breaking the curse of multiple agents has been proved in Jin et al. [30], Song et al. [62]. To improve horizon dependency, one needs to exploit connections between the performance of FTRL and certain variances. Towards this, we develop a refined regret bound for FTRL that unveils the role of variance-style quantities, which was previously unavailable.

- The bonus terms entail Bernstein-style variance estimates that mimic the variance-style quantities appearing in our refined FTRL regret bounds, and are carefully chosen so as to ensure certain decomposability over steps. This is crucial in optimizing the horizon dependency.

Additionally, the policy returned by our algorithm is Markovian (i.e., the action selection probability depends only on the current state s and step h), and the algorithm can be carried out in a decentralized manner without the need of directly observing the opponent's actions.

Notation. Let us gather several convenient notation that will be used multiple times. For any positive integer n, we set $[n] \coloneqq \{1, \cdots, n\}$. We shall abuse notation and let 1 and 0 denote the all-one vector and the all-zero vector, respectively. For a sequence $\{\alpha_k\}_{k \geq 1} \subseteq (0, 1]$, we define

$$\alpha_i^k \coloneqq \begin{cases} \alpha_i \prod_{j=i+1}^{k}(1 - \alpha_j), & \text{if } 0 < i < k \\ \alpha_k, & \text{if } i = k \end{cases} \tag{5}$$

for any $1 \leq i \leq k$. For a given vector $x \in \mathbb{R}^{SA}$ (resp. $y \in \mathbb{R}^{SAB}$), we denote by $x(s, a)$ (resp. $y(s, a, b)$) the entry of x (resp. y) associated with the state-action combination (s, a) (resp. (s, a, b)), as long as it is clear from the context.

Next, consider any two vectors $a = [a_i]_{1 \leq i \leq n}$ and $b = [b_i]_{1 \leq i \leq n}$. We use $a \leq b$ (resp. $a \geq b$) to indicate that $a_i \geq b_i$ (resp. $a_i \leq b_i$) holds for all i; we allow scalar functions to take vector-valued arguments in order to denote entrywise operations (e.g., $a^2 = [a_i^2]_{1 \leq i \leq n}$ and $a^4 = [a_i^4]_{1 \leq i \leq n}$); and we denote by $a \circ b = [a_i b_i]_{1 \leq i \leq n}$ the Hadamard product. For a finite set $\mathcal{A} = \{1, \cdots, A\}$, we denote by $\Delta(\mathcal{A}) = \{x \in \mathbb{R}^A \mid \sum_i x_i = 1; x \geq 0\}$ the probability simplex over $\mathcal{A}$. For any function f with domain $\mathcal{A}$ (or $\mathcal{B}$), we adopt the convenient notation

$$\mathbb{E}_\pi[f] \coloneqq \sum\nolimits_a \pi(a)f(a) \qquad \text{and} \qquad \mathsf{Var}_\pi(f) \coloneqq \sum\nolimits_a \pi(a)\big(f(a) - \mathbb{E}_\pi[f]\big)^2. \tag{6}$$

2 Background and models

In this section, we introduce the basics for two-player zero-sum Markov games and the solution concept of Nash equilibrum.

Two-player Markov games. A non-stationary finite-horizon two-player Markov game, denoted by $\mathcal{MG} = \{\mathcal{S}, \mathcal{A}, \mathcal{B}, H, P, r\}$, involves two players competing against each other — with the first one called a "max-player" and the second one called a "min-player" — and consists of several key elements to be formalized below. To begin with, we denote by $\mathcal{S} = \{1, \cdots, S\}$ a shared state space comprising S different states, and let $\mathcal{A} = \{1, \cdots, A\}$ (resp. $\mathcal{B} = \{1, \cdots, B\}$) represent the action space of the max-player (resp. min-player) containing A (resp. B) different actions. The horizon length of this finite-horizon Markov game is denoted by H. The probability transition kernel of $\mathcal{MG}$ is denoted by $P = \{P_h\}_{1 \le h \le H}$ with $P_h \in \mathbb{R}^{SAB \times S}$; namely, for any $(s, a, b, h, s') \in \mathcal{S} \times \mathcal{A} \times \mathcal{B} \times [H] \times \mathcal{S}$, we let $P_h(s' \,|\, s, a, b)$ indicate the probability of $\mathcal{MG}$ transitioning from state s to state s' at step h when the max-player takes action a and the min-player takes action b. Additionally, $r = \{r_h\}_{1 \le h \le H}$ with $r_h \in \mathbb{R}^{SAB}$ represents the reward function; namely, for any $(s, a, b, h) \in \mathcal{S} \times \mathcal{A} \times \mathcal{B} \times [H]$, $r_h(s, a, b)$ stands for the immediate reward gained in state s at step h if the max-player (resp. min-player) executes action a (resp. b). Given that our focal point is the family of zero-sum Markov games, it suffices to introduce a single reward function r. We shall also assume normalized rewards throughout this paper in the sense that $r_h(s, a, b) \in [0, 1]$ for any $(s, a, b, h) \in \mathcal{S} \times \mathcal{A} \times \mathcal{B} \times [H]$.

Value functions under product policies. Let $\mu = \{\mu_h\}_{1 \le h \le H}$ (resp. $\nu = \{\nu_h\}_{1 \le h \le H}$) denote the policy of the max-player (resp. min-player), where $\mu_h(\cdot \,|\, s) \in \Delta(\mathcal{A})$ and $\nu_h(\cdot \,|\, s) \in \Delta(\mathcal{B})$ for any $s \in \mathcal{S}$. More specifically, $\mu_h(a \,|\, s)$ indicates the probability of the max-player selecting action a in state s at step h; and $\nu_h(b \,|\, s)$ is defined analogously. Consider a Markovian trajectory $\{(s_t, a_t, b_t, r_t)\}_{1 \le t \le H}$, where s_t is the state at time t, a_t (resp. b_t) is the action of the max-player (resp. min-player) at time t, and r_t is the immediate reward observed at time t. For any given policy μ (resp. ν) of the max-player (resp. min-player) and any step h, we define the value function $V_h^{\mu,\nu} : \mathcal{S} \to \mathbb{R}$ under the product policy $\mu \times \nu$ as follows:

$$V_h^{\mu,\nu}(s) \coloneqq \mathbb{E}\left[\sum_{t=h}^{H} r_t(s_t, a_t, b_t) \mid s_h = s \right], \qquad \forall s \in \mathcal{S}, \tag{7}$$

where the expectation is taken over the Markovian trajectory $\{(s_t, a_t, b_t, r_t)\}$ with the max-player and the min-player executing policies μ and ν, respectively, in an independent fashion; that is, conditional on s_t, we draw $a_t \sim \mu_t(\cdot \,|\, s_t)$ and $b_t \sim \nu_t(\cdot \,|\, s_t)$ *independently*, and then $s_{t+1} \sim P_t(\cdot \,|\, s_t, a_t, b_t)$. In addition, conditional on the min-player executing policy ν, the optimal value function $V^{\star,\nu} = \{V_h^{\star,\nu}\}_{1 \le h \le H}$ (with $V_h^{\star,\nu} : \mathcal{S} \to \mathbb{R}$) of the max-player is defined as

$$V_h^{\star,\nu}(s) \coloneqq \max_{\mu: \mathcal{S} \times [H] \to \Delta(\mathcal{A})} V_h^{\mu,\nu}(s), \qquad \forall (s, h) \in \mathcal{S} \times [H]; \tag{8a}$$

similarly, when the max-player chooses to execute policy μ, the optimal value function $V^{\mu,\star} = \{V_h^{\mu,\star}\}_{1 \le h \le H}$ (with $V_h^{\mu,\star} : \mathcal{S} \to \mathbb{R}$) of the min-player is defined as

$$V_h^{\mu,\star}(s) \coloneqq \min_{\nu: \mathcal{S} \times [H] \to \Delta(\mathcal{B})} V_h^{\mu,\nu}(s), \qquad \forall (s, h) \in \mathcal{S} \times [H]. \tag{8b}$$

Furthermore, if we freeze the policy of the min-player to ν, then the Bellman optimality condition for the max-player can be expressed as [8]

$$V_h^{\star,\nu}(s) = \max_{a \in \mathcal{A}} \left\{ \mathbb{E}_{b \sim \nu_h(\cdot|s)} \left[r_h(s, a, b) + \left\langle P_h(\cdot \,|\, s, a, b), V_{h+1}^{\star,\nu} \right\rangle \right] \right\}, \qquad \forall (s, h) \in \mathcal{S} \times [H]. \tag{9}$$

Solution concept: Nash equilibrium. In the zero-sum two-player Markov game, the max-player wishes to maximize the value function, while the min-player aims to minimize the value function instead. Due to the competing objectives, finding some sort of equilibrium — particularly the Nash equilibrium [48] — becomes a central topic in the studies of Markov games. More precisely, a policy pair $(\mu^\star, \nu^\star) \in \Delta(\mathcal{A})^{SH} \times \Delta(\mathcal{B})^{SH}$ is said to be a *(mixed-strategy) Nash equilibrium* of $\mathcal{MG}$ if the resulting product policy $\mu^\star \times \nu^\star$ obeys

$$V_1^{\mu^\star,\nu^\star}(s) = V_1^{\star,\nu^\star}(s) \quad \text{and} \quad V_1^{\mu^\star,\nu^\star}(s) = V_1^{\mu^\star,\star}(s), \qquad \text{for all } s \in \mathcal{S}. \tag{10}$$

In other words, conditional on the opponent's current policy and the assumption that the two players take actions *independently*, no player can harvest any gain by unilaterally deviating from its current policy.

In practice, it might be challenging to compute an "exact" Nash equilibrium, and instead one would seek to find approximate solutions. Towards this end, we find it helpful to define the sub-optimality gap of a policy pair (μ, ν) as follows (measured in an ℓ_∞-based manner)

$$\mathsf{NE\text{-}gap}(\mu, \nu) := \max_{s \in \mathcal{S}} \mathsf{NE\text{-}gap}(\mu, \nu; s), \tag{11a}$$

where

$$\mathsf{NE\text{-}gap}(\mu, \nu; s) := \max \left\{ V_1^{\star, \nu}(s) - V_1^{\mu, \nu}(s), \, V_1^{\mu, \nu}(s) - V_1^{\mu, \star}(s) \right\}. \tag{11b}$$

With this sub-optimality measure in place, a policy pair (μ, ν) is said to be an ε-approximate Nash-equilibrium — or more concisely, ε-Nash — if the resultant sub-optimality gap of the product policy $\mu \times \nu$ obeys $\mathsf{NE\text{-}gap}(\mu, \nu) \leq \varepsilon$.

Generative model / simulator. In reality, we oftentimes do not have access to perfect descriptions (e.g., accurate knowledge of the transition kernel P) of the Markov game under consideration; instead, one has to learn the true model on the basis of a set of data samples. When it comes to the data generating mechanism, this paper assumes access to a generative model (also called a simulator) [34, 33]: in each call to the generative model, the learner can choose an arbitrary quadruple $(s, a, b, h) \in \mathcal{S} \times \mathcal{A} \times \mathcal{B} \times [H]$ and obtain an independent sample generated based on the true transition kernel:

$$s' \sim P_h(\cdot \mid s, a, b).$$

In words, a generative model facilitates query of arbitrary state-action-step combinations, which helps alleviate the sampling constraints arising in online episodic settings for exploration. The goal of the current paper is to compute an ε-approximate Nash equilibrium of $\mathcal{MG}$ with as few samples as possible, i.e., using a minimal number of calls to the generative model.

3 Algorithm and main theory

In this section, we put forward an algorithm aimed at finding an ε-Nash policy pair with the assistance of a generative model, and demonstrate its sample optimality for the full ε-range.

3.1 Algorithm

We now describe the proposed algorithm, which is inspired by the optimism principle and the FTRL algorithm for online/adversarial learning. Following the dynamic programming approach [8], our algorithm employs backward recursion from step $h = H$ back to $h = 1$; in fact, we shall finish estimating the values and policies for step h before moving backward to step $h - 1$. For each h, the max-player (resp. min-player) calls the generative model for K rounds, with each round drawing SA (resp. SB) independent samples; as a result, the total sample size is given by $KS(A + B)H$. In what follows, let us first introduce some convenient notation that facilitates our presentation of the algorithm.

Notation. Consider any step $h \in [H]$, and any data collection round $k \in [K]$. The algorithm maintains the following iterates, whose notation is gathered here.

- $\overline{V}_h \in \mathbb{R}^S$ (resp. $\underline{V}_h \in \mathbb{R}^S$) represents the final estimate of the value function at step h by the max-player (resp. min-player); in particular, we set $\overline{V}_{H+1} = \underline{V}_{H+1} = 0$.

- $\overline{Q}_h^k \in \mathbb{R}^{SA}$ (resp. $\underline{Q}_h^k \in \mathbb{R}^{SB}$) represents the Q-function estimate of the max-player (resp. min-player) at step h after the k-th round of data collection.

- $\overline{q}_h^k \in \mathbb{R}^{SA}$ (resp. $\underline{q}_h^k \in \mathbb{R}^{SB}$) represents a certain "one-step-look-ahead" Q-function estimate of the max-player (resp. min-player) at step h using samples collected in the k-th round.

- $\overline{r}_h^k \in \mathbb{R}^{SA}$ (resp. $\underline{r}_h^k \in \mathbb{R}^{SB}$) denotes the sample reward vector for step h received by the max-player (resp. min-player) in the k-th round.

- $\overline{P}_h^k \in \mathbb{R}^{SA \times S}$ (resp. $\underline{P}_h^k \in \mathbb{R}^{SB \times S}$) denotes the empirical probability transition matrix for step h constructed using the samples collected by the max-player (resp. min-player) in the k-th round.

190 • $\overline{\beta}_{h,V} \in \mathbb{R}^S$ (resp. $\underline{\beta}_{h,V} \in \mathbb{R}^S$) denotes the bonus (resp. penalty) vector chosen by the max-player
191 (resp. min-player) during final value estimation.

192 • $\mu_h^k : \mathcal{S} \to \Delta(\mathcal{A})$ (resp. $\nu_h^k : \mathcal{S} \to \Delta(\mathcal{B})$) denotes the policy iterate of the max-player (resp. min-
193 player) at step h before the beginning of the k-th round of data collection; in particular, we set both
194 μ_h^1 and ν_h^1 to be uniform, namely, $\mu_h^1(a\,|\,s) = 1/A$ for any $(s,a) \in \mathcal{S} \times \mathcal{A}$ and $\nu_h^1(b\,|\,s) = 1/B$
195 for any $(s,b) \in \mathcal{S} \times \mathcal{B}$.

196 Crucially, the above objects are all constructed from the perspective of a single player (either the
197 max-player or the min-player), and are all quantities needed to opearte a "single-agent" MDP (as
198 opposed to MARL). As such, the complexity of storing/updating the above objects only scales with
199 the aggregate size of the individual action space, rather than the size of the product action space.

200 **Main steps of the proposed algorithm.** As mentioned above, our algorithm collects multiple
201 rounds of independent samples for each h. Let us describe below the proposed procedure for the
202 max-player in the k-th round for step h; the procedure for the min-player proceeds analogously.

203 1. *Sampling and model estimation.* For each $(s,a) \in \mathcal{S} \times \mathcal{A}$, draw an *independent* sample as follows
204

$$b_{k,h,s,a} \sim \nu_h^k(\cdot\,|\,s), \qquad s'_{k,h,s,a} \sim P_h(\cdot\,|\,s,a,b_{k,h,s,a}) \tag{12a}$$

205 and receive the reward $r_{k,h,s,a} = r_h\big(s,a,b_{k,h,s,a}\big)$. These samples are then employed to construct
206 the sample reward vector $\overline{r}_h^k \in \mathbb{R}^{SA}$ and empirical probability transition kernel $\overline{P}_h^k \in \mathbb{R}^{SA \times S}$
207 such that

$$\overline{r}_h^k(s,a) = r_{k,h,s,a} \qquad \text{and} \qquad \overline{P}_h^k(s'\,|\,s,a) = \begin{cases} 1, & \text{if } s' = s'_{k,h,s,a} \\ 0, & \text{else} \end{cases} \tag{12b}$$

208 for all $(s,a,s') \in \mathcal{S} \times \mathcal{A} \times \mathcal{S}$. Note that the max-player only needs to compute (12b), without the
209 need of directly observing the opponent's actions (i.e., $\{b_{k,h,s,a}\}$).

210 2. *Q-function estimation.* Following the dynamic programming approach, we first compute the "one-
211 step-look-ahead" Q-function estimate as follows

$$\overline{q}_h^k = \overline{r}_h^k + \overline{P}_h^k \overline{V}_{h+1}. \tag{13}$$

212 We then adopt the update rule of Q-learning:

$$\overline{Q}_h^k = (1 - \alpha_k)\overline{Q}_h^{k-1} + \alpha_k \overline{q}_h^k, \tag{14}$$

213 where $0 < \alpha_k < 1$ is the learning rate. Applying (14) recursively and using the quantities defined
214 in (5), we easily arrive at the following expansion:

$$\overline{Q}_h^k = \sum_{i=1}^k \alpha_i^k \overline{q}_h^i. \tag{15}$$

215 3. *Policy updates.* Once the Q-estimates are updated, we adopt the exponential weights strategy to
216 update the policy iterate of the max-player as follows

$$\mu_h^{k+1}(a\,|\,s) = \frac{\exp\big(\eta_{k+1}\overline{Q}_h^k(s,a)\big)}{\sum_{a' \in \mathcal{A}} \exp\big(\eta_{k+1}\overline{Q}_h^k(s,a')\big)}, \qquad \forall (s,a) \in \mathcal{S} \times \mathcal{A}, \tag{16}$$

217 where $\eta_{k+1} > 0$ denotes another learning rate associated with policy updates for the max-player
218 (to be specified shortly). In fact, this subroutine implements the Follow-the-Regularized-Leader
219 update rule [55]

$$\mu_h^{k+1}(\cdot\,|\,s) = \arg\min_{\pi \in \Delta(\mathcal{A})} \left\{ -\big\langle \pi, \overline{Q}_h^k(s,\cdot) \big\rangle + \frac{1}{\eta_{k+1}} F(\pi) \right\} \tag{17}$$

220 with the regularizer $F(\cdot)$ chosen to be the negative entropy function $F(\pi) := \sum_a \pi(a) \log\big(\pi(a)\big)$.

After carrying out K rounds of the above procedure, our final policy estimate $\widehat{\mu} \in \Delta(\mathcal{A})^{SH}$ and the value estimate $\overline{V}_h : \mathcal{S} \to \mathbb{R}$ for step h are taken respectively to be

$$\widehat{\mu}_h = \sum_{k=1}^{K} \alpha_k^K \mu_h^k \qquad \text{and} \tag{18a}$$

$$\overline{V}_h(s) = \min\left\{ \sum_{k=1}^{K} \alpha_k^K \left\langle \mu_h^k(\cdot \mid s), \overline{q}_h^k(s, \cdot) \right\rangle + \overline{\beta}_{h,V}(s),\ H - h + 1 \right\} \tag{18b}$$

with $\{\alpha_k^K\}$ defined in (5), where $\overline{\beta}_{h,V}(s) \geq 0$ is some bonus term (taking the form of some data-driven upper confidence bound) to be specified momentarily. In particular, the final policy (18a) is a mixture of the policy iterates $\{\mu_h^k\}$ and is Markovian in nature (i.e., the action selection rule depends only on the current state s and step h).

The whole procedure, including the algorithm for the min-player, is summarized in Algorithm 1.

Choices of learning rates. Thus far, we have not yet specified the two sequences of learning rates, which we describe now. The learning rates associated with Q-function updates are set to be rescaled linear, namely,

$$\alpha_k = \frac{c_\alpha \log K}{k - 1 + c_\alpha \log K}, \qquad k = 1, 2, \dots \tag{19}$$

for some absolute constant $c_\alpha \geq 24$. In addition, the learning rates associated with policy updates are chosen to be:

$$\eta_{k+1} = \sqrt{\frac{\log K}{\alpha_k H}}, \qquad k = 1, 2, \dots \tag{20}$$

Choices of bonus terms. It remains to specify the bonus terms, which are selected based on fairly intricate upper confidence bounds and constitutes a key (and perhaps most challenging) component of our algorithm design. Specifically, we take

$$\overline{\beta}_{h,V}(s) = c_{\mathsf{b}} \sqrt{\frac{\log^3 \frac{KS(A+B)}{\delta}}{KH}} \sum_{k=1}^{K} \alpha_k^K \left\{ \mathsf{Var}_{\mu_h^k(\cdot \mid s)}\left(\overline{q}_h^k(s, \cdot)\right) + H \right\} \tag{21}$$

for any $(s, h) \in \mathcal{S} \times [H]$, where $c_{\mathsf{b}} > 0$ is some sufficiently large constant; see also (6) for the definition of the variance-style term. As in previous works, the bonus term, which is chosen carefully in a data-driven fashion, needs to compensate for the uncertainty incurred during the estimation process.

3.2 Main results

As it turns out, the proposed algorithm is provably sample-efficient, whose sample complexity is characterized by the following theorem.

Theorem 1. *Consider any $\varepsilon \in (0, H]$ and any $0 < \delta < 1$. Suppose that*

$$K \geq \frac{c_{\mathsf{k}} H^3 \log^4 \frac{KS(A+B)}{\delta}}{\varepsilon^2} \tag{24}$$

for some large enough universal constant $c_{\mathsf{k}} > 0$. With probability at least $1 - \delta$, the sub-optimality gap (cf. (11)) of the policies $(\widehat{\mu}, \widehat{\nu})$ returned by Algorithm 1 obeys

$$\mathsf{NE\text{-}gap}(\widehat{\mu}, \widehat{\nu}) \leq \varepsilon. \tag{25}$$

Theorem 1 establishes a sample complexity upper bound for the proposed algorithm, which we take a moment to interpret as follows.

Algorithm 1: Nash-Q-FTRL.

---

1 **Input:** number of rounds K for each step, learning rates $\{\alpha_k\}$ (see (19)) and $\{\eta_{k+1}\}$ (see (20)).

// set initial value estimates to 0, and initial policies to uniform distributions.

2 **Initialize:** for all $(s, a, b, h) \in \mathcal{S} \times \mathcal{A} \times \mathcal{B} \times [H]$, set
$\overline{V}_{H+1}(s) = \underline{V}_{H+1}(s) = \overline{Q}_h^0(s, a) = \underline{Q}_h^0(s, b) = 0$, $\mu_h^1(a \mid s) = 1/A$ and $\nu_h^1(b \mid s) = 1/B$.

3 **for** $h = H$ **to** 1 **do**

4   **for** $k = 1$ **to** K **do**

      // draw independent samples, and construct empirical models.

5 $\big(\overline{r}_h^k, \underline{r}_h^k, \overline{P}_h^k, \underline{P}_h^k\big) \leftarrow$ `sampling`$\big(h, \mu_h^k, \nu_h^k\big)$.   /* see Algorithm 2.   */

      // update Q-estimates with upper/lower confidence bounds.

6   Compute $\overline{q}_h^k = \overline{r}_h^k + \overline{P}_h^k \overline{V}_{h+1}$, $\underline{q}_h^k = \underline{r}_h^k + \underline{P}_h^k \underline{V}_{h+1}$, and update

$$\overline{Q}_h^k = (1 - \alpha_k)\overline{Q}_h^{k-1} + \alpha_k \overline{q}_h^k, \quad \underline{Q}_h^k = (1 - \alpha_k)\underline{Q}_h^{k-1} + \alpha_k \underline{q}_h^k.$$

8   // update policy estimates using FTRL.

7   **for** $(s, a, b) \in \mathcal{S} \times \mathcal{A} \times \mathcal{B}$ **do**

9 $\mu_h^{k+1}(a \mid s) = \dfrac{\exp\big(\eta_{k+1}\overline{Q}_h^k(s, a)\big)}{\sum_{a'}\exp\big(\eta_{k+1}\overline{Q}_h^k(s, a')\big)}$, $\nu_h^{k+1}(b \mid s) = \dfrac{\exp\big(-\eta_{k+1}\underline{Q}_h^k(s, b)\big)}{\sum_{b'}\exp\big(-\eta_{k+1}\underline{Q}_h^k(s, b')\big)}.$

   // output the final policy estimate and value estimate for step h.

10   Update

$$\widehat{\mu}_h = \sum_{k=1}^{K}\alpha_k^K \mu_h^k, \quad \overline{V}_h(s) = \min\left\{\sum_{k=1}^{K}\alpha_k^K\big\langle\mu_h^k(\cdot \mid s), \overline{q}_h^k(s, \cdot)\big\rangle + \overline{\beta}_{h,V}(s), \ H - h + 1\right\}, \ \forall s \in \mathcal{S},$$

$$\widehat{\nu}_h = \sum_{k=1}^{K}\alpha_k^K \nu_h^k, \quad \underline{V}_h(s) = \max\left\{\sum_{k=1}^{K}\alpha_k^K\big\langle\mu_h^k(\cdot \mid s), \underline{q}_h^k(s, \cdot)\big\rangle - \underline{\beta}_{h,V}(s), \ 0\right\}, \ \forall s \in \mathcal{S},$$

11   where $\overline{\beta}_{h,V}^k$ is given in (21), and $\underline{\beta}_{h,V}^k$ is obtained by replacing $(\mu_h^k, \overline{q}_h^k)$ in (21) with $(\nu_h^k, \underline{q}_h^k)$.

12 **Output:** $\widehat{\mu} = \{\widehat{\mu}_h\}_{1 \leq h \leq H}$ and $\widehat{\nu} = \{\widehat{\nu}_h\}_{1 \leq h \leq H}$.

Algorithm 2: Auxiliary function `sampling`$\big(h, \mu_h, \nu_h\big)$.

---

1 **Initialize:** $\overline{r} = 0 \in \mathbb{R}^{SA}$, $\underline{r} = 0 \in \mathbb{R}^{SB}$, $\overline{P} = 0 \in \mathbb{R}^{SA \times S}$, and $\underline{P} = 0 \in \mathbb{R}^{SB \times S}$.

2 **for** $(s, a) \in \mathcal{S} \times \mathcal{A}$ **do**

3   Draw an independent sample from the generative model:

$$b_{h,s,a} \sim \nu_h(\cdot \mid s), \qquad s'_{h,s,a} \sim P_h(\cdot \mid s, a, b_{h,s,a}). \tag{22}$$

4   set $\overline{r}(s, a) = r_h\big(s, a, b_{h,s,a}\big)$ and $\overline{P}\big(s'_{h,s,a} \mid s, a\big) = 1$.

5 **for** $(s, b) \in \mathcal{S} \times \mathcal{B}$ **do**

6   Draw an independent sample from the generative model:

$$a_{h,s,b} \sim \mu_h(\cdot \mid s), \qquad s'_{h,s,a} \sim P_h(\cdot \mid s, a_{h,s,b}, b). \tag{23}$$

7   set $\underline{r}(s, b) = r_h\big(s, a_{h,s,b}, b\big)$ and $\underline{P}\big(s'_{h,s,a} \mid s, b\big) = 1$.

8 **Return:** $\big(\overline{r}, \underline{r}, \overline{P}, \underline{P}\big)$.

Sample complexity. When a generative model is available, Theorem 1 asserts that the total number of samples (i.e., $KS(A + B)H$) needed for Algorithm 1 to yield ε-Nash policies is at most

$$\text{(sample complexity)} \qquad \widetilde{O}\left(\frac{H^4 S(A + B)}{\varepsilon^2}\right). \tag{26}$$

As far as we know, this delivers the first result — for any sampling protocol — that simultaneously overcomes the long-horizon barrier and the curse of multiple agents. In comparison to Zhang et al. [78] (cf. (1)), our result reveals that what ultimately matters is the total number of individual actions (i.e., $A + B$) as opposed to the total number AB of possible joint actions. Additionally, our result exhibits improved horizon dependency (by a factor of H^2) compared to Bai et al. [5], Jin et al. [30] (see (3)), although we should emphasize that the online sampling protocol therein is more restrictive than a generative model.

Minimax optimality. In order to assess the tightness of our sample complexity bound (26), it is helpful to look at the minimax lower limit. Suppose without loss of generality that $A \geq B$. Consider the extreme scenario where $B = 1$, in which case the Nash-equilibrium reduces to the optimal policy of a single-agent MDP with S states and A actions. It is well-known that for any given accuracy level $\varepsilon \in (0, H]$, one can construct a non-stationary MDP with S states and A actions such that no algorithm can learn an ε-optimal policy with fewer than the order of $\frac{H^4 S A}{\varepsilon^2}$ samples [2, 41]. This means that in general, the minimax sample complexity lower bound (w.r.t. finding an ε-Nash policy pair) scales as

$$\text{(minimax lower bound)} \qquad \frac{H^4 S (A + B)}{\varepsilon^2} \qquad (27)$$

modulo some logarithmic factor; see Appendix G for a formal statement and its proof. Taking this together with (26) confirms the minimax optimality of our algorithm (up to logarithmic terms).

No burn-in sample size and full ε-range. It is noteworthy that the validity of our sample complexity bound (26) is guaranteed for the entire range of ε-levels (i.e., any $\varepsilon \in (0, H]$). This feature is particularly appealing in the data-starved applications, as it implies that there is no burn-in sample size needed for our algorithm to work optimally.

Miscellaneous properties of our algorithm. Finally, we remark in passing that our learning algorithm enjoys several properties that might be practically appealing. For instance, the algorithm can be carried out in a decentralized fashion, with two players acting in a symmetric and independent manner (without the need of knowing each other's individual action); the algorithm is "rational" in the sense that it converges to the best-response policy if one of the players freezes its policy; and the output policies are inherently Markovian, which depend only on the current state and step number. All this is achieved under minimal sample complexity with the aid of the generative model.

4 Discussion

The primary contribution of this paper has been to develop a sample-optimal paradigm that simultaneously overcomes the curse of multiple agents and optimizes the horizon dependency when solving two-player zero-sum Markov games. This goal was not accomplished in any of the previous works, regardless of the sampling mechanism in use. The adoption of the adversarial learning subroutine helps break the curse of multiple agents compared to the prior model-based approach [78, 43], whereas the availability of the generative model in conjunction with the delicate bonus design enables sharpened horizon dependency compared to Bai et al. [5], Jin et al. [30]. Our work opens further questions surrounding sample efficiency in solving Markov games. For instance, how to attain minimax-optimal sample complexity if we only have access to less idealistic sampling protocol (e.g., local access models [39, 75], and online sampling protocols [3, 29]) as opposed to the flexible generative model? How can we optimize the horizon dependency when computing (coarse) correlated equilibria in multi-agent general-sum scenarios [62, 30, 22] without compromising the dependency on the size of the action spaces. In addition, our refined regret bound for FTRL (based on variance-type quantities) only covers the full-information case; it would be of interest to generalize it to the bandit-feedback setting (where only partial entries of the loss vectors are observable).

References

[1] A. Agarwal, S. Kakade, and L. F. Yang. Model-based reinforcement learning with a generative model is minimax optimal. In *Conference on Learning Theory*, pages 67–83. PMLR, 2020.

[2] M. G. Azar, R. Munos, and H. J. Kappen. Minimax PAC bounds on the sample complexity of reinforcement learning with a generative model. *Machine learning*, 91(3):325–349, 2013.

[3] M. G. Azar, I. Osband, and R. Munos. Minimax regret bounds for reinforcement learning. In *Proceedings of the 34th International Conference on Machine Learning*, pages 263–272. JMLR. org, 2017.

[4] Y. Bai and C. Jin. Provable self-play algorithms for competitive reinforcement learning. In *International Conference on Machine Learning*, pages 551–560. PMLR, 2020.

[5] Y. Bai, C. Jin, and T. Yu. Near-optimal reinforcement learning with self-play. *Advances in neural information processing systems*, 33:2159–2170, 2020.

[6] A. Beck. *First-order methods in optimization*. SIAM, 2017.

[7] C. L. Beck and R. Srikant. Error bounds for constant step-size Q-learning. *Systems & control letters*, 61(12):1203–1208, 2012.

[8] D. P. Bertsekas. *Dynamic programming and optimal control (4th edition)*. Athena Scientific, 2017.

[9] N. Brown and T. Sandholm. Superhuman AI for multiplayer poker. *Science*, 365(6456):885–890, 2019.

[10] S. Cen, Y. Wei, and Y. Chi. Fast policy extragradient methods for competitive games with entropy regularization. *Advances in Neural Information Processing Systems*, 34, 2021.

[11] X. Chen, Y. Cheng, and B. Tang. Well-supported versus approximate Nash equilibria: Query complexity of large games. *arXiv preprint arXiv:1511.00785*, 2015.

[12] Z. Chen, S. T. Maguluri, S. Shakkottai, and K. Shanmugam. Finite-sample analysis of stochastic approximation using smooth convex envelopes. *arXiv preprint arXiv:2002.00874*, 2020.

[13] Z. Chen, S. Ma, and Y. Zhou. Sample efficient stochastic policy extragradient algorithm for zero-sum Markov game. In *International Conference on Learning Representations*, 2021.

[14] Z. Chen, D. Zhou, and Q. Gu. Almost optimal algorithms for two-player Markov games with linear function approximation. *arXiv preprint arXiv:2102.07404*, 2021.

[15] Z. Chen, D. Zhou, and Q. Gu. Almost optimal algorithms for two-player zero-sum linear mixture Markov games. In *International Conference on Algorithmic Learning Theory*, pages 227–261. PMLR, 2022.

[16] Q. Cui and S. S. Du. When is offline two-player zero-sum Markov game solvable? *arXiv preprint arXiv:2201.03522*, 2022.

[17] Q. Cui and S. S. Du. Provably efficient offline multi-agent reinforcement learning via strategy-wise bonus. *arXiv preprint arXiv:2206.00159*, 2022.

[18] Q. Cui and L. F. Yang. Minimax sample complexity for turn-based stochastic game. In *Uncertainty in Artificial Intelligence*, pages 1496–1504. PMLR, 2021.

[19] C. Daskalakis. On the complexity of approximating a nash equilibrium. *ACM Transactions on Algorithms (TALG)*, 9(3):1–35, 2013.

[20] C. Daskalakis, P. W. Goldberg, and C. H. Papadimitriou. The complexity of computing a Nash equilibrium. *SIAM Journal on Computing*, 39(1):195–259, 2009.

[21] C. Daskalakis, D. J. Foster, and N. Golowich. Independent policy gradient methods for competitive reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 33, pages 5527–5540, 2020.

[22] C. Daskalakis, N. Golowich, and K. Zhang. The complexity of markov equilibrium in stochastic games. *arXiv preprint arXiv:2204.03991*, 2022.

[23] Z. Dou, Z. Yang, Z. Wang, and S. Du. Gap-dependent bounds for two-player markov games. In *International Conference on Artificial Intelligence and Statistics*, pages 432–455, 2022.

[24] S. S. Du, S. M. Kakade, R. Wang, and L. F. Yang. Is a good representation sufficient for sample efficient reinforcement learning? In *International Conference on Learning Representations*, 2020.

[25] E. Even-Dar and Y. Mansour. Learning rates for Q-learning. *Journal of machine learning Research*, 5(Dec):1–25, 2003.

[26] D. A. Freedman. On tail probabilities for martingales. *the Annals of Probability*, pages 100–118, 1975.

[27] T. D. Hansen, P. B. Miltersen, and U. Zwick. Strategy iteration is strongly polynomial for 2-player turn-based stochastic games with a constant discount factor. *Journal of the ACM (JACM)*, 60(1):1–16, 2013.

[28] Z. Jia, L. F. Yang, and M. Wang. Feature-based q-learning for two-player stochastic games. *arXiv preprint arXiv:1906.00423*, 2019.

[29] C. Jin, Z. Allen-Zhu, S. Bubeck, and M. I. Jordan. Is Q-learning provably efficient? In *Advances in Neural Information Processing Systems*, pages 4863–4873, 2018.

[30] C. Jin, Q. Liu, Y. Wang, and T. Yu. V-learning–a simple, efficient, decentralized algorithm for multiagent RL. *arXiv preprint arXiv:2110.14555*, 2021.

[31] Y. Jin and A. Sidford. Towards tight bounds on the sample complexity of average-reward MDPs. In *International Conference on Machine Learning*, pages 5055–5064. PMLR, 2021.

[32] Y. Jin, V. Muthukumar, and A. Sidford. The complexity of infinite-horizon general-sum stochastic games. *arXiv preprint arXiv:2204.04186*, 2022.

[33] S. Kakade. *On the sample complexity of reinforcement learning*. PhD thesis, University of London, 2003.

[34] M. Kearns, Y. Mansour, and A. Y. Ng. A sparse sampling algorithm for near-optimal planning in large Markov decision processes. *Machine learning*, 49(2-3):193–208, 2002.

[35] K. Khamaru, A. Pananjady, F. Ruan, M. J. Wainwright, and M. I. Jordan. Is temporal difference learning optimal? an instance-dependent analysis. *SIAM Journal on Mathematics of Data Science*, 3(4):1013–1040, 2021.

[36] T. Lattimore and C. Szepesvári. *Bandit algorithms*. Cambridge University Press, 2020.

[37] G. Li, Y. Wei, Y. Chi, Y. Gu, and Y. Chen. Breaking the sample size barrier in model-based reinforcement learning with a generative model. In *Advances in Neural Information Processing Systems*, volume 33, 2020.

[38] G. Li, C. Cai, Y. Chen, Y. Gu, Y. Wei, and Y. Chi. Is Q-learning minimax optimal? a tight sample complexity analysis. *arXiv preprint arXiv:2102.06548*, 2021.

[39] G. Li, Y. Chen, Y. Chi, Y. Gu, and Y. Wei. Sample-efficient reinforcement learning is feasible for linearly realizable MDPs with limited revisiting. *Advances in Neural Information Processing Systems*, 34:16671–16685, 2021.

[40] G. Li, L. Shi, Y. Chen, Y. Gu, and Y. Chi. Breaking the sample complexity barrier to regret-optimal model-free reinforcement learning. *Advances in Neural Information Processing Systems*, 34, 2021.

[41] G. Li, L. Shi, Y. Chen, Y. Chi, and Y. Wei. Settling the sample complexity of model-based offline reinforcement learning. *arXiv preprint arXiv:2204.05275*, 2022.

[42] M. L. Littman. Markov games as a framework for multi-agent reinforcement learning. In *Machine learning proceedings 1994*, pages 157–163. Elsevier, 1994.

[43] Q. Liu, T. Yu, Y. Bai, and C. Jin. A sharp analysis of model-based reinforcement learning with self-play. In *International Conference on Machine Learning*, pages 7001–7010. PMLR, 2021.

[44] Q. Liu, C. Szepesvári, and C. Jin. Sample-efficient reinforcement learning of partially observable markov games. *arXiv preprint arXiv:2206.01315*, 2022.

[45] W. Mao and T. Başar. Provably efficient reinforcement learning in decentralized general-sum Markov games. *Dynamic Games and Applications*, pages 1–22, 2022.

[46] L. Matignon, L. Jeanpierre, and A.-I. Mouaddib. Coordinated multi-robot exploration under communication constraints using decentralized markov decision processes. In *Twenty-sixth AAAI conference on artificial intelligence*, 2012.

[47] W. Mou, C. J. Li, M. J. Wainwright, P. L. Bartlett, and M. I. Jordan. On linear stochastic approximation: Fine-grained Polyak-Ruppert and non-asymptotic concentration. *arXiv preprint arXiv:2004.04719*, 2020.

[48] J. Nash. Non-cooperative games. *Annals of mathematics*, pages 286–295, 1951.

[49] A. Ozdaglar, M. O. Sayin, and K. Zhang. Independent learning in stochastic games. *arXiv preprint arXiv:2111.11743*, 2021.

[50] A. Pananjady and M. J. Wainwright. Instance-dependent ℓ_∞-bounds for policy evaluation in tabular reinforcement learning. *IEEE Transactions on Information Theory*, 67(1):566–585, 2020.

[51] J. Perolat, B. Scherrer, B. Piot, and O. Pietquin. Approximate dynamic programming for two-player zero-sum Markov games. In *International Conference on Machine Learning*, pages 1321–1329. PMLR, 2015.

[52] A. Rubinstein. Settling the complexity of computing approximate two-player nash equilibria. In *Annual Symposium on Foundations of Computer Science (FOCS)*, pages 258–265, 2016.

[53] M. Sayin, K. Zhang, D. Leslie, T. Basar, and A. Ozdaglar. Decentralized Q-learning in zero-sum Markov games. *Advances in Neural Information Processing Systems*, 34, 2021.

[54] S. Shalev-Shwartz. Online learning: Theory, algorithms, and applications. 2007.

[55] S. Shalev-Shwartz. Online learning and online convex optimization. *Foundations and Trends® in Machine Learning*, 4(2):107–194, 2012.

[56] S. Shalev-Shwartz and Y. Singer. A primal-dual perspective of online learning algorithms. *Machine Learning*, 69(2):115–142, 2007.

[57] S. Shalev-Shwartz, S. Shammah, and A. Shashua. Safe, multi-agent, reinforcement learning for autonomous driving. *arXiv preprint arXiv:1610.03295*, 2016.

[58] L. S. Shapley. Stochastic games. *Proceedings of the national academy of sciences*, 39(10): 1095–1100, 1953.

[59] A. Sidford, M. Wang, X. Wu, L. Yang, and Y. Ye. Near-optimal time and sample complexities for solving Markov decision processes with a generative model. In *Advances in Neural Information Processing Systems*, pages 5186–5196, 2018.

[60] A. Sidford, M. Wang, X. Wu, and Y. Ye. Variance reduced value iteration and faster algorithms for solving Markov decision processes. In *Symposium on Discrete Algorithms*, pages 770–787. SIAM, 2018.

[61] A. Sidford, M. Wang, L. Yang, and Y. Ye. Solving discounted stochastic two-player games with near-optimal time and sample complexity. In *International Conference on Artificial Intelligence and Statistics*, pages 2992–3002. PMLR, 2020.

[62] Z. Song, S. Mei, and Y. Bai. When can we learn general-sum Markov games with a large number of players sample-efficiently? *arXiv preprint arXiv:2110.04184*, 2021.

[63] Y. Tian, Y. Wang, T. Yu, and S. Sra. Online learning in unknown markov games. In *International conference on machine learning*, pages 10279–10288. PMLR, 2021.

[64] S. Vaswani, L. F. Yang, and C. Szepesvári. Near-optimal sample complexity bounds for constrained MDPs. *arXiv preprint arXiv:2206.06270*, 2022.

[65] O. Vinyals, I. Babuschkin, W. M. Czarnecki, M. Mathieu, A. Dudzik, J. Chung, D. H. Choi, R. Powell, T. Ewalds, and P. Georgiev. Grandmaster level in Starcraft II using multi-agent reinforcement learning. *Nature*, 575(7782):350–354, 2019.

[66] M. J. Wainwright. Stochastic approximation with cone-contractive operators: Sharp ℓ_∞-bounds for Q-learning. *arXiv preprint arXiv:1905.06265*, 2019.

[67] M. J. Wainwright. Variance-reduced Q-learning is minimax optimal. *arXiv preprint arXiv:1906.04697*, 2019.

[68] B. Wang, Y. Yan, and J. Fan. Sample-efficient reinforcement learning for linearly-parameterized mdps with a generative model. *Advances in Neural Information Processing Systems*, 34, 2021.

[69] C.-Y. Wei, Y.-T. Hong, and C.-J. Lu. Online reinforcement learning in stochastic games. *Advances in Neural Information Processing Systems*, 30, 2017.

[70] C.-Y. Wei, C.-W. Lee, M. Zhang, and H. Luo. Last-iterate convergence of decentralized optimistic gradient descent/ascent in infinite-horizon competitive Markov games. In *Conference on Learning Theory*, pages 4259–4299. PMLR, 2021.

[71] G. Weisz, P. Amortila, and C. Szepesvári. Exponential lower bounds for planning in MDPs with linearly-realizable optimal action-value functions. In *Algorithmic Learning Theory*, pages 1237–1264. PMLR, 2021.

[72] Q. Xie, Y. Chen, Z. Wang, and Z. Yang. Learning zero-sum simultaneous-move Markov games using function approximation and correlated equilibrium. In *Conference on Learning Theory*, pages 3674–3682. PMLR, 2020.

[73] Y. Yan, G. Li, Y. Chen, and J. Fan. Model-based reinforcement learning is minimax-optimal for offline zero-sum markov games. *arXiv preprint arXiv:2206.04044*, 2022.

[74] L. Yang and M. Wang. Sample-optimal parametric Q-learning using linearly additive features. In *International Conference on Machine Learning*, pages 6995–7004, 2019.

[75] D. Yin, B. Hao, Y. Abbasi-Yadkori, N. Lazić, and C. Szepesvári. Efficient local planning with linear function approximation. In *International Conference on Algorithmic Learning Theory*, pages 1165–1192. PMLR, 2022.

[76] A. Zanette, M. J. Kochenderfer, and E. Brunskill. Almost horizon-free structure-aware best policy identification with a generative model. *Advances in Neural Information Processing Systems*, 32, 2019.

[77] A. Zanette, A. Lazaric, M. J. Kochenderfer, and E. Brunskill. Provably efficient reward-agnostic navigation with linear value iteration. *Advances in Neural Information Processing Systems*, 33:11756–11766, 2020.

[78] K. Zhang, S. Kakade, T. Basar, and L. Yang. Model-based multi-agent RL in zero-sum Markov games with near-optimal sample complexity. *Advances in Neural Information Processing Systems*, 33, 2020.

[79] K. Zhang, Z. Yang, and T. Başar. Multi-agent reinforcement learning: A selective overview of theories and algorithms. *Handbook of Reinforcement Learning and Control*, pages 321–384, 2021.

[80] R. Zhang, Q. Liu, H. Wang, C. Xiong, N. Li, and Y. Bai. Policy optimization for Markov games: Unified framework and faster convergence. *arXiv preprint arXiv:2206.02640*, 2022.

[81] Y. Zhao, Y. Tian, J. D. Lee, and S. S. Du. Provably efficient policy gradient methods for two-player zero-sum Markov games. *arXiv preprint arXiv:2102.08903*, 2021.

[82] H. Zhong, W. Xiong, J. Tan, L. Wang, T. Zhang, Z. Wang, and Z. Yang. Pessimistic minimax value iteration: Provably efficient equilibrium learning from offline datasets. *arXiv preprint arXiv:2202.07511*, 2022.