Parallelised Diffeomorphic Sampling-based Motion Planning

Abstract: We propose Parallelised Diffeomorphic Sampling-based Motion Planning (PDMP). PDMP is a novel parallelised framework that uses bijective and differentiable mappings, or *diffeomorphisms*, to transform sampling distributions of sampling-based motion planners, in a manner akin to normalising flows. Unlike normalising flow models which use invertible neural network structures to represent these diffeomorphisms, we develop them from gradient information of desired costs, and encode desirable behaviour, such as obstacle avoidance. These transformed sampling distributions can then be used for sampling-based motion planning. A particular example is when we wish to imbue the sampling distribution with knowledge of the environment geometry, such that drawn samples are less prone to be in collision. To this end, we propose to learn a continuous occupancy representation from environment occupancy data, such that gradients of the representation defines a valid diffeomorphism and is amenable to fast parallelise evaluation. We use this to "morph" the sampling distribution to draw far less collision-prone samples. PDMP is able to leverage gradient information of costs, to inject specifications, in a manner similar to optimisation-based motion planning methods, but relies on drawing from a sampling distribution, retaining the tendency to find more global solutions, thereby bridging the gap between trajectory optimisation and sampling-based planning methods.

Keywords: Sampling-based motion planning, diffeomorphism, flows, Sampling distribution, RRT, PRM

1 Introduction

This paper addresses the problem of motion planning, and bridges together two motion planning paradigms: *trajectory optimisation approaches* and *sampling-based approaches*. Trajectory optimisation views robot trajectories as solutions of an optimisation problem. The optimisation problem typically incorporates the environment occupancy, along with additionally specified requirements into a cost function. Gradients of the cost function are often assumed to be accessible, allowing for its efficient optimisation. However, trajectory optimisation approaches are known to suffer from local minima, and are generally not *anytime*. On the other hand, sampling-based planners have a complementary set of benefits. Sampling-based planners are probabilistically complete, and are able to quickly find a feasible solution and improve upon it. However, unlike trajectory optimisation approaches, sampling-based planners are unable to utilise gradient information, either from environment occupancy or from user specification.

We propose a novel motion planning framework, Parallelised Diffeomorphic Sampling-based Motion Planning (PDMP), which combines the benefits of both sampling-based and trajectory optimisation methods. PDMP is capable of finding globally optimal solutions, while benefiting from gradient information of cost functions to speed up motion planning. In broad strokes, our method leverages gradient information from specified cost functions, which can be learned from environment data or user specified, to construct differentiable bijections, or *diffeomophisms*. Like normalising flows, PDMP uses diffeomorphisms to shape a simple base sampling distribution into a sampling distribution that is more informative. However, to learn invertible transformations for normalising flows,

Submitted to the 5th Conference on Robot Learning (CoRL 2021). Do not distribute.

one typically assumes that samples from a desired target distribution are accessible. This is typically not the case when learning sampling distributions: generally, we are given information about the occupancy in the environment, as well as designed costs, rather than samples from a "good" sampling distribution. We demonstrate that with relatively mild assumptions, we can obtain diffeomorphisms, from provided cost functions, that allows us to deform the sampling distribution. We provide a specific example of learning a diffeomorphism that conforms to environment occupancy.

The "morphing" of sampling distributions allows sampling-based planners, such as Rapidly-exploring Random Trees (RRTs) and its variants, to more efficiently create connections, speeding-up the planning process. Additionally, the transformation of the sampling distribution can be viewed as a parallel process, while building the expanding trees is an inherently sequential process. We integrate CPU and GPU parallelism: we use GPUs to shape the sampling distribution, which can be processed in parallel, while simultaneously using the CPU to build the expanding tree, which is a sequential process.

Concretely, our contributions are as follows:

1. We propose a method of shaping sampling distributions of sampling-based planners, such that gradient information, for example from environment occupancy gradient or user specified information can be incorporated, allowing for faster motion planning;

2. We provide an efficient implementation of our method integrated into an RRT motion-planner which leverages the parallel capabilities of GPUs. We demonstrate that the shaping of the sampling distribution can be done efficiently in parallel in a GPU, simultaneously with the sequential tree-building process resulting in no additional time cost.

We empirically evaluate PDMP on challenging planning scenarios, and find that it is able to consistently find solutions faster than existing sampling-based motion planners.

2 Related Works

Sampling-based Motion Planning: Sampling-based planners are of a class of predominant methods to compute motion trajectories among roboticists. It poses the motion planning problem as in a probabilistic settings, where the construction of motion plans are formulated as a graph or tree building procedure. Probabilistic Roadmap (PRM) [1] was first proposed to creates a random roadmap of connectivity in the configuration space to avoid the curse of dimensionality. On the other hand, Rapidly-exploring Random Tree (RRT) [2] follows a similar idea but uses tree structures to obtaining solution quicker. Since sampling is one of the core component in sampling-based motion planners, there are a lot of methods that tries to improve the sampling distribution. For example, formulating a restricted distribution to improve planning time [3, 4]. There are also method to learn the sampling distribution from experience using neural network methods [5, 6, 7]. However, most learning-based methods learns a skewed distribution based purely from a subset of successful motion plans configurations, which requires a mixture with uniform distribution to maintain the *probabilistic completeness* guarantee [8].

Gradient-based Cost Optimisation in Motion Planning: Outside of sampling-based motion planner, many other paradigms of motion planning make use of gradient information of some defined cost function. Trajectory optimisation approaches, such as CHOMP [9], STOMP[10] and TrajOpt [11], and potential field approaches [12] are prominent examples of this. These approaches find a single solution by descending in the direction of lower cost, guided by the negative gradient. Likewise, our approach transform a distribution such that samples have lower cost by descending based on negative gradients.

Diffeomorphisms and Normalising Flows: The transforming of distributions via invertible and differentiable mappings is known as *normalising flows* [13]. These invertible and differentiable mappings are known as "flows" [13, 14] or more generally as "diffeomorphisms" [15, 16]. Normalising flows are typically learned using invertible structures [17, 14, 18], with data drawn from the desired target distribution. We take a different approach, and develop invertible mappings from cost gradients, which can be hand specified or learned from other sources of data, such as occupancy information (outlined in section 3).

3 Parallelised Diffeomorphic Sampling-based Motion Planning

We shall detail the proposed Parallelised Diffeomorphic Sampling-based Motion Planning (PDMP) framework. In section 3.1, we begin by introducing neural network representations of occupancy, which allows for fast batched querying of coordinates via the GPU. This occupancy representation will be used to construct diffeomorphisms which transforms a sampling distribution, such that samples have lower likelihood of being in occupied space. Details on constructing this diffeomorphism, along with those from an arbitrary cost function, are elaborated in section 3.2. Finally, in section 3.3, we expand on how we can leverage both the GPU, for the highly parallelisable tranformation of samples, and the CPU, for the inherently sequential tree-building process, to achieve improved performance with the same time budget, for tree-building sampling-based motion planning methods.

3.1 Learning Continuous Occupancy Representations with Neural Networks

Occupancy in an environment have traditionally been represented by occupancy grid maps, which discretise the world into grid-cells and compute occupancy independently for each cell. Recent advancements in machine learning have brought continuous analogues of occupancy maps [19], and continuous distance-based methods [20]. Here we present a straightforward approach of learning the occupancy via a neural network, which is fast to query, fast to obtain derivatives with respect to inputs, and inherently parallelised. These properties are beneficial for querying of large batches of coordinates.

Figure 1: An example of a continuous occupancy representation learned by a neural network. We lay out grid points, and show those predicted to be occupied, with occupancy probability given by colour.

We are assumed to have a dataset of n pairs, containing coordinates and a binary value, which indicates whether the coordinate is occupied, i.e. $\mathcal{D} = \{(\mathbf{x}_i, y_i)\}_{i=1}^{n}$, where $y_i \in \{0, 1\}$ for $i = 1, \ldots, n$. A dataset of this format can be obtained from depth sensors. Our aim is now to learn a mapping f_{map} between a coordinate of interest $\mathbf{x}$ and the probability of being occupied at $\mathbf{x}$, $f_{map}(\mathbf{x}) = p(\mathbf{y} = 1|\mathbf{x})$. We shall model f_{map} is a fully-connected neural network, with $tanh$ activation functions between hidden layers, and a $sigmoid$ activation layer at the output. The resulting setup is a binary classification problem, which can be learned via a binary cross entropy loss with gradient descent optimisers. Derivatives of the neural network can be obtained efficiently, via batched computation on a GPU.

3.2 Cost-informed Diffeomorphisms for Sampling Distributions

In this section we elaborate on building differentiable bijections, or diffeomorphisms, to transform a base distribution such that the "morphed" target distribution density is concentrated at where a provided cost function is low. That is, samples from the target distribution are more likely than the base distribution to be sampled from regions with low cost. Diffeomorphisms ensure that the transformed sampling distribution will have the same topology as the base distribution. For example, if the base distribution has infinite support, then the transformed sampling distribution also has infinite support, and will not have "holes" where there is no probability density.

Constructing Diffeomorphisms via integral curves: Diffeomorphisms can be generated by taking integral curves on the vector field defined by the negative gradients of the cost function. We consider a n-dimensional state vector $\mathbf{y} \in \mathbb{R}^n$ to be an initial time, provided a cost $f_c : \mathbb{R}^n \to \mathbb{R}$, an integral curve for some time $t \in \mathbb{R}$, can be written as an initial value problem (IVP):

$$\phi(\mathbf{y}) := \mathbf{y} - \int_0^t \nabla_{\mathbf{y}(s)} f_c(\mathbf{y}(s)) \mathrm{d}s = \mathbf{z}, \qquad\qquad \mathbf{y}(0) = \mathbf{y}, \qquad\qquad (1)$$

where $\mathbf{z} \in \mathbb{R}^n$ is the resulting By the Picard–Lindelöf theorem [21] (existence and uniqueness of IVPs), which states that if $\nabla_{\mathbf{y}(s)} f_c$ is Lipschitz continuous with respect to $\mathbf{y}(s)$, then the solution

of the IVP exists and is unique. We shall restrict our discussion to cost functions with Lipschitz derivatives, this includes the continuous occupancy representations introduced in section 3.1. Then, $\phi(\mathbf{y})$ is a diffeomorphism, and the inverse is given by:

$$\phi^{-1}(\mathbf{z}) := \mathbf{z} + \int_0^t \nabla_{\mathbf{z}(s)} f_c(\mathbf{z}(s)) \mathrm{d}\mathbf{s} = \mathbf{y}, \qquad\qquad \mathbf{z}(0) = \mathbf{z}. \qquad (2)$$

Therefore, we can use numerical integration techniques, such as Euler's method, to solve the IVP to evaluate the diffeomorphism efficiently.

Bringing Diffeomorphisms in Configuration Space: Motion-planning in robotics typically requires plans to be made in the *configuration space* (C-space) of the robot. On the other hand, costs to shape robot behaviour can be, and is often, defined in the Cartesian task space. For example, collision checking requires information about the task space geometry of the robot to determine whether it overlaps with objects in the environment. We assume that the sampling distribution is defined in the C-space of the robot, and diffeomorphisms need to operate in the C-space. We shall in particular discuss robot manipulators, where the states its C-space are joint angles. We denote the C-space as $\mathcal{Q} \in \mathbb{R}^n$, where there are n joints. Joint configurations, $\mathbf{q} \in \mathcal{Q}$, are elements of the C-space, while Cartesian coordinates in task space are denoted as $\mathbf{x} \in \mathbb{R}^3$. We outline how to *pull* a cost gradients defined in the task space to the C-space, and construct a diffeomorphism there.

We start by defining b body points on the robot, each with a kinematics function mapping configurations to the Cartesian coordinates at the body point, $\psi_i : \mathcal{Q} \to \mathbb{R}^3$, for each $i = 1, \ldots, b$. We take an operational space approach, and make use of the Jacobian of the kinematics functions with respect to the controls. The Jacobian of the i^{th} kinematics function is denoted as $J_\psi^i(\cdot) = \frac{\mathrm{d}\psi_i}{\mathrm{d}\mathbf{q}}(\cdot)$. A cost potential f_c which operates on the body points, such as the occupancy cost potential discussed above, can be *pulled* into the C-space:

$$\nabla_{\mathbf{q}} f_c = \sum_{i=1}^b J_\psi^i(\mathbf{q}) \nabla_{\mathbf{x}} f_c, \qquad\qquad (3)$$

we can then define a diffeomorphism, via solving the IVP as in (1), in the C-space of the robot.

Drawing Samples from the Morphed Target Distribution: We can draw samples from the morphed distribution by drawing samples from the known base distribution, then passing the points through the diffeomorphism ϕ. Unlike normalising flows for density estimation, which are computationally burdened by having to compute the determinant of the Jacobian of ϕ, we only require the mapping of sampled points, which can be done efficiently, and does not require the the Jacobian of ϕ. Furthermore, we note that morphing the sampled points from the base distribution to the transformed distribution can be done in parallel if the cost gradients can be parallelised. In particular, occupancy gradients as introduced in section 3.1 can be batch computed on a GPU efficiently. In the following sections, we shall elaborate on how to exploit the parallel nature of the morphing sampled points.

3.3 Parallelised Diffeomorphic Transform of Sampling Distribution

Rapidly-exploring random trees (RRTs), its variants, along with its graph-based counter parts are some of the most widely-used motion planning algorithms. In this section, we develop the Parallelised Diffeomorphic Sampling-based Motion Planning (PDMP) algorithm to transform the sampling distribution while constructing trees, efficiently integrating CPU and GPU parallelism. We elaborate on the *diffeomorphic sampler*, which can be largely parallelised, and the *motion planner main thread*, which consists of sequential operations. An overview flow-diagram is shown in Fig. 2.

Motion Planner Main Thread Building random trees is inherently a sequential process – sampling a random configuration, searching for nearest neighbour in the k-d tree, collision-checking of potential tree edges, connecting the candidate node , and rewiring of other existing nodes. This process requires knowledge of nodes that are currently connected by the tree, and valid nodes are connected to the tree as soon as they are found. Such a sequential process is repeated within a loop until the time budget exhausted. We will denote this sequential process as the *Motion Planner* because most of the works are to be done within the same thread. Similar to existing methods, we conduct the tree-building on the CPU. However, we proceed with optimising the sampled points in background threads that are parallelised in GPUs.

When the planning request is first received, the *main thread* spawns a background *boostrap thread* that prepares all necessary house keeping works such as constructing a concurrent queue S. Then, the *main thread* will proceed with the rest of the typical tree-building procedures, following the traditional RRT-variant literature. The main modification in this sequenital process lies in the sampling step. Typically, RRT samples from some distribution (e.g. uniform distribution $q_{\text{rand}} \sim \mathcal{U}(0,1)$) within the same thread. Instead, in our PDMP framework we draw samples from the previously constructed concurrent queue S, which is one of the only communication contacts in between the *main thread* and the *diffeomorphic sampler thread*, to avoid any other synchronisation overhead (the other communication happens when the *main thread* requests the background *diffeomorphic sampler* to exits due to time budget being exhausted). This concurrent bucket is filled by our *diffeomorphic sampler thread*. In the event the planner attempts to draw from an empty bucket, sample points are immediately drawn from a simple prior distribution $\mathbf{q} \sim \mathcal{Q}_{prior}$, reverting back to a standard sampling-based planner. Therefore, the main thread does not need to do a blocking-wait on the background thread; which implies that, in the rare event of degraded GPUs performance, PDMP will only be reverting back to the typical planner performance.

Diffeomorphic Sampler The diffeomorphic sampler leverages parallelism on the GPU to provide more informed samples. When the *bootstrap thread* is created, it first spawns multiple background threads that are equal to the target computer's parallelisation power (e.g. the number of CPUs or hyper-threads). Each background thread is in-charge of generating sample points from the morphed distribution in a mini-batch fashion. In contrast to CPUs, we can use the GPU to sample a large batch from a prior distribution. These backgroud threads within *diffeomorphic sampler* in Fig. 2 will also collects the necessary kinematic Jacobians into batches for forward pass in

Figure 2: Flow diagram of the parallelised operations in PDMP.

the GPUs. The batch of samples is then passed through the diffeomorphism to obtain the informed samples. The pass through the diffeomoprhism can be done efficiently when leveraging the parallel computing capabilities of the GPUs, if the gradients of the cost potential can be done in batch. This is often the case if the cost gradients can be expressed analytically. This is particularly the case, if given by the derivative of a neural network.

4 Experimental Results

We empirically analyse our proposed Parallel Diffeomorphic Sampling-based Motion Planning (PDMP) method. In the following sections, we investigate: (i) the performance of finding valid motion plans, with gradients from a cost potential occupancy representations, under time constraints; (ii) the effect of combining multiple cost potentials. For our simulated environments, we construct two challenging environments (illustrated in Fig. 5) (a) *Divider:* this environment consists of a large divider on a cluttered table, the starting position and goal are on the different sides of the divider; (b) this environment consists of a cupboard, the start and end goals are in different shelves of this cupboard.

4.1 Higher Success Rates with Informed Sampling Distributions

We hypothesise that after morphing our sampling distribution with a cost potential from our continuous occupancy representation, we can significantly improve the performance of sampling-based planning strategies. We investigate using RRTs [2], RRT-connect [22], and Lazy-PRM* [23] as the motion planner in the main thread of PDMP, and compare the effect of morphing the sampling distribution provided by our approach.

We provide a time-budget of 20 seconds for each planner, and calculate the percentage of tries, over 30 runs, that result in a successful plan, at different times until the budget of 20s was used up. The results are illustrated in Fig. 4. We see that for each of the three sampling-based planning methods, incorporation within the PDMP framework to morph the sampling distribution improves the success rate. This is the most evident when using RRTs within PDMP, since it allows us to produce more successful samples which in-turns speed up the tree-building process.

We replicate the divider environment (Fig. 5c) in the real-world, with a 6-DOF JACO manipulator included, the planning is shown by video in the supplementary materials.

In the *divider* environment, we see that the success rate of PDMP-RRT reaches 80% at around 7 seconds of planning, and almost has a perfect success rate by the end of the 20s budget. On the other hand, vanilla RRT with uniform sampling distribution has a success rate of under 50% when the time budget is used up. The same trends are observed with the other variants. Overall, the bi-directional RRT-connect within PDMP and with a uniform sampling distribution outperform the other variants. Even still, when using RRT-connect within the PDMP, we observe higher success rates when the planning time is low (under 3 seconds), indicating that PDMP improves the finding of solutions significantly.

In the more challenging *cupboard* environment, we see similar trends. Our PDMP framework provides clear imporvements to the success rates of both the RRT and RRT-connect methods. Additionally, we observe that at the end of the 20s time budget, PDMP variants outperform their counterparts which sample from an uninformed sampling distribution. Lazy-PRM* both within our PDMP framework and with an uninformative distribution cannot complete the planning task.

4.2 Influence of CPU-GPU Parallelisation

Our PDMP method parallelises over the CPU and GPU, but allocating the GPU to filling up a bucket for which samples are drawn, and dedicating the CPU to the planning process, which typically involves building a tree. If the bucket is empty when a sample is needed for the sequential planning process on the CPU, a sample is drawn from an uninformed prior distribution. Therefore, obtaining informed samples come at almost no additional cost: in the worst-case scenario, if the planning process faster than drawing samples from the morphed distribution, PDMP falls back to a vanilla sampling based algorithm, drawing samples from a uninformed distribution.

Intuitively, the more samples obtained from the bucket, used in the planning process, the more informed our samples used are. We investigate how the number of sample points drawn from the bucket, which are from the "morphed" distribution, and the percentage of samples from the uninformed prior as planning time progresses. This is shown in Fig. 3. We observe in the beginning, as the bucket has not yet been filled with samples from the morphed sampling distribution, samples from the uninformed prior is used. However, the GPU is able to quickly fill up the bucket with samples from the morphed distribution, and the number of uninformed samples beyond 0.2s is largely negligible.

Figure 4: The success rate of the planning algorithm variants, over 30 runs. We observe that PDMP enables all flavours of sampling-based motion planning algorithms to have improved success rates, particularly at lower planning times.

(a) Divider   (b) Cupboard   (c) The Jaco arm used in the experiments

Figure 5: Environments of (a) planning across a divider and (b) a cluttered cupboard environment. In both scenarios, the green and blue overlaid manipulators denote the starting starting and target pose respectively. The corresponding *Jaco* robotic arm used in the real-world evaluation is illustrated in (c).

By 1 second of sampling time, the cumulative "morphed" sample points significantly exceeds the cumulative uninformed samples. This indicates that at any reasonable amount of planning time, the process of drawing samples from an informed distribution is much faster than the main planning process.

4.3 Informed Sampling Distribution From Combined Costs

Although the main cost gradient explored through this paper has been the occupancy cost, i.e. we have focused on transforming the distribution such that drawn samples are less likely to be in collision, we wish to incorporate additional cost potentials. We shall investigate incorporating a user bias for joint angles to be 0 radians. This is a cost potential that is inherently defined in the C-space of the robot, and can be achieved by specifying: $f_{bias}(\mathbf{q}) = ||\mathbf{q}||_2^2$, where $\mathbf{q} \in \mathcal{Q}$. We aim to investigate the combination of both the occupancy cost potential and the cost of user bias towards a joint angle of zero radians. The Kernel density estimate smoothed sampling distributions over the first three joints of: (i) the uninformed prior, (ii) the transformed distribution based on occpuancy cost, and (iii) the transformed distribution based on the combination of user bias and occupancy cost, are shown in Fig. 6. We see that the distribution informed by the occupancy information is very different from the uninformed prior. Additionally when combined with the user bias, the probability density at near zero Radians is significantly "sharper", indicating that we have an increased likelihood of drawing sample

Figure 6: Distribution of angles for the first three joint angles, for the uninformed prior, an informed distribution based on occupancy, and an informed distribution based on both user bias and occupancy.

points which are closer to zero radians. This demonstrates that multiple sources of information could be used to produce a more informed sampling distribution, and this can be altered to satisfy the problem requirements.

5 Conclusions

We combine cost gradients from optimisation-based motion planning with probabilistic-complete sampling-base motion planning methods. We present Parallelised Diffeomorphic Sampling-based Motion Planning, a motion-planning framework which utilises *diffeomorphisms*, generated from defined from gradients of defined cost, to morph the sampling distribution for sampling-based motion-planning methods. We demonstrate how such diffeomorphisms can be created from learned models of environment occupancy to encode obstacle avoidance behaviour, or user specified biases. Additionally, we provide an implementation which parallelises this process across the GPU and CPU, such that sampling from the more informed distribution can be achieved at no additional run-time cost. We empirically demonstrate that our method is capable of significantly improving the success rate of finding solutions in challenging planning environments.

Figure 3: Percentage and cumulative counts of sample points drawn from an uninformed prior, and from a transformed distribution that is more informed across planning time.

References

[1] L. E. Kavraki, P. Svestka, J. C. Latombe, and M. H. Overmars. Probabilistic roadmaps for path planning in high-dimensional configuration spaces. 12(4):566–580. ISSN 1042-296X. doi:10/fsgth3.

[2] S. M. LaValle. Rapidly-exploring random trees: A new tool for path planning.

[3] J. D. Gammell, T. D. Barfoot, and S. S. Srinivasa. Informed sampling for asymptotically optimal path planning. 34(4):966–984. doi:10/gd5sp3.

[4] T. Lai, P. Morere, F. Ramos, and G. Francis. Bayesian Local Sampling-Based Planning. 5(2): 1954–1961. doi:10/gg2n24.

[5] T. Lai and F. Ramos. Learning to Plan Optimally with Flow-based Motion Planner. URL http://arxiv.org/abs/2010.11323.

[6] B. Ichter, J. Harrison, and M. Pavone. Learning sampling distributions for robot motion planning. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 7087–7094. IEEE. doi:10/gf7t7z.

[7] G. Sartoretti, J. Kerr, Y. Shi, G. Wagner, T. S. Kumar, S. Koenig, and H. Choset. PRIMAL: Pathfinding via reinforcement and imitation multi-agent learning. 4(3):2378–2385. doi:10/ggzj7h.

[8] M. Elbanhawi and M. Simic. Sampling-based robot motion planning: A review. 2:56–77. doi:10/gdkx6g.

[9] N. Ratliff, M. Zucker, J. A. Bagnell, and S. Srinivasa. CHOMP: Gradient optimization techniques for efficient motion planning. doi:10/cxf9b9.

[10] M. Kalakrishnan, S. Chitta, E. Theodorou, P. Pastor, and S. Schaal. STOMP: Stochastic trajectory optimization for motion planning. In *2011 IEEE International Conference on Robotics and Automation*, pages 4569–4574. doi:10/fxbq67.

[11] J. Schulman, Y. Duan, J. Ho, A. Lee, I. Awwal, H. Bradlow, J. Pan, S. Patil, K. Goldberg, and P. Abbeel. Motion planning with sequential convex optimization and convex collision checking. 33(9):1251–1270. doi:10/f6j8k3.

[12] Y. K. Hwang and N. Ahuja. A potential field approach to path planning. 8(1):23–32. doi:10/br5jnz.

[13] D. Rezende and S. Mohamed. Variational Inference with Normalizing Flows. In *International Conference on Machine Learning*, pages 1530–1538. URL http://proceedings.mlr.press/v37/rezende15.html.

[14] B. Keng. Variational Autoencoders with Inverse Autoregressive Flows. URL http://bjlkeng.github.io/posts/variational-autoencoders-with-inverse-autoregressive-flows/.

[15] G. Papamakarios, E. Nalisnick, D. J. Rezende, S. Mohamed, and B. Lakshminarayanan. Normalizing flows for probabilistic modeling and inference. *Journal of Machine Learning Research*, 2021.

[16] J. M. Lee. Introduction to smooth manifolds. 2002.

[17] L. Ardizzone, J. Kruse, S. Wirkert, D. Rahner, E. W. Pellegrini, R. S. Klessen, L. Maier-Hein, C. Rother, and U. Köthe. Analyzing inverse problems with invertible neural networks. In *ICLR*, 2019.

[18] C. Durkan, A. Bekasov, I. Murray, and G. Papamakarios. Neural spline flows. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, 2019.

[19] F. Ramos and L. Ott. Hilbert maps: Scalable continuous occupancy mapping with stochastic gradient descent. *The International Journal of Robotics Research*, 2016.

[20] J. J. Park, P. R. Florence, J. Straub, R. A. Newcombe, and S. Lovegrove. Deepsdf: Learning continuous signed distance functions for shape representation. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019.

[21] E. Coddington and N. Levinson. Theory of ordinary differential equations. 1955.

[22] S. Klemm, J. Oberländer, A. Hermann, A. Roennau, T. Schamm, J. M. Zollner, and R. Dillmann. Rrt-connect: Faster, asymptotically optimal motion planning. In *2015 IEEE International Conference on Robotics and Biomimetics (ROBIO)*, 2015.

[23] R. Bohlin and L. Kavraki. Path planning using lazy prm. In *Proceedings 2000 ICRA. Millennium Conference. IEEE International Conference on Robotics and Automation. Symposia Proceedings (Cat. No.00CH37065)*, 2000.