Learning Robot Manipulation from Cross-Morphology Demonstration

Abstract: Some Learning from Demonstrations (LfD) methods handle small mismatches in the action spaces of the teacher and student. Here we address the case where the teacher's morphology is substantially different from that of the student. Our framework, Morphological Adaptation in Imitation Learning (**MAIL**), bridges this gap allowing us to train an agent from demonstrations by other agents with significantly different morphologies. **MAIL** learns from suboptimal demonstrations, so long as they provide *some* guidance towards a desired solution. We demonstrate **MAIL** on manipulation tasks with rigid and deformable objects including 3D cloth manipulation interacting with rigid obstacles. We train a visual control policy for a robot with one end-effector using demonstrations from a simulated agent with two end-effectors. **MAIL** shows up to 24% improvement in a normalized performance metric over LfD and non-LfD baselines. It is deployed to a real Franka Panda robot, handles multiple variations in properties for objects (size, rotation, translation), and cloth-specific properties (color, thickness, size, material). We show generalizability to morphology adaptation from n-to-m end-effectors, in a rearrangement task executed in simulation and the real world. An overview is on this website.

Keywords: Imitation from Observation, Learning from Demonstration

1 Introduction

Learning from Demonstration (LfD) [1, 2] is a set of supervised learning methods where a teacher (often, but not always, a human) demonstrates a task, and a student (usually a robot) uses this information to learn to perform the same task. Some LfD methods cope with small morphological mismatches between the teacher and student [3, 4] (*e.g.,* five-fingered hand to two-fingered gripper). However, they typically fail for a large mismatch (*e.g.,* bimanual human demonstration to a robot arm with one gripper). The key difference is that to reproduce the transition from a demonstration state to the next, no single student action suffices - a sequence of actions may be needed.

Supervised methods are appealing where demonstration-free methods [5] do not converge or underperform [6] and purely analytical approaches are computationally infeasible [7, 8]. In such settings, human demonstrations of complex tasks are often readily available *e.g.,* it is straightforward for a human to show a robot how to fold a cloth. An LfD-based imitation learning approach is appealing in such settings *provided* we allow the human demonstrator to use their body in the way they find most convenient (*e.g.,* using two hands to hang a cloth on a clothesline to dry). This requirement induces a potentially large morphology mismatch - we want to learn and execute complex tasks with deformable objects on a single manipulator robot using natural human demonstrations.

We propose a framework, Morphological Adaptation in Imitation Learning (**MAIL**), to bridge this mismatch. **MAIL** enables policy learning for a robot with m end-effectors from teachers with n end-effectors. It does not require demonstrator actions, only the states of the objects in the environment

making it potentially useful for a variety of end-effectors (pickers, suction gripper, two-fingered grippers, or even hands). It uses trajectory optimization to convert state-based demonstrations into (suboptimal) trajectories in the student's morphology. The optimization uses a learned (forward) dynamics model to trade accuracy for speed, especially useful for tasks with high-dimensional state and observation spaces. The trajectories are then used by an LfD method, which is adapted to work with suboptimal demonstrations and improve upon them by interacting with the environment.

Though the original demonstrations contain states, we generalize the solution to work with image observations in the final policy.We showcase our method on challenging cloth manipulation tasks (Sec. 4.1) for a robot with one end-effector, using image observations, shown in Fig. 1. This setting is challenging for multiple reasons. First, cloth manipulation is easy for bimanual human demonstrators but challenging for a one-handed agent (even humans find cloth manipulation non-trivial with one hand). Second, deformable objects exist in a continuous state space; image observations in this setting are also high-dimensional. Third, the cloth being manipulated makes a large number of contacts (hundreds) that are made/broken per time step. These can *significantly* slow down simulation, and consequently learning and optimization. We make the following contributions:

Figure 1: **MAIL** generalizes LfD to large morphological mismatches between teacher and student in difficult manipulation tasks. We show an example task: hang a cloth to dry on a plank (DRY CLOTH). The demonstrations are bimanual, yet the robot learns to execute the task with a single arm and gripper. The learned policy transfers to the real world and is robust to object variations.

1. We propose a novel framework, **MAIL**, that bridges the large morphological mismatch in LfD. **MAIL** trains a robot with m end-effectors to learn manipulation from demonstrations with a different (n) number of end-effectors (n-to-m end-effector transfer).

2. We demonstrate **MAIL** on challenging cloth manipulation tasks on a robot with one end-effector. Our tasks have a high-dimensional (> 15000) state space, with several 100 contacts being made/broken per step, and are non-trivial to solve with one end-effector. Our learned agent outperforms baselines by up to 24% on a normalized performance metric and transfers zero-shot to a real robot. We introduce a new variant of 3D cloth manipulation with obstacles - DRY CLOTH.

3. We illustrate how **MAIL** can handle general instances of n-to-m end-effector transfer, with a simple rearrangement task with three rigid bodies, in simulation and the real world. This task illustrates a 3-to-2, 3-to-1, and 2-to-1 end-effector transfer.

2 Related Work

Imitation Learning and Reinforcement Learning with Demonstrations: Imitation learning methods [9, 10, 11, 12, 13] and methods that combine reinforcement learning and demonstrations [14, 15, 1, 2] have shown excellent results in learning a mapping between observations and actions from demonstrations. However, their objective function requires access to the demonstrator's ground truth actions for optimization. This is infeasible for cross-morphology transfer due to action space mismatch. To work around this, prior works have proposed systems for teachers to provide demonstrations in the students' morphology [16] which limits the ability of teachers to efficiently provide data. Similar to imitation learning, offline RL [17, 18, 19] learns from demonstrations stored in a dataset without online environment interactions. While offline RL can work with large datasets of diverse rollouts to produce generalizable policies [20, 21], it requires the availability of rollouts that have the same action space as the learning agent. **MAIL** learns across morphologies and is not affected by this limitation.

Imitation from Observation: Imitation from observation (IfO) methods [3, 9, 22, 23, 24, 25] learn from the states of the demonstration; they do not use state-action pairs. In [26], an approach is proposed to learn repetitive actions using Dynamic Movement Primitives [27] and Bayesian optimization to maximize the similarity between human demonstrations and robot actions. Many IfO methods [3, 23, 24, 28] assume that the student can take a single action to transition from the demonstration's current state to the next state. Some methods [3, 23] use this to train an inverse dynamics model to infer actions. Others extract keypoints from the observations and compute actions by subtracting consecutive keypoint vectors. However, when the student has a different space than the teacher, it may require more than one action for the student to reach consecutive demonstration states. For example, in an object rearrangement task, a two-picker teacher agent can move two objects with one pick-place action. But a one-picker student will need two or more actions to achieve the same result. Zero-shot visual imitation [9] assumes that the statistics of visual observations and agents observations will be similar. However, when solving a task with different numbers of arms, some intermediate states will not be seen in teacher demonstrations. State-of-the-art learning from observation methods [25, 29] have made significant advancements in exploiting information between states. However, their tasks have much longer horizons, hence more states and learning signals than ours. Whether these methods work well on short-horizon, difficult manipulation tasks is uncertain. To address this and provide a meaningful comparison, we conducted experiments to compare **MAIL** with these methods (Sec. 4).

Trajectory Optimization: Trajectory optimization algorithms [30, 8, 31] optimize a trajectory by minimizing a cost function, subject to a set of constraints. It has been used for manipulation of rigid and deformable objects [7], even through contact [32] using complementarity constraints [33]. Indirect trajectory optimization only optimizes the actions of a trajectory and uses a simulator for the dynamics instead of adding dynamics constraints at every step.

Learned Dynamics: Learning dynamics models is useful when there is no simulator, or if the simulator is too slow or too inaccurate. Learned models have been used with MPC to speed up prediction times [34, 35, 36]. A common use case is model-based RL [37], where learning the dynamics is part of the algorithm and has been shown to learn dynamics from states and pixels [38] and applied to real-world tasks [39].

3 Formulation and Approach

3.1 Preliminaries

We formulate the problem as a POMDP with state $s \in \mathcal{S}$, action $a \in \mathcal{A}$, observation $o \in \mathcal{O}$, transition function $\mathcal{T} : \mathcal{S} \times \mathcal{A} \to \mathcal{S}$, horizon H, discount factor γ and reward function $r : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$. The discounted return at time t is $R_t = \sum_{i=t}^{H} \gamma^i r(s_i, a_i)$ and $s_i \sim \mathcal{T}(s_{i-1}, a_{i-1})$. A task is instantiated with a variant sampled from the task distribution, $v \sim \mathcal{V}$. The initial environment state depends on the task variant, $s_0(v), v \sim \mathcal{V}$. We train a policy π_θ to maximize expected reward $J(\pi_\theta)$ of an episode over task variants v, $J(\pi_\theta) = \mathbb{E}_{v \sim \mathcal{V}}[R_0]$, subject to initial state $s_0(v)$ and the dynamics from $\mathcal{T}$. For a method overview see Fig. 2.

For an agent with morphology M, we differentiate between datasets available as demonstrations ($\mathcal{D}_{Demo}^M$) and those that are optimized ($\mathcal{D}_{Optim}^M$). For our cloth environments, our teacher morphology is two-pickers ($M = 2p$) and student morphology is one-picker ($M = 1p$). We assume the demonstrations are from teachers with a morphology that can be different from the student (and from each other). We refers to these as *teacher* demonstrations, $\mathcal{D}_{Teacher}$, to emphasize that they do not necessarily come from an expert or an oracle. Further, these can be suboptimal. The demonstrations are state trajectories $\tau_T = (s_0, \ldots, s_{H-1})$. The teacher dataset is made up of K_T such trajectories, $\mathcal{D}_{Teacher} = \{\tau_{T,i}\} \forall i = 1, \ldots, K_T$, using a few task variations from the task distribution $v_d \sim \mathcal{V}$.

We now discuss the components of **MAIL**. The user provides teacher demonstrations $\mathcal{D}_{Teacher}$. First, we create a dataset of random actions, $\mathcal{D}_{Random}$, and use it to train a dynamics model, $\mathcal{T}_\psi$. The learned dynamics are not task-specific and depend on the objects in the environment. $\mathcal{T}_\psi$ reduces

Figure 2: An example cloth folding task with demonstrations from a teacher with $n = 2$ end-effectors, deployed on a Franka Panda with $m = 1$ end-effector (parallel-jaw gripper). We train a network to predict the forward dynamics of the object being manipulated in simulation, using a random action dataset $\mathcal{D}_{Random}$. Given teacher demonstrations we use indirect trajectory optimization to find student actions that solve the task. Finally, we pass the optimized dataset $\mathcal{D}_{Student}$ to a downstream LfD method that combines imitation and RL to get a final policy π that generalizes to task variations and extends task learning to image space, enabling real-world deployment.

computational cost when dealing with contact-rich simulations like cloth manipulation (Sec. 4.1). Next, we convert each teacher demonstration to a trajectory suitable for the student's morphology. For our tasks, we find gradient-free indirect trajectory optimization [31] performs the best (Appendix Sec. A.2.1). We used $\mathcal{T}_\psi$ for this optimization as it provides the appropriate speed-accuracy trade-off. The optimization objective is to match with object states in the demonstration (we cannot match demonstration actions across morphologies). We combine these optimized trajectories to create a dataset $\mathcal{D}_{Student}$ for the student. Finally, we pass $\mathcal{D}_{Student}$ to a downstream LfD method to learn a policy π that generalizes from the task variations in $\mathcal{D}_{Teacher}$ to the task distribution $\mathcal{V}$. It also extends π to use image observations and deploys zero-shot on a real robot (rollouts in Fig. 5).

3.2 Learned Spatio-temporal Dynamics Model

MAIL uses trajectory optimization to convert demonstrations into (suboptimal) trajectories in the student's morphology. This can be prohibitively slow for large state spaces and complex tasks such as cloth manipulation. Robotic simulators have come a long way in advancing fidelity and speed, but simulating complex deformable objects and contact-rich manipulation still requires significant computation making optimization intractable for challenging simulations. We use the NVIDIA FLeX simulator that is based on extended position-based dynamics [40]. We learn a CNN-LSTM based spatio-temporal forward dynamics model with parameters ψ, $\mathcal{T}_\psi$, to approximate cloth dynamics, $\mathcal{T}$. This offers a speed-accuracy trade-off with a tractable computation time in environments with large state spaces and complex dynamics. The states of objects are represented as N particle positions: $s = P = \{p_i\}_{i=1...N}$. Each particle state consists of its x, y, and z coordinates. For each task, we generate a corpus of random pick-and-place actions and store them in the dataset $\mathcal{D}_{Random} = \{d_i\}$, where $i = 1, \ldots, K_R$ and $d_i = (P_i, a_i, P'_i)$. For each datum i, we feed P_i to the CNN network to extract features of particle connectivity. These features are concatenated with a_i and input to the LSTM model to extract features based on the previous particle positions. A fully connected layer followed by layer normalization and $tanh$ activation is used to learn the non-linear combinations of features. The outputs are the predicted particle displacements. The objective function is the distance between predicted and ground-truth particle displacements, $\|\Delta P_{sim} - \Delta P_{pred}\|_2$. Here $\Delta P_{sim} = \{\Delta p_i\}_{i=1,\ldots,N}$ is obtained from the simulator and $\Delta p_i = p_{i+1} - p_i$ for every particle i.

Due to its simplicity, the CNN-LSTM dynamics model provides fast inference, compared to a simulator which may have to perform many collision checks at any time step. This speedup is crucial when optimizing over a large state space, as long as the errors in particle positions are tolerable. In our experiments, we were able to get 162 fps with $\mathcal{T}_\psi$, compared to 3.4 fps with the FleX simulator (50x speed up) (Fig. 8). However, this stage is optional if the environment is low-dimensional, or if the simulation speed-up from inference is not significant. Simulation accuracy is important

171 when training a final policy, to provide *accurate* end-effector locations for execution on a real robot.
172 Hence, the learned dynamics model is not used for training in the downstream LfD method.

3.3 Indirect Trajectory Optimization

174 We use indirect trajectory optimization [31] to find the open-loop action trajectory to match the
175 teacher state trajectory, τ_T. This optimizes for the student's actions while propagating the state with
176 a simulator. We use the learned dynamics $\mathcal{T}_\psi$ to give us fast, approximate optimized trajectories.
177 This is in contrast to direct trajectory optimization (or collocation) that optimizes both states and
178 actions at every time step. Direct trajectory optimization requires dynamics constraints to ensure
179 consistency among states being optimized, which can be challenging for discontinuous dynamics.
180 We use the Cross-Entropy Method (CEM) for optimization, and compare this against other methods,
181 such as SAC (Appendix A.2.1). The optimization objective is to match the object's goal state s_{goal}
182 in the demonstration with the same task variant v_d. Formally, the problem is defined as:

$$\min_{a_t} \ \|s_{goal} - s_H\|_2 \ \text{ subject to } \ s_0 \ = s_0(v_d) \ \text{ and } s_{t+1} = \mathcal{T}(s_t, a_t) \ \forall t = 0, \ldots, H-1 \quad (1)$$

183 where s_H is the predicted final state. Note that if τ_T has a longer time horizon, it would help to
184 match intermediate states and use multiple-shooting methods. After optimizing the action trajecto-
185 ries for each demonstration $\tau_{T,i} \in \mathcal{D}_{Teacher}$, we use them with the simulator to obtain the opti-
186 mized trajectories in the student's morphology. These are combined to create the student dataset,
187 $\mathcal{D}_{Student} = \{\tau_1, \tau_2, \tau_3, \ldots\}$, where $\tau_i = (s_t, o_t, a_t, s_{t+1}, o_{t+1}, r_t, d) \forall t = 1 \ldots H-1$. For gener-
188 alizability and real-world capabilities, we train an LfD method using $\mathcal{D}_{Student}$. At this stage, we
189 use the learned dynamics model, trading faster simulation speed for lower accuracy in the learned
190 model. This is also partially responsible for why $\mathcal{D}_{Student}$ contains suboptimal demonstrations.

3.4 Learning from the Optimized Dataset

192 Our chosen LfD method is DMfD [41], an off-policy LfD method that learns in state and image
193 spaces. As part of tuning, we employ 100 demonstrations, about two orders of magnitude fewer than
194 the 8000 recommended by the original work. To prevent the policy from overfitting to suboptimal
195 demonstrations in $\mathcal{D}_{Student}$, we disable demonstration-state matching, *i.e.,* resetting the agent to
196 demonstration states and applying imitation reward (see Appendix A.2.5). These were originally
197 proposed [42] as reference state initialization (RSI). These modifications are essential for our LfD
198 implementation, where the demonstrations do not come from an expert.

199 We use the simulator instead of the learned dynamics model $\mathcal{T}_\psi$ at this stage. This is not because it
200 is computationally infeasible to use the learned model, but because accuracy is important in the final
201 reactive policy. From DMfD, the policy π is parameterized by parameters θ, and learns from data
202 collected in a replay buffer $\mathcal{B}$. The policy loss contains an advantage-weighted loss $\mathcal{L}_A$ where actions
203 are weighted by the advantage function $A^\pi(s, a) = Q^\pi(s, a) - V^\pi(s)$ and temperature parameter
204 λ. It also contains an entropy component $\mathcal{L}_E$ to promote exploration during data collection. The
205 final policy loss $\mathcal{L}_\pi$ is a combination of these terms (Eq. 2).

$$\mathcal{L}_A = \mathop{\mathbb{E}}_{s,a,o\sim\mathcal{B}} \left[\log \pi_\theta(a|o) \exp\left(\frac{1}{\lambda} A^\pi(s, a)\right)\right] \quad \mathcal{L}_E = \mathop{\mathbb{E}}_{s,a,o\sim\mathcal{B}}[\alpha \log \pi_\theta(a|o) - Q(s, a)]$$
$$\mathcal{L}_\pi = (1 - w_E)\mathcal{L}_A + w_E\mathcal{L}_E, \ 0 \le w_E \le 1 \quad (2)$$

207 where w_E is a tuneable hyper-parameter. The resulting policy is denoted as π_θ. We pre-populate
208 buffer $\mathcal{B}$ with $\mathcal{D}_{Student}$. Using LfD, we extend from state inputs to image observations, and gener-
209 alize from v_d to any variation sampled from $\mathcal{V}$.

4 Experiments

211 Our experiments are designed to answer the following questions: (1) How does **MAIL** compare to
212 state-of-the-art (SOTA) methods in solving tasks? (Sec. 4.2) (2) How well can **MAIL** solve tasks
213 in the real world? (Fig. 4.2) (3) Can **MAIL** generalize to different n-to-m end-effector transfers?
214 (Sec. 4.3) (4) How do different components of **MAIL** affect performance? (Sec. 4.4)

4.1 Tasks

We experiment with cloth manipulation tasks that are easy for humans to demonstrate but difficult to perform on a robot. We also discuss a simpler rearrangement task with rigid bodies to illustrate generalizability. The tasks are shown in Appendix Fig. 6. We choose a pick-and-place action space, as is common for cloth manipulation [43, 6, 44, 45]. Our action space is 6D (pick and place pose). The end-effectors are pickers in simulation, and a two-finger parallel jaw gripper on the real robot.

CLOTH FOLD: Fold a square cloth in half, along a specified line. DRY CLOTH: Pick up a square cloth from the ground and hang it on a plank to dry, variant of [46]. THREE BOXES: A simple 2D environment where three boxes of different sizes are randomly placed and need to be moved to designated goal locations. This task is used to illustrate the generalizability of **MAIL** with various n-to-m end-effector transfers, and is not used in the SOTA comparisons. For details on metrics and task variants, see Appendix A.1.

Figure 3: **SOTA performance comparisons.** For each training run, we used the best model in each seed's training run, and evaluated using 100 rollouts across 5 seeds, different from the training seed. Bar height denotes the mean, error bars indicate the standard deviation. **MAIL** outperforms all baselines, in some cases by as much as 24%.

We use particle positions as the state for training dynamics models and trajectory optimization. We record pre-programmed demonstrations for the teacher dataset for each task. For non-LfD and LfD RL training, we use a 32x32 RGB image as the visual observation. The instantaneous reward function, used in learning the policy, is the task performance metric at a given state. Further details on architecture and training are in the supplementary material. In all experiments, we compare each method's normalized performance, measured at the end of the task given by $\hat{p}(t) = \frac{p(\boldsymbol{s}_t) - p(\boldsymbol{s}_0)}{p_{opt} - p(\boldsymbol{s}_0)}$, where p is the performance metric of state $\boldsymbol{s}_t$ at time t, and p_{opt} is the best performance achievable by the task. We use $\hat{p}(H)$ at the end of the episode ($t = H$).

4.2 SOTA comparisons

Many LfD baselines (Sec. 2) are not directly applicable (they do not handle large difference in action space due to different morphologies). We compare **MAIL** with those LfD baselines that produce a policy with image observations, given demonstrations without actions.

1. SAC-CURL [47]: An image-based RL algorithm that uses contrastive learning and SAC [5] as the underlying RL algorithm. It does not require demonstrations.
2. SAC-DrQ [48]: An image-based RL algorithm that uses a regularized Q-function, data augmentations, and SAC as the underlying RL algorithm. It does not require demonstrations.
3. GNS [49]: A SOTA method that represents cloth as a graph and predicts dynamics using a graph neural network (GNN). It does not require demonstrations but learns dynamics on a random action dataset with particle positions. We run this learned model with a planner [43], provided with full state information.
4. SAC-DrQ-IR: A custom variant of SAC [5] that uses DrQ-based [48] image encoding and a state-only imitation reward (IR) to reach the desired state of the object to be manipulated. It does not imitate actions, as they are unavailable.
5. GAIfO [25]: An adversarial imitation learning algorithm that trains a discriminator on state-state pairs (s, s') from both the demonstrator and agent. This is a popular extension of GAIL [13] that learns the same from state-action pairs (s, a).
6. GPIL [29] A goal-directed LfD method that uses demonstrations and agent interactions to learn a goal proximity function. This function provides a dense reward to train a policy.

Fig. 3 shows the results. In each environment, the first three columns are demonstration-free baselines, and the last four are LfD methods. **MAIL** outperforms all baselines, in some cases by as much as 24%. For the easier CLOTH FOLD task, the SAC-DrQ baseline came within 11% of **MAIL**.

However, all baselines do not perform well in the more difficult DRY CLOTH task. RL methods fail because they have not explored the parameter space enough without guidance from demonstrations, and thus converge to a suboptimal solution. Our custom LfD baseline, SAC-DrQ-IR, does have reasonable performance, but the results show that naive imitation alone is not a good form of guidance to solve it. The other LfD baselines, GAIfO and GPIL, have poor performance in both environments. One of the primary reasons for this is the effect of cross-morphological demonstrations. They perform significantly better with student morphology demonstrations, even if they are suboptimal. Moreover, environment difficulty also plays an important part in the final performance. These and other ablations are described in Sec. 4.4 and more thoroughly in Appendix Sec. A.2.

Surprisingly, the GNS baseline with structured dynamics does not perform well, even though it

(a) Teacher demonstration with three pickers.

(b) Final policy: Two pickers

(c) Final policy: One picker

(d) Final policy: One Franka Panda robot

Figure 4: **Sample trajectories of the** THREE BOXES **task.** A three-picker teacher trajectory to reach the goal state (Fig. 4a). Final policy of the two-picker agent (2 actions to solve the task Fig. 4b). Final policy of the one-picker agent (3 actions to solve the task Fig. 4c). The final policy of the one-picker agent in the real world (Fig. 4d).

has been used for cloth modeling [50]. We believe that this is because it is designed to learn particle dynamics via small displacements, but our pick-and-place action space enables large displacements. Similar to [43], we break down each pick-and-place action into 100 delta actions to work with the small displacements that GNS is trained on. Thus, planning will accumulate errors from the 100 GNS steps for every action of the planner, which can grow superlinearly due to compounding errors. This makes it difficult to solve the task. This is especially seen in the DRY CLOTH task (Fig. 3), where the displacements required to move the entire cloth over the plank are much higher than the displacements needed for CLOTH FOLD. The rollouts of **MAIL** on DRY CLOTH show the agent following the demonstrated guidance - it learned to hang the cloth over the plank. However, it also displayed an emergent behavior to straighten out the cloth on top of the plank, in an effort to spread it out to receive higher performance. This was not seen in the two-picker teacher demonstrations. Demonstrations and rollouts are in the supplementary video file, and on this website.

Real-world results For DRY CLOTH and CLOTH FOLD tasks, we deploy the learned policies on a Franka Panda robot (Fig. 5) with a single parallel-jaw gripper. We test the policies with many different variations of square cloth (size, rotation, translation, thickness, color, and material). For performance metrics, see Appendix Sec. A.5 The policies achieve $\sim 80\%$ performance, close to the average performance of our method in simulation, for both tasks.

4.3 Generalizability

We show, in a simple THREE BOXES task (Fig. 4), how **MAIL** learns from a demonstrator morphology with n end-effectors and deploys to a robot with m end-effectors. Consider a three-picker agent that solves the task in one pick-place action. It provides the teacher demonstrations, $\mathcal{D}_{Teacher}$. We transfer them into one-picker or two-picker demonstrations using indirect trajectory optimization and the learned dynamics model. These will be the optimized datasets that are fed to a downstream LfD method. In both cases, the LfD method learns to solve the task with a globally optimal 100% normalized performance. It generalizes from state inputs in the demonstrations to the image inputs we receive from the environment. Fig. 4 shows the three picker demonstration, a 3-to-2 and 3-to-1 end-effector transfer. We could also do this for the 2-to-1 case, in which a two-picker teacher's demonstration would take multiple pick-and-place actions to solve the task. Thus, **MAIL** can solve a task using n-to-m end-effector transfer with $n > m$, shown here for 3-to-2, 3-to-1, and 2-to-1 cases. It is trivial to perform the transfer for n-to-m with $n \leq m$. One may simply append the teacher's action space with $m - n$ arms that do no operations. Thus, **MAIL** is capable of general n-to-m end-effector transfer.

4.4 Ablation studies

We use the DRY CLOTH task for all ablations unless specified; it is the most challenging of our tasks. We provide detailed answers to the following questions in Appendix A.2. Appendix Fig. 7 illustrates the ablations corresponding to each part of the overall method. (1) How do different methods perform in creating optimized dataset $\mathcal{D}_{Student}$? (2) What is the best architecture to learn the task dynamics? (3) How good is $\mathcal{D}_{Student}$ compared to the recorded demonstrations? (4) How well does the downstream LfD method handle different

Cloth fold	Dry cloth		
Performance 0.818	Spread metric 8/10		

Figure 5: **Real-world results for** CLOTH FOLD **and** DRY CLOTH**.** Statistics over 10 rollouts.

kinds of demonstrations? (5) How does the use of expert state matching affect the downstream LfD? (6) How do the baselines perform across related morphologies and environment?

We discovered that the Cross-Entropy Method (CEM) is the most effective optimizer for generating a $\mathcal{D}_{Student}$ from demonstrations. When combined with CEM, the 1D CNN-LSTM architecture produces the best results for trajectory optimization. Our optimized $\mathcal{D}_{Student}$ performs similarly to the pre-programmed $\mathcal{D}_{Demo}^{1p}$, which has access to full state information of the environment. By utilizing our chosen downstream LfD method, we can successfully complete tasks with a variety of demonstrations and achieve superior performance compared to both $\mathcal{D}_{Student}$ and $\mathcal{D}_{Teacher}$. Expert state matching negatively impacts the performance of DMfD. Lastly, we found that GAIfO trained on our $\mathcal{D}_{Student}$ outperforms GAIfO trained on the $\mathcal{D}_{Teacher}$, and the difficulty of the environment significantly influences the performance of GAIfO and GPIL.

4.5 Limitations

MAIL requires object states in demonstrations and during simulation training, however full state information is not needed at deployment time. It has been tested on the pick-place action space. While it works for high-frequency actions (Appendix A.2.7), it will likely be difficult to optimize actions to create the student dataset for high-dimensional actions. The state-visitation distribution of demonstration trajectories must overlap with that of the student agent; this overlap must contain the equilibrium states of the demonstration. For example, a one-gripper agent cannot reach a demonstration state where two objects are moving simultaneously, but it *can* reach a state where both objects are stable at their goal locations (equilibrium). **MAIL** cannot work when the student robot is unable to reach the goal or intermediate states in the demonstration. For example, in trying to open a flimsy bag with two handles, both end-effectors may simultaneously be needed to keep the bag open. **MAIL** builds a separate policy for each student robot morphology. Subsequent work could learn a single policy conditioned on the desired morphology - another way to think about a base model for generalized LfD.

5 Conclusion

We presented **MAIL**, a framework that enables LfD across morphologies. Our framework enables policy learning for a robot with m end-effectors from teachers with n end-effectors. This enables teachers to record demonstrations in the setting of their own morphology, and vastly expands the set of demonstrations to learn from. We show an improvement of up to 24% over SOTA baselines and discuss other baselines that are unable to handle a large mismatch between teacher and student. Our experiments are on challenging household cloth manipulation tasks performed by a robot with one end-effector based on bimanual demonstrations. We showed that our policy can be deployed zero-shot on a real Franka Panda robot, and generalizes across cloths of varying size, color, material, thickness, and robustness to cloth rotation and translation. We further showed LfD generalizability to any transfer from n-to-m end-effectors, with multiple rigid objects. We believe that this is an important step towards allowing LfD to train a robot to learn from *any* robot demonstrations, regardless of robot morphology, expert knowledge, or the medium of demonstration.

References

[1] K. Pertsch, Y. Lee, Y. Wu, and J. J. Lim. Demonstration-guided reinforcement learning with learned skills. *5th Conference on Robot Learning*, 2021.

[2] I.-C. A. Liu, S. Uppal, G. S. Sukhatme, J. J. Lim, P. Englert, and Y. Lee. Distilling motion planner augmented policies into visual control policies for robot manipulation. In A. Faust, D. Hsu, and G. Neumann, editors, *Proceedings of the 5th Conference on Robot Learning*, volume 164 of *Proceedings of Machine Learning Research*, pages 641–650. PMLR, 08–11 Nov 2022. URL https://proceedings.mlr.press/v164/liu22b.html.

[3] I. Radosavovic, X. Wang, L. Pinto, and J. Malik. State-only imitation learning for dexterous manipulation. In *2021 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 7865–7871. IEEE, 2021.

[4] Y. Yang, Y. Li, C. Fermuller, and Y. Aloimonos. Robot learning manipulation action plans by "watching" unconstrained videos from the world wide web. *Proceedings of the AAAI Conference on Artificial Intelligence*, 29(1), Mar. 2015. doi:10.1609/aaai.v29i1.9671. URL https://ojs.aaai.org/index.php/AAAI/article/view/9671.

[5] T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International conference on machine learning*, pages 1861–1870. PMLR, 2018.

[6] J. Hietala, D. Blanco–Mulero, G. Alcan, and V. Kyrki. Learning visual feedback control for dynamic cloth folding. In *2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 1455–1462, 2022. doi:10.1109/IROS47612.2022.9981376.

[7] S. Jin, D. Romeres, A. Ragunathan, D. K. Jha, and M. Tomizuka. Trajectory optimization for manipulation of deformable objects: Assembly of belt drive units. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pages 10002–10008. IEEE, 2021.

[8] J. M. Bern, P. Banzet, R. Poranne, and S. Coros. Trajectory optimization for cable-driven soft robot locomotion. In *Robotics: Science and Systems*, volume 1, 2019.

[9] D. Pathak, P. Mahmoudieh, G. Luo, P. Agrawal, D. Chen, Y. Shentu, E. Shelhamer, J. Malik, A. A. Efros, and T. Darrell. Zero-shot visual imitation. In *ICLR*, 2018.

[10] C. Finn, T. Yu, T. Zhang, P. Abbeel, and S. Levine. One-shot visual imitation learning via meta-learning. In S. Levine, V. Vanhoucke, and K. Goldberg, editors, *Proceedings of the 1st Annual Conference on Robot Learning*, volume 78 of *Proceedings of Machine Learning Research*, pages 357–368. PMLR, 13–15 Nov 2017. URL https://proceedings.mlr.press/v78/finn17a.html.

[11] Y. Duan, M. Andrychowicz, B. Stadie, J. Ho, J. Schneider, I. Sutskever, P. Abbeel, and W. Zaremba. One-shot imitation learning. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, NIPS'17, page 1087–1098, Red Hook, NY, USA, 2017. Curran Associates Inc. ISBN 9781510860964.

[12] M. Laskey, J. Lee, R. Fox, A. D. Dragan, and K. Goldberg. DART: noise injection for robust imitation learning. In *1st Annual Conference on Robot Learning, CoRL 2017, Mountain View, California, USA, November 13-15, 2017, Proceedings*, volume 78 of *Proceedings of Machine Learning Research*, pages 143–156. PMLR, 2017. URL http://proceedings.mlr.press/v78/laskey17a.html.

[13] J. Ho and S. Ermon. Generative adversarial imitation learning. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016. URL https://proceedings.neurips.cc/paper/2016/file/cc7e2b878868cbae992d1fb743995d8f-Paper.pdf.

[14] A. Rajeswaran, V. Kumar, A. Gupta, G. Vezzani, J. Schulman, E. Todorov, and S. Levine. Learning Complex Dexterous Manipulation with Deep Reinforcement Learning and Demonstrations. In *Proceedings of Robotics: Science and Systems (RSS)*, 2018.

[15] M. Vecerík, T. Hester, J. Scholz, F. Wang, O. Pietquin, B. Piot, N. M. O. Heess, T. Rothörl, T. Lampe, and M. A. Riedmiller. Leveraging demonstrations for deep reinforcement learning on robotics problems with sparse rewards. *ArXiv*, abs/1707.08817, 2017.

[16] A. Mandlekar, J. Booher, M. Spero, A. Tung, A. Gupta, Y. Zhu, A. Garg, S. Savarese, and L. Fei-Fei. Scaling robot supervision to hundreds of hours with roboturk: Robotic manipulation dataset through human reasoning and dexterity. In *2019 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 1048–1055. IEEE, 2019.

[17] S. Levine, A. Kumar, G. Tucker, and J. Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv e-prints*, pages arXiv–2005, 2020.

[18] S. Lange, T. Gabel, and M. Riedmiller. Batch reinforcement learning. In *Reinforcement learning*, pages 45–73. Springer, 2012.

[19] F. Fuchs, Y. Song, E. Kaufmann, D. Scaramuzza, and P. Dürr. Super-human performance in gran turismo sport using deep reinforcement learning. *IEEE Robotics and Automation Letters*, 6(3):4257–4264, 2021.

[20] A. Kumar, A. Zhou, G. Tucker, and S. Levine. Conservative q-learning for offline reinforcement learning. *Advances in Neural Information Processing Systems*, 33:1179–1191, 2020.

[21] P. Rashidinejad, B. Zhu, C. Ma, J. Jiao, and S. Russell. Bridging offline reinforcement learning and imitation learning: A tale of pessimism. *Advances in Neural Information Processing Systems*, 2021.

[22] F. Torabi, G. Warnell, and P. Stone. Recent advances in imitation learning from observation. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI-19*, pages 6325–6331. International Joint Conferences on Artificial Intelligence Organization, 7 2019. doi:10.24963/ijcai.2019/882. URL https://doi.org/10.24963/ijcai.2019/882.

[23] F. Torabi, G. Warnell, and P. Stone. Behavioral cloning from observation. In *Proceedings of the Twenty-Seventh International Joint Conference on Artificial Intelligence, IJCAI-18*, pages 4950–4957. International Joint Conferences on Artificial Intelligence Organization, 7 2018. doi:10.24963/ijcai.2018/687. URL https://doi.org/10.24963/ijcai.2018/687.

[24] Y.-T. A. Sun, H.-C. Lin, P.-Y. Wu, and J.-T. Huang. Learning by watching via keypoint extraction and imitation learning. *Machines*, 10(11), 2022. ISSN 2075-1702. doi:10.3390/sun22KeypointExtraction. URL https://www.mdpi.com/2075-1702/10/11/1049.

[25] F. Torabi, G. Warnell, and P. Stone. Generative adversarial imitation from observation. *arXiv preprint arXiv:1807.06158*, 2018.

[26] J. Yang, J. Zhang, C. Settle, A. Rai, R. Antonova, and J. Bohg. Learning periodic tasks from human demonstrations. *IEEE International Conference on Robotics and Automation (ICRA)*, 2022.

[27] A. J. Ijspeert, J. Nakanishi, and S. Schaal. Learning rhythmic movements by demonstration using nonlinear oscillators. In *IEEE/RSJ International Conference on Intelligent Robots and Systems*, volume 1, pages 958–963, 2002. doi:10.1109/IRDS.2002.1041514.

[28] F. Al-Hafez, D. Tateo, O. Arenz, G. Zhao, and J. Peters. Ls-iq: Implicit reward regularization for inverse reinforcement learning. In *Eleventh International Conference on Learning Representations (ICLR)*, 2023. URL https://openreview.net/pdf?id=o3Q4m8jg4BR.

[29] Y. Lee, A. Szot, S.-H. Sun, and J. J. Lim. Generalizable imitation learning from observation via inferring goal proximity. In *Advances in Neural Information Processing Systems*, 2021.

[30] P. T. de Boer, D. P. Kroese, S. Mannor, and R. Y. Rubinstein. A tutorial on the cross-entropy method. *Annals of Operations Research*, 134:19–67, 2005.

[31] M. Kelly. An introduction to trajectory optimization: How to do your own direct collocation. *SIAM Review*, 59(4):849–904, 2017.

[32] M. Posa, C. Cantu, and R. Tedrake. A direct method for trajectory optimization of rigid bodies through contact. *The International Journal of Robotics Research*, 33(1):69–81, 2014.

[33] Z.-Q. Luo, J.-S. Pang, and D. Ralph. *Mathematical programs with equilibrium constraints*. Cambridge University Press, 1996.

[34] G. Williams, N. Wagener, B. Goldfain, P. Drews, J. M. Rehg, B. Boots, and E. A. Theodorou. Information theoretic mpc for model-based reinforcement learning. In *2017 IEEE International Conference on Robotics and Automation (ICRA)*, pages 1714–1721. IEEE, 2017.

[35] A. Venkatraman, R. Capobianco, L. Pinto, M. Hebert, D. Nardi, and J. A. Bagnell. Improved learning of dynamics models for control. In *2016 International Symposium on Experimental Robotics*, pages 703–713. Springer, 2017.

[36] T. G. Thuruthel, E. Falotico, F. Renda, and C. Laschi. Learning dynamic models for open loop predictive control of soft robotic manipulators. *Bioinspiration & Biomimetics*, 12(6): 066003, oct 2017. doi:10.1088/1748-3190/aa839f. URL https://dx.doi.org/10.1088/1748-3190/aa839f.

[37] A. S. Polydoros and L. Nalpantidis. Survey of model-based reinforcement learning: Applications on robotics. *Journal of Intelligent & Robotic Systems*, 86(2):153–173, 2017.

[38] D. Hafner, T. Lillicrap, I. Fischer, R. Villegas, D. Ha, H. Lee, and J. Davidson. Learning latent dynamics for planning from pixels. In *International conference on machine learning*. PMLR, 2019.

[39] P. Wu, A. Escontrela, D. Hafner, K. Goldberg, and P. Abbeel. Daydreamer: World models for physical robot learning. *Conference on Robot Learning*, 2022.

[40] M. Macklin, M. Müller, and N. Chentanez. Xpbd: position-based simulation of compliant constrained dynamics. *In Proceedings of the 9th International Conference on Motion in Games*, 2016.

[41] G. Salhotra, I.-C. A. Liu, M. Dominguez-Kuhne, and G. S. Sukhatme. Learning deformable object manipulation from expert demonstrations. *IEEE Robotics and Automation Letters*, 7(4): 8775–8782, 2022. doi:10.1109/LRA.2022.3187843.

[42] X. B. Peng, P. Abbeel, S. Levine, and M. van de Panne. Deepmimic: Example-guided deep reinforcement learning of physics-based character skills. *ACM Transactions on Graphics (TOG)*, 2018.

[43] X. Lin, Y. Wang, Z. Huang, and D. Held. Learning visible connectivity dynamics for cloth smoothing. In *Conference on Robot Learning*, pages 256–266. PMLR, 2022.

[44] Y. Avigal, L. Berscheid, T. Asfour, T. Kröger, and K. Goldberg. Speedfolding: Learning efficient bimanual folding of garments. In *2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 1–8, 2022. doi:10.1109/IROS47612.2022.9981402.

[45] X. Lin, Y. Wang, J. Olkin, and D. Held. Softgym: Benchmarking deep reinforcement learning for deformable object manipulation. *Conference on Robot Learning (CoRL)*, 2020.

[46] J. Matas, S. James, and A. J. Davison. Sim-to-real reinforcement learning for deformable object manipulation. In *Conference on Robot Learning*, pages 734–743. PMLR, 2018.

[47] M. Laskin, A. Srinivas, and P. Abbeel. CURL: Contrastive unsupervised representations for reinforcement learning. In H. D. III and A. Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 5639–5650. PMLR, 13–18 Jul 2020. URL https://proceedings.mlr.press/v119/laskin20a.html.

[48] D. Yarats, I. Kostrikov, and R. Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL https://openreview.net/forum?id=GY6-6sTvGaf.

[49] A. Sanchez-Gonzalez, J. Godwin, T. Pfaff, R. Ying, J. Leskovec, and P. Battaglia. Learning to simulate complex physics with graph networks. In *International conference on machine learning*, pages 8459–8468. PMLR, 2020.

[50] Z. Huang, X. Lin, and D. Held. Mesh-based Dynamics with Occlusion Reasoning for Cloth Manipulation. In *Proceedings of Robotics: Science and Systems*, New York City, NY, USA, June 2022. doi:10.15607/RSS.2022.XVIII.011.