UNSUPERVISED FEDERATED LEARNING IS POSSIBLE: A CASE OF CLASS-CONDITIONAL-SHARING CLIENTS

ABSTRACT

Supervised *federated learning* (FL) enables multiple clients to share the trained model without sharing their labeled data. However, potential clients might even be *reluctant* to label their own data, which could limit the applicability of FL in practice. In this paper, we show the possibility of *unsupervised* FL whose model is still a classifier for predicting class labels, if there is sufficient *class-prior shift* among the *unlabeled* data owned by the clients and the class priors are known to the clients. We propose *federation of unsupervised learning* (FedUL), where the unlabeled data are transformed into *surrogate* labeled data for each of the clients, a *modified* model is trained by supervised FL, and the *wanted* model is recovered from the modified model. FedUL is a very general solution to unsupervised FL: it is compatible with many supervised FL methods, and the recovery of the wanted model can be theoretically guaranteed as if the data have been labeled. Experiments on benchmark and real-world datasets demonstrate the effectiveness of FedUL. Anonymous code download link is given in Appendix and will be open source later.

1 INTRODUCTION

Federated Learning (FL) has received significant attention from both academic and industrial perspectives in that it can bring together separate data sources and allow multiple clients to train a central model in a collaborative but private manner (McMahan et al., 2017; Kairouz et al., 2019; Yang et al., 2019). So far, the majority of FL researches focused on the *supervised* setting, requiring collected data at each client to be *fully labeled*—this may hinder the spread of FL in practice since labeling large-scale training data can be extremely costly due to laborious mannual annotations, and sometimes may not even be possible for privacy concerns, e.g., in medical diagnosis (Ng et al., 2021).

In this paper, we are interested in a challenging *unsupervised FL* problem where *only unlabeled* (U) data are available at each client. Our goal remains to train a classification model that can predict accurate class labels in the FL setup. It is often observed that each client collects their own data at different time points or from different geographic locations, e.g., a hospital (data center) may store patient data every month or a particular user (mobile device) may take photos at different places. Therefore, we consider a realistic setting that the U data at a client come in the form of *separate data sets*: the data distribution of each U set and the number of U sets available at each client may *vary*.

Without *any* labels, FL becomes significantly harder than before. In this work, we show that the aforementioned unsupervised FL problem can be solved if the class prior probability shifts between the available U sets at each client, and these class priors are known to the clients. Such a learning scenario can be conceivable in many real-world problems. For example, the hospital may not release the patients' diagnostic labels due to privacy reasons, but the morbidity rates of diseases (corresponding to the class priors) may change over time and can be accessible from related public medical reports (Croft et al., 2018); moreover, in many cases it is possible to estimate the class priors much more cheaply than the ground-truth labels (Quadrianto et al., 2009a).

Based on these findings, we propose the *federation of unsupervised learning* (FedUL) (cf. Figure 1), where the original clients with U data are transformed to surrogate clients with (surrogate) labeled data and then supervised FL can be applied. The difficulty is how to infer our wanted model for the original classification task from the surrogate model learned by the surrogate task. We solve this problem by bridging the original and surrogate class probabilities with certain injective transition

Figure 1: Illustration of (a) standard supervised FL scheme vs. (b) proposed FedUL scheme. In (a), each client f_c, $c \in [C]$, has access to the *true labels* of their local data, and collaboratively train a central model f using supervised FL schemes, e.g., Federated Averaging (FedAvg) (McMahan et al., 2017). In (b), each client has access to only unlabeled (U) data coming in the form of separate sets, where supervised FL methods cannot be directly applied. We propose FedUL that treats the indexes of the U sets at each client as *surrogate labels*, transforms the local U datasets to (surrogate) labeled datasets, and formulate a surrogate supervised FL task (shown in blue boxes). Then we modify the client model to adapt into the surrogate task by adding a transition layer Q_c to the original model output f_c (which yields g_c). FedUL can incorporate existing supervised FL methods as its base method for surrogate training, and the wanted model can be retrieved from the surrogate model.

functions. Then we implement it by adding a transition layer to the output of each client model, so that the learned model is guaranteed to be a good approximation of the original class probability.

On one hand, FedUL is a very general and flexible: it works as a wrapper that transforms the original clients to the surrogate ones, such that it is compatible with many supervised FL methods, e.g., FedAvg, and add no additional communication cost. On the other hand, FedUL is computationally efficient and easy-to-implement: since the added transformation layer is fixed and determined by the class priors, FedUL adds no more burden on hyper-parameter tuning and/or optimization. Our contributions can be summarized as follows:

- Methodologically, we propose a novel FedUL method that employs a surrogate FL task, providing new perspectives for dealing with U data in FL.
- Theoretically, we prove that the optimal global model learned by FedUL with only U data converges to the optimal global model learned by supervised FL with fully labeled data under mild conditions.
- Empirically, we demonstrate the effectiveness of FedUL on benchmark and real-world datasets.

Related Work: FL has been extensively studied in the supervised setting. One of the most popular supervised FL paradigms is FedAvg (McMahan et al., 2017) which aggregates the local updates at the server and transmits the averaged model back to local clients. In contrast, FL in the unsupervised setting is less explored. Recent studies have shown the possibility of federated clustering with U data (Ghosh et al., 2020; Dennis et al., 2021). However, these clustering based methods rely on geometric or information-theoretic assumptions to build their learning objectives (Chapelle et al., 2006), and are sub-optimal for classification goals. Our work is intrinsically different from them in the sense that we show the possibility of federated classification with U data based on *empirical risk minimization* (ERM) (Vapnik, 1998), and therefore the optimal model recovery can be guaranteed.

Learning from U datasets has also been studied in the classical centralized learning. Mainstream directions include learning with label proportions (LLP) (Quadrianto et al., 2009b) and U^m classification (Lu et al., 2021). The former learns a multi-class classifier from U datasets based on *empirical proportion risk minimization* (EPRM) (Yu et al., 2014), while the latter learns a binary classifier from U datasts based on ERM. EPRM is inferior to ERM since its learning is not consistent. Yet, it is still unexplored how to learn a multi-class classification model from U datasets based on ERM. To the best of our knowledge, this work is the first attempt to tackle this problem in the FL setup, which is built upon the binary U^m classification in the centralized learning.

2 STANDARD FEDERATED LEARNING

In this section, we review standard FL of a classification model. We consider a K-class classification problem with the feature space $\mathcal{X} \subset \mathbb{R}^d$ and the label space $\mathcal{Y} = [K]$, where d is the input dimension and $[K] := \{1, \ldots, K\}$. Let $\boldsymbol{x} \in \mathcal{X}$ and $y \in \mathcal{Y}$ be the input and output random variables following an underlying joint distribution with density $p(\boldsymbol{x}, y)$, which can be identified via the class priors $\{\pi^k = p(y = k)\}_{k=1}^K$ and the class-conditional densities $\{p(\boldsymbol{x} \mid y = k)\}_{k=1}^K$. Let $\boldsymbol{f} : \mathcal{X} \to \mathbb{R}^K$ be a classification model that assigns a score to each of the K classes for a given input $\boldsymbol{x}$ and then outputs the predicted label by $y_{\text{pred}} = \operatorname{argmax}_{k \in [K]}(\boldsymbol{f}(\boldsymbol{x}))_k$, where $(\boldsymbol{f}(\boldsymbol{x}))_k$ is the k-th element of $\boldsymbol{f}(\boldsymbol{x})$.

In standard FL setup with C clients, each client $c \in [C]$ has access to a labeled training set $\mathcal{D}_c = \{(\boldsymbol{x}_i^c, y_i^c)\}_{i=1}^{n_c} \sim p_c(\boldsymbol{x}, y)$ of sample size n_c and learns its local model $\boldsymbol{f}_c$ by minimizing the following risk:

$$R_c(\boldsymbol{f}_c) := \mathbb{E}_{(\boldsymbol{x},y) \sim p_c(\boldsymbol{x},y)}[\ell(\boldsymbol{f}_c(\boldsymbol{x}), y)], \tag{1}$$

where $\mathbb{E}$ denotes the expectation, $\ell : \mathbb{R}^K \times \mathcal{Y} \to \mathbb{R}_+$ is a proper loss function, e.g., the *softmax cross-entropy loss*, i.e., $\ell_{\text{ce}}(\boldsymbol{f}_c(\boldsymbol{x}), y) = -\sum_{k=1}^K \mathbf{1}(y = k) \log(\boldsymbol{f}_c(\boldsymbol{x}))_k = -\log(\boldsymbol{f}_c(\boldsymbol{x}))_y$, and $\mathbf{1}(\cdot)$ is the indicator function. In practice, ERM is a common practice that computes an approximation of $R_c(\boldsymbol{f}_c)$ based on the client's local data $\mathcal{D}_c$ by $\widehat{R}_c(\boldsymbol{f}_c; \mathcal{D}_c) = \frac{1}{n_c} \sum_{i=1}^{n_c} \ell(\boldsymbol{f}_c(\boldsymbol{x}_i^c), y_i^c)$.

The goal of standard FL (McMahan et al., 2017) is that the C clients collaboratively train a global classification model $\boldsymbol{f}$ that generalizes well with respect to $p(\boldsymbol{x}, y)$, without sharing their local data $\mathcal{D}_c$. The problem can be formalized as minimizing the aggregated risk:

$$R(\boldsymbol{f}) = \frac{1}{C} \sum_{c=1}^C R_c(\boldsymbol{f}). \tag{2}$$

In practice, we typically employ a server to coordinate the iterative distributed training as follows:

- in each global round of training, the server broadcasts its current model $\boldsymbol{f}$ to all the clients $\{\boldsymbol{f}_c\}_{c=1}^C$;
- each client c copies the current server model $\boldsymbol{f}_c = \boldsymbol{f}$, performs L local step updates:

$$\boldsymbol{f}_c \leftarrow \boldsymbol{f}_c - \alpha_l \cdot \nabla \widehat{R}_c(\boldsymbol{f}_c; \mathcal{D}_c), \tag{3}$$

  where α_l is the local step-size, and sends $\boldsymbol{f}_c - \boldsymbol{f}$ back to the server;
- the server aggregates the updates from all clients $\{\boldsymbol{f}_c - \boldsymbol{f}\}_{c=1}^C$ to form the new server model using FedAvg:

$$\boldsymbol{f} \leftarrow \boldsymbol{f} - \alpha_g \cdot \sum_{c=1}^C (\boldsymbol{f}_c - \boldsymbol{f}), \tag{4}$$

  where α_g is the global step-size.

3 FEDERATED LEARNING: NO LABEL NO CRY

In this section, we formulate the novel problem setting of FL with only unlabeled datasets, propose our method called *federation of unsupervised learning* (FedUL), and provide theoretical analysis of FedUL. All the proofs are given in Appendix C.

3.1 PROBLEM FORMULATION

In this paper, we consider a challenging setting: instead of fully labeled training data, each client $c \in [C]$ observes M_c $(M_c \geq K, \forall c)$[1] sets of *unlabeled* samples, $\mathcal{U}_c = \{\mathcal{U}_c^m\}_{m=1}^{M_c}$, where $\mathcal{U}_c^m = \{\boldsymbol{x}_i^{c,m}\}_{i=1}^{n_{c,m}}$ denotes the collection of the m-th U set for client c with sample size $n_{c,m}$. Each U set can be seen as a set of data points drawn from a mixture of the original class-conditional densities:

$$\mathcal{U}_c^m \sim p_c^m(\boldsymbol{x}) = \sum_{k=1}^K \pi_c^{m,k} p(\boldsymbol{x} \mid y = k), \tag{5}$$

---

[1]Note that we do not require each client has the same number of U sets. We only assume the condition $M_c \geq K, \forall c$ to ensure the full column rank matrix Π_c, which is essential for FL with U datasets.

where $\pi_c^{m,k} = p_c^m(y = k)$ denotes the k-th class prior of the m-th U set. These class priors form a full column rank matrix $\Pi_c \in \mathbb{R}^{M_c \times K}$ with the constraint that each row sums up to 1. Note that we do not require *any* labels to be known, only assume the class priors within each of the involved data sets are available, i.e., the training class priors $\pi_c^{m,k}$ and the test class prior $\pi^k = p(y = k)$.

Our goal is the same as standard FL, i.e., the C clients are interested in collaboratively training a global classification model $\boldsymbol{f}$ that generalizes well with respect to $p(\boldsymbol{x}, y)$, but using only unlabeled datasets $\mathcal{U}_c$ on each local client.

3.2 PROPOSED METHOD

As introduced in Section 2, FedAvg is a representative approach for aggregating clients in the FL framework and serves as the basis for many advanced federated aggregation techniques, e.g., Fedprox (Li et al., 2020), FedNova (Wang et al., 2020), and SCAFFOLD (Karimireddy et al., 2020). However, these methods cannot handle clients *without* labels, which are necessary for them to compute the local gradients. To tackle this problem, we consider the construction of *surrogate clients* by transforming the local U datasets to labeled datasets and modifying the local models so that they are compatible with the transformed data for updating.

Local Data Transformation First, we transform the data of the clients. For each client $c \in [C]$, let $\overline{y}$ be the index of given U sets, and $\overline{p}_c(\boldsymbol{x}, \overline{y})$ be an underlying joint distribution for the random variables $\boldsymbol{x} \in \mathcal{X}$ and $\overline{y} \in [M]$, where $M = \max_{c \in [C]} M_c$.[2] By treating $\overline{y}$ as a *surrogate label*, we may transform the original U training sets $\mathcal{U}_c = \{\mathcal{U}_c^m\}_{m=1}^{M_c}$ to a labeled training set for client c,

$$\overline{\mathcal{U}}_c = \{\boldsymbol{x}_i, \overline{y}_i\}_{i=1}^{n_c} \sim \overline{p}_c(\boldsymbol{x}, \overline{y}). \tag{6}$$

Obviously, the surrogate class-conditional density $\overline{p}_c(\boldsymbol{x} \mid \overline{y} = m)$ corresponds to $p_c^m(\boldsymbol{x})$ in Eq. (5), for $m \in [M_c]$. If $\exists M_c < m \leq M$, we pad $\overline{p}_c(\boldsymbol{x} \mid \overline{y} = m) = 0$. The surrogate class-prior $\overline{\pi}_c^m = \overline{p}_c(\overline{y} = m)$ can be estimated by $\overline{\pi}_c^m = n_{c,m}/(\sum_{m=1}^{M_c} n_{c,m})$.

Based on the data transformation, we then formulate a *surrogate supervised FL task*: the C clients aim to collaboratively train a global classification model $\boldsymbol{g} : \mathcal{X} \to \mathbb{R}^M$ that predicts surrogate labels $\overline{y}$ for given inputs $\boldsymbol{x}$, without sharing their local data $\overline{\mathcal{U}}_c$. This task can be easily solved by standard supervised FL methods. More specifically, we minimize

$$J(\boldsymbol{g}) = \frac{1}{C} \sum_{c=1}^{C} J_c(\boldsymbol{g}) := \mathbb{E}_{(\boldsymbol{x}, \overline{y}) \sim \overline{p}_c(\boldsymbol{x}, \overline{y})}[\ell(\boldsymbol{g}(\boldsymbol{x}), \overline{y})] \tag{7}$$

by employing a server $\boldsymbol{g}$ that iteratively broadcasts its model to all local clients $\{\boldsymbol{g}_c\}_{c=1}^C$ and aggregates local updates from all clients using e.g., FedAvg, where the local and global update procedures exactly follow Eq. (3) and Eq. (4) in standard FL.

Now, a natural question arises: can we *infer* our desired classification model $\boldsymbol{f}$ from the surrogate model $\boldsymbol{g}$? To answer this question, we study the relationship of the original and surrogate class probabilities in the following theorem.

Theorem 1. *For each client $c \in [C]$, let $\overline{\boldsymbol{\eta}}_c : \mathcal{X} \to \Delta_{M-1}$ and $\boldsymbol{\eta} : \mathcal{X} \to \Delta_{K-1}$ be the surrogate and original class probability functions, where $(\overline{\boldsymbol{\eta}}_c(\boldsymbol{x}))_m = \overline{p}_c(\overline{y} = m \mid \boldsymbol{x})$ for $m \in [M]$, $(\boldsymbol{\eta}(\boldsymbol{x}))_k = p(y = k \mid \boldsymbol{x})$ for $k \in [K]$, Δ_{M-1} and Δ_{K-1} are the M- and K-dimensional simplexes. Let $\overline{\boldsymbol{\pi}}_c = [\overline{\pi}_c^1, \cdots, \overline{\pi}_c^M]^\top$ and $\boldsymbol{\pi} = [\pi^1, \cdots, \pi^K]^\top$ be vector forms of the surrogate and original class priors, and $\Pi_c \in \mathbb{R}^{M \times K}$ be the matrix form of $\pi_c^{m,k}$ defined in Eq. (5). Then we have*

$$\overline{\boldsymbol{\eta}}_c(\boldsymbol{x}) = \boldsymbol{Q}_c(\boldsymbol{\eta}(\boldsymbol{x}); \boldsymbol{\pi}, \overline{\boldsymbol{\pi}}_c, \Pi_c), \tag{8}$$

where the unnormlized version of vector valued function $\boldsymbol{Q}_c$ is given by

$$\widetilde{\boldsymbol{Q}}_c(\boldsymbol{\eta}(\boldsymbol{x}); \boldsymbol{\pi}, \overline{\boldsymbol{\pi}}_c, \Pi_c) = D_{\overline{\boldsymbol{\pi}}_c} \cdot \Pi_c \cdot D_{\boldsymbol{\pi}}^{-1} \cdot \boldsymbol{\eta}(\boldsymbol{x}).$$

$D_{\boldsymbol{a}}$ denotes the diagonal matrix with diagonal terms being vector $\boldsymbol{a}$ and $\cdot$ denotes matrix multiplication. $\boldsymbol{Q}_c$ is normalized by the sum of all entries, i.e., $(\boldsymbol{Q}_c)_i = \frac{(\widetilde{\boldsymbol{Q}}_c)_i}{\sum_j (\widetilde{\boldsymbol{Q}}_c)_j}$.

---

[2] To make the problem well-defined, for client c with $M_c < M$, we set $\mathcal{U}_c^m = \emptyset, \forall M_c < m \leq M$.

Algorithm 1 Federation of unsupervised learning (FedUL)

Server Input: initial $\boldsymbol{f}$, global step-size α_g, and global communication round R

Client c's Input: local model $\boldsymbol{f}_c$, unlabeled datasets $\mathcal{U}_c = \{\mathcal{U}_c^m\}_{m=1}^{M_c}$, class priors Π_c and $\boldsymbol{\pi}$, local step-size α_l, and local updating iterations L

1: We start with initializing clients with **Procedure A**.
2: For $r = 1 \to R$ rounds, we run **Procedure B** and **Procedure C** iteratively .
3: **procedure A**. CLIENTINIT(c)
4:      transform $\mathcal{U}_c$ to a surrogate labeled dataset $\overline{\mathcal{U}}_c$ according to Eq. (6)
5:      modify $\boldsymbol{f}$ to $\boldsymbol{g}_c = \boldsymbol{Q}_c(\boldsymbol{f})$, where $\boldsymbol{Q}_c$ is computed according to Theorem 1
6: **end procedure**
7: **procedure B**. CLIENTUPDATE(c)
8:      $\boldsymbol{f}_c \leftarrow \boldsymbol{f}$ ▷ Receive updated model from SERVEREXECUTE
9:      $\boldsymbol{g}_c \leftarrow \boldsymbol{Q}_c(\boldsymbol{f}_c)$
10:     **for** $l = 1 \to L$ **do**
11:        $\boldsymbol{g}_c \leftarrow \boldsymbol{g}_c - \alpha_l \cdot \nabla \widehat{J}_c(\boldsymbol{g}_c; \overline{\mathcal{U}}_c)$ ▷ SGD updates based on objective Eq. (7)
12:        $\boldsymbol{f}_c \leftarrow \boldsymbol{f}_c - \alpha_l \cdot \nabla \widehat{J}_c(\boldsymbol{Q}_c(\boldsymbol{f}_c); \overline{\mathcal{U}}_c)$ ▷ The update on $\boldsymbol{g}_c$ induces an update on $\boldsymbol{f}_c$
13:     **end for**
14:     send $\boldsymbol{f}_c - \boldsymbol{f}$ to SERVEREXECUTE
15: **end procedure**
16: **procedure C**. SERVEREXECUTE(r)
17:     receive local models' updates $\boldsymbol{f}_c - \boldsymbol{f}$ from CLIENTUPDATE
18:     $\boldsymbol{f} \leftarrow \boldsymbol{f} - \alpha_g \cdot \sum_{c=1}^{C}(\boldsymbol{f}_c - \boldsymbol{f})$ ▷ FL aggregation
19:     broadcast $\boldsymbol{f}$ to CLIENTUPDATE
20: **end procedure**

Note that $\boldsymbol{\pi}, \overline{\boldsymbol{\pi}}_c$, and Π_c are all fixed, $\boldsymbol{Q}_c$ is deterministic and can be identified with the knowledge of $\boldsymbol{\pi}, \Pi_c$, and an estimate of $\overline{\boldsymbol{\pi}}_c$. In addition, we note that if $M_c < M$, the last $M - M_c$ entries of $\boldsymbol{Q}_c$ are padded with zero by construction. We further study the property of $\boldsymbol{Q}_c$ in the following lemma.

Lemma 2. *For each client $c \in [C]$, the transition function $\boldsymbol{Q}_c : (\mathcal{X} \to \Delta_K) \to (\mathcal{X} \to \Delta_M)$ defined in Theorem 1 is an injective function.*

In this sense, the transition function $\boldsymbol{Q}_c$ naturally bridges the class probability of our *desired* task $\boldsymbol{\eta}(\boldsymbol{x})$ and that of the *learnable* surrogate task $\overline{\boldsymbol{\eta}}_c(\boldsymbol{x})$ given only unlabeled datasets. This motivates us to embed the estimation of $\boldsymbol{\eta}(\boldsymbol{x})$ into the estimation of $\overline{\boldsymbol{\eta}}_c(\boldsymbol{x})$ at each client.

Local model modification   Second, we modify the model for the clients. Let $\boldsymbol{f}(\boldsymbol{x})$ be the original global model output that estimates $\boldsymbol{\eta}(\boldsymbol{x})$. At each client $c \in [C]$, we implement $\boldsymbol{Q}_c$ by adding a transition layer following $\boldsymbol{f}$ and then we have $\boldsymbol{g}_c(\boldsymbol{x}) = \boldsymbol{Q}_c(\boldsymbol{f}(\boldsymbol{x}))$. Based on the model transformation, Eq. (7) can be reformulated as follows:

$$J(\boldsymbol{f}) = \frac{1}{C}\sum_{c=1}^{C} J_c(\boldsymbol{Q}_c(\boldsymbol{f})) := \mathbb{E}_{(\boldsymbol{x}, \overline{y}) \sim \overline{p}_c(\boldsymbol{x}, \overline{y})}[\ell(\boldsymbol{Q}_c(\boldsymbol{f}(\boldsymbol{x})), \overline{y})]. \tag{9}$$

Therefore, local updates on the surrogate client model $\boldsymbol{g}_c$ naturally yield updates on the underlying model $\boldsymbol{f}$. Now we can aggregate these surrogate clients with our selected standard FL scheme. A detailed algorithm, using FedAvg as an example, is given in Algorithm 1.

Remarks   The relationship elucidating the supervised and surrogate FL paradigms (for a single client) is visually shown in Figure 2. The blue part illustrates a supervised FL scheme: the global model is $\boldsymbol{f}(\boldsymbol{x})$ parameterized by $\boldsymbol{\theta}$; the loss is $R(\boldsymbol{f}; y)$ in Eq. (2) where labels y are observed. However, we cannot observe y and thus employ a surrogate FedUL scheme which is shown in green: the global model is $\boldsymbol{g}(\boldsymbol{x})$ directly modified from $\boldsymbol{f}$; the loss is $J(\boldsymbol{g}; \overline{y})$ in Eq. (7) where $\overline{y}$ are surrogate labels.

Figure 2: Graphical representation of supervised FL (in blue) and FedUL (in green)

3.3 THEORETICAL ANALYSIS

In what follows, we provide theoretical analysis on the convergence and optimal model recovery for the proposed method.

Convergence of the algorithm   In supervised FL, convergence analysis has been studied with regularity conditions (see Section 3.2.2 in Kairouz et al. (2019) for a comprehensive survey), e.g. bounded gradient dissimilarity (Karimireddy et al., 2020) that associates the client model with the server model for non-IID data distributions.[3] In our analysis, we focus on the behaviour of our surrogate learning objective J with the effect from transformation $\boldsymbol{Q}_c$.

Proposition 3 (Theorem V in Karimireddy et al. (2020)). *Assume that $J(\boldsymbol{g})$ in Eq. (7) satisfies (A1)-(A3) in Appendix C.3. Denote $\boldsymbol{g}^* = \operatorname{argmin}_{\boldsymbol{g} \in \mathcal{G}} \widehat{J}(\boldsymbol{g})$, where $\widehat{J}(\boldsymbol{g}) = \frac{1}{C} \sum_{c=1}^{C} \widehat{J}_c(\boldsymbol{g}) :=$ $\frac{1}{n_c} \sum_{i=1}^{n_c} \ell(\boldsymbol{g}(\boldsymbol{x}_i), \overline{y}_i)$. Let the global step-size $\alpha_g \geq 1$ and local step-size $\alpha_l \leq \frac{1}{8(1+B^2)\beta L \alpha_g}$, FedUL given by Algorithm 1 is expected to have contracting gradient: with the initialized model $\boldsymbol{g}^0$, $F := J(\boldsymbol{g}^0) - J(\boldsymbol{g}^*)$ and constant $M = \sigma\sqrt{1 + \frac{C}{\eta_g^2}}$, in R rounds, the learned model $\boldsymbol{g}^R$ satisfies*

$$\mathbb{E}[\|\nabla J(\boldsymbol{g}^R)\|^2] \leq \mathcal{O}\left(\frac{\beta M \sqrt{F}}{\sqrt{RLC}} + \frac{\beta^{1/3}(FG)^{2/3}}{(R+1)^{2/3}} + \frac{\beta B^2 F}{R}\right).$$

Note that the proposition statement is w.r.t. the convergence of $\boldsymbol{g}$ learned from the surrogate task. By model construction, $\boldsymbol{g}$ is built from $\boldsymbol{Q}_c(\boldsymbol{f})$. By Lemma 2, the convergence of trained model $\boldsymbol{g}$ to the optimal model $\boldsymbol{g}^*$ in the function class $\mathcal{G}$ implies the convergence of the retrieved model $\boldsymbol{f}$ to the optimal model $\boldsymbol{f}^* = \operatorname{argmin}_{\boldsymbol{f} \in \mathcal{F}} \widehat{J}(\boldsymbol{f})$ in the corresponding function class $\mathcal{F}$ (induced by $\mathcal{G}$), where $\widehat{J}(\boldsymbol{f}) = \frac{1}{C} \sum_{c=1}^{C} \widehat{J}_c(\boldsymbol{Q}_c(\boldsymbol{f})) := \frac{1}{n_c} \sum_{i=1}^{n_c} \ell(\boldsymbol{Q}_c(\boldsymbol{f}(\boldsymbol{x}_i)), \overline{y}_i)$ is the empirical version of Eq. (9).

Optimal model recovery   In our context, the model is optimal in the sense that the minimizer of the surrogate task $J(\boldsymbol{f}; \overline{y})$ coincide with the minimizer of the supervised task $R(\boldsymbol{f}; y)$, as if all the data have been labeled. Based on the convergence of surrogate learning, we show that FedUL can recover this optimal model.

Theorem 4. *Assume that a proper loss function, e.g., the cross-entropy loss, is chosen for ℓ, and the model used for $\boldsymbol{g}$ is very flexible, e.g., deep neural networks, so that $\boldsymbol{g}^{**} \in \mathcal{G}$ where $\boldsymbol{g}^{**} = \operatorname{argmin}_{\boldsymbol{g}} J(\boldsymbol{g}; \overline{y})$. Let $\boldsymbol{f}^* = \operatorname{argmin}_{\boldsymbol{f} \in \mathcal{F}} \widehat{J}(\boldsymbol{f})$ be the optimal classifier learned with FedUL by Algorithm 1, and $\boldsymbol{f}^{\star} = \operatorname{argmin}_{\boldsymbol{f}} R(\boldsymbol{f}; y)$ be the optimal classifier learned with supervised FL. By assumptions in Proposition 3, we have $\boldsymbol{f}^* = \boldsymbol{f}^{\star}$.*

4 EXPERIMENTS

In this section, we conduct experiments to validate the effectiveness of the proposed FedUL method under various testing scenarios. Compared with alternative strategies, FedUL consistently achieves superior results on both benchmark and real-world datasets. The detailed experimental settings and additional supportive results are presented in the Appendix D & E.

4.1 BENCHMARK EXPERIMENTS

Settings: As proof-of-concepts, we first perform experiments on widely adopted benchmarks MNIST (LeCun et al., 1998) and CIFAR10 (Krizhevsky et al., 2009). For all experiments, we split 20% training data for validation and model selection. We generate M sets of U training data according to Eq. (5) for each client $c \in [C]$. The total number of training samples n_c on each client is fixed, and the number of instances contained in each set indexed by m is also fixed as n_c/M. In order to simulate the real world cases, we uniformly select class priors $\pi_c^{m,k} = p_c^m(y = k)$ from range $[0.1, 0.9]$ and then regularize them to formulate a valid $\Pi_c \in \mathbb{R}^{M_c \times K}$ as discussed in Section 3.1.

---

[3]The IID case is equivalent to batch sampling from the same distribution, where the analysis is less interesting associated with our FL setting and we omit here.

Table 1: Quantitative comparison of our method with the baseline methods on benchmark datasets under IID and Non-IID setting (mean error (std)). The best method (paired t-test at significance level 5%) is highlighted in boldface.

IID Task with 5 Clients

Dataset	Sets	FedPL	FedLLP	FedLLP-VAT	FedUL	FedAvg 10%
MNIST	10	2.12 (0.10)	19.00 (15.90)	20.53 (5.39)	**0.78 (0.06)**	
	20	2.98 (0.15)	4.38 (3.95)	4.40 (5.11)	**1.12 (0.09)**	1.79 (0.09)
	40	3.90 (0.22)	10.11 (15.74)	11.96 (9.56)	**1.00 (0.29)**	
CIFAR10	10	34.60 (0.30)	77.01 (5.02)	77.56 (8.71)	**18.56 (0.04)**	
	20	42.06 (1.63)	78.74 (6.96)	84.18 (5.95)	**19.66 (0.30)**	32.85 (1.03)
	40	46.20 (0.67)	73.75 (4.78)	78.65 (6.91)	**20.31 (0.69)**	

Non-IID Task with 5 Clients

Dataset	Sets	FedPL	FedLLP	FedLLP-VAT	FedUL	FedAvg 10%
MNIST	10	15.54 (3.48)	20.52 (15.00)	23.39 (15.34)	**2.98 (1.72)**	
	20	7.54 (2.77)	6.63 (7.94)	11.76 (6.60)	**1.77 (0.49)**	3.82 (1.56)
	40	5.76 (0.90)	5.53 (2.51)	7.82 (10.73)	**1.64 (0.18)**	
CIFAR10	10	70.65 (2.38)	81.12 (5.41)	81.55 (7.09)	**42.92 (3.02)**	
	20	63.53 (1.24)	65.51 (13.16)	70.51 (7.66)	**35.24 (0.98)**	58.62 (8.63)
	40	53.78 (0.13)	65.72 (3.93)	60.23 (5.71)	**31.43 (1.72)**	

For model training, we use the cross-entropy loss and Adam (Kingma & Ba, 2015) optimizer with a learning rate of $1e-4$ and train 100 rounds. If not specified, our default setting for local update epochs (E) is 1 and batch size (B) is 128 with 5 clients (C) in our FL system. We use LeNet (LeCun et al., 1998) and ResNet18 (He et al., 2016) as backbone for MNIST and CIFAR10, respectively. Here, we investigate two different FL settings: **IID** and **Non-IID**, where the overall label distribution across clients is the same in the IID setting, whereas clients have different overall label distributions in the non-IID setting. Specially, for Non-IID setting, we impose class-prior shift following:

- The classes are divided into the majority and minority classes, where the fraction of each minority class is less than 0.08 while the fraction of each majority class is in the range $[0.15, 0.25]$.
- The training data for every client are sampled from 2 majority classes and 8 minority classes.
- The test data are uniformly sampled from all classes.

Baselines: We compare our method with the following baselines: (1) Federated Pseudo labeling (FedPL) (Diao et al., 2021): At each client of a FedAvg system, we choose the label with the largest class prior in a U set as the pseudo labels for all the data in this set. During local training, the pseudo labels are boosted by *Mixup* (Zhang et al., 2017) high-confidence data and low-confidence data, where the confidence is given by model predictions. (2) Federated LLP (FedLLP) (Dulac-Arnold et al., 2019): We update each client model by minimizing the distance between ground truth label proportion and the predicted label proportion, and aggregate them using FedAvg; (3) FedLLP with virtual adversarial training (FedLLP-VAT) (Tsai & Lin, 2020): We add a consistency term to FedLLP as regularization for optimizing client model in FedAvg. (4) FedAvg with 10% labeled data (FedAvg 10%): Followng he classical unsupervised classification literature (Chen et al., 2020), we compare with supervised training using FedAvg on only 10% of total data samples with true labels. The detailed baseline settings are depicted in Appendix D.

Results and Analysis: Table 1 shows the results of our method and baselines on two benchmark datasets under IID and Non-IID settings. The results are reported in mean error (std) format over clients with three independent runs. Given the limited number of total data available in the benchmark datasets, we compare our method with baselines in an FL system with five clients and vary the number of sets in each client $M \in \{10, 20, 40\}$. In this regard, each set contains a sufficient number of data samples to train the model.

Note that our proposed FedUL method outperforms other baseline methods by a large margin under both Non-IID and IID settings. Moreover, we have the following observations: 1) When varying the number of sets $M \in \{10, 20, 40\}$, FedUL not only achieves lower classification errors but also shows more stable performance compared to baselines; 2) As we use FedAvg as the default aggregation method for all the strategies, the performances of FedUL, FedPL, and FedAvg all degrade under the

Figure 3: Ablation studies on MNIST under a Non-IID FL system. (a) Study on the robustness of our method with noisy priors. (b) Effects of the number of accessible Non-IID data. (c) Analysis of local updating epochs. (d) Effects of training batch size.

inter client Non-IID setting, as expected. The error rates of FedLLP and FedLLP-VAT are high and unstable, which demonstrates that the EPRM based methods are inferior as discussed in Section 1.

4.2 ABLATION STUDIES

In the following, we present a comprehensive investigation on the ablation studies of the proposed FedUL method on MNIST benchmark.

Robustness with Noisy Priors: To investigate the robustness of our method, we further apply FedUL in a noisy environment. Specifically, the class priors $\pi_c^{m,k}$ are perturbed by a random noise γ. In this case, the noisy class prior $\widetilde{\pi}_c^{m,k} = \pi_c^{m,k} \cdot ((2\epsilon - 1)\gamma + 1)$, where γ uniform randomly take values in $[0, 1]$ and $\epsilon \in \{0, 0.2, 0.4, 0.8, 1.6\}$, so that the method would treat noisy $\widetilde{\pi}_c^{m,k} \in [\pi_c^{m,k}(1 - \gamma), \pi_c^{m,k}(1 + \gamma)]$ as the true $\pi_c^{m,k}$ during the whole learning process. The experimental setup is the same as before except for the replacement of $\pi_c^{m,k}$. Note that we tailor the noisy $\pi_c^{m,k}$ to $[0, 1]$ if it surpasses the range. Here we conduct experiments with five clients and ten sets in every client. From Figure 3(a), we can see that FedUL performs stably even with very challenging noise perturbation (the noise ratio $\epsilon > 0$).

Effects of the Number of Accessible Non-IID Data: The purpose of FL is utilizing more data to empower model performance. While how unlabeled data, especially unlabeled Non-IID data, can contribute to FL model performance needs investigation. To this end, we analyze the effects of the number of accessible Non-IID data. We set each client with $n_c = 500$ samples $\forall c \in [C]$ and conduct experiments by changing the amount of accessible Non-IID data by increasing the number of clients $C \in \{10, 20, 30, 40, 50\}$. As shown in Figure 3(b), the model performance improves by a large margin as the number of accessible Non-IID data increases.

Analysis of Local Updating Epochs: The frequency of aggregation may sometimes influence the model performance in an FL system. We would like to explore if FedUL is stable when the local clients are updated with different local epochs E. In Figure 3(c), we explore $E \in \{1, 2, 4, 8, 16\}$ with fixed $B = 128$ and $C = 5$. The results demonstrate that with different E, the performance of FedUL are reasonably stable.

Effects of Batch Size: The training batch size is always an important factor in machine learning tasks, especially in an FL system. Hence here, we study how batch size affects our model performance. Specifically, we train the model using three different batch sizes $B \in \{16, 64, 128, 512, \infty\}$ with fixed $E = 1$ and $C = 5$. Here $B = \infty$ stands for loading all of the samples from the training data into a single batch. The results in Figure 3(d) indicate that FedUL can effectively work under a wide range of batch sizes.

4.3 CASE STUDY ON REAL-WORLD PROBLEM

To demonstrate the feasibility of our proposed FedUL scheme to the real problem, we test FedUL on a medical application for the diagnosis of brain disease. In the rest of this section, we introduce the problem formulation, data and setting, and then discuss the results.

Real Problem Formulation: For a real-world scenario, we consider a clinical setting for disease classification in C different healthcare systems. Suppose each healthcare system has M hospitals located in different regions, each associated with a unique class priors due to population diversities.

Table 2: Quantitative comparison of our method with the baseline methods for the five healthcare systems (HS) using the real-world intracranial hemorrhage detection dataset. Results of three runs are reported in mean error (std) format. The best methods are highlighted in boldface.

Hospitals	Method	HS 1	HS 2	HS 3	HS 4	HS 5
12	FedPL	44.69 (4.28)	46.42 (4.35)	46.29 (1.83)	47.55 (2.84)	46.53 (2.40)
	FedUL (ours)	**40.26 (1.39)**	**40.35 (1.10)**	**39.31 (1.10)**	**39.72 (0.67)**	**39.43 (1.42)**
24	FedPL	42.71 (2.97)	42.18 (3.00)	42.30 (1.28)	41.79 (1.98)	41.46 (0.53)
	FedUL (ours)	**32.27 (2.71)**	**30.99 (2.03)**	**31.29 (1.05)**	**31.72 (1.23)**	**31.37 (1.58)**
48	FedPL	41.44 (3.04)	40.38 (1.38)	41.06 (2.88)	41.44 (1.78)	40.26 (2.35)
	FedUL (ours)	**31.48 (2.25)**	**30.92 (0.88)**	**31.16 (0.84)**	**31.55 (0.58)**	**30.57 (1.37)**
-	FedAvg 10%	46.79 (1.91)	46.44 (0.78)	47.19 (1.05)	47.29 (1.93)	46.20 (1.61)

(a) Healthy   (b) Epidural   (c) Intraparenchymal   (d) Intraventricular   (e) Subarachnoid   (f) Subdural

Figure 4: Example samples of each class in the distributed medical dataset (Flanders et al., 2020).

Medical data are not shareable between the healthcare systems for privacy. We assume patient-wise diagnosis information is unavailable, but each hospital provides the prevalence of these patients (a.k.a. class priors of the disease classes).

Dataset and Settings: We use the RSNA Intracranial Hemorrhage Detection dataset (Flanders et al., 2020) (Fig. 4) to simulate this real-world scenario. This dataset contains large-scale Magnetic Response Image (MRI) data from several hospitals. There are $106k$ samples in the dataset belonging to six classes, including five types of intracranial hemorrhage (Epidural, Intraparenchymal, Intraventricular, Subarachnoid, and Subdural) and healthy control type. We model an FL system with five healthcare systems (a.k.a clients). Each healthcare system contains $21.2k$ data samples. To show the effect on the number of samples in each set, we vary the number of hospitals (a.k.a sets) in each system $M = 12, 24$, and 48. Here we generate each $\pi_c^{m,k}$ for the k-th class in m-th set at c-th client from range $[0.1, 0.9]$ and check that the generated class priors are not all identical. For model training, we use the cross-entropy loss and Adam (Kingma & Ba, 2015) optimizer with a learning rate of $1e-4$ and train 100 rounds. We use ResNet18 (He et al., 2016) as backbone for experiments.

Results and Analysis: As indicated in our proof of concept (Table 1), FedPL consistently outperforms the other two LLP baselines, i.e., FedLLP and FedLLP-VAT. Here we focus on comparing FedUL with FedPL. We also include the supervised baseline FedAvg with 10% data. We report the results of each hospital in mean error (std) format over three runs in Table 2. We can see that our method FedUL consistently outperforms FedPL and FedAvg 10% for all the hospitals and under different site number settings. The superiority of FedUL in this challenging real-world FL system further indicates the effectiveness and robustness of our algorithm. These results are inspiring and bring the hope of deploying FedUL to the healthcare field, where data are often very costly to be labeled, heterogeneous, and distributed.

5   CONCLUSION

In this paper, we propose FedUL, a novel FL algorithm using only U data. FedUL works as a wrapper that transforms the client data and modify the client model to form a surrogate supervised learning task, which can be easily solved using existing FL paradigms. Theoretically, we prove that the optimal model learned by supervised FL can be recovered from the FedUL training scheme under mild conditions. Through extensive experiments on benchmark and real datasets, we show FedUL can significantly overperform the baseline methods under different settings. As a wrapper, we expect FedUL can be further improved by incorporating advanced FL aggregation or optimization schemes for the non-IID setting (Wang et al., 2020; Li et al., 2020; 2021; Karimireddy et al., 2020).

ETHICS STATEMENT

Collecting sample-wise labels for training can be costly and may violate data privacy. Considering data in the real world are often collected distributed, we provide a pioneer and promising solution to perform multi-class classification on distributed U data in the FL system. Our method FedUL can be widely applied to data-sensitive fields, such as healthcare, politics, and finance, where the sample-wise label is not available, but populational prevalence can be accessed. With FedUL, we hope the future FL can enjoy significant labeling cost reduction and improve its privacy. Therefore, we believe our proposed method and its potential application have a positive impact on society. The real datasets used in this work are publicly available with appropriate prepossessing to de-identify patients' identities. We provide proper references to the datasets, libraries, and tools used in our study. This study does not have any legal compliance, conflict of interest, or research integrity issues.

REPRODUCIBILITY STATEMENT

We provide the codes to reproduce the main experimental results via the anonymous download link indicated in Appendix. We further provide experimental details and additional information of the datasets in the supplementary materials.

REFERENCES

Dimitri P Bertsekas. Nonlinear programming. *Journal of the Operational Research Society*, 48(3): 334–334, 1997.

Elvis Camacho, Melissa A LoPresti, Sam Bruce, Derek Lin, Mickey Abraham, Geoff Appelboom, Blake Taylor, Michael McDowell, Byron DuBois, Mihika Sathe, et al. The role of age in intracerebral hemorrhages. *Journal of Clinical Neuroscience*, 22(12):1867–1870, 2015.

O. Chapelle, B. Schölkopf, and A. Zien (eds.). *Semi-Supervised Learning*. MIT Press, 2006.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020.

Janet B Croft, Anne G Wheaton, Yong Liu, Fang Xu, Hua Lu, Kevin A Matthews, Timothy J Cunningham, Yan Wang, and James B Holt. Urban-rural county and state differences in chronic obstructive pulmonary disease—united states, 2015. *Morbidity and Mortality Weekly Report*, 67 (7):205, 2018.

Pieter-Tjerk De Boer, Dirk P Kroese, Shie Mannor, and Reuven Y Rubinstein. A tutorial on the cross-entropy method. *Annals of operations research*, 134(1):19–67, 2005.

Don Kurian Dennis, Tian Li, and Virginia Smith. Heterogeneity for the win: One-shot federated clustering. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 2611–2620. PMLR, 18–24 Jul 2021.

Enmao Diao, Jie Ding, and Vahid Tarokh. Semifl: Communication efficient semi-supervised federated learning with unlabeled clients. *arXiv preprint arXiv:2106.01432*, 2021.

Gabriel Dulac-Arnold, Neil Zeghidour, Marco Cuturi, Lucas Beyer, and Jean-Philippe Vert. Deep multi-class learning from label proportions. *arXiv preprint arXiv:1905.12909*, 2019.

Adam E Flanders, Luciano M Prevedello, George Shih, Safwan S Halabi, Jayashree Kalpathy-Cramer, Robyn Ball, John T Mongan, Anouk Stein, Felipe C Kitamura, Matthew P Lungren, et al. Construction of a machine learning dataset through collaboration: the rsna 2019 brain ct hemorrhage challenge. *Radiology: Artificial Intelligence*, 2(3):e190211, 2020.

Avishek Ghosh, Jichan Chung, Dong Yin, and Kannan Ramchandran. An efficient framework for clustered federated learning. In *Proceedings of the 34th Conference on Neural Information Processing Systems*, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Peter Kairouz, H Brendan McMahan, Brendan Avent, Aurélien Bellet, Mehdi Bennis, Arjun Nitin Bhagoji, Kallista Bonawitz, Zachary Charles, Graham Cormode, Rachel Cummings, et al. Advances and open problems in federated learning. *arXiv preprint arXiv:1912.04977*, 2019.

Sai Praneeth Karimireddy, Satyen Kale, Mehryar Mohri, Sashank Reddi, Sebastian Stich, and Ananda Theertha Suresh. Scaffold: Stochastic controlled averaging for federated learning. In *International Conference on Machine Learning*, pp. 5132–5143. PMLR, 2020.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *International Conference on Learning Representation*, pp. 1—-13, 2015.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. *Technical report*, 2009.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Tian Li, Anit Kumar Sahu, Manzil Zaheer, Maziar Sanjabi, Ameet Talwalkar, and Virginia Smith. Federated optimization in heterogeneous networks. In *Conference on Machine Learning and Systems, 2020a*, 2020.

Xiaoxiao Li, Meirui JIANG, Xiaofei Zhang, Michael Kamp, and Qi Dou. FedBN: Federated learning on non-IID features via local batch normalization. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=6YEQUn0QICG.

Nan Lu, Shida Lei, Gang Niu, Issei Sato, and Masashi Sugiyama. Binary classification from multiple unlabeled datasets via surrogate set classification. In *International Conference on Machine Learning*, pp. 7134–7144. PMLR, 2021.

Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial intelligence and statistics*, pp. 1273–1282. PMLR, 2017.

Dianwen Ng, Xiang Lan, Melissa Min-Szu Yao, Wing P Chan, and Mengling Feng. Federated learning: a collaborative effort to achieve better medical imaging models for individual sites that have small labelled datasets. *Quantitative Imaging in Medicine and Surgery*, 11(2):852, 2021.

N. Quadrianto, A. J. Smola, T. S. Caetano, and Q. V. Le. Estimating labels from label proportions. *Journal of Machine Learning Research*, 10:2349–2374, 2009a.

Novi Quadrianto, Alex J Smola, Tiberio S Caetano, and Quoc V Le. Estimating labels from label proportions. *Journal of Machine Learning Research*, 10(10), 2009b.

Mark D Reid and Robert C Williamson. Composite binary losses. *The Journal of Machine Learning Research*, 11:2387–2422, 2010.

Kuen-Han Tsai and Hsuan-Tien Lin. Learning from label proportions with consistency regularization. In *Asian Conference on Machine Learning*, pp. 513–528. PMLR, 2020.

V. N. Vapnik. *Statistical Learning Theory*. John Wiley & Sons, 1998.

Jianyu Wang, Qinghua Liu, Hao Liang, Gauri Joshi, and H Vincent Poor. Tackling the objective inconsistency problem in heterogeneous federated optimization. *arXiv preprint arXiv:2007.07481*, 2020.

Qiang Yang, Yang Liu, Tianjian Chen, and Yongxin Tong. Federated machine learning: Concept and applications. *ACM Transactions on Intelligent Systems and Technology (TIST)*, 10(2):1–19, 2019.

Felix X Yu, Krzysztof Choromanski, Sanjiv Kumar, Tony Jebara, and Shih-Fu Chang. On learning from label proportions. *arXiv preprint arXiv:1402.5902*, 2014.

Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. *arXiv preprint arXiv:1710.09412*, 2017.

Supplementary Material

Roadmap The appendix is organized as follows. We point to the shareable code and preprocessed data in Section A . We introduce the notations used in our paper in Section B. Our proofs are presented in Section C. We provide the detailed experimental settings in Section D. More results on the benchmark dataset are stated in Section E

A DATA AND CODE AVAILABILITY

The trained models, guidelines for data downloading and preparation, code for training, validation, testing of all the methods, readme file, libraries requirement, and environment setup for our benchmark experiments are available at the **anonymous link**: https://drive.google.com/drive/folders/1kcMO0_XoxoPFhv1ZgcZ6bV_HTzZo-zPs?usp=sharing. Due to size limitation, we could not share the preprocessed large scale real-world datasets. We are very happy to release all materials in the final version.

B NOTATION TABLE

Table B.1: Important notations occurred in the paper.

Notations	Description
K	number of classes in the underlying classification problem
d	input dimension
$\mathcal{X}$	input space $\mathcal{X} \subset \mathbb{R}^d$
$\mathcal{Y}$	label space $\mathcal{Y} = [K]$, where $[K] := \{1, \dots, K\}$
$\boldsymbol{x}$	inputs variable, which denotes samples $\boldsymbol{x} \in \mathcal{X}$
y	label variable of the inputs variable x
π^k	class prior of class k and we have $\{\pi^k := p(y = k)\}_{k=1}^K$
$\boldsymbol{f}$	a classification model that assigns a score to each of the K classes for a given input $\boldsymbol{x}$
C	number of clients in the FL, we index client by $c \in [C]$
$\mathcal{D}_c$	$\mathcal{D}_c = \{(\boldsymbol{x}_i^c, y_i^c)\}_{i=1}^{n_c} \sim p_c(\boldsymbol{x}, y)$
n_c	size of samples drawn from distribution for the c-th client
ℓ	loss function for the classification task
α_l	local step size
α_g	global step size
M_c	number of sets in client c
m	index of set m in a client c and $m \in [M_c]$
M	the maximum of the number of sets among all clients c
$\mathcal{U}_c^m$	the mth set of unlabeled data in client c
$\mathcal{U}_c$	unlabeled data in client c, $\mathcal{U}_c = \{\mathcal{U}_c^m\}_{m=1}^{M_c}$
$\bar{y}$	surrogate label and $\bar{y} \in [M]$
$\overline{\mathcal{U}}$	surrogate set and $\overline{\mathcal{U}}_c = \{\boldsymbol{x}_i, \overline{y}_i\}_{i=1}^{n_c} \sim \overline{p}_c(\boldsymbol{x}, \overline{y})$
J_c	local loss function of the surrogate task
R	global communication round
L	local updating iterations

C   PROOFS

In this appendix, we prove all theorems.

C.1   PROOF OF THEOREM 1

By the Bayes' rule, $\forall m \in [M]$ we have:

$$
\begin{aligned}
(\overline{\boldsymbol{\eta}}_c(\boldsymbol{x}))_m &= \frac{\overline{p}_c(\boldsymbol{x}, \overline{y} = m)}{\overline{p}_c(\boldsymbol{x})} \\
&= \frac{\overline{p}_c(\boldsymbol{x}, \overline{y} = m)}{\sum_{m=1}^{M_c} \overline{p}_c(\boldsymbol{x}, \overline{y} = m)} \\
&= \frac{\overline{p}_c(\boldsymbol{x} \mid \overline{y} = m)\overline{p}_c(\overline{y} = m)}{\sum_{m=1}^{M_c} \overline{p}_c(\boldsymbol{x} \mid \overline{y} = m)\overline{p}_c(\overline{y} = m)} \\
&= \frac{p_c^m(\boldsymbol{x})\overline{\pi}_c^m}{\sum_{m=1}^{M_c} p_c^m(\boldsymbol{x})\overline{\pi}_c^m} \\
&= \frac{\overline{\pi}_c^m \sum_{k=1}^{K} \pi_c^{m,k} p(\boldsymbol{x} \mid y = k)}{\sum_{m=1}^{M_c} \overline{\pi}_c^m \sum_{k=1}^{K} \pi_c^{m,k} p(\boldsymbol{x} \mid y = k)} \\
&= \frac{\overline{\pi}_c^m \sum_{k=1}^{K} \pi_c^{m,k} \frac{(\boldsymbol{\eta}(\boldsymbol{x}))_k}{\pi^k}}{\sum_{m=1}^{M_c} \overline{\pi}_c^m \sum_{k=1}^{K} \pi_c^{m,k} \frac{(\boldsymbol{\eta}(\boldsymbol{x}))_k}{\pi^k}}.
\end{aligned}
\tag{10}
$$

By transforming (10) to the matrix form, we complete the proof.   □

C.2   PROOF OF LEMMA 2

Given our data generation process in Section 3.1, we have that $M_c \geq k$ and $\Pi_c \in \mathbb{R}^{M_c \times K}$ is a full column rank matrix. With $D_{\overline{\boldsymbol{\pi}}_c}$ and $D_{\boldsymbol{\pi}}^{-1}$ being non-degenerate, we obtain that $\boldsymbol{Q}_c(\boldsymbol{\eta}(\boldsymbol{x}))$ presents an injective mapping from $\boldsymbol{\eta}(\boldsymbol{x})$ to $\overline{\boldsymbol{\eta}}_c(\boldsymbol{x})$.   □

C.3   PROOF OF PROPOSITION 3

The assumptions **(A1)**-**(A3)** are listed as follows.

(A1) Bounded gradient dissimilarity: $\exists$ constants $G \geq 0$ and $B \geq 1$ s.t.

$$\frac{1}{C} \sum_{c=1}^{C} \|\nabla J_c(\boldsymbol{g})\|^2 \leq G^2 + B^2 \|\nabla J(\boldsymbol{g})\|^2, \forall \boldsymbol{g}.$$

(A2) β-smooth function J_c satisfies

$$\|\nabla J_c(\boldsymbol{\theta}) - \nabla J_c(\boldsymbol{\theta}')\| \leq \beta\|\boldsymbol{\theta} - \boldsymbol{\theta}'\|, \forall c, \boldsymbol{\theta}, \boldsymbol{\theta}'.$$

(A3) Unbiased stochastic gradient with bounded variance:

$$\mathbb{E}[\|\nabla \widehat{J}_c(\boldsymbol{g}; \overline{\mathcal{U}}_c) - \nabla J_c(\boldsymbol{g})\|^2] \leq \sigma^2, \forall c, \boldsymbol{g},$$

where $\widehat{J}_c(\boldsymbol{g}; \overline{\mathcal{U}}_c) = \frac{1}{n_c} \sum_{i=1}^{n_c} \ell(\boldsymbol{g}(\boldsymbol{x}_i), \overline{y}_i)$.

Note that this proposition statement is w.r.t. the convergence of model $\boldsymbol{g}$ learned from the surrogate supervised learning task. The proof follows directly from Theorem V in Karimireddy et al. (2020).   □

C.4   PROOF OF THEOREM 4

When a proper loss (Reid & Williamson, 2010) is used for ℓ, the mapping of $\boldsymbol{g}^{**}$ is the unique minimizer of $J(\boldsymbol{g})$. We show an example of the a widely used proper loss function: the cross-entropy loss (De Boer et al., 2005) defined as

$$\ell_{\text{ce}}(\boldsymbol{g}(\boldsymbol{x}), \overline{y}) = -\sum_{m=1}^{M} \mathbf{1}(\overline{y} = m) \log(\boldsymbol{g}(\boldsymbol{x}))_m = -\log(\boldsymbol{g}(\boldsymbol{x}))_{\overline{y}}.$$

We can see that the cross-entropy loss is non-negative by its definition. Therefore, minimizing $J(\boldsymbol{g})$ can be obtained by minimizing the conditional risk $\mathbb{E}_{p(\overline{y}|\boldsymbol{x})}[\ell(\boldsymbol{g}(\boldsymbol{x}), \overline{y}) \mid \boldsymbol{x}]$ for every $\boldsymbol{x} \in \mathcal{X}$. So we are now optimizing

$$\phi(\boldsymbol{g}) = -\sum_{m=1}^{M} p(\overline{y} = m \mid \boldsymbol{x}) \cdot \log(g(\boldsymbol{x}))_m, \quad \text{s.t.} \sum_{m=1}^{M} (g(\boldsymbol{x}))_m = 1.$$

By using the Lagrange multiplier method (Bertsekas, 1997), we have

$$\mathcal{L} = -\sum_{m=1}^{M} p(\overline{y} = m \mid \boldsymbol{x}) \cdot \log(g(\boldsymbol{x}))_m - \lambda \cdot \left(\sum_{m=1}^{M} (g(\boldsymbol{x}))_m - 1\right).$$

The derivative of $\mathcal{L}$ with respect to $\boldsymbol{g}$ is

$$\frac{\partial \mathcal{L}}{\partial \boldsymbol{g}} = \left[-\frac{p(\overline{y} = 1 \mid \boldsymbol{x})}{(\boldsymbol{g}(\boldsymbol{x}))_1} - \lambda, \cdots, -\frac{p(\overline{y} = M \mid \boldsymbol{x})}{(\boldsymbol{g}(\boldsymbol{x}))_M} - \lambda \right]^{\top}.$$

By setting this derivative to 0 we obtain

$$(\boldsymbol{g}(\boldsymbol{x}))_m = -\frac{1}{\lambda} \cdot p(\overline{y} = m \mid \boldsymbol{x}), \quad \forall m = 1, \ldots, M \text{ and } \forall \boldsymbol{x} \in \mathcal{X}.$$

Since $\boldsymbol{g} \in \Delta_{M-1}$ is the M-dimensional simplex, we have $\sum_{m=1}^{M}(\boldsymbol{g}^{**}(\boldsymbol{x}))_m = 1$ and $\sum_{m=1}^{M} p(\overline{y} = j \mid \boldsymbol{x}) = 1$. Then

$$\sum_{m=1}^{M} (\boldsymbol{g}^{**}(\boldsymbol{x}))_m = -\frac{1}{\lambda} \cdot \sum_{m=1}^{M} p(\overline{y} = m \mid \boldsymbol{x}) = 1.$$

Therefore we obtain $\lambda = -1$ and $(\boldsymbol{g}^{**}(\boldsymbol{x}))_m = p(\overline{y} = m \mid \boldsymbol{x}) = (\overline{\boldsymbol{\eta}}(\boldsymbol{x}))_m, \forall m = 1, \ldots, M$ and $\forall \boldsymbol{x} \in \mathcal{X}$, which is equivalent to $\boldsymbol{g}^{**}(\boldsymbol{x}) = \bar{\boldsymbol{\eta}}(\boldsymbol{x})$. Similarly, we obtain $\boldsymbol{f}^{\star}(\boldsymbol{x}) = \boldsymbol{\eta}(\boldsymbol{x})$.

Given Proposition 3 and the assumption that the model used for $\boldsymbol{g}$ is sufficiently flexible, we obtain the classification model learned with FedUL by Algorithm 1 $\boldsymbol{g}^* = \boldsymbol{g}^{**}$. By our model construction, $\boldsymbol{g}$ is built from $\boldsymbol{Q}_c(\boldsymbol{f})$. We have $\boldsymbol{f}^* = \boldsymbol{f}^{**} = \arg\min_{\boldsymbol{f}} J(\boldsymbol{f})$ which is induced by the convergence of $\boldsymbol{g}$. Given Theorem 1 and Lemma 2, we obtain that $\boldsymbol{g}^{**}(\boldsymbol{x}) = \bar{\boldsymbol{\eta}}(\boldsymbol{x})$ if and only if $\boldsymbol{f}^{**}(\boldsymbol{x}) = \boldsymbol{\eta}(\boldsymbol{x})$. So we obtain $\boldsymbol{f}^* = \boldsymbol{f}^{\star}$. $\qquad\square$

D   EXPERIMENTAL DETAILS

We illustrate our model architectures and training details of the benchmark and real-world experiments in this section.

D.1   MODEL ARCHITECTURE

For our benchmark experiment on MNIST, we use a six-layer convolutional neural network. The network details are listed in Table D.2. For our benchmark experiment on CIFAR10 and real-world experiment, we use ResNet18 as our backbone. The network details are listed in Table D.3.

Layer	Details
1	Conv2D(3, 64, 5, 1, 2), BN(64), ReLU, MaxPool2D(2, 2)
2	Conv2D(64, 64, 5, 1, 2), BN(64), ReLU, MaxPool2D(2, 2)
3	Conv2D(64, 128, 5, 1, 2), BN(128), ReLU
4	FC(6272, 2048), BN(2048), ReLU
5	FC(2048, 512), BN(512), ReLU
6	FC(512, 10)

Table D.2: Model architecture of the benchmark experiment on MNIST. For convolutional layer (Conv2D), we list parameters with sequence of input and output dimension, kernal size, stride and padding. For max pooling layer (MaxPool2D), we list kernal and stride. For fully connected layer (FC), we list input and output dimension. For BatchNormalization layer (BN), we list the channel dimension.

D.2   TRAINING DETAILS

Benchmark Experiments: We implement all the methods by PyTorch and conducted all the experiments on an NVIDIA TITAN X GPU. Please note for all experiments, we split 20% training data for validation and select model. During training process, we use Adam optimizer with learning rate $1e-4$ and cross-entropy loss, we set batch size to 128 and training rounds to 100. To avoid overfitting, we use L1 regularization. The detailed weight of L1 regularization used in benchmark experiments is shown in Table D.4.

The detailed number of samples in each client for MNIST and CIFAR10 under IID and Non-IID setting is given in Table D.5 and Table D.6, respectively.

We describe details of the baseline methods and corresponding hyper-parameters as follows.

- FedPL (Diao et al., 2021): this method is based on empirical classification risk minimization. The learning objective is

$$\widehat{R}(\boldsymbol{f}) = \frac{1}{C} \sum_{c=1}^{C} \sum_{m=1}^{M_c} \mathcal{L}_{fix} + \lambda \mathcal{L}_{mix}, \qquad (11)$$

where

$$\mathcal{L}_{\text{fix}} = \ell\left(\boldsymbol{f}\left(x_b^+\right), y_b^+\right) \qquad (12)$$

is the "fix" loss, where (x_b^+, y_b^+) represents for a sample x_b^+ with high confidence pseudo label y_b^+ and

$$\mathcal{L}_{\text{mix}} = \lambda_{\text{mix}} \cdot \ell\left(\boldsymbol{f}\left(x_{\text{mix}}\right), y_b^+\right) + (1 - \lambda_{\text{mix}}) \cdot \ell\left(\boldsymbol{f}\left(x_{\text{mix}}\right), y_b^-\right)) \qquad (13)$$

is the "mix" loss, in which

$$\lambda_{\text{mix}} \sim \text{Beta}(a, a), \quad x_{\text{mix}} \leftarrow \lambda_{\text{mix}} x_b^+ + (1 - \lambda_{\text{mix}}) x_b^-, \qquad (14)$$

where a is the mixup hyper-parameter and (x_b^-, y_b^-) represents for a sample x_b^- with low confidence pseudo label y_b^-. Following the default implementation in (Diao et al., 2021),

Layer	Details
1	Conv2D(3, 64, 7, 2, 3), BN(64), ReLU
2	Conv2D(64, 64, 3, 1, 1), BN(64), ReLU
3	Conv2D(64, 64, 3, 1, 1), BN(64)
4	Conv2D(64, 64, 3, 1, 1), BN(64), ReLU
5	Conv2D(64, 64, 3, 1, 1), BN(64)
6	Conv2D(64, 128, 3, 2, 1), BN(128), ReLU
7	Conv2D(128, 128, 3, 1, 1), BN(64)
8	Conv2D(64, 128, 1, 2, 0), BN(128)
9	Conv2D(128, 128, 3, 1, 1), BN(128), ReLU
10	Conv2D(128, 128, 3, 1, 1), BN(64)
11	Conv2D(128, 256, 3, 2, 1), BN(128), ReLU
12	Conv2D(256, 256, 3, 1, 1), BN(64)
13	Conv2D(128, 256, 1, 2, 0), BN(128)
14	Conv2D(256, 256, 3, 1, 1), BN(128), ReLU
15	Conv2D(256, 256, 3, 1, 1), BN(64)
16	Conv2D(256, 512, 3, 2, 1), BN(512), ReLU
17	Conv2D(512, 512, 3, 1, 1), BN(512)
18	Conv2D(256, 512, 1, 2, 0), BN(512)
19	Conv2D(512, 512, 3, 1, 1), BN(512), ReLU
20	Conv2D(512, 512, 3, 1, 1), BN(512)
21	AvgPool2D
22	FC(512, 10)

Table D.3: Model architecture of the benchmark experiment on CIFAR10. For convolutional layer (Conv2D), we list parameters with sequence of input and output dimension, kernal size, stride and padding. For max pooling layer (MaxPool2D), we list kernal and stride. For fully connected layer (FC), we list input and output dimension. For BatchNormalization layer (BN), we list the channel dimension.

Table D.4: Detailed weight of L1 regularization used in benchmark experiments.

Dataset	MNIST			CIFAR10		
Sets	10	20	30	10	20	30
Weight	1e-5	5e-5	2e-6	2e-5	1e-5	4e-6

we set hyper-parameter $a = 0.75$. Moreover, we set the weight of "mix" loss $\lambda = 0.3$ and the confidence threshold $\tau = 0.4$.

• FedLLP (Dulac-Arnold et al., 2019): this baseline method is based on empirical proportion risk minimization. The learning objective is

$$\widehat{R}(\boldsymbol{f}) = \frac{1}{C} \sum_{c=1}^{C} \sum_{m=1}^{M_c} d_{\text{prop}} \left(\pi_c^m, \widehat{\pi}_c^m\right) \tag{15}$$

is the aggregated proportion risk, π_c^m and $\widehat{\pi}_c^m$ are the true and predicted label proportions for the m-th U set $\mathcal{U}_c^m$ in c-th client, $\widehat{\pi}_c^m := \frac{1}{M_c} \sum_{\boldsymbol{x} \sim \mathcal{U}_c^m} f(\boldsymbol{x})$. For each client c, d_{prop} is defined as

$$d_{\text{prop}}(\pi_c^m, \widehat{\pi}_c^m) := -\sum_{k=1}^{K} \pi_c^{m,k} \log \widehat{\pi}_c^{m,k}$$

Table D.5: Detailed number of samples in each client for MNIST benchmark

	Class	0	1	2	3	4	5	6	7	8	9
IID	Client1	920	1098	970	972	945	893	898	1007	971	926
	Client2	920	1098	970	972	945	893	898	1007	971	926
	Client3	920	1098	970	972	945	893	898	1007	971	926
	Client4	920	1098	970	972	945	893	898	1007	971	926
	Client5	920	1098	970	972	945	893	898	1007	971	926
Non-IID	Client1	4498	4646	56	56	54	57	54	60	60	54
	Client2	57	54	4425	4737	49	50	49	58	57	58
	Client3	64	61	57	61	4316	4217	54	53	58	57
	Client4	53	58	55	35	50	0	4572	4576	60	57
	Client5	57	58	61	0	60	0	19	54	4418	4576

Table D.6: Detailed number of samples in each client for CIFAR10 benchmark

	Class	airplane	automobile	bird	cat	deer	dog	frog	horse	ship	truck
IID	Client1	755	788	794	796	791	842	827	788	820	799
	Client2	755	788	794	796	791	842	827	788	820	799
	Client3	755	788	794	796	791	842	827	788	820	799
	Client4	755	788	794	796	791	842	827	788	820	799
	Client5	755	788	794	796	791	842	827	788	820	799
Non-IID	Client1	3748	3872	47	46	45	47	45	50	50	45
	Client2	48	45	3688	3938	41	41	41	48	48	48
	Client3	53	51	48	0	3597	3887	45	53	48	47
	Client4	44	18	46	0	42	0	3810	3813	50	48
	Client5	47	0	51	0	50	0	46	45	3788	3790

- FedLLP-VAT (Tsai & Lin, 2020): this method is based on empirical proportion risk mini-mization, integrated with a consistency regularization term. The learning objective is

$$\widehat{R}(\boldsymbol{f}) = \frac{1}{C} \sum_{c=1}^{C} \left(\sum_{m=1}^{M_c} d_{\text{prop}}\left(\pi_c^m, \widehat{\pi}_c^m\right) + \alpha \ell_{\text{cons}}\left(f\right) \right) \qquad (16)$$

is the aggregated proportion risk with consistency regularization, π_c^m and $\widehat{\pi}_c^m$ are the true and predicted label proportions for the m-th U set $\mathcal{U}_c^m$ in c-th client, d_{prop} is a distance function, and

$$\ell_{\text{cons}}\left(f\right) = d_{\text{cons}}\left(f(\boldsymbol{x}), f(\widehat{\boldsymbol{x}})\right) \qquad (17)$$

is the consistency loss, d_{cons} is a distance function, $\widehat{\boldsymbol{x}}$ is a perturbed input from the original one $\boldsymbol{x}$. Following the default implementation in their paper (Tsai & Lin, 2020), we set the hyper-parameter the weight of consistency loss $\alpha = 0.05$ and the perturbation weight $\mu = 6.0$ for FedLLP-VAT on CIFAR10 benchmark experiment. For MNIST benchmark, we set the hyper-parameter the weight of consistency loss $\alpha = 5e - 4$ and the perturbation weight $\mu = 1e - 2$.

Real-world Experiments: We perform a study case on an important clinical task — intracranial hemorrhage diagnosis. Intracranial hemorrhage, described as bleeding that occurs inside the cranium, is a severe health problem. The distribution of intracranial hemorrhage depends on the patient's ethnicity, such as age (Camacho et al., 2015). Thus, considering age distributions vary in different regions, this dataset and problem naturally fits into our setting.

We use the RSNA Intracranial Hemorrhage Detection dataset (Flanders et al., 2020) (Fig. 4), which contains large-scale Magnetic Response Image (MRI) data from several hospitals.There are $106k$ samples in the dataset belonging to six classes, including five types of intracranial hemorrhage (Epidural, Intraparenchymal, Intraventricular, Subarachnoid, and Subdural) and healthy control type. In our experiments, we simulate a real-world scenario with five healthcare systems (a.k.a. clients) and assume the number of hospitals (a.k.a sets) in each healthcare systems varies $M = 12, 24$, and 48.

Table D.7: Detailed number of samples in each healthcare system (HS) for real-world RSNA Intracranial Hemorrhage Detection dataset (Flanders et al., 2020).

Type	Healthy	Epidural	Intraparenchymal	Intraventricular	Subarachnoid	Subdural
HS 1	3726	221	2023	1198	2027	4005
HS 2	3756	226	1923	1190	2063	4042
HS 3	3804	177	1932	1266	2040	3981
HS 4	3805	224	1939	1187	2074	3971
HS 5	3711	198	1929	1299	2080	3983

At first, we randomly split the whole dataset for five healthcare systems equally, so each healthcare systems is assigned $21.2k$ samples. Then we generate π_c^m for m-th set in c-th client from range $[0.1, 0.9]$ for all the hospitals with U data only. We check that the generated class priors are not all identical. Finally, we load samples for each the hospitals following the generated π. Detailed dataset statistics is given in Table D.7.

During training process, we use Adam optimizer with learning rate $1e - 4$ and cross-entropy loss, we set batch size to 128 and training rounds to 100. To avoid overfitting, we use L1 regularization. We set the weight of L1 regularization as $2e - 6$, $8e - 7$ and $4e - 7$ for 10, 20 and 40 sets, respectively. In real-world experiments, we use the same hyper-parameters as benchmark experiments for all methods except FedLLP-VAT. For FedLLP-VAT, we set the hyper-parameter the weight of consistency loss $\alpha = 0.05$ and the perturbation weight $\mu = 6.0$.

Training Efficiency: We further evaluate the training efficiency of our method with comparison to baseline methods. The detailed one epoch training time (mean) and forward FLOPs are given in Table D.8. The computation time is evaluated on a PC with one Nvidia TITAN X GPU. We can see that our method slightly increase the forward FLOPs and can achieve higher training efficiency compared with FedPL and FedLLP-VAT.

Table D.8: Quantitative comparison of our method with the baseline methods training epoch time and forward flops on benchmark and real-world datasets under Non-IID and IID setting.

Dataset	Method	Non-IID Task with 5 Clients		IID Task with 5 Clients	
		Computation time (s)	FLOPs (G)	Computation time (s)	FLOPs (G)
MNIST	FedPL	3.29		4.78	
	FedLLP	1.67	0.048125312	2.45	0.048125312
	FedLLP-VAT	2.10		2.87	
	FedUL	1.80	0.048125422	2.35	0.048125422
CIFAR10	FedPL	3.37		5.70	
	FedLLP	1.95	0.141595648	2.44	0.141595648
	FedLLP-VAT	3.43		4.86	
	FedUL	2.63	0.141595758	3.80	0.141595758
Real-world	FedPL	32.47	6.937938944	-	-
	FedUL	32.34	6.937939028	-	-

E   MORE EXPERIMENTAL RESULTS ON BENCHMARK DATASET MNIST

E.1   DETAILED STATISTICS OF FIGURE 3(A)

We show detailed statistics of figure 3(a) in Table E.9. With different noisy class priors, even challenging $\epsilon = 0.8$ and $\epsilon = 1.6$, our method still achieves low error rate, which strongly verify the robustness and effectiveness of our method.

Table E.9: Inaccurate class priors experiments with different noise ratio ϵ on MNIST under Non-IID setting with 5 clients and 10 sets in every client (mean error (std)).

$\epsilon = 0$ (Clean)	$\epsilon = 0.2$	$\epsilon = 0.4$	$\epsilon = 0.8$	$\epsilon = 1.6$
2.98 (1.72)	3.02 (1.30)	3.10 (0.96)	3.02 (1.36)	3.49 (1.74)

E.2   DETAILED STATISTICS OF FIGURE 3(B)

We show detailed statistics of figure 3(b) in Table E.10. With more Non-IID data can be accessed, our method performs better, which validate that more unlabeled Non-IID data can be helpful for FL.

Table E.10: Experiments on accessible data amount under the Non-IID setting (mean error (std)).

5k	10k	15k	20k	25k
3.56 (0.09)	2.62 (0.07)	1.97 (0.38)	1.75 (0.11)	1.72 (0.13)

E.3   DIFFERENT COMBINATIONS OF E AND B

We compare our method with different combinations of E and B on benchmark dataset MNIST with the Non-IID setting. The classification error rate (mean and std) are consistently small as presented (cf. Table E.11), which indicates our method can work under a wide range combinations of E and B.

Table E.11: Experiments using different combinations of training batch size B and local update epoch E on benchmark dataset MNIST with the Non-IID setting (mean error (std)).

E	1			4			16		
B	16	128	∞	16	128	∞	16	128	∞
Error	7.99 (9.83)	2,93 (1.20)	3.69 (0.88)	2.54 (1.09)	4.16 (3.44)	2.81 (0.37)	2.92 (1.12)	3.51 (1.88)	2.88 (1.06)

F   BENCHMARK EXPERIMENTS ON CLIENTS WITH DIFFERENT SETS

Here we conduct experiments on benchmark datasets under IID and Non-IID setting with 5 clients and different sets in each client (10, 20, 30, 40, 50). The experimental results are shown in Table F.12, which further indicates the effectiveness of our method even under this challenging setting.

Table F.12: Quantitative comparison of our method with the baseline methods on benchmark datasets under Non-IID and IID setting (mean error (std)) with different sets in each client. The best method (paired t-test at significance level 5%) is highlighted in boldface.

IID Task with 5 Clients					
Dataset	FedPL	FedLLP	FedLLP-VAT	FedUL	FedAvg 10%
MNIST	3.74 (0.78)	5.22 (5.38)	2.24 (0.05)	**1.19 (0.11)**	2.21 (0.07)
CIFAR10	45.49 (2.74)	84.16 (0.71)	86.01 (2.54)	**31.17 (2.80)**	42.27 (1.06)
Non-IID Task with 5 Clients					
Dataset	FedPL	FedLLP	FedLLP-VAT	FedUL	FedAvg 10%
MNIST	12.03 (2.89)	4.26 (3.20)	3.88 (2.89)	**2.31 (1.14)**	3.42 (0.20)
CIFAR10	59.06 (3.73)	62.44 (16.99)	59.72 (18.73)	**35.46 (1.40)**	53.13 (0.22)

G BENCHMARK EXPERIMENTS WITH MORE CLIENTS

To study the influence of the number of clients, here we further conduct benchmark experiments on both MNIST and CIFAR10 with 10 clients. The detailed results are shown in Table G.13, in which we has the similar observations as in Table 1.

Table G.13: Quantitative comparison of our method with the baseline methods on benchmark datasets under Non-IID and IID setting (mean error (std)). The best method (paired t-test at significance level 5%) is highlighted in boldface.

IID Task with 10 Clients						
Dataset	Sets	FedPL	FedLLP	FedLLP-VAT	FedUL	FedAvg 10%
MNIST	10	2.19 (0.04)	10.11 (7.12)	25.83 (22.64)	**0.74 (0.14)**	
	20	2.55 (0.30)	24.23 (17.52)	28.40 (23.20)	**1.05 (0.05)**	1.58 (0.23)
	40	3.13 (0.25)	32.53 (16.93)	34.46 (15.46)	**1.47 (0.11)**	
CIFAR10	10	40.47 (0.58)	76.23 (1.47)	76.25 (1.65)	**20.40 (0.63)**	
	20	46.44 (0.71)	78.10 (3.58)	76.26 (3.83)	**21.61 (0.23)**	33.57 (1.03)
	40	51.58 (1.18)	79.10 (2.34)	80.44 (1.60)	**22.71 (0.17)**	
Non-IID Task with 10 Clients						
Dataset	Sets	FedPL	FedLLP	FedLLP-VAT	FedUL	FedAvg 10%
MNIST	10	12.24 (1.36)	20.81 (14.72)	17.26 (10.39)	**1.91 (0.16)**	
	20	5.73 (0.89)	17.67 (11.48)	18.45 (4.30)	**1.45 (0.27)**	3.03 (0.24)
	40	4.16 (0.56)	14.98 (10.11)	13.62 (5.47)	**1.27 (0.12)**	
CIFAR10	10	68.53 (1.14)	84.11 (2.63)	82.17 (2.58)	**39.20 (0.79)**	
	20	61.49 (1.42)	71.69 (7.59)	72.34 (7.39)	**34.12 (0.57)**	52.48 (1.55)
	40	55.89 (2.19)	58.21 (4.95)	59.42 (9.59)	**32.21 (1.02)**	