TRANSFORMERS ARE SAMPLE-EFFICIENT WORLD MODELS

ABSTRACT

Deep reinforcement learning agents are notoriously sample inefficient, which considerably limits their application to real-world problems. Recently, many model-based methods have been designed to address this issue, with learning in the imagination of a world model being one of the most prominent approaches. However, while virtually unlimited interaction with a simulated environment sounds appealing, the world model has to be accurate over extended periods of time. Motivated by the success of Transformers in sequence modeling tasks, we introduce IRIS, a data-efficient agent that learns in a world model composed of a discrete autoencoder and an autoregressive Transformer. With the equivalent of only two hours of gameplay in the Atari 100k benchmark, IRIS achieves a mean human normalized score of 1.046, and outperforms humans on 10 out of 26 games, setting a new state of the art for methods without lookahead search. To foster future research on Transformers and world models for sample-efficient reinforcement learning, we release our codebase at this https URL. For the review process, we provide the code and visualizations in the supplementary materials.

1 INTRODUCTION

Deep Reinforcement Learning (RL) has become the dominant paradigm for developing competent agents in challenging environments. Most notably, human experts were surpassed by deep RL algorithms in a multitude of arcade (Mnih et al., 2015; Schrittwieser et al., 2020; Hafner et al., 2021), real-time strategy (Vinyals et al., 2019; Berner et al., 2019), board (Silver et al., 2016; 2018; Schrittwieser et al., 2020) and imperfect information (Schmid et al., 2021; Brown et al., 2020a) games. However, a common drawback of these methods is their extremely low sample efficiency. Indeed, experience requirements range from months of gameplay for DreamerV2 (Hafner et al., 2021) in Atari 2600 games (Bellemare et al., 2013b) to thousands of years for OpenAI Five in Dota2 (Berner et al., 2019). While some environments can be sped up for training agents, real-world applications often cannot. Besides, additional cost or safety considerations related to the number of environmental interactions may arise (Yampolskiy, 2018). Hence, sample efficiency is a necessary condition to bridge the gap between research and the deployment of deep RL agents in the wild.

Model-based methods (Sutton & Barto, 2018) constitute a promising direction to achieve data efficiency. Recently, world models were leveraged in several ways: pure representation learning (Schwarzer et al., 2021), lookahead search (Schrittwieser et al., 2020; Ye et al., 2021), and learning in imagination (Ha & Schmidhuber, 2018; Kaiser et al., 2020; Hafner et al., 2020; 2021). The latter approach is particularly appealing because training an agent inside a world model frees it from sample efficiency constraints. Nevertheless, this framework relies heavily on accurate world models since the policy is purely trained in imagination. In a pioneering work, Ha & Schmidhuber (2018) successfully built imagination-based agents in toy environments. SimPLe recently showed promise in the more challenging Atari 100k benchmark (Kaiser et al., 2020). Currently, the best Atari agent learning in imagination is DreamerV2 (Hafner et al., 2021), although it was developed and evaluated with two hundred million frames available, far from the sample-efficient regime. Therefore, designing new world model architectures, capable of handling visually complex and partially observable environments with few samples, is key to realize their potential as surrogate training grounds.

Figure 1: Unrolling imagination over time. This figure shows the policy π, depicted with purple arrows, taking a sequence of actions in imagination. The green arrows correspond to the encoder E and the decoder D of a discrete autoencoder, whose task is to represent frames in its learnt symbolic language. The backbone G of the world model is a GPT-like Transformer, illustrated with blue arrows. For each action that the policy π takes, G simulates the environment dynamics, by autoregressively unfolding new frame tokens that D can decode. G also predicts a reward and a potential episode termination. More specifically, an initial frame x_0 is encoded with E into tokens $z_0 = (z_0^1, \ldots, z_0^K) = E(x_0)$. The decoder D reconstructs an image $\hat{x}_0 = D(z_0)$, from which the policy π predicts the action a_0. From z_0 and a_0, G predicts the reward $\hat{r}_0$, episode termination $\hat{d}_0 \in \{0, 1\}$, and in an autoregressive manner $\hat{z}_1 = (\hat{z}_1^1, \ldots, \hat{z}_1^K)$, the tokens for the next frame. A dashed box indicates image tokens for a given time step, whereas a solid box represents the input sequence of G, *i.e.* (z_0, a_0) at $t = 0$, $(z_0, a_0, \hat{z}_1, a_1)$ at $t = 1$, etc. The policy π is purely trained with imagined trajectories, and is only deployed in the real environment to improve the world model (E, D, G).

The Transformer architecture (Vaswani et al., 2017) is now ubiquitous in Natural Language Processing (Devlin et al., 2019; Radford et al., 2019; Brown et al., 2020b; Raffel et al., 2020), and is also gaining traction in Computer Vision (Dosovitskiy et al., 2021; He et al., 2022), as well as in Offline Reinforcement Learning (Janner et al., 2021; Chen et al., 2021). In particular, the GPT (Radford et al., 2018; 2019; Brown et al., 2020b) family of models delivered impressive results in language understanding tasks. Similarly to world models, these attention-based models are trained with high-dimensional signals and a self-supervised learning objective, thus constituting ideal candidates to simulate an environment.

Transformers particularly shine when they operate over sequences of discrete tokens (Devlin et al., 2019; Brown et al., 2020b). For textual data, there are simple ways (Schuster & Nakajima, 2012; Kudo & Richardson, 2018) to build a vocabulary, but this conversion is not straightforward with images. A naive approach would consist in treating pixels as image tokens, but standard Transformer architectures scale quadratically with sequence length, making this idea computationally intractable. To address this issue, VQGAN (Esser et al., 2021) and DALL-E (Ramesh et al., 2021) employ a discrete autoencoder (Van Den Oord et al., 2017) as a mapping from raw pixels to a much smaller amount of image tokens. Combined with an autoregressive Transformer, these methods demonstrate strong unconditional and conditional image generation capabilities. Such results suggest a new approach to design world models.

In the present work, we introduce IRIS (Imagination with auto-Regression over an Inner Speech), an agent trained in the imagination of a world model composed of a discrete autoencoder and an autoregressive Transformer. IRIS learns behaviors by accurately simulating millions of trajectories. Our approach casts dynamics learning as a sequence modeling problem, where an autoencoder builds a language of image tokens and a Transformer composes that language over time. With minimal tuning and a drastically different architecture, IRIS outperforms a line of recent methods (Kaiser et al., 2020; Hessel et al., 2018; Laskin et al., 2020; Yarats et al., 2021; Schwarzer et al., 2021) for sample-efficient RL in the Atari 100k benchmark (Kaiser et al., 2020). After only two hours of real-time experience, it achieves a mean human normalized score of 1.046, and reaches superhuman performance on 10 out of 26 games. We describe IRIS in Section 2 and present our results in Section 3.

Figure 2: Four imagined trajectories in *KungFuMaster*. We use the same conditioning frame across the four rows, in green, and let the world model imagine the rest. As the initial frame only contains the player, there is no information about the enemies that will come next. Consequently, the world model generates different types and numbers of opponents in each simulation. It is also able to reflect an essential game mechanic, highlighted in the blue box, where the first enemy disappears after getting hit by the player.

2 METHOD

We formulate the problem as a Partially Observable Markov Decision Process (POMDP) with image observations $x_t \in \mathbb{R}^{h \times w \times 3}$, discrete actions $a_t \in \{1, \dots, A\}$, scalar rewards $r_t \in \mathbb{R}$, episode termination $d_t \in \{0, 1\}$, discount factor $\gamma \in (0, 1)$, initial observation distribution ρ_0, and environment dynamics $x_{t+1}, r_t, d_t \sim p(x_{t+1}, r_t, d_t \mid x_{\leq t}, a_{\leq t})$. The reinforcement learning objective is to train a policy π that yields actions maximizing the expected sum of rewards $\mathbb{E}_\pi[\sum_{t \geq 0} \gamma^t r_t]$.

Our method relies on the three standard components to learn in imagination (Sutton & Barto, 2018): experience collection, world model learning, and behavior learning. In the vein of Ha & Schmidhuber (2018); Kaiser et al. (2020); Hafner et al. (2020; 2021), our agent learns to act exclusively within its model of the world, and we only make use of real experience to learn the environment dynamics.

We repeatedly perform the three following steps:

- `collect_experience`: gather experience in the real environment with the current policy.

- `update_world_model`: improve rewards, episode ends and next observations predictions.

- `update_behavior`: in imagination, improve the policy and value functions.

The world model is composed of a discrete autoencoder (Van Den Oord et al., 2017), to convert an image to tokens and back, and a GPT-like autoregressive Transformer (Vaswani et al., 2017; Radford et al., 2019; Brown et al., 2020b), whose task is to capture environment dynamics. Figure 1 illustrates the interplay between the policy and these two components during imagination. We first describe the autoencoder and the Transformer in Sections 2.1 and 2.2, respectively. Section 2.3 then details the procedure to learn the policy and value functions in imagination. Appendix A provides a comprehensive description of model architectures and hyperparameters. Algorithm 1 summarizes the training protocol.

2.1 FROM IMAGE OBSERVATIONS TO TOKENS

The discrete autoencoder (E, D) learns a symbolic language of its own to represent high-dimensional images as a small number of tokens. The back and forth between frames and tokens is illustrated with green arrows in Figure 1.

Figure 3: Pixel perfect predictions in *Pong*. The top row displays a test trajectory collected in the real environment. The bottom row depicts the reenactment of that trajectory inside the world model. More precisely, we condition the world model with the first two frames of the true sequence, in green. We then sequentially feed it the true actions and let it imagine the subsequent frames. After only 120 games of training, the world model perfectly simulates the ball's trajectory and players' movements. Notably, it also captures the game mechanic of updating the scoreboard after winning an exchange, as shown in the blue box.

More precisely, the encoder $E : \mathbb{R}^{h \times w \times 3} \rightarrow \{1, \ldots, N\}^K$ converts an input image x_t into K tokens from a vocabulary of size N. Let $\mathcal{E} = \{e_i\}_{i=1}^N \in \mathbb{R}^{N \times d}$ be the corresponding embedding table of d-dimensional vectors. The input image x_t is first passed through a Convolutional Neural Network (CNN) (LeCun et al., 1989) producing output $y_t \in \mathbb{R}^{K \times d}$. We then obtain the output tokens $z_t = (z_t^1, \ldots, z_t^K) \in \{1, \ldots, N\}^K$ as $z_t^k = \mathrm{argmin}_i \| y_t^k - e_i \|_2$, the index of the closest embedding vector in $\mathcal{E}$ (Van Den Oord et al., 2017; Esser et al., 2021). Conversely, the CNN decoder $D : \{1, \ldots, N\}^K \rightarrow \mathbb{R}^{h \times w \times 3}$ turns K tokens back into an image.

This discrete autoencoder is trained on previously collected frames, with an equally weighted combination of a L_2 reconstruction loss, a commitment loss (Van Den Oord et al., 2017; Esser et al., 2021), and a perceptual loss (Esser et al., 2021; Johnson et al., 2016; Larsen et al., 2016). We use a straight-through estimator (Bengio et al., 2013) to enable backpropagation training.

2.2 MODELING DYNAMICS

At a high level, the Transformer G captures the environment dynamics by modeling the language of the discrete autoencoder over time. Its central role of unfolding imagination is highlighted with the blue arrows in Figure 1.

Specifically, G operates over sequences of interleaved frame and action tokens. An input sequence $(z_0^1, \ldots, z_0^K, a_0, z_1^1, \ldots, z_1^K, a_1, \ldots, z_t^1, \ldots, z_t^K, a_t)$ is obtained from the raw sequence $(x_0, a_0, x_1, a_1, \ldots, x_t, a_t)$ by encoding the frames with E, as described in Section 2.1.

At each time step t, the Transformer models the three following distributions:

$$\text{Transition:} \quad \hat{z}_{t+1} \sim p_G(\hat{z}_{t+1} \mid z_{\leq t}, a_{\leq t}) \text{ with } \hat{z}_{t+1}^k \sim p_G(\hat{z}_{t+1}^k \mid z_{\leq t}, a_{\leq t}, z_{t+1}^{<k}) \tag{1}$$

$$\text{Reward:} \quad \hat{r}_t \sim p_G(\hat{r}_t \mid z_{\leq t}, a_{\leq t}) \tag{2}$$

$$\text{Termination:} \quad \hat{d}_t \sim p_G(\hat{d}_t \mid z_{\leq t}, a_{\leq t}) \tag{3}$$

Note that the conditioning for the k-th token also includes $z_{t+1}^{<k} := (z_{t+1}^1, \ldots, z_{t+1}^{k-1})$, the tokens that were already predicted, i.e. the autoregressive process happens at the token level.

We train G in a self-supervised manner on segments of L time steps, sampled from past experience. We use a cross-entropy loss for the transition and termination predictors, and a mean-squared error loss for the reward predictor.

2.3 LEARNING IN IMAGINATION

Together, the discrete autoencoder (E, D) and the Transformer G form a world model, capable of imagination. The policy π, depicted with purple arrows in Figure 1, exclusively learns in this imagination MDP.

Figure 4: Imagining rewards and episode ends in *Breakout* (top) and *Gopher* (bottom). Each row depicts an imagined trajectory initialized with a single frame from the real environment. Yellow boxes indicate frames where the world model predicts a positive reward. In *Breakout*, it captures that breaking a brick yields rewards, and the brick is correctly removed from the following frames. In *Gopher*, the player has to protect the carrots from rodents. The world model successfully internalizes that plugging a hole or killing an enemy leads to rewards. Predicted episode terminations are highlighted with red boxes. The world model accurately reflects that missing the ball in *Breakout*, or letting an enemy reach the carrots in *Gopher*, will result in the end of an episode.

At time step t, the policy observes a reconstructed image observation $\hat{x}_t$ and samples action $a_t \sim \pi(a_t|\hat{x}_{\leq t})$. The world model then predicts the reward $\hat{r}_t$, the episode end $\hat{d}_t$, and the next observation $\hat{x}_{t+1} = D(\hat{z}_{t+1})$, with $\hat{z}_{t+1} \sim p_G(\hat{z}_{t+1} \mid z_0, a_0, \hat{z}_1, a_1, \ldots, \hat{z}_t, a_t)$. This imagination procedure is initialized with a real observation x_0 sampled from past experience, and is rolled out for H steps, the imagination horizon hyperparameter. We stop if an episode end is predicted before reaching the horizon. Figure 1 illustrates the imagination procedure.

As we roll out imagination for a fixed number of steps, we cannot simply use a Monte Carlo estimate for the expected return. Hence, to bootstrap the rewards that the agent would get beyond a given time step, we have a value network V that estimates $V(\hat{x}_t) \simeq \mathbb{E}_\pi \left[\sum_{\tau \geq t} \gamma^{\tau - t} \hat{r}_\tau \right]$.

Many actor-critic methods could be employed to train π and V in imagination (Sutton & Barto, 2018; Kaiser et al., 2020; Hafner et al., 2020). For the sake of simplicity, we opt for the learning objectives and hyperparameters of DreamerV2 (Hafner et al., 2021), that delivered strong performance in Atari games. Appendix B gives a detailed breakdown of the reinforcement learning objectives.

3 EXPERIMENTS

Sample-efficient reinforcement learning is a growing field with multiple benchmarks in complex visual environments (Hafner, 2022; Kanervisto et al., 2022). In this work, we focus on the well established Atari 100k benchmark (Kaiser et al., 2020). We present the benchmark and its baselines in Section 3.1. We describe the evaluation protocol and discuss the results in Section 3.2. Qualitative examples of the world model's capabilities are given in Section 3.3.

Table 1: Returns on the 26 games of Atari 100k after 2 hours of real-time experience, and human-normalized aggregate metrics. Bold numbers indicate the top methods without lookahead search while underlined numbers specify the overall best methods. IRIS outperforms learning-only methods in terms of number of superhuman games, mean, interquartile mean (IQM), and optimality gap.

| Game | Random | Human | Lookahead search | | No lookahead search | | | | |
			MuZero	EfficientZero	SimPLe	CURL	DrQ	SPR	IRIS (ours)
Alien	227.8	7127.7	530.0	808.5	616.9	711.0	**865.2**	841.9	420.0
Amidar	5.8	1719.5	38.8	148.6	74.3	113.7	137.8	__179.7__	143.0
Assault	222.4	742.0	500.1	1263.1	527.2	500.9	579.6	565.6	__1524.4__
Asterix	210.0	8503.3	1734.0	__25557.8__	**1128.3**	567.2	763.6	962.5	853.6
BankHeist	14.2	753.1	192.5	__351.0__	34.2	65.3	232.9	**345.4**	53.1
BattleZone	2360.0	37187.5	7687.5	13871.2	4031.2	8997.8	10165.3	__14834.1__	13074.0
Boxing	0.1	12.1	15.1	52.7	7.8	0.9	9.0	35.7	__70.1__
Breakout	1.7	30.5	48.0	__414.1__	16.4	2.6	19.8	19.6	**83.7**
ChopperCommand	811.0	7387.8	1350.0	1117.3	979.4	783.5	844.6	946.3	__1565.0__
CrazyClimber	10780.5	35829.4	56937.0	__83940.2__	**62583.6**	9154.4	21539.0	36700.5	59324.2
DemonAttack	152.1	1971.0	3527.0	__13003.9__	208.1	646.5	1321.5	517.6	**2034.4**
Freeway	0.0	29.6	21.8	21.8	16.7	28.3	20.3	19.3	__31.1__
Frostbite	65.2	4334.7	255.0	296.3	236.9	**1226.5**	1014.2	1170.7	259.1
Gopher	257.6	2412.5	1256.0	__3260.3__	596.8	400.9	621.6	660.6	**2236.1**
Hero	1027.0	30826.4	3095.0	__9315.9__	2656.6	4987.7	4167.9	5858.6	**7037.4**
Jamesbond	29.0	302.8	87.5	__517.0__	100.5	331.0	349.1	366.5	**462.7**
Kangaroo	52.0	3035.0	62.5	724.1	51.2	740.2	1088.4	__3617.4__	838.2
Krull	1598.0	2665.5	4890.8	5663.3	2204.8	3049.2	4402.1	3681.6	__6616.4__
KungFuMaster	258.5	22736.3	18813.0	__30944.8__	14862.5	8155.6	11467.4	14783.2	**21759.8**
MsPacman	307.3	6951.6	1265.6	1281.2	**1480.0**	1064.0	1218.1	1318.4	999.1
Pong	-20.7	14.6	-6.7	__20.1__	12.8	-18.5	-9.1	-5.4	**14.6**
PrivateEye	24.9	69571.3	56.3	96.7	35.0	81.9	3.5	86.0	__100.0__
Qbert	163.9	13455.0	3952.0	__13781.9__	1288.8	727.0	**1810.7**	866.3	745.7
RoadRunner	11.5	7845.0	2500.0	__17751.3__	5640.6	5006.1	11211.4	**12213.1**	9614.6
Seaquest	68.4	42054.7	208.0	__1100.2__	**683.3**	315.2	352.3	558.1	661.3
UpNDown	533.4	11693.2	2896.9	17264.2	3350.3	2646.4	4324.5	**10859.2**	3546.2
#Superhuman (↑)	0	N/A	5	__14__	1	2	3	6	**10**
Mean (↑)	0.000	1.000	0.562	__1.943__	0.332	0.261	0.465	0.616	**1.046**
Median (↑)	0.000	1.000	0.227	__1.090__	0.134	0.092	0.313	**0.396**	0.289
IQM (↑)	0.000	1.000	N/A	N/A	0.130	0.113	0.280	0.337	**0.501**
Optimality Gap (↓)	1.000	0.000	N/A	N/A	0.729	0.768	0.631	0.577	**0.512**

3.1 BENCHMARK AND BASELINES

Atari 100k consists of 26 Atari games (Bellemare et al., 2013a) with various mechanics, evaluating a wide range of agent capabilities. In this benchmark, an agent is only allowed 100k actions in each environment. This constraint is roughly equivalent to 2 hours of human gameplay. By way of comparison, unconstrained Atari agents are usually trained for 50 million steps, a 500 fold increase in experience.

Multiple baselines were benchmarked on Atari 100k. SimPLe (Kaiser et al., 2020) trains a policy with PPO (Schulman et al., 2017) in a video generation model. CURL (Laskin et al., 2020) develops off-policy agents from high-level image features obtained with contrastive learning. DrQ (Yarats et al., 2021) augments input images and averages Q-value estimates over several transformations. SPR (Schwarzer et al., 2021) enforces consistent representations of input images across augmented views and neighbouring time steps. The aforementioned baselines carry additional techniques to improve performance. Instead, IRIS does not rely on prioritized experience replay (Schaul et al., 2016), epsilon-greedy scheduling, or data augmentations.

We make a distinction between methods with and without lookahead search. Indeed, algorithms such as Monte Carlo Tree Search (MCTS) (Silver et al., 2016; 2018; Schrittwieser et al., 2020) can vastly improve agent performance, but they come at a premium in computational resources and code complexity. On the contrary, IRIS and the baselines above do not require distributed infrastructures and multiple GPUs. Moreover, IRIS could be combined with MCTS, both in imagination and in the real environment. Therefore, methods involving lookahead search should not be seen as direct competitors but rather as potential extensions to learning-only methods.

MuZero (Schrittwieser et al., 2020) and EfficientZero (Ye et al., 2021) are the current standard for search-based methods. MuZero leverages MCTS as a policy improvement operator, by unrolling

Figure 5: Mean, median, and interquartile mean human normalized scores, computed with stratified bootstrapped confidence intervals. 5 runs for IRIS and SimPLe, 100 runs for SPR, CURL, and DrQ (Agarwal et al., 2021).

(a) Performance profiles, i.e. fraction of runs above a given human normalized score.

(b) Probabilities of improvement, i.e. how likely it is for IRIS to outperform baselines on any game.

Figure 6: Performance profiles (left) and probabilities of improvement (right) (Agarwal et al., 2021).

multiple hypothetical trajectories in the latent space of a world model. EfficientZero improves upon MuZero by introducing a self-supervised consistency loss, predicting returns over short horizons in one shot, and correcting off-policy trajectories with its world model.

3.2 RESULTS

The human normalized score is the established measure of performance in Atari 100k. It is defined as $\frac{score\_agent - score\_random}{score\_human - score\_random}$, where *score_random* comes from a random policy, and *score_human* is obtained from human players (Wang et al., 2016).

Table 1 displays returns across games and human-normalized aggregate metrics. For MuZero and EfficientZero, we report the averaged results published by Ye et al. (2021) (3 runs). We use results from the Atari 100k case study conducted by Agarwal et al. (2021) for the other baselines (100 new runs for CURL, DrQ, SPR, and 5 existing runs for SimPLe). Finally, we evaluate IRIS by computing an average over 100 episodes collected at the end of training for each game (5 runs).

Agarwal et al. (2021) discuss the limitations of mean and median scores, and show that substantial discrepancies arise between standard point estimates and interval estimates in RL benchmarks. Following their recommendations, we summarize in Figure 5 the human normalized scores with stratified bootstrapped confidence intervals for mean, median, and interquartile mean (IQM). For finer comparisons, we also provide performance profiles and probabilities of improvement in Figure 6.

With the equivalent of only two hours of gameplay, IRIS achieves a superhuman mean score of 1.046 (+70%), an IQM of 0.501 (+49%), an optimality gap of 0.512 (+11%), and outperforms human players on 10 out of 26 games (+67%), where the relative improvements are computed with respect to SPR (Schwarzer et al., 2021). These results constitute a new state of the art for methods without lookahead search in the Atari 100k benchmark. We also note that IRIS outperforms MuZero, although the latter was not designed for the sample-efficient regime.

Figure 7: Three consecutive levels in the games *Frostbite* (left) and *Krull* (right). In our experiments, the world model struggles to simulate subsequent levels in *Frostbite*, but not in *Krull*. Indeed, exiting the first level in *Frostbite* requires a long and unlikely sequence of actions to first build the igloo, and then go back to it from the bottom of the screen. Such rare events prevent the world model from internalizing new aspects of the game, which will therefore not be experienced by the policy in imagination. While *Krull* features more diverse levels, the world model successfully reflects this variety, and IRIS even sets a new state of the art in this environment. This is likely due to more frequent transitions from one stage to the next in *Krull*, resulting in a sufficient coverage of each level.

In addition, performance profiles (Figure 6a) reveal that IRIS is on par with the strongest baselines for its bottom 50% of games, at which point it stochastically dominates (Agarwal et al., 2021; Dror et al., 2019) the other methods. Similarly, the probability of improvement is greater than 0.5 for all baselines (Figure 6b).

In terms of median score, IRIS overlaps with other methods (Figure 5). Interestingly, Schwarzer et al. (2021) observe that the median is only influenced by a few decisive games, as evidenced by the width of the confidence intervals for median scores, even with 100 runs for DrQ, CURL and SPR.

We observe that IRIS is particularly strong in games that do not suffer from distributional shifts as the training progresses. Examples of such games include *Pong*, *Breakout*, and *Boxing*. On the contrary, the agent struggles when a new level or game mechanic is unlocked through an unlikely event. This sheds light on a double exploration problem. IRIS has to first discover a new aspect of the game for its world model to internalize it. Only then may the policy rediscover and exploit it. Figure 7 details this phenomenon in *Frostbite* and *Krull*, two games with multiple levels. In summary, as long as transitions between levels do not depend on low-probability events, the double exploration problem does not hinder performance.

Another kind of games difficult to simulate are mazes with moving enemies, such as *MsPacman*, *BankHeist*, and *Alien*. As discussed in Appendix E, this is due to the small number of tokens used to encode frames. When we increase that amount, the world model is able to situate enemies, albeit at the cost of increased computation.

3.3 WORLD MODEL ANALYSIS

As IRIS learns behaviors entirely in its imagination, the quality of the world model is the cornerstone of our approach. For instance, it is key that the discrete autoencoder correctly reconstructs elements like a ball, a player, or an enemy. Similarly, the potential inability of the Transformer to capture important game mechanics, like reward attribution or episode termination, can severely hamper the agent's performance. Hence, no matter the amount of imagined trajectories, the agent will learn suboptimal policies if the world model is flawed.

While Section 3.2 provides a quantitative evaluation, we aim to complement the analysis with qualitative examples of the abilities of the world model. Figure 2 shows the generation of many plausible futures in the face of uncertainty. Figure 3 depicts pixel-perfect predictions in *Pong*. Finally, we illustrate in Figure 4 predictions for rewards and episode terminations, which are crucial to the reinforcement learning objective.

4 RELATED WORK

LEARNING IN THE IMAGINATION OF WORLD MODELS

The idea of training policies in a learnt model of the world was first investigated in tabular environments (Sutton & Barto, 2018). Ha & Schmidhuber (2018) showed that simple visual environments could be simulated with autoencoders and recurrent networks. SimPLe (Kaiser et al., 2020) demonstrated that a PPO policy (Schulman et al., 2017) trained in a video prediction model outperformed humans in some Atari games. Improving upon Dreamer (Hafner et al., 2020), DreamerV2 (Hafner et al., 2021) was the first agent learning in imagination to achieve human-level performance in the Atari 50M benchmark. Its world model combines a convolutional autoencoder with a recurrent state-space model (RSSM) (Hafner et al., 2019) for latent dynamics learning. More recently, Chen et al. (2022) explored a variant of DreamerV2 where a Transformer replaces the recurrent network in the RSSM.

REINFORCEMENT LEARNING WITH TRANSFORMERS

Following spectacular advances in natural language processing (Manning & Goldie, 2022), the reinforcement learning community has recently stepped into the realm of Transformers. Parisotto et al. (2020) make the observation that the standard Transformer architecture is difficult to optimize with RL objectives. The authors propose to replace residual connections by gating layers to stabilize the learning procedure. Our world model does not require such modifications, which is most likely due to its self-supervised learning objective. The Trajectory Transformer (Janner et al., 2021) and the Decision Transformer (Chen et al., 2021) represent offline trajectories as a static dataset of sequences. The Trajectory Transformer is trained to predict future returns, states and actions. At inference time, it can thus plan for the optimal action with a reward-driven beam search, yet the approach is limited to low-dimensional states. On the contrary, the Decision Transformer can handle image inputs but it cannot be easily extended as a world model. Ozair et al. (2021) introduce an offline variant of MuZero (Schrittwieser et al., 2020) capable of handling stochastic environments by performing an hybrid search with a Transformer over both actions and trajectory-level discrete latent variables.

VIDEO GENERATION WITH DISCRETE AUTOENCODERS AND TRANSFORMERS

VQGAN (Esser et al., 2021) and DALL-E (Ramesh et al., 2021) use discrete autoencoders to compress a frame into a small sequence of tokens, that a transformer can then model autoregressively. Other works extend the approach to video generation. GODIVA (Wu et al., 2021) models sequences of frames instead of a single frame for text conditional video generation. VideoGPT (Yan et al., 2021) introduces video-level discrete autoencoders, and Transformers with spatial and temporal attention patterns, for unconditional and action conditional video generation.

5 CONCLUSION

We introduced IRIS, an agent that learns purely in the imagination of a world model composed of a discrete autoencoder and an autoregressive Transformer. IRIS sets a new state of the art in the Atari 100k benchmark for methods without lookahead search. We showed that its world model acquires a deep understanding of game mechanics, resulting in pixel perfect predictions in some games. We also illustrated the generative capabilities of the world model, providing a rich gameplay experience when training in imagination. Ultimately, with minimal tuning compared to existing battle-hardened agents, IRIS opens a new path towards efficiently solving complex environments.

In the future, IRIS could be scaled up to computationally demanding and challenging tasks that would benefit from the speed of its world model. Besides, its policy currently learns from reconstructed frames, but it could probably leverage the internal representations of the world model. Another exciting avenue of research would be to combine learning in imagination with MCTS. Indeed, both approaches deliver impressive results, and their contributions to agent performance are orthogonal.

REPRODUCIBILITY STATEMENT

The different components and their training objectives are introduced in Section 2 and Appendix B. We describe model architectures and list hyperparameters in Appendix A. We specify the resources used to produce our results in Appendix F. Algorithm 1 makes explicit the interplay between components in the training loop. In Section 3.2, we provide the source of the reported results for the baselines, as well as the evaluation protocol.

The code is part of the supplementary materials, and will be open-sourced to ensure reproducible results and foster future research. Minimal dependencies are required to run the codebase and we provide a thorough user guide to get started. Training and evaluation can be launched with simple commands, customization is possible with configuration files, and we include scripts to visualize agents playing and let users interact with the world model.

ETHICS STATEMENT

The development of autonomous agents for real-world environments raises many safety and environmental concerns. During its training period, an agent may cause serious harm to individuals and damage its surroundings. It is our belief that learning in the imagination of world models greatly reduces the risks associated with training new autonomous agents. Indeed, in this work, we propose a world model architecture capable of accurately modeling environments with very few samples. However, in a future line of research, one could go one step further and leverage existing data to eliminate the necessity of interacting with the real world.

REFERENCES

Rishabh Agarwal, Max Schwarzer, Pablo Samuel Castro, Aaron C Courville, and Marc Bellemare. Deep reinforcement learning at the edge of the statistical precipice. *Advances in neural information processing systems*, 34:29304–29320, 2021.

Marc G Bellemare, Yavar Naddaf, Joel Veness, and Michael Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47: 253–279, 2013a.

Marc G Bellemare, Yavar Naddaf, Joel Veness, and Michael Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47: 253–279, 2013b.

Yoshua Bengio, Nicholas Léonard, and Aaron Courville. Estimating or propagating gradients through stochastic neurons for conditional computation. *arXiv preprint arXiv:1308.3432*, 2013.

Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemysław Dębiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, et al. Dota 2 with large scale deep reinforcement learning. *arXiv preprint arXiv:1912.06680*, 2019.

Noam Brown, Anton Bakhtin, Adam Lerer, and Qucheng Gong. Combining deep reinforcement learning and search for imperfect-information games. *Advances in Neural Information Processing Systems*, 33:17057–17069, 2020a.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020b.

Chang Chen, Yi-Fu Wu, Jaesik Yoon, and Sungjin Ahn. Transdreamer: Reinforcement learning with transformer world models. *arXiv preprint arXiv:2202.09481*, 2022.

Lili Chen, Kevin Lu, Aravind Rajeswaran, Kimin Lee, Aditya Grover, Misha Laskin, Pieter Abbeel, Aravind Srinivas, and Igor Mordatch. Decision transformer: Reinforcement learning via sequence modeling. *Advances in neural information processing systems*, 34, 2021.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, 2019.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021.

Rotem Dror, Segev Shlomov, and Roi Reichart. Deep dominance-how to properly compare deep neural models. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 2773–2785, 2019.

Patrick Esser, Robin Rombach, and Bjorn Ommer. Taming transformers for high-resolution image synthesis. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 12873–12883, 2021.

F. A. Gers, J. Schmidhuber, and F. Cummins. Learning to forget: Continual prediction with LSTM. *Neural Computation*, 12(10):2451–2471, 2000.

David Ha and Jürgen Schmidhuber. Recurrent world models facilitate policy evolution. *Advances in neural information processing systems*, 31, 2018.

Danijar Hafner. Benchmarking the spectrum of agent capabilities. In *International Conference on Learning Representations*, 2022.

Danijar Hafner, Timothy Lillicrap, Ian Fischer, Ruben Villegas, David Ha, Honglak Lee, and James Davidson. Learning latent dynamics for planning from pixels. In *International conference on machine learning*, pp. 2555–2565. PMLR, 2019.

Danijar Hafner, Timothy Lillicrap, Jimmy Ba, and Mohammad Norouzi. Dream to control: Learning behaviors by latent imagination. In *International Conference on Learning Representations*, 2020.

Danijar Hafner, Timothy P Lillicrap, Mohammad Norouzi, and Jimmy Ba. Mastering atari with discrete world models. In *International Conference on Learning Representations*, 2021.

Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16000–16009, 2022.

Matteo Hessel, Joseph Modayil, Hado Van Hasselt, Tom Schaul, Georg Ostrovski, Will Dabney, Dan Horgan, Bilal Piot, Mohammad Azar, and David Silver. Rainbow: Combining improvements in deep reinforcement learning. In *Thirty-second AAAI conference on artificial intelligence*, 2018.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural Computation*, 9(8): 1735–1780, 1997.

Michael Janner, Qiyang Li, and Sergey Levine. Offline reinforcement learning as one big sequence modeling problem. *Advances in neural information processing systems*, 34, 2021.

Justin Johnson, Alexandre Alahi, and Li Fei-Fei. Perceptual losses for real-time style transfer and super-resolution. In *European conference on computer vision*, pp. 694–711. Springer, 2016.

Łukasz Kaiser, Mohammad Babaeizadeh, Piotr Miłos, Błażej Osiński, Roy H Campbell, Konrad Czechowski, Dumitru Erhan, Chelsea Finn, Piotr Kozakowski, Sergey Levine, et al. Model based reinforcement learning for atari. In *International Conference on Learning Representations*, 2020.

Anssi Kanervisto, Stephanie Milani, Karolis Ramanauskas, Nicholay Topin, Zichuan Lin, Junyou Li, Jianing Shi, Deheng Ye, Qiang Fu, Wei Yang, Weijun Hong, Zhongyue Huang, Haicheng Chen, Guangjun Zeng, Yue Lin, Vincent Micheli, Eloi Alonso, François Fleuret, Alexander Nikulin, Yury Belousov, Oleg Svidchenko, and Aleksei Shpilman. Minerl diamond 2021 competition: Overview, results, and lessons learned. *arXiv preprint arXiv:2202.10583*, 2022.

Steven Kapturowski, Georg Ostrovski, John Quan, Remi Munos, and Will Dabney. Recurrent experience replay in distributed reinforcement learning. In *International conference on learning representations*, 2019.

Andrej Karpathy. minGPT: A minimal PyTorch re-implementation of the OpenAI GPT (Generative Pretrained Transformer) training, 2020. URL https://github.com/karpathy/minGPT.

Taku Kudo and John Richardson. Sentencepiece: A simple and language independent subword tokenizer and detokenizer for neural text processing. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pp. 66–71, 2018.

Anders Boesen Lindbo Larsen, Søren Kaae Sønderby, Hugo Larochelle, and Ole Winther. Autoencoding beyond pixels using a learned similarity metric. In *International conference on machine learning*, pp. 1558–1566. PMLR, 2016.

Michael Laskin, Aravind Srinivas, and Pieter Abbeel. CURL: Contrastive unsupervised representations for reinforcement learning. In *International Conference on Machine Learning*, pp. 5639–5650. PMLR, 2020.

Yann LeCun, Bernhard Boser, John S Denker, Donnie Henderson, Richard E Howard, Wayne Hubbard, and Lawrence D Jackel. Backpropagation applied to handwritten zip code recognition. *Neural computation*, 1(4):541–551, 1989.

Christopher Manning and Anna Goldie. Cs224n natural language processing with deep learning, 2022.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International conference on machine learning*, pp. 1928–1937. PMLR, 2016.

Sherjil Ozair, Yazhe Li, Ali Razavi, Ioannis Antonoglou, Aaron Van Den Oord, and Oriol Vinyals. Vector quantized models for planning. In *International Conference on Machine Learning*, pp. 8302–8313. PMLR, 2021.

Emilio Parisotto, Francis Song, Jack Rae, Razvan Pascanu, Caglar Gulcehre, Siddhant Jayakumar, Max Jaderberg, Raphael Lopez Kaufman, Aidan Clark, Seb Noury, et al. Stabilizing transformers for reinforcement learning. In *International Conference on Machine Learning*, pp. 7487–7498. PMLR, 2020.

Alec Radford, Karthik Narasimhan, Tim Salimans, and Ilya Sutskever. Improving language understanding by generative pre-training, 2018.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners, 2019.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 21:1–67, 2020.

Aditya Ramesh, Mikhail Pavlov, Gabriel Goh, Scott Gray, Chelsea Voss, Alec Radford, Mark Chen, and Ilya Sutskever. Zero-shot text-to-image generation. In *International Conference on Machine Learning*, pp. 8821–8831. PMLR, 2021.

Tom Schaul, John Quan, Ioannis Antonoglou, and David Silver. Prioritized experience replay. In *International Conference on Learning Representations*, 2016.

Martin Schmid, Matej Moravcik, Neil Burch, Rudolf Kadlec, Josh Davidson, Kevin Waugh, Nolan Bard, Finbarr Timbers, Marc Lanctot, Zach Holland, et al. Player of games. *arXiv preprint arXiv:2112.03178*, 2021.

Julian Schrittwieser, Ioannis Antonoglou, Thomas Hubert, Karen Simonyan, L. Sifre, Simon Schmitt, Arthur Guez, Edward Lockhart, Demis Hassabis, Thore Graepel, Timothy P. Lillicrap, and David Silver. Mastering atari, go, chess and shogi by planning with a learned model. *Nature*, 588(7839): 604–609, 2020.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Mike Schuster and Kaisuke Nakajima. Japanese and korean voice search. In *2012 IEEE international conference on acoustics, speech and signal processing (ICASSP)*, pp. 5149–5152. IEEE, 2012.

Max Schwarzer, Ankesh Anand, Rishab Goel, R Devon Hjelm, Aaron Courville, and Philip Bachman. Data-efficient reinforcement learning with self-predictive representations. In *International Conference on Learning Representations*, 2021.

David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of go with deep neural networks and tree search. *Nature*, 529(7587):484–489, 2016.

David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, et al. A general reinforcement learning algorithm that masters chess, shogi, and go through self-play. *Science*, 362(6419): 1140–1144, 2018.

Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. A Bradford Book, Cambridge, MA, USA, 2018.

Aaron Van Den Oord, Oriol Vinyals, et al. Neural discrete representation learning. *Advances in neural information processing systems*, 30, 2017.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in StarCraft II using multi-agent reinforcement learning. *Nature*, 575(7782):350–354, 2019.

Ziyu Wang, Tom Schaul, Matteo Hessel, Hado Hasselt, Marc Lanctot, and Nando Freitas. Dueling network architectures for deep reinforcement learning. In *International conference on machine learning*, pp. 1995–2003. PMLR, 2016.

Chenfei Wu, Lun Huang, Qianxi Zhang, Binyang Li, Lei Ji, Fan Yang, Guillermo Sapiro, and Nan Duan. Godiva: Generating open-domain videos from natural descriptions. *arXiv preprint arXiv:2104.14806*, 2021.

Roman V Yampolskiy. *Artificial Intelligence Safety and Security*. Chapman & Hall/CRC, 2018.

Wilson Yan, Yunzhi Zhang, Pieter Abbeel, and Aravind Srinivas. Videogpt: Video generation using vq-vae and transformers. *arXiv preprint arXiv:2104.10157*, 2021.

Denis Yarats, Ilya Kostrikov, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. In *International Conference on Learning Representations*, 2021.

Weirui Ye, Shaohuai Liu, Thanard Kurutach, Pieter Abbeel, and Yang Gao. Mastering atari games with limited data. *Advances in Neural Information Processing Systems*, 34, 2021.