PROVABLY EFFICIENT NEURAL OFFLINE REINFORCEMENT LEARNING VIA PERTURBED REWARDS

ABSTRACT

We propose a novel offline reinforcement learning (RL) algorithm, namely PEturbed-Reward Value Iteration (PERVI) which amalgamates the randomized value function idea with the pessimism principle. Most current offline RL algorithms explicitly construct statistical confidence regions to obtain pessimism via lower confidence bounds (LCB), which cannot easily scale to complex problems where a neural network is used to estimate the value functions. Instead, PERVI implicitly obtains pessimism by simply perturbing the offline data for multiple times with carefully-designed i.i.d Gaussian noises to learn an ensemble of estimated state-action values and acting greedily to the minimum of the ensemble. The estimated state-action values are obtained via fitting a parametric model (e.g. neural networks) to the perturbed datasets using gradient descent. As a result, PERVI only needs $\mathcal{O}(1)$ time complexity for action selection while LCB-based algorithms require at least $\Omega(K^2)$, where K is the total number of trajectories in the offline data. We also propose a novel data splitting technique that helps remove the potentially large log covering number in the learning bound. We prove that PERVI yields a provable uncertainty quantifier with overparameterized neural networks and achieves an $\tilde{\mathcal{O}}\left(\frac{\kappa H^{5/2}\tilde{d}}{\sqrt{K}}\right)$ sub-optimality where $\tilde{d}$ is the effective dimension, H is the horizon length and κ measures the distributional shift. We corroborate the statistical and computational efficiency of PERVI with an empirical evaluation in a wide set of synthetic and real-world datasets. To the best of our knowledge, PERVI is the first offline RL algorithm that is both provably and computationally efficient in general Markov decision processes (MDPs) with neural network function approximation.

1 INTRODUCTION

Offline reinforcement learning (offline RL) (Lange et al., 2012; Levine et al., 2020) is a practical paradigm of RL for domains where exploration is prohibitively expensive or even implausible but a fixed dataset of previous experiences is available a priori. Offline RL finds vast applications in a number of critical domains including healthcare (Gottesman et al., 2019; Nie et al., 2021), recommendation systems (Strehl et al., 2010; Thomas et al., 2017), econometrics (Kitagawa & Tetenov, 2018; Athey & Wager, 2021), whereas it has also recently attracted substantial research efforts and yielded several important empirical successes (Chen et al., 2021; Wang et al., 2022b;a; Meng et al., 2021), just to name a few.

A core problem in offline RL is to efficiently exploit the offline dataset to learn an optimal policy without any further exploration as in the online RL. To deal with this exploration-free policy learning problem, dominant approaches incorporate uncertainty from the offline dataset into the decision making (Buckman et al., 2020; Jin et al., 2021; Xiao et al., 2021; Nguyen-Tang et al., 2021a; Ghasemipour et al., 2022a; Brandfonbrener et al., 2022; An et al., 2021; Bai et al., 2022). The main idea for the uncertainty-aware approach for offline RL is the pessimism principle which constrains the learned policy to the offline data and leads to various lower confidence bound (LCB) algorithms. However, these methods cannot easily extend and scale to complex problems where neural function approximation is used to estimate the value functions. In particular, it is costly to explicitly compute the statistical confidence regions of the model or value functions if the function approximator is overparameterized neural networks. For example, the LCB construction for neural offline contex-

tual bandits (Nguyen-Tang et al., 2021a) and RL (Xu & Liang, 2022) requires the inverse of a large covariance matrix of the size as large as the number of parameters in the neural network. This computational cost hinders the practical application of these provably efficient offline RL algorithms. Thus, *a largely open problem is the design of a computationally and provably efficient offline RL algorithm with neural network function approximation.*

In this work, we address the problem above by combining the randomized value function idea (Osband et al., 2016; Ishfaq et al., 2021) and the pessimism principle (Jin et al., 2021). The algorithm is strikingly simple: we randomly perturb the offline rewards several times and act greedily with respect to the minimum of the estimated state-action values. The intuition is that taking the minimum from an ensemble of randomized state-action values can efficiently achieve pessimism with high probability while avoiding explicitly computing any statistical confidence regions. We consider the optimization in our algorithm where the estimated state-action values are obtained via training of the neural network with gradient descent (GD). Moreover, we propose a novel data splitting technique that helps remove the dependence on the potentially large log covering number in the learning bound. We show that our proposed algorithm yields a provable uncertainty quantifier with over-parameterized neural network function approximation and obtains an $\tilde{\mathcal{O}}\left(\frac{\kappa H^{5/2}\tilde{d}}{\sqrt{K}}\right)$ sub-optimality

where K is the total number of episodes in the offline data, $\tilde{d}$ is the effective dimension, H is the horizon length and κ measures the distributional shift. The provable efficiency is achieved along with computational efficiency as our algorithm needs only $\mathcal{O}(1)$ time complexity for action selection while LCB-based algorithms require $\mathcal{O}(K^2)$ time complexity. We empirically corroborate the statistical and computational efficiency of our proposed algorithm in a wide set of synthetic and real-world datasets. The experimental results show that our proposed algorithm has a strong advantage in computational efficiency while even outperforming LCB-based neural algorithms. To the best of our knowledge, our proposed method is the first offline RL algorithm that is both provably and computationally efficient in general Markov decision processes (MDPs) with neural network function approximation.

2 RELATED WORK

Randomized value functions for RL. For online RL, Osband et al. (2016; 2019) was the first to propose randomized value functions for exploration where the learner plans with respect to randomized value function estimates. This idea was inspired by posterior sampling for RL (Osband et al., 2013) that samples a value function from a posterior distribution and acts greedily with respect to the sampled function. This algorithm generates randomized value functions by injecting Gaussian noise into the training data and fit a model into the perturbed data. Jia et al. (2022) extend the perturbed reward idea to online contextual bandit with neural function approximation. Ishfaq et al. (2021) obtain provably efficient online RL with general function approximation using the perturbed rewards. While the randomized value functions are intuitive to obtain optimism for online RL, for offline RL, under distributional shift, it can be paradoxically difficult to properly obtain pessimism with randomization and ensemble (Ghasemipour et al., 2022b), especially with neural function approximation. In our work, we propose a simple trick that generates multiple randomized value functions and takes the minimum to enforce sufficient pessimism for offline RL that is both provably and computationally efficient.

Offline RL with function approximation. Provably efficient offline RL has been extensively studied under linear function approximation. Jin et al. (2021) were the first to show that pessimistic value iteration is provably efficient for offline linear MDPs. Xiong et al. (2022); Yin et al. (2022) improve Jin et al. (2021) by leveraging variance reduction. Xie et al. (2021) propose Bellman-consistent assumption with general function approximation which improves the bound of Jin et al. (2021) by a factor of $\sqrt{d}$ when realized to finite action space and linear MDPs. Wang et al. (2020a); Zanette (2021) study the statistical hardness of offline RL with linear function approximation via exponential lower bound and Foster et al. (2021) suggests that only realizability and strong uniform data coverage are not sufficient for sample-efficient offline RL. Beyond linearity, some works study offline RL in general, nonparametric and parametric function approximation, either based on Fitted-Q Iteration (FQI) (Munos & Szepesvári, 2008; Le et al., 2019; Chen & Jiang, 2019; Duan et al., 2021a;b; Hu et al., 2021b;a; Nguyen-Tang et al., 2021b; Ji et al., 2022) or pessimism principle

(Uehara & Sun, 2021; Nguyen-Tang et al., 2021a; Jin et al., 2021). While pessimism-based algorithms avoid the strong assumptions of data coverage used by FQI-based algorithms, they require an explicit construction of valid confidence regions and possibly the inverse of large covariance matrix which are computationally prohibited and cannot easily scale to complex function approximation setting. This limits the applicability of pessimism-based provably efficient offline RL to practical settings. Recent work (Bai et al., 2022) has proposed to estimate the uncertainty for constructing LCB via the disagreement of bootstrapped Q-functions. However, the uncertainty quantifier is only guaranteed in linear MDPs and needs to be explicit.

3 PRELIMINARIES

In this section, we provide basic background on offline RL and overparameterized neural networks.

3.1 EPISODIC TIME-INHOMOGENOUS MARKOV DECISION PROCESSES (MDPS)

A finite-horizon Markov decision process (MDP) is denoted as the tuple $\mathcal{M} = (\mathcal{S}, \mathcal{A}, \mathbb{P}, r, H, d_1)$, where $\mathcal{S}$ is an arbitrary state space, $\mathcal{A}$ an arbitrary action space, H the episode length, and d_1 the initial state distribution. We assume that $SA := |\mathcal{S}||\mathcal{A}|$ is finite but arbitrarily large, e.g. it can be as large as the total number of atoms in the observable universe $\approx 10^{82}$. A time-inhomogeneous transition kernel $\mathbb{P} = \{\mathbb{P}_h\}_{h=1}^{H}$, where $\mathbb{P}_h : \mathcal{S} \times \mathcal{A} \to \mathcal{P}(\mathcal{S})$ (where $\mathcal{P}(\mathcal{S})$ denotes the set of probability measures over $\mathcal{S}$) maps each state-action pair (s_h, a_h) to a probability distribution $\mathbb{P}_h(\cdot|s_h, a_h)$, and $r = \{r_h\}_{h=1}^{H}$ where $r_h : \mathcal{S} \times \mathcal{A} \to [0, 1]$ is the mean reward function at step h. A policy $\pi = \{\pi_h\}_{h=1}^{H}$ assigns each state $s_h \in \mathcal{S}$ to a probability distribution, $\pi_h(\cdot|s_h)$, over the action space and induces a random trajectory $s_1, a_1, r_1, \ldots, s_H, a_H, r_H, s_{H+1}$ where $s_1 \sim d_1$, $a_h \sim \pi_h(\cdot|s_h)$, $s_{h+1} \sim \mathbb{P}_h(\cdot|s_h, a_h)$. We define the state value function $V_h^{\pi} \in \mathbb{R}^{\mathcal{S}}$ and the action-state value function $Q_h^{\pi} \in \mathbb{R}^{\mathcal{S} \times \mathcal{A}}$ at each timestep h as $Q_h^{\pi}(s, a) = \mathbb{E}_{\pi}[\sum_{t=h}^{H} r_t|s_h = s, a_h = a]$, and $V_h^{\pi}(s) = \mathbb{E}_{a \sim \pi(\cdot|s)}[Q_h^{\pi}(s, a)]$, where the expectation $\mathbb{E}_{\pi}$ is taken with respect to the randomness of the trajectory induced by π. For any $V : \mathcal{S} \to \mathbb{R}$, we define the Bellman operator at timestep h as $(\mathbb{B}_h V)(s, a) := r_h(s, a) + (\mathbb{P}_h V)(s, a)$, where $\mathbb{P}_h$ is the transition operator defined as $(\mathbb{P}_h V)(s, a) := \mathbb{E}_{s' \sim \mathbb{P}_h(\cdot|s, a)}[V(s')]$. The Bellman equations are given as follows. For any $(s, a, h) \in \mathcal{S} \times \mathcal{A} \times [H]$,

$$Q_h^{\pi}(s, a) = (\mathbb{B}_h V_{h+1}^{\pi})(s, a), \quad V_h^{\pi}(s) = \langle Q_h^{\pi}(s, \cdot), \pi_h(\cdot|s) \rangle_{\mathcal{A}}, \quad V_{H+1}^{\pi}(s) = 0,$$

where $[H] := \{1, 2, \ldots, H\}$, and $\langle \cdot, \cdot \rangle_{\mathcal{A}}$ denotes the inner product over $\mathcal{A}$. We define an optimal policy π^* as any policy that yields the optimal value function, i.e. $V_h^{\pi^*}(s) = \sup_{\pi} V_h^{\pi}(s)$ for any $(s, h) \in \mathcal{S} \times [H]$. For simplicity, we denote $V_h^{\pi^*}$ and $Q_h^{\pi^*}$ as V_h^* and Q_h^*, respectively. The Bellman optimality equation can be written as

$$Q_h^*(s, a) = (\mathbb{B}_h V_{h+1}^*)(s, a), \quad V_h^*(s) = \max_{a \in \mathcal{A}} Q_h^*(s, a), \quad V_{H+1}^*(s) = 0.$$

We define the occupancy density as $d_h^{\pi}(s, a) := \mathbb{P}((s_h, a_h) = (s, a)|\pi)$ which is the probability that state-action pair at timestep h is (s, a) if the policy π is followed. We write $d_h^{\pi^*}$ as d_h^*.

Offline regime. In the offline regime, the RL learner is given a fixed dataset $\mathcal{D} = \{(s_h^t, a_h^t, r_h^t, s_{h+1}^t)\}_{h \in [H]}^{t \in [K]}$ generated a priori by some unknown behaviour policy $\mu = \{\mu_h\}_{h \in [H]}$, where K is the total number of trajectories, $a_h^t \sim \mu_h(\cdot|s_h^t), s_{h+1}^t \sim \mathbb{P}_h(\cdot|s_h^t, a_h^t)$ for any $(t, h) \in [K] \times [H]$. Note that we allow the trajectory at any time $t \in [K]$ to depend on the trajectories at the previous times. The goal of offline RL is to learn a policy $\hat{\pi}$ only from $\mathcal{D}$ such that it minimizes the sub-optimality of $\hat{\pi}$, which is defined as

$$\text{SubOpt}(\hat{\pi}) := \mathbb{E}_{s_1 \sim d_1}[\text{SubOpt}(\hat{\pi}; s_1)], \quad \text{where} \quad \text{SubOpt}(\hat{\pi}; s) := V_1^{\pi^*}(s_1) - V_1^{\hat{\pi}}(s_1).$$

Notation. For simplicity, we write $x_h^t = (s_h^t, a_h^t)$ and $x = (s, a)$. We write $\tilde{\mathcal{O}}(\cdot)$ to hide logarithmic factors of the problem parameters $(d, H, K, m, 1/\delta)$ in the standard Big-Oh notation. We use $\Omega(\cdot)$ as the standard Omega notation. We write $u \lesssim v$ if $u = \mathcal{O}(v)$ and write $u \gtrsim v$ if $v \lesssim u$. We write $A \preceq B$ iff $B - A$ is a positive definite matrix. We denote I_d the identity matrix in $\mathbb{R}^d$.

3.2 OVERPARAMETERIZED NEURAL NETWORKS

In this paper, we consider neural function approximation setting where the state-action value function is approximated by a two-layer neural network. For simplicity, we denote $\mathcal{X} := \mathcal{S} \times \mathcal{A}$ and view it as a subset of $\mathbb{R}^d$. Without loss of generality, we assume $\mathcal{X} \subset \mathbb{S}_{d-1} := \{x \in \mathbb{R}^d : \|x\|_2 = 1\}$. We consider a standard two-layer neural network: $f(x; W, b) = \frac{1}{\sqrt{m}} \sum_{i=1}^{m} b_i \sigma(w_i^T x)$, where m is an even number, $\sigma(\cdot) = \max\{\cdot, 0\}$ is the ReLU activation function (Agarap, 2018), and $W = (w_1^T, \ldots, w_m^T)^T \in \mathbb{R}^{md}$. During the training, we initialize (W, b) via the symmetric initialization scheme (Gao et al., 2019) as follows: For any $i \leq \frac{m}{2}$, $w_i = w_{\frac{m}{2}+i} \sim \mathcal{N}(0, I_d/d)$, and $b_{\frac{m}{2}+i} = -b_i \sim \mathrm{Unif}(\{-1, 1\})$. [1] For simplicity, during training we fix all b_i after initialization and only optimize over W, thus we write $f(x; W, b)$ as $f(x; W)$. Denote $g(x; W) = \nabla_W f(x; W) \in \mathbb{R}^{md}$, and let W_0 be the initial parameters of W. We assume the neural network is overparameterized in the sense that the width m is sufficiently larger than the number of samples K. Overparameterization has been shown to be effective to study the convergence and interpolation phenomenon of neural networks (Arora et al., 2019; Allen-Zhu et al., 2019; Hanin & Nica, 2019; Cao & Gu, 2019; Belkin, 2021). Under such an overparameterization regime, the dynamics of the training of the neural network can be captured by the framework of neural tangent kernel (NTK) (Jacot et al., 2018).

4 ALGORITHM

Algorithm 1 Perturbed-Reward Value Iteration (PERVI)

1: **Input**: Offline data $\mathcal{D} = \{(s_h^k, a_h^k, r_h^k)\}_{h \in [H]}^{k \in [K]}$, a parametric function family $\mathcal{F} = \{f(\cdot, \cdot; W) : W \in \mathcal{W}\} \subset \{\mathcal{X} \to \mathbb{R}\}$ (e.g. neural networks), perturbed variances $\{\sigma_h\}_{h \in [H]}$, number of bootstraps M, regularization parameter λ, step size η, number of gradient descent steps J, and cutoff margin ψ, split indices $\{\mathcal{I}_h\}_{h \in [H]}$ where $\mathcal{I}_h := [(H - h)K' + 1, \ldots, (H - h + 1)K']$
2: Initialize $\tilde{V}_{H+1}(\cdot) \leftarrow 0$ and initialize $f(\cdot, \cdot; W)$ with initial parameter W_0
3: **for** $h = H, \ldots, 1$ **do**
4:     **for** $i = 1, \ldots, M$ **do**
5:         Sample $\{\xi_h^{k,i}\}_{k \in \mathcal{I}_h} \sim \mathcal{N}(0, \sigma_h^2)$ and $\zeta_h^i = \{\zeta_h^{j,i}\}_{j \in [d]} \sim \mathcal{N}(0, \sigma_h^2 I_d)$
6:         Perturb the dataset $\tilde{\mathcal{D}}_h^i \leftarrow \{s_h^k, a_h^k, r_h^k + \tilde{V}_{h+1}(s_{h+1}^k) + \xi_h^{k,i}\}_{k \in \mathcal{I}_h}$
7:         Let $\tilde{W}_h^i \leftarrow \mathrm{GradientDescent}(\lambda, \eta, J, \tilde{\mathcal{D}}_h^i, \zeta_h^i, W_0)$ (Algorithm 2)
8:     **end for**
9:     Compute $\tilde{Q}_h(\cdot, \cdot) \leftarrow \min\{\min_{i \in [M]} f(\cdot, \cdot; \tilde{W}_h^i), H - h + 1 + \psi\}^+$
10:     $\tilde{\pi}_h \leftarrow \arg\max_{\pi_h} \langle \tilde{Q}_h, \pi_h \rangle$ and $\tilde{V}_h \leftarrow \langle \tilde{Q}_h, \tilde{\pi}_h \rangle$
11: **end for**
12: **Output**: $\tilde{\pi} = \{\tilde{\pi}_h\}_{h \in [H]}$.

In this section, we propose PEturbed-Reward Value Iteration (PERVI) algorithm for offline RL (Algorithm 1). The key idea of PERVI is to train a parametric model (e.g. a neural network) on a perturbed-reward dataset for several times and simply act greedily with respect to the minimum of the estimated state-action values. In particular, at each timestep $h \in [H]$, we perturb the offline rewards with σ_h-variance Gaussian noise for M times and combine with the upper-timestep estimated state value $\tilde{V}_{h+1}$ to obtain a perturbed dataset $\{\tilde{D}_h^i\}_{i \in [M]}$ (Line 6). PERVI then updates $\tilde{W}_h^i$ by minimizing the perturbed regularized squared loss on $\{\tilde{D}_h^i\}_{i \in [M]}$

Algorithm 2 GradientDescent$(\lambda, \eta, J, \tilde{\mathcal{D}}_h^i, \zeta_h^i, W_0)$

1: **Input:** Regularization parameter λ, step size η, number of gradient descent steps J, perturbed dataset $\tilde{\mathcal{D}}_h^i = \{s_h^k, a_h^k, r_h^k + \tilde{V}_{h+1}(s_{h+1}^k) + \xi_h^{t,i}\}_{k \in \mathcal{I}_h}$, regularization perturber ζ_h^i, initial parameter W_0
2: $L(W) := \frac{1}{2} \sum_{k \in \mathcal{I}_h} (f(s_h^k, a_h^k; W) - (r_h^k + \tilde{V}_{h+1}(s_{h+1}^k) + \xi_h^{k,i}))^2 + \frac{\lambda}{2} \|W + \zeta_h^i - W_0\|_2^2$
3: **for** $j = 0, \ldots, J - 1$ **do**
4:     $W_{j+1} \leftarrow W_j - \eta \nabla L(W_j)$
5: **end for**
6: **Output:** W_J.

---

[1]This symmetric initialization scheme makes $f(x; W_0) = 0$ and $\langle g(x; W_0), W_0 \rangle = 0$ for any x.

using gradient descent (Line 7). The returned policy is greedy with respect to the truncated version of the minimum of the ensemble of the estimated state-action values (Line 9 and 10). We truncate the ensemble minimum by $H - h + 1 + \psi$ (Line 9) where $\psi \geq 0$ is the small cutoff margin that is for the theoretical analysis and will be chosen later. It is important to note that we split the trajectory indices $[K]$ evenly into H disjoint buckets $[K] = \cup_{h \in [H]} \mathcal{I}_h$, where $\mathcal{I}_h = [(H - h)K' + 1, \ldots, (H - h + 1)K']$ with $K' := \lfloor K/H \rfloor$ [2], as illustrated in Figure 1. The estimated $\tilde{Q}_h$ is thus obtained only from the offline data with (trajectory) indices from $\mathcal{I}_h$ along with $\tilde{V}_{h+1}$. This novel design removes the data dependence structure in offline RL with function approximation (Nguyen-Tang et al., 2021b) and avoids a log covering number term in the sub-optimality bound, as we show in Subsection D.1.

To deal with non-linearity of the underlying MDP, we adopt a two-layer fully connected neural network for the parametric function family $\mathcal{F}$ in Algorithm 1 to approximate the action-state values: $f(x; W) = \frac{1}{\sqrt{m}} \sum_{i=1}^{m} b_i \sigma(w_i^T x)$, as defined in Subsection 3.2. We use two-layer neural networks to simplify the later analysis. We adopt gradient descent to train for the randomized neural state-action value functions $\{f(\cdot, \cdot; \tilde{W}_h^i)\}_{i \in [M]}$. The use of gradient descent is for analysis convenience and we can extend to stochastic gradient descent based on recent works in overparameterized neural networks (Allen-Zhu et al., 2019; Cao & Gu, 2019) with more involved analysis.

Existing offline RL algorithms explicitly construct statistical confidence regions to perform pessimism for the offline setting. Such explicit confidence construction is computationally expensive in complex problems where a neural network is used as function approximation. For example, the lower-confidence-bound-based algorithms in neural offline contextual bandits (Nguyen-Tang et al., 2021a) and RL (Xu & Liang, 2022) require the inverse of the covariance matrix that is as large as the square of the number of parameters in overparameterized neural networks. This is computationally prohibited for most practical settings. Instead, PERVI avoids such issue while still obtaining pessimism with a provable implicit uncertainty quantifier and $\tilde{\mathcal{O}}(\frac{1}{\sqrt{K}})$, as shown in the next section.

5 SUB-OPTIMALITY ANALYSIS

In this section, we provide a theoretical analysis of the sub-optimality of PERVI when the parametric class $\mathcal{F}$ in Algorithm 1 is the overparameterized neural network defined in Subsection 3.2. Our analysis is built on the recent advances in generalization and optimization of deep neural networks (Arora et al., 2019; Allen-Zhu et al., 2019; Hanin & Nica, 2019; Cao & Gu, 2019; Belkin, 2021) that the dynamics of the neural parameters learned by (stochastic) gradient descent can be captured by the corresponding neural tangent kernel (NTK) space (Jacot et al., 2018) when the network is overparameterized.

We define the NTK kernel as follows.

Definition 1 (NTK (Jacot et al., 2018))**.** *The NTK kernel $K_{ntk} : \mathcal{X} \times \mathcal{X} \to \mathbb{R}$ is defined as*

$$K_{ntk}(x, x') = \mathbb{E}_{w \sim \mathcal{N}(0, I_d/d)} \langle x\sigma'(w^T x), x'\sigma'(w^T x') \rangle.$$

Figure 1: Data splitting.

Let $\mathcal{H}_{ntk}$ be the reproducing kernel Hilbert space (RKHS) induced by K_{ntk}. In the following, we present the notion of effective dimension.

Definition 2 (Effective dimension)**.** *For any $h \in [H]$, the effective dimension of the NTK matrix on data $\{x_h^k\}_{k \in \mathcal{I}_h}$ is defined as*

$$\tilde{d}_h := \frac{\text{logdet}(I_{K'} + \mathcal{K}_h/\lambda)}{\log(1 + K'/\lambda)},$$

where $\mathcal{K}_h := [K_{ntk}(x_h^i, x_h^j)]_{i,j \in \mathcal{I}_h}$ is the Gram matrix of K_{ntk} on the data $\{x_h^k\}_{k \in \mathcal{I}_h}$. We further define $\tilde{d} := \max_{h \in [H]} \tilde{d}_h$.

---

[2]Without loss of generality, we assume $K/H \in \mathbb{N}$.

Remark 1. *The effective dimension $\tilde{d}_h$ is the data-dependent quantity that measures the number principle dimensions over which the number projection of the data $\{x_h^k\}_{k\in[K]}$ in the RKHS $\mathcal{H}_{ntk}$ is spread. It was first introduced by Valko et al. (2013) for kernalized contextual bandits and was subsequently adopted by Yang & Wang (2020) and Zhou et al. (2020) for kernelized RL and neural contextual bandits, respectively. The effective dimension is data-dependent and can be bounded by $\tilde{d} \lesssim K'^{(d+1)/(2d)}$ in the worst case (see Section B).* [3]

We define the function class: $\mathcal{Q}^* := \{f(x) = \int_{\mathbb{R}^d} c(w)^T x \sigma'(w^T x) dw : \sup_w \frac{\|c(w)\|_2}{p_0(w)} \leq B\}$, where $c : \mathbb{R}^d \to \mathbb{R}^d$ is any function, p_0 is the probability density function of $\mathcal{N}(0, I_d/d)$, and B is some constant. We impose the following assumption about the regularity of the underlying MDP under function approximation.

Assumption 5.1 (Completeness). *For any $V : \mathcal{S} \to [0, H+1]$ and any $h \in [H]$, $\mathbb{B}_h V \in \mathcal{Q}^*$.* [4]

Assumption 5.1 ensures that the Bellman operator $\mathbb{B}_h$ can be captured by an infinite-width neural network. This assumption is mild as $\mathcal{Q}^*$ is a dense subset of $\mathcal{H}_{ntk}$ (Gao et al., 2019, Lemma C.1), thus is an expressive function class when B is sufficiently large. Moreover, similar assumptions has been used in many prior provably efficient RL works with function approximation (Cai et al., 2019; Wang et al., 2020b; Yang et al., 2020; Nguyen-Tang et al., 2021b).

We can now present the suboptimality of the policy $\tilde{\pi}$ returned by Algorithm 1. Recall that we use the initialization scheme defined in Subsection 3.2 throughout the paper. Fix any $\delta \in (0, 1)$.

Theorem 1. *Let*

$$
\begin{aligned}
\beta &= 1 + \lambda^{1/2}B + (H+1)\left[\sqrt{\tilde{d}_h \log(1 + K'/\lambda) + 2} + 2\log(3H/\delta)\right]\\
\iota &:= Bm^{-1/2}(2\sqrt{d} + \sqrt{2\log(3H/\delta)}) + 3C_g R^{4/3} m^{-1/6} \sqrt{\log m}\\
&+ \sqrt{2K'(H+1+\beta\sqrt{\log(KM/\delta)})^2 + \lambda\beta^2 d\log(dKM/\delta) + 8C_g R^{4/3} m^{-1/6}\sqrt{\log m}}\\
&\times \sqrt{K'}C_g^2 R^{1/3} m^{-1/6}\sqrt{\log m} + 3K'C_g^2 R^{4/3} m^{-1/6}\sqrt{\log m}\\
&+ C_g(1-\eta\lambda)^J\left[\left(K(H+1+\beta\sqrt{\log(KM/\delta)})^2 + \lambda\beta^2 d\log(dKM/\delta)\right) + 2K(H+1)^2\right],
\end{aligned}
$$

for some absolute constant C_g and any R such that

$$
4\sqrt{K'}(H+1+\beta\sqrt{\log(K'M/\delta)}) + 4\beta\sqrt{d\log(dK'M/\delta)} \leq R \lesssim K'.
$$

If we set $m \gtrsim \max\{R^8 \log^3 m, K'^{10}(H+1)^2 \log(3K'H/\delta), d^{3/2}R^{-1}\log^{3/2}(\sqrt{m}/R), K'^6 R^8 \log^3 m, B^2 K'^2 d\log(3H/\delta)\}$, $m \gtrsim [2K'(H+1+\beta\sqrt{\log(K'M/\delta)})^2 + \lambda\beta^2 d\log(dK'M/\delta) + 1]^3 K'^3 R \log^3 m$, $\lambda = 1 + \frac{H}{K}$, $\sigma_h = \beta$, $\eta \lesssim (\lambda + K')^{-1}$, $J \gtrsim \eta\lambda \log\left(K'H^2\lambda\beta^2 d\log(dK'M/\delta)\right)$, $\psi = 1$, and $M = \log\frac{HSA}{\delta} / \log\frac{1}{1-\Phi(-1)}$ where $\Phi(\cdot)$ is the cumulative distribution function of the standard normal distribution, then under Assumption 5.1, with probability at least $1 - MHm^{-2} - 2\delta$, for any $s_1 \in \mathcal{S}$, we have

$$
\text{SubOpt}(\tilde{\pi}; s_1) \leq \beta(1 + \sqrt{2\log(SAH/\delta)}) \cdot \mathbb{E}_{\pi^*}\left[\sum_{h=1}^{H} \|g(x_h; W_0)\|_{\Lambda_h^{-1}}\right] + 2\iota,
$$

where $\Lambda_h := \lambda I_{md} + \sum_{k\in\mathcal{I}_h} g(x_h^k; W_0)g(x_h^k; W_0)^T \in \mathbb{R}^{md\times md}$.

Remark 2. *Theorem 1 shows that the randomized design in our proposed algorithm yields a provable uncertainty quantifier even we do not explicitly maintain any confidence regions in the algorithm. If we further set that $m \gtrsim \max\{K'^{12}R^8 \log^3 m, K'^{12}(B + H\sqrt{\tilde{d}})^6 R^2 \log^3 m\}$ and $J \gtrsim K'\log(K'(H\sqrt{\tilde{d}} + B))$, then we have $\iota \lesssim \frac{1}{K'}$.*

We build upon Theorem 1 to obtain an explicit bound using the following data coverage assumption.

---

[3] Note that this is the worst-case bound and $\tilde{d}$ can be significantly smaller than that rate in the training data.

[4] We consider $V : \mathcal{S} \to [0, H+1]$ instead of $V : \mathcal{S} \to [0, H]$ due to the cutoff margin ψ in Algorithm 1.

Work	Bound	I.I.D. ?	Well-Explored Data?	Finite Spectrum?	Matrix Inverse?	Opt
(Jin et al., 2021)	$\tilde{\mathcal{O}}\left(\frac{d_{lin}^{3/2}H^2}{\sqrt{K}}\right)$	no	yes	yes	yes	analytical
(Yang et al., 2020)	$\tilde{\mathcal{O}}\left(\frac{H^2\sqrt{\tilde{d}^2+\tilde{d}\tilde{n}}}{\sqrt{K}}\right)$	no	–	no	yes	oracle
(Xu & Liang, 2022)	$\tilde{\mathcal{O}}\left(\frac{\tilde{d}H^2}{\sqrt{K}}\right)$	yes	yes	yes	yes	oracle
This work	$\tilde{\mathcal{O}}\left(\frac{\kappa H^{5/2}\tilde{d}}{\sqrt{K}}\right)$	**no**	**no**	**no**	**no**	**GD**

Table 1: SOTA results for offline RL with function approximation. The third and fourth columns ask if the data needs to be i.i.d, and well-explored, resp.; the fifth column asks if the induced RKHS needs to have finite spectrum, the sixth column asks if the algorithm needs to inverse a covariance matrix and the last column present the optimizer being used. Here $\tilde{n}$ is the log covering number.

Assumption 5.2 (Optimal-Policy Concentrability). $\exists \kappa < \infty, \sup_{(h,s_h,a_h)} \frac{d_h^*(s_h,a_h)}{d_h^\mu(s_h,a_h)} \leq \kappa$.

Assumption 5.2 requires any positive-probability trajectory induced by the optimal policy to be covered by the behavior policy. This data coverage assumption is significantly milder than the uniform coverage assumptions in many FQI-based offline RL algorithms (Munos & Szepesvári, 2008; Chen & Jiang, 2019; Nguyen-Tang et al., 2021b) and is common in pessimism-based algorithms (Rashidinejad et al., 2021; Nguyen-Tang et al., 2021a; Chen & Jiang, 2022; Zhan et al., 2022).

Theorem 2. *For the parameter setting in Theorem 1 and additionally for $\lambda \geq C_g^2$ and $m = \Omega(K^4 \log(KH/\delta))$, under Assumption 5.1-5.2, with probability at least $1 - MHm^{-2} - 5\delta$,*

$$\mathrm{SubOpt}(\tilde{\pi}) \leq \frac{2\tilde{\beta}\kappa H}{\sqrt{K'}}(\sqrt{2\tilde{d}\log(1+K'/\lambda)+1} + \sqrt{\frac{\log\frac{H}{\delta}}{\lambda}}) + \frac{16H}{3K'}\log\frac{\log_2(K'H)}{\delta} + \frac{2}{K} + 2\iota,$$

where $\tilde{\beta} := \beta(1 + \sqrt{2\log(SAH/\delta)})$.

Remark 3. *Theorem 2 shows that PERVI achieves an $\tilde{\mathcal{O}}\left(\frac{\kappa H^{3/2}\sqrt{\tilde{d}}\cdot\max\{B,H\sqrt{\tilde{d}}\}}{\sqrt{K}}\right)$ sub-optimality.[5]*

Compared to (Yang et al., 2020), we improve by a factor of $K^{\frac{2}{4\gamma-1}}$ for some $\gamma \in (0,1)$ at the expense of $\sqrt{H}$. When realized to a linear MDP in $\mathbb{R}^{d_{lin}}$, $\tilde{d} = d_{lin}$ and our bound reduces into $\tilde{\mathcal{O}}\left(\frac{\kappa H^{5/2}d_{lin}}{\sqrt{K}}\right)$ which improves the bound $\tilde{\mathcal{O}}(d_{lin}^{3/2}H^2/\sqrt{K})$ of PEVI (Jin et al., 2021, Corollary 4.6) by a factor of $\sqrt{d_{lin}}$. We provide the result summary and comparison in Table 1 and give a more detailed discussion in Subsection B.1.

6 EXPERIMENTS

In this section, we empirically evaluate the proposed algorithm PERVI against several state-of-the-art baselines, including PEVI (Jin et al., 2021) which explicitly constructs lower confidence bound (LCB) for pessimism in a linear model (thus we re-name this algorithm as LinLCB for comparison convenience in our experiments), NeuraLCB (Nguyen-Tang et al., 2021a) which explicitly construct LCB using neural network gradients. We also include NeuraLCB (Diag), which is NeuraLCB with diagonal approximation for estimating the confidence set as suggested in NeuraLCB (Nguyen-Tang et al., 2021a), LinPER which is PERVI realized to the linear function approximation instead of neural network function approximation, and NeuralGreedy (LinGreedy, respectively) which uses neural networks (linear models, respectively) to fit into the offline data and act greedily with respect to the estimated state-action value functions without any pessimism. Note that when the parametric class $\mathcal{F}$ in Algorithm 1 is realized to neural networks, we name PERVI as NeuralPER. We do not use data split in the experiments. We provide detailed algorithms of the baselines in Section H.

We evaluated all algorithms in two problem settings: (1) the underlying MDP is a linear MDP whose reward functions and transition kernels are linear in some known feature map (Jin et al., 2020), and (2) the underlying MDP is non-linear with horizon length $H = 1$ (i.e. non-linear contextual bandits)

---

[5]e.g. when we set the parameters as in Remark 2 with $\delta = 1/K$.

Figure 2: Empirical results of sub-optimality (in log scale) on linear MDPs.

(Zhou et al., 2020), where the reward functions either synthetic or constructed from MNIST dataset (LeCun et al., 1998). We implemented all algorithms in Pytorch (Paszke et al., 2019) on a server with Intel(R) Xeon(R) Gold 6248 CPU @ 2.50GHz, 755G RAM, and one NVIDIA Tesla V100 Volta GPU Accelerator 32GB Graphics Card.

6.1 LINEAR MDPS

The main purpose of this experiment is to evaluate our design of perturbed rewards for implicit pessimism in Algorithm 1 for offline RL. We constructed a hard instance of linear MDPs (Yin et al., 2022; Min et al., 2021). Due to page limit, we describe in detail the linear MDP in Subsection A.1. We run over $H \in \{20, 30, 50, 80\}$ and report the averaged sub-optimality of LinLCB, LinPER and LinGreedy in Figure 2.

In Figure 2, we can observe that LinGreedy, which is uncertainty-agnostic, clearly failed to offline-learn the linear MDP and suffered much higher sub-optimality than pessimism-based algorithms LinLCB and LinPER. Moreover, LinLCB outperforms LinPER when K is smaller than around 400 samples but they match eventually for larger sample size. Note that unlike LinLCB, LinPER does not construct any confidence regions nor involve inverse of a large covariance matrix and that the y-axis is in log scale thus LinPER already has small sub-optimality in the first $K \approx 400$ samples. These show the effectiveness of the randomized design for implicit pessimism in Algorithm 1.

6.2 NEURAL CONTEXTUAL BANDITS

(a)   (b)   (c)

Figure 3: Empirical results of sub-optimality (in log scale) in neural contextual bandits: (a) $r(s,a) = \cos(3s^T\theta_a)$, (b) $r(s,a) = \exp(-10(s^T\theta_a)^2)$, and (c) MNIST.

The main purpose of this experiment is to evaluate the performance and computational efficiency of the proposed algorithm when neural networks are employed. For that purpose and for simplicity, we evaluated on contextual bandits which are simply MDPs with one-step horizon, i.e. $H = 1$. In particular, following (Zhou et al., 2020; Nguyen-Tang et al., 2021a), we use the bandit problems specified by the following reward functions: (a) $r(s,a) = \cos(3s^T\theta_a)$, (b) $r(s,a) = \exp(-10(s^T\theta_a)^2)$, where s and θ_a are generated uniformly at random from the unit sphere $\mathbb{S}_{d-1}$ with $d = 16$ and $A = 10$ and (c) MNIST, where $r(s,a) = 1$ if a is the true label of input image s and $r(s,a) = 0$ otherwise. To predict the value of different actions from the same state s using neural networks, we transform a state $s \in \mathbb{R}^d$ into dA-dimensional vectors $s^{(1)} = (s, 0, \ldots, 0), s^{(2)} = (0, s, 0, \ldots, 0), \ldots, s^{(A)} = (0, \ldots, 0, s)$ and train the network to map $s^{(a)}$ to $r(s,a)$ given a pair of data (s,a). For NeuralPER, NeuralGreedy, NeuraLCB and NeuraLCB (Diag), we use the same neural network architecture with two hidden layers whose width $m = 64$, train the network with Adam optimizer (Kingma & Ba, 2014). Due to page limit, we present in detail the experimental and hyperparameter setting in Subsection A.2. The averaged sub-optimality over 5 run times are reported in Figure 3.

In Figure 3, we can observe that algorithms that use a linear model i.e. LinLCB and LinPER significantly underperform neural-based algorithms i.e. NeuralGreedy, NeuraLCB, NeuraLCB (Diag) and NeuralPER, suggesting the crucial impact of neural representation for non-linear problems. It is also interesting to observe from the experimental results that NeuraLCB does not always outperform its diagonal approximation NeuraLCB (Diag) (e.g. in Figure 3.b), triggering a new question on the empirical effectiveness of NTK-based uncertainty for offline RL. Finally, NeuralPER outperforms all algorithms in the tested benchmarks, suggesting the effectiveness of our randomized design with neural function approximation.

(a)   (b)

Figure 4: Elapsed time (in seconds) for action selection in the contextual bandit $r(s,a) = 10(s^T\theta_a)^2$: (a) Running time of action selection versus the number of (offline) data points K, and (b) running time of action selection versus the network width m (for $K = 500$).

Figure 4 shows the average running time for action selection of neural-based algorithms NeuraLCB, NeuraLCB (Diag), and NeuralPER. We can observe that algorithms that use explicit confidence regions i.e. NeuraLCB and NeuraLCB (Diag) takes significantly much time on selecting an action when either the number of offline samples K or the network width m increase. This can be foreseeable as to sample an action, NeuraLCB and NeuraLCB (Diag) need to compute the inverse of a large covariance matrix based on the offline data and maintain the confidence region for each action per state. The diagonal approximation significantly reduces the running time of NeuraLCB but still has the running time scaled with the number of samples and the

Figure 5: Sub-optimality of NeuralPER versus different values of M.

network width while the running time for action selection of NeuralPER is constant. As NeuraLCB, NeuraLCB (Diag), and NeuralPER use the same neural network architecture, the running time spent in training one model is similar. The only difference is that NeuralPER trains M models while NeuraLCB and NeuraLCB (Diag) train one single model. However, as the perturbed data in Algorithm 1 are independent, training M models in NeuralPER is embarrassingly parallelizable.

In Figure 5, we show the performance of NeuralPER when M changes in $\{1, 2, 5, 10, 20, 30, 50, 100, 200\}$ at fixed $K = 1000$. We can see that the sub-optimality of NeuralPER graciously decreases with larger values of M. The grid search from the previous experiment for Figure 3 also yield $M = 10$ and $M = 20$ from the search space $M \in \{1, 10, 20\}$ as the best result. This consistently suggests the crucial impact of our algorithmic design using the minimum of the ensemble to obtain pessimism for offline RL.

7   CONCLUSION

We propose a novel algorithm that combines randomized value functions with pessimism principle for offline RL. As a result, our algorithm eliminates the computational overhead of explicitly maintaining a valid confidence region and the inverse of a large covariance matrix for pessimism. We show that our algorithm yields a provable pessimism and obtains an $\tilde{\mathcal{O}}\left(\frac{\kappa H^{5/2}\tilde{d}}{\sqrt{K}}\right)$ sub-optimality. Extensive experiments demonstrate the strong advantage of our algorithm for both computational efficiency and effectiveness for offline RL.

REFERENCES

Yasin Abbasi-yadkori, Dávid Pál, and Csaba Szepesvári. Improved algorithms for linear stochastic bandits. In J. Shawe-Taylor, R. Zemel, P. Bartlett, F. Pereira, and K.Q. Weinberger (eds.), *Advances in Neural Information Processing Systems*, volume 24. Curran Associates, Inc., 2011. URL https://proceedings.neurips.cc/paper/2011/file/e1d5be1c7f2f456670de3d53c7b54f4a-Paper.pdf.

Abien Fred Agarap. Deep learning using rectified linear units (relu). *arXiv preprint arXiv:1803.08375*, 2018.

Zeyuan Allen-Zhu, Yuanzhi Li, and Zhao Song. A convergence theory for deep learning via over-parameterization. In *International Conference on Machine Learning*, pp. 242–252. PMLR, 2019.

Gaon An, Seungyong Moon, Jang-Hyun Kim, and Hyun Oh Song. Uncertainty-based offline reinforcement learning with diversified q-ensemble. *Advances in neural information processing systems*, 34:7436–7447, 2021.

Sanjeev Arora, Simon S Du, Wei Hu, Zhiyuan Li, Ruslan Salakhutdinov, and Ruosong Wang. On exact computation with an infinitely wide neural net. *arXiv preprint arXiv:1904.11955*, 2019.

Susan Athey and Stefan Wager. Policy learning with observational data. *Econometrica*, 89(1): 133–161, 2021.

Chenjia Bai, Lingxiao Wang, Zhuoran Yang, Zhi-Hong Deng, Animesh Garg, Peng Liu, and Zhaoran Wang. Pessimistic bootstrapping for uncertainty-driven offline reinforcement learning. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=Y4cs1Z3HnqL.

Peter L Bartlett, Olivier Bousquet, and Shahar Mendelson. Local rademacher complexities. *The Annals of Statistics*, 33(4):1497–1537, 2005.

Mikhail Belkin. Fit without fear: remarkable mathematical phenomena of deep learning through the prism of interpolation. *arXiv preprint arXiv:2105.14368*, 2021.

Alberto Bietti and Julien Mairal. On the inductive bias of neural tangent kernels. *Advances in Neural Information Processing Systems*, 32, 2019.

David Brandfonbrener, Remi Tachet des Combes, and Romain Laroche. Incorporating explicit uncertainty estimates into deep offline reinforcement learning. *arXiv preprint arXiv:2206.01085*, 2022.

Jacob Buckman, Carles Gelada, and Marc G Bellemare. The importance of pessimism in fixed-dataset policy optimization. *arXiv preprint arXiv:2009.06799*, 2020.

Qi Cai, Zhuoran Yang, Jason D Lee, and Zhaoran Wang. Neural temporal-difference and q-learning provably converge to global optima. *arXiv preprint arXiv:1905.10027*, 2019.

Yuan Cao and Quanquan Gu. Generalization bounds of stochastic gradient descent for wide and deep neural networks. *Advances in Neural Information Processing Systems*, 32:10836–10846, 2019.

Jinglin Chen and Nan Jiang. Information-theoretic considerations in batch reinforcement learning. In *International Conference on Machine Learning*, pp. 1042–1051. PMLR, 2019.

Jinglin Chen and Nan Jiang. Offline reinforcement learning under value and density-ratio realizability: the power of gaps. 2022.

Lili Chen, Kevin Lu, Aravind Rajeswaran, Kimin Lee, Aditya Grover, Misha Laskin, Pieter Abbeel, Aravind Srinivas, and Igor Mordatch. Decision transformer: Reinforcement learning via sequence modeling. *Advances in neural information processing systems*, 34:15084–15097, 2021.

Sayak Ray Chowdhury and Aditya Gopalan. On kernelized multi-armed bandits. In *International Conference on Machine Learning*, pp. 844–853. PMLR, 2017.

Yaqi Duan, Chi Jin, and Zhiyuan Li. Risk bounds and rademacher complexity in batch reinforcement learning. In *International Conference on Machine Learning*, pp. 2892–2902. PMLR, 2021a.

Yaqi Duan, Mengdi Wang, and Martin J Wainwright. Optimal policy evaluation using kernel-based temporal difference methods. *arXiv preprint arXiv:2109.12002*, 2021b.

Dylan J Foster, Akshay Krishnamurthy, David Simchi-Levi, and Yunzong Xu. Offline reinforcement learning: Fundamental barriers for value function approximation. *arXiv preprint arXiv:2111.10919*, 2021.

Ruiqi Gao, Tianle Cai, Haochuan Li, Cho-Jui Hsieh, Liwei Wang, and Jason D Lee. Convergence of adversarial training in overparametrized neural networks. *Advances in Neural Information Processing Systems*, 32, 2019.

Seyed Kamyar Seyed Ghasemipour, Shixiang Shane Gu, and Ofir Nachum. Why so pessimistic? estimating uncertainties for offline rl through ensembles, and why their independence matters. *arXiv preprint arXiv:2205.13703*, 2022a.

Seyed Kamyar Seyed Ghasemipour, Shixiang Shane Gu, and Ofir Nachum. Why so pessimistic? estimating uncertainties for offline RL through ensembles, and why their independence matters., 2022b. URL `https://openreview.net/forum?id=wQ7RCayXUSl`.

Omer Gottesman, Fredrik Johansson, Matthieu Komorowski, Aldo Faisal, David Sontag, Finale Doshi-Velez, and Leo Anthony Celi. Guidelines for reinforcement learning in healthcare. *Nature medicine*, 25(1):16–18, 2019.

Boris Hanin and Mihai Nica. Finite depth and width corrections to the neural tangent kernel. *arXiv preprint arXiv:1909.05989*, 2019.

Jiachen Hu, Xiaoyu Chen, Chi Jin, Lihong Li, and Liwei Wang. Near-optimal representation learning for linear bandits and linear rl. In *International Conference on Machine Learning*, pp. 4349–4358. PMLR, 2021a.

Yichun Hu, Nathan Kallus, and Masatoshi Uehara. Fast rates for the regret of offline reinforcement learning. *arXiv preprint arXiv:2102.00479*, 2021b.

Haque Ishfaq, Qiwen Cui, Viet Nguyen, Alex Ayoub, Zhuoran Yang, Zhaoran Wang, Doina Precup, and Lin Yang. Randomized exploration in reinforcement learning with general value function approximation. In *International Conference on Machine Learning*, pp. 4607–4616. PMLR, 2021.

Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: Convergence and generalization in neural networks. *arXiv preprint arXiv:1806.07572*, 2018.

Xiang Ji, Minshuo Chen, Mengdi Wang, and Tuo Zhao. Sample complexity of nonparametric off-policy evaluation on low-dimensional manifolds using deep networks. *arXiv preprint arXiv:2206.02887*, 2022.

Yiling Jia, Weitong Zhang, Dongruo Zhou, Quanquan Gu, and Hongning Wang. Learning contextual bandits through perturbed rewards. *arXiv preprint arXiv:2201.09910*, 2022.

Chi Jin, Zhuoran Yang, Zhaoran Wang, and Michael I Jordan. Provably efficient reinforcement learning with linear function approximation. In *Conference on Learning Theory*, pp. 2137–2143. PMLR, 2020.

Ying Jin, Zhuoran Yang, and Zhaoran Wang. Is pessimism provably efficient for offline rl? In *International Conference on Machine Learning*, pp. 5084–5096. PMLR, 2021.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Toru Kitagawa and Aleksey Tetenov. Who should be treated? empirical welfare maximization methods for treatment choice. *Econometrica*, 86(2):591–616, 2018. doi: https://doi.org/10.3982/ECTA13288. URL `https://onlinelibrary.wiley.com/doi/abs/10.3982/ECTA13288`.

Sascha Lange, Thomas Gabel, and Martin Riedmiller. Batch reinforcement learning. In *Reinforcement learning*, pp. 45–73. Springer, 2012.

Hoang Minh Le, Cameron Voloshin, and Yisong Yue. Batch policy learning under constraints. In *ICML*, volume 97 of *Proceedings of Machine Learning Research*, pp. 3703–3712. PMLR, 2019.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

Linghui Meng, Muning Wen, Yaodong Yang, Chenyang Le, Xiyun Li, Weinan Zhang, Ying Wen, Haifeng Zhang, Jun Wang, and Bo Xu. Offline pre-trained multi-agent decision transformer: One big sequence model conquers all starcraftii tasks. *arXiv preprint arXiv:2112.02845*, 2021.

Yifei Min, Tianhao Wang, Dongruo Zhou, and Quanquan Gu. Variance-aware off-policy evaluation with linear function approximation. *Advances in neural information processing systems*, 34, 2021.

Rémi Munos and Csaba Szepesvári. Finite-time bounds for fitted value iteration. *J. Mach. Learn. Res.*, 9:815–857, 2008.

Thanh Nguyen-Tang, Sunil Gupta, A Tuan Nguyen, and Svetha Venkatesh. Offline neural contextual bandits: Pessimism, optimization and generalization. *arXiv preprint arXiv:2111.13807*, 2021a.

Thanh Nguyen-Tang, Sunil Gupta, Hung Tran-The, and Svetha Venkatesh. Sample complexity of offline reinforcement learning with deep relu networks, 2021b.

Xinkun Nie, Emma Brunskill, and Stefan Wager. Learning when-to-treat policies. *Journal of the American Statistical Association*, 116(533):392–409, 2021.

Ian Osband, Daniel Russo, and Benjamin Van Roy. (more) efficient reinforcement learning via posterior sampling. *Advances in Neural Information Processing Systems*, 26, 2013.

Ian Osband, Benjamin Van Roy, and Zheng Wen. Generalization and exploration via randomized value functions. In *International Conference on Machine Learning*, pp. 2377–2386. PMLR, 2016.

Ian Osband, Benjamin Van Roy, Daniel J Russo, Zheng Wen, et al. Deep exploration via randomized value functions. *J. Mach. Learn. Res.*, 20(124):1–62, 2019.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32, 2019.

Paria Rashidinejad, Banghua Zhu, Cong Ma, Jiantao Jiao, and Stuart Russell. Bridging offline reinforcement learning and imitation learning: A tale of pessimism. *Advances in Neural Information Processing Systems*, 34, 2021.

Niranjan Srinivas, Andreas Krause, Sham M Kakade, and Matthias Seeger. Gaussian process optimization in the bandit setting: No regret and experimental design. *arXiv preprint arXiv:0912.3995*, 2009.

Ingo Steinwart and Andreas Christmann. *Support vector machines*. Springer Science & Business Media, 2008.

Alex Strehl, John Langford, Sham Kakade, and Lihong Li. Learning from logged implicit exploration data. *arXiv preprint arXiv:1003.0120*, 2010.

Philip S. Thomas, Georgios Theocharous, Mohammad Ghavamzadeh, Ishan Durugkar, and Emma Brunskill. Predictive off-policy policy evaluation for nonstationary decision problems, with applications to digital marketing. In *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence*, AAAI'17, pp. 4740–4745. AAAI Press, 2017.

Joel Tropp. Freedman's inequality for matrix martingales. *Electronic Communications in Probability*, 16:262–270, 2011.

Masatoshi Uehara and Wen Sun. Pessimistic model-based offline reinforcement learning under partial coverage. *arXiv preprint arXiv:2107.06226*, 2021.

Michal Valko, Nathaniel Korda, Rémi Munos, Ilias Flaounas, and Nelo Cristianini. Finite-time analysis of kernelised contextual bandits. *arXiv preprint arXiv:1309.6869*, 2013.

Kerong Wang, Hanye Zhao, Xufang Luo, Kan Ren, Weinan Zhang, and Dongsheng Li. Bootstrapped transformer for offline reinforcement learning. *arXiv preprint arXiv:2206.08569*, 2022a.

Ruosong Wang, Dean P Foster, and Sham M Kakade. What are the statistical limits of offline rl with linear function approximation? *arXiv preprint arXiv:2010.11895*, 2020a.

Ruosong Wang, Russ R Salakhutdinov, and Lin Yang. Reinforcement learning with general value function approximation: Provably efficient approach via bounded eluder dimension. *Advances in Neural Information Processing Systems*, 33:6123–6135, 2020b.

Zhendong Wang, Jonathan J Hunt, and Mingyuan Zhou. Diffusion policies as an expressive policy class for offline reinforcement learning. *arXiv preprint arXiv:2208.06193*, 2022b.

Chenjun Xiao, Yifan Wu, Jincheng Mei, Bo Dai, Tor Lattimore, Lihong Li, Csaba Szepesvari, and Dale Schuurmans. On the optimality of batch policy optimization algorithms. In *International Conference on Machine Learning*, pp. 11362–11371. PMLR, 2021.

Tengyang Xie, Ching-An Cheng, Nan Jiang, Paul Mineiro, and Alekh Agarwal. Bellman-consistent pessimism for offline reinforcement learning. *Advances in neural information processing systems*, 34, 2021.

Wei Xiong, Han Zhong, Chengshuai Shi, Cong Shen, Liwei Wang, and T. Zhang. Nearly minimax optimal offline reinforcement learning with linear function approximation: Single-agent mdp and markov game. *ArXiv*, abs/2205.15512, 2022.

Tengyu Xu and Yingbin Liang. Provably efficient offline reinforcement learning with trajectory-wise reward. *arXiv preprint arXiv:2206.06426*, 2022.

Lin Yang and Mengdi Wang. Sample-optimal parametric q-learning using linearly additive features. In *International Conference on Machine Learning*, pp. 6995–7004. PMLR, 2019.

Lin Yang and Mengdi Wang. Reinforcement learning in feature space: Matrix bandit, kernels, and regret bound. In *International Conference on Machine Learning*, pp. 10746–10756. PMLR, 2020.

Zhuoran Yang, Chi Jin, Zhaoran Wang, Mengdi Wang, and Michael I Jordan. On function approximation in reinforcement learning: Optimism in the face of large state spaces. *arXiv preprint arXiv:2011.04622*, 2020.

Ming Yin, Yaqi Duan, Mengdi Wang, and Yu-Xiang Wang. Near-optimal offline reinforcement learning with linear representation: Leveraging variance information with pessimism. *International Conference on Learning Representations*, 2022.

Andrea Zanette. Exponential lower bounds for batch reinforcement learning: Batch rl can be exponentially harder than online rl. In *International Conference on Machine Learning*, pp. 12287–12297. PMLR, 2021.

Wenhao Zhan, Baihe Huang, Audrey Huang, Nan Jiang, and Jason D Lee. Offline reinforcement learning with realizability and single-policy concentrability. *arXiv preprint arXiv:2202.04634*, 2022.

Dongruo Zhou, Lihong Li, and Quanquan Gu. Neural contextual bandits with ucb-based exploration. In *International Conference on Machine Learning*, pp. 11492–11502. PMLR, 2020.

A   EXPERIMENT DETAILS

A.1   LINEAR MDPS

In this subsection, we provide further details to the experiment setup used in Subsection 6.1. We describe in detail a variant of the hard instance of linear MDPs (Yin et al., 2022; Min et al., 2021) used in our experiment. The linear MDP has $\mathcal{S} = \{0, 1\}$, $\mathcal{A} = \{0, 1, \cdots, 99\}$, and the feature dimension $d = 10$. Each action $a \in [99] = \{1, \ldots, 99\}$ is represented by its binary encoding vector $u_a \in \mathbb{R}^8$ with entry being either -1 or 1. The feature mapping $\phi(s, a)$ is given by $\phi(s, a) = [u_a^T, \delta(s, a), 1 - \delta(s, a)]^T \in \mathbb{R}^{10}$, where $\delta(s, a) = 1$ if $(s, a) = (0, 0)$ and $\delta(s, a) = 0$ otherwise. The true measure $\nu_h(s)$ is given by $\nu_h(s) = [0, \cdots, 0, (1 - s) \oplus \alpha_h, s \oplus \alpha_h]$ where $\{\alpha_h\}_{h \in [H]} \in \{0, 1\}^H$ are generated uniformly at random and $\oplus$ is the XOR operator. We define $\theta_h = [0, \cdots, 0, r, 1 - r]^T \in \mathbb{R}^{10}$ where $r = 0.99$. Recall that the transition follows $\mathbb{P}_h(s'|s, a) = \langle \phi(s, a), \nu_h(s') \rangle$ and the mean reward $r_h(s, a) = \langle \phi(s, a), \theta_h \rangle$. We generated a priori $K \in \{1, \ldots, 1000\}$ trajectories using the behavior policy μ, where for any $h \in [H]$ we set $\mu_h(0|0) = p, \mu_h(1|0) = 1 - p, \mu_h(a|0) = 0, \forall a > 1; \mu_h(0|1) = p, \mu_h(a|1) = (1 - p)/99, \forall a > 0$, where we set $p = 0.6$.

We run over $K \in \{1, \ldots, 1000\}$ and $H \in \{20, 30, 50, 80\}$. We set $\lambda = 0.01$ for all algorithms. For LinPER, we grid searched $\sigma_h = \sigma \in \{0.0, 0.1, 0.5, 1.0, 2.0\}$ and $M \in \{1, 2, 10, 20\}$. For LinLCB, we grid searched its uncertainty multiplier $\beta \in \{0.1, 0.5, 1, 2\}$. The sub-optimality metric is used to compare algorithms. For each $H \in \{20, 30, 50, 80\}$, each algorithm was executed for 30 times and the averaged results (with std) are reported in Figure 2.

A.2   NEURAL CONTEXTUAL BANDITS

In this subsection, we provide in detail the experimental and hyperparameter setup in our experiment in Subsection 6.2. For NeuralPER, NeuralGreedy, NeuraLCB and NeuraLCB (Diag), we use the same neural network architecture with two hidden layers whose width $m = 64$, train the network with Adam optimizer (Kingma & Ba, 2014) with learning rate being grid-searched over $\{0.0001, 0.001, 0.01\}$ and batch size of 64. For NeuraLCB, NeuraLCB (Diag), and LinLCB, we grid-searched β over $\{0.001, 0.01, 0.1, 1, 5, 10\}$. For NeuralPER and LinPER, we grid-searched $\sigma_h = \sigma$ over $\{0.001, 0.01, 0.1, 1, 5, 10\}$ and M over $\{1, 10, 20\}$. We did not run NeuraLCB in MNIST as the inverse of a full covariance matrix in this case is extremely expensive. We fixed the regularization parameter $\lambda = 0.01$ for all algorithms. Offline data is generated by the $(1 - \epsilon)$-optimal policy which generates non-optimal actions with probability ϵ and optimal actions with probability $1 - \epsilon$. We set $\epsilon = 0.5$ in our experiments. To estimate the expected sub-optimality, we randomly obtain $1,000$ novel samples (i.e. not used in training) to compute the average sub-optimality and keep these same samples for all algorithms.

B   EXTENDED DISCUSSION

B.1   COMPARISON WITH OTHER WORKS AND DISCUSSION

We provide further discussion regarding comparison with other works in the literature.

Comparing to (Jin et al., 2021).   When the underlying MDP reduces into a linear MDP, if we use the linear model as the plug-in parametric model in Algorithm 1, our bound reduces into $\tilde{\mathcal{O}}\left(\frac{\kappa H^{5/2} d_{lin}}{\sqrt{K}}\right)$ which improves the bound $\tilde{\mathcal{O}}(d_{lin}^{3/2} H^2/\sqrt{K})$ of PEVI (Jin et al., 2021, Corollary 4.6) by a factor of $\sqrt{d_{lin}}$ and worsen by a factor of $\sqrt{H}$ due to the data splitting. Thus, our bound is more favorable in the linear MDPs with high-dimensional features. Moreover, our bound is guaranteed in more practical scenarios where the offline data can have been adaptively generated and is not required to uniformly cover the state-action space. The explicit bound $\tilde{\mathcal{O}}(d_{lin}^{3/2} H^2/\sqrt{K})$ of PEVI (Jin et al., 2021, Corollary 4.6) is obtained under the assumption that the offline data has uniform coverage and are generated independently on the episode basis.

Comparing to (Yang et al., 2020).   Though Yang et al. (2020) work in the online regime, it shares some part of the literature with our work in function approximation for RL. Besides from different

learning regimes (offline versus online), we offer three key distinctions which can potentially used in the online regime as well: (i) perturbed rewards, (ii) optimization and (iii) data split. Regarding (i), our perturbed reward design can be applied to online RL with function approximation to obtain a provably efficient online RL that is computationally efficient, and thus remove the need of maintaining an explicit confidence regions and performing the inverse of a large covariance matrix. Regarding (ii), we incorporate the optimization analysis into our algorithm which makes our algorithm and analysis more practical. We also note that unlike (Yang et al., 2020), we do not make any assumption on the eigenvalue decay rate of the empirical NTK kernel as the empirical NTK kernel is data-dependent. Regarding (iii), our data split technique completely removes the factor $\sqrt{\log \mathcal{N}_\infty(\mathcal{H}, 1/K, B)}$ in the bound at the expense of increasing the bound by a factor of $\sqrt{H}$. In complex models, such log covering number can be excessively larger than the horizon H, making the algorithm too optimistic in the online regime (optimistic in the offline regime, respectively). For example, the target function class is RKHS with a γ-polynomial decay, the log covering number scales as (Yang et al., 2020, Lemma D1),

$$\sqrt{\log \mathcal{N}_\infty(\mathcal{H}, 1/K, B)} \lesssim K^{\frac{2}{\alpha\gamma - 1}},$$

for some $\alpha \in (0, 1)$. In the case of two-layer ReLU NTK, $\gamma = d$ (Bietti & Mairal, 2019), thus $\sqrt{\log \mathcal{N}_\infty(\mathcal{H}, 1/K, B)} \lesssim K^{\frac{2}{\alpha d - 1}}$ which is much larger than $\sqrt{H}$ when the size of dataset is large. Note that our data splitting technique is general that can be used in the online regime as well.

Comparing with (Xu & Liang, 2022). Xu & Liang (2022) consider a different setting where per-timestep rewards are not available and only the total reward of the whole trajectory is given. Used with neural function approximation, they obtain $\tilde{\mathcal{O}}(D_{\text{eff}} H^2 / \sqrt{K})$ where D_{eff} is their effective dimension. Note that Xu & Liang (2022) do not use data splitting and still achieve the same order of D_{eff} as our result with data splitting. It at first might appear that our bound is inferior to their bound as we pay the cost of $\sqrt{H}$ due to data splitting. However, to obtain that bound, they make three critical assumptions: (i) the offline data trajectories are independently and identically distributed (i.i.d.) (see their Assumption 3), (ii) the offline data is uniformly explorative over all dimensions of the feature space (also see their Assumption 3), and (iii) the eigenfunctions of the induced NTK RKHS has finite spectrum (see their Assumption 4). The i.i.d. assumption under the RKHS space with finite dimensions (due to the finite spectrum assumption) and the well-explored dataset is critical in their proof to use a matrix concentration that does not incur an extra factor of $\sqrt{D_{\text{eff}}}$ as it would normally do without these assumptions (see Section E, the proof of their Lemma 2). Note that the celebrated ReLU NTK does not satisfy the finite spectrum assumption (Bietti & Mairal, 2019). Moreover, we do not make any of these three assumptions above for our bound to hold. That suggests that our bound is much more general. In addition, we do not need to compute any confidence regions nor perform the inverse of a large covariance matrix.

B.2 Worse-Case Rate of Effective Dimension

In the main paper, we prove an $\tilde{\mathcal{O}}\left(\frac{\kappa H^{5/2} \tilde{d}}{\sqrt{K}}\right)$ sub-optimality bound which depends on the notion of effective dimension defined in Definition 2. Here we give a worst-case rate of the effective dimension $\tilde{d}$ for the two-layer ReLU NTK. We first briefly review the background of RKHS.

Let $\mathcal{H}$ be an RKHS defined on $\mathcal{X} \subseteq \mathbb{R}^d$ with kernel function $\rho : \mathcal{X} \times \mathcal{X} \to \mathbb{R}$. Let $\langle \cdot, \cdot \rangle_{\mathcal{H}} : \mathcal{H} \times \mathcal{H} \to \mathbb{R}$ and $\|\cdot\|_{\mathcal{H}} : \mathcal{H} \to \mathbb{R}$ be the inner product and the RKSH norm on $\mathcal{H}$. By the reproducing kernel property of $\mathcal{H}$, there exists a feature mapping $\phi : \mathcal{X} \to \mathcal{H}$ such that $f(x) = \langle f, \phi(x) \rangle_{\mathcal{H}}$ and $\rho(x, x') = \langle \phi(x), \phi(x') \rangle_{\mathcal{H}}$. We assume that the kernel function rho is uniformly bounded, i.e. $\sup_{x \in \mathcal{X}} \rho(x, x) < \infty$. Let $\mathcal{L}^2(\mathcal{X})$ be the space of square-integral functions on $\mathcal{X}$ with respect to the Lebesgue measure and let $\langle \cdot, \cdot \rangle_{\mathcal{L}^2}$ be the inner product on $\mathcal{L}^2(\mathcal{X})$. The kernel function ρ induces an integral operator $T_\rho : \mathcal{L}^2(\mathcal{X}) \to \mathcal{L}^2(\mathcal{X})$ defined as

$$T_\rho f(x) = \int_{\mathcal{X}} \rho(x, x') f(x') dx'.$$

By Mercer's theorem (Steinwart & Christmann, 2008), T_ρ has countable and positive eigenvalues $\{\lambda_i\}_{i \geq 1}$ and eigenfunctions $\{\nu_i\}_{i \geq 1}$. The kernel function and $\mathcal{H}$ can be expressed as

$$\rho(x, x') = \sum_{i=1}^{\infty} \lambda_i \nu_i(x) \nu_i(x'),$$

$$\mathcal{H} = \{f \in \mathcal{L}^2(\mathcal{X}) : \sum_{i=1}^{\infty} \frac{\langle f, \nu_i \rangle_{\mathcal{L}^2}}{\lambda_i} < \infty\}.$$

Now consider the NTK defined in Definition 1:

$$K_{ntk}(x, x') = \mathbb{E}_{w \sim \mathcal{N}(0, I_d/d)} \langle x \sigma'(w^T x), x' \sigma'(w^T x') \rangle.$$

It follows from (Bietti & Mairal, 2019, Proposition 1) that $\lambda_i \asymp i^{-d}$. Thus, by (Srinivas et al., 2009, Theorem 5), the data-dependent effective dimension of $\mathcal{H}_{ntk}$ can be bounded in the worst case by

$$\tilde{d} \lesssim K'^{(d+1)/(2d)}.$$

We remark that this is the worst-case bound that considers uniformly over all possible realizable of training data. The effective dimension $\tilde{d}$ is on the other hand data-dependent, i.e. its value depends on the specific training data at hand thus $\tilde{d}$ can be actually much smaller than the worst-case rate.

C   PROOF OF THEOREM 1 AND THEOREM 2

In this section, we provide both the outline and detailed proofs of Theorem 1 and Theorem 2.

C.1   PROOF OF THEOREM 1

In this subsection, we present the proof of Theorem 1. We first decompose the suboptimality $\mathrm{SubOpt}(\tilde{\pi}; s)$ and present the main lemmas to bound the evaluation error and the summation of the implicit confidence terms, respectively. The detailed proof of these lemmas are deferred to Section D. For proof convenience, we first provide the key parameters that we use consistently throughout our proofs in Table 2.

We define the model evaluation error at any $(x, h) \in \mathcal{X} \times [H]$ as

$$err_h(x) = (\mathbb{B}_h \tilde{V}_{h+1} - \tilde{Q}_h)(x), \tag{1}$$

where $\mathbb{B}_h$ is the Bellman operator defined in Section 3, and $\tilde{V}_h$ and $\tilde{Q}_h$ are the estimated (action-) state value functions returned by Algorithm 1. Using the standard suboptimality decomposition (Jin et al., 2021, Lemma 3.1), for any $s_1 \in \mathcal{S}$,

$$\mathrm{SubOpt}(\tilde{\pi}; s_1) = -\sum_{h=1}^{H} \mathbb{E}_{\tilde{\pi}} [err_h(s_h, a_h)] + \sum_{h=1}^{H} \mathbb{E}_{\pi^*} [err_h(s_h, a_h)]$$

$$+ \sum_{h=1}^{H} \mathbb{E}_{\pi^*} \underbrace{\left[\langle \tilde{Q}_h(s_h, \cdot), \pi_h^*(\cdot|s_h) - \tilde{\pi}_h(\cdot|s_h) \rangle_{\mathcal{A}} \right]}_{\leq 0},$$

where the third term is third term is non-positive as $\tilde{\pi}_h$ is greedy with respect to $\tilde{Q}_h$. Thus, for any $s_1 \in \mathcal{S}$, we have

$$\mathrm{SubOpt}(\tilde{\pi}; s_1) \leq -\sum_{h=1}^{H} \mathbb{E}_{\tilde{\pi}} [err_h(s_h, a_h)] + \sum_{h=1}^{H} \mathbb{E}_{\pi^*} [err_h(s_h, a_h)]. \tag{2}$$

In the following main lemma, we bound the evaluation error $err_h(s, a)$. In the rest of the proof, we consider an additional parameter R and fix any $\delta \in (0, 1)$.

Parameters	Meaning/Expression
m	Network width
λ	Regularization parameter
η	Learning rate
M	Number of bootstraps
$\{\sigma_h\}_{h\in[H]}$	Noise variances
J	Number of GD steps
ψ	Cutoff margin
K	Number of offline episodes
R	Radius parameter
δ	Failure level
K'	bucket size, K/H
$\mathcal{I}_h$	index buckets, $[(H-h)K'+1, (H-h)K'+2, \ldots, (H-h+1)K']$
B	Parameter radius of the Bellman operator
$\gamma_{h,1}$	$c_1\sigma_h\sqrt{\log(KM/\delta)}$
$\gamma_{h,2}$	$c_2\sigma_h\sqrt{d\log(dKM/\delta)}$
B_1	$\lambda^{-1}\sqrt{2K(H+\psi)^2 + 8C_gR^{4/3}m^{-1/6}\sqrt{\log m}}\sqrt{K}C_gR^{1/3}m^{-1/6}\sqrt{\log m}$
$\tilde{B}_1$	$\lambda^{-1}\sqrt{2K'(H+\psi+\gamma_{h,1})^2 + \lambda\gamma_{h,2}^2 + 8C_gR^{4/3}m^{-1/6}\sqrt{\log m}}\sqrt{K'}C_gR^{1/3}m^{-1/6}\sqrt{\log m}$
$\tilde{B}_2$	$\lambda^{-1}K'C_gR^{4/3}m^{-1/6}\sqrt{\log m}$
ι_0	$Bm^{-1/2}(2\sqrt{d} + \sqrt{2\log(3H/\delta)})$
ι_1	$C_gR^{4/3}m^{-1/6}\sqrt{\log m} + C_g\left(\tilde{B}_1 + \tilde{B}_2 + \lambda^{-1}(1-\eta\lambda)^J\left(K'(H+\psi+\gamma_{h,1})^2 + \lambda\gamma_{h,2}^2\right)\right)$
ι_2	$C_gR^{4/3}m^{-1/6}\sqrt{\log m} + C_g\left(B_1 + \tilde{B}_2 + \lambda^{-1}(1-\eta\lambda)^JK'(H+\psi)^2\right)$
ι	$\iota_0 + \iota_1 + 2\iota_2$
β	$\frac{BK'}{\sqrt{m}}(2\sqrt{d} + \sqrt{2\log(3H/\delta)})\lambda^{-1/2}C_g + \lambda^{1/2}B$ $+(H+\psi)\left[\sqrt{\tilde{d}_h\log(1+\frac{K'}{\lambda})} + K'\log\lambda + 2\log(3H/\delta)\right]$

Table 2: The problem parameters and the additional parameters that we introduce for our proofs. Here c_1, c_2, and C_g are some absolute constants independent of the problem parameters.

Lemma C.1. *Let*

$$\begin{cases} m = \Omega\left(d^{3/2}R^{-1}\log^{3/2}(\sqrt{m}/R)\right) \\ R = \mathcal{O}\left(m^{1/2}\log^{-3}m\right), \\ m = \Omega\left(K'^{10}(H+\psi)^2\log(3K'H/\delta)\right) \\ \lambda > 1 \\ K'C_g^2 \geq \lambda R \geq \max\{4\tilde{B}_1, 4\tilde{B}_2, 2\sqrt{2\lambda^{-1}K'(H+\psi+\gamma_{h,1})^2 + 4\gamma_{h,2}^2}\}, \\ \eta \leq (\lambda + K'C_g^2)^{-1}, \\ \psi > \iota, \\ \sigma_h \geq \beta, \forall h \in [H], \end{cases} \quad (3)$$

where $\tilde{B}_1$, $\tilde{B}_2$, $\gamma_{h,1}$, $\gamma_{h,2}$, and ι are defined in Table 2, C_g is a absolute constant given in Lemma G.1, and R is an additional parameter. Let $M = \log\frac{HSA}{\delta}/\log\frac{1}{1-\Phi(-1)}$ where $\Phi(\cdot)$ is the cumulative distribution function of the standard normal distribution. With probability at least $1 - MHm^{-2} - 2\delta$, for any $(x, h) \in \mathcal{X} \times [H]$, we have

$$-\iota \leq err_h(x) \leq \sigma_h(1 + \sqrt{2\log(SAH/\delta)}) \cdot \|g(x; W_0)\|_{\Lambda_h^{-1}} + \iota$$

where $\Lambda_h := \lambda I_{md} + \sum_{k \in \mathcal{I}_h} g(x_h^k; W_0)g(x_h^k; W_0)^T \in \mathbb{R}^{md \times md}$.

Now we can prove Theorem 1.

Proof of Theorem 1. Theorem 1 can directly follows from substituting Lemma C.1 into Equation (2). We now only need to simplify the conditions in Equation (3). To satisfy Equation (3), it suffices to set

$$\begin{cases} \lambda = 1 + \frac{H}{K} \\ \psi = 1 > \iota \\ \sigma_h = \beta \\ 8C_g R^{4/3}m^{-1/6}\sqrt{\log m} \leq 1 \\ \lambda^{-1}K'H^2 \geq 2 \\ \tilde{B}_1 \leq \sqrt{2K'(H+\psi+\gamma_{h,1})^2 + \lambda\gamma_{h,2}^2 + 1}\sqrt{K'}C_g R^{1/3}m^{-1/6}\sqrt{\log m} \leq 1 \\ \tilde{B}_2 \leq K'C_g R^{4/3}m^{-1/6}\sqrt{\log m} \leq 1. \end{cases}$$

Combining with Equation 3, we have

$$\begin{cases} \lambda = 1 + \frac{H}{K} \\ \psi = 1 > \iota \\ \sigma_h = \beta \\ \eta \lesssim (\lambda + K')^{-1} \\ m \gtrsim \max\left\{R^8\log^3 m, K'^{10}(H+1)^2\log(3K'H/\delta), d^{3/2}R^{-1}\log^{3/2}(\sqrt{m}/R), K'^6 R^8\log^3 m\right\} \\ m \gtrsim [2K'(H+1+\beta\sqrt{\log(K'M/\delta)})^2 + \lambda\beta^2 d\log(dK'M/\delta) + 1]^3 K'^3 R\log^3 m \\ 4\sqrt{K'}(H+1+\beta\sqrt{\log(K'M/\delta)}) + 4\beta\sqrt{d\log(dK'M/\delta)} \leq R \lesssim K'. \end{cases} \quad (4)$$

Note that with the above choice of $\lambda = 1 + \frac{H}{K}$, we have

$$K'\log\lambda = \log(1 + \frac{1}{K'})^{K'} \leq \log 3 < 2.$$

We further set that $m \gtrsim B^2 K'^2 d\log(3H/\delta)$, we have

$$\beta = \frac{BK'}{\sqrt{m}}(2\sqrt{d} + \sqrt{2\log(3H/\delta)})\lambda^{-1/2}C_g + \lambda^{1/2}B + (H+\psi)\left[\sqrt{\tilde{d}_h\log(1 + \frac{K'}{\lambda})} + K'\log\lambda + 2\log(3H/\delta)\right]$$

$$\le 1 + \lambda^{1/2} B + (H+1) \left[\sqrt{\tilde{d}_h \log(1 + \frac{K'}{\lambda})} + 2 + 2\log(3H/\delta) \right] = o(\sqrt{K'}).$$

Thus,

$$4\sqrt{K'}(H + 1 + \beta\sqrt{\log(K'M/\delta)}) + 4\beta\sqrt{d\log(dK'M/\delta)} << K'$$

for K' large enough. Therefore, there exists R that satisfies Equation (4). We now only need to verify $\iota < 1$. We have

$$\iota_0 = Bm^{-1/2}(2\sqrt{d} + \sqrt{2\log(3H/\delta)}) \le 1/3,$$

$$\iota_1 = C_g R^{4/3} m^{-1/6} \sqrt{\log m} + C_g \left(\tilde{B}_1 + \tilde{B}_2 + \lambda^{-1}(1 - \eta\lambda)^J \left(K'(H + 1 + \gamma_{h,1})^2 + \lambda\gamma_{h,2}^2 \right) \right) \lesssim 1/3$$

if

$$(1 - \eta\lambda)^J \left[K'(H + 1 + \beta\sqrt{\log(K'M/\delta)})^2 + \lambda\beta^2 d\log(dK'M/\delta) \right] \lesssim 1. \qquad (5)$$

Note that

$$(1 - \eta\lambda)^J \le e^{-\eta\lambda J},$$

$$K'(H + 1 + \beta\sqrt{\log(K'M/\delta)})^2 + \lambda\beta^2 d\log(dK'M/\delta) \lesssim K'H^2\lambda\beta^2 d\log(dK'M/\delta).$$

Thus, Equation (5) is satisfied if

$$J \gtrsim \eta\lambda \log \left(K'H^2\lambda\beta^2 d\log(dK'M/\delta) \right).$$

Finally note that $\iota_2 \le \iota_1$. Rearranging the derived conditions here gives the complete parameter conditions in Theorem 1.

$\square$

C.2 PROOF OF THEOREM 2

In this subsection, we give a detailed proof of Theorem 2. We first present intermediate lemmas whose proofs are deferred to Section D. For any $h \in [H]$ and $k \in \mathcal{I}_h = [(H - h)K' + 1, \dots, (H - h + 1)K']$, we define the filtration

$$\mathcal{F}_h^k = \sigma \left(\{(s_{h'}^t, a_{h'}^t, r_{h'}^t)\}_{h' \in [H]}^{t \le k} \cup \{(s_{h'}^{k+1}, a_{h'}^{k+1}, r_{h'}^{k+1})\}_{h' \le h-1} \cup \{(s_h^{k+1}, a_h^{k+1})\} \right).$$

Let

$$\Lambda_h^k := \lambda I + \sum_{t \in \mathcal{I}_k, t \le k} g(x_h^t; W_0) g(x_h^t; W_0)^T,$$

$$\tilde{\beta} := \beta(1 + 2\sqrt{\log(SAH/\delta)}).$$

In the following lemma, we connect the expected sub-optimality of $\tilde{\pi}$ to the summation of the uncertainty quantifier at empirical data.

Lemma C.2. *Suppose that the conditions in Theorem 1 all hold. With probability at least* $1 - MHm^{-2} - 3\delta$,

$$\text{SubOpt}(\tilde{\pi}) \le \frac{2\tilde{\beta}}{K'} \sum_{h=1}^{H} \sum_{k \in \mathcal{I}_h} \mathbb{E}_{\pi^*} \left[\|g(x_h; W_0)\|_{(\Lambda_h^k)^{-1}} \Big| \mathcal{F}_h^{k-1}, s_1^k \right] + \frac{16}{3K'} H \log(\log_2(K'H)/\delta) + \frac{2}{K'} + 2\iota,$$

Lemma C.3. *Under Assumption 5.2, for any $h \in [H]$ and fixed W_0, with probability at least $1 - \delta$,*

$$\sum_{k \in \mathcal{I}_h} \mathbb{E}_{\pi^*} \left[\|g(x_h; W_0)\|_{(\Lambda_h^k)^{-1}} \Big| \mathcal{F}_{k-1}, s_1^k \right] \le \sum_{k \in \mathcal{I}_h} \kappa \|g(x_h; W_0)\|_{(\Lambda_h^k)^{-1}} + \kappa \sqrt{\frac{K' \log(1/\delta)}{\lambda}}.$$

Lemma C.4. *If $\lambda \ge C_g^2$ and $m = \Omega(K'^4 \log(K'H/\delta))$, then with probability at least $1 - \delta$, for any $h \in [H]$, we have*

$$\sum_{k \in \mathcal{I}_h} \|g(x_h; W_0)\|_{(\Lambda_h^k)^{-1}}^2 \le 2\tilde{d}_h \log(1 + K'/\lambda) + 1.$$

where $\tilde{d}_h$ is the effective dimension defined in Definition 2.

Proof of Theorem 2. Theorem 2 directly follows from Lemma C.2-C.3-C.4 using the union bound.

$\square$

D PROOF OF LEMMA C.1

In this section, we provide the proof for Lemma C.1. We set up preparation for all the results in the rest of the paper and provide intermediate lemmas that we use to prove Lemma C.1. The detailed proofs of these intermediate lemmas are deferred to Section E.

D.1 PREPARATION

To prepare for the lemmas and proofs in the rest of the paper, we define the following quantities. Recall that we use abbreviation $x = (s, a) \in \mathcal{X} \subset \mathbb{S}_{d-1}$ and $x_h^k = (s_h^k, a_h^k) \in \mathcal{X} \subset \mathbb{S}_{d-1}$. For any $h \in [H]$ and $i \in [M]$, we define the perturbed loss function

$$\tilde{L}_h^i(W) := \frac{1}{2} \sum_{k \in \mathcal{I}_h} \left(f(x_h^k; W) - \tilde{y}_h^{i,k} \right)^2 + \frac{\lambda}{2} \|W + \zeta_h^i - W_0\|_2^2, \tag{6}$$

where

$$\tilde{y}_h^{i,k} := r_h^k + \tilde{V}_{h+1}(s_{h+1}^k) + \xi_h^{i,k},$$

$\tilde{V}_{h+1}$ is computed by Algorithm 1 at Line 10 for timestep $h+1$, and $\{\xi_h^{i,k}\}$ and ζ_h^i are the Gaussian noises obtained at Line 5 of Algorithm 1.

Here the subscript h and the superscript i in $\tilde{L}_h^i(W)$ emphasize the dependence on the ensemble sample i and timestep h. The gradient descent update rule of $\tilde{L}_h^i(W)$ is

$$\tilde{W}_h^{i,(j+1)} = \tilde{W}_h^{i,(j)} - \eta \nabla \tilde{L}_h^i(W), \tag{7}$$

where $\tilde{W}_h^{i,(0)} = W_0$ is the initialization parameters. Note that

$$\tilde{W}_h^i = \text{GradientDescent}(\lambda, \eta, J, \tilde{\mathcal{D}}_h^i, \zeta_h^i, W_0) = \tilde{W}_h^{i,(J)},$$

where $\tilde{W}_h^i$ is returned by Line 7 of Algorithm 1. We consider a non-perturbed auxiliary loss function

$$L_h(W) := \frac{1}{2} \sum_{k \in \mathcal{I}_h} \left(f(x_h^k; W) - y_h^k \right)^2 + \frac{\lambda}{2} \|W - W_0\|_2^2, \tag{8}$$

where

$$y_h^k := r_h^k + \tilde{V}_{h+1}(s_{h+1}^k).$$

Note that $L_h(W)$ is simply a non-perturbed version of $\tilde{L}_h^i(W)$ where we drop all the noises $\{\xi_h^{i,k}\}$ and $\{\zeta_h^i\}$. We consider the gradient update rule for $L_h(W)$ as follows

$$\hat{W}_h^{(j+1)} = \hat{W}_h^{(j)} - \eta \nabla L_h(W), \tag{9}$$

where $\hat{W}_h^{(0)} = W_0$ is the initialization parameters. To correspond with $\tilde{W}_h^i$, we denote

$$\hat{W}_h := \hat{W}_h^{(J)}. \tag{10}$$

We also define the auxiliary loss functions for both non-perturbed and perturbed data in the linear model with feature $g(\cdot; W_0)$ as follows

$$\tilde{L}_h^{i,lin}(W) := \frac{1}{2} \sum_{k \in \mathcal{I}_h} \left(\langle g(x_h^k; W_0), W \rangle - \tilde{y}_h^{i,k} \right)^2 + \frac{\lambda}{2} \|W + \zeta_h^i - W_0\|_2^2, \tag{11}$$

$$L_h^{lin}(W) := \frac{1}{2} \sum_{k \in \mathcal{I}_h} \left(\langle g(x_h^k; W_0), W \rangle - y_h^k \right)^2 + \frac{\lambda}{2} \|W - W_0\|_2^2. \tag{12}$$

We consider the auxiliary gradient updates for $\tilde{L}_h^{i,lin}(W)$ as

$$\tilde{W}_h^{i,lin,(j+1)} = \tilde{W}_h^{i,lin,(j)} - \eta \nabla \tilde{L}_h^{i,lin}(W), \tag{13}$$

$$\hat{W}_h^{lin,(j+1)} = \hat{W}_h^{lin,(j)} - \eta\nabla\tilde{L}_h^{lin}(W), \tag{14}$$

where $\tilde{W}_h^{i,lin,(0)} = \hat{W}_h^{i,lin,(0)} = W_0$ for all i,h. Finally, we define the least-square solutions to the auxiliary perturbed and non-perturbed loss functions for the linear model as follows

$$\tilde{W}_h^{i,lin} = \underset{W\in\mathbb{R}^{md}}{\arg\max}\ \tilde{L}_h^{i,lin}(W), \tag{15}$$

$$\hat{W}_h^{lin} = \underset{W\in\mathbb{R}^{md}}{\arg\max}\ L_h^{lin}(W). \tag{16}$$

For any $h \in [H]$, we define the auxiliary covariance matrix Λ_h as follows

$$\Lambda_h := \lambda I_{md} + \sum_{k\in\mathcal{I}_h} g(x_h^k; W_0)g(x_h^k; W_0)^T. \tag{17}$$

It is worth remarking that Algorithm 1 only uses Equation (6) and (7) thus it does not actually require any of the auxiliary quantities defined in this subsection during its run time. The auxiliary quantities here are only for our theoretical analysis.

D.2   PROOF OF LEMMA C.1

In this subsection, we give a detailed proof of Lemma C.1. To prepare for proving Lemma C.1, we first provide the following intermediate lemmas. The detailed proofs of these intermediate lemmas are deferred to Section E.

In the following lemma, we bound the uncertainty $f(x; \hat{W}_h)$ in estimating the Bellman operator at the estimated state-value function $\mathbb{B}_h\tilde{V}_{h+1}$.

Lemma D.1. *Let*

$$\begin{cases} m = \Omega\left(K'^{10}(H+\psi)^2\log(3K'H/\delta)\right) \\ \lambda > 1 \\ K'C_g^2 \geq \lambda \end{cases}$$

With probability at least $1 - Hm^{-2} - 2\delta$, for any $x \in \mathbb{S}_{d-1}$, and any $h \in [H]$,

$$|f(x; \hat{W}_h) - (\mathbb{B}_h\tilde{V}_{h+1})(x)| \leq \beta \cdot \|g(x; W_0)\|_{\Lambda_h^{-1}} + \iota_2 + \iota_0,$$

where $\tilde{V}_{h+1}$ is computed by Algorithm 1 for timestep $h+1$, $\hat{W}_h$ is defined in Equation (10), and β, ι_2 and ι_0 are defined in Table 2.

In the following lemma, we establish the anti-concentration of $\tilde{Q}_h$.

Lemma D.2. *Let*

$$\begin{cases} m = \Omega\left(d^{3/2}R^{-1}\log^{3/2}(\sqrt{m}/R)\right) \\ R = \mathcal{O}\left(m^{1/2}\log^{-3} m\right), \\ \eta \leq (\lambda + K'C_g^2)^{-1}, \\ R \geq \max\{4\tilde{B}_1, 4\tilde{B}_2, 2\sqrt{2\lambda^{-1}K'(H+\psi+\gamma_{h,1})^2 + 4\gamma_{h,2}^2}\}, \end{cases} \tag{18}$$

where $\tilde{B}_1$, $\tilde{B}_2$, $\gamma_{h,1}$ and $\gamma_{h,2}$ are defined in Table 2, and C_g is a constant given in Lemma G.1. Let $M = \log\frac{HSA}{\delta}/\log\frac{1}{1-\Phi(-1)}$ where $\Phi(\cdot)$ is the cumulative distribution function of the standard normal distribution and M is the number of bootstrapped samples in Algorithm 1. Then with probability $1 - MHm^{-2} - \delta$, for any $x \in \mathbb{S}_{d-1}$ and $h \in [H]$,

$$\tilde{Q}_h(x) \leq \max\{\langle g(x; W_0), \hat{W}_h^{lin} - W_0\rangle - \sigma_h\|g(x; W_0)\|_{\Lambda_h^{-1}} + \iota_1 + \iota_2, 0\},$$

where $\hat{W}_h^{lin}$ is defined in Equation (16), $\tilde{Q}_h$ is computed by Line 9 of Algorithm 1, and ι_1 and ι_2 are defined in Table 2.

We prove the following linear approximation error lemma.

Lemma D.3. *Let*

$$
\begin{cases}
m = \Omega\left(d^{3/2}R^{-1}\log^{3/2}(\sqrt{m}/R)\right) \\
R = \mathcal{O}\left(m^{1/2}\log^{-3}m\right), \\
\eta \le (\lambda + K'C_g^2)^{-1}, \\
R \ge \max\{4\tilde{B}_1, 4\tilde{B}_2, 2\sqrt{2\lambda^{-1}K'(H + \psi + \gamma_{h,1})^2 + 4\gamma_{h,2}^2}\},
\end{cases}
\tag{19}
$$

where $\tilde{B}_1$, $\tilde{B}_2$, $\gamma_{h,1}$ and $\gamma_{h,2}$ are defined in Table 2, and C_g is a constant given in Lemma G.1. With probability at least $1 - MHm^{-2} - \delta$, for any $(x, i, j, h) \in \mathbb{S}_{d-1} \times [M] \times [J] \times [H]$,

$$
|f(x; \tilde{W}_h^{i,(j)}) - \langle g(x; W_0), \tilde{W}_h^{i,lin} - W_0\rangle| \le \iota_1,
$$

where $\tilde{W}_h^{i,(j)}$, $\tilde{W}_h^{i,lin}$, and ι_1 are defined in Equation (7), Equation (15), and Table 2, respectively.

In addition, with probability at least $1 - Hm^{-2}$, for any for any $(x, j, h) \in \mathbb{S}_{d-1} \times [J] \times [H]$,

$$
|f(x; \hat{W}_h^{(j)}) - \langle g(x; W_0), \hat{W}_h^{lin} - W_0\rangle| \le \iota_2,
$$

where $\hat{W}_h^{(j)}$, $\hat{W}_h^{lin}$, and ι_2 are defined in Equation (9), Equation (16), and Table 2, respectively.

We now can prove Lemma C.1.

Proof of Lemma C.1. Note that the the first fourth conditions in Equation (3) of Lemma C.1 satisfy Equation (19). Moreover, the event in which the inequality in Lemma D.3 holds already implies the event in which the inequality in Lemma D.1 holds (see the proofs of Lemma D.3 and Lemma D.1 in Section D). Now in the rest of the proof, we consider the joint event in which both the inequality of Lemma D.3 and that of Lemma D.1 hold. Then, we also have the inequality in Lemma D.1. Consider any $x \in \mathcal{X}, h \in [H]$.

It follow from Lemma D.1 that

$$
(\mathbb{B}_h\tilde{V}_{h+1})(x) \ge f(x; \hat{W}_h) - \beta \cdot \|g(x; W_0)\|_{\Lambda_h^{-1}} - \iota_0 - \iota_2.
$$

It follows from Lemma D.2 that

$$
\tilde{Q}_h(x) \le \max\{\langle g(x; W_0), \hat{W}_h^{lin} - W_0\rangle - \sigma_h\|g(x; W_0)\|_{\Lambda_h^{-1}} + \iota_1 + \iota_2, 0\}.
\tag{20}
$$

Note that $\tilde{Q}_h(x) \ge 0$. If $\langle g(x; W_0), \hat{W}_h^{lin} - W_0\rangle - \sigma_h\|g(x; W_0)\|_{\Lambda_h^{-1}} + \iota_1 + \iota_2 \le 0$, Equation (20) implies that $\tilde{Q}_h(x) = 0$ and thus

$$
\begin{aligned}
err_h(x) &= (\mathbb{B}_h\tilde{V}_{h+1})(x) - \tilde{Q}_h(x) \\
&= (\mathbb{B}_h\tilde{V}_{h+1})(x) \ge 0.
\end{aligned}
$$

Otherwise, if $\langle g(x; W_0), \hat{W}_h^{lin} - W_0\rangle - \sigma_h\|g(x; W_0)\|_{\Lambda_h^{-1}} + \iota_1 + \iota_2 > 0$, Equation (20) implies that

$$
\tilde{Q}_h(x) \le \langle g(x; W_0), \hat{W}_h^{lin} - W_0\rangle - \sigma_h\|g(x; W_0)\|_{\Lambda_h^{-1}} + \iota_1 + \iota_2,
$$

and thus, combing the two inequalities above with the choice $\sigma_h \ge \beta$, we have

$$
err_h(x) := (\mathbb{B}_h\tilde{V}_{h+1})(x) - \tilde{Q}_h(x) \ge -(\iota_0 + \iota_1 + 2\iota_2) = -\iota.
$$

As $\iota \ge 0$, in either case, we have

$$
err_h(x) := (\mathbb{B}_h\tilde{V}_{h+1})(x) - \tilde{Q}_h(x) \ge -\iota.
\tag{21}
$$

Note that due to Equation (21), we have

$$
\tilde{Q}_h(x) \le (\mathbb{B}_h\tilde{V}_{h+1})(x) + \iota \le H - h + 1 + \iota < H - h + 1 + \psi,
$$

where the last inequality holds due to the choice $\psi > \iota$. Thus, we have

$$\tilde{Q}_h(x) = \min\{\min_{i\in[M]} f(x;\tilde{W}_h^i), H - h + 1 + \psi\}^+ = \max\{\min_{i\in[M]} f(x;\tilde{W}_h^i), 0\}. \qquad (22)$$

Substituting Equation (22) into the definition of $err_h(x)$, we have

$$
\begin{aligned}
err_h(x) &= (\mathbb{B}_h\tilde{V}_{h+1})(x) - \tilde{Q}_h(x) \\
&\leq (\mathbb{B}_h\tilde{V}_{h+1})(x) - \min_{i\in[M]} f(x;\tilde{W}_h^i) \\
&= (\mathbb{B}_h\tilde{V}_{h+1})(x) - f(x;\hat{W}_h) + f(x;\hat{W}_h) - \min_{i\in[M]} f(x;\tilde{W}_h^i) \\
&\leq \beta \cdot \|g(x;W_0)\|_{\Lambda_h^{-1}} + \iota_0 + \iota_2 + f(x;\hat{W}_h) - \min_{i\in[M]} f(x;\tilde{W}_h^i) \\
&\leq \beta \cdot \|g(x;W_0)\|_{\Lambda_h^{-1}} + \iota_0 + \iota_2 + \langle g(x;W_0), \tilde{W}_h^{lin} - W_0\rangle + \iota_1 \\
&\quad - \min_{i\in[M]} \langle g(x;W_0), \tilde{W}_h^{i,lin} - W_0\rangle + \iota_2 \\
&= \beta \cdot \|g(x;W_0)\|_{\Lambda_h^{-1}} + \iota_0 + \iota_2 + \max_{i\in[M]} \langle g(x;W_0), \tilde{W}_h^{lin} - \tilde{W}_h^{i,lin}\rangle + \iota_1 + \iota_2 \\
&\leq \beta \cdot \|g(x;W_0)\|_{\Lambda_h^{-1}} + \iota_0 + \iota_2 + \sqrt{2\log(SAH/\delta)}\sigma_h\|g(x;W_0)\|_{\Lambda_h^{-1}} + \iota_1 + \iota_2
\end{aligned}
$$

where the first inequality holds due to Equation (22), the second inequality holds due to Lemma D.1, the third inequality holds due to Lemma D.3, and the last inequality holds due to Lemma E.2 and Lemma G.3 via the union bound.

$\square$

D.3 PROOF OF LEMMA C.2

Proof of Lemma C.2. Let $Z_k := \tilde{\beta}\sum_{h=1}^H \mathbb{E}_{\pi^*}\left[\mathbb{1}\{k\in\mathcal{I}_h\}\|g(x_h;W_0)\|_{(\Lambda_h^k)^{-1}}|s_1^k, \mathcal{F}_h^{k-1}\right]$ where $\mathbb{1}\{\}$ is the indicator function. Under the event in which the inequality in Theorem 1 holds, we have

$$
\begin{aligned}
\text{SubOpt}(\tilde{\pi}) &\leq \min\left\{H, \tilde{\beta}\cdot\mathbb{E}_{\pi^*}\left[\sum_{h=1}^H \|g(x_h;W_0)\|_{\Lambda_h^{-1}}\right] + 2\iota\right\} \\
&\leq \min\left\{H, \tilde{\beta}\mathbb{E}_{\pi^*}\left[\sum_{h=1}^H \|g(x_h;W_0)\|_{\Lambda_h^{-1}}\right]\right\} + 2\iota \\
&= \frac{1}{K'}\sum_{k=1}^K \min\left\{H, \tilde{\beta}\mathbb{E}_{\pi^*}\left[\sum_{h=1}^H \mathbb{1}\{k\in\mathcal{I}_h\}\|g(x_h;W_0)\|_{\Lambda_h^{-1}}\right]\right\} + 2\iota \\
&\leq \frac{1}{K'}\sum_{k=1}^K \min\left\{H, \tilde{\beta}\mathbb{E}_{\pi^*}\left[\sum_{h=1}^H \mathbb{1}\{k\in\mathcal{I}_h\}\|g(x_h;W_0)\|_{(\Lambda_h^k)^{-1}}|\mathcal{F}_h^{k-1}\right]\right\} + 2\iota \\
&= \frac{1}{K'}\sum_{k=1}^K \min\left\{H, \mathbb{E}[Z_k|\mathcal{F}_h^{k-1}]\right\} + 2\iota \\
&\leq \frac{1}{K'}\sum_{k=1}^K \mathbb{E}\left[\min\{H, Z_k\}|\mathcal{F}_h^{k-1}\right] + 2\iota, \qquad (23)
\end{aligned}
$$

where the first inequality holds due to Theorem 1 and that $\text{SubOpt}(\tilde{\pi}; s_1) \leq H, \forall s_1 \in \mathcal{S}$, the second inequality holds due to $\min\{a, b + c\} \leq \min\{a, b\} + c$, the third inequality holds due to that $\Lambda_h^{-1} \preceq (\Lambda_h^k)^{-1}$, the fourth inequality holds due to Jensen's inequality for the convex function $f(x) = \min\{H, x\}$. It follows from Lemma G.9 that with probability at least $1 - \delta$,

$$\sum_{k=1}^K \mathbb{E}\left[\min\{H, Z_k\}|\mathcal{F}_{k-1}\right] \leq 2\sum_{k=1}^K Z_k + \frac{16}{3}H\log(\log_2(KH)/\delta) + 2. \qquad (24)$$

Substituting Equation (24) into Equation (23) and using the union bound complete the proof.

$\square$

D.4 PROOF OF LEMMA C.3

Proof of Lemma C.3. Let $Z_h^k := \mathbb{1}\{k \in \mathcal{I}_h\}\frac{d_h^*(x_h^k)}{d_h^\mu(x_h^k)}\|g(x_h^k; W_0)\|_{(\Lambda_h^k)^{-1}}$. We have Z_h^k is $\mathcal{F}_h^k$-measurable, and by Assumption 5.2, we have,

$$|Z_h^k| \leq \frac{d_h^*(x_h^k)}{d_h^\mu(x_h^k)}\|g(x_h^k; W_0))\|_2 \sqrt{\|(\Lambda_h^k)^{-1}\|} \leq 1/\sqrt{\lambda}\frac{d_h^*(x_h^k)}{d_h^\mu(x_h^k)} < \infty,$$

$$\mathbb{E}\left[Z_h^k | \mathcal{F}_h^{k-1}, s_1^k\right] = \mathbb{E}_{x_h \sim d_h^\mu}\left[\mathbb{1}\{k \in \mathcal{I}_h\}\frac{d_h^*(x_h)}{d_h^\mu(x_h)}\|g(x_h; W_0)\|_{(\Lambda_h^k)^{-1}} \middle| \mathcal{F}_h^{k-1}, s_1^k\right].$$

Thus, by Lemma G.4, for any $h \in [H]$, with probability at least $1 - \delta$, we have:

$$\sum_{k=1}^K \mathbb{E}_{x \sim d_h^*}\left[\mathbb{1}\{k \in \mathcal{I}_h\}\|g(x_h; W_0)\|_{(\Lambda_h^k)^{-1}} \middle| \mathcal{F}_h^{k-1}, s_1^k\right]$$

$$= \sum_{k=1}^K \mathbb{E}_{x_h \sim d_h^\mu)}\left[\mathbb{1}\{k \in \mathcal{I}_h\}\frac{d_h^*(x_h)}{d_h^\mu(x_h)}\|\phi_h(x_h)\|_{(\Lambda_h^k)^{-1}} \middle| \mathcal{F}_h^{k-1}, s_1^k\right]$$

$$\leq \sum_{k=1}^K \mathbb{1}\{k \in \mathcal{I}_h\}\frac{d_h^*(x_h^k)}{d_h^\mu(x_h^k)}\|g(x_h^k; W_0)\|_{(\Lambda_h^k)^{-1}} + \sqrt{\frac{1}{\lambda}\log(1/\delta)}\sqrt{\sum_{k=1}^K \mathbb{1}\{k \in \mathcal{I}_h\}\left(\frac{d_h^*(x_h^k)}{d_h^\mu(x_h^k)}\right)^2}$$

$$\leq \kappa \sum_{k=1}^K \mathbb{1}\{k \in \mathcal{I}_h\}\|g(x_h; W_0)\|_{(\Lambda_h^k)^{-1}} + \kappa\sqrt{\frac{K'\log(1/\delta)}{\lambda}}$$

$$= \kappa \sum_{k \in \mathcal{I}_h} \|g(x_h; W_0)\|_{(\Lambda_h^k)^{-1}} + \kappa\sqrt{\frac{K'\log(1/\delta)}{\lambda}}$$

$\square$

D.5 PROOF OF LEMMA C.4

Proof of Lemma C.4. For any fixed $h \in [H]$, let

$$U = [g(x_h^k; W_0)]_{k \in \mathcal{I}_h} \in \mathbb{R}^{md \times K'}.$$

By the union bound, with probability at least $1 - \delta$, for any $h \in [H]$, we have

$$\sum_{k \in \mathcal{I}_h} \|g(x_h; W_0)\|_{(\Lambda_h^k)^{-1}}^2 \leq 2\log\frac{\det \Lambda_h}{\det(\lambda I)}$$

$$= 2\log\det\left(I + \sum_{k \in \mathcal{I}_h} g(x_h^k; W_0)g(x_h^k; W_0)^T/\lambda\right)$$

$$= 2\log\det(I + UU^T/\lambda)$$

$$= 2\log\det(I + U^TU/\lambda)$$

$$= 2\log\det(I + \mathcal{K}_h/\lambda + (U^TU - \mathcal{K}_h)/\lambda)$$

$$\leq 2\log\det(I + \mathcal{K}_h/\lambda) + 2\operatorname{tr}\left((I + \mathcal{K}_h/\lambda)^{-1}(U^TU - \mathcal{K}_h)/\lambda\right)$$

$$\leq 2\log\det(I + \mathcal{K}_h/\lambda) + 2\|(I + \mathcal{K}_h/\lambda)^{-1}\|_F\|U^TU - \mathcal{K}_h\|_F$$

$$\leq 2\log\det(I + \mathcal{K}_h/\lambda) + 2\sqrt{K'}\|U^TU - \mathcal{K}_h\|_F$$

$$\leq 2\log\det(I + \mathcal{K}_h/\lambda) + 1$$

$$= 2\tilde{d}_h\log(1 + K'/\lambda) + 1$$

where the first inequality holds due to $\lambda \geq C_g^2$ and (Abbasi-yadkori et al., 2011, Lemma 11), the third equality holds due to that $\log\det(I + AA^T) = \log\det(I + A^T A)$, the second inequality holds due to that $\log\det(A + B) \leq \log\det(A) + \mathrm{tr}(A^{-1}B)$ as the result of the convexity of $\log\det$, the third inequality holds due to that $\mathrm{tr}(A) \leq \|A\|_F$, the fourth inequality holds due to $2\sqrt{K'}\|U^T U - \mathcal{K}_h\|_F \leq 1$ by the choice of $m = \Omega(K'^4 \log(K'H/\delta))$, Lemma G.2 and the union bound, and the last equality holds due to the definition of $\tilde{d}_h$. $\qquad\square$

E PROOFS OF LEMMAS IN SECTION D

E.1 PROOF OF LEMMA D.1

In this subsection, we give a detailed proof of Lemma D.1. For this, we first provide a lemma about linear approximation of the Bellman operator. In the following lemma, we show that $\mathbb{B}_h \tilde{V}_{h+1}$ can be well approximated by the class of linear functions with features $g(\cdot; W_0)$ with respect to l_∞-norm.

Lemma E.1. *Under Assumption 5.1, with probability at least $1 - \delta$ over $w_1, \ldots, w_m$ drawn i.i.d. from $\mathcal{N}(0, I_d)$, for any $h \in [H]$, there exist $c_1, \ldots, c_m$ where $c_i \in \mathbb{R}^d$ and $\|c_i\|_2 \leq \frac{B}{m}$ such that*

$$\bar{Q}_h(x) := \sum_{i=1}^m c_i^T x \sigma'(w_i^T x),$$

$$\|\mathbb{B}_h \tilde{V}_{h+1} - \bar{Q}_h\|_\infty \leq \frac{B}{\sqrt{m}}(2\sqrt{d} + \sqrt{2\log(H/\delta)})$$

Moreover, $\bar{Q}_h(x)$ can be re-written as

$$\bar{Q}_h(x) = \langle g(x; W_0), \bar{W}_h \rangle,$$
$$\bar{W}_h := \sqrt{m}[a_1 c_1^T, \ldots, a_m c_m^T]^T \in \mathbb{R}^{md}, \text{ and } \|\bar{W}_h\|_2 \leq B. \tag{25}$$

We now can prove Lemma D.1.

Proof of Lemma D.1. We first bound the difference $\langle g(x; W_0), \bar{W}_h \rangle - \langle g(x; W_0), \hat{W}_h^{lin} - W_0 \rangle$:

$$\langle g(x; W_0), \bar{W}_h \rangle - \langle g(x; W_0), \hat{W}_h^{lin} - W_0 \rangle = g(x; W_0)^T \bar{W}_h - g(x; W_0)^T \Lambda_h^{-1} \sum_{k \in \mathcal{I}_h} g(x_h^k; W_0) y_h^k$$

$$= \underbrace{g(x; W_0)^T \bar{W}_h - g(x; W_0)^T \Lambda_h^{-1} \sum_{k \in \mathcal{I}_h} g(x_h^k; W_0) \cdot (\mathbb{B}_h \tilde{V}_{h+1})(x_h^k)}_{I_1}$$

$$+ \underbrace{g(x; W_0)^T \Lambda_h^{-1} \sum_{k \in \mathcal{I}_h} g(x_h^k; W_0) \cdot \left[(\mathbb{B}_h \tilde{V}_{h+1})(x_h^k) - (r_h^k + \tilde{V}_{h+1}(s_{h+1}^k)) \right]}_{I_2}.$$

For bounding I_1, it follows from Lemma E.1 that with probability at least $1 - \delta/3$, for any for any $x \in \mathbb{S}_{d-1}$ and any $h \in [H]$,

$$|(\mathbb{B}_h \tilde{V}_{h+1})(x) - \langle g(x; W_0), \bar{W}_h \rangle| \leq \iota_0,$$

where ι_0 is defined in Table 2. where $\bar{W}_h$ is defined in Lemma E.1. Thus, with probability at least $1 - \delta/3$, for any for any $x \in \mathbb{S}_{d-1}$ and any $h \in [H]$,

$$I_1 = g(x; W_0)^T \bar{W}_h - g(x; W_0)^T \Lambda_h^{-1} \sum_{k \in \mathcal{I}_h} g(x_h^k; W_0) \cdot \left[(\mathbb{B}_h \tilde{V}_{h+1})(x_h^k) - g(x_h^k; W_0)^T \bar{W}_h \right]$$

$$- g(x; W_0)^T \bar{W}_h + \lambda g(x; W_0)^T \Lambda_h^{-1} \bar{W}_h$$

$$\leq \|g(x; W_0)^T\|_{\Lambda_h^{-1}} \sum_{k \in \mathcal{I}_h} \iota_0 \|g(x_h^k; W_0)^T\|_{\Lambda_h^{-1}} + \lambda \|g(x; W_0)\|_{\Lambda_h^{-1}} \|\bar{W}_h\|_{\Lambda_h^{-1}}$$

$$\leq \|g(x; W_0)\|_{\Lambda_h^{-1}} \left[K' \iota_0 \lambda^{-1/2} C_g + \lambda^{1/2} B \right], \tag{26}$$

where the first equation holds due to the definition of Λ_h, and the last inequality holds due to Step I with $\|\bar{W}_h\|_{\Lambda_h^{-1}} \leq \sqrt{\|\Lambda_h^{-1}\|_2} \cdot \|\bar{W}_h\|_2 \leq \lambda^{-1/2} B$.

For bounding I_2, we have

$$I_2 \leq \underbrace{\left\| \sum_{k \in \mathcal{I}_h} g(x_h^k; W_0) \left[(\mathbb{B}_h \tilde{V}_{h+1})(x_h^k) - r_h^k - \tilde{V}_{h+1}(s_{h+1}^k) \right] \right\|_{\Lambda_h^{-1}}}_{I_3} \|g(x; W_0)\|_{\Lambda_h^{-1}}. \tag{27}$$

If we directly apply the result of (Jin et al., 2021) in linear MDP, we would get

$$I_2 \lesssim dmH \sqrt{\log(2dmK'H/\delta)} \cdot \|g(x; W_0)\|_{\Lambda_h^{-1}},$$

which gives a vacuous bound as m is sufficiently larger than K in our problem. Instead, in the following, we present an alternate proof that avoids such vacuous bound.

For notational simplicity, we write

$$\epsilon_h^k := (\mathbb{B}_h \tilde{V}_{h+1})(x_h^k) - r_h^k - \tilde{V}_{h+1}(s_{h+1}^k),$$
$$E_h := [(\epsilon_h^k)_{k \in \mathcal{I}_h}]^T \in \mathbb{R}^{K'}.$$

We denote $\mathcal{K}_h^{init} := [\langle g(x_h^i; W_0), g(x_h^j; W_0) \rangle]_{i,j \in \mathcal{I}_h}$ as the Gram matrix of the empirical NTK kernel on the data $\{x_h^k\}_{k \in [K]}$. We denote

$$G_0 := \left(g(x_h^k; W_0) \right)_{k \in \mathcal{I}_h} \in \mathbb{R}^{md \times K'},$$
$$\mathcal{K}_h^{int} := G_0^T G_0 \in \mathcal{R}^{K' \times K'}.$$

Recall the definition of the Gram matrix $\mathcal{K}_h$ of the NTK kernel on the data $\{x_h^k\}_{k \in \mathcal{I}_h}$. It follows from Lemma G.2 and the union bound that if $m = \Omega(\epsilon^{-4} \log(3K'H/\delta))$ with probability at least $1 - \delta/3$, for any $h \in [H]$,

$$\|\mathcal{K}_h - \mathcal{K}_h^{init}\|_F \leq \sqrt{K'}\epsilon. \tag{28}$$

We now can bound I_3. We have

$$
\begin{aligned}
I_3^2 &= \left\| \sum_{k = \mathcal{I}_h} g(x_h^k; W_0)\epsilon_h^k \right\|_{\Lambda_h^{-1}}^2 \\
&= E_h^T G_0^T (\lambda I_{md} + G_0 G_0^T)^{-1} G_0 E_h \\
&= E_h^T G_0^T G_0 (\lambda I_{K'} + G_0^T G_0)^{-1} E_h \\
&= E_h^T \mathcal{K}_h^{init} (\mathcal{K}_h^{init} + \lambda I_K)^{-1} E_h \\
&= \underbrace{E_h^T \mathcal{K}_h (\mathcal{K}_h + \lambda I_{K'})^{-1} E_h}_{I_5} + \underbrace{E_h^T \left(\mathcal{K}_h(\mathcal{K}_h + \lambda I_{K'})^{-1} - \mathcal{K}_h^{init}(\mathcal{K}_h^{int} + \lambda I_{K'})^{-1} E_h \right)}_{I_4}. \tag{29}
\end{aligned}
$$

We bound each I_4 and I_5 separately. For bounding I_4, applying Lemma G.1, with $1 - Hm^{-2}$, for any $h \in [H]$,

$$
\begin{aligned}
I_4 &\leq \left\| \mathcal{K}_h(\mathcal{K}_h + \lambda I_{K'})^{-1} - \mathcal{K}_h^{init}(\mathcal{K}_h^{int} + \lambda I_{K'})^{-1} \right\|_2 \|E_h\|_2^2 \\
&= \left\| (\mathcal{K}_h - \mathcal{K}_h^{init})(\mathcal{K}_h + \lambda I_{K'})^{-1} + \mathcal{K}_h^{init} \left((\mathcal{K}_h + \lambda I_{K'})^{-1} - (\mathcal{K}_h^{int} + \lambda I_{K'})^{-1} \right) \right\|_2 \|E_h\|_2^2 \\
&\leq \|\mathcal{K}_h - \mathcal{K}_h^{init}\|_2/\lambda + \|\mathcal{K}_h^{init}\|_2 \cdot \|\mathcal{K}_h - \mathcal{K}_h^{init}\|_2/\lambda^2 \|E_h\|_2^2 \\
&\leq \frac{\lambda + K'C_g^2}{\lambda^2} \|\mathcal{K}_h - \mathcal{K}_h^{init}\|_2 \|E_h\|_2^2
\end{aligned}
$$

$$\leq 2K'C_g^2 K'(H+\psi)^2 \|\mathcal{K}_h - \mathcal{K}_h^{init}\|_2, \tag{30}$$

where the first inequality holds due to the triangle inequality, the second inequality holds due to the triangle inequality, Lemma G.6, and $\|(\mathcal{K}_h + \lambda I_{K'})^{-1}\|_2 \leq \lambda^{-1}$, the third inequality holds due to $\|\mathcal{K}_h^{init}\|_2 \leq \|G_0\|_2^2 \leq \|G_0\|_F^2 \leq K'C_g^2$ due to Lemma G.1, the fourth inequality holds due to $\|E_h\|_2 \leq \sqrt{K'}(H+\psi)$, $\lambda \geq 1$, and $K'C_g^2 \geq \lambda$.

Substituting Equation (28) in Equation (30) using the union bound, with probability $1 - Hm^{-2} - \delta/3$, for any $h \in [H]$,

$$I_4 \leq 2K'C_g^2 K'(H+\psi)^2 \sqrt{K'}\epsilon \leq 1, \tag{31}$$

where the last inequality holds due to the choice of $\epsilon = 1/2K'^{-5/2}(H+\psi)^{-2}C_g^{-2}$ and thus

$$m = \Omega(\epsilon^{-4}\log(3K'H/\delta)) = \Omega\left(K'^{10}(H+\psi)^2 \log(3K'H/\delta)\right).$$

For bounding I_5, as $\lambda > 1$, we have

$$\begin{aligned}
I_5 &= E_h^T \mathcal{K}_h (\mathcal{K}_h + \lambda I_{K'})^{-1} E_h \\
&\leq E_h^T (\mathcal{K}_h + (\lambda - 1)I_K)(\mathcal{K}_h + \lambda I_{K'})^{-1} E_h \\
&= E_h^T \left[(\mathcal{K}_h + (\lambda - 1)I_{K'})^{-1} + I_{K'}\right]^{-1} E_h. \tag{32}
\end{aligned}$$

Let $\sigma(\cdot)$ be the σ-algebra induced by the set of random variables. For any $h \in [H]$ and $k \in \mathcal{I}_h = [(H-h)K'+1, \ldots, (H-h+1)K']$, we define the filtration

$$\mathcal{F}_h^k = \sigma\left(\{(s_{h'}^t, a_{h'}^t, r_{h'}^t)\}_{h' \in [H]}^{t \leq k} \cup \{(s_{h'}^{k+1}, a_{h'}^{k+1}, r_{h'}^{k+1})\}_{h' \leq h-1} \cup \{(s_h^{k+1}, a_h^{k+1})\}\right)$$

which is simply all the data up to episode $k+1$ and timestep h but right before r_h^{k+1} and s_{h+1}^{k+1} are generated (in the offline data). [6] Note that for any $k \in \mathcal{I}_h$, we have $(s_h^k, a_h^k, r_h^k, s_{h+1}^k) \in \mathcal{F}_h^k$, and

$$\tilde{V}_{h+1} \in \sigma\left(\{(s_{h'}^k, a_{h'}^k, r_{h'}^k)\}_{h' \in [h+1, \ldots, H]}^{k \in \mathcal{I}_{h'}}\right) \subseteq \mathcal{F}_h^{k-1} \subseteq \mathcal{F}_h^k.$$

Thus, for any $k \in \mathcal{I}_h$, we have

$$\epsilon_h^k = (\mathbb{B}_h \tilde{V}_{h+1})(x_h^k) - r_h^k - \tilde{V}_{h+1}(s_{h+1}^k) \in \mathcal{F}_h^k.$$

The key property in our data split design is that we nicely have that

$$\tilde{V}_{h+1} \in \sigma\left(\{(s_{h'}^k, a_{h'}^k, r_{h'}^k)\}_{h' \in [h+1, \ldots, H]}^{k \in \mathcal{I}_{h'}}\right) \subseteq \mathcal{F}_h^{k-1}.$$

Thus, conditioned on $\mathcal{F}_h^{k-1}$, $\tilde{V}_{h+1}$ becomes deterministic. This implies that

$$\mathbb{E}\left[\epsilon_h^k | \mathcal{F}_h^{k-1}\right] = \left[(\mathbb{B}_h \tilde{V}_{h+1})(s_h^k, a_h^k) - r_h^k - \tilde{V}_{h+1}(s_{h+1}^k) | \mathcal{F}_h^{k-1}\right] = 0.$$

Note that this is only possible with our data splitting technique. Otherwise, ϵ_h^k is not zero-mean due to the data dependence structure induced in offline RL with function approximation (Nguyen-Tang et al., 2021b). Our data split technique is a key to avoid the uniform convergence argument with the log covering number that is often used to bound this term in (Jin et al., 2021), which is often large for complex models. For example, in a two-layer ReLU NTK, the eigenvalues of the induced RKHS has d-polynomial decay (Bietti & Mairal, 2019), thus its log covering number roughly follows, by (Yang et al., 2020, Lemma D1),

$$\log \mathcal{N}_\infty(\mathcal{H}_{ntk}, \epsilon, B) \lesssim \left(\frac{1}{\epsilon}\right)^{\frac{4}{\alpha d - 1}},$$

for some $\alpha \in (0, 1)$.

---

[6]To be more precise, we need to include into the filtration the randomness from the generated noises $\{\xi_h^{k,i}\}$ and $\{\zeta_h^i\}$ but since these noises are independent of any other randomness, they do not affect any derivations here but only complicate the notations and representations.

Therefore, for any $h \in [H]$, $\{\epsilon_h^k\}_{k \in \mathcal{I}_h}$ is adapted to the filtration $\{\mathcal{F}_h^k\}_{k \in \mathcal{I}_h}$. Applying Lemma G.5 with $Z_t = \epsilon_t^h \in [-(H + \psi), H + \psi]$, $\sigma^2 = (H + \psi)^2$, $\rho = \lambda - 1$, for any $\delta > 0$, with probability at least $1 - \delta/3$, for any $h \in [H]$,

$$E_h^T \left[(\mathcal{K}_h + (\lambda - 1)I_{K'})^{-1} + I \right]^{-1} E_h \leq (H + \psi)^2 \log\det (\lambda I_{K'} + \mathcal{K}_h) + 2(H + \psi)^2 \log(3H/\delta) \tag{33}$$

Substituting Equation (33) into Equation (32), we have

$$
\begin{aligned}
I_5 &\leq (H + \psi)^2 \log\det(\lambda I_{K'} + \mathcal{K}_h) + 2(H + \psi)^2 \log(H/\delta) \\
&= (H + \psi)^2 \log\det(I_{K'} + \mathcal{K}_h/\lambda) + (H + \psi)^2 K' \log \lambda + 2(H + \psi)^2 \log(H/\delta) \\
&= (H + \psi)^2 \tilde{d}_h \log(1 + K'/\lambda) + (H + \psi)^2 K' \log \lambda + 2(H + \psi)^2 \log(H/\delta), \tag{34}
\end{aligned}
$$

where the last equation holds due to the definition of the effective dimension.

Combining Equations (34), (31), (29), (27), and (26) via the union bound, with probability at least $1 - Hm^{-2} - \delta$, for any $x \in \mathbb{S}_{d-1}$ and any $h \in [H]$,

$$|\langle g(x; W_0), \bar{W}_h \rangle - \langle g(x; W_0), \hat{W}_h^{lin} - W_0 \rangle| \leq \beta \cdot \|g(x; W_0)\|_{\Lambda_h^{-1}},$$

where

$$\beta := K' \iota_0 \lambda^{-1/2} C_g + \lambda^{1/2} B + (H + \psi) \left[\sqrt{\tilde{d}_h \log(1 + K'/\lambda) + K' \log \lambda + 2 \log(3H/\delta)} \right]. \tag{35}$$

Combing with Lemma D.3 using the union bound, with probability at least $1 - Hm^{-2} - 2\delta$, for any $x \in \mathbb{S}_{d-1}$, and any $h \in [H]$,

$$
\begin{aligned}
f(x; \hat{W}_h) - (\mathbb{B}_h \tilde{V}_{h+1})(x) &\leq \langle g(x; W_0), \hat{W}_h^{lin} - W_0 \rangle + \iota_2 - \langle g(x; W_0), \bar{W}_h \rangle + \iota_0 \\
&\leq \beta \cdot \|g(x; W_0)\|_{\Lambda_h^{-1}} + \iota_2 + \iota_0, \\
&= \beta \cdot \|g(x; W_0)\|_{\Lambda_h^{-1}} + \iota_2 + \iota_0
\end{aligned}
$$

where ι_2, and β are defined in Table 2.

Similarly, it is easy to show that

$$(\mathbb{B}_h \tilde{V}_{h+1})(x) - f(x; \hat{W}_h) \leq \beta \cdot \|g(x; W_0)\|_{\Lambda_h^{-1}} + \iota_2 + \iota_0.$$

$\square$

E.2 PROOF OF LEMMA D.2

Before proving Lemma D.2, we prove the following intermediate lemmas. The detailed proofs of these intermediate lemmas are deferred to Section F.

Lemma E.2. *Conditioned on all the randomness except $\{\xi_h^{k,i}\}$ and $\{\zeta_h^i\}$, for any $i \in [M]$,*

$$\tilde{W}_h^{i,lin} - \hat{W}_h^{lin} \sim \mathcal{N}(0, \sigma_h^2 \Lambda_h^{-1}).$$

Lemma E.3. *If we set $M = \log \frac{HSA}{\delta} / \log \frac{1}{1 - \Phi(-1)}$ where $\Phi(\cdot)$ is the cumulative distribution function of the standard normal distribution, then with probability at least $1 - \delta$, for any $(x, h) \in \mathcal{X} \times [H]$,*

$$\min_{i \in [M]} \langle g(x; W_0), \tilde{W}_h^{i,lin} \rangle \leq \langle g(x; W_0), \hat{W}_h^{lin} \rangle - \sigma_h \|g(x; W_0)\|_{\Lambda_h^{-1}}.$$

We are now ready to prove Lemma D.2.

Proof of Lemma D.2. Note that the parameter condition in Equation (18) of Lemma D.2 satisfies Equation 19 of Lemma D.3, thus given the parameter condition Lemma D.2, Lemma D.3 holds. For the rest of the proof, we consider under the joint event in which both the inequality of Lemma D.3 and that of Lemma E.3 hold. By the union bound, probability that this joint event holds is at least $1 - MHm^{-2} - \delta$. Thus, for any $x \in \mathbb{S}_{d-1}$, $h \in [H]$, and $i \in [M]$,

$$\min_{i \in [M]} f(x; \tilde{W}_h^i) - f(x; \hat{W}_h) \leq \min_{i \in [M]} \langle g(x; W_0), \tilde{W}_h^{i,lin} - W_0 \rangle - \langle g(x; W_0), \hat{W}_h^{lin} - W_0 \rangle + \iota_1 + \iota_2$$

$$\leq -\sigma_h \|g(x; W_0)\|_{\Lambda_h^{-1}} + \iota_1 + \iota_2$$

where the first inequality holds due to Lemma D.3, and the second inequality holds due to Lemma E.3. Thus, we have

$$\tilde{Q}_h(x) = \min\{\min_{i \in [M]} f(x; \tilde{W}_h^i), H - h + 1 + \psi\}^+ \leq \max\{\min_{i \in [M]} f(x; \tilde{W}_h^i), 0\}$$

$$\leq \max\{\langle g(x; W_0), \hat{W}_h^{lin} - W_0 \rangle - \sigma_h \|g(x; W_0)\|_{\Lambda_h^{-1}} + \iota_1 + \iota_2, 0\}.$$

$\square$

E.3   PROOF OF LEMMA D.3

In this subsection, we provide a detailed proof of Lemma D.3. We first provide intermediate lemmas that we use for proving Lemma D.3. The detailed proofs of these intermediate lemmas are deferred to Section F.

The following lemma bounds the the gradient descent weight of the perturbed loss function around the linear weight counterpart.

Lemma E.4. *Let*

$$\begin{cases} m = \Omega\left(d^{3/2} R^{-1} \log^{3/2}(\sqrt{m}/R)\right) \\ R = \mathcal{O}\left(m^{1/2} \log^{-3} m\right), \\ \eta \leq (\lambda + K' C_g^2)^{-1}, \\ R \geq \max\{4\tilde{B}_1, 4\tilde{B}_2, 2\sqrt{2\lambda^{-1} K'(H + \psi + \gamma_{h,1})^2 + 4\gamma_{h,2}^2}\}, \end{cases} \tag{36}$$

where where $\tilde{B}_1$, $\tilde{B}_2$, $\gamma_{h,1}$ and $\gamma_{h,2}$ are defined in Table 2 and C_g is a constant given in Lemma G.1. With probability at least $1 - MHm^{-2} - \delta$, for any $(i, j, h) \in [M] \times [J] \times [H]$, we have

- $\tilde{W}_h^{i,(j)} \in \mathcal{B}(W_0; R)$,

- $\|\tilde{W}_h^{i,(j)} - \tilde{W}_h^{i,lin}\|_2 \leq \tilde{B}_1 + \tilde{B}_2 + \lambda^{-1}(1 - \eta\lambda)^j \left(K'(H + \psi + \gamma_{h,1})^2 + \lambda\gamma_{h,2}^2\right)$

Similar to Lemma E.4, we obtain the following lemma for the gradient descent weights of the non-perturbed loss function.

Lemma E.5. *Let*

$$\begin{cases} m = \Omega\left(d^{3/2} R^{-1} \log^{3/2}(\sqrt{m}/R)\right) \\ R = \mathcal{O}\left(m^{1/2} \log^{-3} m\right), \\ \eta \leq (\lambda + K' C_g^2)^{-1}, \\ R \geq \max\{4B_1, 4\tilde{B}_2, 2\sqrt{2\lambda^{-1} K'}(H + \psi)\}, \end{cases} \tag{37}$$

where B_1, $\tilde{B}_2$, $\gamma_{h,1}$ and $\gamma_{h,2}$ are defined in Table 2 and C_g is a constant given in Lemma G.1. With probability at least $1 - MHm^{-2} - \delta$, for any $(i, j, h) \in [M] \times [J] \times [H]$, we have

- $\hat{W}_h^{(j)} \in \mathcal{B}(W_0; R)$,

- $\|\hat{W}_h^{(j)} - \hat{W}_h^{lin}\|_2 \leq B_1 + \tilde{B}_2 + \lambda^{-1}(1 - \eta\lambda)^j K'(H + \psi)^2$

We now can prove Lemma D.3.

Proof of Lemma D.3. Note that Equation 19 implies both Equation (36) of Lemma E.4 and Equation (37) of Lemma E.5, thus both Lemma E.4 and Lemma E.5 holds under Equation (19). Thus, by the union bound, with probability at least $1 - MHm^{-2} - \delta$, for any $(i, j, h) \in [M] \times [J] \times [H]$, and $x \in \mathbb{S}_{d-1}$,

$$|f(x; \tilde{W}_h^{i,(j)}) - \langle g(x; W_0), \tilde{W}_h^{i,lin} - W_0 \rangle|$$
$$\leq |f(x; \tilde{W}_h^{i,(j)}) - \langle g(x; W_0), \tilde{W}_h^{i,(j)} - W_0 \rangle| + |\langle g(x; W_0), \tilde{W}_h^{i,(j)} - \tilde{W}_h^{i,lin} \rangle|$$
$$\leq C_g R^{4/3} m^{-1/6} \sqrt{\log m} + C_g \left(\tilde{B}_1 + \tilde{B}_2 + \lambda^{-1}(1 - \eta\lambda)^j \left(K'(H + \psi + \gamma_{h,1})^2 + \lambda\gamma_{h,2}^2 \right) \right) = \iota_1,$$

where the first inequality holds due to the triangle inequality, the second inequality holds due to Cauchy-Schwarz inequality, and Lemma G.1, and Lemma E.4.

Similarly, by the union bound, with probability at least $1 - Hm^{-2}$, for any $(i, j, h) \in [M] \times [J] \times [H]$, and $x \in \mathbb{S}_{d-1}$,

$$|f(x; \hat{W}_h^{(j)}) - \langle g(x; W_0), \hat{W}_h^{lin} - W_0 \rangle| \leq |f(x; \hat{W}_h^{(j)}) - \langle g(x; W_0), \hat{W}_h^{(j)} - W_0 \rangle|$$
$$+ |\langle g(x; W_0), \hat{W}_h^{(j)} - \hat{W}_h^{lin} \rangle|$$
$$\leq C_g R^{4/3} m^{-1/6} \sqrt{\log m} + C_g \left(B_1 + \tilde{B}_2 + \lambda^{-1}(1 - \eta\lambda)^j K'(H + \psi)^2 \right) = \iota_2,$$

where the first inequality holds due to the triangle inequality, the second inequality holds due to Cauchy-Schwarz inequality, and Lemma E.5, and Lemma G.1. □

F PROOFS OF LEMMAS IN SECTION E

In this section, we provide the detailed of Lemmas in Section E.

F.1 PROOF OF LEMMA E.1

Proof of Lemma E.1. As $\mathbb{B}_h \tilde{V}_{h+1} \in \mathcal{Q}^*$ by Assumption 5.1, where $\mathcal{Q}^*$ is defined in Equation (5), we have

$$\mathbb{B}_h \tilde{V}_{h+1} = \int_{\mathbb{R}^d} c(w)^T x \sigma'(w^T x) dw,$$

for some $c : \mathbb{R}^d \to \mathbb{R}^d$ such that $\sup_w \frac{\|c(w)\|_2}{p_0(w)} \leq B$. The lemma then directly follows from approximation by finite sum (Gao et al., 2019). □

F.2 PROOF OF LEMMA E.2

Proof of Lemma E.2. Let $\bar{W} := W + \zeta_h^i$ and

$$\bar{L}_h^i(\bar{W}) := \sum_{k \in \mathcal{I}_h} \left(\langle g(x_h^k; W_0), \bar{W} \rangle - \bar{y}_h^{i,k} \right)^2 + \lambda \|\bar{W}\|_2^2,$$

where $\bar{y}_h^k = r_h^k + \tilde{V}_{h+1}(s_{h+1}^k) + \xi_h^{k,i} + \langle g(x_h^k; W_0), \zeta_h^i \rangle$. We have $\tilde{L}_h^{i,lin}(W) = \bar{L}_h^i(\bar{W})$ and $\arg\max_W \tilde{L}_h^{i,lin}(W) = \arg\max_{\bar{W}} \bar{L}_h^i(\bar{W}) - \zeta_h^i$ as both $\tilde{L}_h^{i,lin}(W)$ and $\bar{L}_h^i$ are convex. Using the regularized least-squares solution,

$$\arg\max_{\bar{W}} \bar{L}_h^i(\bar{W}) = \Lambda_h^{-1} \sum_{k \in \mathcal{I}_h} g(x_h^k; W_0) \bar{y}_h^k$$

$$= \Lambda_h^{-1} \left[\sum_{k \in \mathcal{I}_h} g(x_h^k; W_0)(r_h^k + \tilde{V}_{h+1}(s_{h+1}^k) + \xi_h^{k,i}) + \sum_{k \in \mathcal{I}_h} g(x_h^k; W_0)\langle g(x_h^k; W_0), \zeta_h^i \rangle \right]$$

$$= \Lambda_h^{-1} \left[\sum_{k \in \mathcal{I}_h} g(x_h^k; W_0)(r_h^k + \tilde{V}_{h+1}(s_{h+1}^k) + \xi_h^{k,i}) + \sum_{k \in \mathcal{I}_h} g(x_h^k; W_0)g(x_h^k; W_0)^T \zeta_h^i \right]$$

$$= \Lambda_h^{-1} \left[\sum_{k \in \mathcal{I}_h} g(x_h^k; W_0)(r_h^k + \tilde{V}_{h+1}(s_{h+1}^k) + \xi_h^{k,i}) + (\Lambda_h - \lambda I_{md})\zeta_h^i \right].$$

Thus, we have

$$\tilde{W}_h^i = \arg\max_W \tilde{L}_h^{i,lin}(W) = \arg\max_{\bar{W}} \bar{L}_h^i(\bar{W}) - \zeta_h^i$$

$$= \Lambda_h^{-1} \left[\sum_{k \in \mathcal{I}_h} g(x_h^k; W_0)(r_h^k + \tilde{V}_{h+1}(s_{h+1}^k) + \xi_h^{k,i}) + (\Lambda_h - \lambda I_{md})\zeta_h^i \right] - \zeta_h^i$$

$$= \Lambda_h^{-1} \left[\sum_{k \in \mathcal{I}_h} g(x_h^k; W_0)(r_h^k + \tilde{V}_{h+1}(s_{h+1}^k) + \xi_h^{k,i}) - \lambda \zeta_h^i \right]$$

$$= \hat{W}_h + \Lambda_h^{-1} \left[\sum_{k \in \mathcal{I}_h} g(x_h^k; W_0)\xi_h^{k,i} - \lambda \zeta_h^i \right]$$

By direct computation, it is easy to see that

$$\tilde{W}_h^i - \hat{W}_h = \Lambda_h^{-1} \left[\sum_{k \in \mathcal{I}_h} g(x_h^k; W_0)\xi_h^{k,i} - \lambda \zeta_h^i \right] \sim \mathcal{N}(0, \sigma_h^2 \Lambda_h^{-1}).$$

$\square$

F.3 PROOF OF LEMMA E.3

In this subsection, we provide a proof for E.3. We first provide a bound for the perturbed noises used in Algorithm 1 in the following lemma.

Lemma F.1. *There exist absolute constants $c_1, c_2 > 0$ such that for any $\delta > 0$, event $\mathcal{E}(\delta)$ holds with probability at least $1 - \delta$, for any $(k, h, i) \in [K] \times [H] \times [M]$,*

$$|\xi_h^{k,i}| \leq c_1 \sigma_h \sqrt{\log(K'HM/\delta)} =: \gamma_{h,1},$$
$$\|\zeta_h^i\|_2 \leq c_2 \sigma_h \sqrt{d \log(dK'HM/\delta)} =: \gamma_{h,2}.$$

Proof of Lemma F.1. It directly follows from the Gaussian concentration inequality in Lemma G.3 and the union bound. $\square$

We now can prove Lemma E.3.

Proof of Lemma E.3. By Lemma E.2,

$$\tilde{W}_h^{i,lin} - \hat{W}_h^{lin} \sim \mathcal{N}(0, \sigma_h^2 \Lambda_h^{-1}).$$

Using the anti-concentration of Gaussian distribution, for any $x = (s, a) \in \mathcal{S} \times \mathcal{A}$ and any $i \in [M]$,

$$\mathbb{P}\left(\langle g(x; W_0), \tilde{W}_h^{i,lin} \rangle \leq \langle g(x; W_0), \hat{W}_h^{lin} \rangle - \sigma_h \|g(x; W_0)\|_{\Lambda_h^{-1}} \right) = \Phi(-1) \in (0, 1).$$

As $\{\tilde{W}_h^{i,lin}\}_{i \in [M]}$ are independent, using the union bound, with probability at least $1 - SAH(1 - \Phi(-1))^M$, for any $x = (s, a) \in \mathcal{S} \times \mathcal{A}$, and $h \in [H]$,

$$\min_{i \in [M]} \langle g(x; W_0), \tilde{W}_h^{i,lin} \rangle \leq \langle g(x; W_0), \hat{W}_h^{lin} \rangle - \sigma_h \|g(x; W_0)\|_{\Lambda_h^{-1}}.$$

Setting $\delta = SAH(1 - \Phi(-1))^M$ completes the proof. $\square$

F.4 PROOF OF LEMMA E.4

In this subsection, we provide a detailed proof of Lemma E.4. We first prove the following intermediate lemma whose proof is deferred to Subsection F.5.

Lemma F.2. *Let*

$$\begin{cases} m = \Omega\left(d^{3/2} R^{-1} \log^{3/2}(\sqrt{m}/R)\right) \\ R = \mathcal{O}\left(m^{1/2} \log^{-3} m\right). \end{cases}$$

and additionally let

$$\begin{cases} \eta \leq (K' C_g^2 + \lambda/2)^{-1}, \\ \eta \leq \frac{1}{2\lambda}. \end{cases}$$

Then with probability at least $1 - MHm^{-2} - \delta$, for any $(i, j, h) \in [M] \times [J] \times [H]$, if $\tilde{W}_h^{i,(j)} \in \mathcal{B}(W_0; R)$ for any $j' \in [j]$, then

$$\|f_{j'} - \tilde{y}\|_2 \leq \sqrt{K'(H + \psi + \gamma_{h,1})^2 + \lambda \gamma_{h,2}^2 + 4 C_g R^{4/3} m^{-1/6} \sqrt{\log m}}.$$

We now can prove Lemma E.4.

Proof of Lemma E.4. To simplify the notations, we define

$$\Delta_j := \tilde{W}_h^{i,(j)} - \tilde{W}_h^{i,lin,(j)} \in \mathbb{R}^{md},$$
$$G_j := \left(g(x_h^k; \tilde{W}_h^{i,(j)})\right)_{k \in \mathcal{I}_h} \in \mathbb{R}^{md \times K'},$$
$$H_j := G_j G_j^T \in \mathbb{R}^{md \times md},$$
$$f_j := \left(f(x_h^k; \tilde{W}_h^{i,(j)})\right)_{k \in \mathcal{I}_h} \in \mathbb{R}^{K'}$$
$$\tilde{y} := \left(\tilde{y}_h^{i,k}\right)_{k \in \mathcal{I}_h} \in \mathbb{R}^{K'}.$$

The gradient descent update rule for $\tilde{W}_h^{i,(j)}$ in Equation (7) can be written as:

$$\tilde{W}_h^{i,(j+1)} = \tilde{W}_h^{i,(j)} - \eta \left[G_j(f_j - \tilde{y}) + \lambda(\tilde{W}_h^{i,(j)} + \zeta_h^i - W_0) \right].$$

The auxiliary updates in Equation (13) can be written as:

$$\tilde{W}_h^{i,lin,(j+1)} = \tilde{W}_h^{i,lin,(j)} - \eta \left[G_0 \left(G_0^T(\tilde{W}_h^{i,lin,(j)} - W_0) - \tilde{y} \right) + \lambda(\tilde{W}_h^{i,lin,(j)} + \zeta_h^i - W_0) \right].$$

Step 1: Proving $\tilde{W}_h^{i,(j)} \in \mathcal{B}(W_0; R)$ for all j. In the first step, we prove by induction that with probability at least $1 - MHm^{-2} - \delta$, for any $(i, j, h) \in [M] \times [J] \times [H]$, we have

$$\tilde{W}_h^{i,(j)} \in \mathcal{B}(W_0; R).$$

In the rest of the proof, we consider under the event that Lemma F.2 holds. Note that the condition in Lemma E.4 satisfies that of Lemma F.2 and under the above event of Lemma F.2, Lemma G.1 and Lemma F.1 both hold. It is trivial that

$$\tilde{W}_h^{i,(0)} = W_0 \in \mathcal{B}(W_0; R).$$

For any fix $j \geq 0$, we assume that

$$\tilde{W}_h^{i,(j')} \in \mathcal{B}(W_0; R), \forall j' \in [j]. \tag{38}$$

We will prove that $\tilde{W}_h^{i,(j+1)} \in \mathcal{B}(W_0; R)$. We have

$$\|\Delta_{j+1}\|_2$$

$$= \left\| (1-\eta\lambda)\Delta_j - \eta\left[G_0(f_j - G_0^T(\tilde{W}_h^{i,(j)} - W_0)) + G_0 G_0^T(\tilde{W}_h^{i,(j)} - \tilde{W}_h^{i,lin,(j)}) + (f_j - \tilde{y})(G_j - G_0) \right] \right\|_2$$

$$\leq \underbrace{\|(I - \eta(\lambda I + H_0))\Delta_j\|_2}_{I_1} + \underbrace{\eta\|f_j - \tilde{y}\|_2\|G_j - G_0\|_2}_{I_2} + \underbrace{\eta\|G_0\|_2\|f_j - G_0^T(\tilde{W}_h^{i,(j)} - W_0)\|_2}_{I_3}.$$

We bound I_1, I_2 and I_3 separately.

Bounding I_1. For bounding I_1,

$$\begin{aligned}
I_1 &= \|(I - \eta(\lambda I + H_0))\Delta_j\|_2 \\
&\leq \|I - \eta(\lambda I + H_0)\|_2\|\Delta_j\|_2 \\
&\leq (1 - \eta(\lambda + K'C_g^2))\|\Delta_j\|_2 \\
&\leq (1 - \eta\lambda)\|\Delta_j\|_2
\end{aligned}$$

where the first inequality holds due to the spectral norm inequality, the second inequality holds due to

$$\eta(\lambda I + H_0) \preceq \eta(\lambda + \|G_0\|^2)I \preceq \eta(\lambda + K'C_g^2)I \preceq I,$$

where the first inequality holds due to that $H_0 \preceq \|H_0\|_2 I \preceq \|G_0\|_2^2 I$, the second inequality holds due to that $\|G_0\|_2 \leq \sqrt{K}C_g$ due to Lemma G.1, and the last inequality holds due to the choice of η in Equation (36).

Bounding I_2. For bounding I_2,

$$\begin{aligned}
I_2 &= \eta\|f_j - \tilde{y}\|_2\|G_j - G_0\|_2 \\
&\leq \eta\|f_j - \tilde{y}\|_2 \max_{k \in \mathcal{I}_h} \sqrt{K'}\|g(x_h^k; \tilde{W}_h^{i,(j)}) - g(x_h^k; W_0)\|_2 \\
&\leq \eta\|f_j - \tilde{y}\|_2\sqrt{K'}C_g R^{1/3}m^{-1/6}\sqrt{\log m} \\
&\leq \eta\sqrt{2K'(H + \psi + \gamma_{h,1})^2 + \lambda\gamma_{h,2}^2 + 8C_g R^{4/3}m^{-1/6}\sqrt{\log m}}\sqrt{K'}C_g R^{1/3}m^{-1/6}\sqrt{\log m}
\end{aligned}$$

where the first inequality holds due to Cauchy-Schwarz inequality, the second inequality holds due to the induction assumption in Equation (38) and Lemma G.1, and the third inequality holds due to Lemma F.2 and the induction assumption in Equation (38).

Bounding I_3. For bounding I_3,

$$\begin{aligned}
I_3 &= \eta\|G_0\|_2\|f_j - G_0^T(\tilde{W}_h^{i,(j)} - W_0)\|_2 \\
&\leq \eta\sqrt{K'}C_g\sqrt{K'}\max_{k \in \mathcal{I}_h}|f(x_h^k; \tilde{W}_h^{i,(j)}) - g(x_h^k; W_0)^T(\tilde{W}_h^{i,(j)} - W_0)| \\
&\leq \eta K'C_g R^{4/3}m^{-1/6}\sqrt{\log m},
\end{aligned}$$

where the first inequality holds due to Cauchy-Schwarz inequality and due to that $\|G_0\|_2 \leq \sqrt{K'}C_g$ and the second inequality holds due to the induction assumption in Equation (38) and Lemma G.1.

Combining the bounds of I_1, I_2, I_3 above, we have

$$\|\Delta_{j+1}\|_2 \leq (1 - \eta\lambda)\|\Delta_j\|_2 + I_2 + I_3.$$

Recursively applying the inequality above for all j, we have

$$\|\Delta_j\|_2 \leq \frac{I_2 + I_3}{\eta\lambda} \leq \frac{R}{4} + \frac{R}{4} = \frac{R}{2}, \tag{39}$$

where the second inequality holds due the choice specified in Equation (36). We also have

$$\begin{aligned}
\lambda\|\tilde{W}_h^{i,lin,(j+1)} + \zeta_h^i - W_0\|_2^2 &\leq 2\tilde{L}_h^{i,lin}(\tilde{W}_h^{i,lin,(j+1)}) \\
&\leq 2\tilde{L}_h^{i,lin}(\tilde{W}_h^{i,lin,(0)})
\end{aligned}$$

$$
\begin{aligned}
&= 2\tilde{L}_h^{i,lin}(W_0) \\
&= \sum_{k \in \mathcal{I}_h} \Bigg(\underbrace{\langle g(x_h^k; W_0), W_0 \rangle}_{=0} - \tilde{y}_h^{i,k} \Bigg)^2 + \lambda \|\zeta_h^i\|_2^2 \\
&= \sum_{k \in \mathcal{I}_h} (\tilde{y}_h^{i,k})^2 + \lambda \|\zeta_h^i\|_2^2 \\
&\leq K'(H + \psi + \gamma_{h,1})^2 + \lambda \gamma_{h,2}^2,
\end{aligned}
\tag{40}
$$

where the first inequality holds due the the definition of $\tilde{L}_h^{i,lin}(\tilde{W}_h^{i,lin,(j+1)})$, the second inequality holds due to the monotonicity of $\tilde{L}_h^{i,lin}(W)$ on the gradient descent updates $\{\tilde{W}_h^{i,lin,(j')}\}_{j'}$ for the squared loss on a linear model, the third equality holds due to $\langle g(x_h^k; W_0), W_0 \rangle = 0$ from the symmetric initialization scheme, and the last inequality holds due to Lemma F.1. Thus, we have

$$
\begin{aligned}
\|\tilde{W}_h^{i,lin,(j+1)} - W_0\|_2 &\leq \sqrt{2\|\tilde{W}_h^{i,lin,(j+1)} + \zeta_h^i - W_0\|_2^2 + \|\zeta_h^i\|_2^2} \\
&\leq \sqrt{2\lambda^{-1}K'(H + \psi + \gamma_{h,1})^2 + 4\gamma_{h,2}^2} \\
&\leq \frac{R}{2},
\end{aligned}
\tag{41}
$$

where the first inequality holds due to Cauchy-Schwarz inequality, the second inequality holds due to Equation (40) and Lemma F.1, and the last inequality holds due to the choice specified in Equation (36).

Combining Equation (39) and Equation (41), we have

$$
\begin{aligned}
\|\tilde{W}_h^{i,(j+1)} - W_0\|_2 &\leq \|\tilde{W}_h^{i,(j+1)} - \tilde{W}_h^{i,lin,(j+1)}\|_2 + \|\tilde{W}_h^{i,lin,(j+1)} - W_0\|_2 \\
&\leq \frac{R}{2} + \frac{R}{2} = R,
\end{aligned}
$$

where the first inequality holds due to the triangle inequality.

Step 2: Bounding $\|\tilde{W}_h^{i,(j)} - \tilde{W}_h^{i,lin}\|_2$. By the standard result of gradient descent on ridge linear regression, $\tilde{W}_h^{i,(j)}$ converges to $\tilde{W}_h^{i,lin}$ with the convergence rate,

$$
\begin{aligned}
\|\tilde{W}_h^{i,lin,(j)} - \tilde{W}_h^{i,lin}\|_2^2 &\leq (1 - \eta\lambda)^j \frac{2}{\lambda}(\tilde{L}(W_0) - \tilde{L}(\tilde{W}_h^{i,lin})) \\
&\leq (1 - \eta\lambda)^j \frac{2}{\lambda} \tilde{L}(W_0) \\
&\leq \lambda^{-1}(1 - \eta\lambda)^j \left(K'(H + \psi + \gamma_{h,1})^2 + \lambda\gamma_{h,2}^2 \right).
\end{aligned}
$$

Thus, for any j, we have

$$
\begin{aligned}
\|\tilde{W}_h^{i,(j)} - \tilde{W}_h^{i,lin}\|_2 &\leq \|\tilde{W}_h^{i,(j)} - \tilde{W}_h^{i,lin,(j)}\|_2 + \|\tilde{W}_h^{i,lin,(j)} - \tilde{W}_h^{i,lin}\|_2 \\
&\leq (\eta\lambda)^{-1}(I_2 + I_3) + \lambda^{-1}(1 - \eta\lambda)^j \left(K'(H + \psi + \gamma_{h,1})^2 + \lambda\gamma_{h,2}^2 \right),
\end{aligned}
\tag{42}
$$

where the first inequality holds due to the triangle inequality, the second inequality holds due to Equation 39 and Equation (42). $\qquad\square$

F.5 PROOF OF LEMMA F.2

Proof of Lemma F.2. We bound this term following the proof flow of (Zhou et al., 2020, Lemma C.3) with modifications for different neural parameterization and noisy targets. Suppose that for some fixed j,

$$
\tilde{W}_h^{i,(j')} \in \mathcal{B}(W_0; R), \forall j' \in [j].
\tag{43}
$$

Let us define

$$
G(W) := \left(g(x_h^k; W) \right)_{k \in \mathcal{I}_h} \in \mathbb{R}^{md \times K'},
$$

$$f(W) := \left(f(x_h^k; W) \right)_{k \in \mathcal{I}_h} \in \mathbb{R}^{K'},$$
$$e(W', W) := f(W') - f(W) - G(W)^T(W' - W) \in \mathbb{R}.$$

To further simplify the notations in this proof, we drop i, h in $\tilde{L}_h^i(W)$ defined in Equation (6) to write $\tilde{L}_h^i(W)$ as $\tilde{L}(W)$ and write $W_j = W_h^{i,(j)}$, where

$$\tilde{L}(W) = \frac{1}{2} \sum_{k \in \mathcal{I}_h} \left(f(x_h^k; W) - \tilde{y}_h^{i,k} \right)^2 + \frac{\lambda}{2} \|W + \zeta_h^i - W_0\|_2^2$$

$$= \frac{1}{2} \|f(W) - \tilde{y}\|_2^2 + \frac{\lambda}{2} \|W + \zeta_h^i - W_0\|_2^2.$$

Suppose that $W \in \mathbb{B}(W_0; R)$. By that $\|\cdot\|_2^2$ is 1-smooth,

$$\tilde{L}(W') - \tilde{L}(W) \leq \langle f(W) - \tilde{y}, f(W') - f(W) \rangle + \frac{1}{2} \|f(W') - f(W)\|_2^2$$

$$+ \lambda \langle W + \zeta_h^i - W_0, W' - W \rangle + \frac{\lambda}{2} \|W' - W\|_2^2$$

$$= \langle f(W) - \tilde{y}, G(W)^T(W' - W) + e(W', W) \rangle + \frac{1}{2} \|G(W)^T(W' - W) + e(W', W)\|_2^2$$

$$+ \lambda \langle W + \zeta_h^i - W_0, W' - W \rangle + \frac{\lambda}{2} \|W' - W\|_2^2$$

$$= \langle \nabla \tilde{L}(W), W' - W \rangle$$

$$+ \underbrace{\langle f(W) - \tilde{y}, e(W', W) \rangle + \frac{1}{2} \|G(W)^T(W' - W) + e(W', W)\|_2^2 + \frac{\lambda}{2} \|W' - W\|_2^2}_{I_1}. \quad (44)$$

For bounding I_1,

$$I_1 \leq \|f(W) - \tilde{y}\|_2 \|e(W', W)\|_2 + K' C_g^2 \|W' - W\|_2^2 + \|e(W', W)\|_2^2 + \frac{\lambda}{2} \|W' - W\|_2^2$$

$$= \|f(W) - \tilde{y}\|_2 \|e(W', W)\|_2 + (K' C_g^2 + \lambda/2) \|W' - W\|_2^2 + \|e(W', W)\|_2^2, \quad (45)$$

where the first inequality holds due to Cauchy-Schwarz inequality, $W \in \mathcal{B}(W_0; R)$ and Lemma G.1. Substituting Equation (45) into Equation (44) with $W' = W - \eta \nabla \tilde{L}(W)$,

$$\tilde{L}(W') - \tilde{L}(W) \leq -\eta(1 - (KC_g^2 + \lambda/2)\eta) \|\nabla \tilde{L}(W)\|_2^2 + \|f(W) - \tilde{y}\|_2 \|e(W', W)\|_2$$

$$+ \|e(W', W)\|_2^2. \quad (46)$$

By the 1-strong convexity of $\|\cdot\|_2^2$, for any W',

$$\tilde{L}(W') - \tilde{L}(W) \geq \langle f(W) - \tilde{y}, f(W') - f(W) \rangle + \lambda \langle W + \zeta_h^i - W_0, W' - W \rangle + \frac{\lambda}{2} \|W' - W\|_2^2$$

$$= \langle f(W) - \tilde{y}, G(W)^T(W' - W) + e(W', W) \rangle + \lambda \langle W + \zeta_h^i - W_0, W' - W \rangle + \frac{\lambda}{2} \|W' - W\|_2^2$$

$$= \langle \nabla \tilde{L}(W), W' - W \rangle + \langle f(W) - \tilde{y}, e(W', W) \rangle + \frac{\lambda}{2} \|W' - W\|_2^2$$

$$\geq -\frac{\|\nabla \tilde{L}(W)\|_2^2}{2\lambda} - \|f(W) - \tilde{y}\|_2 \|e(W', W)\|_2, \quad (47)$$

where the last inequality holds due to Cauchy-Schwarz inequality.

Substituting Equation (47) into Equation (46), for any W',

$$\tilde{L}(W - \eta \nabla \tilde{L}(W)) - \tilde{L}(W)$$

$$\leq \underbrace{2\lambda \eta (1 - (KC_g^2 + \lambda/2)\eta)}_{\alpha} \left(\tilde{L}(W') - \tilde{L}(W) + \|f(W) - \tilde{y}\|_2 \|e(W', W)\|_2 \right)$$

$$+ \|f(W) - \tilde{y}\|_2 \|e(W - \eta \nabla \tilde{L}(W), W)\|_2 + \|e(W - \eta \nabla \tilde{L}(W), W)\|_2^2$$

$$\leq \alpha \left(\tilde{L}(W') - \tilde{L}(W) + \frac{\gamma_1}{2} \|f(W) - \tilde{y}\|_2^2 + \frac{1}{2\gamma_1} \|e(W', W)\|_2^2 \right)$$
$$+ \frac{\gamma_2}{2} \|f(W) - \tilde{y}\|_2^2 + \frac{1}{2\gamma_2} \|e(W - \eta \nabla \tilde{L}(W), W)\|_2^2 + \|e(W - \eta \nabla \tilde{L}(W), W)\|_2^2$$
$$\leq \alpha \left(\tilde{L}(W') - \tilde{L}(W) + \gamma_1 \tilde{L}(W) + \frac{1}{2\gamma_1} \|e(W', W)\|_2^2 \right)$$
$$+ \gamma_2 \tilde{L}(W) + \frac{1}{2\gamma_2} \|e(W - \eta \nabla \tilde{L}(W), W)\|_2^2 + \|e(W - \eta \nabla \tilde{L}(W), W)\|_2^2, \tag{48}$$

where the second inequality holds due to Cauchy-Schwarz inequality for any $\gamma_1, \gamma_2 > 0$, and the third inequality holds due to $\|f(W) - \tilde{y}\|_2^2 \leq 2\tilde{L}(W)$.

Rearranging terms in Equation (48) and setting $W = W_j$, $W' = W_0$, $\gamma_1 = \frac{1}{4}$, $\gamma_2 = \frac{\alpha}{4}$,

$$\tilde{L}(W_{j+1}) - \tilde{L}(W_0) \leq (1 - \alpha + \alpha\gamma_1 + \gamma_2)\tilde{L}(W_j) - (1 - \frac{\alpha}{2})\tilde{L}(W_0) + \frac{\alpha}{2}\tilde{L}(W_0) + \frac{\alpha}{2\gamma_1}\|e(W_0, W_j)\|_2^2$$
$$+ \frac{1}{2\gamma_2}\|e(W_{j+1}, W_j)\|_2^2 + \|e(W_{j+1}, W_j)\|_2^2$$
$$= (1 - \frac{\alpha}{2})\left(\tilde{L}(W_j) - \tilde{L}(W_0)\right) + \frac{\alpha}{2}\tilde{L}(W_0) + 2\alpha\|e(W_0, W_j)\|_2^2$$
$$+ (1 + \frac{2}{\alpha})\|e(W_{j+1}, W_j)\|_2^2$$
$$\leq (1 - \frac{\alpha}{2})\left(\tilde{L}(W_j) - \tilde{L}(W_0)\right) + \frac{\alpha}{2}\tilde{L}(W_0) + (1 + \frac{2}{\alpha} + 2\alpha)e, \tag{49}$$

where $e := C_g R^{4/3} m^{-1/6}\sqrt{\log m}$, the last inequality holds due to Equation (43) and Lemma G.1. Applying Equation (49), we have

$$\tilde{L}(W_j) - \tilde{L}(W_0) \leq \frac{\alpha}{2}\left(\frac{\alpha}{2}\tilde{L}(W_0) + (1 + \frac{2}{\alpha} + 2\alpha)e\right).$$

Rearranging the above inequality,

$$\tilde{L}(W_j) \leq (1 + \frac{\alpha^2}{4})\tilde{L}(W_0) + (\frac{\alpha}{2} + 1 + \alpha^2)e$$
$$\leq (1 + (2\lambda\eta)^2/4)\tilde{L}(W_0) + (\lambda\eta + 1 + 4\lambda^2\eta^2)e$$
$$\leq (1 + \lambda\eta)(\tilde{L}(W_0) + 2e)$$

where the last inequality holds due to the choice of η. Finally, we have

$$\|f_j - \tilde{y}\|_2^2 \leq 2\tilde{L}(W_j) \leq 2(1 + \lambda\eta)(\tilde{L}(W_0) + 2e) \leq 4(\tilde{L}(W_0) + 2e),$$

where $\tilde{L}(W_0) = \frac{1}{2}\|\tilde{y}\|_2^2 + \frac{\lambda}{2}\|\zeta_h^i\|_2^2 \leq \frac{K'}{2}(H + \psi + \gamma_{h,1})^2 + \frac{\lambda}{2}\gamma_{h,2}^2$ due to Lemma F.1. $\qquad\square$

G SUPPORT LEMMAS

Lemma G.1. *Let $m = \Omega\left(d^{3/2}R^{-1}\log^{3/2}(\sqrt{m}/R)\right)$ and $R = \mathcal{O}\left(m^{1/2}\log^{-3}m\right)$. With probability at least $1 - e^{-\Omega(\log^2 m)} \geq 1 - m^{-2}$ with respect to the random initialization, it holds for any $W, W' \in \mathcal{B}(W_0; R)$ and $x \in \mathbb{S}_{d-1}$ that*

$$\|g(x; W)\|_2 \leq C_g,$$
$$\|g(x; W) - g(x; W_0)\|_2 \leq \mathcal{O}\left(C_g R^{1/3} m^{-1/6}\sqrt{\log m}\right),$$
$$|f(x; W) - f(x; W') - \langle g(x; W'), W - W'\rangle| \leq \mathcal{O}\left(C_g R^{4/3} m^{-1/6}\sqrt{\log m}\right),$$

where $C_g = \mathcal{O}(1)$ is a constant independent of d and m. Moreover, without loss of generality, we assume $C_g \leq 1$.

Proof of Lemma G.1. Due to (Yang et al., 2020, Lemma C.2) and (Cai et al., 2019, Lemma F.1, F.2), we have the first two inequalities and the following:

$$|f(x;W) - \langle g(x;W_0), W - W_0 \rangle| \leq \mathcal{O}\left(C_g R^{4/3} m^{-1/6} \sqrt{\log m}\right).$$

For any $W, W' \in \mathcal{B}(W_0; R)$,

$$\begin{aligned} &f(x;W) - f(x;W') - \langle g(x;W'), W - W' \rangle \\ &= f(x;W) - \langle g(x;W_0), W - W_0 \rangle - (f(x;W') - \langle g(x;W_0), W' - W_0 \rangle) \\ &+ \langle g(x;W_0) - g(x;W'), W_0 - W' \rangle. \end{aligned}$$

Thus,

$$\begin{aligned} &|f(x;W) - f(x;W') - \langle g(x;W'), W - W' \rangle| \\ &\leq |f(x;W) - \langle g(x;W_0), W - W_0 \rangle| + |f(x;W') - \langle g(x;W_0), W' - W_0 \rangle| \\ &+ \|g(x;W_0) - g(x;W')\|_2 \|W_0 - W'\|_2 \leq \mathcal{O}\left(C_g R^{4/3} m^{-1/6} \sqrt{\log m}\right). \end{aligned}$$

$\square$

Lemma G.2 ((Arora et al., 2019, Theorem 3)). *If $m = \Omega(\epsilon^{-4} \log(1/\delta))$, then for any $x, x' \in \mathcal{X} \subset \mathbb{S}_{d-1}$, with probability at least $1 - \delta$,*

$$|\langle g(x;W_0), g(x';W_0) \rangle - K_{ntk}(x,x')| \leq 2\epsilon.$$

Lemma G.3. *Let $X \sim \mathcal{N}(0, a\Lambda^{-1})$ be a d-dimensional normal variable where a is a scalar. There exists an absolute constant $c > 0$ such that for any $\delta > 0$, with probability at least $1 - \delta$,*

$$\|X\|_\Lambda \leq c\sqrt{da \log(d/\delta)}.$$

For $d = 1$, $c = \sqrt{2}$.

Lemma G.4 (A variant of Hoeffding-Azuma inequality). *Suppose $\{Z_k\}_{k=0}^\infty$ is a real-valued stochastic process with corresponding filtration $\{\mathcal{F}_k\}_{k=0}^\infty$, i.e. $\forall k$, Z_k is $\mathcal{F}_k$-measurable. Suppose that for any k, $\mathbb{E}[|Z_k|] < \infty$ and $|Z_k - \mathbb{E}[Z_k|\mathcal{F}_{k-1}]| \leq c_k$ almost surely. Then for all positive n and t, we have:*

$$\mathbb{P}\left(\left|\sum_{k=1}^n Z_k - \sum_{k=1}^n \mathbb{E}[Z_k|\mathcal{F}_{k-1}]\right| \geq t\right) \leq 2\exp\left(\frac{-t^2}{\sum_{i=1}^n c_i^2}\right).$$

Lemma G.5 ((Chowdhury & Gopalan, 2017, Theorem 1)). *Let $\mathcal{H}$ be an RKHS defined over $\mathcal{X} \subseteq \mathbb{R}^d$. Let $\{x_t\}_{t=1}^\infty$ be a discrete time stochastic process adapted to filtration $\{\mathcal{F}_t\}_{t=0}^\infty$. Let $\{Z_k\}_{k=1}^\infty$ be a real-valued stochastic process such that $Z_k \in \mathcal{F}_k$, and Z_k is zero-mean and σ-sub Gaussian conditioned on $\mathcal{F}_{k-1}$. Let $E_k = (Z_1, \ldots, Z_{k-1})^T \in \mathbb{R}^{k-1}$ and $\mathcal{K}_k$ be the Gram matrix of $\mathcal{H}$ defined on $\{x_t\}_{t \leq k-1}$. For any $\rho > 0$ and $\delta \in (0,1)$, with probability at least $1 - \delta$,*

$$E_k^T \left[(\mathcal{K}_k + \rho I)^{-1} + I\right]^{-1} E_k \leq \sigma^2 \text{logdet}\left[(1+\rho)I + \mathcal{K}_k\right] + 2\sigma^2 \log(1/\delta).$$

Lemma G.6. *For any matrices A and B where A is invertible,*

$$\text{logdet}(A + B) \leq \text{logdet}(A) + tr(A^{-1}B).$$

Lemma G.7 (Proof of Lemma G.6). *For any invertible matrices A, B,*

$$\|A^{-1} - B^{-1}\|_2 \leq \frac{\|A - B\|_2}{\lambda_{\min}(A)\lambda_{\min}(B)}.$$

Proof. We have:

$$\|A^{-1} - B^{-1}\|_2 = \|(AB)^{-1}(AB)(A^{-1} - B^{-1})\|_2$$

$$
\begin{aligned}
&= \|(AB)^{-1}(ABA^{-1} - A)\|_2 \\
&\leq \|(AB)^{-1}\|_2 \|ABA^{-1} - A\|_2 \\
&= \|(AB)^{-1}\|_2 \|ABA^{-1} - AAA^{-1}\|_2 \\
&= \|(AB)^{-1}\|_2 \|A(B - A)A^{-1}\|_2 \\
&= \|(AB)^{-1}\|_2 \|B - A\|_2 \\
&\leq \lambda_{\max}(A^{-1})\lambda_{\max}(B^{-1})\|_2 \|B - A\|_2.
\end{aligned}
$$

$\square$

Lemma G.8 (Freedman's inequality (Tropp, 2011)). *Let $\{X_k\}_{k=1}^n$ be a real-valued martingale difference sequence with the corresponding filtration $\{\mathcal{F}_k\}_{k=1}^n$, i.e. X_k is $\mathcal{F}_k$-measurable and $\mathbb{E}[X_k|\mathcal{F}_{k-1}] = 0$. Suppose for any k, $|X_k| \leq M$ almost surely and define $V := \sum_{k=1}^n \mathbb{E}\left[X_k^2|\mathcal{F}_{k-1}\right]$. For any $a, b > 0$, we have:*

$$
\mathbb{P}\left(\sum_{k=1}^n X_k \geq a, V \leq b\right) \leq \exp\left(\frac{-a^2}{2b + 2aM/3}\right).
$$

In an alternative form, for any $t > 0$, we have:

$$
\mathbb{P}\left(\sum_{k=1}^n X_k \geq \frac{2Mt}{3} + \sqrt{2bt}, V \leq b\right) \leq e^{-t}.
$$

Lemma G.9 (Improved online-to-batch argument). *Let $\{X_k\}$ be any real-valued stochastic process adapted to the filtration $\{\mathcal{F}_k\}$, i.e. X_k is $\mathcal{F}_k$-measurable. Suppose that for any k, $X_k \in [0, H]$ almost surely for some $H > 0$. For any $K > 0$, with probability at least $1 - \delta$, we have:*

$$
\sum_{k=1}^K \mathbb{E}\left[X_k|\mathcal{F}_{k-1}\right] \leq 2\sum_{k=1}^K X_k + \frac{16}{3}H\log(\log_2(KH)/\delta) + 2.
$$

Proof of Lemma G.9. Let $Z_k = X_k - \mathbb{E}\left[X_k|\mathcal{F}_{k-1}\right]$ and $f(K) = \sum_{k=1}^K \mathbb{E}\left[X_k|\mathcal{F}_{k-1}\right]$. We have Z_k is a real-valued difference martingale with the corresponding filtration $\{\mathcal{F}_k\}$ and that

$$
V := \sum_{k=1}^K \mathbb{E}\left[Z_k^2|\mathcal{F}_{k-1}\right] \leq \sum_{k=1}^K \mathbb{E}\left[X_k^2|\mathcal{F}_{k-1}\right] \leq H\sum_{k=1}^K \mathbb{E}\left[X_k|\mathcal{F}_{k-1}\right] = Hf(K).
$$

Note that $|Z_k| \leq H$ and $f(K) \in [0, KH]$ and let $m = \log_2(KH)$. Also note that $f(K) = \sum_{k=1}^K X_k - \sum_{k=1}^K Z_k \geq -\sum_{k=1}^K Z_k$. Thus if $\sum_{k=1}^K Z_k \leq -1$, we have $f(K) \geq 1$. For any $t > 0$, leveraging the peeling technique (Bartlett et al., 2005), we have:

$$
\begin{aligned}
&\mathbb{P}\left(\sum_{k=1}^K Z_k \leq -\frac{2Ht}{3} - \sqrt{4Hf(K)t} - 1\right) \\
&= \mathbb{P}\left(\sum_{k=1}^K Z_k \leq -\frac{2Ht}{3} - \sqrt{4Hf(K)t} - 1, f(K) \in [1, KH]\right) \\
&\leq \sum_{i=1}^m \mathbb{P}\left(\sum_{k=1}^K Z_k \leq -\frac{2Ht}{3} - \sqrt{4Hf(K)t} - 1, f(K) \in [2^{i-1}, 2^i)\right) \\
&\leq \sum_{i=1}^m \mathbb{P}\left(\sum_{k=1}^K Z_k \leq -\frac{2Ht}{3} - \sqrt{4H2^{i-1}t} - 1, V \leq H2^i, f(K) \in [2^{i-1}, 2^i)\right) \\
&\leq \sum_{i=1}^m \mathbb{P}\left(\sum_{k=1}^K Z_k \leq -\frac{2Ht}{3} - \sqrt{2H2^it}, V \leq H2^i\right)
\end{aligned}
$$

$$\leq \sum_{i=1}^{m} e^{-t} = me^{-t},$$

where the first equation is by that $\sum_{k=1}^{K} Z_k \leq -\frac{2Ht}{3} - \sqrt{4Hf(K)t} - 1 \leq -1$ thus $f(K) \geq 1$, the second inequality is by that $V \leq Hf(K)$, and the last inequality is by Lemma G.8. Thus, with probability at least $1 - me^{-t}$, we have:

$$\sum_{k=1}^{K} X_k - f(K) = \sum_{k=1}^{K} Z_k \geq -\frac{2Ht}{3} - \sqrt{4Hf(K)t} - 1.$$

The above inequality implies that $f(K) \leq 2\sum_{k=1}^{K} X_k + 4Ht/3 + 2 + 4Ht$, due to the simple inequality: if $x \leq a\sqrt{x} + b$, $x \leq a^2 + 2b$. Then setting $t = \log(m/\delta)$ completes the proof. $\qquad \square$

H   BASELINE ALGORITHMS

For completeness, we give the definition of linear MDPs as follows.

Definition 3 (Linear MDPs (Yang & Wang, 2019; Jin et al., 2020))**.** *An MDP has a linear structure if for any* (s, a, s', h)*, we have:*

$$r_h(s, a) = \phi_h(s, a)^T \theta_h, \mathbb{P}_h(s'|s, a) = \phi_h(s, a)^T \mu_h(s'),$$

where $\phi : \mathcal{S} \times \mathcal{A} \to \mathbb{R}^{d_{lin}}$ *is a known feature map,* $\theta_h \in \mathbb{R}^{d_{lin}}$ *is an unknown vector, and* $\mu_h : \mathcal{S} \to \mathbb{R}^{d_{lin}}$ *are unknown signed measures.*

We aslo give the details of the baseline algorithms: LinLCB in Algorithm 3, LinGreedy in Algorithm 4, LinPER in Algorithm 5, NeuraLCB in Algorithm 6 and NeuralGreedy in Algorithm 7. For simplicity, we do not use data split in these algorithms presented here.

Algorithm 3 LinLCB (Jin et al., 2021)

1: **Input**: Offline data $\mathcal{D} = \{(s_h^k, a_h^k, r_h^k)\}_{h \in [H]}^{k \in [K]}$, uncertainty multiplier β, regularization parameter λ.
2: Initialize $\tilde{V}_{H+1}(\cdot) \leftarrow 0$
3: **for** $h = H, \ldots, 1$ **do**
4: $\quad \Lambda_h \leftarrow \sum_{k=1}^{K} \phi(s_h^k, a_h^k)\phi(s_h^k, a_h^k)^T + \lambda I$
5: $\quad \hat{\theta}_h \leftarrow \Sigma_h^{-1} \sum_{k=1}^{K} \phi_h(s_h^k, a_h^k) \cdot (r_h^k + \hat{V}_{h+1}(s_{h+1}^k))$
6: $\quad b_h(\cdot, \cdot) \leftarrow \beta \cdot \|\phi_h(\cdot, \cdot)\|_{\Sigma_h^{-1}}$.
7: $\quad \hat{Q}_h(\cdot, \cdot) \leftarrow \min\{\langle \phi_h(\cdot, \cdot), \hat{\theta}_h \rangle - b_h(\cdot, \cdot), H - h + 1\}^+$.
8: $\quad \hat{\pi}_h \leftarrow \arg\max_{\pi_h} \langle \hat{Q}_h, \pi_h \rangle$ and $\hat{V}_h^k \leftarrow \langle \hat{Q}_h^k, \pi_h^k \rangle$.
9: **end for**
10: **Output**: $\hat{\pi} = \{\hat{\pi}_h\}_{h \in [H]}$

Algorithm 4 LinGreedy

1: **Input**: Offline data $\mathcal{D} = \{(s_h^k, a_h^k, r_h^k)\}_{h \in [H]}^{k \in [K]}$, perturbed variances $\{\sigma_h\}_{h \in [H]}$, number of bootstraps M, regularization parameter λ.
2: Initialize $\tilde{V}_{H+1}(\cdot) \leftarrow 0$
3: **for** $h = H, \ldots, 1$ **do**
4: $\quad \hat{\theta}_h \leftarrow \Sigma_h^{-1} \sum_{k=1}^{K} \phi_h(s_h^k, a_h^k) \cdot (r_h^k + \hat{V}_{h+1}(s_{h+1}^k))$
5: $\quad \hat{Q}_h(\cdot, \cdot) \leftarrow \min\{\langle \phi_h(\cdot, \cdot), \hat{\theta}_h \rangle, H - h + 1\}^+$.
6: $\quad \hat{\pi}_h \leftarrow \arg\max_{\pi_h} \langle \hat{Q}_h, \pi_h \rangle$ and $\hat{V}_h^k \leftarrow \langle \hat{Q}_h^k, \pi_h^k \rangle$.
7: **end for**
8: **Output**: $\hat{\pi} = \{\hat{\pi}_h\}_{h \in [H]}$

Algorithm 5 LinPER

1: **Input**: Offline data $\mathcal{D} = \{(s_h^k, a_h^k, r_h^k)\}_{h\in[H]}^{k\in[K]}$, perturbed variances $\{\sigma_h\}_{h\in[H]}$, number of bootstraps M, regularization parameter λ.
2: Initialize $\tilde{V}_{H+1}(\cdot) \leftarrow 0$
3: **for** $h = H, \ldots, 1$ **do**
4:      $\Lambda_h \leftarrow \sum_{k=1}^K \phi(s_h^k, a_h^k)\phi(s_h^k, a_h^k)^T + \lambda I$
5:      **for** $i = 1, \ldots, M$ **do**
6:          Sample $\{\xi_h^{\tau,i}\}_{\tau\in[K]} \sim \mathcal{N}(0, \sigma_h^2)$ and $\zeta_h^i = \{\zeta_h^{j,i}\}_{j\in[d]} \sim \mathcal{N}(0, \sigma_h^2 I_d)$
7:          Solve the perturbed regularized least-squares regression:

$$\tilde{\theta}_h^i \leftarrow \underset{\theta\in\mathbb{R}^d}{\arg\max} \sum_{k=1}^K \left(\langle\phi(s_h^k, a_h^k), \theta\rangle - (r_h^k + \tilde{V}_{h+1}(s_{h+1}^k) + \xi_h^{k,i})\right)^2 + \lambda\|\theta + \zeta_h^i\|_2^2,$$

8:      **end for**
9:      Compute $\tilde{Q}_h(\cdot, \cdot) \leftarrow \min\{\min_{i\in[M]}\langle\phi(\cdot, \cdot), \tilde{\theta}_h^i\rangle, H - h + 1\}^+$
10:      $\tilde{\pi}_h \leftarrow \arg\max_{\pi_h}\langle\tilde{Q}_h, \pi_h\rangle$ and $\tilde{V}_h \leftarrow \langle\tilde{Q}_h, \tilde{\pi}_h\rangle$
11: **end for**
12: **Output**: $\tilde{\pi} = \{\tilde{\pi}_h\}_{h\in[H]}$

Algorithm 6 NeuraLCB (a modification of (Nguyen-Tang et al., 2021a))

1: **Input**: Offline data $\mathcal{D} = \{(s_h^k, a_h^k, r_h^k)\}_{h\in[H]}^{k\in[K]}$, neural networks $\mathcal{F} = \{f(\cdot, \cdot; W) : W \in \mathcal{W}\} \subset \{\mathcal{X} \rightarrow \mathbb{R}\}$, uncertainty multiplier β, regularization parameter λ, step size η, number of gradient descent steps J
2: Initialize $\tilde{V}_{H+1}(\cdot) \leftarrow 0$ and initialize $f(\cdot, \cdot; W)$ with initial parameter W_0
3: **for** $h = H, \ldots, 1$ **do**
4:      $\hat{W}_h \leftarrow \text{GradientDescent}(\lambda, \eta, J, \{(s_h^k, a_h^k, r_h^k)\}_{k\in[K]}, 0, W_0)$ (Algorithm 2)
5:      $\Lambda_h \leftarrow \lambda I + \sum_{k=1}^K g(s_h^k, a_h^k; \hat{W}_h)g(x_h^k; \hat{W}_h)^T$
6:      Compute $\hat{Q}_h(\cdot, \cdot) \leftarrow \min\{f(\cdot, \cdot; \hat{W}_h) - \beta\|g(\cdot, \cdot; \hat{W}_h)\|_{\Lambda_h^{-1}}, H - h + 1\}^+$
7:      $\hat{\pi}_h \leftarrow \arg\max_{\pi_h}\langle\hat{Q}_h, \pi_h\rangle$ and $\hat{V}_h \leftarrow \langle\hat{Q}_h, \hat{\pi}_h\rangle$
8: **end for**
9: **Output**: $\hat{\pi} = \{\hat{\pi}_h\}_{h\in[H]}$.

Algorithm 7 NeuralGreedy

1: **Input**: Offline data $\mathcal{D} = \{(s_h^k, a_h^k, r_h^k)\}_{h\in[H]}^{k\in[K]}$, neural networks $\mathcal{F} = \{f(\cdot, \cdot; W) : W \in \mathcal{W}\} \subset \{\mathcal{X} \rightarrow \mathbb{R}\}$, uncertainty multiplier β, step size η, number of gradient descent steps J
2: Initialize $\tilde{V}_{H+1}(\cdot) \leftarrow 0$ and initialize $f(\cdot, \cdot; W)$ with initial parameter W_0
3: **for** $h = H, \ldots, 1$ **do**
4:      $\hat{W}_h \leftarrow \text{GradientDescent}(\lambda, \eta, J, \{(s_h^k, a_h^k, r_h^k)\}_{k\in[K]}, 0, W_0)$ (Algorithm 2)
5:      Compute $\hat{Q}_h(\cdot, \cdot) \leftarrow \min\{f(\cdot, \cdot; \hat{W}_h), H - h + 1\}^+$
6:      $\hat{\pi}_h \leftarrow \arg\max_{\pi_h}\langle\hat{Q}_h, \pi_h\rangle$ and $\hat{V}_h \leftarrow \langle\hat{Q}_h, \hat{\pi}_h\rangle$
7: **end for**
8: **Output**: $\hat{\pi} = \{\hat{\pi}_h\}_{h\in[H]}$.