On the Pitfalls of Visual Learning in Referential Games

Abstract

This paper focuses on the effect of game design and visual representations of real-world entities on emergent languages in referential games. Strikingly, we find that the agents in such games learn to successfully communicate even when provided with visual features from a randomly initialized neural network. Through a series of experiments, we highlight the agents' inability to effectively utilize high-level features. Using Gradient weighted-Class Activation Mapping, we verify that the agents often 'look' at regions not related to entities. Culminating with a positive result, we show how environmental pressure from agent population can nudge the learners into effectively capturing high-level visual features.

1 Introduction

The ability to communicate through natural language is often seen as a long standing goal in AI. The current prevalent paradigm in natural language learning leverages statistical patterns using large amounts of data. Alternatively, the field of language emergence [2, 9, 29, 13] exploits language's functional nature. Recently, there has been a revival of interest in language emergence games by studying them through the lens of neural agents [20, 14, 21]. Efforts are made to understand the linguistic properties of emergent languages, such as grammar [30], compositionality [1], priors and biases [6, 11] and capacity and bandwidth [24]. Another line of work stresses upon the shortcomings of emergent language through neural agents, such as anti-efficient encoding [5] and the need for specialized environmental pressures [18, 25]. However, an area that is often ignored is the effect of visual representations on shaping the emergent language properties. [3] demonstrate an alarming behaviour in emergent languages where agents rely on low-level visual features for communication. In our work, we highlight the role of visual representations and game design in aggravating this behaviour. Through empirical results, we show that the agents are ineffective at learning from high-level visual representations of images. This is surprising since it has been common practice in emergent language literature to represent real-world images as either final layer activations of pre-trained deep ConvNets such as VGG-16 [28] (e.g. in [14, 20, 19, 12]) or using representations learned in-game [8, 25, 22]. Further, we reformulate Gradient-weighted Class Activation Mapping (Grad-CAM) [26] to visualize where the agents are looking. This is the first application of Grad-CAM in interpreting referential games. Lastly, we conduct experiments in line with strong results obtained from language emergence in population of agents [17, 16, 23, 7]. We show that a simple population-based Referential Game induces a regularization effect, nudging the agents to communicate through high-level visual features. Our novel contributions are thus as follows:

1) We evaluate agents' reliance on low-level features for communication using two synthetic testbeds in Emergent Communication.

2) We reformulate Grad-CAM for use in Multi-Agent Reinforcement Learning setting and show that the agents 'look' at regions not related to entities.

37 3) We demonstrate that environmental pressure through population of agents regularize agents to use
38 high-level visual features for communication.

2 Referential Game

40 Two agents, a sender S and a receiver R play the game. The sender is shown a target image t and K
41 distracting images $\mathcal{D} = \{d_k\}_{k=1}^{i=K}$. Consequently, sender must come up with a message m of length l
42 with tokens from vocabulary $\mathcal{V}$. The receiver is shown the target image and distracting images in a
43 shuffled order, along with the message m. A payoff of 1 is provided to both the agents iff the receiver
44 identifies the target correctly.
45 We consider the following agent and game variants:
46 **Distractor Aware Sender**: Given the target image t and distracting images $\mathcal{D}$, sender must come up
47 with message m.
48 **Distractor Agnostic Sender**: Given only target image t, sender must come up with message m.
49 **Same Target Game**: Given message m and a shuffled set of images containing t and $\mathcal{D}$, the receiver
50 must identify the target correctly.
51 **Different Target Game**: Instead of target image t, the receiver is shown a different target image t',
52 which is conceptually same as t.

53 We use $K = 1, l = 5, |\mathcal{V}| = 10$ in all experiments. Previous works have shown that even a small
54 game size can be a challenging learning environment. Crucially, keeping these hyperparameters fixed
55 makes sure that there are no confounding factors when studying the effects of game variations.

2.1 Data

57 We generate two synthetic datasets [1], SHAPES and BULLET, to represent images corresponding to
58 different visual attributes. Both datasets consist of 30 X 30 images with objects characterized by one
59 of 3 colours, 2 sizes and 3 shapes. SHAPES has 2D objects placed on a background with randomized
60 location. BULLET has 3D objects placed on a checkered plane with randomized location as well
61 as camera viewpoint. Unlike SHAPES where background is constant, BULLET has a checkered
62 plane where pixel values change with changing camera orientation. Thus, BULLET showcases more
63 variation in pixel-level features as compared to SHAPES, while having the same high-level attribute
64 set. We argue that studying emergent languages using proposed datasets has an advantage over
65 ImageNet [10], as attribute information can readily be controlled. Further, raw pixel inputs provide
66 a much more realistic task [19], than using one-hot vectors of attributes, as has been done in many
67 prior works [18, 4].

2.2 Learning and Architecture

69 We re-implement agent architectures from [14]. The sender and receiver both have one ConvNet
70 visual module f_s and f_r and one LSTM language module L_s and L_r respectively. The visual
71 module maps input images to fixed dimension embedding. Sender's language module L_s generates
72 sequence of message tokens m with embeddings from f_s as the initial hidden state. The receiver's
73 language module L_r receives message m and a message embedding is obtained by performing affine
74 transformation g on last hidden state in L_r. Finally, the receiver compares the message embedding
75 and visual embeddings from each of the images to point to a target. We use Straight-Through
76 Gumbel-softmax (GS) relaxation [15], while sampling messages from sender's language module.
77 This allows the game to be end-to-end differentiable which is crucial for Grad-CAM (Section 4.2).
78 The energy function for each image v, $E(v, m) = f_r(v)^T g(L_r(m))$, can be used to define probability
79 distribution over images as $p(v|m) \propto e^{E(v,m)}$. Since our learning setup is similar to the one proposed
80 by [14], we optimize the same loss function. $\mathcal{L} = \mathbb{E}_{m \sim \Pi_\theta} \sum_{k=1}^{K-1} max(0, 1 - E(t, m)) + E(d_k, m)$

81 To study the effect of visual representations, we also include the following two learning variants:
82 **In-game learning (I):** The weights for both f_r and f_s are updated during learning in game play.
83 **Pre-trained classifier (P):** A visual module is pre-trained on the task of classifying entities. Weights
84 are saved and representations of input images are computed before gameplay. f_s and f_r are not used.

---

[1]Dataset generation script will be open-sourced upon acceptance

Metric	Distractor Aware						Distractor Agnostic					
	Same Target			Diff Target			Same Target			Diff Target		
	I	**P**	**R**	**I**	**P**	**R**	**I**	**P**	**R**	**I**	**P**	**R**
SHAPES												
Comm Acc	98.3∓0.72	98.03∓0.9	98.5∓0.5	96.57∓1.9	95.8∓1.7	95.4∓1.8	94.32∓1.8	94.04∓2.0	94.02∓1.8	88.16∓5.1	86.5∓4.0	86.39∓3.0
Noise Acc	87.94∓8.8	63.5∓4.4	71.24∓8.1	56.25∓7.9	56.6∓8.1	57.2∓4.8	55.9∓2.7	59.1∓9.5	51.02∓8.1	50.26∓2.2	51.56∓3.3	53.9∓9.2
General Acc	93.2∓0.94	92.8∓1.4	96.93∓1.2	72.7∓0.80	78.3∓0.91	96.93∓1.2	66.18∓0.69	67.3∓1.4	86.7∓0.93	68.2∓0.71	69.3∓1.0	86.7∓0.93
Top Sim	0.07∓0.14	0.03∓0.13	0.02∓0.13	0.05∓0.10	0.01∓0.13	0.08∓0.15	0.28∓0.11	0.14∓0.14	0.12∓0.14	0.41∓0.11	0.20∓0.12	0.38∓0.12
BULLET												
Comm Acc	98.25∓0.76	97.77∓1.1	97.27∓0.83	96.59∓1.6	96.16∓1.7	95.45∓1.7	94.98∓1.9	94.2∓2.0	93.71∓2.2	88.93∓4.1	87.18∓3.4	87.78∓2.4
Noise Acc	86.86∓7.8	86.41∓1.21	84.05∓4.1	63∓2.5	62.8∓3.9	60.71∓2.6	51.49∓1.3	61.22∓5.6	65.96∓3.6	50.78∓2.0	51.68∓1.5	52.2∓2.7
General Acc	95.3∓0.96	94.11∓0.6	96.7∓0.9	92.6∓0.94	90.1∓1.8	96.7∓0.9	82.2∓0.83	80.8∓0.77	81.5∓0.9	69.6∓0.71	66.8∓0.9	81.5∓0.9
Top Sim	0.06∓0.15	0.019∓0.14	0.045∓0.13	0.08∓0.15	0.09∓0.11	0.08∓0.14	0.29∓0.15	0.25∓0.15	0.19∓0.17	0.32∓0.13	0.29∓0.15	0.33∓0.13

Table 1: Evaluation metrics (mean and std-dev) on different variations of referential game.

3 Evaluation Metrics

We evaluate the game variants on four metrics: **(1) Communication Success:** Measured as average reward obtained at convergence. **(2) Generalization Success:** Measured as communication success on novel combinations of unseen concepts. **(3) Topographical Similarity:** Measured as correlation between all-pair distances in message space and in input space and can be seen as language compositionality measure [20]. **(4) Noise Accuracy:** Measured as test time communication success over images containing only gaussian noise. It quantifies agents' reliance on pixel-level visual features [3].

4 Experiments

4.1 Effects from game variations

All combinations of proposed game variants are enumerated and run until convergence for 10 different seed values. Evaluation metrics are reported in Table 1. To develop a baseline for comparison, we also report results from games with a **random visual module (R)**. In this setting, f_s and f_r are fully connected single layer networks with weights randomly initialized and frozen during training.

We obtain the following statistically significant observations from our experiments:

- High levels of communication success are reached in all the games ($> 90\%$). Surprisingly, experiments with *Random Visual Module* also achieve high communication success.
- Noise accuracy is lower in *Distractor-Agnostic* setting as compared to *Distractor-Aware*. A plausible reason could be the absence of context for sender without distractors. Since relative comparison is not possible, encoding high-level visual information would be incentivized. Higher topographical similarity in *Distractor-Agnostic* also supports our argument.
- While *Distractor-Aware* setting has a high noise accuracy, using *Different-Target* lowers it as compared to *Same-Target* game. This matches with the results obtained in [3].
- All *Distractor-Aware Pre-Train* experiments have performance comparable to baseline (random) experiment. This is an alarming result as it suggests that agents gain no significant benefit in communication when provided with high-level visual information.

Statistical significance is calculated using t-test for comparison of means when comparing two groups. All the above observations are significance with p-value < 0.05.

4.2 Where are the agents looking?

To qualitatively access whether the agents are looking at high-level visual attributes or at pixel-level differences, we reformulate Gradient-weighted Class Activation Mapping [26]. As the game is end-to-end differentiable, we can attribute the outcome of the game to specific regions in the inputs by generating a class discriminative localization map. Let m be the message generated by sender and $u \in t \cup \mathcal{D}$ be the image chosen by the receiver. The energy function $E(u, m)$ represents the likelihood of u being the target image. For any image $v \in t \cup \mathcal{D}$, for which we want to generate localization map H, we define A_s^u and A_r^u as activations from final convolutional layers in sender's and receiver's visual modules. We calculate the localization map for sender as $\alpha_s^u = \frac{\partial E(v,m)}{\partial A_s^u}, H_s^u = ReLU(\alpha_s^u A_s^u)$ We repeat this process for receiver and for all the images in the sender's and receiver's input. Figure 1 shows that grad-CAM can accurately highlight regions of entities in targets and distractors. However,

Figure 1: Grad-CAM heatmaps for different referential game variants (all with Pre-trained (P) visual module), averaged over 5 seeded runs.

in many cases, the agents "look" at background regions. This is more prominent in BULLET dataset. Interestingly, in some cases, agents look at negative space of the object. This suggests that agents may communicate through negation of attributes (e.g. 'the object not in the bottom right corner') as has been previously expressed in [8, 27].

4.3 Population based Referential Game

We extend the referential game setup to a population of agents. Consider N agents, consisting of an equal number of senders and receivers. At every game turn, a referential game is played between a random pair of sender and a receiver. We argue that population as an environmental pressure should reduce the agents' reliance on low-level features. This is because high communication success from low-level features is a sign of conceptual pact between two agents. However, when the game partners are continuously shuffled, low-level pacts would no longer always match. Figure 2 shows that noise accuracy at convergence indeed reduces with larger population sizes.

5 Conclusion

Our work ascertains that agents in referential games often rely on low-level features for communication; however, some game settings are more susceptible to do so than others. Thus, noise accuracy should always be reported in emergent language experiments. Moreover, a high generalization accuracy can be misleading as it may result from pixel-level comparison rather than a compositional language. Additionally, as we observe a prevalence of negation of attributes in emergent communication, there is a need to incorporate it in compositionality measures.

Figure 2: Noise Accuracy at convergence for different population sizes. *Distractor Aware*, *Same Target* game on BULLET dataset

The multi-input, multi-output Grad-CAM setup through GS channel, presented in our work, can be adapted as an interpretability tool for numerous Multi-Agent RL scenarios such as visual dialog agents, embodied agents or in cooperative/competitive communication games. Lastly, a promising direction for future work is the effect of population interaction on conceptual pacts among agents and how it evolves over time.

References

[1] Jacob Andreas. Measuring compositionality in representation learning. In *International Conference on Learning Representations*, 2019.

[2] John Langshaw Austin. *How to do things with words*, volume 88. Oxford university press, 1975.

[3] Diane Bouchacourt and Marco Baroni. How agents see things: On visual representations in an emergent language game. In Ellen Riloff, David Chiang, Julia Hockenmaier, and Jun'ichi Tsujii, editors, *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing, Brussels, Belgium, October 31 - November 4, 2018*, pages 981–985. Association for Computational Linguistics, 2018.

[4] Rahma Chaabouni, Eugene Kharitonov, Diane Bouchacourt, Emmanuel Dupoux, and Marco Baroni. Compositionality and generalization in emergent languages. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel R. Tetreault, editors, *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, ACL 2020, Online, July 5-10, 2020*, pages 4427–4442. Association for Computational Linguistics, 2020.

[5] Rahma Chaabouni, Eugene Kharitonov, Emmanuel Dupoux, and Marco Baroni. Anti-efficient encoding in emergent communication. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32, pages 6293–6303. Curran Associates, Inc., 2019.

[6] Rahma Chaabouni, Eugene Kharitonov, Alessandro Lazaric, Emmanuel Dupoux, and Marco Baroni. Word-order biases in deep-agent emergent communication. In Anna Korhonen, David R. Traum, and Lluís Màrquez, editors, *Proceedings of the 57th Conference of the Association for Computational Linguistics, ACL 2019, Florence, Italy, July 28- August 2, 2019, Volume 1: Long Papers*, pages 5166–5175. Association for Computational Linguistics, 2019.

[7] Rahma Chaabouni, Florian Strub, Florent Altché, Eugene Tarassov, Corentin Tallec, Elnaz Davoodi, Kory Wallace Mathewson, Olivier Tieleman, Angeliki Lazaridou, and Bilal Piot. Emergent communication at scale. In *International Conference on Learning Representations*, 2021.

[8] Edward Choi, Angeliki Lazaridou, and Nando de Freitas. Compositional obverter communication learning from raw visual input. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018.

[9] Vincent Crawford. A survey of experiments on communication via cheap talk. *Journal of Economic Theory*, 78(2):286–298, Feb 1998.

[10] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Fei-Fei Li. Imagenet: A large-scale hierarchical image database. In *2009 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR 2009), 20-25 June 2009, Miami, Florida, USA*, pages 248–255. IEEE Computer Society, 2009.

[11] Tom Eccles, Yoram Bachrach, Guy Lever, Angeliki Lazaridou, and Thore Graepel. Biases for emergent communication in multi-agent reinforcement learning. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pages 13111–13121, 2019.

[12] Katrina Evtimova, Andrew Drozdov, Douwe Kiela, and Kyunghyun Cho. Emergent communication in a multi-modal, multi-step referential game. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018.

[13] Michael C Frank and Noah D Goodman. Predicting pragmatic reasoning in language games. *Science*, 336(6084):998–998, 2012.

[14] Serhii Havrylov and Ivan Titov. Emergence of language with multi-agent games: Learning to communicate with sequences of symbols. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, 4-9 December 2017, Long Beach, CA, USA*, pages 2149–2159, 2017.

[15] Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017.

[16] Simon Kirby, Tom Griffiths, and Kenny Smith. Iterated learning and the evolution of language. *Current opinion in neurobiology*, 28:108–114, 2014.

[17] Simon Kirby and James R Hurford. The emergence of linguistic structure: An overview of the iterated learning model. *Simulating the evolution of language*, pages 121–147, 2002.

[18] Satwik Kottur, José M. F. Moura, Stefan Lee, and Dhruv Batra. Natural language does not emerge 'naturally' in multi-agent dialog. In Martha Palmer, Rebecca Hwa, and Sebastian Riedel, editors, *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing, EMNLP 2017, Copenhagen, Denmark, September 9-11, 2017*, pages 2962–2967. Association for Computational Linguistics, 2017.

[19] Angeliki Lazaridou, Karl Moritz Hermann, Karl Tuyls, and Stephen Clark. Emergence of linguistic communication from referential games with symbolic and pixel input. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018.

[20] Angeliki Lazaridou, Alexander Peysakhovich, and Marco Baroni. Multi-agent cooperation and the emergence of (natural) language. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017.

[21] Igor Mordatch and Pieter Abbeel. Emergence of grounded compositional language in multi-agent populations. In Sheila A. McIlraith and Kilian Q. Weinberger, editors, *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence, (AAAI-18), the 30th innovative Applications of Artificial Intelligence (IAAI-18), and the 8th AAAI Symposium on Educational Advances in Artificial Intelligence (EAAI-18), New Orleans, Louisiana, USA, February 2-7, 2018*, pages 1495–1502. AAAI Press, 2018.

[22] Jesse Mu and Noah Goodman. Emergent communication of generalizations. *Advances in Neural Information Processing Systems*, 34, 2021.

[23] Limor Raviv, Antje Meyer, and Shiri Lev-Ari. Larger communities create more systematic languages. *Proceedings of the Royal Society B*, 286(1907):20191262, 2019.

[24] Cinjon Resnick, Abhinav Gupta, Jakob N. Foerster, Andrew M. Dai, and Kyunghyun Cho. Capacity, bandwidth, and compositionality in emergent language learning. In Amal El Fallah Seghrouchni, Gita Sukthankar, Bo An, and Neil Yorke-Smith, editors, *Proceedings of the 19th International Conference on Autonomous Agents and Multiagent Systems, AAMAS '20, Auckland, New Zealand, May 9-13, 2020*, pages 1125–1133. International Foundation for Autonomous Agents and Multiagent Systems, 2020.

[25] Diana Rodríguez Luna, Edoardo Maria Ponti, Dieuwke Hupkes, and Elia Bruni. Internal and external pressures on language emergence: least effort, object constancy and frequency. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 4428–4437, Online, November 2020. Association for Computational Linguistics.

[26] Ramprasaath R. Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *IEEE International Conference on Computer Vision, ICCV 2017, Venice, Italy, October 22-29, 2017*, pages 618–626. IEEE Computer Society, 2017.

[27] Josefina Sierra-Santibanez. An agent-based model of the emergence and evolution of a language system for boolean coordination: Jaamas track. In *Proceedings of the 18th International Conference on Autonomous Agents and MultiAgent Systems*, AAMAS '19, page 1761–1763, Richland, SC, 2019. International Foundation for Autonomous Agents and Multiagent Systems.

[28] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

[29] Luc Steels. Evolving grounded communication for robots. *Trends in cognitive sciences*, 7(7):308–312, 2003.

[30] Oskar van der Wal, Silvan de Boer, Elia Bruni, and Dieuwke Hupkes. The grammar of emergent languages. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 3339–3359, Online, November 2020. Association for Computational Linguistics.

On the Pitfalls of Visual Learning in Referential Games: Appendix

1. FORMAL DESCRIPTION OF REFERENTIAL GAME

Since the referential game formulation has already been provided in prior works, we omitted it from the main text. However, for clarity, we provide a formal description of the game here.

1. Two agents play the game, a sender S and a receiver R.
2. From a set of real world concepts $\{C_i\}_{i=1}^{i=N}$, a target concept C_t and K distracting concepts $\{C_{k_i}\}_{i=1}^{i=K}$ are chosen, $t \neq k_i \; \forall i \in \{1, ..., N\}$.
3. At each turn of the game, we sample an image I_t representing concept C_t and images $T_d = \{I_{k_i}\}_{i=1}^{i=K}$ for each of the K distracting concepts. Sampling is done from a large set of images for every concept.
4. Sender variations:

   - Distractor Aware: Given the target image I_t and distracting images I_d, the sender must come up with a message m.
   - Distractor Agnostic: Given only the target image I_t the sender must come up with a message m.

5. The message m is represented using a sequence of symbols from a vocabulary of size $|\mathcal{V}|$ and having maximum length l.
6. Game variations:

   - Same Target: Given message m and a shuffled set of images containing target image I_t and distracting images I_d, the receiver must identify the target correctly.
   - Different Target: Instead of target image I_t, the receiver is shown different target image I_t' of the same concept C_t

7. A payoff of 1 is provided to both the agents only if the receiver correctly identifies the target. Otherwise the payoff is 0.

2. GENERATING DATA

We generate two synthetic datasets, SHAPES and BULLET, both consisting of 30 x 30 images. In SHAPES, a 2D object is placed on a blank image and is characterized by shape (circle, square, triangle), colour (red, green, blue) and size (small, big) resulting in 18 concepts. In BULLET, a 3D object of shape (sphere, cube, capsule), colour (red, green, blue) and size (small, big) is placed on a plane. See Figure S1. 100 randomized versions (location and orientation randomization) for each concept are generated, resulting in 1800 unique images for each dataset. Further, we holdout 3 concepts which are never used during training or testing but are used to evaluate generalization accuracy. Note that during gameplay, we do not use a single image but use a subset of images to form target and distractors. This results in combinatorially large number of unique sets. For images not belonging to holdout set, we sample 7000 combinations for use during training and 1000 for testing while making sure the two sets are disjoint. The 300 holdout images are then used for creating 1000 combinations on which generalization accuracy is calculated.

We use PyCairo library for generating SHAPES dataset and PyBullet library to generate BULLET dataset.

3. HYPERPARAMETER DETAILS

Both sender and receiver agents have visual module, language module and a set of densely connected layers. The visual module consists of 3 Convolutional layers with 20 filters each. These map the 30 X 30 images into a 500 dimension vector. This is further mapped to a visual embedding E of dimension 2048 using a fully connected layer. ReLU activation function is used between all the layers. The language module is a Long Short term Memory (LSTM) network with hidden state size h=512 and embedding size as 256. For the sender, it is used to generate a sequence of message tokens with embeddings from the visual module as the initial hidden state. Instead of categorical sampling to obtain message tokens, we use a Straight-Through Gumbel Softmax Relaxation which allows the game to remain end-to-end differentiable. We keep temperature parameter $\tau = 1.2$. The receiver uses the language module to create a message embedding, which is an affine transformation of the last hidden state in its LSTM network. This affine transform is modelled through a fully connected layer with input size same as hidden state size h and output size same as visual embedding vector size E. Adam optimizer is used and the

(a) Big Green Square

(b) Big Red Triangle

(c) Big Green Cube

(d) Big Blue Sphere

Fig. S1. Examples from SHAPES and BULLET datasets

r

(a) Noise-Image of size 30×30 in single channel

(b) Noise-Image of size 30×30 in RGB channels

Fig. S2. Examples Noise Images

learning rate is kept at 0.001. Batch size 128 is used. We use these hyperparameters choices without tuning in all our experiments.

For game configuration, we use $K = 1$ as the number of distractors. This helps in easy visualizing of grad-CAM heatmaps. Vocabulary size $|\mathcal{V}|$ is taken as 10, and messages are restricted to length $l = 5$. Keeping these game hyperparameters fixed ensures that performance variations in the games are only because of the different proposed settings under our study.

All the experiments are inexpensive to run and have been performed on Google Colab Instance with GPU. Experiments with multiple seed values took about an hour to reach completion.

4. CALCULATING EVALUATION METRICS

Generalization Success: Measured as communication success on novel combinations of unseen concepts. Here we report it to quantify how much the communication success is grounded in the game. It is implemented by having a held-out set of concepts which are never shown to the agents during the training. The communication success on this held out set is then reported. Note that while higher generalization success is desirable and might be due to a compositional language, it isn't a measure of compositionality.

Noise Accuracy: In order to quantify whether agents are using high-level image features or pixel level differences, we test communication success on noise-images. Prior to this test, the agents are trained using the SHAPES/BULLET dataset images only. A noise-image is composed entirely of gaussian-noise (see Figure S2) and has no easily perceivable features such as edges, shapes and textures for humans. The random noise is sampled from a standard gaussian distribution and normalized to 0-255 range. If the agents are indeed using high-level image features, communication should be incredibly hard. But evaluation metrics shown in the main text report otherwise.

Topographical Similarity: Measured as the correlation between all-pair distances in message space and in input space. The input space is defined using a one-hot attribute vector for each image, and Cosine Similarity is used as distance metric. Messages are already tokenized hence no new representation is needed for it. We use Levenshtein-Distance to calculate distance between any two messages. These design choices are taken from prior works in Neural emergent language literature.

5. GENERATING HEATMAPS THROUGH GRAD-CAM

In addition to heatmaps reported in the main text, we show more examples on how the agents percieve their visual inputs in Figures S3,S4

6. COMMUNICATION SUCCESS IN POPULATION BASED REFERENTIAL GAME

In addition to noise accuracy, we also plot communication accuracy for all population sizes. Agents are trained until the mean communication accuracy of the population reaches 95%.

It can be observed that larger population sizes require more games to reach convergence. Additionally, we show the number of games required per agent for each of the population in Table S1. The trend shows that steps

(a) Same Target Game   **(b)** Different Target Game   **(c)** Same Target Game   **(d)** Different Target Game

Fig. S3. Examples from Distractor Agnostic Games on SHAPES(a,b) and BULLET(c,d) dataset

(a) Same Target Game   **(b)** Different Target Game   **(c)** Same Target Game   **(d)** Different Target Game

Fig. S4. Examples from Distractor Aware Games on SHAPES (a, b) and BULLET (c,d) datasets

Fig. S5. Communication Success for different population sizes

Population Size	Steps (till convergence)	Steps per agent (till convergence)	Population Size	Steps (till convergence)	Steps per agent (till convergence)
2	16382	8191	12	42448	3537
4	22241	5560	14	57639	4117
6	28255	4710	16	45860	2866
8	31146	3893	18	69391	3855
10	41323	4132	20	75642	3782

Table S1. Total game steps and game steps per agent for different population sizes (over 5 seeded runs)

per agent reduce over increasing population sizes, although, it doesn't reduce monotonically. We leave further study into this phenomenon for future work.