FASTER REINFORCEMENT LEARNING WITH VALUE TARGET LOWER BOUNDING

ABSTRACT

We show that an arbitrary lower bound of the maximum achievable value can be used to improve the Bellman value target during value learning. In the tabular case, value learning using the lower bounded Bellman operator converges to the same optimal value as using the original Bellman operator, at a potentially faster speed. In practice, discounted episodic return in episodic tasks and n-step bootstrapped return in continuing tasks can serve as lower bounds to improve the value target. We experiment on Atari games, FetchEnv tasks and a challenging physically simulated car push and reach task. We see large gains in sample efficiency as well as converged performance over common baselines such as TD3, SAC and Hindsight Experience Replay (HER) in most tasks, and observe a reliable and competitive performance against the stronger n-step methods such as td-lambda, Retrace and optimality tightening. Prior works have already successfully applied a special case of lower bounding (using episodic return), but are limited to a small number of episodic tasks. To the best of our knowledge, we are the first to propose the general method of value target lower bounding (with possibly bootstrapped return), to demonstrate its optimality in theory, and effectiveness in a wide range of tasks over many strong baselines.

1 INTRODUCTION

The value function is a key concept in dynamic programming approaches to Reinforcement Learning (RL) (Bellman, 1957). It estimates the sum of all future rewards (usually time-discounted) of a given state. In temporal difference (TD) learning, the value function is adjusted toward its Bellman target which adds the reward of the current step with the (discounted) value of the next state (Sutton & Barto, 2018). This forms the basis of many state of the art RL algorithms such as DQN (Mnih et al., 2013), DDPG (Lillicrap et al., 2016), TD3 (Fujimoto et al., 2018), and SAC (Haarnoja et al., 2018).

The value of the next state is typically estimated using a "bootstrapped value" based on the value function itself, which is being actively learned during training. The bootstrapped values can be random and far from the optimal value, especially at the initial stage of training, or with sparse reward tasks where rewards can only be achieved through a long sequence of actions. Consequently, the Bellman value targets as well as the learned values are usually far away from the optimal value (the value of the optimal policy).

Naturally, this leads to the following idea: If we can make the value target closer to the optimal value, we may speedup TD learning. For example, we know that the optimal value is just the expected discounted return of the optimal policy, which always upper bounds the expected return of any policy. For episodic RL tasks, we could use the observed discounted return up to episode end from the training trajectories to lower bound the value target. This makes the new value target closer to the optimal value, when the empirical return is higher than the Bellman target.

The case for continuing or non-episodic tasks is less clear though. When a continuing task can return negative rewards, any safe lower bound of the optimal value can be too low to be useful. One could take the risk and use n-step bootstrapped return as a lower bound, which is unsafe because bootstrapped return can overestimate and be greater than the optimal value. Can we still use them as lower bounds to improve TD value targets?

Algorithm 1 Value iteration with value target lower bounding

Input: Finite MDP $p(s', r|s, a)$, convergence threshold θ, a lower bound $f(s)$ of the maximum achievable value $\bar{G}^v(s)$
Output: State value $v(s)$
$v(s) \leftarrow 0$
repeat
  $\Delta \leftarrow 0$
  $v_p(s) \leftarrow v(s)$
  for each state s **do**
    $\hat{v}(s) \leftarrow \max_a \sum_{s',r} p(s', r|s, a)[r + \gamma v_p(s')]$
    $\hat{v}_f(s) \leftarrow \max(f(s), \hat{v}(s))$
    $v(s) \leftarrow \hat{v}_f(s)$
    $\Delta \leftarrow \max(\Delta, |v(s) - v_p(s)|)$
  end for
until $\Delta < \theta$

---

2 THEORETICAL RESULTS FOR THE TABULAR CASE

Our results show that for the tabular case, arbitrary functions below a certain bootstrap bound can be used to lower bound the value target to still converge to the same optimal value.

2.1 BACKGROUND

In finite MDPs with a limited number of states and actions, a table can keep track of the value of each state. Using dynamic programming algorithms such as value iteration, values are guaranteed to converge to the optimum through Bellman updates (Chapter 4.4 (Sutton & Barto, 2018)).

The core of the value iteration algorithm (Algorithm 1) is the Bellman update of the value function, $\mathcal{B}(v)$, where $v(s')$ is the bootstrapped value:

$$\mathcal{B}(v)(s) := \max_a \sum_{s',r} p(s', r|s, a)[r + \gamma v(s')] \tag{1}$$

It is well known that the Bellman operator, $\mathcal{B}$, is a contraction mapping over value functions (Denardo, 1967). That is, for any two value functions v_1 and v_2, $||\mathcal{B}(v_1) - \mathcal{B}(v_2)||_\infty \leq \gamma ||v_1 - v_2||_\infty$ for the discount factor $\gamma \in [0, 1)$ and $||x||_\infty := \max_i |x_i|$ (the L_∞ norm). This guarantees that any value function under the algorithm converges to the optimal value $\mathcal{B}^\infty(v) = v^*$.[1]

2.2 CONVERGENCE OF VALUE TARGET LOWER BOUNDING

Definition 2.1. The expected n-step bootstrapped return for a given policy π and value function $v(s)$ is defined as the expected bootstrapped return of taking n steps according to policy π:

$$G_n^{\pi,v}(s_0) := \mathbb{E}^\pi \{r_1 + ... + \gamma^{n-1} r_n + \gamma^n v(s_n)\} \tag{2}$$

Here, the step rewards r_i and the resulting n-th step state s_n are random variables, with the expectation $\mathbb{E}^\pi$ taken over all possible n-step trajectories under the policy π and the given MDP.

Definition 2.2. Given the current learned value function $v(s)$, policy class Π, the *maximum achievable value* of a state s is defined as:

$$\bar{G}^v(s) := \max_{\pi \in \Pi, n \in [1,+\infty)} G_n^{\pi,v}(s) \tag{3}$$

---

[1]For the gist of the proof, see for example page 8 of `https://people.eecs.berkeley.edu/~pabbeel/cs287-fa09/lecture-notes/lecture5-2pp.pdf`

This is a more relaxed definition of maximum because for each state s, a different policy $\pi(s)$ and a different number of steps $n(s)$ can be used to achieve the maximum $\bar{G}^v(s)$. And the theorem below says any function not exceeding the maximum achievable value can be used to lower bound the value target, and still achieve the optimal value in convergence.

Theorem 2.3. *Under the same assumptions for Bellman value contraction, for any function f that lower bounds the maximum achievable value, i.e. $\forall s, f(s) \leq \bar{G}^v(s)$, if we define the lower bounded Bellman operator as $\mathcal{B}_f(v) := \max(\mathcal{B}(v), f)$, then $\mathcal{B}_f^\infty(v) = \mathcal{B}^\infty(v)$.*

Note, the value $v(s)$ and the bootstrapped value can be inaccurate, and even above the optimal value. As a consequence, when n is finite, the maximum achievable value $\bar{G}^v(s)$ (and f) can be above the maximum expected return (i.e. the optimal value). On the other hand, when n is sufficiently large, the effect of the bootstrap value $v(s_n)$ diminishes (see Equation 2), and the maximum achievable value becomes the maximum expected return (i.e. the optimal value). Therefore, $\forall s, \bar{G}^v(s)$ is no smaller than the optimal value $\mathcal{B}^\infty(v)(s)$. As a special case of the theorem, as long as f is below the optimal value, value target lower bounding converges correctly:

Corollary 2.4. *If function f lower bounds the optimal value, i.e. $\forall s, f(s) \leq \mathcal{B}^\infty(v)(s)$, then $\mathcal{B}_f^\infty(v) = \mathcal{B}^\infty(v)$.*

A few things to note about the proof of Theorem 2.3 (included in Appendix A.1).

First, this only proves convergence, not contraction under the original $||v_1 - v_2||_\infty$ metric. In the case of the Bellman operator, contraction shows that $\forall v_1, v_2$ value functions, $||\mathcal{B}(v_1) - \mathcal{B}(v_2)||_\infty \leq \gamma ||v_1 - v_2||_\infty$. Here, for value target lower bounding, what's proved is convergence to v^* at a rate of γ, not contraction. There can be counter examples where the distance between v_1 and v_2 under one application of $\mathcal{B}_f$ can increase in the original L_∞ metric space, even though v_1 and v_2 are both getting closer to v^* at a rate of γ. One difficulty caused by convergence instead of contraction is that the stopping criterion in Algorithm 1 ($\Delta < \theta$) no longer works, due to the inaccessible v^* during learning. In practice, this may not be a serious concern, as people often train algorithms for a fixed number of iterations or time steps.

Second, based on the proof, the new algorithm is at least as fast as the original. When the lower bound actually improves the value target, i.e. $f(s) > \mathcal{B}(v_1)(s)$, there is a chance for the convergence to be faster. Convergence is strictly faster when the lower bound f has an impact on the L_∞ distance between the current value and the optimal value, i.e. it increases the value target for the states where the differences between the current value and the optimal value are the largest.

Third, the lower bound function doesn't have to be static during training. As long as there is a single f during each training update, convergence is preserved.

The following sections detail how to compute lower bounds of the maximum achievable value (Section 3), how to integrate the lower bounds into state of the art RL algorithms (Section 4), and provide an illustration of how this method may benefit value learning in practice (Section 4.3).

3 EXAMPLE LOWER BOUND FUNCTIONS

We show a few cases where lower bound functions can be readily obtained from the training experience. Future work may investigate alternatives.

3.1 EPISODIC TASKS

In episodic tasks, discounted return is accumulated up to the last step of an episode. During training, we can wait until an episode ends, and compute discounted returns for all time steps. To make it more efficient, we compute and store the discounted return for each time step into the replay buffer, and read it out when the experience is used in training, which adds very little computation to the baseline one-step TD learning.

$$f(s_0) = \sum_{i=0,..,\infty} \gamma^i r(s_i, a_i) \tag{4}$$

We call this variant "lb-DR", short for lower bounding with discounted return.

3.1.1 Episodic with hindsight relabeled goals

In goal conditioned tasks, one helpful technique is hindsight goal relabeling (Andrychowicz et al., 2017). It takes a future state that is d time steps away from the current state as the hindsight / relabeled goal for the current state. When the goal is reached, a reward of 0 is given, otherwise a -1 reward is given for each time step.

In this case, we know it took d steps to reach the hindsight goal, so the discounted future return is:

$$
\begin{aligned}
f(s_0) &= \sum_{i=0,..,d-1} -1\gamma^i \\
&= -1(1 - \gamma^d)/(1 - \gamma)
\end{aligned}
\tag{5}
$$

This calculation can be done on the fly as hindsight relabeling happens, requiring no extra space and very little computation.

We call this variant "lb-GD", short for lower bounding with goal distance based return.

Additionally, we can also apply lb-DR and lb-GD together, with discounted episodic return (lb-DR) on the original experience and goal distance based return (lb-GD) on the hindsight experience, giving the "lb-DR+GD" variant, which was used in Fujita et al. (2020).

3.2 In general (including non-episodic tasks)

If the task is continuing, without an episode end[2], discounted return needs to be accumulated all the way to infinity. When rewards are always non-negative, one can still use the accumulated discounted reward of the future n-steps to lower bound the value. But accumulated n-step discounted reward is no longer a lower bound when rewards can be negative, in which case, the more general lower bounding with bootstrapped value can be used: given a trajectory of training experience $\tau :=< s_0, ..., s_n >$:

$$
G_n^v(\tau) := r_1 + \gamma r_2 + ... + \gamma^{n-1} r_n + \gamma^n v(s_n)
\tag{6}
$$

In this case, two variations are possible: Given a trajectory of length n,

1. compute $v(s_i)$ for all $i \in [1, n]$ and take the maximum of all $G_i^v(\tau)$ to obtain a tighter lower bound. We call this variant "lb-b-$n$step":

$$
f(s_0) = \max_{i \in [1,n]} G_i^v(\tau)
\tag{7}
$$

2. only evaluate v on the last (i.e. the nth) step and use the nth-step bootstrapped return as the lower bound, which involves less compute but results in a looser bound. (When n is large enough, this becomes the lb-DR variant.) We call this variant "lb-b-$n$step-only".

$$
f(s_0) = G_n^v(\tau)
\tag{8}
$$

4 Integration into RL algorithms

4.1 Background

The value target lower bounds can be readily plugged into RL algorithms that regresses value to a target, e.g. DQN, DDPG or SAC.

In these algorithms, the action value $q(s, a)$ is learned through a squared loss with the target value y. In one step TD return, for a batch $\mathbf{B}$ of experience $\{s, a \to r, s'\}$, the loss is:

$$
\mathcal{L}_q := \sum_{(s,a,r,s') \in \mathbf{B}} |q(s, a) - y|^2
\tag{9}
$$

---

[2]Chapter 3.3 of Sutton & Barto (2018) has more details on episodic vs continuing tasks.

Figure 1: Illustration of value target lower bounding speeding up value learning as training progresses from stages 0 to 3. The task is to navigate in the state space from start state S to end state T, with sparse reward 1 at T and 0 elsewhere. The curve from S to T denotes a training experience that reaches the target. The shaded areas denote roughly states whose value has been significantly improved during training up to that stage.

In one step TD return, y is the one step TD return $\hat{q}(s, a, r, s')$:

$$\hat{q}(s, a, r, s') \coloneqq r(s, a) + \gamma q'(s', \mu'(s')) \tag{10}$$

Here, q' and μ' are the bootstrap value and policy functions, typically following the value and policy functions in a delayed schedule during training. (They are also called "target value" and "target policy", and are very different from the "value target" y in this paper.)

4.2 VALUE TARGET LOWER BOUNDING

With lower bounding, we replace the value target y with the lower bounded target:

$$y \leftarrow \max(f, \hat{q}(s, a, r, s')) = \max(f, r + \gamma q'(s', \mu'(s'))) \tag{11}$$

This way of lower bounding the value target is the same as was done by Fujita et al. (2020), but is subtly and importantly different from lower bounding the q value directly (Oh et al., 2018; Tang, 2020): $q(s, a) \leftarrow \max(f, q(s, a))$, which stays overestimated if $q(s, a)$ initially overestimates.

To the best of our knowledge, value target lower bounding with bootstrapped values is a novel contribution of this work.

4.3 AN ILLUSTRATIVE EXAMPLE

Figure 1 includes a fairly general example showing how value target lower bounding would improve value learning. Suppose we enhance an off policy algorithm such as DDPG with value target lower bounding (lb-DR), when there is no training experience hitting the target state, no meaningful training happens for the baseline or lb-DR. However, when there is one trajectory hitting the target state, all states along the trajectory will soon be propagated with meaningful return, and nearby states will also enjoy faster learning. As the state space becomes larger and the time horizon longer, a successful trajectory will speed up learning quite a bit.

5 EXPERIMENTS

The goal is to demonstrate the sample efficiency of lower bounding the value target over baseline such as DDPG, TD3, SAC and HER. Because the lower bounded value target can now look potentially many steps into the future, we suspect it to be best suited for long horizon, sparse reward tasks. Hence, we choose to experiment on a sampled subset of Atari games, the goal conditioned FetchEnv

tasks and the harder goal conditioned Pioneer Push and Reach tasks. See details of the experiment setup in Appendix A.2.

5.1 BASELINES

Baselines include DDPG (Lillicrap et al., 2016), TD3 (Fujimoto et al., 2018), SAC (Haarnoja et al., 2018) and HER (Andrychowicz et al., 2017; Plappert et al., 2018). Implementations are based on open sourced repositories, and baseline performance is verified against published results under similar settings. The Appendix A.6 and A.5 include results on more baselines such as DDQN (van Hasselt et al., 2015), td-labmda (Sutton & Barto, 2018) and Retrace (Munos et al., 2016).

5.2 HYPERPARAMETERS

Value target lower bounding is applied on top of these baselines without any additional hyperparameter (Section 4). The only hyperparameters come from the baselines. These hyperparameters follow published work as much as possible. When baseline hyperparameters need to be tuned for an environment, e.g. Atari games or Pioneer tasks, we search for the best performance in total episode reward averaged across all tasks for that environment on one set of random seeds, then the optimal hyperparameters are fixed and evaluated on a separate set of random seeds never seen during development. Value target lower bounding simply uses the the parameter values optimal for the baselines. Details are in Appendix A.3.

5.3 RESULTS

We report results on both episodic and continuing/non-episodic tasks. We report evaluation performance averaged across several runs of the algorithms (five for the less stable Atari games and three for the others). Each run uses a random seed never seen during development. Due to space constraints, the main paper only reports performance aggregated across all tasks for each environment. During each run, we take one task and one random seed, run baseline and treatment algorithms, and record whether treatment agent evaluates strictly above the baseline agent as training progresses. We average across all the runs of the same environment, and plot the fraction of times where treatment is above baseline and the standard deviation of that fraction in Figure 2. Appendix A.4 contains per task evaluation curves.

5.3.1 LOWER BOUNDING VS BASELINES SAC/DDPG/HER

Figure 2 compares the lower bounding treatment with SAC, DDPG or HER baseline on 17 sampled Atari games, the FetchEnv tasks and the Pioneer tasks. For all the environments, value target lower bounding is not only more sample efficient, but also enjoys a higher converged performance. After training starts, it quickly gains ground and outperforms the baseline for 70% to 100% of the runs. It keeps that advantage even at the end of the training, outperforming baseline in converged performance. These plots show how frequently treatment is above baseline, but is insensitive to the magnitude of change.

Appendix A.4 shows the magnitude of change with total episode return plotted for each task, often with large gains in sample efficiency and sometimes much higher converged performance. Among all the 22 tasks, only one task (Atari Breakout) shows lb-DR underperforming the baseline.

Investigations show that the loss on Atari Breakout is likely due to the mismatch between training objective and evaluation metric. During training, raw rewards are clipped to [-1, 1] and step discounted at $\gamma = 0.99$ to compute value, while in evaluation, total reward is the unclipped and undiscounted sum of all episode rewards. The discount and clipping together severely penalizes large rewards earned later in the episode, which is what's happening for Breakout, because hitting a top layer block produces a reward of 7 while hitting a bottom layer block produces only 1. When we use non-clipped rewards or a higher γ in training, the lower bounding method performs much better in total reward. Note, this train-test discrepancy as well as an additional training bias (Thomas, 2014) is likely present in all of the prior works using policy gradient methods on Atari games.

    (a) Atari (lb-DR)   (b) Atari (bootstrapped)   (c) FetchEnv   (d) Pioneer

Figure 2: Aggregated evaluation performance: The fraction of times where treatment performs strictly above baseline, plotted along the number of time steps used for training. The solid curve is the sample mean of the fraction across all runs, and the shaded area is +/- one standard deviation. We use, for Atari (lb-DR), 85 runs – 17 games each with 5 seeds, for Atari (bootstrapped), 20 runs – 4 games 5 seeds, for FetchEnv, 9 runs – 3 tasks 3 seeds, and for Pioneer, 6 runs – 2 tasks 3 seeds.

    (a) Atari (lb-DR)   (b) Atari (bootstrapped)   (c) FetchEnv   (d) Pioneer

Figure 3: Average fraction of training experience where lower bounding improves Bellman value target, plotted along the number of iterations of training. The solid curve is the average of the fraction across all runs – number of tasks times number of seeds, and the shaded area is +/- one standard deviation. Other setups are the same as Figure 2.

5.3.2 VALUE TARGET IMPROVEMENT

The lb-DR method is mostly effective, but is it really due to improvements to the value targets? Figure 3 looks at the fraction of training experience where lower bounding actually improves the Bellman value target over the course of training. Overall, improved value target roughly coincides with performance gains. Appendix A.4 shows the plots per each task.

The Appendix also has more results, comparing with baselines such as n-step methods, DDQN and optimality tightening, and more analyses such as ablations and robustness to hyperparameter choices.

6 RELATED WORK

Prior works (Fujita et al., 2020; Hoppe & Toussaint, 2020; He et al., 2017; Oh et al., 2018; Tang, 2020) employed several different ways of computing future returns and using that as a lower bound to improve value learning. It is quite easy to introduce biases and inefficiencies into the process and end up with a suboptimal or inefficient algorithm. Our work is the first to propose the general form of value target lower bounding (possibly with bootstrapping), to show its convergence to the optimal value in the tabular case, and to demonstrate its effectiveness in illustrative examples and extensive experiments on a wide range of tasks.

Fujita et al. (2020)'s method is similar to a special case (the lb-DR+GD variant) of the general method. They used it as a part of a large system and showed that it improved sample efficiency for a robotic grasping task. Hoppe & Toussaint (2020) also bounded the value target. But instead of using empirical return, they used a simplified MDP with a subset of actions. Although without theoretical proof and only experimented on a limited set of robotic manipulation tasks, both works show that

value target lower bounding increased sample efficiency. This work, in addition to the theory and the more general method, shows that lower bounding improves both sample efficiency and converged performance in a wide range of tasks.

He et al. (2017) used empirical return with bootstrap to improve value learning. They formulated value learning as a constrained optimization problem with the empirical bootstrapped value being the lower (and upper) constraints of the value function. In their experiments, the Lagrangian multiplier was fixed, which would likely lead to suboptimal solutions. Our lb-b-$n$step method also uses bootstrapped value. But we lower bound the value target directly, which is simpler, more efficient, and likely more optimal. Our work points out that for episodic tasks, even more efficient and effective methods like lb-DR exist. Appendix A.5 offers more discussion and results related to this.

Our work is subtly but importantly different from the prior works on lower bound Q learning or Self Imitation Learning (SIL) (Oh et al., 2018; Tang, 2020). SIL uses empirical return R to lower bound the value function itself (instead of the *value target*). This is achieved by adding an off policy value loss during on-policy (AC or PPO) training ($L_{value}^{sil} = \frac{1}{2}|v(s) - \max(v(s), R)|^2$). When the value function overestimates, the SIL value loss becomes zero, and keeps overestimating. Mixing the SIL loss with the loss from the baseline algorithms probably helped to correct the overestimation, but no theoretical guarantee was given. In evaluation, SIL was often compared to on-policy Actor Critic or PPO baselines, so it was not clear how much of the gain was due to lower bounding and how much due to off-policy value learning. In this work, we bound the Bellman value target (Equation 11), so overestimates are automatically corrected via Bellman updates, and convergence is guaranteed in the tabular case. We also use off-policy algorithms as baselines for a cleaner comparison.

N-step return methods such as td-lambda (Sutton & Barto, 2018) and Retrace (Munos et al., 2016) also look a few steps ahead, but to obtain more accurate value of the behavior policy. Traditionally, this requires careful off-policy correction, and the value can still be far from the optimal value due to the often suboptimal behavior. This work shows that value target lower bounding efficiently and effectively looks ahead much further without the need for off-policy correction, due to aiming at the optimal value. Appendix A.5 has more detailed observations and discussions.

Planning methods can look into the future to achieve higher value targets and better control. Examples include Monte Carlo Tree Search (MCTS) (Schrittwieser et al., 2019; Ye et al., 2021) and Model Predictive Control (MPC) or receding horizon planning with raw actions (Chua et al., 2018; Hafner et al., 2019; Zhang et al., 2022), options (Silver & Ciosek, 2012), or subgoals (Nasiriany et al., 2019; Nair & Finn, 2020; Chane-Sane et al., 2021). Planning methods use either a dynamics model together with the learned value or just the learned value (in the case of goal conditioned tasks) (Nasiriany et al., 2019) to improve policy or value estimates. Planning typically happens during roll out (Nasiriany et al., 2019), but can also be used to improve the value target, as in Reanalyze of MuZero (Schrittwieser et al., 2019; Ye et al., 2021). During value improvement, if planning takes the maximum over a set of possible future values (e.g. from different trajectories as in the case of MPC), and if this set includes the one step Bellman value target, then the planner is essentially using alternative trajectories and their values to lower bound the Bellman value target. In this sense, the theory developed here can potentially justify and improve Reanalyze. In general, planning is orthogonal to value target lower bounding, and typically requires additional components and a lot more compute than the basic TD learning does. Therefore, we leave it to future work to explore the synergy between the two.

Interestingly, it is common practice to lower and upper bound the returns to the possible region, e.g. Andrychowicz et al. (2017) bounds value between $[-\frac{1}{1-\gamma}, 0]$. Similar to lower bounding with episodic return (Section 3.1), such strict bounds of the actual value can be thought of as admissible heuristics (bounds) used during search of the optimal solution (Russell & Norvig, 2020). What's new in this work is that lower bounding with bootstrapped values (which can overestimate the value) still converges to the optimal value.

Kumar et al. (2020) (DisCor) also recognized that bootstrapped value targets can be inaccurate. This bias impacts learning adversely under function approximation. DisCor uses distribution correction to sample experience with accurate bootstrap targets more frequently, while value target lower bounding aims to directly reduce the bias.

Overall, value target lower bounding is a simple (no hyperparameters), efficient, highly effective, and theoretically justified approach. A similar prior work to compare would be Hindsight Experi-

ence Replay (HER) (Andrychowicz et al., 2017), which is simple, effective, efficient, and relies on replaying past experience as well. HER works best in sparse reward goal conditioned tasks. Unlike our work, HER additionally requires the task to be goal conditioned, requires full knowledge of the reward function, has a hyperparameter to tune (the proportion of hindsight experience), and gives no theoretical justification. Our work employs an orthogonal way (value target lower bounding) to improve RL training, therefore provides additional gains even when applied on top of HER, as shown in the experiments on hard continuous control tasks.

7 CONCLUSIONS

We propose a general form of lower bounding the value target using possibly bootstrapped return. In theory, value target lower bounding converges to the same optimal solution as the original Bellman operator. In practice, several ways of finding value lower bounds are examined, and can be readily integrated into any TD learning based RL algorithm, such as DQN, DDPG, SAC, etc..

For episodic tasks, discounted episodic return lower bound is efficient and effective, achieving much higher sample efficiency and converged performance than one-step baselines such as SAC, DDPG or TD3 in most tasks, and is competitive among n-step baselines. For goal conditioned tasks, simple goal distance based return achieves large gains over Hindsight experience relabeling (HER) in difficult long horizon tasks.

For non-episodic tasks or in general, lower bounding with n-step bootstrapped return outperforms one-step baselines and is a strong competitor to the n-step methods such as (truncated) td-lambda and Retrace.

7.1 FUTURE WORK

There could be better value lower bounds that improve training even more. One such direction is to use planning (e.g. Monte Carlo Tree Search, the Cross Entropy Method or using subgoals) to achieve tighter lower bounds with the help of a model of the task.

Other ways of bounding the value target, e.g. upper bounding (He et al., 2017), may be worth investigating as well, e.g. to reduce overestimation in regions of poor reward.

ETHICS STATEMENT

This research belongs to basic reinforcement learning, accelerating the training of reinforcement learning algorithms. Helpful agents trained on benevolent tasks will learn faster, so will malicious agents trained to do damage. All the usual societal impact of reinforcement learning algorithms apply. The reader and user has to use caution and their own judgments when applying these automation algorithms to the real world: careful testing and scaling is needed, starting from virtual simulations, to testing in a lab environment, to small scale real world tests, and eventually to full scale deployment with careful monitoring in place.

REPRODUCIBILITY STATEMENT

Our code change is based on a publicly available RL library, with strong baselines already implemented. Our relatively small code change is committed to a private github repository, which we plan to open source upon publication. Experiment parameters are configured and controlled by an automation script, with each experiment label corresponding to the set of configurations used for that experiment, so there is little room for manual error when running many experiments across different tasks, methods and hyperparameters. When running experiments, the snapshot of the code used to run each experiment is stored together with the results for verification.

Experiments are done in simulation with pseudo randomness. We've run our code on different machines with different GPU hardware using the same docker image, and the results are reproducible up to every float number using the same random seed. In a few cases, we've also run our code on different versions of hardware and software (CUDA and pytorch), and the results are similar, though not the same at the float number level.

ACKNOWLEDGMENTS

Use unnumbered third level headings for the acknowledgments. All acknowledgments, including those to funding agencies, go at the end of the paper.

REFERENCES

Marcin Andrychowicz, Dwight Crow, Alex Ray, Jonas Schneider, Rachel Fong, Peter Welinder, Bob McGrew, Josh Tobin, Pieter Abbeel, and Wojciech Zaremba. Hindsight experience replay. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 5048–5058, 2017. URL https://proceedings.neurips.cc/paper/2017/hash/453fadbd8a1a3af50a9df4df899537b5-Abstract.html.

Richard Bellman. *Dynamic Programming*. Princeton Univ. Press, Princeton, NJ, USA, 1957. ISBN 0-691-07951-X.

Elliot Chane-Sane, Cordelia Schmid, and Ivan Laptev. Goal-conditioned reinforcement learning with imagined subgoals. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 1430–1440. PMLR, 18–24 Jul 2021. URL https://proceedings.mlr.press/v139/chane-sane21a.html.

Kurtland Chua, Roberto Calandra, Rowan McAllister, and Sergey Levine. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, NIPS'18, pp. 4759–4770, Red Hook, NY, USA, 2018. Curran Associates Inc.

Eric V. Denardo. Contraction mappings in the theory underlying dynamic programming. *SIAM Review*, 9(2):165–177, 1967. ISSN 00361445. URL http://www.jstor.org/stable/2027440.

Scott Fujimoto, Herke van Hoof, and David Meger. Addressing function approximation error in actor-critic methods. *CoRR*, 2018. URL http://arxiv.org/abs/1802.09477.

Yasuhiro Fujita, Kota Uenishi, Avinash Ummadisingu, Prabhat Nagarajan, Shimpei Masuda, and Mario Castro. Distributed reinforcement learning of targeted grasping with active vision for mobile manipulators. In *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 9712–9719, Oct 2020.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 1861–1870. PMLR, 10–15 Jul 2018. URL https://proceedings.mlr.press/v80/haarnoja18b.html.

Danijar Hafner, Timothy Lillicrap, Ian Fischer, Ruben Villegas, David Ha, Honglak Lee, and James Davidson. Learning latent dynamics for planning from pixels. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2555–2565. PMLR, 09–15 Jun 2019. URL https://proceedings.mlr.press/v97/hafner19a.html.

Frank S. He, Yang Liu, Alexander G. Schwing, and Jian Peng. Learning to play in a day: Faster deep reinforcement learning by optimality tightening. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. URL https://openreview.net/forum?id=rJ8Je4clg.

Sabrina Hoppe and Marc Toussaint. Qgraph-bounded q-learning: Stabilizing model-free off-policy deep reinforcement learning. *CoRR*, abs/2007.07582, 2020. URL https://arxiv.org/abs/2007.07582.

Aviral Kumar, Abhishek Gupta, and Sergey Levine. Discor: Corrective feedback in reinforcement learning via distribution correction. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 18560–18572. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/d7f426ccbc6db7e235c57958c21c5dfa-Paper.pdf.

Sameera Lanka and Tianfu Wu. Archer: Aggressive rewards to counter bias in hindsight experience replay. *NeurIPS 2018 Deep Reinforcement Learning Workshop*, 2018. URL https://arxiv.org/abs/1809.02070.

Timothy P. Lillicrap, Jonathan J. Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In Yoshua Bengio and Yann LeCun (eds.), *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*, 2016. URL http://arxiv.org/abs/1509.02971.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin A. Riedmiller. Playing atari with deep reinforcement learning. *CoRR*, abs/1312.5602, 2013. URL http://arxiv.org/abs/1312.5602.

Rémi Munos, Tom Stepleton, Anna Harutyunyan, and Marc G. Bellemare. Safe and efficient off-policy reinforcement learning. In Daniel D. Lee, Masashi Sugiyama, Ulrike von Luxburg, Isabelle Guyon, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, pp. 1046–1054, 2016. URL https://proceedings.neurips.cc/paper/2016/hash/c3992e9a68c5ae12bd18488bc579b30d-Abstract.html.

Suraj Nair and Chelsea Finn. Hierarchical foresight: Self-supervised learning of long-horizon tasks via visual subgoal generation. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=H1gzR2VKDH.

Soroush Nasiriany, Vitchyr Pong, Steven Lin, and Sergey Levine. Planning with goal-conditioned policies. *Advances in Neural Information Processing Systems*, 2019.

Junhyuk Oh, Yijie Guo, Satinder Singh, and Honglak Lee. Self-imitation learning. *CoRR*, abs/1806.05635, 2018. URL http://arxiv.org/abs/1806.05635.

Matthias Plappert, Marcin Andrychowicz, Alex Ray, Bob McGrew, Bowen Baker, Glenn Powell, Jonas Schneider, Josh Tobin, Maciek Chociej, Peter Welinder, Vikash Kumar, and Wojciech Zaremba. Multi-goal reinforcement learning: Challenging robotics environments and request for research. *CoRR*, abs/1802.09464, 2018. URL http://arxiv.org/abs/1802.09464.

Stuart J. Russell and Peter Norvig. *Artificial Intelligence: A Modern Approach (4th Edition)*. Pearson, 2020. ISBN 9780134610993. URL http://aima.cs.berkeley.edu/.

Julian Schrittwieser, Ioannis Antonoglou, Thomas Hubert, Karen Simonyan, Laurent Sifre, Simon Schmitt, Arthur Guez, Edward Lockhart, Demis Hassabis, Thore Graepel, Timothy P. Lillicrap, and David Silver. Mastering atari, go, chess and shogi by planning with a learned model. *CoRR*, abs/1911.08265, 2019. URL http://arxiv.org/abs/1911.08265.

David Silver and Kamil Ciosek. Compositional Planning Using Optimal Option Models. In *Proceedings of the 29th International Conference on Machine Learning*, pp. 165. icml.cc / Omnipress, 2012.

Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. A Bradford Book, Cambridge, MA, USA, 2018. ISBN 0262039249.

Yunhao Tang. Self-imitation learning via generalized lower bound q-learning. *CoRR*, abs/2006.07442, 2020. URL https://arxiv.org/abs/2006.07442.

Philip Thomas. Bias in natural actor-critic algorithms. In Eric P. Xing and Tony Jebara (eds.), *Proceedings of the 31st International Conference on Machine Learning*, volume 32 of *Proceedings of Machine Learning Research*, pp. 441–448, Bejing, China, 22–24 Jun 2014. PMLR. URL https://proceedings.mlr.press/v32/thomas14.html.

Hado van Hasselt, Arthur Guez, and David Silver. Deep reinforcement learning with double q-learning. *CoRR*, abs/1509.06461, 2015. URL http://arxiv.org/abs/1509.06461.

Weirui Ye, Shaohuai Liu, Thanard Kurutach, Pieter Abbeel, and Yang Gao. Mastering atari games with limited data. *CoRR*, abs/2111.00210, 2021. URL https://arxiv.org/abs/2111.00210.

Haichao Zhang, Wei Xu, and Haonan Yu. Generative planning for temporally coordinated exploration in reinforcement learning. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=YZHES8wIdE.

A   APPENDIX

A.1   PROOFS

Before going on to Theorem 2.3, we first prove the easier Corollary 2.4.

We want to show that given a lower bound of the optimal value, $\forall s, f(s) \leq \mathcal{B}^\infty(v)(s)$, under the new operator $\mathcal{B}_f$, the value function converges to the same optimal value function given by the Bellman operator $\mathcal{B}$.

Proof. Let v^* be the fixed point and optimal value of the original Bellman operator: $v^* := \mathcal{B}^\infty(v)$, v be any value function, and s any state.

First, for the simple case of $\forall s$, where $f(s) \leq \mathcal{B}(v)(s)$, the new operator backs off to the Bellman operator, and follows the convergence of the Bellman operator:

$$
\begin{aligned}
&|\mathcal{B}_f(v)(s) - v^*(s)| \\
=&|\max(\mathcal{B}(v)(s), f(s)) - v^*(s)| \\
=&|\mathcal{B}(v)(s) - v^*(s)| \\
=&|\mathcal{B}(v)(s) - \mathcal{B}(v^*)(s)| \\
\leq&\gamma||v - v^*||_\infty
\end{aligned}
$$

Second, $\forall s$, where $f(s) > \mathcal{B}(v)(s)$,

$$
\begin{aligned}
&|\mathcal{B}_f(v)(s) - v^*(s)| \\
=&|\max(\mathcal{B}(v)(s), f(s)) - v^*(s)| \\
=&|f(s) - v^*(s)| \\
=&v^*(s) - f(s) \quad \text{(because } f \text{ lower bounds } v^* : v^*(s) \geq f(s)) \\
<&v^*(s) - \mathcal{B}(v)(s) \quad \text{(because } f(s) > B(v)(s)) \\
=&|\mathcal{B}(v)(s) - v^*(s)| \\
\leq&|\mathcal{B}(v)(s) - v^*(s)| \\
=&|\mathcal{B}(v)(s) - \mathcal{B}(v^*)(s)| \\
\leq&\gamma||v - v^*||_\infty
\end{aligned}
$$

Therefore, the distance to the optimal value shrinks by γ with every application of $\mathcal{B}_f$:

$||\mathcal{B}_f(v) - v^*||_\infty = \max_s |\mathcal{B}_f(v)(s) - v^*(s)| \leq \gamma||v - v^*||_\infty$.

According to the definition of convergence to v^*, we need to find an N, such that $\forall \epsilon > 0, \forall v \neq v^*$, $\forall n > N, ||\mathcal{B}_f^n(v) - v^*||_\infty < \epsilon$.

We can easily calculate that any $N \geq \log_\gamma \frac{\epsilon}{||v-v^*||_\infty}$ (note, $\gamma < 1$) satisfies the condition, which concludes the proof that any value function v will converge to v^* under the lower bounded Bellman operator $\mathcal{B}_f$. □

Note, from the proof above, we can see that $\mathcal{B}_f$ converges faster than γ (the speed of Bellman contraction), when the lower bound is strictly above the Bellman value target, i.e. $f(s) > \mathcal{B}(v)(s)$.

Now for Theorem 2.3: given the maximum achievable value $\bar{G}^v(s)$ and given that $f(s) \le \bar{G}^v(s)$, we want to show convergence to the optimal value.

Proof. First, $\forall s$, where $f(s) < \mathcal{B}(v)(s)$, the value target backs off to the original Bellman target, and the distance to the optimal value shrinks at rate γ.

Second, $\forall s$, where $f(s) < v^*(s)$, it follows from Corollary 2.4 that the distance to the optimal value shrinks at rate γ.

Last, we only need to prove for any s, where $f(s) \ge v^*(s)$ and $f(s) \ge \mathcal{B}(v)(s)$, the distance to the optimal value still shrinks:

$$|\mathcal{B}_f(v)(s) - v^*(s)|$$
$$=|\max(\mathcal{B}(v)(s), f(s)) - v^*(s)|$$
$$=|f(s) - v^*(s)|$$
$$=f(s) - v^*(s)$$
$$\le\bar{G}^v(s) - v^*(s)$$

According to the definition of $\bar{G}^v$ in Equation 3 of the main text:

$$= \max_{\pi \in \Pi, n \in [1,+\infty)} G_n^{\pi,v}(s) - v^*(s)$$

Now suppose π' and $n(s)$ achieves the maximum bootstrapped value $\bar{G}^v(s)$:

$$=G_{n(s)}^{\pi',v}(s) - v^*(s)$$

According to the definition of n-step bootstrapped value $G_n^{\pi,v}(s)$ in Equation 2 of the main text:

$$=\mathbb{E}^{\pi'}\{r_1 + \gamma r_2 + ... + \gamma^{n(s)-1} r_{n(s)} + \gamma^{n(s)} v(s_{n(s)})\} - v^*(s)$$

(The expectation above is over all possible $n(s)$-step trajectories of the given policy π' and MDP.)

Suppose π^* is the optimal policy, which achieves maximum value v^* for any number of steps n and state s:

$$=\mathbb{E}^{\pi'}\{r_1 + \gamma r_2 + ... + \gamma^{n(s)-1} r_{n(s)} + \gamma^{n(s)} v(s_{n(s)})\}-$$
$$\mathbb{E}^{\pi^*}\{r_1 + \gamma r_2 + ... + \gamma^{n(s)-1} r_{n(s)} + \gamma^{n(s)} v^*(s_{n(s)})\}$$
$$\le\mathbb{E}^{\pi'}\{r_1 + \gamma r_2 + ... + \gamma^{n(s)-1} r_{n(s)} + \gamma^{n(s)} v(s_{n(s)})\}-$$
$$\mathbb{E}^{\pi'}\{r_1 + \gamma r_2 + ... + \gamma^{n(s)-1} r_{n(s)} + \gamma^{n(s)} v^*(s_{n(s)})\}$$

(This is because π^* maximizes the expected n-step bootstrapped value. So the expected value of any other policy, e.g. π', bootstrapped with v^* cannot be greater.)

$$=\gamma^{n(s)}\mathbb{E}^{\pi'}\{v(s_{n(s)}) - v^*(s_{n(s)})\}$$
$$\le\gamma^{n(s)}\mathbb{E}^{\pi'}|v(s_{n(s)}) - v^*(s_{n(s)})|$$
$$=\gamma^{n(s)}\sum_{s_{n(s)}}\{p^{\pi'}(s_{n(s)}|s) \times |v(s_{n(s)}) - v^*(s_{n(s)})|\}$$
$$\le\gamma^{n(s)}\max_s |v(s) - v^*(s)|$$
$$\le\gamma^{\min_s n(s)}\max_s |v(s) - v^*(s)|$$
$$=\gamma^{\min_s n(s)}||v - v^*||_\infty$$

This means in the case of overestimated bootstrap values, the new operator promises to shrink at a rate of $\gamma^{\min_s n(s)}$, and overall, the new operator will at least shrink at a rate of γ. □

Note, from the proof above, we can see that when the lower bound overestimates, i.e. $f(s) \ge v^*(s)$, $\mathcal{B}_f$ converges at a speed of $\gamma^{\min_s n(s)}$, which could be faster than γ, the speed of Bellman contraction.

These proofs work for stochastic MDPs, because we treat trajectory rewards and states as random variables conditioned on the MDP and the policy. The proofs work for action values as well, by simply replacing the value function above $v(s)$ with the action value $q(s, a)$, and the value lower bound $f(s)$ with the action value lower bound $f(s, a)$.

π' in theory can be different for different state s, so that when unrolling from state s_0 for a few steps into s_i, it still follows $\pi'(s_0)$, instead of $\pi'(s_i)$. However, it's easy to prove (by contradiction) that there exists a single policy π' which achieves the maximum achievable value (as long as ties are split deterministically).

A.2 EXPERIMENT SETUPS

We experiment on three sets of tasks with different input characteristics and control difficulty. Some of the tasks are not goal conditioned, so only lower bounding with empirical discounted return is available. Some of them are goal conditioned, so both empirical discounted return and hindsight relabeling with discounted goal return as lower bound are available.

A.2.1 ATARI GAMES

We experiment on the classical Atari games with image input to test using discounted episodic return to lower bound value target. We picked the popular games Breakout, Seaquest, Space Invaders (these three were used for hyperparameter tuning by Mnih et al. (2013)), Atlantis, Frostbite and Q*bert (these three were highlighted in (He et al., 2017)), and randomly sampled another 11 games from the total 56. As with prior work (Mnih et al., 2013; Oh et al., 2018), we evaluate on the standard NoFrameskip-v4 versions of the games with actions repeated for a fixed four frames and each game started with up to 30 random noop steps before handing to the agent. Each episode of the games is capped at 10,000 time steps, with the last time step having discount 0.99 when the time limit is reached, i.e. resetting the game without ending the episode. For a regular game end after losing all lives, the episode ends, i.e. last step discount is 0. Because the games are episodic, both lb-DR and lb-b-$n$step methods can be applied.

A.2.2 FETCH PUSH, SLIDE AND PICKANDPLACE

The FetchEnv tasks (Plappert et al., 2018) are goal conditioned tasks with a robotic arm moving objects on a table. Robot states and object position serve as input. The agent outputs continuous actions taking the form of relative positions to move to. A PID controller translates the relative position actions into the exact torque applied at each joint. Rewards are sparse and goal-conditioned, with -1 for non-goal states and 0 for goal states.

By default the FetchEnv tasks are non-episodic. They reset every 50 steps, but all steps including the step right before task reset have the same positive discount (Andrychowicz et al., 2017). As explained in Section 3.1, to use episodic discounted return as lower bound, we can make them episodic by adding a gym wrapper around the environment to end an episode after its goal is achieved, and reset the task. When a goal is not reached within 50 steps, we just reset the task without ending the episode, as is done in the original FetchEnv, and such experience is not used in value target lower bounding.[3] This also changes the nature of the tasks, so the agent does not have to stay at the goal state indefinitely, but instead only needs to reach the goal position as fast as possible. This makes the episodic FetchEnv tasks slightly easier to train than the original tasks, because the agent only needs to reach the goal state quickly, instead of having to reach and stay at the goal position indefinitely. (There are ways to avoid changing the desired behavior by e.g. including agent's speed into the goal state or requiring the agent to stay at the goal position for several time steps before ending the episode. This seems orthogonal to the main idea here, and is not included in this work.)

We experiment on both the original/non-episodic FetchEnv tasks (with lb-b-$n$step methods) and the episodic FetchEnv tasks (with lb-DR and lb-GD methods).

---

[3]Fujita et al. (2020) chose to end episodes when either a maximum of T time steps is reached or the goal is reached, and provided the agent with the number of timesteps since episode start as input to the agent, so that the agent is aware of the approaching episode end.

Compared with the Atari games, the inputs are simpler, no longer image based, but the control task is continuous, under realistic physical simulation and harder.

A.2.3   PIONEER PUSH AND REACH TASKS

Figure 4: The Pioneer Push task and the Push and Reach task.

This is a set of challenging goal reaching and object pushing tasks for the physically simulated car Pioneer 2dx. The car is 0.4 meter long. Objects and goal positions are randomly initialized between 0.5 meter to 1 meter of each other inside a 10 meter by 10 meter flat space. Inputs are the car and object states and the goal positions, and actions are the forces applied on the two driving wheels.

For the Pioneer Push task, the car has to push a block to within 0.5 meter of the 2 dimensional goal position indicated by a small red dot on the ground. For the Pioneer Push and Reach task, the car has to first push the object to the goal location (red dot) and then drive to a separate goal position (red ball in the air); the goal is achieved when the concatenation of the two goal locations (for Push and for Reach) is within 0.5 of the concatenated achieved positions (of the block and the car) in L_2-distance.

These tasks are episodic with sparse goal reward, and we only test the lb-GD and lb-DR+GD methods on them with HER as baseline. (TD3 without HER takes too long to train.)

These tasks take longer time to accomplish, and also take longer time to train than the FetchEnv tasks. Some of the reasons are the force based wheel control instead of the higher level position control, and the arena space being much larger than just a tabletop.

A.3   HYPERPARAMETERS

Table 1 lists the hyperparameters of the baseline algorithms. For FetchEnv, they follow published work (Plappert et al., 2018). For Atari and Pioneer tasks, they are tuned using one set of random seeds and after keeping the hyperparameters fixed, trained with a different set of random seeds and evaluated. Value target lower bounding has no parameter, and we did not re-tune any parameters of the baseline RL algorithms for value target lower bounding. When comparing lb-b-$n$step methods with other n-step methods, we simply use the same n as the other baselines.

For the Atari games, the original DQN setup with only one training environment takes too long to train so we decided to tune SAC as baseline and found it to outperform published Actor-Critic results (Oh et al., 2018) and our tuned DDQN (results in Appendix A.6).

For Pioneer Push and PushReach tasks, TD3 is used, (we simply equip DDPG with two critics for clipped double Q learning (Fujimoto et al., 2018)), which works better than DDPG with one critic.

Table 1: Hyperparameters for all the tasks

Hyperparameters\Tasks	Atari (SAC)	FetchEnv (DDPG)	Pioneer (TD3)
Parallel environments	30	38	30
Unrolls per train iteration	8	50	100
Updates per train iteration	4	40	40
Mini-batch size	500	5,000	5,000
Training updates per target network update	20	40	40
Target update weight	0.95	0.95	0.95
Discount per time step	0.99	0.98	0.99
Initial collect steps	100,000	10,000	10,000
Total training time steps	12 million (x4 environment frames)	2 million	Push: 5 million, PushReach: 14 mil
Max steps before task reset	10,000	50	Push: 100, PushReach: 200
Replay buffer size	1 million	2 million	6 million
Adam optimizer learn rate[a]	$5e^{-4}$	$1e^{-3}$	$1e^{-3}$
Network structure	conv((32, 8, 4), (64, 4, 2), (64, 3, 1)) + fc(512)[b]	fc(256, 256, 256)	fc(256, 256, 256)
Number of critics	2	1	2
ϵ-greedy for evaluation	0.05	0.3	0.3
Evaluation interval in train iters	1000	40	200
Evaluation episodes	100	200	100
Life loss as terminal[c]	Yes	n/a	n/a
Action repeat	4	n/a	n/a
Image scaling	[-1, 1]	n/a	n/a
Frame stacking	4	n/a	n/a
Reward clipping	[-1, 1]	n/a	n/a
SAC target entropy	calculated[d]	n/a	n/a
Hindsight percentage	n/a	80%	50%
Observation normalization[e]	No	Yes	No
TD-lambda: λ	0.95	0.95	n/a
n-step bootstrap: n	3	2	n/a

[a] Adam $\hat{\epsilon} = 1e^{-7}$ for all tasks.

[b] Netowrk structure for Atari follows DDQN (van Hasselt et al., 2015).

[c] Life loss in Atari games is treated as a terminal state in training, following EfficientZero (Ye et al., 2021).

[d] The SAC target entropy is set to the entropy of uniformly distributing 0.1 probability mass across all but one actions.

[e] Observations are normalized to have zero mean and unit variance based on the statistics of the training observations, and we found the normalization to be critical in reproducing HER results on FetchEnv.

A.4 RESULTS

Applying lower bounding (e.g. lb-DR) on different baseline algorithms e.g. DDPG or SAC results in different treatment methods. Since we always compare treatment with its corresponding baseline, throughout the paper, we simply call the treatment lb-DR etc. without mentioning the baseline algorithm.

A.4.1 LB-DR (EPISODIC RETURN) VS BASELINE SAC/DDPG

Figure 5 compares lower bounding with discounted return (lb-DR) against SAC or DDPG baseline on 17 sampled Atari games and the episodic FetchEnv tasks.

For 16 out of the 17 Atari games, lower bounding with episodic discounted return (lb-DR) performs at least as well as the baseline, often much better. On more than half of the Atari games and on the Fetch PickAndPlace task, there are large gains in both sample efficiency and final performance. On FetchPush and a few of the Atari games (Alien, Bank Heist and Fishing Derby), there is about 70% sample efficiency gain with similar converged performance. Among all the 20 tasks, only 1 task (Atari Breakout) shows lb-DR underperforming the baseline.

A.4.1.1 Value learning plots

This section presents plots of learned value and how often value is improved by the proposed methods, in order to show the effect of lower bounding on value improvement.

Figure 6 shows the fraction of training experience where lb-DR value target is greater than the Bellman target from SAC/DDPG on the 17 Atari games and the episodic FetchEnv tasks (without hindsight). They correlate well with actual performance (Figure 5) and with how value is learning (Figure 7).

Figure 5: Evaluated average return of value target lower bounding with discounted return (lb-DR) vs SAC or DDPG on Atari games and episodic FetchEnv tasks. Solid curves are the mean across five (for Atari) or three (others) seeds, and shaded areas are +/- one standard deviation.

Figure 6: Fraction of training experience where lb-DR value target is greater than the Bellman target, on Atari games and episodic FetchEnv tasks, plotted against the number of training iterations. Solid curves are the mean across five (for Atari) or three (others) seeds, and shaded areas are +/- one standard deviation.

Figure 7: Learned values of lb-DR and SAC (for Atari games) and DDPG (for FetchEnv tasks), evaluated on the training experience and plotted against the number of training iterations. Solid curves are the mean across five (for Atari) or three (others) seeds, and shaded areas are +/- one standard deviation.

(a) FetchPush (b) FetchSlide (c) PickAndPlace

(d) PioneerPush (e) PushReach

Figure 8: Value target lower bounding with goal distance return (lb-GD) and lb-DR+GD vs HER on episodic FetchEnv and Pioneer tasks. Solid curves are the mean across three seeds, and shaded areas are +/- one standard deviation.

A.4.2   LB-GD (GOAL DISTANCE RETURN) AND LB-DR+GD VS HER

Figure 8 compares lower bounding with goal distance return (lb-GD) and lower bounding with both goal distance and discounted return combined (lb-DR+GD) against the much stronger HER baseline, on the goal conditioned episodic FetchEnv and Pioneer tasks.

On the easier FetchEnv tasks, lower bounding is similar as HER, but on the more challenging Pioneer Push and Reach tasks, lower bounding is able to achieve over 70% more sample efficiency. It seems the harder the task, the wider the margin of gain.

A.4.2.1   Value learning plots

This section presents plots of learned value and how often value is improved by the proposed methods, in order to show the effect of lower bounding on value improvement.

Figure 9 shows the fraction of training experience where the lb-GD is higher than the Bellman value target from HER, in the goal conditioned (episodic FetchEnv and Pioneer) tasks, and the learned value. It seems, for FetchEnv tasks, where lb-GD only performs slightly better than HER, the fraction of experience with improved value target is quite small (less than 1%). Hindsight relabeling is probably already producing fairly high value targets. For Pioneer Push and Reach tasks, lb-GD performs much better in average return, and the fraction of experience with higher value target is also much larger (peaking around 2-8%).

Figure 9: Fraction of training experience where lb-GD or lb-DR+GD value target is greater than the Bellman target (a-e) and learned values (f-j), on episodic FetchEnv and Pioneer tasks, plotted against the number of training iterations. Solid curves are the mean across three seeds, and shaded areas are +/- one standard deviation.

(a) Atari Breakout   (b) Atari Seaquest   (c) Atari Frostbite

(d) Atari Q*bert   (e) FetchPush   (f) PickAndPlace

Figure 10: Evaluated average return of value target lower bounding with n-step bootstrapped return (lb-b-$n$step) vs SAC or DDPG, td-lambda, Retrace and optimality-tightening on Atari games and the original/non-episodic FetchEnv tasks. $n = 3$ for Atari and 2 for FetchEnv tasks. Solid curves are the mean across five (for Atari) or three (others) seeds; shaded areas are +/- one standard deviation.

A.4.3 N-STEP BOOTSTRAPPED METHODS

Figure 10 shows performance of lb-b-$n$step methods on a subset of the Atari games (episodic) and the original (non-episodic) FetchEnv tasks. Besides SAC/DDPG, baselines also include n-step methods such as td-lambda, Retrace (Munos et al., 2016) and optimality tightening (He et al., 2017). lb-b-$n$step methods are at least as good as the best baseline method, and clearly outperforms the baselines in two of the six tasks.

A.4.3.1 Value learning plots

Figure 11 shows the fraction of experience where lb-b-$n$step lower bounds are above one step Bellman value targets. There seems to be a correlation between improving the value target over more experience and actually improving the policy, at least for FetchEnv tasks. The correlation does not seem as clear as that of lb-DR. With bootstrapping, the fractions are generally higher than those of lb-DR in Figure 6, potentially due to overestimated bootstrap values.

A.4.4 N-STEP METHOD ABLATIONS

The following three sections include ablations which show the lower bounding methods to be robust to variations in the hyperparameters.

A.4.4.1 lb-b-$n$step with different n (number of steps)

Figure 12 shows the effect of how the number of steps n in n-step bootstrapped return impacts lower bounding performance. The lb-b-$n$step method is not very sensitive to the value n, typically, the higher the value n the better the performance, while n-step methods like td-lambda or Retrace would degrade a lot as n increases above 3 or 4. We also observe lower value overestimation as n increases (Figure 16).

Figure 11: Fraction of training experience where lb-b-$n$step value target or optimality-tightening lower bound is greater than the value target of baselines SAC (for Atari games) and DDPG (for FetchEnv tasks), plotted against the number of training iterations. Solid curves are the mean across five (for Atari) or three (others) seeds, and shaded areas are +/- one standard deviation.

A.4.4.2   lb-b-$n$step vs lb-b-$n$step-only (only n-th step)

Figure 13 shows the effect of taking a maximum of all 2- to n-step bootstrapped returns versus only using the n-step bootstrapped return. It seems using the maximum bootstrapped return of all 2- to n-steps, hence a tighter lower bound, works better than only using the n-step return.

A.4.4.3   lb-b-$n$step (bootstrap) or lb-DR (episodic return)

In continuing tasks (with negative rewards), we have to use the bootstrapped lb-b-$n$step method. But for episodic tasks, should we use bootstrapped return or episodic return as value target lower bound? In theory, lb-b-$n$step-only becomes lb-DR when n is large enough. In practice, in terms of effectiveness, we can compare lb-b-$n$step with lb-DR on the Atari games (Figure 10 and 5 respectively). lb-b-$n$step is better than lb-DR on Atari Breakout. On Seaquest, the two are similar. On the other two games: Frostbite and Q*bert, episodic return is better. It seems lb-DR is better on tasks where rewards are more sparse and longer term planning is needed. In terms of efficiency, as n becomes larger, the memory and compute efficient lb-DR method will become more attractive. Overall, both methods show a clear advantage over the baselines.

A.4.4.4   Value learning plots

Figure 14 shows the fraction of experience where lb-b-$n$step lower bounds are above one step Bellman value targets.

Figures 15 and 16 show the learned value of the lb-b-$n$step and lb-b-$n$step-only methods. It's convenient to look at the FetchEnv tasks which should always have non-positive value. From Figure 16(a,b), it seems as n increases, value decreases, maybe due to more accurate estimates of value. From Figure 16(c,d), it seems the tighter lower bounds of lb-b-$n$step method do lead to slightly more overestimation in value.

(a) FetchPush   (b) PickAndPlace

Figure 12: Evaluated average return of value target lower bounding with n-step bootstrapped return (lb-b-$n$step) with different n on the original/non-episodic FetchEnv tasks. Solid curves are the mean across three seeds, and shaded areas are +/- one standard deviation.

(a) FetchPush   (b) PickAndPlace

Figure 13: Evaluated average return of value target lower bounding with all n-step bootstrap (lb-b-$n$step) and nth-step only (lb-b-$n$step-only) on the original/non-episodic FetchEnv tasks. Solid curves are the mean across three seeds, and shaded areas are +/- one standard deviation.

(a) FetchPush   (b) FetchPickAndPlace   (c) FetchPush   (d) FetchPickAndPlace

Figure 14: Fraction of training experience where lb-b-$n$step or lb-b-$n$step-only improves over the baseline Bellman value target, evaluated on the training experience and plotted against the number of training iterations. Solid curves are the mean across three seeds, and shaded areas are +/- one standard deviation.

Figure 15: Learned values of lb-b-$n$step and SAC (for Atari games), DDPG (for FetchEnv tasks), optimality-tightening, td-lambda and Retrace, evaluated on the training experience and plotted against the number of training iterations. Solid curves are the mean across five (for Atari) or three (others) seeds, and shaded areas are +/- one standard deviation.

Figure 16: Learned values of lb-b-$n$step, lb-b-$n$step-only, DDPG (for FetchEnv tasks), optimality-tightening, td-lambda and Retrace, evaluated on the training experience and plotted against the number of training iterations. Solid curves are the mean across three seeds, and shaded areas are +/- one standard deviation.

A.5   N-STEP RETURN BASED METHODS

A.5.1   N-STEP RETURN METHODS

lb-b-$n$step methods and n-step return methods are similar in their data and computation requirements, and we already compare their performance in Figure 10.

Here, we additionally compare lb-DR directly with n-step methods in Figure 17.

(a) Atari Breakout   (b) Atari Seaquest   (c) Atari Frostbite

(d) Atari Q*bert   (e) FetchPush   (f) FetchPickAndPlace

Figure 17: Evaluated average return of value target lower bounding with discounted return (lb-DR) vs SAC or DDPG, td-lambda and Retrace on four Atari games and the episodic FetchEnv tasks. Solid curves are the mean across five (for Atari) or three (others) seeds, and shaded areas are +/- one standard deviation.

During experimentation, we found that n-step methods are typically harder to tune and more expensive to compute.

1) Tuning n: A small n for n-step methods works similarly as the baseline one-step method, and a larger n hurts performance. This is likely due to the off-policy bias in n-step return causing the n-step estimate to be potentially worse than the one-step estimate. Introducing importance sampling weights (Retrace) would help reduce the bias, but at the same time significantly downweight the off-policy high return experiences, making an ineffective use of such experiences.

None of these issues exist in value target lower bounding: (a) It does not incur any off-policy bias, and (b) as long as an experience renders high reward, being off-policy does not affect its ability to improve the value target.

2) Tuning involves other hyperparameters like the td-lambda parameter, replay buffer size, prioritized replay (to potentially expire old experiences and sample recent ones more frequently), target network update parameters (to reduce potential overestimation), and parameters for importance sampling. But still, after all the tuning, it only slightly outperforms one-step DDPG on FetchEnv or SAC on Atari games, and is often below the lower bounding methods. For td-lambda and Retrace, the best performance comes from 2-step (for FetchEnv) or 3-step (for Atari) td with $\lambda = 0.95$, all other parameters the same as the baseline DDPG or SAC. Retrace underperforming the baseline in Breakout and Frostbite is similarly observed in the original paper (Munos et al., 2016).

Figure 18: Learned values of lb-DR and SAC (for Atari games), DDPG (for FetchEnv tasks), td-lambda and Retrace, evaluated on the training experience and plotted against the number of training iterations. Solid curves are the mean across five (for Atari) or three (others) seeds, and shaded areas are +/- one standard deviation.

On the other hand, value target lower bounding with episodic return requires no hyperparameter tuning, (lb-b-$n$step with bootstrapping is not very sensitive to the choice of n), and learns faster on most tasks and converges higher on many tasks.

3) Computing n-step td-lambda return requires more computation due to evaluating value networks on all n-steps of the experience. It limits how large n can be due to GPU memory limits, and slows down training time significantly with a large n.

On the other hand, value target lower bounding precomputes and stores episodic discounted return in the replay buffer, and incurs very little additional computation.

Overall, n-step methods are much more expensive and difficult to use, and the much simpler and effective lower bounding methods maintain an advantage in both effectiveness and efficiency. We show the performance comparison in Figure 17 with learned values in Figure 18.

A.5.2 OPTIMALITY TIGHTENING WITH N-STEP RETURNS

He et al. (2017) use bootstrapped n-step return to lower and upper bound the value during training. They frame the problem as a constrained optimization problem where the distance between the value and the Bellman value target is minimized subject to the constraints that the value function must be within the lower (and upper) bounds. This is similar to our lb-b-$n$step method, except instead of applying a constraint on the value, we use the bootstrapped return to directly lower bound and improve the value target, which is likely more optimal and more efficient. In their experiments, the Lagrangian multiplier was fixed, which would likely lead to suboptimal solutions, and no theoretical guarantee was given. For episodic tasks, even more efficient and effective methods like lb-DR exist.

Some detailed differences:

1) The prior work bounds the value function itself (similar to lower bound q learning (Oh et al., 2018; Tang, 2020)), instead of bounding the Bellman value target. This could cause suboptimal training

because the Bellman target itself could be outside the bounds, causing contradictory training targets and losses. Imagine the current value for a state is 1, its Bellman value target may be a low 0, and the lower bound may be a high 2, then it's unclear which way the value function should go. It will depend largely on the mixing weight between the two losses λ and whether initial values overestimate, which can be hard to tune in practice. In their experiments, a fixed Lagrangian multiplier λ was used, which makes the method likely non-optimal.

2) In order to compute the bootstrapped values, the value network needs to be evaluated on all n future time steps, severely increasing GPU memory consumption and compute. Because of this increase in compute, in experiments, it could only look at a limited (4) timesteps into the future, while lb-DR and lb-b-$n$step-only can look ahead much further with very little extra computation and storage.

We implemented the method (He et al., 2017) (only using the lower bounds, no upper bounds) and integrated into our baselines. We ran on FetchPush and FetchPickAndPlace with hyperparameters number of time steps $n = 2$, and the penalty coefficient $\lambda = 4$ following the original paper. Results in Figure 10 show optimality tightening to be either not as stable or not as optimal as our lb-b-$n$step. We also ran it on Atari games, and found that optimality tightening overestimates value a lot, leading to much worse behavior than even the SAC baseline. The constrained optimization formulation might have an adverse interaction with RL training, and the upper bounds in the original optimality tightening work may be necessary to bring training back on track. As future work, it will be interesting to see whether value target upper bounding with bootstrapped values (as proposed in (He et al., 2017) as value upper bound constraints) can lead to optimal converged value in theory, and whether the upper bounds would help optimality tightening in experiments.

A.6 VALUE TARGET LOWER BOUNDING ON DDQN

Because DQN is a more popular baseline for the Atari games, we've also applied value target lower bounding (lb-DR) on DDQN, and ran on a subset of the Atari games. Different from (van Hasselt et al., 2015), our implementation of DDQN finds the maximal action using the target critic network and evaluates the target value on the target network. It also uses two critic replicas like in (Fujimoto et al., 2018). Figure 19 shows the results. Compared to SAC (Figure 5), DDQN either lowers the baseline performance or the treatment (lb-DR) performance, and does not seem as strong as SAC.

| (a) Atari Breakout | (b) Atari Seaquest | (c) Atari Frostbite | (d) Atari Q*bert |

Figure 19: Evaluated average return of value target lower bounding with discounted return (lb-DR) implemented on DDQN vs DDQN baseline on four of the Atari games. Solid curves are the mean across five seeds, and shaded areas are +/- one standard deviation.

A.7 UNBIASED EXPERIENCE REPLAY

When prior experience cannot be reliably reproduced, empirical return lower bounded value target could become biased, similar to the hindsight bias of Hindsight Experience Replay (Lanka & Wu, 2018). This bias can lead to value overestimation, as shown in the example below.

Assume state S_0 always goes to S_1. S_1 gives reward $+2$ or -2 50% of the times uniformly randomly, and transitions to the terminal state. Then the true values are $v(S_0) = v(S_1) = 0$. For one lucky experience with reward $+2$, empirical return for S_0 is 2γ, and for an unlucky one, -2γ. Averaging the two leads to the unbiased estimate of return for S_0, 0, which could be safely used as a valid lower bound. However, if the lower bound is computed only using one lucky experi-

ence or one unlucky experience, then the lower bounded value target for S_0 is $\gamma \max(2, v(S_1))$ and $\gamma \max(-2, v(S_1))$ respectively, averaging to be $\frac{\gamma \max(2,v(S_1)) + \gamma \max(-2,v(S_1))}{2} = \frac{2\gamma + 0}{2} = \gamma$, which overestimates $v(S_0)$.[4]

Computing the unbiased estimate of the value target lower bound using empirical return could be tricky if multiple experiences are needed to compute the value target of a single state. Luckily, when reward sequences can be repeated, (which is the case for many tasks in the macroscopic physical world, where the same actions from the same beginning state usually lead to the same final state), then, the empirical return from a single experience can be used to provide an unbiased estimate of the value target lower bound, which is the case for all the experiments in this paper.

A.8 POTENTIAL IMPROVEMENT

Note that the goal distance based return (lb-GD) of Section 3.1.1 is a very simple way of arriving at a reasonable lower bound with near zero additional computation. The bound could be made tighter. Typically, an L_2 distance threshold is used to judge goal achievement, which will likely be satisfied a few time steps before exactly arriving at the hindsight goal. To compute such a tighter bound would require evaluating the reward function across the trajectories of experience using all possible hindsight goal states, and storing them in the replay buffer, i.e. episode length squared more computation and more storage space. It may be worth doing when episodes are short, or doing it only for a small number of time steps into the future when e.g. rewards are non-negative.

---

[4]For this argument, we can simply assume $v(S_1)$ to be 0, the correct value.