Def-DTS: Deductive Reasoning for Open-domain Dialogue Topic Segmentation

Abstract

Dialogue Topic Segmentation (DTS) aims to divide dialogues into coherent segments. DTS has a crucial role in various NLP downstream tasks, but suffers from chronic problems: data shortage, labeling ambiguity and incremental complexity of recently proposed solutions. On the other hand, Despite advancements in Large Language Models (LLMs) and reasoning strategies, these have rarely been applied to DTS. This paper introduces Def-DTS: Deductive Reasoning for Open-domain Dialogue Topic Segmentation, which utilizes LLM-based multi-step deductive reasoning to enhance DTS performance and enable case study using intermediate result. Our method employs a structured prompting approach for bidirectional context summarization, utterance intent classification, and deductive topic shift detection. In the intent classification process, we propose the generalizable intent list for domain-agnostic dialogue intent classification. Experiments on various dialogue settings demonstrate that Def-DTS consistently outperforms traditional and state-of-the-art approaches, with each subtask contributing to improved performance, particularly in reducing type 2 error. We also explore the potential for autolabeling, emphasizing the importance of LLM reasoning techniques in DTS.

1 Introduction

Dialogue Topic Segmentation (DTS) is a task that aims to divide a dialogue into segments where each segment focuses on a coherent topic. Figure 1 shows an example of topic shift within a single dialogue. DTS is crucial for various natural language processing (NLP) tasks, including response prediction (Lin et al., 2020; Xu et al., 2021b; He et al., 2022), response generation (Li et al., 2016; Xu et al., 2021a; Liu et al., 2022), dialogue state tracking (Das et al., 2024), summarization (Bokaei et al., 2016; Chen and Yang, 2020; Qi et al., 2021; Zhong

Figure 1: An example of a topic shift in a conversation. The cues for a topic shift are highlighted in red.

et al., 2022), question answering (Yoon et al., 2018; Zhang et al., 2022), and machine reading comprehension (Ma et al., 2024).

Despite growing interest, DTS suffers from several chronic challenges. First, the shortage of annotated data has led most recent DTS studies to unsupervised way, which generally yield suboptimal performance. Second, The ambiguity in segment labeling has hindered the development of effective approaches. Specifically, the low kappa scores of early datasets, such as TIAGE(Xie et al., 2021) reveal inconsistencies in the decisions regarding segment boundaries. On the other hand, recent studies: DialSTART (Gao et al., 2023), UR-DTS (Hou et al., 2024)) have proposed incremental approaches that require more parameter and complexity, enhancing prior studies: CSM (Xing and Carenini, 2021) and DialSTART (Gao et al., 2023), respectively. These progression indicate that DTS is a challenging and often underestimated problem.

While DTS struggles with its complexities, NLP has witnessed significant advancements with the rise of Large Language Models (LLMs) and reasoning methodologies. LLMs demonstrate remarkable capabilities such as in-context learning, and reason-

ing strategies like Chain-of-Thought (CoT) have enabled LLMs to handle complex logical tasks and perform factual reasoning using natural language queries. However, even considering robust problem-solving skills of these LLMs and the challenges posed by DTS, reasoning strategies are rarely applied in DTS area. This is primarily because DTS has been implemented as a lightweight subtask within other NLP tasks. As AI-driven chat services continue to expand, there is a pressing need for more sophisticated DTS modules. LLMs with reasoning capability, are timely and well-positioned to meet this demand, making LLM-based DTS feasible.

To provide a explicit criteria for topic shifts while reducing the effort required to complex subtasks, we propose Def-DTS: Deductive Reasoning for Open-domain Dialogue Topic Segmentation, which incorporates LLM-based multi-step and deductive reasoning to DTS with verified subtask sequence. Def-DTS employs a structured prompting methodology that sequentially directs the LLM to perform bidirectional context summarization, utterance intent classification, and deductive topic shift classification at the utterance level. Our approach emphasizes domain-agnostic intent classification as key component of the methodology.

To validate the effectiveness of Def-DTS, we conduct experiments on three distinct dialogue datasets, covering both open-domain and task-oriented settings, and evaluate across three metrics. Our method consistently outperforms traditional and state-of-the-art approaches, including unsupervised, supervised, and prompt engineering techniques, in most of benchmarks with a large margin. Moreover, our ablative analysis demonstrates that each subtask effectively enhances performance around the entire dataset, further analysis using valuable intermediate intents argues that our method particularly improves the ability to correctly identify true-positive cases to earlier methods. At the end of the work, we discuss the possibility of auto-labeling for LLM DTS. In summary, our contribution are 4-fold:

- We introduce LLM reasoning techniques to DTS for the first time, consolidating insights from previous methodologies into a deductive and cohesive prompt design.

- We propose a reformulation of DTS as utterance-level intent classification, enabling flexible and task-agnostic prompting.

- Our method empirically demonstrates superior performance across nearly all comparative baselines, underscoring the efficacy of prompt engineering in DTS.

- Through an in-depth analysis of our approach's reasoning results, we shed light on the challenges LLM reasoning faces in DTS and discuss the possibility of using LLM as a DTS auto-labeler.

2 Related Works

2.1 Dialogue Topic Segmentation

Dialogue topic segmentation aims to segment a dialogue session into the topical coherent units. Due to lack of annotated datasets, researchers have favored unsupervised approaches, despite the complexity of the task (Xing and Carenini, 2021). Early unsupervised solutions were based on TextTiling (Hearst, 1997), which detects topic shifts by measuring lexical similarity between adjacent text blocks. This approach was later enhanced by using embedding vectors (Song et al., 2016), which better captures deeper semantic relationships.

Recent DTS researchs focus more on scoring topical coherence and similarity. CSM (Xing and Carenini, 2021) leverages coherence between adjacent utterances by BERT-based embeddings. Dial-START (Gao et al., 2023) not only calculates coherence score like CSM, but simultaneously consider the topic similarity score by leveraging Sim-CSE(Gao et al., 2021). SumSeg (Artemiev et al., 2024) uses summary to extract key information from less structured dialogue data and applies Savitzky–Golay smoothing to handle high-frequency topic signals. Most recently, UR-DTS (Hou et al., 2024) combines utterance rewriting method with DialSTART to enhance topic segmentation accuracy by recovering co-referents and omitted words in unlabeled dialogues. Despite variety of unsupervised methods, performance challenges still persist, and data scarcity problem remains unsolved.

SuperDialSeg (Jiang et al., 2023) tries to overcome data scarcity by supervised approach. it claims excellence of supervised methods in dialogue topic segmentation with providing large scale supervision on task oriented dialogue setting from DGDS(Document Grounded Dialogue System) datasets (Feng et al., 2020, 2021). While the study shows high performance and introduces new method for data creation, the available datasets are

still limited in terms of open-domain and daily conversational formats.

The emergence of large language models (LLMs) also impacts DTS. S3-DST (Das et al., 2024), organizes prompt strategy for open-domain dialogue state tracking and dialogue topic segmentation based on PAR (Pre Analytical Recollection) and XML-style input-output format. However, S3-DST is primarily designed for dialogue state tracking and does not take universal dialogue settings into account, so it cannot implement a wide range of DTS settings.

2.2 Reasoning Strategy at LLM Inference

Since the rise of large language models (LLMs)(Brown et al., 2020a), their rapid advancement has prompted ongoing investigation into their potential performance. Research has also focused on techniques to inject System 2 thinking capabilities into these models, such as in-context learning(Brown et al., 2020b) and chain of thought prompting(Wei et al., 2022). Consequently, LLMs are now capable of addressing complex tasks(Achiam et al., 2023), including solving symbolic mathematics problems(Yang et al., 2024), leveraging external knowledge bases to provide more accurate information(Lewis et al., 2020), and even generating datasets for model training(Adler et al., 2024). Furthermore, with appropriate prompting, LLMs can perform intricate and sophisticated multitask operations. Certain studies have demonstrated that the performance on specific tasks (i.e. multi hop open domain reasoning(Wang et al., 2023), math reasoning(Imani et al., 2023)) can be significantly enhanced through intermediate reasoning processes.

In our study, we apply LLM in our method with the belief that the vast potential of LLMs will also lead to strong performance in Dialogue Topic Segmentation (DTS), which is a complex challenging task.

3 Def-DTS

3.1 Overall Flow

Our method, as illustrated in Figure 2, incorporates multiple subtasks applied to each utterance in a structured prompt format.

The prompt template is shown in (b) of Figure 2. It consists of four parts: valid label list, task description, output format, input. An explanation of the input is provided in section 3.2. As shown in (c)

Algorithm 1 Def-DTS

Require: IntentPool $X = \{x_1, x_2, \ldots, x_m\}$
Require: StructuredDialogue $D = \{d_i\}_{i=1}^{N}$, where $d_i = \{u_i, s_i\}$ (utterance u_i and speaker s_i)
Ensure: Results $R = \{r_i\}_{i=1}^{N}$, where $r_i = \{P_i, Q_i, X_i, T_i\}$ (bidirectional context (P_i, Q_i), intent X_i, topic shift T_i)
1: $R \leftarrow \emptyset, S \leftarrow$ STRUCTUREDIALOGUE(D)
2: **for** $i \leftarrow 1$ to N **do**
3: $\quad P_i \leftarrow$ EXTRACTCONTEXT$(D, max(1, i-2), i)$
4: $\quad Q_i \leftarrow$ EXTRACTCONTEXT$(D, i+1, min(i+3, N))$
5: $\quad X_i \leftarrow$ CLASSIFYINTENT$(D[i], P_i, Q_i, X)$
6: $\quad T_i \leftarrow$ CLASSIFYTOPICSHIFT(X_i)
7: $\quad r_i \leftarrow r_i \cup \{(P_i, Q_i, X_i, T_i)\}$
8: **end for**
9: **return** R

10: **function** EXTRACTCONTEXT$(D, start, end)$
11: $\quad context \leftarrow$ SUMMARIZE$(D[start : end])$
12: $\quad$ **return** "U_{start}-U_{end}"$, context$
13: **end function**

14: **function** CLASSIFYINTENT$(utterance, P, Q, X)$
15: $\quad$ **return** $classified\_intent$
16: **end function**

17: **function** CLASSIFYTOPICSHIFT(x)
18: $\quad$ **return** $x \in \{$"introduce_topic", "change_topic"$\}$? "YES" : "NO"
19: **end function**

20: **function** SUMMARIZE$(context)$
21: $\quad$ **return** $summarized\_context$
22: **end function**

---

of Figure 2, our method consists of three main subtasks: (i) bidirectional context extraction, (ii) utterance intent classification, and (iii) deductive topic shift classification. Each subtask is executed deductively, and detailed explanations of each subtask are provided in Sections 3.3 to 3.5. We also provide algorithm of our methodology in Algorithm 1.

3.2 Structured Format

We benchmark previous DST research(Das et al., 2024) by using a structured template in XML format. Prompt formatting helps ensure LLM outputs follow labeling instructions by providing structured, well-defined formats that increase alignment and make parsing easier, reducing the need for postprocessing(Das et al., 2024). We believe our deductive, multi-step method can similarly benefit from these advantages, enhancing alignment with labeling instructions and reducing postprocessing efforts.

Consequently, we present our prompt in XML tree structure except for task descriptions. The input template, described as (b) of Figure 2, is organized according to the order of utterances (<Ux>, x is the order of

Figure 2: Prompt configuration and overall flow of our method: Def-DTS. (a) We utilize general intent list including the intent-specific examples to enable domain-agnostic categorization. (b) We employ the xml structured input-output format to stably provide the dialogue. (c) We instruct LLM to process the multi-step reasoning for each utterance in a inference.

each utterance) and each `<Ux>` element contains corresponding speaker information and utterance content at `<speaker>...</speaker>` and `<utterance>...</utterance>`, respectively. The output, described as (c) of 2, consists of set of subtask results for each utterance in XML tree structure as well. A complete prompt template can be found in Appendix A.1.

3.3 Bidirectional Context Extraction

At the first stage of Def-DTS, We instruct LLM to summarize the preceding and subsequent dialogues for each utterance. Considering bidirectional context is commonly used in many methods such as the BERT architecture (Devlin et al., 2019) and frequently employed in unsupervised settings (Gao et al., 2023; Hou et al., 2024). While Das et al., 2024 only extracts preceding context to prevent contextual forgetting, we improve upon this by extract both preceding and subsequent context to enable context-aware dialogue topic segmentation and prevent contextual forgetting.

As shown in (i) of Figure 2, we instruct the model to summarize no more than two preceding turns using the `<preceding_context>` tag and no more than three subsequent turns using the `<subsequent_context>` tag. Each element is composed of `<range>. . . </range>` for defining the summary scope and `<context>. . . </context>` for the actual summary. Our experiments reveal that this approach effectively facilitates observing nuanced topic relationships.

3.4 Utterance Intent Classification

Intent	Description
JUST COMMENT	Commenting on the preceding context without any asking. Not a topic shift
JUST ANSWER	Answering preceding utterance. Not a topic shift
DEVELOP TOPIC	Developing the conversation to similar and inclusive sub-topics. Not a topic shift
INTRODUCE TOPIC	Introducing a relevant but different topic. A topic shift
CHANGE TOPIC	Completely changing the topic. A topic shift

Table 1: Utterance intent list for open-domain dialogue. Using this list, we categorize the utterance and deductively classify the topic shift label.

As there are issues with the ambiguity of the DTS datasets, simply providing descriptions for topic classification is insufficient to convey a precise definition of topic changes. Therefore, we suggest that classifying utterance using a well-defined and distinct list of labels, similar to intent classification, would be beneficial for DTS. However, most of intent classification tasks have been conducted within the context of Task Oriented Dialogue(TOD) (Liu and Lane, 2016; Chen and Luo, 2023).

In this context, we find that Xie et al., 2021 identified five patterns of conversational responses which is utilized in their annotation guidelines. These patterns reflect the natural characteristics of utterances, enabling intent classification for various forms of dialogue. Detailed intent patterns and

descriptions are in Table 1.

Inspired by this research, we instruct model to detect topic change through utterance intent classification. Specifically, after the bidirectional context extraction, as shown in (ii) of Figure 2, model classifies the utterance into an intent of the predefined general intent pool (upper box of (a) of Figure 2), considering previously generated bidirectional context.

Additionally, we enhance the model's understanding of the intents by providing example dialogue for each intent, as shown in General intent pool at (a) of Figure 2. The intent-specific examples provide the model with a helpful guideline detecting topic changes, allowing it to derive results in the subsequent subtask, deductive topic shift. We observed significant performance improvements across various dialogue settings using this technique, enabling a detailed analysis of each intent. Details of intent list and their corresponding definitions for each dataset is in Appendix A.2.

3.5 Deductive Topic Shift Classification

Finally, model predicts whether the topic is changing based on the deductive guidelines from the previous intent classification results as shown in (iii) of Figure 2. This task is processed in enforced manner, the model deductively outputs the predetermined label based on the intent classification results of previous step, according to the tail of description (i.e. Not a topic shift or A topic shift) for each intent described in Table 1.

We explicitly instruct model to process this step for two reasons. First, it simplifies the parsing process, making the task easy to handle. Second, it ensures that the model explicitly outputs the result of primary goal, allowing it to stay focused on the main objective(DTS), while working through the subtasks.

4 Experiments

We verify the performance of our method by experiments on various settings. Detailed setting what we use for experiment is explained below, including evaluated datasets, compared methods and used model for our prompt evaluation.

4.1 Datasets

We evaluate our method on three datasets: TIAGE, SuperDialseg, Dialseg711 to verify performance of our method at both open-domain and task-oriented setting. Dataset statistics are presented in Table 2.

Dataset	# Sample	Utterance per Dial.			Segment per Dial.	
		avg	min	max	avg	avg.len
TIAGE	100	15.6	14	16	4.2	3.8
SuperDialseg	1322	12.1	7	19	4.0	3.0
Dialseg711	711	26.2	7	47	4.9	5.4

Table 2: Statistics of datasets for dialogue topic segmentation.

TIAGE (Xie et al., 2021) is the only publicly available dataset with topically segmented daily conversations, derived from PersonaChat (Zhang et al., 2018) and designed for modeling topic shifts in open-domain dialogue. SuperDialseg (Jiang et al., 2023) is a large-scale dialogue segmentation dataset based on document-grounded corpora, offering a framework for identifying segmentation points in document-based dialogues. Dialseg711 (Xu et al., 2021b) is a real-world dialogue dataset auto-labeled from MultiWOZ (Budzianowski et al., 2018) and Stanford Dialog Dataset (Eric et al., 2017), created by joining dialogues with distinct topics, resulting in clear topical differences and low coherency at segment boundaries due to its synthetic nature.

4.2 Evaluation Metrics

As early studies (Xing and Carenini, 2021; Jiang et al., 2023; Artemiev et al., 2024) did, we leverage P_k score (Beeferman et al., 1997), WindowDiff (WD) score (Pevzner and Hearst, 2002) and f1 score. The P_k score is calculated by counting the existance of misallocated segment with sliding window of predictions. The WD score is calculated by comparing numbers of boundaries within sliding window of gold labels and predictions. Note that the lower P_k or WD means the higher performance.

4.3 Comparison Methods

We propose a sophisticated DTS method based on prompt engineering way and compare its performance with various unsupervised, supervised, and LLM-based methodologies. First, we compare our method to a random baseline that arbitrarily assigns segment boundaries based on a randomly chosen number of segments. Next, we compare it to notable unsupervised learning methods based on TextTiling like Coherence Scoring Model (CSM) (Xing and Carenini, 2021), DialSTART (Gao et al., 2023), SumSeg (Artemiev et al., 2024). We also compare supervised learning methodologies. We selected the basic BERT model(Devlin et al., 2019), the advanced and high-performing RoBERTa model(Liu,

2019), RetroTS-T5(Xie et al., 2021) system for our comparative analysis. Finally, we compare with the LLM-based methods, which were recently introduced, include our approach. we applied these methods by using gpt-4o.[1] We selected the Plain-Text prompts performed in SuperDialseg(Jiang et al., 2023) and the prompt of S3-DST(Das et al., 2024). The details of the methodology utilized for each of the actual comparisons are discussed in Appendix C.1.

4.4 Experimental Results

The experimental results are presented in Table 3. Our methodology consistently demonstrated superior performance among LLM-based methods and achieved state-of-the-art results on both the TIAGE and Dialseg711 datasets, which closely align with our objective of analyzing general, open-domain dialogues.

In TIAGE dataset, our method yielded reductions of over 0.2 in both P_k and WD scores, coupled with an impressive increase of more than 0.4 in the f1 score. These outcomes underscore the efficacy of our proposed Utterance Intent Classification and the incorporation of Bidirectional Context within the framework of Prompt Engineering on the open-domain dialogue setting.

However, our method did not achieve comparable improvements in the SuperDialseg dataset relative to other datasets. We hypothesize that this is attributable to two primary factors. Firstly, SuperDialseg primarily comprises dialogues with a consistent consultative tone, potentially making the presence or absence of training a more crucial factor in determining performance improvements. Secondly, the characteristic of segmentation based on referenced documents potentially limits the efficacy of our detection strategy reliant on the nature of utterance patterns.

5 Analysis and Discussion

5.1 Ablation Study

To assess the contributions of each part of our approach, we perform an ablation study. The results are shown in Table 4. Among the methods we tested, the lowest performing method was the variant without intent (w/o intent), which included structured prompts and bidirectional context extraction.

---

[1] https://platform.openai.com/docs/models/gpt-4o

We believe the lower performance of w/o intent compared to the variant without all components (w/o all) is due to an excessive focus on context, which can limit understanding of the conversation as a whole and lead to an overemphasis on specific details. Our results show non-linear performance improvements with addition of subtasks, suggesting that reframing the problem as a classification task is more effective than relying solely on context for segmentation.

5.2 Intent Classification Accuracy

As our method directly used utterance intent to deduce topic shifts, analyzing intent classification results plays a crucial role in affecting performance in our experiments. Accordingly, we examine the confusion matrix of the model's predictions to identify the utterance types it struggles with. Since there is no ground truth about intent and only topic shift labels are provided, the correctness of each category only relies on whether the utterance was predicted to the correct topic shift label. For example, at the case of an utterance with a topic shift of True, if the model's prediction outputs JUST_COMMENT for the intent classification task and NO for the topic shift task, it is counted as a False Negative (FN) in the confusion matrix.

As shown in Table 5, all but two of the results performed well on the deductive topic shift classification. We use these statistics to confirm that the model primarily struggles with determining whether a subtle topic difference should be treated as an actual topic change, and we identify this as a more significant factor in performance degradation than the challenges posed by other types of utterances. The analysis of other datasets (i.e., SuperDialseg, Dialseg711) is in the Appendix B.

5.3 Intent Level Comparison

We compared the performance of various approaches across different intent categories that our method predicted, as shown in Figure 3. In (a) MATCHED INTENT, for utterances without a topic shift, other methodologies achieved approximately 80-85% accuracy when our method was also correct. However, for utterances involving a topic shift, the accuracy of other methods dropped to around 20-50% for the correct case of our method. In (b) MISMATCHED CASE, for utterances without a topic shift, other methods correctly classified over 50% of the cases where our method was incorrect. However, for utterances with

Method	TIAGE			SuperDialseg			Dialseg711		
	$P_k\downarrow$	WD↓	F1↑	$P_k\downarrow$	WD↓	F1↑	$P_k\downarrow$	WD↓	F1↑
Unsupervised Learning Methods									
Random	0.526	0.664	0.237	0.494	0.649	0.266	0.533	0.714	0.204
TextTiling	0.469	0.488	0.204	0.441	0.453	0.388	0.470	0.493	0.245
TextTiling+Glove	0.486	0.511	0.236	0.519	0.524	0.353	0.399	0.438	0.436
CSM	**0.400**	**0.420**	**0.427**	0.462	0.467	0.381	0.278	0.302	0.610
DialSTART	0.482	0.528	0.378	**0.373**	**0.412**	**0.627**	**0.179**	**0.198**	**0.733**
SumSeg	0.482	0.496	0.075	0.479	0.485	0.119	0.477	0.483	0.070
Supervised Learning Methods									
BERT	0.418	0.435	0.124	0.214	0.225	0.725	-	-	-
RoBERTa	**0.265**	**0.287**	0.572	0.185	0.192	0.784	-	-	-
RetroTS-T5	0.280	0.317	**0.576**	0.227	0.237	0.733	-	-	-
LLM-based Methods									
Plain Text	0.445	0.485	0.185	0.412	0.427	0.048	0.333	0.353	0.010
S3-DST$_{uttr}$	0.439	0.498	0.265	0.442	0.469	0.404	0.087	0.109	0.790
Def-DTS (Ours)	**0.232**	**0.256**	**0.699**	**0.315**	**0.324**	**0.686**	**0.015**	**0.018**	**0.979**

Table 3: Performances on three datasets. Due to absence of train and validation split for Dialseg711 dataset, There are no report in dialseg711's supervised learning part. The best results for each method group are highlighted in bold. The best performances around all method are indicated as red colored text.

Method	TIAGE		
	$P_k\downarrow$	WD↓	F1↑
w/o all	0.295	0.333	0.605
w/o intent	0.316	0.342	0.524
w/o examples	0.287	0.308	0.617
w/o context	0.263	0.296	0.682
Def-DTS	**0.232**	**0.256**	**0.699**

Table 4: Ablation study for identifying effectiveness of each subtask within our method.

Intent	TP	FP	TN	FN	Acc
JUST_COMMENT	0	1	498	35	0.93
JUST_ANSWER	0	1	456	23	0.95
DEVELOP_TOPIC	0	0	119	47	0.71
INTRODUCE_TOPIC	189	68	0	0	0.73
CHANGE_TOPIC	21	6	0	0	0.78

Table 5: Intent-level confusion matrix for TIAGE benchmark.

a topic shift, other methods failed to classify 80% of the cases that our method also missed. This demonstrates that detecting utterances with actual topic shifts is considerably more challenging than detecting those without topic shifts. Our method outperforms the other methodologies by roughly 20% in cases without topic shifts, and by over 40% in cases with topic shifts. In summary, while our approach improves accuracy across all cases, it shows even greater improvement when handling utterances with topic shifts.

5.4 Performance Comparison for Local LLMs

We conducted experiments using local LLMs instead of GPT-4o, the models used were meta-llama/Llama-3.1-70B-Instruct and Qwen/Qwen2.5-72B-Instruct for Llama and Qwen in Table 6, respectively, with three test prompts: Plain Text, S3-DST$_{uttr}$, and Def-DTS. For efficient experiment, we randomly sampled 100 examples for each dataset except for TIAGE. Likewise, Def-DTS achieved the highest performance across all datasets in this experiment.

In the case of Qwen, formatting error were observed across all datasets. Despite being an unstructured method, plain did not experience formatting errors with the 70B and 72B LLMs, but its performance remained comparatively lower. These re-

Model	TIAGE			SuperDialseg			Dialseg711		
	$P_k\downarrow$	WD$\downarrow$	F1$\uparrow$	$P_k\downarrow$	WD$\downarrow$	F1$\uparrow$	$P_k\downarrow$	WD$\downarrow$	F1$\uparrow$
Plain Text + Llama	0.472	0.515	0.215	0.492	0.495	0.026	0.350	0.373	0.032
Plain Text + Qwen	0.495	0.533	0.162	0.485	0.487	0.059	0.422	0.434	0.012
S3-DST$_{uttr}$ + Llama	0.456	0.474	0.143	0.490	0.512	0.072	0.158	0.190	0.553
S3-DST$_{uttr}$ + Qwen	-	-	-	-	-	-	-	-	-
Def-DTS + Llama	**0.307**	**0.339**	**0.552**	**0.384**	**0.385**	**0.432**	**0.029**	**0.039**	**0.941**
Def-DTS + Qwen	0.327	0.345	0.530	0.433	0.434	0.171	0.102	0.208	0.729

Table 6: Performances on the local LLMs. We employed Llama-3.1-70B-Instruct and Qwen2.5-72B-Instruct for Llama and Qwen, respectively. The case of best performance across all method are highlighted in bold.

Figure 3: (a) MATCHED INTENT indicates the accuracy of the other methodologies for grouped utterances by our intent classification process only in the true cases of our method. (b) MISMATCHED CASE indicates the co-error count of the other methodologies with our methods for only in the false cases of our method.

sults demonstrate that our approach maintains high accuracy across different LLMs.

5.5 Discussion for Possibility of Auto-Labeling

As various auto-labeling methodologies have been proposed to date, we assess prompt engineering could potentially serve as a viable auto-labeling methodology.

we conducted a preliminary experiment to assess the feasibility of using prompt engineering for DTS. We compared the segment labels generated by GPT-4 for Def-DTS with the correct labels using Cohen's Kappa score. The results showed Kappa scores of 0.485 for TIAGE, 0.429 for SuperDialseg, and 0.975 for Dialseg711, indicating moderate agreement for TIAGE and SuperDialseg, and almost perfect agreement for Dialseg711. Notably, our labeling result for TIAGE exceeded the 0.479

agreement score observed between actual human annotators. While improvements are needed given the moderate agreement, these findings suggest that our approach can still function as a minimal annotator.

6 Conclusion

Previous approaches to DTS have been constrained by several challenges, including data shortage, ambiguity of segment labeling, and increasingly complex model architectures. Concurrently, The promising approach of reasoning with LLMs has yet to be explored in the context of DTS. To address these issues, we propose Def-DTS, that leverages LLMs in conjunction with sophisticated reasoning strategies. Def-DTS incorporates bidirectional context extraction, a crucial component in previous research, along with the novel task of utterance intent classification. This approach demonstrates significant performance improvements in both open-domain dialogue setting and task-oriented dialogue setting. Its efficacy across diverse datasets is enhanced through the provision of dataset-specific examples in the utterance intent classification task, enabling adaptable performance in varied dialogue contexts. Through its primary findings and diverse analysis, we demonstrates the efficacy of LLM-reasoning as a promising approach for DTS. It not only highlights the potential of our method but also statistically delineates challenges to be addressed in future research. In subsequent investigations, we intend to explore the feasibility of automated labeling for DTS and examine the potential integration of DTS with other NLP downstream tasks through LLM reasoning.

7 Limitations

Primarily, our methodology necessitates the inclusion of representative examples from the dialogue dataset within the provided prompt. Experimental results demonstrated a significant performance disparity contingent upon the presence or absence of these examples. Furthermore, an in-depth exploration of methodologies for selecting optimal examples has not yet been conducted. In addition, the intent labels employed in our study were derived from previous research and did not undergo comprehensive linguistic analysis that can induce the more sophisticated intent set. Consequently, we acknowledge the potential existence of more suitable intent labels that may enhance the efficacy of our approach.

In order to improve the quality of intents and examples in a variety of dialogue settings, the fundamental problem must be addressed first, namely the provision of quality datasets for DTS. The dialogue should include thorough labeling criteria and realistic dialogue domains to address our limitations. However, human labeling is not only still expensive but also carries the risk of inconsistent or ambiguous labeling. We believe that the automated labeling using LLMs with sophisticated guideline will play a crucial role in creating a more sustainable and reliable DTS environment.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Bo Adler, Niket Agarwal, Ashwath Aithal, Dong H Anh, Pallab Bhattacharya, Annika Brundyn, Jared Casper, Bryan Catanzaro, Sharon Clay, Jonathan Cohen, et al. 2024. Nemotron-4 340b technical report. *arXiv preprint arXiv:2406.11704*.

Aleksei Artemiev, Daniil Parinov, Alexey Grishanov, Ivan Borisov, Alexey Vasilev, Daniil Muravetskii, Aleksey Rezvykh, Aleksei Goncharov, and Andrey Savchenko. 2024. Leveraging summarization for unsupervised dialogue topic segmentation. In *Findings of the Association for Computational Linguistics: NAACL 2024*, pages 4697–4704, Mexico City, Mexico. Association for Computational Linguistics.

Doug Beeferman, Adam Berger, and John Lafferty. 1997. Text segmentation using exponential models. In *Second Conference on Empirical Methods in Natural Language Processing*.

Mohammad Hadi Bokaei, Hossein Sameti, and Yang Liu. 2016. Extractive summarization of multi-party meetings through discourse segmentation. *Natural Language Engineering*, 22(1):41–72.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020a. Language models are few-shot learners. In *Advances in Neural Information Processing Systems*, volume 33, pages 1877–1901. Curran Associates, Inc.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020b. Language models are few-shot learners. In *Advances in Neural Information Processing Systems*, volume 33, pages 1877–1901. Curran Associates, Inc.

Paweł Budzianowski, Tsung-Hsien Wen, Bo-Hsiang Tseng, Iñigo Casanueva, Ultes Stefan, Ramadan Osman, and Milica Gašić. 2018. Multiwoz - a large-scale multi-domain wizard-of-oz dataset for task-oriented dialogue modelling. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.

Jiaao Chen and Diyi Yang. 2020. Multi-view sequence-to-sequence models with conversational structure for abstractive dialogue summarization. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 4106–4118, Online. Association for Computational Linguistics.

Yan Chen and Zhenghang Luo. 2023. Pre-trained joint model for intent classification and slot filling with semantic feature fusion. *Sensors*, 23(5).

Sarkar Snigdha Sarathi Das, Chirag Shah, Mengting Wan, Jennifer Neville, Longqi Yang, Reid Andersen, Georg Buscher, and Tara Safavi. 2024. S3-DST: Structured open-domain dialogue segmentation and state tracking in the era of LLMs. In *Findings of the Association for Computational Linguistics ACL 2024*, pages 14996–15014, Bangkok, Thailand and virtual meeting. Association for Computational Linguistics.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of*

the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.

Mihail Eric, Lakshmi Krishnan, Francois Charette, and Christopher D. Manning. 2017. Key-value retrieval networks for task-oriented dialogue. In Proceedings of the 18th Annual SIGdial Meeting on Discourse and Dialogue, pages 37–49, Saarbrücken, Germany. Association for Computational Linguistics.

Song Feng, Siva Sankalp Patel, Hui Wan, and Sachindra Joshi. 2021. MultiDoc2Dial: Modeling dialogues grounded in multiple documents. In Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing, pages 6162–6176, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Song Feng, Hui Wan, Chulaka Gunasekara, Siva Patel, Sachindra Joshi, and Luis Lastras. 2020. doc2dial: A goal-oriented document-grounded dialogue dataset. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP), pages 8118–8128, Online. Association for Computational Linguistics.

Haoyu Gao, Rui Wang, Ting-En Lin, Yuchuan Wu, Min Yang, Fei Huang, and Yongbin Li. 2023. Unsupervised dialogue topic segmentation with topic-aware contrastive learning. In Proceedings of the 46th International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR '23, page 2481–2485, New York, NY, USA. Association for Computing Machinery.

Tianyu Gao, Xingcheng Yao, and Danqi Chen. 2021. SimCSE: Simple contrastive learning of sentence embeddings. In Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing, pages 6894–6910, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Wanwei He, Yinpei Dai, Yinhe Zheng, Yuchuan Wu, Zheng Cao, Dermot Liu, Peng Jiang, Min Yang, Fei Huang, Luo Si, Jian Sun, and Yongbin Li. 2022. Galaxy: A generative pre-trained model for task-oriented dialog with semi-supervised learning and explicit policy injection. Proceedings of the AAAI Conference on Artificial Intelligence, 36(10):10749–10757.

Marti A. Hearst. 1997. Text tiling: Segmenting text into multi-paragraph subtopic passages. Computational Linguistics, 23(1):33–64.

Xia Hou, Qifeng Li, and Tongliang Li. 2024. An unsupervised dialogue topic segmentation model based on utterance rewriting. arXiv preprint arXiv:2409.07672.

Shima Imani, Liang Du, and Harsh Shrivastava. 2023. MathPrompter: Mathematical reasoning using large language models. In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 5: Industry Track), pages 37–42, Toronto, Canada. Association for Computational Linguistics.

Junfeng Jiang, Chengzhang Dong, Sadao Kurohashi, and Akiko Aizawa. 2023. SuperDialseg: A large-scale dataset for supervised dialogue segmentation. In Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, pages 4086–4101, Singapore. Association for Computational Linguistics.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. 2020. Retrieval-augmented generation for knowledge-intensive nlp tasks. In Advances in Neural Information Processing Systems, volume 33, pages 9459–9474. Curran Associates, Inc.

Jiwei Li, Will Monroe, Alan Ritter, Dan Jurafsky, Michel Galley, and Jianfeng Gao. 2016. Deep reinforcement learning for dialogue generation. In Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing, pages 1192–1202, Austin, Texas. Association for Computational Linguistics.

Ting-En Lin, Hua Xu, and Hanlei Zhang. 2020. Discovering new intents via constrained deep adaptive clustering with cluster refinement. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 34, pages 8360–8367.

Bing Liu and Ian Lane. 2016. Attention-based recurrent neural network models for joint intent detection and slot filling. arXiv preprint arXiv:1609.01454.

Che Liu, Rui Wang, Junfeng Jiang, Yongbin Li, and Fei Huang. 2022. Dial2vec: Self-guided contrastive learning of unsupervised dialogue embeddings. In Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing, pages 7272–7282, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Yinhan Liu. 2019. Roberta: A robustly optimized bert pretraining approach. arXiv preprint arXiv:1907.11692.

Xinbei Ma, Yi Xu, Hai Zhao, and Zhuosheng Zhang. 2024. Multi-turn dialogue comprehension from a topic-aware perspective. Neurocomputing, 578:127385.

Lev Pevzner and Marti A. Hearst. 2002. A critique and improvement of an evaluation metric for text segmentation. Computational Linguistics, 28(1):19–36.

MengNan Qi, Hao Liu, YuZhuo Fu, and Ting Liu. 2021. Improving abstractive dialogue summarization with

hierarchical pretraining and topic segment. In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pages 1121–1130, Punta Cana, Dominican Republic. Association for Computational Linguistics.

Yiping Song, Lili Mou, Rui Yan, Li Yi, Zinan Zhu, Xiaohua Hu, and Ming Zhang. 2016. Dialogue session segmentation by embedding-enhanced texttiling. *Interspeech 2016*, pages 2706–2710.

Jinyuan Wang, Junlong Li, and Hai Zhao. 2023. Self-prompted chain-of-thought on large language models for open-domain multi-hop reasoning. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 2717–2731, Singapore. Association for Computational Linguistics.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, brian ichter, Fei Xia, Ed Chi, Quoc V Le, and Denny Zhou. 2022. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems*, volume 35, pages 24824–24837. Curran Associates, Inc.

Huiyuan Xie, Zhenghao Liu, Chenyan Xiong, Zhiyuan Liu, and Ann Copestake. 2021. TIAGE: A benchmark for topic-shift aware dialog modeling. In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pages 1684–1690, Punta Cana, Dominican Republic. Association for Computational Linguistics.

Linzi Xing and Giuseppe Carenini. 2021. Improving unsupervised dialogue topic segmentation with utterance-pair coherence scoring. In *Proceedings of the 22nd Annual Meeting of the Special Interest Group on Discourse and Dialogue*, pages 167–177, Singapore and Online. Association for Computational Linguistics.

Jun Xu, Zeyang Lei, Haifeng Wang, Zheng-Yu Niu, Hua Wu, and Wanxiang Che. 2021a. Discovering dialog structure graph for coherent dialog generation. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 1726–1739, Online. Association for Computational Linguistics.

Yi Xu, Hai Zhao, and Zhuosheng Zhang. 2021b. Topic-aware multi-turn dialogue modeling. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 14176–14184.

An Yang, Beichen Zhang, Binyuan Hui, Bofei Gao, Bowen Yu, Chengpeng Li, Dayiheng Liu, Jianhong Tu, Jingren Zhou, Junyang Lin, Keming Lu, Mingfeng Xue, Runji Lin, Tianyu Liu, Xingzhang Ren, and Zhenru Zhang. 2024. Qwen2.5-math technical report: Toward mathematical expert model via self-improvement. *arXiv preprint arXiv:2409.12122*.

Seunghyun Yoon, Joongbo Shin, and Kyomin Jung. 2018. Learning to rank question-answer pairs using hierarchical recurrent encoder with latent topic clustering. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 1575–1584, New Orleans, Louisiana. Association for Computational Linguistics.

Sai Zhang, Yuwei Hu, Yuchuan Wu, Jiaman Wu, Yongbin Li, Jian Sun, Caixia Yuan, and Xiaojie Wang. 2022. A slot is not built in one utterance: Spoken language dialogs with sub-slots. In *Findings of the Association for Computational Linguistics: ACL 2022*, pages 309–321, Dublin, Ireland. Association for Computational Linguistics.

Saizheng Zhang, Emily Dinan, Jack Urbanek, Arthur Szlam, Douwe Kiela, and Jason Weston. 2018. Personalizing dialogue agents: I have a dog, do you have pets too? In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2204–2213, Melbourne, Australia. Association for Computational Linguistics.

Ming Zhong, Yang Liu, Yichong Xu, Chenguang Zhu, and Michael Zeng. 2022. Dialoglm: Pre-trained model for long dialogue understanding and summarization. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 11765–11773.

A Prompts

A.1 Prompt Template

We provide prompt template for main dataset: TIAGE. Each dataset has different characteristics to other datasets, so we modified intent pool from original template for each dataset.

```
<valid_utterance_intent>
<item>
<name>JUST_COMMENT</name>
<desc>Commenting on the preceding context without
any asking. Not a topic shift</desc>
<example>
<speaker1>My dad works for the New York
Times.</speaker1>
<speaker2>Oh wow! You know, I dabble in
photography; maybe you can introduce us
sometime.</speaker2>
<speaker1>Photography is the greatest art out
there. (not a topic shift)</speaker1>
</example>
</item>
<item>
<name>JUST_ANSWER</name>
<desc>Answering preceding utterance. Not a topic
```

shift</desc>
<example>
<speaker1>Do you teach cooking? </speaker1>
<speaker2>No, since I'm a native of Mexico, I teach Spanish. (not a topic shift)</speaker2>
</example>
</item>
<item>
<name>DEVELOP_TOPIC</name>
<desc>Developing the conversation to similar and inclusive sub-topics. Not a topic shift</desc>
<example>
<speaker1>Pets are cute!</speaker1>
<speaker2>I heard that Huskies are difficult dogs to take care of. (not a topic shift)</speaker2>
</example>
</item>
<item>
<name>INTRODUCE_TOPIC</name>
<desc>Introducing a relevant but different topic. A topic shift</desc>
<example>
<speaker1>You are an artist? What kind of art, I do American Indian stuff.</speaker1>
<speaker2> I love to eat too, sometimes too much. (a topic shift)</speaker2>
</example>
</item>
<item>
<name>CHANGE_TOPIC</name>
<desc>Completely changing the topic. A topic shift</desc>
<example>
<speaker1>What do you do for fun?</speaker1>
<speaker2>I drive trucks so me and my buds go truckin in the mud.</speaker2>
<speaker1>Must be fun! My version of that's running around a library!</speaker1>
<speaker2>That's cool! I love that too. Do you have a favourite animal? Chickens are my favourite. I love them. (topic shift)</speaker2>
</example>
</item>
</valid_utterance_intent>
<valid_topic_shift_label>
<item>
<name>YES</name>
<desc>The current utterance has **weak OR no topical** relation to the preceding conversation context OR is the first utterance in the conversation, marking the beginning of a new dialogue segment.</desc>

</item>
<item>
<name>NO</name>
<desc>The current utterance has **relevant OR equal** topic to the preceding conversation context.</desc>
</item>
</valid_topic_shift_label>

TASK
You are given a dialogue starting with U. From utterance number 0, you have to answer the following sub-tasks for each utterance.
1. Summarize the preceding and subsequent context in <=3 sentences seperately
The range of the context should be previous or next 1-3 utterances except for the case of the first or last utterance.
For example, given current utterance number is 2, preceding range is 0-1, subsequent range is 3-5.
2. Output the utterance_intent
Use the list <valid_utterance_intent> ... </valid_utterance_intent> to categorize utterance.
Consider topical difference between preceding and subsequent context.
3. Output the topic_shift_label
Use the list <valid_topic_shift_label> ... </valid_topic_shift_label>.

OUTPUT FORMAT
<U{utterance number}>
<preceding_context>
<range>{range of utterances referred in context}</range>
<context>{context of the previous 1-3 utterances}</context>
</preceding_context>
<subsequent_context>
<range>{range of utterances referred in context}</range>
<context>{context of the next 1-3 utterances}</context>
</subsequent_context>
<utterance_intent>{valid utterance intent}</utterance_intent>
<topic_shift_label>{valid topic shift label}</topic_shift_label>
</U{utterance number}>

INPUT
{XML-structured dialogue}

```
## OUTPUT ##
```

A.2   Intent Labels for other datasets

Intent	Description
DIFFERENT QUESTION	Questioning about something that is not similar or topically different to preciding context. A topic shift
RELEVANT QUESTION	Questioning about something that is similar or topically coherent to preceding context. Not a topic shift
ANSWERING	Answering preceding utterance. Not a topic shift
ADDITIONAL COMMENT	An additional comment from the same speaker in addition to a previous utterance. Not a topic shift

Table 7: Utterance intent list for SuperDialseg dataset.

For Dialseg711 dataset, We delete a intent named INTRODUCE_TOPIC from original intent list. For SuperDialseg dataset, the topic shift occurs when the utterance refers to different document to previous utterance. As shown in Table 7, We entirely change the intent from the original so as to fit to document grounded dialogue setting based topic transition.

B   Analysis on other datasets

B.1   Ablation Study

As shown in Table 8, We found the absence of some module lead to performance degradation. For efficient evaluation, we used randomly sampled 100 dialogue for ablation study for SuperDialseg and Dialseg711 each. this data is same to we used in Section 5.4. Especially on the SuperDialseg dataset, we observed consistent improvement by adding any subtask. However w.r.t Dialseg711 dataset, the existence of context extraction module is crucial to performance improvement. even w/o case surpasses our full-attached method. we conjecture that the issue is due to over-concentration for local context, same as result of ablation study for TIAGE, moreover, on the case of dialseg711 having clear topic shift signal, just predicting label is enough to solve the problem. After all, our intent classification module elevates the performance across all datasets.

B.2   Intent Classification Accuracy

We conduct detailed accuracy analysis for the other datasets and the results are presented in Table 9.

For SuperDialseg, as shown in Table 7, four new intent pools were applied. ADDITIONAL_COMMENT, ANSWERING, and RELEVANT_QUESTION are classified as non-topic shift cases, while the case of DIFFERENT_QUESTION is classified as a topic shift case. However, instruction following was not well executed for the case of DIFFERENT_QUESTION. For the case of RELEVANT_QUESTION, instruction following was well executed with one exception, but its accuracy was relatively low. The difference in explanations between the case of RELEVANT_QUESTION and DIFFERENT_QUESTION could be linked to the actual dataset characteristics and topic changes. In contrast, the cases of ANSWERING and ADDITIONAL_COMMENT showed significantly high classification accuracy. This comparison suggest that improving Question-type intents will lead to an overall improvement in performance.

For Dialseg711, overall accuracy was higher compared to other datasets which deductive instruction following not executed for less than 1% of utterances. For the results of the three intents, excluding the case of CHANGE_TOPIC, 18% of DEVELOP_TOPIC, 30% of JUST_COMMENT, and 42% of JUST_ANSWER cases among all false cases were misclassified due to errors in instruction following. It is believed that this issue can be resolved through additional instructions or prompt modifications for instruction following.

C   Details for Experiment

C.1   Details for Implementation

The model employed for our experiments is gpt-4o for closed LLM, Llama-3.1-70B-Instruct and Qwen2.5-72B-Instruct for open-source LLM. At first, we considered a two closed models: gpt-4o and Claude-3.5-sonnet. But the Claude was excluded due to poor accuracy compared to gpt-4o at a preliminary evaluations and there are no prior studies applied their method to the claude family. For the inference of open-source LLMs, we utilized a computational infrastructure consisting of 4*NVIDIA A100 80GB GPU. We conducted our experiments without employing any model-specific tuning or quantization techniques, thus maintaining the original model architecture and parameters. We kept the hyperparameters initially stated, except for temperature that we set to 0 for reproducibility of our experiments.

Method	SuperDialseg			Dialseg711		
	$P_k\downarrow$	WD$\downarrow$	F1$\uparrow$	$P_k\downarrow$	WD$\downarrow$	F1$\uparrow$
w/o all	0.378	0.382	0.467	0.007210	0.009416	0.987245
w/o intent	0.363	0.364	0.448	0.093486	0.127211	0.701330
w/o examples	0.338	0.341	0.646	0.005826	0.012322	0.984733
w/o context	0.327	0.331	0.635	**0.005800**	**0.008464**	**0.989770**
Def-DTS	**0.317**	**0.322**	**0.674**	0.009024	0.013738	0.982143

Table 8: Ablation study for identifying effectiveness of each subtask within our method.

SuperDialseg					
Intent	TP	FP	TN	FN	Acc
DIFFERENT_QUESTION	2456	688	83	192	0.74
RELEVANT_QUESTION	1	0	811	989	0.45
ANSWERING	0	2	7819	168	0.98
ADDITIONAL_COMMENT	0	0	1264	211	0.86
Dialseg711					
Intent	TP	FP	TN	FN	Acc
JUST_COMMENT	0	6	5067	14	0.996
JUST_ANSWER	0	6	7675	8	0.998
DEVELOP_TOPIC	0	3	2359	13	0.993
CHANGE_TOPIC	2708	66	0	0	0.976

Table 9: Intent-level confusion matrix for other datasets.

Model	TIAGE			SuperDialseg			Dialseg711		
	$P_k\downarrow$	WD$\downarrow$	F1$\uparrow$	$P_k\downarrow$	WD$\downarrow$	F1$\uparrow$	$P_k\downarrow$	WD$\downarrow$	F1$\uparrow$
Unsupervised Learning Methods									
DialSTART	-	-	-	-	-	-	0.179	0.198	-
SumSeg	0.438	0.455	-	0.469	0.480	-	-	-	-
LLM-based Methods									
Plain Text (GPT-3.5)	0.496	0.560	0.362	0.318	0.347	0.658	0.290	0.355	0.690
S3-DST$_{turn}$	-	-	-	-	-	-	0.009	0.008	-

Table 10: Performances reported in their original papers. Denoted as DialSTART indicates main result of Gao et al., 2023, SumSeg indicates main result of Artemiev et al., 2024, Plain Text indicates ChatGPT variant of Jiang et al., 2023's main result and S3-DST$_{turn}$ indicates main result of Das et al., 2024

.

C.2 Details for Reproduce

For the SuperDialseg paper(Jiang et al., 2023), we obtained experimental results for Random, Text-Tiling, TextTiling+Glove, CSM, BERT, RoBERTa, and RetroTS-T5 methods.

We reproduced experiment result for Plain-Text(Jiang et al., 2023), S3-DST(Das et al., 2024), DialSTART(Gao et al., 2023), and Sum-Seg(Artemiev et al., 2024), which either lacked F1 scores or did not conduct experiments on certain datasets.

During reproduction, we maintained all settings, including seeds, without any parameter modifications. However, We observed results that differed from the original experiments. Their original experimental results are presented in Table 10.

For the reproduction of LLM-based methods, we made necessary modifications in the following cases.

Plain Text (Jiang et al., 2023): As Plain Text was the only methodology that disclosed the system prompt, we equitably refrained from using system prompts. We compared results with and without system prompts, finding nearly identical performance aside from parsing inconveniences.

S3-DST (Das et al., 2024): S3-DST constructs prompts on a turn basis, while we performed on an utterance basis. Their approach is not suitable for our approach when dialogue has consecutive utterance or odd numbers of utterances. Therefore, we modified turn-based inference to utterance-based.

All final prompts used are attached to our repository (prompts directory).

D Licenses for artifacts

Datasets TIAGE, SuperDialseg: MIT License, Dialseg711: We were unable to find a licence for this dataset. However, you can find details of the dataset in the original paper(Xu et al., 2021b).

Models Qwen2.5-70B-Instruct: Qwen License, Llama3.1-72B-Instruct: Llama License.