SCIURus: Shared Circuits for Interpretable Uncertainty Representations in Language Models

Abstract

We investigate the mechanistic sources of uncertainty in large language models (LLMs), an area with important implications for language model reliability and trustworthiness. To do so, we conduct a series of experiments designed to identify whether the factuality of generated responses and a model's uncertainty originate in separate or shared circuits in the model architecture. We approach this question by adapting the well-established mechanistic interpretability techniques of causal tracing and two styles of zero-ablation to study the effect of different circuits on LLM generations. Our experiments on eight different models and five datasets, representing tasks predominantly requiring factual recall, provide strong evidence that a model's uncertainty is produced in the same parts of the network that are responsible for the factuality of generated responses.

1 Introduction

Uncertainty quantification (UQ) in large language models (LLMs) for knowledge-intensive tasks (Petroni et al., 2020) remains a critical yet understudied area. Despite achieving human-level performance on various benchmarks, LLMs often struggle with reliable uncertainty estimation, leading to issues such as overconfidence and hallucination (Zhang et al., 2024). This limitation has strong implications for their trustworthiness and safety in high-stakes applications. While recent research has explored verbalized uncertainty in LLMs (Band et al., 2024; Kadavath et al., 2022; Kuhn et al., 2022), significant gaps remain in our understanding of and ability to improve uncertainty quantification. In particular, existing UQ techniques typically provide little insight into the factors responsible for an uncertainty estimate, limiting their usefulness both as practical tools for improving trustworthiness and as methods for understanding uncertainty reasoning. We propose leveraging mechanistic interpretability, an approach focused on characterizing models' internal reasoning mechanisms, to advance our comprehension and enhancement of uncertainty quantification in large language models.

Following Kadavath et al. (2022), to better understand how language models generate uncertainty estimates, we used parametric $\mathbb{P}(\text{IK})$ ("probability that I know") probes—one-layer binary classifiers that are trained to predict the probability that a given LM knows the answer to a given question. As in Kadavath et al. (2022), we trained $\mathbb{P}(\text{IK})$ probes on several datasets and with several models. We then used these probes' predicted confidences as target metrics for causal tracing and zero-ablation, two mechanistic interpretability techniques which identify the components of a model relevant for a task by testing the effect of an intervention made on activations in the model during evaluation. We compared the mechanistic signatures of changes in the model's accuracy and the probe's output to evaluate whether the same circuits were responsible for the answer and the predicted confidence.

In our empirical evaluation, in which we performed leave-one-out and COAR-style zero-ablation for a large range of model–dataset combinations and causal tracing for several more combinations, we found that model accuracy and probe behavior largely responded to the same interventions, indicating that circuits responsible for the factuality of responses and for the model's uncertainty are located in the same parts of the model.

For a group of knowledge-intensive question answering tasks (Petroni et al., 2020), model accuracy and probe confidence are (highly) positively related to one another. We conclude that, at least on recall tasks, a language model's representation of confidence may derive mainly from introspection on its question-answering process, rather than from separate reasoning specific to its uncertainty.

Figure 1: **Left:** $\mathbb{P}(\text{IK})$ probing. The LLM takes a question as input and returns an answer and last-layer activations. Answers are checked for correctness. The probe learns to predict whether the model's answer is correct, based on the last-layer activations. Our analysis uses the probe as a proxy for an LLM's $\mathbb{P}(\text{IK})$. We conduct path patching and zero ablation studies on the probe and the corresponding LLM. **Right:** Locations used in interventions. Path-patching restorations are at `mlp.resid`, `mlp.out`, `layer.out`, and `embed.out`. Zero-ablations are at `attn.out` and `mlp.out`.

To summarize, the key contributions of this paper are as follows:

1. We use mechanistic interpretability and uncertainty quantification tools to investigate the mechanistic sources of uncertainty in large language models. To do so, we use a logistic $\mathbb{P}(\text{IK})$ probe with causal tracing and zero-ablation to perform a hypothesis test to examine whether LLM uncertainty and the factuality of answers generated by an LLM reside in shared or separate circuits within the model.

2. We perform an extensive empirical analysis on eight different models and five recall-intensive datasets, and find evidence that for knowledge recall, uncertainty and the factuality of answers generated by an LLM are handled by the same parts of the model.

2 Related Work

2.1 Uncertainty Quantification in Large Language Models

Uncertainty quantification in large language models is crucial for enhancing reliability, particularly in high-stakes applications. While LLMs provide token probabilities that are often well-calibrated for next-token prediction, practical applications of UQ often require quantifications of the uncertainty in the semantic content of the output (Gawlikowski et al., 2023). Language models' ability to quantify semantic uncertainty remains limited, espe-

cially for open-ended tasks resembling broader real-world applications. Various techniques have been proposed to address this, including both "black-box" and "white-box" methods.

Black-box methods. A well-studied set of techniques involves *multiple sampling and clustering* based on consistency. This can be effective when there is a clear way to cluster responses (Kuhn et al., 2022; Fomicheva et al., 2020; Lin et al., 2024; Ao et al., 2024), but methods for achieving this except on narrow task types remain elusive. Another approach, sometimes called *verbalized uncertainty*, is to ask the model to provide a confidence estimate, either directly in probability terms or using verbal measures (Kadavath et al., 2022), for a factual claim. However, the performance of such methods is often inconsistent.

White-box methods. On multiple-choice questions, the *token probabilities* may yield well-calibrated uncertainty estimates. This can be extended to other questions by converting an open-ended question into a true/false format; this is generally ineffective for smaller models but may show some promise for larger models (Kadavath et al., 2022). Another option is to train a $\mathbb{P}(IK)$ *probe*, a binary classifier predicting whether the model knows the answer. This approach is effective in-distribution but struggles with generalization to out-of-distribution data (Kadavath et al., 2022).

Poor epistemic uncertainty management in LLMs may be related to these models' broader

tendencies to fail to behave like Bayesian reasoners with coherent beliefs: for example, in some cases a model's answer to a question may depend on details in the wording, such as the ordering of key terms (Gao et al., 2024). Other work (Meng et al., 2022) finds that information about a relationship between two entities may be stored separately for the two directions, meaning that a model can be straightforwardly edited to assert (for example) that *Rome contains the Colosseum* but *the Colosseum is in Paris*. Recent work by (Gao et al., 2024) has shown some improvements in sampling-based UQ by perturbing inputs, potentially better accommodating this diffuse knowledge representation.

In this work, we focus on $\mathbb{P}(\text{IK})$ probing, as it provides a potentially interpretable view into a model's self-assessed uncertainty by identifying a specific feature direction within the model. Beyond the introduction of $\mathbb{P}(\text{IK})$ probing itself (Kadavath et al., 2022), little research has been conducted on interpreting the mechanisms behind uncertainty reasoning in LLMs. While most UQ techniques rely on eliciting information about uncertainty through explicit or indirect methods, we still lack an understanding of where this information is represented internally. Analyzing these mechanisms could improve UQ techniques and provide insights into broader epistemic weaknesses in LLMs.

2.2 Mechanistic Interpretability Techniques

"Mechanistic" or "white-box" interpretability aims to understand how neural networks function internally, with a focus on understanding the internal mechanisms and computational processes involved in performing a task.

Mechanistic interpretability (MI) work often revolves around identifying "circuits" responsible for specific tasks (Olah et al., 2020). To achieve this, several intervention techniques have been developed, with tradeoffs in resolution, breadth of applicability, and computational cost.

Ablation, also called *knockout,* involves removing parts of the model, such as layers or neurons, to observe changes in behavior. Such approaches may ablate components of various sizes (individual neurons, attention heads, or entire layers) and in various ways (replacing the output of a component with the zero vector, a dataset mean, or the value from another run). We use zero-ablation for one of our analyses because it is highly general, well-supported in the literature (Wang et al., 2022;

Elhage et al., 2021) and computationally inexpensive, albeit less precise than other methods.

In earlier ablation work, a common approach has been to use "leave-one-out" ablation, i.e., to ablate a single layer on each trial. However, other approaches may perform better in cases where models are very robust to ablations (as is commonly the case for LLMs, especially with larger models). COAR (**co**mponent **a**ttribution via **r**egression) (Shah et al., 2024) is a recently proposed technique which ablates random subsets of components in a model and produces attributions using linear regression. We perform both leave-one-out and COAR ablations and compare the results of the two.

Causal tracing, also called *activation patching*, treats the model's hidden states as a causal graph (Pearl, 2009), which can be analyzed with an approach based on causal mediation analysis (Vig et al., 2020). (We discuss this further in Section 3.) Causal tracing is more precise than ablation, at the cost of higher computational costs and a need for more careful setup.

Path patching (Chan et al., 2022), also based on causal mediation analysis, extends causal tracing by making interventions on individual connections between components, corresponding to the edges of the causal graph (Vig et al., 2020). Because the causal graph has many more edges than nodes, path patching can be very computationally expensive. *Causal scrubbing* (Chan et al., 2022) is a framework for testing mechanistic claims, based on path patching. While impractically slow for many applications, causal scrubbing can be useful as an approach to formalizing interpretability hypotheses.

Probing techniques (Alain and Bengio, 2018) involve training a simple probe (commonly a one-layer binary classifier) on model activations, in order to find places in the model's representation space that represent specific functions of the input. The $\mathbb{P}(\text{IK})$ probes used in this paper are an example of this. Probing can be seen as an "inverse" of *feature visualization* (Voss et al., 2021), which aims to describe the function represented by a specific activation by finding dataset examples which excite that activation.

Feature visualization has shown success in image models but struggles in LLMs, partly due to the problem of superposition (Henighan et al., 2023), in which meaningful features are not aligned with the natural basis of a model's representation space.

Recent work in *dictionary learning with sparse autoencoders* has been used to improve this (Bricken et al., 2023; Lieberum et al., 2024) by attempting to "learn" meaningful features.

2.3 Applications for Interpretable Uncertainty Quantification

Reliable UQ could help to improve trustworthiness by allowing auditing in high-stakes applications of LLMs, such as their use for medical and legal advice (Gawlikowski et al., 2023) and for constructing LLM-based agents (Yang et al., 2023). Interpretability could also help to ensure that UQ techniques remain reliable under distribution shifts, and could contribute to detecting deception (Hendrycks et al., 2021a). Finally, if limitations in UQ are related to broader epistemic weaknesses in LLMs, interpretable UQ could shed light on problems such as hallucination (Zhang et al., 2023; Manakul et al., 2023) and could deepen our understanding of LLM epistemics in general, possibly helping to address problems such as eliciting latent knowledge (Christiano et al., 2024).

3 Methods

Probe Design   We use a $\mathbb{P}(\text{IK})$ probing approach in part because of the difficulty of reasoning about uncertainty using token probabilities. Token probabilities for open-ended questions are a highly imperfect proxy for a model's confidence, because they conflate semantic uncertainty, or uncertainty about content, with syntactic uncertainty, or uncertainty about form (Kuhn et al., 2022). Furthermore, we are most interested in improving uncertainty quantification for fine-tuned chat models, for which token probabilities do not correspond to an underlying distribution over possible text strings.

We construct a dataset on which to train the $\mathbb{P}(\text{IK})$ probe according to the following steps.

1. Perform 32 forward passes for each question on the question-answering task. We used few-shot prompting with 5 examples to ensure that the model answered in the right format.

2. Check whether a model's answers are correct. Specifically, we check whether a model's answer contains any correct answer as a substring, ignoring case.

3. For each question in the dataset, save the number of correct and incorrect answers (implying a "true probability" of the model answering correctly).

4. Also, for each question, save the output of the model's last layer (before the unembedding). This is a vector in $\mathbb{R}^{d_{\text{model}}}$.

The $\mathbb{P}(\text{IK})$ probe is a logistic classifier $p : \mathbb{R}^{d_{\text{model}}} \to (0,1)$ which takes these last layer activations as input and returns the proportion of correct answers. For example, if the model answers a question correctly 47% of the time, the probe should output 0.47 when given the last-layer activations at the last token of that question. We trained with binary cross-entropy loss, using dropout and a triangular learning rate schedule, and used a low learning rate ($\eta = 3 \times 10^{-6}$) as in Kadavath et al. (2022).

Models and Datasets   We studied the following eight models and five datasets:

Table 1: Models studied.

Model	Parameters	Layers
Llama 2 7B	7B	32
Llama 2 7B Chat	7B	32
Llama 2 13B	13B	40
Llama 2 13B Chat	13B	40
Llama 3 8B	8B	32
Llama 3 8B Instruct	8B	32
Gemma 2 2B Instruct	2B	26
Gemma 2 9B Instruct	9B	42

(Llama 2 Team, Meta AI, 2023; Llama 3 Team, Meta AI, 2024; Gemma Team, Google AI, 2024)

Table 2: Datasets studied.

Dataset	
TriviaQA	(Joshi et al., 2017)
WebQuestions	(Berant et al., 2013)
MMLU	(Hendrycks et al., 2021b)
ARC	(Clark et al., 2018)
CounterFact	(Meng et al., 2022)

All the datasets studied, with the partial exception of MMLU, are "recall-intensive" in that they largely depend on recalling factual information learned during training. Based on some preliminary zero-ablation experiments, we believe that models may exhibit separate circuits on some non-recall tasks such as simple synthetic math questions.

ARC includes both the ARC-Easy and ARC-Challenge splits. ARC questions are drawn from

standardized tests; the datasets listed as ARC (Hg) and ARC (Other) correspond, to the "Mercury" test and to a combination of the other 20 tests.

We used the CounterFact dataset exclusively for causal tracing. We reformulated CounterFact prompts as questions to match the format of our other datasets. Because we used the TriviaQA probe for the causal tracing experiment with CounterFact, we also did few-shot prompting with the prompt from TriviaQA.

Causal Tracing. Causal tracing is a causal intervention method that aims to trace and identify important components in neural models for a given task (Meng et al., 2022; Wang et al., 2023), which is a generalization of causal mediation analysis (Vig et al., 2020). In this work, we use causal tracing (Meng et al., 2022) to examine the importance and role of individual circuits and components in LLMs. Specifically, given a specific input q, causal tracing involves three runs: (1) a clean run, in which the original input q is given to the model, which is used to obtain the hidden states of each layer; (2) a corrupted run, in which the input embeddings of certain tokens are corrupted by adding noise or (in this paper) replaced with zeros; and (3) a corrupted-with-restoration run, in which the computation is similar to the corrupted run except that the hidden states at specific locations ℓ in the model are restored using the hidden states obtained from the clean run. By comparing the differences between the output (predicted probabilities) of the clean, corrupted, and restored runs, causal tracing allows the identification of important components in LLMs. That is, if the restored run achieves a similar effect as the clean run, it is likely that the corresponding restored component plays an important role in the model's processing.

Zero-Ablation. Zero-ablation is a mechanistic intervention technique that takes advantage of a transformer's residual structure by treating attention or MLP layers as separable modules which read from and write to the residual stream (Elhage et al., 2021; Nostalgebraist, 2020). A component ℓ (in this paper, an attention or MLP layer) is "ablated" by replacing its output with zero. The drop in model performance on a given task after an intervention removing a component ℓ provides a measure of the importance of ℓ for the task.

Leave-one-out and COAR interventions. Interpretability work using ablation commonly employs leave-one-out style interventions, in which an intervention is applied to a single component at a time. Since larger Transformer LMs are often insensitive to smaller interventions, leave-one-out interventions may struggle to meaningfully affect the target metrics. COAR (Shah et al., 2024) is a recent approach which addresses this by applying ablation interventions to random subsets of model components. In a COAR experiment, ablations are performed for many dataset examples and subsets of components, and linear regression is used to predict the target metrics from a vector of ablated components; the coefficients of the linear predictor then reflect the predicted effect of ablating each component on the target metric. (We refer the reader to Shah et al. (2024) for details.)

4 Uncertainty Introspection: Investigating the Shared Circuits Hypothesis

The aim of this paper is to make progress toward characterizing the mechanistic structures used for UQ in language models. To this end, we propose a theoretical hypothesis ("shared circuits") about the locations of these structures, along with operationalizations which we test experimentally.

Shared Circuits Hypothesis. Uncertainty quantification in question-answering (QA) systems may be carried out in a variety of ways. We hypothesize that language models are capable of expressing uncertainty using **shared circuits** that both solve the underlying question-answering task and output uncertainty information. This contrasts with the possibility that uncertainty quantification emerges in **separate circuits**, either to post-process messy uncertainty signals from question-answering circuits or to do uncertainty calculations of their own.

4.1 Experiment Design: Causal Tracing

On a given question q_i in a dataset $\mathcal{Q}$, for each causal tracing run (clean, corrupted, and restored) we compute the model's sample probability $m(q_i)$ for the correct first token of the answer, and the probe's confidence $p(q_i)$. (We omit the question for the rest of this section for legibility; we consider questions individually.) Locations ℓ where $m_{\text{restored}(\ell)} \approx m_{\text{clean}}$ correspond to parts of the model which are important for solving the QA task;

Figure 2: Representative results of causal tracing, shown for Gemma 2 9B Instruct on three questions in CounterFact. Only `layer.out` locations are shown (plus `embed.out` in the first row). The input embeddings for the starred tokens are replaced with zeros in the corrupted and restored runs.

likewise, locations ℓ where $p_{\text{restored}(\ell)} \approx p_{\text{clean}}$ correspond to parts of the model which are important for the UQ task.[12] In the context of causal tracing, we operationalize the shared circuits hypothesis in the claim that m_{restored} can be predicted from p_{restored} by interpolating between the clean and corrupted values: for example, if the model's correct-token probability on a restored run is halfway between the values from the clean and corrupted runs, then the probe's confidence should also be halfway between the clean and corrupted runs.

Specifically, for each question $q_i \in \mathcal{Q}$, we claim that the linear predictor $\hat{m}_{\text{restored}}$ defined by

$$\frac{\hat{m}_{\text{restored}(\ell)} - m_{\text{corrupted}}}{m_{\text{clean}} - m_{\text{corrupted}}} = \frac{p_{\text{restored}(\ell)} - p_{\text{corrupted}}}{p_{\text{clean}} - p_{\text{corrupted}}}$$

explains most of the variance in m_{restored} (i.e., has a high coefficient of determination R^2). As a (somewhat weak) formalization of this, we attempt to reject the null hypothesis

H_0 : R^2 is no greater than expected under random permutations of the set of locations ℓ.

4.2 Experiment Design: Zero-Ablation

We also test the shared circuits hypothesis via zero-ablation on layers. Here, because we are interested in multi-token answers, we define $m(q_i)$ as the probability of a correct answer sampled by the model when prompted on the question $q_i \in \mathcal{Q}$, and $p(q_i)$ as the probe output on that question. Taking the means over $\mathcal{Q}$, we can compare changes in the accuracy of the model $\overline{m}$ and the average output of the probe $\overline{p}$.

4.2.1 Leave-One-Out Ablation

Under the shared circuits hypothesis, the change in the probe output from ablation $|\overline{p}_{\text{ablated}(\ell)} - p_{\text{clean}}|$ is large when the change in model accuracy $|\overline{m}_{\text{ablated}(\ell)} - m_{\text{clean}}|$ is large. Concretely, we claim that the predictor $\hat{\overline{m}}$ defined by

$$m_{\text{clean}} - \hat{\overline{m}}_{\text{ablated}(\ell)} = |\overline{p}_{\text{ablated}(\ell)} - p_{\text{clean}}|$$

explains most of the variance in $\overline{m}_{\text{ablated}}$ (has a high R^2), and attempt to reject the null hypothesis

H_0 : R^2 is no greater than expected under random permutations of the set of layers ℓ.

---

[1]Although note that the converse is not necessarily true; see Appendix 5 for details.

[2]Here, $\mathbb{P}(\text{corr})_{\text{restored}(\ell)}$ and $\mathbb{P}(\text{IK})_{\text{restored}(\ell)}$ represent the correct token probability and p probe output for a run with the hidden state restored at location ℓ in the model; notation is likewise for clean and corrupted runs.

Figure 3: **Top.** Results of leave-one-out style zero ablation for Llama 3 8B Instruct on five different datasets. Circle, triangle, and small X markers represent MLP ablations, attention ablations, and clean runs respectively. Warmer colors represent earlier layers. **Bottom.** Coefficients for zero ablation with COAR, for Gemma 2 9B Instruct on four different datasets. Circle and triangle markers represent MLP and attention respectively. Warmer colors represent earlier layers.

4.2.2 COAR

COAR constructs least-squares predictors for model accuracy and probe output based on vectors of ablated components, in which the coefficient corresponding to a component ℓ represents the expected effect of ablating ℓ. Under the shared circuits hypothesis, the predictors $\mathbf{w}_m$ and $\mathbf{w}_p$ for the model accuracy and probe output should be similar. Concretely, we attempt to reject the null hypothesis H_0 : *The correlation between $\mathbf{w}_m$ and $\mathbf{w}_p$ is no greater than expected under random permutations of the set of layers ℓ.*

4.3 Testing the Hypothesis

Causal Tracing. We performed causal tracing with all eight models on a random sample of 100 questions from the CounterFact dataset (Meng et al., 2022). In the final analysis, we considered only questions which the model was somewhat able to answer ($m_{\text{clean}} > 0.05$), because the restored performance was almost universally near zero otherwise, with very little signal (that is, if the model was unable to answer a question, a causal tracing intervention generally did not change that). We used the probe and few-shot prompt for TriviaQA. Across this sample, the predictors $\hat{m}_{\text{restored}}$ generally estimated m_{restored} well, with $R^2 > 0.6$ in most cases cases. For each question q_i, we tested the null

hypothesis (1) by sampling 1,000 permutations: specifically, we shuffled the values of $m_{\text{restored}(\ell)}$ independently for the `mlp.out`, `mlp.resid`, and `layer.out`/`embed.out` locations, to exclude the explanation that the predictor works well because the `mlp.out` and `mlp.resid` states each carry less information than `layer.out`. In almost all cases (see Table 3), we reject H_0 with $p < 0.05$.

Model	$p < 0.05$	$p \geq 0.05$
Llama 2 7B	55	0
Llama 2 7B Chat	51	0
Llama 3 8B	53	1
Llama 3 8B Instruct	51	2
Llama 2 13B	51	3
Llama 2 13B Chat	45	4
Gemma 2 2B Instruct	47	1
Gemma 2 9B Instruct	50	0

Table 3: Number of occurrences of p-values for causal tracing.

Based on manual inspection (see graphs in the Supplementary Materials), we conclude that $R^2 < 1$ both due to small discrepancies between UQ and QA circuitry and due to nonlinearity in the UQ/QA relationship. In the cases studied, the model is more resilient than the probe: that is, interventions

Figure 4: **Left and center.** Predicting the correct-token probability m given the probe output p, for Gemma 2 9B Instruct (left) and Llama 2 7B (center). The black and red X (small, top-right and bottom-left) show the clean and corrupted runs; all others show restored runs. Yellow points are later in the sequence. The grey line shows the predictor $\hat{m}$. **Right.** Values of R^2 for the causal tracing predictor. "$<$" signifies cases where $R^2 < -1$ (which is possible because the predictor is not a linear-regression line).

generally have a greater effect on the probe than the model (creating the convex shape in Figure 3, left); this depends to some extent on the model architecture. In some cases, when the probe is confidently wrong (see Figure 2, right), the probe may be following the path for the model's (incorrect) highest-probability token.

Zero-Ablation (Leave-One-Out). We performed 500 ablation trials each with eight models across five question-answering datasets. Across this sample, the predictors $\hat{\overline{m}}_{\text{ablated}}$ generally estimated $\overline{m}_{\text{ablated}}$ better than chance, with a median of $R^2 = 0.33$. For each model–dataset combination, we tested the null hypothesis (2) by sampling 10,000 permutations. As with the causal tracing analysis, we shuffled attention and MLP layer interventions independently, to exclude the explanation that one type of layer was more important than the other in a way not specific to the QA and UQ tasks. We reject the null hypothesis with $p < 0.05$ in 36 out of 38 cases, and $p < 0.0001$ in 31 out of 38 cases.

In many cases, the model's uncertainty representation plays particularly nicely with zero-ablation, remaining calibrated on average even after an intervention: using the same statistical framework as above, the very simple predictor $\hat{\overline{m}}_{\text{ablated}} = \overline{p}_{\text{ablated}}$ does better than expected under random permutations in 27 out of 38 cases (at $p < 0.05$).[3]

While other explanations may be possible, one interpretation of these results is that a given component makes a nonzero contribution to the model's uncertainty representation if and only if it can also contribute information about the answer.

Zero-Ablation (COAR). We performed 2000 COAR trials each with all models and four datasets.[4] For each trial, the probability of ablating any given component was set at $\alpha = 0.2$. We reject the null hypothesis with $p < 0.05$ in all but one case. Particularly strong correlations were present for the Gemma models; this may be related to our choice of α and these models' robustness to interventions in the leave-one-out experiments.

5 Discussion and Conclusion

The results of the causal tracing and zero-ablation analyses presented in the previous section broadly support the shared circuits hypothesis, implying that—across the setups we considered—the sets of model components used for question-answering and uncertainty quantification were largely, albeit not entirely, the same. This suggests that $\mathbb{P}(\text{IK})$ probing may be a viable way of eliciting introspective, interpretable uncertainty estimates. Based on these findings, further research could analyze the mechanisms responsible for $\mathbb{P}(\text{IK})$ estimates in greater detail or apply $\mathbb{P}(\text{IK})$ probing as an interpretability tool to study phenomena such as hallucination in LLMs and meaningfully contribute to technical AI governance.

---

[3]If R^2 is the fraction of the variance in $\overline{m}_{\text{ablated}}$ explained by $\hat{\overline{m}}_{\text{ablated}} = \overline{p}_{\text{ablated}}$, we reject the null hypothesis R^2 *is no greater than expected under random permutations of the set of layers* at $p < 0.05$ in 27/38 cases.

[4]We excluded MMLU because of computational resource constraints.

Limitations

Causal tracing and zero-ablation, like many interpretability techniques, yield results which can imperfectly reflect the contributions of model internals to a task. In particular:

Zero-ablation. We chose to ablate activations in the model with zeros. While the zero vector is far from an arbitrary choice, especially given its relevance to dropout and the additive residual structure of a transformer, this approach may lack specificity. For example, zero-ablating an early or late MLP layer sometimes severely damages a model's ability to produce coherent language in general, so accuracies from ablation do not necessarily correspond to the flow of question-specific information through the model. Approaches such as causal scrubbing (Chan et al., 2022) avoid this limitation but are generally more computationally expensive.

Causal tracing. The "path" through the model identified comprises, to a first approximation, the set of points in the model at which *all* information relevant to the task is present. As such, when information relevant to a question passes along multiple paths in parallel, it may be that no individual path shows a substantial difference between the restored and baseline conditions. For example, in the question in Fig. 2 (center), restoring the input embedding for any one token of "Google Street View" without the others has little effect on the model.

References

Guillaume Alain and Yoshua Bengio. 2018. Understanding intermediate layers using linear classifier probes.

Shuang Ao, Stefan Rueger, and Advaith Siddharthan. 2024. Css: Contrastive semantic similarities for uncertainty quantification of llms.

Neil Band, Xuechen Li, Tengyu Ma, and Tatsunori Hashimoto. 2024. Linguistic calibration of long-form generations. In *Forty-first International Conference on Machine Learning*.

Jonathan Berant, Andrew Chou, Roy Frostig, and Percy Liang. 2013. Semantic parsing on Freebase from question-answer pairs. In *Proceedings of the 2013 Conference on Empirical Methods in Natural Language Processing*, pages 1533–1544, Seattle, Washington, USA. Association for Computational Linguistics.

Trenton Bricken, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermyn, Tom Conerly, Nicholas L. Turner, Cem Anil, Carson Denison, Amanda Askell, Robert Lasenby, Yifan Wu, Shauna Kravec, Nicholas Schiefer, Tim Maxwell, Nicholas Joseph, Alex Tamkin, Karina Nguyen, Brayden McLean, Josiah E. Burke, Tristan Hume, Shan Carter, Tom Henighan, and Chris Olah. 2023. Towards monosemanticity: Decomposing language models with dictionary learning.

Lawrence Chan, Adrià Garriga-Alonso, Nicholas Goldowsky-Dill, Ryan Greenblatt, Jenny, Ansh Radhakrishnan, Buck Shlegeris, and Nate Thomas. 2022. Causal scrubbing: A method for rigorously testing interpretability hypotheses.

Paul Christiano, Mark Xu, and Ajeya Cotra. 2024. Eliciting latent knowledge.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. 2018. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv:1803.05457v1*.

Nelson Elhage, Neel Nanda, Catherine Olsson, Tom Henighan, Nicholas Joseph, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, Nova DasSarma, Dawn Drain, Deep Ganguli, Zac Hatfield-Dodds, Danny Hernandez, Andy Jones, Jackson Kernion, Liane Lovitt, Kamal Ndousse, Dario Amodei, Tom Brown, Jack Clark, Jared Kaplan, Sam McCandlish, and Chris Olah. 2021. A mathematical framework for transformer circuits. *Transformer Circuits Thread*. Https://transformer-circuits.pub/2021/framework/index.html.

Marina Fomicheva, Shuo Sun, Lisa Yankovskaya, Frédéric Blain, Francisco Guzmán, Mark Fishel, Nikolaos Aletras, Vishrav Chaudhary, and Lucia Specia. 2020. Unsupervised quality estimation for neural machine translation. *Transactions of the Association for Computational Linguistics*, 8:539–555.

Xiang Gao, Jiaxin Zhang, Lalla Mouatadid, and Kamalika Das. 2024. Spuq: Perturbation-based uncertainty quantification for large language models.

Jakob Gawlikowski, Cedrique Rovile Njieutcheu Tassi, Mohsin Ali, Jongseok Lee, Matthias Humt, Jianxiang Feng, Anna Kruspe, Rudolph Triebel, Peter Jung, Ribana Roscher, Muhammad Shahzad, Wen Yang, Richard Bamler, and Xiao Xiang Zhu. 2023. A survey of uncertainty in deep neural networks. *Artificial Intelligence Review*, 56(1):1513–1589.

Gemma Team, Google AI. 2024. Gemma 2: Improving open language models at a practical size.

Dan Hendrycks, Collin Burns, Steven Basart, Andrew Critch, Jerry Li, Dawn Song, and Jacob Steinhardt. 2021a. Aligning ai with shared human values. *Proceedings of the International Conference on Learning Representations (ICLR)*.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021b. Measuring massive multitask language understanding. *Proceedings of the International Conference on Learning Representations (ICLR).*

Tom Henighan, Shan Carter, Tristan Hume, Nelson Elhage, Robert Lasenby, Stanislav Fort, Nicholas Schiefer, and Christopher Olah. 2023. Superposition, memorization, and double descent.

Mandar Joshi, Eunsol Choi, Daniel Weld, and Luke Zettlemoyer. 2017. TriviaQA: A large scale distantly supervised challenge dataset for reading comprehension. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, page 1601–1611, Vancouver, Canada. Association for Computational Linguistics.

Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, Scott Johnston, Sheer El-Showk, Andy Jones, Nelson Elhage, Tristan Hume, Anna Chen, Yuntao Bai, Sam Bowman, Stanislav Fort, Deep Ganguli, Danny Hernandez, Josh Jacobson, Jackson Kernion, Shauna Kravec, Liane Lovitt, Kamal Ndousse, Catherine Olsson, Sam Ringer, Dario Amodei, Tom Brown, Jack Clark, Nicholas Joseph, Ben Mann, Sam McCandlish, Chris Olah, and Jared Kaplan. 2022. Language models (mostly) know what they know.

Lorenz Kuhn, Yarin Gal, and Sebastian Farquhar. 2022. Semantic uncertainty: Linguistic invariances for uncertainty estimation in natural language generation. In *Proceedings of the Eleventh International Conference on Learning Representations.*

Tom Lieberum, Senthooran Rajamanoharan, Arthur Conmy, Lewis Smith, Nicolas Sonnerat, Vikrant Varma, János Kramár, Anca Dragan, Rohin Shah, and Neel Nanda. 2024. Gemma scope: Open sparse autoencoders everywhere all at once on gemma 2.

Zhen Lin, Shubhendu Trivedi, and Jimeng Sun. 2024. Generating with confidence: Uncertainty quantification for black-box large language models. (arXiv:2305.19187). ArXiv:2305.19187 [cs, stat].

Llama 2 Team, Meta AI. 2023. Llama 2: Open foundation and fine-tuned chat models.

Llama 3 Team, Meta AI. 2024. The llama 3 herd of models.

Potsawee Manakul, Adian Liusie, and Mark Gales. 2023. SelfCheckGPT: Zero-resource black-box hallucination detection for generative large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 9004–9017, Singapore. Association for Computational Linguistics.

Kevin Meng, David Bau, Alex J Andonian, and Yonatan Belinkov. 2022. Locating and editing factual associations in GPT. In *Advances in Neural Information Processing Systems.*

Nostalgebraist. 2020. Interpreting GPT: The logit lens.

Chris Olah, Nick Cammarata, Ludwig Schubert, Gabriel Goh, Michael Petrov, and Shan Carter. 2020. Zoom in: An introduction to circuits. *Distill.* Https://distill.pub/2020/circuits/zoom-in.

Judea Pearl. 2009. *Causality: Models, Reasoning and Inference*, 2nd edition. Cambridge University Press, USA.

Fabio Petroni, Aleksandra Piktus, Angela Fan, Patrick S. H. Lewis, Majid Yazdani, Nicola De Cao, James Thorne, Yacine Jernite, Vassilis Plachouras, Tim Rocktäschel, and Sebastian Riedel. 2020. KILT: a benchmark for knowledge intensive language tasks. *CoRR*, abs/2009.02252.

Harshay Shah, Andrew Ilyas, and Aleksander Madry. 2024. Decomposing and Editing Predictions by Modeling Model Computation.

Jesse Vig, Sebastian Gehrmann, Yonatan Belinkov, Sharon Qian, Daniel Nevo, Yaron Singer, and Stuart Shieber. 2020. Investigating gender bias in language models using causal mediation analysis. In *Advances in Neural Information Processing Systems*, volume 33, pages 12388–12401. Curran Associates, Inc.

Chelsea Voss, Nick Cammarata, Gabriel Goh, Michael Petrov, Ludwig Schubert, Ben Egan, Swee Kiat Lim, and Chris Olah. 2021. Visualizing weights. *Distill.* Https://distill.pub/2020/circuits/visualizing-weights.

Kevin Ro Wang, Alexandre Variengien, Arthur Conmy, Buck Shlegeris, and Jacob Steinhardt. 2022. Interpretability in the wild: A circuit for indirect object identification in GPT-2 Small. In *Proceedings of the Eleventh International Conference on Learning Representations.*

Kevin Ro Wang, Alexandre Variengien, Arthur Conmy, Buck Shlegeris, and Jacob Steinhardt. 2023. Interpretability in the wild: a circuit for indirect object identification in GPT-2 small. In *The Eleventh International Conference on Learning Representations.*

Hui Yang, Sifu Yue, and Yunzhong He. 2023. Autogpt for online decision making: Benchmarks and additional opinions.

Muru Zhang, Ofir Press, William Merrill, Alisa Liu, and Noah A. Smith. 2024. How language model hallucinations can snowball. In *Forty-first International Conference on Machine Learning.*

Yue Zhang, Yafu Li, Leyang Cui, Deng Cai, Lemao Liu, Tingchen Fu, Xinting Huang, Enbo Zhao, Yu Zhang, Yulong Chen, Longyue Wang, Anh Tuan Luu, Wei

Bi, Freda Shi, and Shuming Shi. 2023. Siren's song in the ai ocean: A survey on hallucination in large language models.

A   Reproducibility

Code to reproduce our results can be found at

https://anonymous.4open.science/r/sciurus_anonymized-E434/

B   Licenses for Models and Datasets

Models:

- Llama 2 is licensed under the Llama 2 Community License Agreement, available at https://ai.meta.com/llama/license/.

- Llama 3 is licensed under the Meta Llama 3 License, available at https://llama.meta.com/llama3/license/.

- Gemma 2 is licensed under the Gemma Terms of Use, available at https://ai.google.dev/gemma/terms.

Datasets:

- TriviaQA is licensed under the Apache License 2.0, available at https://www.apache.org/licenses/LICENSE-2.0.

- WebQuestions is licensed under the Creative Commons Attribution 4.0 International License, available at https://creativecommons.org/licenses/by/4.0/.

- MMLU (Massive Multitask Language Understanding) is licensed under the MIT License, available at https://opensource.org/licenses/MIT.

- ARC (AI2 Reasoning Challenge) is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License, available at https://creativecommons.org/licenses/by-sa/4.0/.

- CounterFact is licensed under the MIT License, available at https://opensource.org/licenses/MIT.

C Model and Probe Performance

Model	Dataset	Model accuracy	Probe accuracy (bal.)	ECE
Llama 2 7B	TriviaQA	0.6006	0.7787	0.0342
	WebQuestions	0.4016	0.6674	0.0320
	MMLU	0.3984	0.6571	0.0265
	ARC (Mercury)	0.5845	0.6731	0.0363
	ARC (Other)	0.6260	0.7011	0.0327
Llama 2 7B Chat	TriviaQA	0.5850	0.7819	0.0315
	WebQuestions	0.4343	0.7051	0.0213
	MMLU	0.4688	0.6701	0.0272
	ARC (Mercury)	0.6973	0.6375	0.0294
	ARC (Other)	0.7632	0.6719	0.0395
Llama 3 8B	TriviaQA	0.6582	0.7026	0.0366
	WebQuestions	0.4158	0.7034	0.0405
	MMLU	0.6055	0.7455	0.0171
	ARC (Mercury)	0.8496	0.6035	0.0459
	ARC (Other)	0.8423	0.5991	0.0313
Llama 3 8B Instruct	TriviaQA	0.6509	0.7037	0.0397
	WebQuestions	0.4460	0.7213	0.0530
	MMLU	0.6445	0.7201	0.0300
	ARC (Mercury)	0.8779	0.6014	0.0495
	ARC (Other)	0.8569	0.6658	0.0362
Llama 2 13B	TriviaQA	0.6680	0.6938	0.0324
	WebQuestions	0.4346	0.6948	0.0403
	MMLU	0.4958	0.7252	0.0284
	ARC (Mercury)	0.7290	0.5010	0.1029
	ARC (Other)	0.7764	0.6691	0.0239
Llama 2 13B Chat	TriviaQA	0.6377	0.7020	0.0414
	WebQuestions	0.4468	0.7202	0.0306
	MMLU	0.4902	0.6913	0.0208
	ARC (Mercury)	0.7134	0.6395	0.0475
	ARC (Other)	0.7637	0.5973	0.0192
Gemma 2 2B Instruct	TriviaQA	0.4180	0.7221	0.0136
	WebQuestions	0.2910	0.6501	0.0517
	MMLU	0.4617	0.6803	0.0344
	ARC (Mercury)	0.7876	0.6310	0.0228
	ARC (Other)	0.7705	0.6051	0.0612
Gemma 2 9B Instruct	TriviaQA	0.6392	0.7374	0.0306
	WebQuestions	0.3579	0.7264	0.0529
	ARC (Other)	0.9126	0.5786	0.0354

Table 4: Model performance metrics

D Full Results for Zero-Ablation

Figure 5: Results of zero-ablation for eight models and five datasets. Circle, triangle, and X markers represent MLP ablations, attention ablations, and clean runs respectively. Warmer colors represent earlier layers. Error bars for individual points are omitted for legibility, but std. err. < 0.032 in all cases (by the bounds on p and m).

Figure 6: *(continued)* Results of zero-ablation for eight models and five datasets. Circle, triangle, and X markers represent MLP ablations, attention ablations, and clean runs respectively. Warmer colors represent earlier layers. Error bars for individual points are omitted for legibility, but std. err. < 0.032 in all cases (by the bounds on p and m).

E   Full Results for COAR

Figure 7: COAR coefficients for zero-ablation for eight models and four datasets. Circle and triangle markers represent MLP and attention ablations respectively. Warmer colors represent earlier layers. Error bars for individual points are omitted for legibility. The two values for R^2_{COAR} are the fraction of variance in m and p explained by the COAR prediction from the set of ablations.

Figure 8: *(continued)* COAR coefficients for zero-ablation for eight models and four datasets. Circle and triangle markers represent MLP and attention ablations respectively. Warmer colors represent earlier layers. Error bars for individual points are omitted for legibility. The two values for R^2_{COAR} are the fraction of variance in m and p explained by the COAR prediction from the set of ablations.

F Computational Resources

This project has used approximately 1200 GPU-hours of computation time on an academic cluster, mainly on RTX8000 GPUs with 48 GB of memory, including approximately 600 GPU-hours for results used directly in this paper. Results for individual model/dataset combinations can be reproduced independently; for example, the code to produce the TriviaQA / Llama 3 8B Instruct results ran in approximately 20 GPU-hours.

G Ethics Statement

This paper intends to advance the areas of interpretability and uncertainty quantification for language models, with the primary aim of making language models more reliable and more trustworthy. We expect these research directions in general to reduce societal risks from machine learning (for example, by allowing for warning signals in situations where a model might be lying or making a dangerous mistake). Nevertheless, since reliability work also makes systems more useful, some caution is warranted: for example, users might be tempted to deploy the resultant more-reliable systems in higher-stakes contexts in which tail risks from failures are greater.

The humanoid and sciuroid robots in Fig. 1 were created using DALL-E 3.