DeepTOP: Deep Threshold-Optimal Policy for MDPs and RMABs

Abstract

We consider the problem of learning the optimal threshold policy for control problems. Threshold policies make control decisions by evaluating whether an element of the system state exceeds a certain threshold, whose value is determined by other elements of the system state. By leveraging the monotone property of threshold policies, we prove that their policy gradients have a surprisingly simple expression. We use this simple expression to build an off-policy actor-critic algorithm for learning the optimal threshold policy. Simulation results show that our policy significantly outperforms other reinforcement learning algorithms due to its ability to exploit the monotone property.

In addition, we show that the Whittle index, a powerful tool for restless multi-armed bandit problems, is equivalent to the optimal threshold policy for an alternative problem. This observation leads to a simple algorithm that finds the Whittle index by learning the optimal threshold policy in the alternative problem. Simulation results show that our algorithm learns the Whittle index much faster than several recent studies that learn the Whittle index through indirect means.

1 Introduction

This paper considers a class of control policies, called *threshold policies*, that naturally arise in many practical problems. For example, a smart home server may only turn on the air conditioner when the room temperature exceeds a certain threshold, and a central bank may only raise the interest rate when inflation exceeds a certain threshold. For such problems, finding the optimal control policies can be reduced to finding the appropriate thresholds given other factors of the system, such as the number of people in the room in the smart home server scenario or the unemployment rate and the current interest rate in the central bank scenario.

An important feature of threshold policies is that their actions are monotone. For example, if a smart home server would turn on the air conditioner at a certain temperature, then, all other factors being equal, the server would also turn on the air conditioner when the temperature is even higher. By leveraging this monotone property, an algorithm aiming to learn the optimal threshold can potentially be much more efficient than generic reinforcement learning algorithms seeking to learn the optimal action at different points of temperature separately.

In order to design an efficient algorithm for learning the optimal threshold policy, we first formally define a class of Markov decision processes (MDPs) that admit threshold policies and its objective function. The optimal threshold policy is then the one that maximizes the objective function. However, the objective function involves an integral over a continuous range, which makes it infeasible to directly apply standard tools, such as backward-propagation in neural networks, to perform gradient updates.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Surprisingly, we show that, by leveraging the monotone property of threshold policies, the gradient of the objective function has a very simple expression. Built upon this expression, we propose Deep Threshold-Optimal Policy (DeepTOP), a model-free actor-critic deep reinforcement learning algorithm that finds the optimal threshold policies. We evaluate the performance of DeepTOP by considering three practical problems, an electric vehicle (EV) charging problem that determines whether to charge an EV in the face of unknown fluctuations of electricity price, an inventory management problem that determines whether to order for goods in the face of unknown seasonal demands, and a make-to-stock problem for servicing jobs with different sizes. For all problems, DeepTOP significantly outperforms other state-of-the-art deep reinforcement learning algorithms due to its ability to exploit the monotone property.

We also study the notoriously hard restless multi-armed bandit (RMAB) problem. We show that the Whittle index policy, a powerful tool for RMABs, can be viewed as an optimal threshold policy for an alternative problem. Based on this observation, we define an objective function for the alternative problem, of which the Whittle index is the maximizer. We again show that the gradient of the objective function has a simple expression. This simple expression allows us to extend DeepTOP for the learning of the Whittle index. We compare this DeepTOP extension to three recently proposed algorithms that seek to learn the optimal index policies through other indirect properties. Simulation results show that the DeepTOP extension learns much faster because it directly finds the optimal threshold policy.

The rest of the paper is organized as follows. Section 2 defines the MDP setting and threshold policies. We present the DeepTOP algorithm for MDP in Section 3. We then discuss how the Whittle index policy for RMABs can be viewed as a threshold policy in Section 4 and develop a DeepTOP extension for learning it in Section 5. We show DeepTOP's performance results for MDPs and RMABs in Section 6, and give related works in Section 7 before concluding.

2 Threshold Policies for MDPs

Consider an agent controlling a stochastic environment $\mathcal{E}$ described as an MDP $\mathcal{E} = (\mathcal{S}, \mathcal{A}, \mathcal{R}, \mathcal{P}, \gamma)$, with state space $\mathcal{S}$, binary action space $\mathcal{A} := \{0, 1\}$, reward function $\mathcal{R} : \mathcal{S} \times \mathcal{A} \rightarrow \Omega$, transition dynamics $\mathcal{P} : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \rightarrow \mathbb{R}$, and discount factor $\gamma \in [0, 1)$, where $\mathbb{R}$ is the set of real numbers and Ω is the set of random variables. At each timestep t, the agent picks an action $a_t \in \mathcal{A}$ for the current state s_t. The state $s_t \in \mathcal{S} = \mathbb{R} \times \mathcal{V}$ has two components: a scalar state $\lambda_t \in \mathbb{R}$, and a vector state $v_t \in \mathcal{V}$, where $\mathcal{V}$ is a discrete set of vectors. We assume the environment state is fully observable. Given the state-action pair (s_t, a_t), the MDP generates a reward r_t following the unknown random variable $\mathcal{R}(s_t, a_t)$, and a random next state $s_{t+1} = (\lambda_{t+1}, v_{t+1})$ following the unknown distribution $\mathcal{P}$. We use $\bar{r}(\lambda, v, a) := E[\mathcal{R}((\lambda, v), a)]$ to denote the unknown expected one-step reward that can be obtained for the state-action pair (λ, v, a).

A threshold policy is one that defines a threshold function $\mu : \mathcal{V} \rightarrow \mathbb{R}$ mapping each vector state to a real number. The policy then deterministically picks $a_t = \mathbb{1}(\mu(v_t) > \lambda_t)$, where $\mathbb{1}(\cdot)$ is the indicator function. There are many applications where it is natural to consider threshold policies and we discuss some of them below.

Example 1. *Consider the problem of charging electric vehicles (EV). When an EV arrives at a charging station, it specifies its demands for charge and a deadline upon which it will leave the station. The electricity price changes over time following some random process. The goal of the operator is to fulfill the EV's requirement with minimum cost. In this problem, we can model the system by letting the scalar state λ_t be the current electricity price and the vector state v_t be the remaining charge and time to deadline of the EV. For this problem, it is natural to consider a threshold policy that defines a threshold $\mu(v_t)$ as the highest price the operator is willing to pay to charge the EV under vector state v_t. The operator only charges the vehicle, i.e., chooses $a_t = 1$, if $\lambda_t < \mu(v_t)$.*

Example 2. *Consider the problem of warehouse management. A warehouse stores goods waiting to be sold. When the number of stored goods exceeds the demand, then there is a holding cost for each unsold good. On the other hand, if the number of stored goods is insufficient to fulfill the demand, then there is a cost of lost sales. The goal of the manager is to decide when to place orders so as to minimize the total cost. In this problem we can let the scalar state λ_t be the current inventory and let the vector state v_t be the vector of all factors, such as upcoming holidays, that can influence future demands. It is natural to consider a threshold policy where the manager only places a new order if the current inventory λ_t falls below a threshold $\mu(v_t)$ based on the current vector state v_t.*

Example 3. *Consider a smart home server that controls the air conditioner. Let λ_t be $-$(current temperature) and v_t be the time of the day and the number of people in the house. The server should turn on the air conditioner only if the temperature exceeds some threshold determined by v_t, or, equivalently, $\lambda_t < \mu(v_t)$.*

Given a threshold policy with threshold function $\mu(\cdot)$, we can define the corresponding action-value function by $Q_\mu(\lambda, v, a)$. Let $\rho_\mu(\lambda', v', \lambda, v)$ be the discounted state distribution when the initial state is (λ, v) under the threshold policy to a visited state (λ', v'). When the initial state is (λ, v), the expected discounted reward under the policy is

$$Q_\mu\big(\lambda, v, \mathbb{1}(\mu(v) > \lambda)\big) = \sum_{v' \in \mathcal{V}} \int_{\lambda' = -M}^{\lambda' = +M} \rho_\mu(\lambda', v', \lambda, v) \bar{r}(\lambda', v', \mathbb{1}(\mu(v') > \lambda')). \tag{1}$$

Let M be a sufficiently large constant such that $\lambda_t \in [-M, +M]$ for all t. Our goal is to learn the optimal threshold function $\mu^\phi(v)$ parametrized by a vector ϕ that maximizes the objective function

$$K(\mu^\phi) := \int_{\lambda = -M}^{\lambda = +M} \sum_{v \in \mathcal{V}} Q_{\mu^\phi}\big(\lambda, v, \mathbb{1}(\mu^\phi(v) > \lambda)\big) d\lambda. \tag{2}$$

3 Deep Threshold Optimal Policy for MDPs

In this section, we present a deep threshold optimal policy (DeepTOP) for MDPs that finds the optimal ϕ for maximizing $K(\mu^\phi)$.

3.1 Threshold Policy Gradient Theorem for MDPs

In order to design DeepTOP, we first study the gradient $\nabla_\phi K(\mu^\phi)$. At first glance, computing $\nabla_\phi K(\mu^\phi)$ looks intractable since it involves an integral over $\lambda \in [-M, +M]$. However, we establish the following threshold policy gradient theorem that shows the surprising result that $\nabla_\phi K(\mu^\phi)$ has a simple expression.

Theorem 1. *Given the parameter vector ϕ, if all vector states $v \in \mathcal{V}$ have distinct values of $\mu^\phi(v)$, then,*

$$\nabla_\phi K(\mu^\phi) = \sum_{v \in \mathcal{V}} \Big(Q_{\mu^\phi}(\mu^\phi(v), v, 1) - Q_{\mu^\phi}(\mu^\phi(v), v, 0)\Big) \nabla_\phi \mu^\phi(v). \tag{3}$$

Proof. Given ϕ, we number all states in $\mathcal{V}$ such that $\mu^\phi(v^1) > \mu^\phi(v^2) > \dots$. Let $\mathbb{M}^0 = +M$, $\mathbb{M}^n = \mu^\phi(v^n)$, for all $1 \le n \le |\mathcal{V}|$, and $\mathbb{M}^{|\mathcal{V}|+1} = -M$. Also, let $\mathbb{V}^n$ be the subset of states $\{v | \mu^\phi(v) > \mathbb{M}^n\} = \{v^1, v^2, \dots, v^{n-1}\}$.

Now, consider the interval $(\mathbb{M}^{n+1}, \mathbb{M}^n)$ for some n. Notice that, for all $\lambda \in (\mathbb{M}^{n+1}, \mathbb{M}^n)$, $\mathbb{1}(\mu^\phi(v) > \lambda) = 1$ if and only if $v \in \mathbb{V}^{n+1}$. In other words, for any vector state v, the threshold policy would take the same action under all $\lambda \in (\mathbb{M}^{n+1}, \mathbb{M}^n)$, and we use $\pi^{n+1}(v)$ to denote this action. We then have

$$\nabla_\phi K(\mu^\phi) = \int_{\lambda = -M}^{\lambda = +M} \sum_{v \in \mathcal{V}} Q_{\mu^\phi}\big(\lambda, v, \mathbb{1}(\mu^\phi(v) > \lambda)\big) d\lambda = \sum_{v \in \mathcal{V}} \nabla_\phi \int_{\lambda = -M}^{\lambda = +M} Q_{\mu^\phi}(\lambda, v, \mathbb{1}(\mu^\phi(v) > \lambda)) d\lambda$$

$$= \sum_{v \in \mathcal{V}} \sum_{n=0}^{|\mathcal{V}|} \nabla_\phi \int_{\lambda = \mathbb{M}^{n+1}}^{\lambda = \mathbb{M}^n} Q_{\mu^\phi}(\lambda, v, \pi^{n+1}(v)) d\lambda$$

$$= \sum_{v \in \mathcal{V}} \sum_{n=0}^{|\mathcal{V}|} \Big(Q_{\mu^\phi}(\mathbb{M}^n, v, \pi^{n+1}(v)) \nabla_\phi \mathbb{M}^n - Q_{\mu^\phi}(\mathbb{M}^{n+1}, v, \pi^{n+1}(v)) \nabla_\phi \mathbb{M}^{n+1}\Big) \quad \text{(Leibniz integral rule)}$$

$$= \sum_{v \in \mathcal{V}} \sum_{n=1}^{|\mathcal{V}|} \Big(Q_{\mu^\phi}(\mu^\phi(v^n), v, \mathbb{1}(v \in \mathbb{V}^{n+1})) - Q_{\mu^\phi}(\mu^\phi(v^n), v, \mathbb{1}(v \in \mathbb{V}^n))\Big) \nabla_\phi \mu^\phi(v^n)$$

$$= \sum_{v \in \mathcal{V}} \Big(Q_{\mu^\phi}(\mu^\phi(v), v, 1) - Q_{\mu^\phi}(\mu^\phi(v), v, 0)\Big) \nabla_\phi \mu^\phi(v).$$

Algorithm 1 Deep Threshold Optimal Policy Training for MDPs (DeepTOP-MDP)

Randomly select initial actor network parameters ϕ and critic network parameters θ.
Set target critic network parameters $\theta' \leftarrow \theta$, and initialize replay memory $\mathcal{M}$.
for timestep $t = 0, 1, 2, \dots$ **do**
    Receive state $s_t = (\lambda_t, v_t)$ from environment $\mathcal{E}$.
    Select action $a_t = \mathbb{1}(\mu^\phi(v_t) > \lambda_t)$ with probability $1 - \epsilon$. Otherwise, select action a_t randomly.
    Execute action a_t, and observe reward r_t and next state s_{t+1} from $\mathcal{E}$.
    Store transition $\{s_t, a_t, r_t, s_{t+1}\}$ into $\mathcal{M}$.
    Sample a minibatch of B transitions $\{s_{t_k}, a_{t_k}, r_{t_k}, s_{t_k+1}\}$, for $1 \le k \le B$ from $\mathcal{M}$.
    Update critic network parameters θ using the estimated gradient from Equation (5).
    Update actor network parameters ϕ using the estimated gradient from Equation (6).
    Soft update target critic parameters θ': $\theta' \leftarrow \tau\theta + (1 - \tau)\theta'$.
end for

Since $Q_{\mu^\phi}\big(\lambda, v, \mathbb{1}(\mu^\phi(v) > \lambda)\big)$ is discounted for all vector states, the summation converges to a finite value. The summation-integration swap in the first equation follows from the Fubini-Tonelli theorem. The last equation follows because $Q_{\mu^\phi}(\mu^\phi(v^n), v, \mathbb{1}(v \in \mathbb{V}^{n+1})) = Q_{\mu^\phi}(\mu^\phi(v^n), v, \mathbb{1}(v \in \mathbb{V}^n))$ for all $v \ne v^n$. $\qquad\square$

3.2 DeepTOP Algorithm Design for MDPs

Motivated by Theorem 1, we now present DeepTOP-MDP, a model-free, actor-critic Deep RL algorithm. DeepTOP-MDP maintains an actor network with parameters ϕ that learns a threshold function $\mu^\phi(v)$, and a critic network with parameters θ that learns an action-value function $Q^\theta(\lambda, v, a)$. DeepTOP-MDP also maintains a target critic network with parameters θ' that is updated slower than the critic parameters θ. The purpose of the target critic network is to improve the learning stability as demonstrated in [8, 18]. The objective of the critic network is to find θ that minimizes the loss function

$$\mathcal{L}(\theta) := \mathop{\mathbb{E}}_{s_t, a_t, r_t, s_{t+1}} \left[\left(Q^\theta(\lambda_t, v_t, a_t) - r_t - \gamma \max_{a' \in \mathcal{A}} Q^{\theta'}(\lambda_{t+1}, v_{t+1}, a') \right)^2 \right], \qquad (4)$$

where (s_t, a_t, r_t, s_{t+1}) is sampled under some policy with $s_t = (\lambda_t, v_t)$. The objective of the actor network is to find ϕ that maximizes $\int_{\lambda=-M}^{\lambda=+M} \sum_{v \in \mathcal{V}} Q_{\mu^\phi}^\theta\big(\lambda, v, \mathbb{1}(\mu^\phi(v) > \lambda)\big)d\lambda$.

In each timestep t, the environment $\mathcal{E}$ provides a state s_t to the agent. We set an exploration parameter $\epsilon \in [0, 1)$ that takes a random action with probability ϵ. Otherwise, DeepTOP-MDP calculates $\mu^\phi(v_t)$ based on v_t, and chooses $a_t = \mathbb{1}(\mu^\phi(v_t) > \lambda_t)$. $\mathcal{E}$ generates a reward r_t and a next state s_{t+1}. A replay memory denoted by $\mathcal{M}$ then stores the transition $\{s_t, a_t, r_t, s_{t+1}\}$. After filling the memory with at least B transitions, DeepTOP-MDP updates the parameters ϕ, θ, θ' in every timestep using a sampled minibatch of size B of transitions $\{s_{t_k}, a_{t_k}, r_{t_k}, s_{t_k+1}\}$, for $1 \le k \le B$. The critic network uses the sampled transitions to calculate the estimated gradient of $\mathcal{L}(\theta)$:

$$\hat{\nabla}_\theta \mathcal{L}(\theta) := \frac{2}{B} \sum_{k=1}^{B} \left(Q^\theta(\lambda_{t_k}, v_{t_k}, a_{t_k}) - r_{t_k} - \gamma \max_{a' \in \mathcal{A}} Q^{\theta'}(\lambda_{t_k+1}, v_{t_k+1}, a') \right) \nabla_\theta Q^\theta(\lambda_{t_k}, v_{t_k}, a_{t_k}). \qquad (5)$$

Similarly, the actor network uses the sampled transitions and Equation (3) to calculate the estimated gradient:

$$\hat{\nabla}_\phi K(\mu^\phi) := \frac{1}{B} \sum_{k=1}^{B} \left(Q_{\mu^\phi}^\theta\big(\mu^\phi(v_{t_k}), v_{t_k}, 1\big) - Q_{\mu^\phi}^\theta\big(\mu^\phi(v_{t_k}), v_{t_k}, 0\big) \right) \nabla_\phi \mu^\phi(v_{t_k}). \qquad (6)$$

Both the critic network and the actor network then take a gradient update step. Finally, we soft update the target critic's parameters θ' using $\theta' \leftarrow \tau\theta + (1 - \tau)\theta'$, with $\tau < 1$. The complete pseudocode is given in Algorithm 1.

4 Whittle Index Policy for RMABs

In this section, we demonstrate how the Whittle index policy [30], a powerful tool for solving the notoriously intractable Restless Multi-Armed Bandit (RMAB) problem, can be represented with a set

of threshold functions. We first describe the RMAB control problem, and then define the Whittle index function.

An RMAB problem consists of N arms. The environment of an arm i, denoted as $\mathcal{E}_i$, is an MDP with a discrete state space $s_{i,t} \in \mathcal{S}_i$, and a binary action space $a_{i,t} \in \mathcal{A} := \{0, 1\}$, where $a_{i,t} = 1$ means that arm i is activated, and $a_{i,t} = 0$ means that arm i is left passive at time t. Given the state-action pair $(s_{i,t}, a_{i,t})$, $\mathcal{E}_i$ generates a random reward $r_{i,t}$ and a random next state $s_{i,t+1}$ following some unknown probability distributions based on $(s_{i,t}, a_{i,t})$. Here we also use $\bar{r}_i(s_i, a_i)$ to denote the unknown expected one-step reward that can be obtained for the state-action pair (s_i, a_i).

A control policy over all arms takes the states $(s_{1,t}, s_{2,t}, \ldots, s_{N,t})$ as input, and activates V out of N arms in every timestep. Solving for the optimal control policy for RMABs was proven to be intractable [20], since the agent must optimize over an input state space exponential in N. To circumvent the dimensionality challenge, the Whittle index policy assigns real values to an arm's states using a Whittle index function for each arm $W_i : \mathcal{S}_i \to \mathbb{R}$. Based on the assigned Whittle indices $(W_1(s_{1,t}), W_2(s_{2,t}), \ldots, W_N(s_{N,t}))$, the Whittle index policy activates the V highest-valued arms out of N arms in timestep t, and picks the passive action for the remaining arms.

4.1 The Whittle Index Function as The Optimal Threshold Function

To define the Whittle index and relate it to threshold functions, let us first consider an alternative control problem of a single arm i as environment $\mathcal{E}_i$ with *activation cost* λ. In this problem, the agent follows a control policy that determines whether the arm is activated or not based on its current state $s_{i,t}$. If the policy activates the arm, then the agent must pay an activation cost of λ. Hence, the agent's *net reward* at timestep t is defined as $r_{i,t} - \lambda a_{i,t}$.

We now consider applying threshold policies for this alternative control problem. A threshold policy defines a threshold function $\mu_i : \mathcal{S}_i \to \mathbb{R}$ that maps each state to a real value. It then activates the arm if and only if $\mu_i(s_{i,t}) > \lambda$, i.e., $a_{i,t} = \mathbb{1}(\mu_i(s_i) > \lambda)$. The value of $\mu_i(s_{i,t})$ can therefore be viewed as the largest activation cost that the agent is willing to pay to activate the arm under state $s_{i,t}$.

To characterize the performance of a threshold policy with a threshold function $\mu_i(\cdot)$, we let $\rho_{\mu_i,\lambda}(s_i', s_i)$ be the discounted state distribution, which is the average discounted number of visits of state s_i' when the initial state is s_i under the threshold policy and λ. When the initial state is s_i, the expected discounted net reward under the threshold policy is

$$Q_{i,\lambda}(s_i, \mathbb{1}(\mu_i(s_i) > \lambda)) = \sum_{s_i' \in \mathcal{S}_i} \rho_{\mu_i,\lambda}(s_i', s_i)\Big(\bar{r}_i(s_i', \mathbb{1}(\mu_i(s_i') > \lambda)) - \lambda\mathbb{1}(\mu_i(s_i') > \lambda)\Big). \tag{7}$$

The performance of the threshold policy under a given λ is defined as $J_{i,\lambda}(\mu_i) := \sum_{s_i \in \mathcal{S}_i} Q_{i,\lambda}(s_i, \mathbb{1}(\mu_i(s_i) > \lambda))$. The Whittle index of this arm is defined as the function $\mu_i(\cdot)$ whose corresponding threshold policy maximizes $J_{i,\lambda}(\mu_i)$ for all λ:

Definition 1. *(Whittle Index) If there exists a function $\mu_i : \mathcal{S}_i \to \mathbb{R}$ such that choosing $\mathbb{1}(\mu_i(s_i) > \lambda)$ maximizes $J_{i,\lambda}(\mu_i)$ for all $\lambda \in (-\infty, +\infty)$, then we say that $\mu_i(s_i)$ is the Whittle index $W_i(s_i)$* [1].

We note that, for some arms, there does not exist any function $\mu_i(s_i)$ that satisfies the condition in Definition 1. For such arms, the Whittle index does not exist. We say that an arm is *indexable* if it has a well-defined Whittle index function.

Definition 1 shows that finding the Whittle index is equivalent to finding the optimal $\mu_i(\cdot)$ that maximizes $J_{i,\lambda}(\mu_i)$ for all $\lambda \in (-\infty, +\infty)$. Parameterizing a threshold function $\mu_i^{\phi_i}(\cdot)$ by parameters ϕ_i and letting M be a sufficiently large number such that $\mu_i^{\phi_i}(s_i) \in (-M, +M)$ for all s_i and ϕ_i, we aim to find the optimal ϕ_i for maximizing the objective function

$$K_i(\mu_i^{\phi_i}) := \int_{\lambda=-M}^{\lambda=+M} \sum_{s_i \in \mathcal{S}_i} Q_{i,\lambda}(s_i, \mathbb{1}(\mu_i^{\phi_i}(s_i) > \lambda))d\lambda. \tag{8}$$

---

[1] To simplify notations, we use a necessary and sufficient condition for the Whittle index as its definition. We refer interested readers to [9] for more thorough discussions on the Whittle index.

5 Deep Threshold Optimal Policy for RMABs

To design a DeepTOP variant for RMABs, we first give the gradient of the objective function.

Theorem 2. *Given the parameter vector ϕ_i, if all states $s_i \in \mathcal{S}_i$ have distinct values of $\mu_i^{\phi_i}(s_i)$, then,*

$$\nabla_{\phi_i} K_i(\mu_i^{\phi_i}) = \sum_{s_i \in \mathcal{S}_i} \left(Q_{i,\mu_i^{\phi_i}(s_i)}(s_i, 1) - Q_{i,\mu_i^{\phi_i}(s_i)}(s_i, 0) \right) \nabla_{\phi_i} \mu_i^{\phi_i}(s_i). \tag{9}$$

Proof. The proof is similar to that of Theorem 1. For completeness, we provide it in Appendix A. □

We note that Theorem 2 does not require the arm to be indexable. Whether an arm is indexable or not, using Theorem 2 along with a gradient ascent algorithm will find a locally-optimal ϕ_i that maximizes $K_i(\mu_i^{\phi_i})$. When the arm is indexable, the resulting threshold function $\mu_i^{\phi_i}$ is the Whittle index function.

Using the gradient result from Equation (9), we present the algorithm DeepTOP-RMAB for finding the optimal parametrized threshold functions $\mu_i^{\phi_i}$ for arms $i = 1, 2, \ldots, N$. The training method is similar to the MDP version, except for two important differences. First, the training of each arm is done independently from others. Second, the value of λ is an artificial value that only exists in the alternative problem but not in the original RMAB problem.

Similar to DeepTOP-MDP, we maintain three network parameters for each arm i: actor ϕ_i, critic θ_i, and target-critic θ'_i. The critic network parametrizes the action-value function, and is optimized by minimizing the loss function

$$\mathcal{L}_i(\theta_i) := \int_{\lambda=-M}^{\lambda=+M} \mathbb{E}_{s_{i,t}, a_{i,t}, r_{i,t}, s_{i,t+1}} \left[\left(Q_{i,\lambda}^{\theta_i}(s_{i,t}, a_{i,t}) - r_{i,t} - \gamma \max_{a' \in \mathcal{A}} Q_{i,\lambda}^{\theta'_i}(s_{i,t+1}, a') \right)^2 \right] d\lambda, \tag{10}$$

with $(s_{i,t}, a_{i,t}, r_{i,t}, s_{i,t+1})$ sampled under some policy.

In each timestep t, each arm environment $\mathcal{E}_i$ provides its current state $s_{i,t}$ to the agent. For each arm $i = 1, 2, \ldots, N$, DeepTOP-RMAB calculates the state value $\mu_i^{\phi_i}(s_{i,t})$ with the arm's respective actor network parameters ϕ_i. Given an exploration parameter $\epsilon \in [0, 1)$, DeepTOP-RMAB activates the V arms with the largest $\mu_i^{\phi_i}(s_{i,t})$ with probability $1 - \epsilon$, and activates V randomly selected arms with probability ϵ. Based on the executed actions, each arm provides a reward $r_{i,t}$ and the next state $s_{i,t+1}$. An arm's transition $\{s_{i,t}, a_{i,t}, r_{i,t}, s_{i,t+1}\}$ is then stored in the arm's memory denoted by $\mathcal{M}_i$.

After filling each arm's memory with at least B transitions, DeepTOP-RMAB updates ϕ_i, θ_i, and θ'_i in every timestep. For each arm i, DeepTOP-RMAB first samples a minibatch of size B of transitions $\{s_{i,t_k}, a_{i,t_k}, r_{i,t_k}, s_{i,t_k+1}\}$, for $1 \leq k \leq B$ from the memory $\mathcal{M}_i$. It then randomly samples B values $[\lambda_{i,1}, \lambda_{i,2}, \ldots, \lambda_{i,B}]$ from the range $[-M, +M]$. Using the sampled transitions and λ values, it estimates the gradient of $\mathcal{L}_i(\theta_i)$ as

$$\hat{\nabla}_{\theta_i} \mathcal{L}_i(\theta_i) := \frac{2}{B} \sum_{k=1}^{B} \left(Q_{i,\lambda_k}^{\theta_i}(s_{i,t_k}, a_{i,t_k}) - r_{i,t_k} - \gamma \max_{a' \in \mathcal{A}} Q_{i,\lambda_k}^{\theta'_i}(s_{i,t_k+1}, a') \right) \nabla_{\theta_i} Q_{i,\lambda_k}^{\theta_i}(s_{i,t_k}, a_{i,t_k}). \tag{11}$$

Using the sampled transitions and Equation (9), it estimates the gradient of $K_i(\mu_i^{\phi_i})$ as

$$\hat{\nabla}_{\phi_i} K_i(\mu_i^{\phi_i}) := \frac{1}{B} \sum_{k=1}^{B} \left(Q_{i,\mu_i^{\phi_i}(s_{i,t_k})}^{\theta_i}(s_{i,t_k}, 1) - Q_{i,\mu_i^{\phi_i}(s_{i,t_k})}^{\theta_i}(s_{i,t_k}, 0) \right) \nabla_{\phi_i} \mu_i^{\phi_i}(s_{i,t_k}). \tag{12}$$

A gradient update step is taken after calculating the actor and critic networks' gradients. Finally, DeepTOP-RMAB soft updates the target critic parameters θ'_i using $\theta'_i \leftarrow \tau \theta_i + (1 - \tau)\theta'_i$, with $\tau < 1$. The complete DeepTOP-RMAB pseudocode is given in Appendix B.

6 Simulations

We have implemented and tested both DeepTOP-MDP and DeepTOP-RMAB in a variety of settings. The training procedure of the two DeepTOP algorithms are similar to that of the DDPG [18] algorithm

except for the expression of gradients. We implemented the DeepTOP algorithms by modifying an open-source implementation of DDPG [12]. All source code can be found in the repository [redacted for submission version].

6.1 Simulations for MDPs

We evaluate three MDPs, namely, the electric vehicle charging problem, the inventory management problem, and the make-to-stock problem.

EV charging problem. This problem is based on Yu, Xu, and Tong [32]. It considers a charging station serving EVs. When an EV arrives at the station, it specifies the amount of charges it needs and a deadline upon which it will leave the station. The electricity price changes over time and we model it by an Ornstein-Uhlenbeck process [28]. In each timestep, the station decides whether to charge the EV or not. If it decides to charge the EV, then it provides one unit charge to the EV. The station then obtains a unit reward and pays the current electricity price. If the station fails to fully charge the EV by the deadline of the EV, then the station suffers from a penalty that is a convex function of the remaining needed charge. A new EV arrives at the station when the previous EV leaves.

We model this problem by letting the scalar state be the current electricity price and the vector state be the remaining needed charge and time-to-deadline of the current EV. A threshold policy is one that calculates a threshold based on the EV's remaining needed charge and time-to-deadline, and then decides to charge the EV if and only if the current electricity price is below the threshold.

Inventory management problem. We construct an inventory management problem by jointly incorporating a variety of practical challenges, including seasonal fluctuations in demands and lead times in orders, in the literature [26, 14, 10, 25]. We consider a warehouse holding goods. In each timestep, there is a random amount of demand whose mean depends on the time of the year. The warehouse can fulfill the demand as long as it has sufficient inventory, and it makes a profit for each unit of sold goods. At the end of the timestep, the warehouse incurs a unit holding cost for each unit of unsold goods. The warehouse manager needs to decide whether to order more goods. When it places an order for goods, there is a lead time of one time step, that is, the goods ordered at timestep t are only available for sale at timestep $t + 1$.

We model this problem by letting the scalar state be the current inventory and the vector state be the time of the year. A threshold policy calculates a threshold based on the time of the year and decides to place an order for goods if the current inventory is below the threshold.

Make-to-stock production problem. This problem is considered in [24]. It studies a system that produces m items with W demand classes and buffer size S. Accepting a class v order leads to a reward R_v, as long as there is still room in the buffer for the order. The classes of demands are ordered such that $R_1 > R_2 > \dots$. In this problem, the scalar state is the number of accepted but unfinished orders and the vector state is the class of the next arriving order.

More details about the three MDPs can be found in Appendix C.

Figure 1: Average reward results on MDP problems averaged over 20 independent runs.

²⁵⁷ **Evaluated policies.** We compare DeepTOP-MDP against DDPG [18] and TD3 [8], two state-of-
²⁵⁸ the-art off-policy and model free deep RL algorithms. We use open-source implementations of
²⁵⁹ these two algorithms for [12, 7]. We use the same hyper-parameters, including the neural network
²⁶⁰ architecture, learning rates, etc., for all three algorithms. We also evaluate the Structure-Aware
²⁶¹ Learning for Multiple Thresholds algorithm (SALMUT) [24], a reinforcement learning algorithm
²⁶² that finds the optimal threshold policy. SALMUT requires the vector states to be pre-sorted by their
²⁶³ threshold values. Hence, SALMUT can only be applied to the make-to-stock production problem.
²⁶⁴ Details about the training parameters can be found in Appendix D. For the EV charging problem, Yu,
²⁶⁵ Xu, and Tong [32] has found the optimal threshold policy. We call the optimal threshold policy the
²⁶⁶ *Deadline Index* policy and compare DeepTOP-MDP against it.

²⁶⁷ **Simulations results.** Simulation results of the three MDPs are shown in Figure 1. The results are
²⁶⁸ the average of 20 independent runs. Before starting a run, we fill an agent's memory with 1000
²⁶⁹ transitions by randomly selecting actions. We plot the average reward obtained from the previous
²⁷⁰ 100 timesteps, and average them over 20 runs. In addition, we provide the standard deviation bounds
²⁷¹ from the average reward.

²⁷² It can be observed that DeepTOP significantly outperforms DDPG, TD3, and SALMUT. Although
²⁷³ the training procedure of DeepTOP is similar to that of DDPG, DeepTOP is able to achieve much
²⁷⁴ faster learning by leveraging the monotone property. Without leveraging the monotone property,
²⁷⁵ DDPG and TD3 need to learn the optimal policy for each scalar state independently, and therefore
²⁷⁶ have much worse performance. DeepTOP performs better than SALMUT because DeepTOP directly
²⁷⁷ employs the threshold policy gradient. We also note that DeepTOP performs virtually the same as
²⁷⁸ the Deadline Index policy for the EV charging problem in about 2000 timesteps, suggesting that
²⁷⁹ DeepTOP indeed finds the optimal threshold policy quickly. We also evaluate DeepTOP for different
²⁸⁰ neural network architectures in Appendix E, and show that DeepTOP performs the best in all settings.

6.2 Simulations for RMABs

²⁸² **Description of the RMAB.** We consider an extension of the RMAB problem evaluated in Killian
²⁸³ et al. [16]. Killian et al. [16] considers the case when each arm is a two-state Markov process. We
²⁸⁴ extend it so that each arm is a Markov process with 100 states, numbered as $0, 1, \ldots, 99$, as shown in
²⁸⁵ Figure 2 where state 99 is the optimal state.

²⁸⁶ The reward of an arm depends on the dis-
²⁸⁷ tance between its current state and state
²⁸⁸ 99. Suppose the current state of arm i is $s_{i,t}$,
²⁸⁹ then it generates a reward $r_{i,t} = 1 - (\frac{s_{i,t}-99}{99})^2$.
²⁹⁰ If the arm is activated, then it changes to
²⁹¹ state $s_{i,t+1} = \min\{s_{i,t} + 1, 99\}$ with probabil-
²⁹² ity p_i. If the arm is not activated, then it
²⁹³ changes to state $s_{i,t+1} = \max\{s_{i,t} - 1, 0\}$ with
²⁹⁴ probability q_i. In the simulations, we pick
²⁹⁵ the probabilities p_i to be evenly spaced de-
²⁹⁶ pending on the number of arms N from the
²⁹⁷ interval $[0.2, 0.8]$. We set the probabilities

Figure 2: Arm i as a Markov process with 100 states
and transition probabilities p_i and q_i.

²⁹⁸ $q_i = p_i$. We consider that there are N arms and that the agent needs to activate V arms in each
²⁹⁹ timestep. We evaluate three settings of $(N, V) = (10, 3), (20, 5),$ and $(30, 6)$.

³⁰⁰ **Evaluated policies.** We compare DeepTOP-RMAB against three recent studies that aim to learn
³⁰¹ index policies for RMABs, namely, Lagrange policy Q learning (LPQL) [16], Whittle index based Q
³⁰² learning (WIBQL) [1], and neural Whittle index network (NeurWIN) [19]. LPQL consists of three
³⁰³ steps: First, it learns a Q function for each arm independently. Second, it uses the Q functions of
³⁰⁴ all arms to determine a common Lagrangian. Third, it uses the Lagrangian to calculate the index of
³⁰⁵ each arm. WIBQL is a two-timescale algorithm that learns the Whittle indices of indexable arms
³⁰⁶ by updating Q values on the fast timescale, and index values on the slower timescale. NeurWIN is
³⁰⁷ an off-line training algorithm based on REINFORCE that requires a simulator to learn the Whittle
³⁰⁸ index. Both LPQL and WIBQL are tabular learning methods which may perform poorly compared
³⁰⁹ to deep RL algorithms when the size of the state space is large. Hence, we also design deep RL
³¹⁰ equivalent algorithms that approximate their Q functions using neural networks. We refer to the Deep

RL extensions as neural LPQL and neural WIBQL. In all experiments, neural LPQL, neural WIBQL, and NEurWIN use the same hyper-parameters as DeepTOP-RMAB. It can be shown that the Whittle index in this setting is in the range of $[-1, 1]$, and hence we set $M = 1$.

Simulation results. Simulation results are shown in Figure 3. It can be observed that DeepTOP achieves the optimal average rewards in all cases. The reason that neural LPQL performs worse than DeepTOP may lie in its reliance on a common Lagrangian. Since the common Lagrangian is calculated based on the Q functions of all arms, an inaccuracy in one arm's Q function can result in an inaccurate Lagrangian, which, in turn, leads to inaccuracy in the index values of all arms. Prior work [16] has already shown that WIBQL performs worse than LPQL. Hence, it is not surprising that neural WIBQL performs worse than both neural LPQL and DeepTOP. NeurWIN performs worse than DeepTOP because it is based on REINFORCE and therefore can only apply updates at the end of each episode. We also evaluate DeepTOP for different neural network architectures. Results are shown in Appendix F, which show that DeepTOP performs the best in all settings.

(a) $N = 10$. $V = 3$.   (b) $N = 20$. $V = 5$.   (c) $N = 30$. $V = 6$.

Figure 3: Average reward for RMABs with N arms averaged over 20 independent runs.

7 Related Work

Threshold policies have been analysed for many decision-making problems formed as MDPs. [11] examined the residential energy storage under price fluctuations problem, and proved the existence of optimal threshold policies for minimizing the cost. [5] proved that MDPs with a convex and piecewise linear cost functions admit an optimal threshold policy. [23] shows the existence of an optimal threshold policy for energy arbitrage given degrading battery capacity, with [2] using the REINFORCE algorithm [31] to learn a trading policy with price thresholds for intraday electricity markets. [13] considered mean field games in a multi-agent MDP setting, and characterized individual agent strategy with a threshold policy when the mean game admits a threshold policy.

More recently, [29] studies finding a job assigning threshold policy for data centers with heterogeneous servers and job classes, and gave conditions for the existence of optimal threshold policies. [33] proposed a distributed threshold-based control policy for graph traversal by assigning a state threshold that determines if the agent stays in or leaves a state. For minimizing the age of information in energy-harvesting sensors, [4] used the finite-difference policy gradient [22] to learn a possibly sub-optimal threshold policy in the average cost setting. [27] used the Deep Q-network RL algorithm for selecting alert thresholds in anti-fraud systems with simulations showing performance improvements over static threshold policies. [24] described the SALMUT RL algorithm for exploiting the ordered multi-threshold structure of the optimal policy with SALMUT implementations in [15] for computing node's overload protection. In contrast to these works, DeepTOP-MDP is applicable to any MDP that admits threshold policies.

In learning the Whittle index policy for RMABs, [6] proposed a Q-learning heuristic called the Q Whittle Index Controller (QWIC) which may not find the Whittle indices even when the training converges. [19] describes a Deep RL algorithm called NeurWIN for learning the Whittle index of a restless arm independently of other arms. However, NeurWIN requires a simulator to train the neural networks. Some recent studies, such as [1, 3, 16], proposed various online learning algorithms that can find Whittle index when the algorithms converge. These algorithms rely on some indirect property of the Whittle index which explains why they converge slower than DeepTOP.

8 Conclusion

In this paper, we presented DeepTOP: a Deep RL actor-critic algorithm that learns the optimal threshold function for MDPs that admit a threshold policy and for RMAB problems. We first developed the threshold policy gradient theorem, where we proved that a threshold function has a simple to compute gradient. Based on the gradient expressions, we design the DeepTOP-MDP and DeepTOP-RMAB algorithm variants and compare them against state-of-the-art learning algorithms. In both the MDP and RMAB settings, experiment results showed that DeepTOP exceeds the performance of baselines in all considered problems.

(a) $N = 10$. $V = 3$.   (b) $N = 20$. $V = 5$.   (c) $N = 30$. $V = 6$.

Figure 4: Average reward for RMABs with N arms averaged over 20 independent runs using linear reward function $1 - \frac{(99 - s_{i,t})}{99}$.

(a) $N = 10$. $V = 3$.   (b) $N = 20$. $V = 5$.   (c) $N = 30$. $V = 6$.

Figure 5: Average reward for RMABs with N arms averaged over 20 independent runs using cubic reward function $1 - (\frac{(99 - s_{i,t})}{99})^3$.

(a) EV charging.   (b) Inventory management.   (c) Make-to-stock production.

Figure 6: Decaying ϵ with initial $\epsilon_{t=0} = 1$ and a linear decay rate $1/500$ per timestep. Average reward results on MDP problems averaged over 20 independent runs.

References

[1] Konstantin Avrachenkov and Vivek S. Borkar. Whittle index based q-learning for restless bandits with average reward. *CoRR*, abs/2004.14427, 2020.

[2] Gilles Bertrand and Anthony Papavasiliou. Reinforcement-learning based threshold policies for continuous intraday electricity market trading. In *2019 IEEE Power Energy Society General Meeting (PESGM)*, pages 1–5, 2019.

[3] Arpita Biswas, Gaurav Aggarwal, Pradeep Varakantham, and Milind Tambe. Learn to Intervene: An Adaptive Learning Policy for Restless Bandits in Application to Preventive Healthcare. In *Proceedings of the Thirtieth International Joint Conference on Artificial Intelligence*, pages 4039–4046, Montreal, Canada, August 2021. International Joint Conferences on Artificial Intelligence Organization.

[4] Elif Tuğçe Ceran, Deniz Gündüz, and András György. Reinforcement learning to minimize age of information with an energy harvesting sensor with harq and sensing cost. In *IEEE INFOCOM 2019 - IEEE Conference on Computer Communications Workshops (INFOCOM WKSHPS)*, pages 656–661, 2019.

[5] Tomaso Erseghe, Andrea Zanella, and Claudio G Codemo. Markov decision processes with threshold based piecewise linear optimal policies. *IEEE Wireless Communications Letters*, 2(4):459–462, 2013.

[6] Jing Fu, Yoni Nazarathy, Sarat Moka, and Peter G. Taylor. Towards q-learning the whittle index for restless bandits. In *2019 Australian New Zealand Control Conference (ANZCC)*, pages 249–254, 2019.

[7] Scott Fujimoto. Sfujim/td3: Author's pytorch implementation of td3 for openai gym tasks. <https://github.com/sfujim/TD3>.

[8] Scott Fujimoto, Herke Hoof, and David Meger. Addressing function approximation error in actor-critic methods. In *International Conference on Machine Learning*, pages 1582–1591, 2018.

[9] John Gittins, Kevin Glazebrook, and Richard Weber. *Multi-armed bandit allocation indices*. John Wiley & Sons, 2011.

[10] SK Goyal and Bibhas Chandra Giri. The production–inventory problem of a product with time varying demand, production and deterioration rates. *European Journal of Operational Research*, 147(3):549–557, 2003.

[11] Nidhi Hegde, Laurent Massoulié, Theodoros Salonidis, et al. Optimal control of residential energy storage under price fluctuations. *Energy*, 2011.

[12] Guan Horng Liu. Ghliu/pytorch-ddpg: Implementation of the deep deterministic policy gradient (ddpg) using pytorch. <https://github.com/ghliu/pytorch-ddpg>.

[13] Minyi Huang and Yan Ma. Mean field stochastic games: Monotone costs and threshold policies. In *2016 IEEE 55th Conference on Decision and Control (CDC)*, pages 7105–7110, 2016.

[14] Marko Jakšič and Jan C Fransoo. Optimal inventory management with supply backordering. *International journal of production economics*, 159:254–264, 2015.

[15] Anirudha Jitani, Aditya Mahajan, Zhongwen Zhu, Hatem Abou-Zeid, Emmanuel Thepie Fapi, and Hakimeh Purmehdi. Structure-aware reinforcement learning for node-overload protection in mobile edge computing. In *ICC 2021 - IEEE International Conference on Communications*, pages 1–6, 2021.

[16] Jackson A. Killian, Arpita Biswas, Sanket Shah, and Milind Tambe. *Q-Learning Lagrange Policies for Multi-Action Restless Bandits*, page 871–881. Association for Computing Machinery, New York, NY, USA, 2021.

[17] Diederick P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations (ICLR)*, 2015.

[18] Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.

[19] Khaled Nakhleh, Santosh Ganji, Ping-Chun Hsieh, I-Hong Hou, and Srinivas Shakkottai. NeurWIN: Neural whittle index network for restless bandits via deep RL. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021.

[20] Christos H. Papadimitriou and John N. Tsitsiklis. The complexity of optimal queuing network control. *Mathematics of Operations Research*, 24(2):293–305, 1999.

[21] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. dAlché Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 8026–8037. Curran Associates, Inc., 2019.

[22] Jan Peters and Stefan Schaal. Policy gradient methods for robotics. In *2006 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 2219–2225. IEEE, 2006.

[23] Marek Petrik and Xiaojian Wu. Optimal threshold control for energy arbitrage with degradable battery storage. In *UAI*, pages 692–701. Citeseer, 2015.

[24] Arghyadip Roy, Vivek S. Borkar, Abhay Karandikar, and Prasanna Chaporkar. Online reinforcement learning of optimal threshold policies for markov decision processes. *IEEE Transactions on Automatic Control*, pages 1–1, 2021.

[25] Luis A San-José, Joaquín Sicilia, Manuel González-de-la Rosa, and Jaime Febles-Acosta. Profit maximization in an inventory system with time-varying demand, partial backordering and discrete inventory cycle. *Annals of Operations Research*, pages 1–21, 2021.

[26] Maike Schwarz and Hans Daduna. Queueing systems with inventory management with random lead times and with backordering. *Mathematical Methods of Operations Research*, 64(3):383–414, 2006.

[27] Hongda Shen and Eren Kurshan. Deep q-network-based adaptive alert threshold selection policy for payment fraud systems in retail banking. In *Proceedings of the First ACM International Conference on AI in Finance*, ICAIF '20, New York, NY, USA, 2020. Association for Computing Machinery.

[28] G. E. Uhlenbeck and L. S. Ornstein. On the theory of the brownian motion. *Phys. Rev.*, 36:823–841, Sep 1930.

[29] Paul Weng, Zeqi Qiu, John Costanzo, Xiaoqi Yin, and Bruno Sinopoli. Optimal threshold policies for robust data center control. In *International Conference on Advanced Engineering Theory and Applications*, pages 104–114. Springer, 2017.

[30] Peter Whittle. Restless bandits: Activity allocation in a changing world. *Journal of applied probability*, pages 287–298, 1988.

[31] Ronald J. Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Mach. Learn.*, 8(3–4):229–256, May 1992.

[32] Zhe Yu, Yunjian Xu, and Lang Tong. Deadline scheduling as restless bandits. *IEEE Transactions on Automatic Control*, 63(8):2343–2358, 2018.

[33] Nan Zhou, Christos G Cassandras, Xi Yu, and Sean B Andersson. Optimal threshold-based distributed control policies for persistent monitoring on graphs. In *2019 American Control Conference (ACC)*, pages 2030–2035. IEEE, 2019.