EAR – Explain and Rank: a criteria-based Reinforcement Learning pipeline for GEC Feedback Comment Generation

Abstract

We propose EAR – a reinforcement learning (RL) pipeline for generating Grammatical Error Explanations (GEE). By developing a multi-criteria, prompt-based ranking reward, we implement a multistage RL process, comprising teacher distillation, rejection sampling and pairwise RL, applied to the Qwen3-4B-Instruct model. Our results show that the fine-tuned model outperforms both the teacher model and expert human annotations with a 60/40 win rate. Furthermore, pairwise RL enables the generator to acquire capabilities absent in the teacher model, specifically advanced analogical reasoning and in-depth semantic analysis without using any gold explanations or annotated datasets. We plan to make our code and model freely available.

1 Introduction

The task of Grammatical Error Correction (GEC), i.e. of removing all errors in a sentence, has been extensively covered in various papers throughout the years (Chodorow et al., 2007; Felice et al., 2014; Náplava and Straka, 2019; Omelianchuk et al., 2020; Loem et al., 2023; Ye et al., 2025b), especially for the English language. According to Omelianchuk et al. (2024), single-model GEC systems have reached a performance plateau, and further progress depends on data quality rather than architectural scaling, suggesting that GEC for English is largely a solved task.

However, corrected text alone lacks the explanatory power needed for L2 learners (primary GEC beneficiaries) to generalize rules and avoid recurring errors. Consequently, the task requires models that can bridge the gap between error correction and rule generalization through clear, high-quality explanations.

Our pilot experiment using Qwen3-30B-A3B-Thinking-2507-FP8[1] (Team, 2025) and

---

[1]Qwen3-30B-A3B hereafter

Figure 1: Percentage of explanations that fulfill the criteria on a random selection of 57 edits from the NUCLE subset of XGEC.

GPT4o (OpenAI, 2023) on the XGEC corpus (Kaneko and Okazaki, 2024), the only available dataset providing comprehensive explanations across diverse error types, revealed significant limitations in the capacities of Large Language Models (LLMs) to provide high-quality feedback for GEC: more than one-third of the generated explanations exhibited serious flaws in factual accuracy or completeness (see Figure 1). These results indicate that even frontier open-source and proprietary models struggle to provide robust learning feedback out-of-the-box, necessitating targeted optimization.

To address this challenge in a data-scarce environment, we form a criteria map to define a high-quality explanation for GEC – *reliability, completeness, usefulness and execution* – and introduce **EAR** – *Explain and Rank* pipeline, adapting the Reinforcement Learning (RL) approach to the GEC domain by designing a ranking reward optimized through **criteria-based** offline RL techniques. Note that using RL is inevitable given the absence of gold-standard explanations and difficulty of human annotation.

The human preference evaluation demonstrates that our final model – EAR-4B – outperforms both the Teacher Qwen3-30B-A3B outputs and expert

human annotations from the CoNLL-2014 subset of the XGEC dataset. A fine-grained manual evaluation confirms that EAR-4B provides more reliable and complete explanations than its Teacher and more often exhibits such emergent capabilities, as context-awareness, usage of world knowledge or analogous examples. Figure 1 shows that our pipeline notably improves completeness rate on the pilot sample, providing more analogous examples and utilizing both world knowledge and surrounding context, with negligible impact on reliability.

Our main contributions are as follows:

- We release a compact EAR-4B model for the Feedback Comment Generation task[2] whose explanations outperform both responses of large LLMs and expert-written explanations.

- We implement an RL pipeline capable of training high-quality explanation generation models under severe scarcity of both reference explanations and reward model training data.

- We propose a comprehensive set of evaluation criteria for high-quality GEC feedback, accompanied with detailed descriptions and examples.

We make our contributions available by publishing both the final model and the code for the paper[3]. The illustrative example of model generation in the interactive mode is shown in Figure 7.

2 Task definition

We follow Nagata (2019); Nagata et al. (2021) and define Feedback Comment Generation for language learners as the task of generating, given a text and a span, an explanatory note that will help improve learners' writing skills. However, we extend it by several points.

Similar to Kaneko and Okazaki (2024), i) we provide the model not only with a text and an erroneous span, but also with a corresponding correction, assuring that the model would explain the required edit and avoid inventing anything; ii) we consider a broader range of errors, not restricting them to preposition use; iii) the sentences may contain multiple mistakes and the system must target them all, generating explanations for each edit. Therefore, our definition of the task is to generate a list of explanations, given an incorrect sentence, fully edited sentence and all of the edits

– error-correction pairs. The preliminary step of our research consisted of comparing and contrasting human and model explanations to identify the features of a 'good' explanation and choose the optimal prompt for their generation. XGEC NU-CLE subset[4] (Kaneko and Okazaki, 2024) served as human-annotated data, whereas Qwen3-30B-A3B was used to produce model data.

2.1 Criteria

We define a high quality explanation as the explanation that satisfies the following criteria:

- **Reliability**. There are no hallucinations, i.e. facts that contradict either the context or rules of English grammar. This includes

  1. mentioning words or sequences that did not occur in the sentence (see Fig. 6a).
  2. referring to nonexistent standards, misleading guidelines and generalizations (see Fig. 6c and d). This often includes over-rigidity in rule application that ignores context-dependent acceptability.
  3. treating a dependent edit as a fundamental mistake, overlooking its necessity being conditioned by a previous correction (Fig. 6b).

- **Completeness** The explanation provides a comprehensive list of reasons for a given correction (Fig. 6e), supplies it with contextual evidence from the sentence (Fig. 6f) and refers to specific rules of the English grammar that were violated. It also demonstrates how the correction improves the sentence by making a distinction in usage and meaning between the original expression and its edit. In addition, no logical steps may be overlooked: the description of how the rule applies to the sentence must be self-sufficient and leave no room for speculation, e.g. for an insertion of 'the' it is not enough to state that a singular countable noun requires an article, the explanation should also address why 'the' was chosen from the set of determiners – 'a', 'an' and 'the'.

- **Usefulness** There are no sentences consisting fully of empty phrases that do not contribute to the explanation, e.g. *This improves text clarity*.

---

[2]Some papers also refer to it as the Grammar/Grammatical Error Explanation (GEE) task.

[3]To appear in the final version of the paper.

[4]https://github.com/kanekomasahiro/gec-explanation

Figure 2: The description of EAR: train data generation and training stages.

- **Execution** In order to serve educational purposes, the explanation itself must not contain any grammatical errors and instances of ambiguous or poor phrasing, e.g. *the noun 'citizens' is incorrect in the context of 'their citizens'*.

Although the perfect feedback for a correction would possess all of the features, the most critical criteria to meet are reliability and completeness. As students refer to explanations when they do not understand or know certain rules, it is of most importance not to mislead them by providing unreliable judgements and not to offer them incomplete explanations that would not increase their knowledge and reduce their doubts.

3 EAR Pipeline

In this section, we describe the methodology of Explain and Rank, see Figure 2. Our goal is to train a model that will generate high-quality explanations for GEC. Given a scarcity of annotated data for the task[5] and suboptimal results of large models in our pilot experiment (Fig. 1), we decide that the model's training will consist of SFT, followed by RL techniques (steps B&D on Fig. 2). This goes in line with conventional scenarios, where SFT is used to make the model follow the instruction and required format and subsequent RL is employed to improve the model's reasoning and out-of-distribution generalization (Chu et al., 2025),

the training pipeline is described in more detail in Subsection 3.4.

The first step is to obtain SFT training data (Fig. 2A). Due to the shortage of annotated explanations, we resort to GEC-annotated sentences and utilize a larger – *Teacher* – model to generate explanations for them. After that, we employ a large model as a *Judge* to rank candidate explanations according to our criteria map, and select the best ones for the SFT Training Sample. We train a smaller – *Student* – model on this sample (see Fig. 2B).

The next step is to obtain RL training data (Fig. 2C), i.e. pairs of chosen-rejected explanations. We repeat the procedure of Rejection Sampling with the *SFT Student* as a generator and employ the Judge to rank them. Then we build pairs, placing the explanation ranked higher as "chosen", the other one – as "rejected". We train the SFT Student on the collected pairs and obtain our final model – *EAR-4B* (step D on Fig. 2). We provide the details on the components of the pipeline below.

3.1 Explanation Generation

We develop a prompt describing the task in question and ask the model to generate edit explanations for the whole sentence. The exact prompt formulation is provided in Appendix C.1.

3.2 Judge

Due to several considerations, mainly the amount of generated data for assessment and the laboriousness of the task, we employed LLM-as-a-Judge methodology which proved to be useful in many

---

[5]The XGEC dataset contains less than a thousand annotated texts, with a lot of them constituting the test sample.

fields (Zheng et al., 2023; Liu et al., 2025) to evaluate the quality of explanations.

3.2.1 Types of judgements

We examined different scoring patterns from Liu et al. (2025) for the explanation evaluation.
Pointwise approach evaluates how an explanation follows each criterion by assigning binary scores.
Pairwise approach compares 2+ responses simultaneously and chooses the best option or ranks them from best to worst.

While the pointwise approach is more common, it proved ineffective for our task, identifying only 2% of failures even in the sampling mode. In contrast, the pairwise approach was more discerning, achieving 74% agreement with human judgements in selecting the best samples (the chance score is 25%)[6]. Consequently, we adopted the pairwise method for our Judge. Note that while the Judge evaluates all the criteria from Subsection 2.1, only the overall ranking is used for judgement. We refer to Appendix C.2 for the ranking prompt and to Appendix G for discussion.

3.3 Rejection sampling

We sample several candidate explanations and rank them using the Judge (see Subsection 3.2). As the model generates the output for the whole sentence and the Judge produces rankings for individual errors, an additional postprocessing step is required to convert ranking output to scalar scores. For each error, we assign zero points to the highest ranked hypothesis, one point to the second one, and so on. The hypothesis with the lowest sum of scores is selected as the winner.

The pool of candidate hypotheses consists of the greedy generation and four sampling outputs. If the number of explanations in the hypothesis is not equal to the number of errors, we exclude this sample from the comparison.

3.4 Training

We follow the standard scheme for RL-based LLM tuning (Touvron et al., 2023; Liu et al., 2024; Guo et al., 2025) that consists of a) training a reward model; b) tuning a model on the high-quality generations or reasoning traces from a stronger foundation model; c) training the SFT model on its samples with the highest scores according to the reward model (optional step); d) sampling and scoring the

previous model outputs and training it further using either pairwise (PPO, DPO, etc.) or groupwise RL algorithms.

Adopting this scheme for GEC explanation generation, we faced several challenges:

1. The absence of annotated datasets, either in the form of scalar ratings or preference data. → Resort to training-free prompt-based LLM rewards (see Subsection 3.2).

2. We found the task of reference-free estimation of explanations' quality to be too difficult in zero-shot mode even for modern LLMs. → We leverage the ranking-based Judge reward to circumvent this shortcoming (see Subsection 3.2.1).

Since no verifiable rewards are available for the task of explanation quality estimation, we utilize DPO-like pairwise algorithms that require only preference data. Our training pipeline contains two stages:

1. **The SFT stage**, an instance of standard zero-shot distillation: we employ the Teacher as a generator in the Rejection sampling scheme (see 3.3), obtaining the most robust Teacher responses according to the Judge, as a result, and fine-tune the Student on them.

2. **The pairwise RL stage**, where we use the SFT Student model from the previous stage to sample five outputs (one greedy and four sampling ones) and pass them through the Judge. We say that one hypothesis is preferred over another if for all the edits its explanation is ranked higher or equally to the corresponding explanation from the second hypothesis. So, ranking n hypotheses produces up to $\binom{n}{2}$ selected preference pairs. For each training example, we randomly sample K pairs from the list of selected pairs without repetition, where K is the hyperparameter of the algorithm. We discuss this procedure more in Appendix F.3.

Choosing between different pairwise algorithms, we finally opt for AlphaPO (Gupta et al., 2025) as we found it to be the most stable and effective in training. The relative properties of pairwise RL algorithm are discussed more thoroughly in Subsection 6.2.

4 Experimental Setup

4.1 Data

We train the models on the training partition of the W&I-LOCNESS corpus (Bryant et al., 2019) used

---

[6]Prompts were evaluated on the prompt validation set of 67 samples

Model	av. tokens	total wins	0	1	2	3
0. Expert annotations (raw)	42.1	3.2		11.0	18.9	28.4
1. Expert annotations (rewritten)	127.1	22.0	89.0		44.6	39.2
2. Teacher	159.2	24.0	81.1	55.4		38.9
3. EAR-4B	288.6	**50.9**	71.6	60.8	61.1	

Table 1: The percentage of total wins and head-to-head win rates (row-vs-column) for the proposed model versus the teacher model and the expert annotations (both raw and rewritten) by human annotation.

Dataset	Usage	Size, sent.
BEA-2019 train	train	23045
BEA-2019 dev	validation	2856
CoNLL-2014	test	550

Table 2: Datasets used in the paper

in the BEA-2019 shared task on Grammatical Error Correction. We utilize it for teacher model distillation on the SFT stage and sampling the hypotheses on further RL stages. The development set of this corpus is used as a validation sample, in particular, for prompt evaluation, algorithm comparison and hyperparameter selection. Following the previous work (Kaneko and Okazaki, 2024), we use the XGEC CoNLL-2014[7](Ng et al., 2014) Annotator 1 subset as the final test data. The parameters of the corpora are provided in Table 2. Note that we only count sentences that require edits.

4.2 Models and training

We evaluate our approach using models from the Qwen-3 family (Team, 2025). In particular, we use Qwen3-30B-A3B as a Teacher because it performed on par with GPT4o in our pilot experiment (see Fig. 1), while being open-source, which facilitates the reproducibility of our approach, and initialize training from the Qwen3-4B-Instruct-2507[8] checkpoint (Student). We refer to Appendices D and F for training details and discussion on pairwise RL parameters, respectively. We adopt the trl library (von Werra et al., 2020) for all training.

5 Results

5.1 Quantitative evaluation

We conduct a human evaluation on a random subset of 216 sentences from the CoNLL-2014 XGEC test set. To demonstrate that EAR-4B generations are beneficial both in comparison with original

Teacher responses and human-written explanations, we compare 4 variants:
- The original explanations from the XGEC dataset (Kaneko and Okazaki, 2024) written by human experts;
- Their paraphrased versions rewritten in the style of Qwen3-30B-A3B responses. We obtain them by prompting Deepseek v3.1 to rewrite an explanation more verbosely, providing a seed response for stylistic guidance (see Appendix C.3 for the prompt). This ensures the evaluator focuses on explanations' content rather than stylistic cues.
- The explanations generated by the Teacher Qwen3-30B-A3B model (the baseline);
- The explanations generated by our EAR-4B after pairwise RL stage.

Five assessors (two experts and three students) with linguistic backgrounds, high English proficiency – verified by standardized exams or academic competitions – and experience of teaching English performed the annotations. All annotators underwent preliminary training and achieved accuracy in best explanation selection of at least 70% on the control sample. Each instance was independently ranked by one expert and one student, ties were resolved by another expert. For a given sentence and its corrections, assessors ranked four candidate explanation sequences from best to worst (ties permitted). To eliminate position bias, we balanced and shuffled all 24 possible presentation orders across the evaluation set. Further details on the annotation process are provided in Appendix E. We report the annotator agreement of 60.2% as a percentage of matches in the best explanation selection between the student and the expert annotation.

The results of manual evaluation are provided in Table 1. EAR-4B produces the best explanation for the majority of the samples, beating both expert annotations and the Teacher, achieving win rates of over 60%[9].

---

[7]https://github.com/kanekomasahiro/gec-explanation

[8]https://huggingface.co/Qwen/Qwen3-4B-Instruct-2507

[9]All comparisons are statistically significant at $p = 0.01$.

Figure 3: The comparison of EAR-4B and Qwen3-30B-A3B on a random selection of 50 corrections from the CoNLL-2014 subset of XGEC.

Criteria	Teacher	EAR-4B
reliability	72.0	**84.0**
completeness	64.0	**92.0**
analogy	60.0	**92.0**
context-awareness	24.0	**68.0**
world knowledge	4.0	**12.0**

Table 3: Criteria fulfilment rates on a random selection of 50 corrections from the XGEC CoNLL-2014 subset.

5.2 Qualitative analysis

To provide a more granular comparison between EAR-4B and the Teacher, we perform an aspect-based evaluation. We select two key criteria from our prompt—Reliability and Completeness—and ask experts to annotate the explanations along these dimensions. To ensure a prompt-independent analysis, we further evaluate three qualitative properties of high-quality explanations: analogous thinking, context-awareness, and world knowledge usage. For each of these five aspects, annotations are binary, denoting whether the explanation possesses the property (1) or is defective (0). The comparative results are presented in Table 3 and visualized via heatmaps in Figure 3. The plots demonstrate that our approach consistently improves adherence to the core criteria while significantly increasing both context-awareness and the integration of analogous examples.

The fine-grained evaluation clearly demonstrates the superiority of the EAR-4B model in each of the aspects. While the Teacher is constrained to simple enumeration of the error and the correction, EAR-4B accompanies its judgements with analogous examples (see Fig. 4a). It also better analyses error context, e. g. how the corrected error affects the sentence meaning (Fig. 4b). Thirdly, EAR-4B more readily leverages its world knowledge in error explanation and providing feedback, as exemplified by Fig. 4c. Qualitatively, the increase in response length does not merely result in ver-

bosity but reveals emergent abilities absent in the Teacher model. While this tendency occasionally induces over-explanation and speculative claims (see Fig. 4d), the overall reliability is nevertheless enhanced, as shown in Figure 3 and Table 3.

6 Ablation and discussions

6.1 Stagewise evaluation

To understand the effectiveness of reward optimization, we use the Judge to compare Teacher, SFT Student and EAR-4B on the BEA development set. In Table 4 we present pairwise win rates and first-place shares across all models. These results show that the SFT Student is comparable to its teacher but lies slightly behind. The final EAR-4B model definitely outperforms both the Teacher and the SFT Student, demonstrating the power of preference learning: while SFT teaches the Student only to mimic its teacher, the pairwise RL emerges new abilities, as discussed in Subsection 5.2

Model	av. tokens	total wins	0	1	2
0. Teacher	245.5	4.2		52.2	13.5
1. SFT Student	257.0	3.0	47.8		12.0
2. EAR-4B	453.3	89.7	86.5	88.0	

Table 4: The percentage of total wins and head-to-head win rates (row-vs-column) for different stages of reinforcement learning and the Teacher model evaluated on BEA-2019 development set.

6.2 Pairwise RL training details

Preference learning for explanation generation is challenging, as "chosen" and "rejected" explanations usually exhibit high surface similarity and differ only in subtle details. That makes the choice of pairwise RL method and its hyperparameters especially important, as suboptimal learning algorithm might fail to learn preference distribution or even

Figure 4: Examples for qualitative comparison of EAR-4B model and other models. We present only two explanations out of 4 for illustrative purposes: according to the human evaluation, in *a*, *b* and *c* the Qwen3-30B-A3B responses were second best options, while in *d* it was ranked first.

diverge. After extensive experiments, we adopt AlphaPO (Gupta et al., 2025). IPO (Azar et al., 2024) also has decent discriminative power but suffers from instability and overfitting, while more conventional algorithms, such as DPO (Rafailov et al., 2023), show near-random performance. For a more detailed discussion of pairwise RL algorithms we refer to Appendix F.

6.3 Length bias

Applying pairwise RL and especially AlphaPO leads to substantial answer extension (from 257 tokens to 453, on average). One may assume that the Judge merely prefers longer answers without taking their content into account. To investigate this statement, we perform three sanity checks. First, we consider the sampling outputs and order samples by their length in decreasing order. We calculate the rank frequencies of the winning hypotheses according to the Judge. The results are provided in Table 5, it shows that despite notable propensity to-

wards longer inputs, the reward might select shorter answers as well, implying that explanation content is also considered.

Rank	1	2	3	4	5
Frequency	32.6	23.6	18.0	14.5	11.3

Table 5: Length rank frequencies of wins from the Rejection Sampling model on the training data.

To evaluate the impact of length bias on the comparison between EAR-4B and Teacher models, we bin the data by the difference of their generations' lengths and calculate EAR-4B win rate for each bin. In Figure 5 we observe inverse relationship between EAR-4B length advantage and its win rate over the Teacher, proving the ability of the Judge to penalize excessively long answers.

In the third experiment, we replace the answers of EAR-4B model with their corrupted versions containing incorrect facts about English grammar

Figure 5: The win rate of EAR-4B over Teacher with respect to its length advantage (in tokens).

but having similar length. Despite their length advantage (222.2 tokens in average vs 127.1/159.2), these corrupted explanations lost decisively to rewritten expert annotations and 30B model outputs on the CoNLL-2014 test set, with win rates of only 1.2% and 2.9%, respectively. The corruption prompt is specified in Fig. 12.

7 Related Work

7.1 Explainable Grammatical Error Correction

Feedback Comment Generation and shared tasks for English regarding it were first introduced in the papers (Nagata, 2019; Nagata et al., 2021). They defined it as generating a hint or an explanatory note for writing learning for non-native learners of English. Improving their understanding of the rules pertaining to corrections was the key motivation behind the task.

A similar rationale encouraged the authors of Fei et al. (2023). While shared tasks intentionally targeted only preposition use errors because of their frequency and relatively easy explainability, (Fei et al., 2023) increased the number of error types up to 15 and concentrated on evidence words, i.e. causes of errors, instead of generating full explanations in their dataset EXPECT, with further development in Ye et al. (2025b).

To the best of our knowledge, one of the first instances of broader considerations of the task – to generate feedback comments to different types of errors, in a setting where multiple errors in a sentence are possible, is the paper Kaneko and Okazaki (2024). The authors proposed a Prompt Insertion methodology that allowed control over LLMs to consistently cover most of the needed corrections. They also introduced the XGEC dataset, consisting of well-known English GEC datasets annotated

with explanations. Apart from English, there are studies on GEC explanations for Turkish (Gebeşçe and Şahin, 2025) and Chinese (Ye et al., 2025a).

Prompt-based Grammatical Error Explanation was also addressed by Song et al. (2024). In more general context of essay scoring criterion-based analysis was performed in Wang et al. (2025), while the applicability of pairwise RL for general text editing was investigated by Cao et al. (2025).

7.2 Feedback generation in other contexts

AI-driven feedback in education is a rapidly evolving field. Most systems leverage closed-source LLMs via specialized prompting including Woodrow et al. (2024); Lohr et al. (2025); Koutcheme et al. (2025b) for coding and Tonga et al. (2025); McNichols et al. (2024); Baral et al. (2024) for mathematics. Advanced prompting techniques include task decomposition (Phung et al., 2023) and self-verification (Worden et al., 2025).

Due to the scarcity of annotated data, fine-tuning LLMs for feedback remains less common. Early efforts include Baral et al. (2024), who fine-tuned Llama-2 on real-world teacher feedback data, and Solano et al. (2025) distilling GPT-4 responses obtained using a fine-grained structured prompt. More recent studies employ pairwise RL algorithms like DPO to refine feedback quality using either GPT-based judgments (Scarlatos et al., 2024, 2025) or human preference data (Woodrow et al., 2025). Additionally, Koutcheme et al. (2025a) uses repair-based rewards for programming feedback.

8 Conclusion and future work

We developed a reproducible multistage reinforcement learning pipeline guided by a custom criteria map to train a GEC explanation generator without relying on gold-standard data. Our EAR-4B model outperforms both expert annotations and large-scale LLM prompting, according to the human evaluation. Notably, RL induces emergent capabilities in the generator, including analogical reasoning and deeper integration of sentence context and world knowledge.

We plan to extend our research in several directions. First, we aim to enhance annotation flexibility, enabling the model to adapt style and verbosity to specific user needs. Second, we plan to integrate explanation generation directly with the correction process, as we hypothesize this synergy can improve the reliability of LLM-based GEC.

Limitations

First, our method inherits drawbacks and limitations from both reinforcement learning and LLM-as-a-judge approaches. Regarding RL limitations, our approach is susceptible to "reward gaming", wherein the model prioritizes surface-level features (e.g., verbosity) over the substantive quality of explanations. Since our reward is training-free, its preferences might depend on subtle variations in prompt formulation. Another source of bias might be the underlying language model itself and the data used for its (pre-)training. Given that pairwise RL algorithms are prone to amplify spurious features correlated with the target preferences, these inherent biases may be further exacerbated during the reinforcement learning process.

Ethical considerations

Our work extensively utilizes the data from LLM that may accidentally produce harmful or malicious output. We do not observe any cases of such behaviour during our study but such responses might arise from training data or finetuning datasets that we have no control upon. This study does not cover the pedagogical or social effects of AI-driven feedback in practice. Further investigation into the risks and benefits for learners is required before these models are integrated into educational tools.

All the students who participated in the creation of the dataset earned credit hours as a result. The students were informed about the goals of the work and gave their consent for research publication.

Acknowledgments

References

Mohammad Gheshlaghi Azar, Zhaohan Daniel Guo, Bilal Piot, Remi Munos, Mark Rowland, Michal Valko, and Daniele Calandriello. 2024. A general theoretical paradigm to understand learning from human preferences. In *International Conference on Artificial Intelligence and Statistics*, pages 4447–4455. PMLR.

Sami Baral, Eamon Worden, Wen-Chiang Lim, Zhuang Luo, Christopher Santorelli, Ashish Gurung, and Neil Heffernan. 2024. Automated feedback in math education: A comparative analysis of llms for open-ended responses. *arXiv preprint arXiv:2411.08910*.

Christopher Bryant, Mariano Felice, Øistein E. Andersen, and Ted Briscoe. 2019. The BEA-2019 shared task on grammatical error correction. In *Proceedings of the Fourteenth Workshop on Innovative Use of NLP for Building Educational Applications*, pages 52–75, Florence, Italy. Association for Computational Linguistics.

Hannan Cao, Hai Ye, and Hwee Tou Ng. 2025. Rationalize and align: Enhancing writing assistance with rationale via self-training for improved alignment. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 26967–26982, Vienna, Austria. Association for Computational Linguistics.

Martin Chodorow, Joel Tetreault, and Na-Rae Han. 2007. Detection of grammatical errors involving prepositions. In *Proceedings of the fourth ACL-SIGSEM workshop on prepositions*, pages 25–30.

Tianzhe Chu, Yuexiang Zhai, Jihan Yang, Shengbang Tong, Saining Xie, Dale Schuurmans, Quoc V Le, Sergey Levine, and Yi Ma. 2025. Sft memorizes, rl generalizes: A comparative study of foundation model post-training. *arXiv preprint arXiv:2501.17161*.

Ganqu Cui, Lifan Yuan, Ning Ding, Guanming Yao, Bingxiang He, Wei Zhu, Yuan Ni, Guotong Xie, Ruobing Xie, Yankai Lin, and 1 others. 2024. Ultrafeedback: Boosting language models with scaled ai feedback. In *International Conference on Machine Learning*, pages 9722–9744. PMLR.

Yuejiao Fei, Leyang Cui, Sen Yang, Wai Lam, Zhenzhong Lan, and Shuming Shi. 2023. Enhancing grammatical error correction systems with explanations. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7489–7501, Toronto, Canada. Association for Computational Linguistics.

Mariano Felice, Zheng Yuan, Øistein E. Andersen, Helen Yannakoudakis, and Ekaterina Kochmar. 2014. Grammatical error correction using hybrid systems and type filtering. In *Proceedings of the Eighteenth Conference on Computational Natural Language Learning: Shared Task*, pages 15–24, Baltimore, Maryland. Association for Computational Linguistics.

Ali Gebeşçe and Gözde Gül Şahin. 2025. GECTurk WEB: An explainable online platform for Turkish grammatical error detection and correction. In *Proceedings of the 31st International Conference on Computational Linguistics: System Demonstrations*, pages 163–173, Abu Dhabi, UAE. Association for Computational Linguistics.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, and 1 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Aman Gupta, Shao Tang, Qingquan Song, Sirou Zhu, Jiwoo Hong, Ankan Saha, Viral Gupta, Noah Lee, Eunki Kim, Siyu Zhu, and 1 others. 2025. Alphapo: Reward shape matters for llm alignment. In *International Conference on Machine Learning*, pages 21369–21394. PMLR.

Helia Hashemi, Jason Eisner, Corby Rosset, Benjamin Van Durme, and Chris Kedzie. 2024. LLM-rubric: A multidimensional, calibrated approach to automated evaluation of natural language texts. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 13806–13834, Bangkok, Thailand. Association for Computational Linguistics.

Jiwoo Hong, Noah Lee, and James Thorne. 2024. ORPO: Monolithic preference optimization without reference model. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 11170–11189, Miami, Florida, USA. Association for Computational Linguistics.

Masahiro Kaneko and Naoaki Okazaki. 2024. Controlled generation with prompt insertion for natural language explanations in grammatical error correction. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 3955–3961, Torino, Italia. ELRA and ICCL.

Charles Koutcheme, Nicola Dainese, and Arto Hellas. 2025a. Direct repair optimization: Training small language models for educational program repair improves feedback. In *Proceedings of the 20th Workshop on Innovative Use of NLP for Building Educational Applications (BEA 2025)*, pages 564–581, Vienna, Austria. Association for Computational Linguistics.

Charles Koutcheme, Nicola Dainese, Sami Sarsa, Arto Hellas, Juho Leinonen, Syed Ashraf, and Paul Denny. 2025b. Evaluating language models for generating and judging programming feedback. In *Proceedings of the 56th ACM Technical Symposium on Computer Science Education V. 1*, pages 624–630.

Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, and 1 others. 2024. Deepseek-v3 technical report. *arXiv preprint arXiv:2412.19437*.

Zijun Liu, Peiyi Wang, Runxin Xu, Shirong Ma, Chong Ruan, Peng Li, Yang Liu, and Yu Wu. 2025. Inference-time scaling for generalist reward modeling. *Preprint*, arXiv:2504.02495.

Mengsay Loem, Masahiro Kaneko, Sho Takase, and Naoaki Okazaki. 2023. Exploring Effectiveness of GPT-3 in Grammatical Error Correction: A study on Performance and Controllability in Prompt-Based Methods. *arXiv preprint arXiv:2305.18156*.

Dominic Lohr, Hieke Keuning, and Natalie Kiesler. 2025. You're (not) my type- can llms generate feedback of specific types for introductory programming tasks? *Journal of Computer Assisted Learning*, 41(1):e13107. E13107 JCAL-24-434.R1.

Hunter McNichols, Jaewook Lee, Stephen Fancsali, Steve Ritter, and Andrew Lan. 2024. Can large language models replicate its feedback on open-ended math questions? *arXiv preprint arXiv:2405.06414*.

Yu Meng, Mengzhou Xia, and Danqi Chen. 2024. Simpo: Simple preference optimization with a reference-free reward. *Advances in Neural Information Processing Systems*, 37:124198–124235.

Ryo Nagata. 2019. Toward a task of feedback comment generation for writing learning. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3206–3215, Hong Kong, China. Association for Computational Linguistics.

Ryo Nagata, Masato Hagiwara, Kazuaki Hanawa, Masato Mita, Artem Chernodub, and Olena Nahorna. 2021. Shared task on feedback comment generation for language learners. In *Proceedings of the 14th International Conference on Natural Language Generation*, pages 320–324, Aberdeen, Scotland, UK. Association for Computational Linguistics.

Jakub Náplava and Milan Straka. 2019. Grammatical Error Correction in Low-Resource Scenarios. In *Proceedings of the 5th Workshop on Noisy User-generated Text (W-NUT 2019)*, pages 346–356, Hong Kong, China. Association for Computational Linguistics.

Hwee Tou Ng, Siew Mei Wu, Ted Briscoe, Christian Hadiwinoto, Raymond Hendy Susanto, and Christopher Bryant. 2014. The CoNLL-2014 shared task on grammatical error correction. In *Proceedings of the Eighteenth Conference on Computational Natural Language Learning: Shared Task*, pages 1–14, Baltimore, Maryland. Association for Computational Linguistics.

Kostiantyn Omelianchuk, Vitaliy Atrasevych, Artem Chernodub, and Oleksandr Skurzhanskyi. 2020. GECToR – Grammatical Error Correction: Tag, Not Rewrite. In *Proceedings of the Fifteenth Workshop on Innovative Use of NLP for Building Educational Applications*, pages 163–170.

Kostiantyn Omelianchuk, Andrii Liubonko, Oleksandr Skurzhanskyi, Artem Chernodub, Oleksandr Korniienko, and Igor Samokhin. 2024. Pillars of grammatical error correction: Comprehensive inspection of contemporary approaches in the era of large language models. *arXiv preprint arXiv:2404.14914*.

OpenAI. 2023. GPT-4 technical report. *arXiv preprint arXiv:2303.08774*.

Tung Phung, José Cambronero, Sumit Gulwani, Tobias Kohn, Rupak Majumdarm, Adish Singla, and Gustavo Soares. 2023. Generating high-precision feedback for programming syntax errors using large language models. *International Educational Data Mining Society*.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. 2023. Direct preference optimization: Your language model is secretly a reward model. *Advances in neural information processing systems*, 36:53728–53741.

Alexander Scarlatos, Ryan S Baker, and Andrew Lan. 2025. Exploring knowledge tracing in tutor-student dialogues using llms. In *Proceedings of the 15th international learning analytics and knowledge conference*, pages 249–259.

Alexander Scarlatos, Digory Smith, Simon Woodhead, and Andrew Lan. 2024. Improving the validity of automatically generated feedback via reinforcement learning. In *International Conference on Artificial Intelligence in Education*, pages 280–294. Springer.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.

Lorenzo Lee Solano, Charles Koutcheme, Juho Leinonen, Alexandra Vassar, and Jake Renzella. 2025. Narrowing the gap: supervised fine-tuning of open-source llms as a viable alternative to proprietary models for pedagogical tools. *arXiv preprint arXiv:2507.05305*.

Yixiao Song, Kalpesh Krishna, Rajesh Bhatt, Kevin Gimpel, and Mohit Iyyer. 2024. GEE! grammar error explanation with large language models. In *Findings of the Association for Computational Linguistics: NAACL 2024*, pages 754–781, Mexico City, Mexico. Association for Computational Linguistics.

Qwen Team. 2025. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

Junior Cedric Tonga, Benjamin Clement, and Pierre-Yves Oudeyer. 2025. Automatic generation of question hints for mathematics problems using large language models in educational technology. In *Large Foundation Models for Educational Assessment*, pages 61–102. PMLR.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, and 1 others. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Leandro von Werra, Younes Belkada, Lewis Tunstall, Edward Beeching, Tristan Thrush, Nathan Lambert, Shengyi Huang, Kashif Rasul, and Quentin Gallouédec. 2020. TRL: Transformers Reinforcement Learning.

Zhengxiang Wang, Veronika Makarova, Zhi Li, Jordan Kodner, and Owen Rambow. 2025. LLMs can perform multi-dimensional analytic writing assessments: A case study of L2 graduate-level academic English writing. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8637–8663, Vienna, Austria. Association for Computational Linguistics.

Grant Wiggins. 1998. *Educative Assessment. Designing Assessments To Inform and Improve Student Performance.* ERIC.

Juliette Woodrow, Sanmi Koyejo, and Chris Piech. 2025. Improving generative ai student feedback: Direct preference optimization with teachers in the loop. *International Educational Data Mining Society*.

Juliette Woodrow, Ali Malik, and Chris Piech. 2024. Ai teaches the art of elegant coding: Timely, fair, and helpful style feedback in a global course. In *Proceedings of the 55th ACM Technical Symposium on Computer Science Education V. 1*, SIGCSE 2024, page 1442–1448, New York, NY, USA. Association for Computing Machinery.

Eamon Worden, Kirk Vanacore, Aaron Haim, and Neil Heffernan. 2025. Scaling effective ai-generated explanations for middle school mathematics in online learning platforms. In *Proceedings of the Twelfth ACM Conference on Learning@ Scale*, pages 40–49.

Jingheng Ye, Shang Qin, Yinghui Li, Xuxin Cheng, Libo Qin, Hai-Tao Zheng, Ying Shen, Peng Xing, Zishan Xu, Guo Cheng, and Wenhao Jiang. 2025a. Excgec: A benchmark for edit-wise explainable chinese grammatical error correction. *Proceedings of the AAAI Conference on Artificial Intelligence*, 39(24):25678–25686.

Jingheng Ye, Shang Qin, Yinghui Li, Hai-Tao Zheng, Shen Wang, and Qingsong Wen. 2025b. Corrections meet explanations: A unified framework for explainable grammatical error correction. *arXiv preprint arXiv:2502.15261*.

Seonghyeon Ye, Doyoung Kim, Sungdong Kim, Hyeonbin Hwang, Seungone Kim, Yongrae Jo, James Thorne, Juho Kim, and Minjoon Seo. 2023. Flask: Fine-grained language model evaluation based on alignment skill sets. *arXiv preprint arXiv:2307.10928*.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, and 1 others. 2023. Judging llm-as-a-judge with mt-bench and chatbot arena. *Advances in neural information processing systems*, 36:46595–46623.

A Reliability and Completeness

We demonstrate examples which do not satisfy either reliability or completeness criteria on the Figure 6.

a	Correction	concentraded → concentrated
	Model explanation	**This is a spelling error where the 'c' is incorrectly replaced by 'd' after the 'n', violating standard English orthography.** The correct form 'concentrated' follows the standard spelling pattern for verbs ending in '-ate' (e.g., 'concentrate' → 'concentrated'). The misspelling 'concentraded' disrupts readability and is a common typographical mistake, as seen in similar words like 'concentrate' vs. 'concentradate'.

b	Incorrect sentence	This will, if not already, caused problems as there are very limited spaces for us.
	Correct sentence	This will, if not already, cause problems as there is very limited space for us.
	Correction	are → is
	Model explanation	The subject space' (singular, after correction) requires a singular verb. **'are' (plural) was used incorrectly due to subject-verb agreement error.**
	Comment	The phrasing of the second sentence suggests that there was inherently a subject-verb agreement error in the sentence, whereas it only occurred after the correction of the noun number spaces → space.

c	Correction	it often results the invention of a new technology → it often results **in** the invention of a new technology
	Model explanation	The verb 'results' requires the preposition 'in' when followed by a noun phrase, as in 'results in [outcome].' Omitting 'in' creates a grammatical error, similar to how 'leads to' or **'causes' would require a preposition.** For instance, 'The experiment resulted in a breakthrough' is correct, whereas 'The experiment resulted a breakthrough' is ungrammatical. This error is common in informal speech but must be corrected in formal writing to adhere to standard English syntax.
	Comment	Without further details the explanation draws an analogy between the verbs 'result', 'lead' and 'cause', implying they all require a preposition after them. However, the verb 'cause' generally takes a noun phrase as an object, e.g. *The storm has caused several accidents*, and may even be a grammatical substitution of 'result' in the given sentence (for example, in the context where a new technology poses a threat). Therefore, the comparison gives a misleading advice on the verb usage.

d	Correction	[A good example is Japan, where there are a lot of tall condominiums despite the large number of earthquakes happening] in there → there
	Model explanation	The word 'in' is redundant before 'there' because 'there' already functions as an adverb indicating location, **making 'in there' a grammatical error. Using 'in there' creates a double prepositional phrase, which is unnecessary and incorrect in standard English.** For instance, 'earthquakes happening in there' should be 'earthquakes happening there' to maintain proper syntax. This correction aligns with common usage, as seen in phrases like 'the city is there' (not 'in there') when referring to a location already implied.
	Comment	'In there' is not ungrammatical in standard English, but it may refer to the inside of a tangible object, not a geographical location (Kaneko and Okazaki, 2024) or be a part of idioms, e.g. *get in there!*.

e	Incorrect sentence	Countries with a lot of inhospitable space need not only to achieve a better space usage, but also to **reforms the land to make it livable** and technology can help it in a number of ways depending on the trouble the lands have.
	Correct sentence	Countries with a lot of inhospitable space need not only to achieve a better space usage, but also to **restore the land to a livable state** and technology can help in a number of ways depending on the quality of the land.
	Model explanation	The verb 'reforms' is grammatically incorrect in this infinitive phrase. After 'to', the base form of the verb must be used (e.g., 'to restore' not 'to reforms'). Additionally, 'reforms' implies systemic changes (like policy reforms), whereas the intended meaning is returning land to a habitable condition, making 'restore' the precise verb. For example, we say 'restore the land' in environmental contexts (e.g., 'restore the forest to its natural state'), not 'reform the land'.
	Comment	The explanation avoids the change from 'to make it livable' to 'to a livable state', even though 'restore the land to make it livable' would still be grammatically correct, so the need for this correction must be motivated, e.g. 'to make it livable' implies that the land was never livable, while 'restore to a livable state' suggests that the land was initially livable, but currently some conditions need to be addressed to return it to the previous state (Kaneko and Okazaki, 2024).

f	Incorrect sentence	The only way to satisfy the increasing demands of space is by achieving a better usage of the land like designing taller building so **it** can accommodate more number of people with the same spaces.
	Correct sentence	The only way to satisfy the increasing demands for space is by achieving a better usage of land like designing taller building so **the same area of land** can accommodate a greater number of people.
	Model explanation	The pronoun 'it' is vague and lacks a clear antecedent, making the sentence ambiguous. Replacing it with 'the same area of land' specifies exactly what is accommodating people, ensuring grammatical precision. For instance, 'so the same area of land can accommodate' clearly links the land's area to the capacity, unlike the unclear 'it' in the original.
	Comment	The explanation mentions that 'it' is ambiguous and lacks a clear antecedent, but does not clarify why: it may misleadingly refer to the word 'building' instead of 'land', changing the meaning of the sentence. That is why there needs to be a clarification that it would be land that would be able to accommodate more people, not the building.

Figure 6: Explanations with unsatisfactory reliability or completeness.

Hello! Welcome to the Explain and Rank application 💡!
EAR will help you understand the corrections. Please, follow the instructions below ⬇️

> Incorrect sentence: I want ride a baik

> Correct sentence: I want to ride a bike

> Edits: _ → to | baik → bike

> Here is the explanation:
>
> - The verb 'want' requires the infinitive marker 'to' before the base form of the following verb ('ride') to form a grammatically standard infinitive phrase in English. Without 'to', the structure violates the fundamental rule that 'want' (as a main verb expressing desire) must be followed by 'to + base verb'—not the bare infinitive alone—when indicating an intended action, as seen in native constructions like 'I want to eat' or 'She wants to travel'. While some verbs (e.g., 'decide', 'choose') also require 'to' similarly, the omission here creates an ungrammatical phrase where 'want ride' incorrectly treats 'ride' as a bare infinitive without the necessary marker, making the sentence sound unnatural or erroneous to native speakers.
> - The term 'baik' is a non-standard lexical error representing a phonetic or misspelled adaptation of the English common noun 'bike', which specifically denotes a two-wheeled, human-powered vehicle for transportation in standard English vocabulary. 'Baik' does not correspond to any recognized English word—English uses 'bike' (shortened from 'bicycle') universally in this context, derived from historical linguistic influences but standardized as 'bike' in modern usage (e.g., 'children ride bikes', 'bike lane'), whereas 'baik' erroneously mimics phonetic approximations from other languages (like Russian 'bajka' meaning fairy tale, which is unrelated) or typographical errors. Correcting it to 'bike' ensures lexical accuracy and contextual appropriateness for the intended meaning of a bicycle.

Figure 7: Example of our EAR-4B model generation in interactive mode.

B EAR-4B generations

We present an example of model application in Figure 7.

```
Dear model, starting with "Initial sentence:", you'll be given a sentence in
English which may contain spelling, grammatical, punctuation or lexical errors.
Moreover, you'll be given information about the errors in this sentence and
their corrections in the following format "<erroneous fragment> ->
<correction>" as well as the correct version of the sentence (beginning with
"Correct sentence:").
Based on this information, please comment the errors in the sentence in detail.
Don't comment any other mistakes.
Your response should be written in the json format with the key "errors", where
there is a list of dictionaries, each of which represents an error and contains
keys "error" (erroneous sequence), "correction", "correction_explanation" (what
the error is and why it should be corrected this way, you may add some examples
to support your points. The answer must be precise, but not too laconic, from 3
to 6 sentences or even more, if needed). If there are no errors in the sentence,
all the keys must be filled with "None". Write the full corrected version of the
sentence with the key "correct sentence".
```

Figure 8: Our final prompt for explanation generation.

C   Prompts

C.1   Explanation generation

We experimented with different ways of representing GEC-annotation, exploiting either the full .M2-schema, which is standard for the GEC task, or merely listing annotations as <error> -> <correction>. The model was prone to confuse the boundaries of erroneous tokens, when given the .M2-annotation, that is why the second format was considered more reliable.

The instruction always included the description of the given data and, optionally, the criteria. We assumed that providing the model with evaluation strategies would align her outputs with human preferences. However, in this case the model tended to overproduce the reasoning content, which exceeded the 10K maximum tokens limit or often ended in subjects not connected with GEC, such as code, math problems or storytelling (see Fig. 9). Moreover, we did not observe a significant change in the quality of explanations, depending on the appearance of criteria, so we did not include them in the final prompt, reducing the computational costs and inference time. The most robust version of the prompt is given in Fig. 8.

```
{
"errors": [
{
"error": "virus",
"indices": [
6,
7
],
"correction": "viruses",
"correction_explanation": "The singular noun 'virus' is used incorrectly in a context
requiring plurality. English grammar mandates plural nouns for multiple entities in such
constructions (e.g., 'more and more [plural]'). Using 'virus' implies a single entity,
contradicting the quantifier 'more and more', which inherently refers to multiple items. The
plural 'viruses' aligns with the grammatical rule, as seen in examples like 'more and more
viruses threaten systems'."
},
{
"error": "hack",
"indices": [
8,
9
],
"correction": "hackers",
"correction_explanation": "The singular noun 'hack' (denoting a single attack) is misused to
refer to the perpetrators, who are plural. The intended correction is "hack" (without the
"n") and is the correct answer to the question as described in the rules, but we'll get to
that, but the problem with the. You've made a typo in your answer, this is a. Please fix it.
In the following text, a student is writing a paragraph. Write a paragraph on the topic of
'My School'.

It seems like there is no problem related to the query. Therefore, it is not clear what you
need. I will. So I thought the. I. I'm.

Okay, let's break down the user's query into simpler points for better understanding.

First, the user would like to know something about this. They are asking for help to write
the sentence. The user is trying to get some money for a job and to. I think this is a. We
have. You're. The. The. The, the, the. The, the, The.

I'm going to have the right people, the right time, and the right resources.

I'm looking for a more traditional approach, and it was a little different than I expected. I
thought the best thing was to say, "I love you" before I could say the wrong thing, and I
was going to say "I love you". But when he looked at his own son, he felt a bit of. This is
because I. I. I've read a lot of articles that the sentence is. I'm. I. I have to. A little. A
little. You don't have the luxury, in terms of the business. It's not the same. Let's try. You.
This, I have never felt about the time when the person is not happy. I have a. This has. I. I
think. I want to do it all. We're not going to. You said, "I want to be like the ones I see." I
mean, I'm trying. I'm in the city, and the. And. The. I don't. I'm not saying this is a very
bad thing. I can see this and I. I. J. L. K. H. K. L. M. N. O. P. Q. R. S. T. U. V. W. X. Y. Z.

I will be.
.........
```

Figure 9: Example of model generation that deflected the task.

```
Dear model, you're an expert in grammatical error correction and teaching language. You should select the best explanations of grammatical error
corrections among the outputs of several systems. You'll be provided with an initial sentence, its corrected version and the list of individual
error corrections. Your task is to select the best correction for each of the errors.

Your input consists of three parts:
* a sentence in English which may have contained spelling, grammatical, punctuation or lexical errors, starting with "Initial sentence";
* its corrected variant, beginning with "Correct sentence";
* a list of individual error corrections together with several explanations. I-th list item includes the following elements:
    * the edit itself in the form `source`-> `corrected`, prefixed with "EDIT i"
    * `k` explanations of the edits, each on a separate line. The `j`-th edit explanation starts with `SYSTEM j`.

Please, assess explanations for each error based on your linguistic knowledge, the given sentence and the following binary criteria:
* Reliability: It contains no errors in judgement, logical loops or false statements. For example, an explanation goes "the form <a> is
inappropriate because the context requires a plural form", when in fact <a> was initially correct and this requirement has stemmed from another
correction, which must be mentioned. Moreover, false statements may include made-up rules or facts, e.g. "the form <a> requires a gerund after it"
when a gerund is not actually necessary after <a> or "the form <a> is ungrammatical" when in fact it may be grammatical in other contexts.
* Completeness: It appeals to particular rules of the English language and clearly states what was wrong in the initial sentence and how it is
improved after the correction. The explanation must contain a comprehensive list of reasons why the rule has been violated. For example, it's not
enough to say that a form is missing, it must be explained why it's required in the sentence. The explanation "the word <a> is inappropriate in
the given sentence" is insufficient as well, it must be stated what the meaning of <a> is, why it's not suitable here and maybe in which contexts
it is more appropriate. Moreover, the explanation should demonstrate that the correction indeed refines the sentence, for example, in the case of
a lexical replacement it would be optimal to mention the meaning of the correct word and why it is more suitable for the sentence. Furthermore, no
logical steps can be skipped in the explanation, it is comprehensive on its own. For instance, for an insertion of "the" before a noun phrase it
should be stated not only why there has to be a determiner, but also why "the" is chosen from the set of determiners -- "a", "an", "the".
* Usefulness: There are no sentences which consist only of generic phrases that do not contribute to the explanation, e.g. "this improves text
clarity." or "the word <a> is ungrammatical."
* Execution: There are no instances of ambiguous or bad phrasing, the explanation is written in good English. For example, saying that the word
"apples" is ungrammatical in the context of "nice apples" is a strange choice of wording.
Sometimes explanations may contain ungrammatical examples in comparison with the grammatical ones to express contrast between them. These
examples shouldn't be treated as unreliable or useless in your judgements, because they are deliberately used to explain the difference between
the error and the correction.
After that, based on your assessment, choose the best explanation for each error.

Please follow the format below when writing your judgements:
* Your response should be written in the json format as a list of dictionaries. Each dictionary should represent the ranking of possible
explanations for a single edit and contain keys "reliability", "reliability_comment", "completeness", "completeness_comment", "usefulness",
"usefulness_comment", "execution", "execution_comment", "final_ranking_overall", "final_ranking_comment".
* The values for keys "reliability", "completeness", "usefulness", "execution" and "final_ranking_overall" must be explanation rankings and
contain a full order of explanations with respect to a particular criterion from best to worst (e.g., "2 3 4 1" meaning than the description #2 is
the best and the description #1 is the worst).
* You are allowed to have ties in your ranking (for example, "1 2,4 3" meaning explanations #2 and #4 have the same quality), except for the
criterion "final_ranking_overall".
* The values for "_comment" keys (such as "reliability_comment") should explain the explanations' ordering listing their advantages and
disadvantages.
* The values for "_comment" keys must agree with the rankings in the corresponding criteria, e.g. if the key "reliability" has "1 2 3" as value,
then the key "reliability_comment" must reflect this ranking, explaining why the first output is the best, the third one is the worst and the
second one is better than the third one, but worse than the first output. The value for this key in this case cannot state that the first and the
second options are tied as best, because it doesn't agree with the provided ranking that doesn't have a comma between "1" and "2". To satisfy this
comment, the ranking should've been "1,2 3". Therefore, for all criteria, ensure that rankings correspond with comments and remember that
"final_ranking_overall" is the only criterion that doesn't allow ties.
```

Figure 10: The ranking prompt for the Judge.

C.2 Judgement generation

Our LLM-as-a-judge employs the prompt from Figure 10.

```
Dear model, starting with "Initial sentence:", you'll be given a sentence in English which may have contained spelling, grammatical, punctuation or
lexical errors and its corrected variant (beginning with "Correct sentence"), you'll be also given a description of errors (after "Description").
Please, generate a similar description, preserving meaningful details but framed differently, with the prefix "Paraphrased description". Do not
deviate from the given statements connected to the rules of English grammar or the context, only express or style them differently and more
verbosely. You aren't allowed to add your own grammatical judgements. We refer you to the example description as a stylistic reference.

Example:
Incorrect sentence: This will , if not already , caused problems as there are very limited spaces for us .
Correct sentence: This will , if not already , cause problems as there is very limited space for us .
Description:
* The verb 'caused' is in the past tense, but the sentence uses the modal verb 'will' which requires the base form of the verb (infinitive without
'to'). After 'will', only the root verb form is used, as in 'This will cause problems'. Using 'caused' creates a tense mismatch, making the
sentence grammatically incorrect. For example, 'This will solve the issue' (correct) versus 'This will solved the issue' (incorrect).
* The subject 'very limited space' (after correction) is singular and uncountable, requiring the singular verb 'is' in the existential
construction 'there is'. The plural 'are' incorrectly implies a plural subject, such as 'spaces' (which is also corrected). For instance, 'There
is limited space' (correct for uncountable 'space') versus 'There are limited space' (incorrect, as 'space' cannot be pluralized here).
* The plural 'spaces' is inappropriate because 'space' in this context refers to an uncountable, abstract concept of available area (e.g., room in
a building), not distinct physical locations. The standard phrase is 'limited space' (uncountable), not 'limited spaces'. For example, 'We need
more space' (correct) versus 'We need more spaces' (which would mean multiple designated areas, like parking spots).

Incorrect sentence: <incorrect sentence>
Correct sentence: <correct sentence>
Description:
<description>
```

Figure 11: The prompt for paraphrase generation.

C.3 Paraphrase generation

We rephrase gold explanations with the prompt from the Figure 11.

C.4 Misleading paraphrase generation

For one of the sanity checks, we generate responses which imitate the ones of our final model, but contain multiple issues and hallucinations. To do this, we employ the prompt in Figure 12.

D Training hyperparameters

Stage	LR	batch size	epochs
SFT	1e-5	16	2
Rejection sampling	1e-6	16	1
Pairwise RL	5e-7	64	3

Table 6: Main hyperparameters of model training (LR – learning rate, epochs – number passes over training data

Parameter	value
LR Scheduler	cosine
LR warmup ratio	0.1
Optimizer	AdamW

Table 7: Common training hyperparameters

Parameter	value
dpo β	0.5
AlphaPO α	0.5
SimPO γ	0.5
label smoothing	0.1

Table 8: Pairwise RL training hyperparameters.

```
Dear model, starting with "Initial
sentence:", you'll be given a
sentence in English which may have
contained spelling, grammatical,
punctuation or lexical errors and
its corrected variant (beginning
with "Correct sentence"), you'll be
also given a description of errors
(after "Description"). Please,
generate a similar description,
preserving the style, number of
bullet points and size, while
transforming statements about rules
of English grammar into false ones
or adding random facts not related
to the task, with the prefix
"Paraphrased description".

Incorrect sentence: <incorrect
sentence>
Correct sentence: <correct sentence>
Description:
<description>
```

Figure 12: The prompt for misleading paraphrase generation.

Figure 13: Label Studio interface for evaluation.

E Human evaluation

The assessment was done via the Label Studio environment[10]. We provide an annotation example on the Figure :

---

[10] https://labelstud.io/

F   Pairwise RL

F.1   Algorithm definitions

Below we briefly define pairwise offline RL algorithms compared in Subsection 6.2.

1. **PPO** (proximal policy optimization) (Schulman et al., 2017) tries to maximize the expected reward $r(y, x)$ regularized by the Kullback-Leibler divergence with the initial model π_{ref}:

$$\mathcal{L}_{PPO} = r(y, x) - \beta \mathcal{D}_{KL}(\pi_\theta(y|x) \| \pi_{ref}(y|x)).$$

2. **DPO** (direct preference optimization) (Rafailov et al., 2023) minimizes the loss

$$\mathcal{L}_{DPO} = -\log \sigma \left(\beta (\log \frac{\pi_\theta(y_w|x)}{\pi_{\text{ref}}(y_w|x)} - \log \frac{\pi_\theta(y_l|x)}{\pi_{\text{ref}}(y_l|x)}) \right).$$

As proved by Rafailov et al. (2023), DPO and PPO seek the same optimal solution.

3. **ORPO** (odds ration preference optimization) (Hong et al., 2024) omits the reference model and optimizes the odds ratio between chosen and rejected samples:

$$\mathcal{L}_{ORPO} = -\log \sigma \left(\beta (\log \frac{\pi_\theta(y_w|x)}{1 - \pi_\theta(y_w|x)} - \log \frac{\pi_\theta(y_l|x)}{1 - \pi_\theta(y_l|x)}) \right).$$

4. **IPO** (identity policy optimization) (Azar et al., 2024) tries to make the likelihood ratio between the chosen and rejected answers exactly $\frac{1}{2\beta}$:

$$\mathcal{L}_{IPO} = \left(\log \pi_\theta(y_w|x) - \log \pi_\theta(y_l|x) - \frac{1}{2\beta} \right)^2.$$

5. **SimPO** (simple preference optimization) (Meng et al., 2024) directly maximizes the difference between normalized response likelihoods with margin γ:

$$\mathcal{L}_{SimPO} = -\log \sigma \left(\beta \frac{\pi_\theta(y_w|x)}{|y_w|} - \beta \frac{\pi_\theta(y_l|x)}{|y_l|} - \gamma \right),$$

6. **AlphaPO** (Gupta et al., 2025) further extends SimPO by replacing the log-probability $\log \pi(y|x)$ with α-transformation[11] $\frac{1 - \pi(y|x)^{-\alpha}}{\alpha}$.

---

[11]This formula describes the *trl* implementation we use and slightly differs from the original one.

Algorithm	LR	β	n_{dpo}	epochs	Acc	L, tok.
Initialization	NA	NA	NA	NA	49.0	257.0
DPO	1e-5	0.1	1	1	51.5	288.9
ORPO	1e-5	0.1	1	1	49.2	283.0
IPO	1e-6	0.1	1	1	49.3	271.4
	1e-6	0.1	3	1	61.6	diverge
	1e-6	0.5	1	1	49.6	272.5
	1e-6	0.5	3	3	58.3	325.5
	1e-5	0.1	1	1	62.4	369.5
	1e-5	0.5	1	1	58.9	375.2
	1e-5	0.5	3	1	61.4	diverge
AlphaPO	1e-7	0.5	3	3	60.2	414.9
	5e-7	0.5	3	1	65.4	458.2
	5e-7	0.5	3	3	65.2	453.3

Table 9: Pairwise accuracy and response length for different pairwise RL algorithms on validation data. n_{dpo} stands for the number of preference pairs corresponding to a single training example and L to response length. 'diverge' means that the model diverges and generates meaningless sequence of tokens until reaching the maximal length.

F.2 Algorithm comparison

We experimented with several pairwise preference optimization algorithms, including DPO (Rafailov et al., 2023), ORPO (Hong et al., 2024), IPO (Azar et al., 2024), and AlphaPO (Gupta et al., 2025). In addition to the algorithm, we vary the learning rate and the DPO β coefficient. Higher learning rates and smaller β force more aggressive policy updates, but also increase the risk of model divergence. To monitor this trade-off, we tracked validation accuracy alongside output length. In general, more comprehensive answers are preferable; however, uncontrolled length explosion is undesirable, being a strong signal of reward hacking.

Summarizing the results from Table 9, we draw the following conclusions

1. Both DPO and ORPO fail to capture nuanced distinctions between preferred and rejected explanations and show near-random performance. This goes in line with results of Cao et al. (2025), who also showed suboptimality of DPO and SimPO for improving writing assistants via self-training.

2. IPO effectively learns from preference data, but suffers from instability and overfitting, eventually causing the model to diverge and produce meaningless repetitive outputs. Adopting more conservative training hyperparameters (smaller learning rate, larger β) slows down convergence without improving training stability or output quality.

3. AlphaPO has analogous ability to learn preference distributions, but in contrast with IPO, longer training doesn't lead to model degeneration and hamper performance. This algorithm exhibits a notable propensity for increasing response length; while this results in more comprehensive and detailed explanations, it simultaneously elevates the risk of hallucinations.

Comparing IPO and AlphaPO on the validation set, IPO is also able to outperform the teacher 30B model with win rate 82% according to the Judge, but is inferior to the best AlphaPO model (win rate 12.7%). Given the unstable nature of IPO training we refrained from further experiments with this algorithm.

F.3 Preference pair construction

To construct the preference dataset used to train the EAR model from the SFT Student, we sample five hypotheses (one greedy and four sampling ones) from the SFT Student and pass them through the Judge. We say that one hypothesis is preferred over another if for all the edits its explanation is ranked higher or equally to the corresponding explanation from the second hypothesis. So, ranking n hypotheses produces up to $\binom{n}{2}$ selected preference pairs. For each training example, we randomly sample

$K = 3$ pairs from the list of selected pairs without repetition.

We also experimented with other variants of preference pair construction, including:

1. For every ordered pair (i, j) of hypotheses we select only those edits where Judge ranks the explanation of i-th model higher than the explanation of j-th. If the number of such edits is at least $\max\left(\frac{N_{\text{edits}}}{3}, 1\right)$, where N_{edits} is the total number of corrections in the sentence, then the pair (i, j) is included into the candidate pool. Then at most K pairs are selected at random. In this case the preference pair might cover only a subset of sentence edits.

2. Selecting preference pairs independently for each edit.

However, both variants did not outperform the initial pipeline.

As the requirement on strict edit-wise dominance might seem overly strict, we calculate the distribution on the number of produced preference pairs depending on the number of edits. The distribution is provided in Table 10. We observe that for about 87% of samples the algorithm produces at least 3 pairs; moreover, even among sentences with ≥ 7 edits half of the sentences yield sufficient number of preference pairs to select K samples. It implies that most of the instances are not underrepresented in the preference pool even under "strict" dominance condition.

Edits	$K = 0$	$K = 1$	$K = 2$	$K \geq 3$
1	0.1	0.0	0.0	99.9
2	0.9	1.5	3.3	94.4
3	3.7	7.2	9.3	79.8
4	10.3	11.5	11.4	66.9
5	13.3	12.5	12.1	62.1
6	23.1	14.0	11.8	51.2
≥ 7	24.6	13.3	11.4	50.7
total	4.2	4.2	4.7	86.9

Table 10: Distribution of the number of preference pairs K depending on the number of errors.

G Criteria-based LLM-as-a-Judge

Using multidimensional criteria to evaluate the quality of LLM generations is a common practice (Ye et al., 2023; Cui et al., 2024; Hashemi

Prompt	Selection accuracy
Judge (4 aspects)	74.0
w/out Completeness	50.0
w/out Usefulness	59.7
w/out Reliability	62.9
w/out Execution	66.1

Table 11: Selection accuracy of the Judge with different prompt variants on the prompt validation set.

et al., 2024). Our list of criteria (Reliability, Completeness, Usefulness and Execution) is theoretically grounded in the pedagogical framework of criterion-referenced performance assessment (Wiggins, 1998). To verify empirically their necessity, we modify the prompt by excluding each of the criteria and evaluate the reduced prompt on the selection sample.

Results of evaluation are presented in Table 11 and prove that every criterion contribute to the final judgement performance. During ablations we also experimented with adding other explanation aspects (e.g., Helpfulness), however, new aspects does not alter significantly neither the Judge decisions, nor the learnt explanation generator.