Co-Evolving Graph and Text Memory for Training-Free Multi-Hop Question Answering

Abstract

Multi-hop question answering requires coordinating relational and textual evidence across reasoning steps, a combination neither a text corpus nor a knowledge graph can supply alone. Prior work often emphasizes only part of this loop: graph-augmented RAG retrieves from a pre-built or query-updated graph, KGQA systems search within topic-centered subgraphs, and memory-augmented agents maintain evolving memories without continuously reconciling graph memory with textual context. We propose Co-E, a training-free system built around synchronized bidirectional graph-text working memory. A synchronization cycle consolidates textual memory, extracts relational triples into graph memory, and injects graph facts back into the generation context. Because both memories are maintained, they shape subsequent retrieval and generation. Evaluated on six multi-hop QA benchmarks, Co-E improves over comparable training-free open-backbone baselines and is competitive with larger or trained systems.

1 Introduction

Retrieval-augmented generation (RAG) has become the dominant paradigm for knowledge-intensive question answering (Zhao et al., 2024; Singh et al., 2026). Multi-hop questions, however, expose a limitation deeper than retrieval recall. Later evidence often depends on entities, relations, or constraints discovered only after earlier hops are resolved. A passage may reveal a bridge entity that should expand the graph frontier; a graph edge may reveal a constraint that should reshape the next textual query. Standard RAG pipelines cannot perform this update because they select context before reasoning unfolds. Likewise, graph-augmented methods that rely on a pre-built corpus graph or a fixed topic-centered candidate subgraph cannot fully revise their relational state during reasoning, leaving missed bridge entities, noisy edges, and incomplete

paths uncorrected. The central challenge is to maintain a reasoning state in which textual evidence and relational structure revise each other as the answer is constructed.

Existing systems address parts of this problem, but usually privilege one side of the reasoning state. Corpus-graph RAG systems build a graph index before inference and retrieve from it (Dong et al., 2026; Ma et al., 2026; Zhou et al., 2026b). KGQA systems such as ToG (Sun et al., 2024) and ToG 2.0 (Ma et al., 2025) improve graph-based reasoning over knowledge bases, but rely on pre-existing topology and do not maintain paired textual working memory. Graph search methods such as MCTS-KBQA (Xiong et al., 2025) and ReKG-MCTS (Song et al., 2025) navigate a fixed frontier rather than extending it. A parallel line equips agents with evolving memories: HGMem (Zhou et al., 2026a) builds hypergraph memory from retrieved text, SubQRAG (Li et al., 2025a) accumulates extracted triples as graph memory, while SE-Search (Li et al., 2026a), MemSearch-o1 (Zhang et al., 2026), and A-MEM (Xu et al., 2025) maintain textual or reflective memories. These systems show that maintained memory is useful; what remains less explored is how textual and graph memories should revise one another in same reasoning loop.

We argue that this coupling requires **bidirectional, within-step co-evolution of graph and text**. When a passage mentions a new entity, it should become available for graph expansion; when a triple is extracted or retrieved, it should enter the textual context for the next generation step. Without both directions, the system either accumulates unstructured text that must be reinterpreted from scratch, or traverses a graph whose useful facts are not exposed to the generator. We introduce **Co-E** (**Co-E**volving), a training-free multi-hop QA system built around synchronized graph-text working memory. Co-E maintains a shared memory with two coupled stores: question-relevant text

snippets and graph memory containing KB-schema and open-vocabulary triples. At each step, Co-E retrieves from text and knowledge-base streams, filters evidence, and applies a four-operation synchronization cycle: it consolidates textual evidence, extracts and merges triples into graph memory, injects surviving graph facts back into textual memory, and re-consolidates the context. This cycle lets text expand the graph frontier while graph structure grounds subsequent generation. Because the same mechanism operates during inference, Co-E requires no fine-tuning and serves both multi-hop text-QA and KGQA settings.

Empirically, Co-E achieves strong results across six benchmarks spanning text-QA and KGQA. With a Qwen3-8B backbone and no training, Co-E reaches 72.6 EM on 2WikiMultiHopQA, 70.0 EM on Bamboogle and 74.9 Hits@1 on CWQ, outperforming comparable open-backbone baselines and competing with larger or trained systems.

2 Related Work

We organize prior work by how evidence is represented and updated during multi-hop reasoning.

Corpus-based retrieval and agentic search. Corpus-based RAG methods decompose complex questions into sub-queries and interleave retrieval with intermediate reasoning. IRCoT (Trivedi et al., 2023) alternates retrieval with chain-of-thought reasoning, while HopRAG (Liu et al., 2025), ComposeRAG (Wu et al., 2025), and RT-RAG (Shi et al., 2026) improve query decomposition, structured prompting, or reasoning-tree construction. A related line trains or prompts agents to search over multiple turns, such as Search-R1 (Jin et al., 2025) and MR-Search (Xiao et al., 2026). These systems make retrieval adaptive, but evidence remains primarily textual. Relational structure must be inferred from snippets rather than maintained as explicit state. Co-E complements adaptive retrieval with graph memory that makes entities and relations available to later retrieval and generation.

Graph-augmented RAG and KG reasoning. Graph-augmented approaches add structured evidence to RAG, but many rely on graph structure fixed before or outside the current reasoning trajectory. Corpus-graph systems such as HippoRAG 2 and C2RAG (Gutiérrez et al., 2025; Ma et al., 2026) build graph-like indices over text and retrieve from them at inference time. EA-GraphRAG (Dong et al., 2026), GraphAnchor (Liu et al., 2026), PAGER (Li et al., 2026b), and Graph-R1 + EKA (Wang et al., 2026) improve when or how structured evidence is retrieved. KGQA systems differ in how they choose the graph frontier. Learned/subgraph systems such as SubgraphRAG (Li et al., 2025b), GNN-RAG (Mavromatis and Karypis, 2025), and iQUEST (Wang and Yu, 2025) learn or compute query-specific subgraphs before handing evidence to the LLM. Live-KG methods such as ToG (Sun et al., 2024), ToG 2.0 (Ma et al., 2025), PoG (Tan et al., 2025), Interactive-KBQA (Xiong et al., 2024), MCTS-KBQA (Xiong et al., 2025), ReKG-MCTS (Song et al., 2025), and KERAG (Sun et al., 2025) focus on traversing or quering a knowledge graph during inference. Trained graph-reasoning systems such as RoG (Luo et al., 2024), KBQA-R1 (Sun et al., 2026), and GraphWalker (Xu et al., 2026) improve retrieval or reasoning through supervised or reinforcement learning. These systems provide strong graph retrieval; Co-E focuses on synchronizing structured and textual working state during reasoning.

Memory-augmented reasoning. Memory-augmented reasoning systems maintain intermediate state across reasoning or search steps, whether in text, graph, or both. HGMem (Zhou et al., 2026a) builds hypergraph memory from retrieved text. SubQRAG (Li et al., 2025a) is closest to Co-E among graph-memory systems: it decomposes questions, consults source documents when the graph is insufficient, and accumulates extracted triples into graph memory. SE-Search (Li et al., 2026a) purifies evidence through a Think-Search-Memorize loop, MemSearch-o1 (Zhang et al., 2026) grows reasoning-aligned memory paths, and A-MEM (Xu et al., 2025) revises textual notes retroactively. These works show that memory should be maintained, not merely accumulated. Co-E is complementary: instead of treating memory as a textual note store or graph-only trace, it maintains paired textual and graph memories and reconciles them after each reasoning step. Graph facts are therefore injected back into the textual context that conditions later retrieval and generation.

3 Methodology

3.1 System Overview

Given a question q, Co-E answers it through an iterative reasoning process over a shared graph-text memory. At step t, the memory is

$$\mathcal{M}^{(t)} = (\mathcal{T}^{(t)}, \mathcal{G}^{(t)}), \qquad (1)$$

Figure 1: Co-E framework. Left: MCTS mode, where synchronized shared memory guides tree expansion. Right: the four-stage reasoning loop. Each step generates a sub-query from shared graph-text memory $\mathcal{M}^{(t)}$, retrieves text snippets $S^{(t)}$ and graph triples $R^{(t)}$, generates an intermediate answer, and applies bidirectional Sync to produce the next step's memory $\mathcal{M}^{(t+1)}$.

where $\mathcal{T}^{(t)}$ is textual memory and $\mathcal{G}^{(t)}$ is graph memory. Co-E produces a final answer a while updating both memories after each reasoning step. Unlike pipelines that treat retrieved graph context as fixed, Co-E actively maintains $\mathcal{G}$: it can add text-derived triples, prune irrelevant edges, and write surviving facts back into textual memory.

Each reasoning step has four stages. First, **Request Generation** produces a focused sub-query $q^{(t)}$ from the original question and current memory. Second, **Dual-Stream Retrieval/Search** retrieves textual snippets $S^{(t)}$ and graph triples $R^{(t)}$. Third, **Response Generation** produces an intermediate answer or reasoning state $y^{(t)}$. Fourth, **Memory Synchronization** updates both memories through a bidirectional operator:

$$(\mathcal{T}^{(t+1)}, \mathcal{G}^{(t+1)}) \leftarrow \text{Sync}(\mathcal{T}^{(t)}, \mathcal{G}^{(t)}, S^{(t)}, R^{(t)}, y^{(t)}) \quad (2)$$

Co-E supports both MCTS and CoT reasoning modes; both use the same retrieval and synchronization machinery, differing only in how they choose the next sub-query.

3.2 Shared Graph-Text Memory

Co-E maintains a single shared memory object rather than independent per-hop contexts. Every step reads from the current memory and writes verified evidence back the same memory, so early evidence can affect later retrieval and generation.

Textual memory. The textual memory $\mathcal{T}$ stores self-contained, question-relevant snippets: extracted evidence, intermediate sub-answers, verifier feedback, and natural-language statements produced from graph triples. Raw documents never enter memory; an extractor filters each retrieved document into atomic snippets.

Graph memory. The graph memory $\mathcal{G}$ is a directed graph over entities and relations. *KB-schema triples* are canonical and retrieved directly from a knowledge base. *Open-vocabulary triples* are extracted from textual memory and use natural-language relation labels. The former provide reliable schema-grounded structure, while the latter let Co-E represent relations expressed in text but absent from the KB schema. A shared entity dictionary links surface mentions in $\mathcal{T}$ to KB identifiers in $\mathcal{G}$, allowing textual and graph evidence to refer to the same entities.

Before triples are merged into $\mathcal{G}$, a triple pruner removes irrelevant, redundant, or contradicted edges. Nodes that resolve to the same KB identifier are collapsed, and isolated low-value nodes are discarded. Thus graph memory is actively maintained rather than monotonically accumulated.

3.3 Bidirectional Memory Synchronization

The synchronization operator is the core mechanism of Co-E. It co-evolves text and graph memory through four operations.

Textual consolidation. Co-E first consolidates $\mathcal{T}^{(t)}$, newly retrieved snippets $S^{(t)}$, and the interme-

diate response $y^{(t)}$. The consolidator deduplicates overlapping snippets, merges complementary evidence, and retracts contradicted intermediate predictions. This prevents the memory from becoming an ever-growing block of noisy context.

Text-to-graph propagation. From the consolidated textual memory, an entity linker identifies entities and maps them to KB identifiers when possible. A relation extractor then proposes open-vocabulary triples from the text. These triples are combined with KB triples $R^{(t)}$, pruned for relevance and consistency, and merged into $\mathcal{G}^{(t)}$. This step lets newly discovered textual evidence expand the relational frontier.

Graph-to-text propagation. Co-E textualizes surviving graph triples and appends them to textual memory as explicit relational statements. This gives the generator direct access to graph constraints in natural language, rather than requiring it to infer them from graph structure separately.

Textual re-consolidation. Finally, the consolidator runs a second pass over the textual memory after graph-derived statements have been injected. The result is a coherent memory state $\mathcal{M}^{(t+1)}$ in which textual evidence and graph evidence are reconciled. This updated memory conditions the next sub-query, retrieval step, and response generation.

3.4 Dual-Stream Retrieval

Co-E retrieves from both text and graph sources: **Corpus retrieval.** A query generator rewrites $q^{(t)}$ into search-oriented queries conditioned on $\mathcal{M}^{(t)}$. These queries are sent to either web search or dense retrieval over a local corpus. Retrieved documents are passed to the extractor, which produces the snippet set $S^{(t)}$. Only atomic extracted snippets enter memory. **Graph retrieval.** Graph retrieval uses the current memory to choose which KB regions to explore. Co-E links entities from $q^{(t)}$ and $\mathcal{M}^{(t)}$ to KB identifiers, augments the seed set with relevant entities already present in $\mathcal{G}^{(t)}$, and issues k-hop SPARQL queries from this seed set. To control combinatorial growth, candidate triples are reranked between hops and then filtered by the triple pruner. The resulting triples form $R^{(t)}$. Because the seed set depends on the current graph memory, graph retrieval is memory-conditioned rather than a fixed precomputed traversal.

3.5 Reasoning Modes

Co-E can run the same memory update cycle under two reasoning policies.

MCTS mode. MCTS mode searches over candidate reasoning trajectories. The root is the original question q, and child nodes are generated by the LLM. Following (Qi et al., 2024), nodes may represent sub-question answering, self-correction, synthesis, question rephrasing, or final-answer generation. Selection uses a prior-weighted UCB score, following the PUCT-style family (Silver et al., 2017) rather than classic UCT:

$$S(s,a) = \bar{Q}(s,a) + c \cdot P(s,a) \cdot \frac{\sqrt{N_{\mathrm{p}}(s)+1}}{1+N(s,a)} \quad (3)$$

where $\bar{Q}(s,a)$ is the average reward accumulated by backpropagation, $P(s,a)$ is a child node type's heuristic prior, $N(s,a)$ is the child visit count, $N_{\mathrm{p}}(s)$ is the parent visit count, and c controls exploration. Co-E separates tree statistics from memory state: node visits and values remain branch-specific, while evidence discovered during MCTS is accumulated in a shared working memory. After rollout, a verifier scores candidate terminal states under three views: no retrieved context, textual memory, and graph memory. Its natural-language assessments are added to textual memory as system-prediction items. After backpropagation, Co-E applies Sync once to the shared memory, where consolidation can remove unsupported predictions and filters newly introduced triples. This lets high-quality search feedback shape later retrieval, while relying on verifier feedback and active maintenance to reduce contamination from weak branches.

CoT mode. CoT mode follows a sequential reasoning chain. At each step, the model generates and answers sub-questions conditioned on q and $\mathcal{M}^{(t)}$, then applies the same synchronization operator before continuing. CoT mode is cheaper because it avoids tree search and verifier-guided branch selection, while MCTS mode explores multiple candidate reasoning paths before committing.

4 Experiments

4.1 Experimental Setup

Datasets. We evaluate on six benchmarks spanning KGQA over structured knowledge bases and multi-hop text-QA over unstructured corpora. For KGQA, WebQSP (Yih et al., 2016) contains mostly 1-2 hop Freebase questions, while CWQ (Talmor and Berant, 2018) requires conjunction, composition, and longer relation chains. The main KGQA comparison follows the standard topic-subgraph

Method	Backbone	Training	WebQSP	CWQ
Learned/Subgraph KG-Retrieval KGQA				
SubgraphRAG (Li et al., 2025b)	*GPT-4o-mini/ GPT-4o*	*MLP Retriever*	*90.1*	*66.7*
iQUEST (Wang and Yu, 2025)	*GPT-4o*	*GNN*	*88.9*	*73.9*
GNN-RAG (Mavromatis and Karypis, 2025)	LLaMA-2-7B	GNN	**85.7**	66.8
Live-KG KGQA				
ToG 2.0 (Ma et al., 2025)	*GPT-3.5-turbo*	*-*	*81.1*	*-*
PoG (Tan et al., 2025)	*GPT-3.5-turbo*	*-*	*93.9*	*74.7*
Interactive-KBQA (Xiong et al., 2024)	*GPT-4*	*-*	*72.5*	*59.2*
ReKG-MCTS (Song et al., 2025)	LLaMA-3-8B	-	72.2	59.8
KBQA-o1 (Luo et al., 2025)	LLaMA-3.1-8B	-	68.3	57.8
MCTS-KBQA (Xiong et al., 2025)	LLaMA-3.1-8B	-	73.5	72.1
RoG (Luo et al., 2024)	LLaMA-2-7B	SFT	**85.7**	62.6
Ours				
Co-E (CoT)	Qwen3-8B	-	85.3	70.1
Co-E (MCTS)	Qwen3-8B	-	85.5	**74.9**

Table 1: KGQA Hits@1 on WebQSP and CWQ. *Italic* rows use closed-source or >14B backbones; **bold** marks the best open ≤8B score.

protocol: each question is evaluated against a topic-centered Freebase candidate graph rather than against the full KB. For text-QA, 2WikiMulti-HopQA (Ho et al., 2020) emphasizes entity-centric bridge reasoning, HotpotQA (Yang et al., 2018) contains Wikipedia questions with stronger lexical cues, MuSiQue (Trivedi et al., 2022) composes single-hop questions into longer chains, and Bamboogle (Press et al., 2023) contains adversarial multi-hop questions that stress bridge-entity reuse.

Metrics. For KGQA, we report Hits@1, following prior work on WebQSP and CWQ (Ma et al., 2025; Li et al., 2025b); a prediction is correct if the top answer matches any gold alias after normalization. For text-QA, we report Exact Match (EM) (Trivedi et al., 2023; Liu et al., 2025). Some reported baselines only release F1; these are labeled explicitly and treated as reference points rather than direct EM comparisons. Because EM penalizes correct paraphrases or formatting differences, ablations and Appendix A also report LLM-judged accuracy (Acc) using Qwen3-30B-A3B-Thinking-2507 (Team, 2025), which receives the question, gold answer, and prediction.

Baselines. We group baselines by evidence representation. For text-QA, *Corpus-Based RAG* methods rely primarily on textual retrieval and reasoning, including IRCoT (Trivedi et al., 2023), HopRAG (Liu et al., 2025), ComposeRAG (Wu et al., 2025), RT-RAG (Shi et al., 2026), Search-o1 (Li et al., 2025c), Search-R1 (Jin et al., 2025), MR-Search (Xiao et al., 2026), and Search-P1 (Xia et al., 2026). *Graph-Augmented Retrieval* includes corpus-graph and graph-trained systems such as HippoRAG 2 (Gutiérrez et al., 2025), C2RAG (Ma et al., 2026), PAGER (Li et al., 2026b), GraphAnchor (Liu et al., 2026), EA-GraphRAG (Dong et al., 2026), Graph-R1 + EKA (Wang et al., 2026), and ProGraph-R1 (Park et al., 2026). *Memory-*

Augmented systems include SubQRAG (Li et al., 2025a), MemSearch-o1 (Zhang et al., 2026), and SE-Search (Li et al., 2026a). For KGQA, *Learned/-Subgraph KG-Retrieval KGQA* systems learn or compute query-specific candidate subgraphs before LLM reasoning, including SubgraphRAG (Li et al., 2025b), GNN-RAG (Mavromatis and Karypis, 2025), and iQUEST (Wang and Yu, 2025). *Live-KG KGQA* systems traverse or query a knowledge graph at inference time, including ToG 2.0 (Ma et al., 2025), PoG (Tan et al., 2025), Interactive-KBQA (Xiong et al., 2024), MCTS-KBQA (Xiong et al., 2025), ReKG-MCTS (Song et al., 2025), KBQA-o1 (Luo et al., 2025), RoG (Luo et al., 2024), and KERAG (Sun et al., 2025). Open ≤8B models are our primary comparison group; closed-source and much larger models are reference.

Implementation Details. Co-E is training-free. We use Qwen3-8B (Team, 2025) as the reasoning backbone, Qwen3-Embedding-4B (Zhang et al., 2025) for dense retrieval over the Wiki23 corpus, and SPARQL for graph retrieval. The same graph-text memory mechanism is used across settings, but the graph source differs. In the main KGQA experiments, graph retrieval is restricted to the benchmark-provided Freebase candidate subgraph. In text-QA, graph retrieval uses full live-Wikidata. For detail implementation, see Appendix B.

4.2 KGQA Results

Table 1 reports Hits@1 on WebQSP and CWQ under the standard topic-subgraph protocol. Each question is paired with a compact Freebase subgraph centered on the topic entity. This setting tests reasoning over a noisy but bounded candidate graph: Co-E does not expand the Freebase search space beyond the provided subgraph, but it can prune candidate relations, preserve intermediate entities, and textualize graph facts for later generation. On WebQSP, where questions are short 1-2 hop queries and the answer path is often exposed by the topic graph, the highest scores come from closed-source or trained systems such as PoG, SubgraphRAG, and iQUEST. Co-E (MCTS) reaches 85.5 Hits@1, below those systems but essentially tied with the strongest open 7B trained baselines, RoG and GNN-RAG (both 85.7). Co-E (CoT) reaches a similar 85.3, suggesting that synchronized memory, rather than tree search alone, accounts for most of Co-E's WebQSP performance. On CWQ, the advantage of maintaining graph-text state is clearer because questions require conjunc-

Method	Backbone	Training	HotpotQA	2WikiMultiHopQA	MuSiQue	Bamboogle
Corpus-Based RAG						
HopRAG (Liu et al., 2025)	*GPT-4o*	*-*	*62.0*	*61.1*	*42.2*	*-*
Search-o1 (Li et al., 2025c)	*QwQ-32B*	*-*	*45.2*	*58.0*	*16.6*	*56.0*
IRCoT (Trivedi et al., 2023)	Qwen3-8B	-	50.9	47.6	16.4	32.2
Search-R1 (Jin et al., 2025)	Qwen2.5-7B	PPO	43.3	38.2	19.6	43.2
MR-Search (Xiao et al., 2026)	Qwen2.5-7B	Meta-RL	46.8	43.6	22.1	45.2
Graph-Augmented Retrieval						
C2RAG (Ma et al., 2026)	*GPT-4o-mini*	*-*	*55.3*	*65.9*	*33.2*	*-*
PAGER (Li et al., 2026b)	*Qwen3-32B*	*-*	*50.6*	*57.4*	*23.0*	*62.4*
GraphAnchor (Liu et al., 2026)	Qwen2.5-7B	-	53.8	52.2	21.2	24.8
Graph-R1 + EKA (Wang et al., 2026)	Qwen2.5-7B	GRPO	59.4	60.9	40.6	-
ProGraph-R1 (Park et al., 2026)	Qwen2.5-7B	GRPO	60.9	59.4	39.8	-
Memory-Augmented						
SubQRAG (Li et al., 2025a)	*GPT-4o-mini*	*-*	*56.0*	*61.9*	*29.7*	*-*
SE-Search (Li et al., 2026a)	Qwen2.5-3B	GRPO	45.0	36.1	18.3	42.4
Ours						
Co-E (CoT)	Qwen3-8B	-	59.6	70.1	49.3	66.4
Co-E (MCTS)	Qwen3-8B	-	**61.8**	**72.6**	**52.5**	**70.0**

Table 2: Multi-hop text-QA EM. *Italic* rows use closed-source or >14B backbones; **bold** marks the best open ≤8B.

Variant	MCTS		CoT	
	EM	Acc	EM	Acc
Co-E (full)	**70.0**	**77.6**	**66.4**	**75.2**
Memory synchronization				
− Bidirectional sync	61.1	65.9	52.5	55.7
− Unidirectional (text→graph)	64.0	71.5	56.1	61.6
− Unidirectional (graph→text)	63.1	70.3	55.9	60.9
− Active maintenance	49.5	59.7	49.0	47.1
Memory modality				
− Graph memory (text only)	54.8	62.3	50.3	54.9
− Textual memory (graph only)	55.0	63.6	50.6	54.7
Retrieval and extraction				
− Extractor	50.2	61.3	48.1	50.9
− Graph retriever	49.8	54.2	49.9	50.8
− Textual retriever	46.6	50.3	45.8	50.1

Table 3: Bamboogle ablations for MCTS and CoT.

tions, composition, and longer relation chains. Co-E (MCTS) reaches 74.9 Hits@1, slightly above PoG (74.7) and iQUEST (73.9), and improves over MCTS-KBQA by 2.8 points, GNN-RAG by 8.1 points, SubgraphRAG by 8.2 points, RoG by 12.3 points, and ReKG-MCTS by 15.1 points. The larger MCTS-CoT gap on CWQ indicates that search helps when several plausible relation paths compete. Overall, the KGQA results support Co-E as a training-free graph-memory reasoner, with the largest gains when the model must preserve and select among multi-step relations.

4.3 Multi-hop Text-QA Results

Table 2 reports EM on the four text-QA benchmarks. Co-E (MCTS) is strongest among open ≤8B systems, reaching 61.8 on HotpotQA, 72.6 on 2WikiMultiHopQA, 52.5 on MuSiQue, and 70.0 on

Bamboogle. Co-E (CoT) is lower than MCTS but remains competitive with same scale baselines, suggesting that synchronized memory provides much of the improvement while tree search adds gain when bridge candidates compete.

The largest gains appear on datasets where a later hop depends on preserving a bridge entity or relation discovered earlier. On 2WikiMultiHopQA, Co-E improves over C2RAG by 6.7 points and SubQRAG by 10.7 points. This supports the intended use of text-to-graph propagation: once a passage identifies a bridge entity, Co-E can link it, store it as graph memory, and use it to seed later graph or corpus retrieval. The advantage is clearer on harder compositional text-QA benchmarks. On MuSiQue, Co-E reaches 52.5 EM, outperforming HopRAG-GPT-4o by 10.3 points, ProGraph-R1 by 12.7 points, and SubQRAG by 22.8 points. MuSiQue's longer 2-4 hop chains make retrieval noise compound; active consolidation and graph-text synchronization preserve the resolved chain while discarding stale content. Bamboogle shows a similar pattern: Co-E reaches 70.0 EM, improving over Search-R1-7B by 26.8 points and PAGER-32B by 7.6 points. These questions often cannot be answered until an intermediate entity is resolved, so MCTS explores alternative bridge candidates while synchronization commits verified evidence into both memories. HotpotQA has the smallest margin: Co-E reaches 61.8 EM, ahead of SubQRAG and ProGraph-R1 but close to HopRAG-GPT-4o. HotpotQA often has stronger lexical cues and shorter chains, making corpus-only or closed-

Method	WebQSP Hits@1	CWQ Hits@1
Co-E (subgraph protocol)	85.5	74.9
Co-E (Full-Wikidata)	78.6	73.4

Table 4: Co-E with Freebase topic-subgraph versus Full-Wikidata retrieval (Hits@1).

Figure 2: Pass@k on Bamboogle; k is the number of tree expansions for MCTS and chain depth for CoT.

source pipelines more competitive.

4.4 Ablation Study

Table 3 ablates Co-E on Bamboogle, where questions often require a resolved bridge entity in a later hop. The ablations test three design choices: whether synchronization must be bidirectional, whether both memory modalities are needed, and whether retrieval-time filtering can replace persistent memory.

Synchronization. Removing bidirectional synchronization drops MCTS EM from 70.0 to 61.1 and CoT EM from 66.4 to 52.5. The drop under both search policies shows that the effect is not merely a byproduct of tree exploration. One-way propagation is also insufficient: text→graph reaches 64.0 MCTS EM, while graph→text reaches 63.1. These variants preserve one half of the loop, but lose the feedback cycle that lets textual evidence expand the graph frontier and graph facts shape the next textual context. Removing active maintenance causes the largest synchronization-related degradation, reducing MCTS EM to 49.5. This variant can still propagate evidence across modalities, but it no longer reliably deduplicates, merges, or retracts stale content. The result suggests that co-evolution must be selective rather than purely accumulative.

Memory modality. Removing graph memory lowers MCTS EM to 54.8, and removing textual memory lowers it to 55.0. The degradation suggests that textual memory provides grounding that KB triples may not encode, while graph memory preserves explicit entity-relation structure that text leaves implicit. Neither memory alone recovers the full behavior, supporting paired graph-text state.

Retrieval and extraction. Removing textual retrieval causes the largest component drop (-23.4 MCTS EM), followed by graph retrieval (-20.2) and the extractor (-19.8). This confirms that Co-E depends on both evidence streams, but also that retrieval alone is not enough. The extractor ablation shows that raw documents are too noisy to accumulate directly; filtering them into concise, self-contained snippets is part of memory construction rather than a minor preprocessing detail.

4.5 Full-Wikidata Evaluation

The KGQA results above follow the standard topic-subgraph protocol, where each question is paired with a pre-retrieved Freebase subgraph centered on its topic entity. This protocol enables controlled comparison with prior KGQA systems, but it assumes question-specific preprocessing: a topic entity must be identified and a compact candidate graph extracted before reasoning begins. Such preprocessing is not always available in open-domain settings, where systems may need to start from a large KG and from entities discovered during retrieval. To test this harder setting, we rerun Co-E (MCTS) on WebQSP and CWQ using the same Full-Wikidata retrieval stack as the text-QA experiments. This experiment is a stress test rather than a matched replacement for Freebase evaluation, since entity identifiers, relation schemas, and answer aliases differ between Freebase and Wikidata. Table 4 shows that moving from Freebase topic subgraphs to full Wikidata has only a small effect on CWQ, reducing Hits@1 from 74.9 to 73.4. For compositional questions, memory-conditioned entity discovery and SPARQL expansion can recover much of the useful relational frontier even without a benchmark-provided candidate graph. The drop is larger on WebQSP, from 85.5 to 78.6, because many WebQSP questions are short and the preprocessed subgraph often exposes the answer path directly (due to its significant smaller size and better schema match). Without this pruning, retrieval noise has a larger effect on short questions with less compositional structure. Overall, the Full-Wikidata setting shows that Co-E benefits from topic-subgraph pruning when available, while retaining strong compositional KGQA performance when forced to retrieve from a much larger and

Step	Sub-query	Textual memory after sync
1	Who is George Washington's father?	[Retrieval] George Washington's father was Augustine Washington.
2	Who is Augustine Washington's mother? *(graph-guided)*	[Retrieval] Augustine Washington was born to Mildred Warner and Capt. Lawrence Washington. [Graph] Augustine Washington -**mother**→ Mildred Warner

Table 5: Memory walkthrough for *"Who is the mother of the father of George Washington?"*. Graph-injected text grounds step 2 retrieval on Augustine Washington; dead-end graph branches are gray and ⋆ marks the gold answer.

schema-mismatched graph.

4.6 Analysis

Pass@k. Figure 2 separates search from memory. MCTS improves rapidly in the first few expansions because it can evaluate multiple bridge candidates before committing, whereas CoT must extend a single chain. The CoT curve also improves as memory accumulates, indicating that synchronization strengthens later reasoning even without branch exploration. Both curves eventually plateau, suggesting that most gains come from early memory updates and that the remaining MCTS advantage reflects exploration over alternative bridge entities or relation chains.

Memory evolution. Table 5 illustrates how bidirectional synchronization changes the next retrieval action, not just the final context. For the question *"Who is the mother of the father of George Washington?"*, the first step retrieves Augustine Washington as George Washington's father. Text→graph propagation turns this evidence into parentage edges, and graph→text propagation writes the resolved father relation back into textual memory. The second step can therefore query around Augustine Washington as a grounded entity rather than around an under-specified phrase. This steers SPARQL expansion toward Augustine Washington's parentage triples and injects the mother edge to Mildred Warner back into memory. The example also clarifies the role of pruning and search: memory may contain plausible off-path facts, while verification and branch selection decide which path answers the question.

Failure analysis. Manual inspection of Bamboogle failures, detailed in Appendix D, shows that remaining errors usually come from evidence quality or path selection rather than from the absence of graph-text memory. Retrieval gaps account for 45% of failures: the system often identifies the right entity chain, but the corpus repeatedly supports an incorrect value, which synchronization cannot fix when the evidence is internally consistent. Incomplete reasoning chains account for 21%, usually when relevant facts are present in memory but the

synthesizer selects a chain that is too short, too long, or off by one hop. Wrong entity linking and synthesis errors each account for 14%, and surface-form mismatch accounts for 7%. These categories suggest remedies: stronger source cross-checking for retrieval gaps, better entity disambiguation for linking errors, and explicit chain-completeness verification for incomplete reasoning.

5 Conclusion

We introduced Co-E, a training-free multi-hop QA system built around synchronized graph-text working memory. Co-E treats reasoning as an iterative memory-maintenance problem: textual evidence can expand the graph frontier when open graph retrieval is available, and graph facts can be written back into the textual context that conditions later retrieval and generation. This bidirectional synchronization lets the system revise its relational state during inference rather than relying on a static retrieved context or a fixed topic-centered candidate graph. Across six KGQA and text-QA benchmarks, Co-E consistently improves over comparable training-free open-backbone baselines, achieving 72.6 EM on 2WikiMultiHopQA, 70.0 EM on Bamboogle, 52.5 EM on MuSiQue, and 74.9 Hits@1 on CWQ. Ablations show that both propagation directions and active memory maintenance are necessary: simply accumulating evidence is not enough. The main KGQA results show strong performance under the standard Freebase topic-subgraph protocol, while the Full-Wikidata stress test shows that Co-E can retain strong compositional KGQA performance without benchmark-specific subgraph preprocessing. Together, these results support graph-text co-evolution as a practical mechanism for training-free multi-hop reasoning.

Limitations

Co-E is limited by the quality of the evidence it retrieves. Bidirectional synchronization can reconcile redundant or contradicted memory entries, but it cannot reliably correct a wrong fact that is

repeatedly supported by the retrieved corpus. This appears in the Bamboogle failure analysis, where retrieval gaps account for 45% of errors. Future systems could cross-check numerical attributes, superlatives, and entity facts against independent sources, though doing so would add latency. Co-E also depends on accurate entity linking and path selection. Wrong entity linking accounts for 14% of Bamboogle failures, and incomplete reasoning chains account for 21%. These errors suggest that graph-text memory is not sufficient by itself: the system still needs better candidate disambiguation, stronger hop-count constraints, and more explicit verification of whether the selected chain fully answers the question. MCTS mode uses a shared global working memory rather than a fully branch-local memory. Verifier assessments, consolidation, and graph pruning mitigate contamination from weak branches, but they do not provide roll-back semantics; future work could compare shared-memory MCTS with branch-local or reward-gated memory commits. Finally, Co-E trades additional inference cost for stronger reasoning. MCTS mode requires multiple LLM calls per expansion; CoT mode is cheaper but less accurate. Stronger early stopping, cached verification, or adaptive switching between CoT and MCTS could reduce this cost. Our experiments primarily use a Qwen3-8B backbone, with a Bamboogle-only Qwen3.5-4B check in Appendix C; evaluating larger or more specialized models, and extending the smaller-backbone study across all benchmarks, remains future work.

References

Su Dong, Qinggang Zhang, Yilin Xiao, Shengyuan Chen, Chuang Zhou, and Xiao Huang. 2026. Use graph when it needs: Efficiently and adaptively integrating retrieval-augmented generation with graphs. *Preprint*, arXiv:2602.03578.

Bernal Jiménez Gutiérrez, Yiheng Shu, Weijian Qi, Sizhe Zhou, and Yu Su. 2025. From rag to memory: Non-parametric continual learning for large language models. *Preprint*, arXiv:2502.14802.

Xanh Ho, Anh-Khoa Duong Nguyen, Saku Sugawara, and Akiko Aizawa. 2020. Constructing a multi-hop QA dataset for comprehensive evaluation of reasoning steps. In *Proceedings of the 28th International Conference on Computational Linguistics*, pages 6609–6625, Barcelona, Spain (Online). International Committee on Computational Linguistics.

MinGyu Jeon, SuWan Cho, and JaeYoung Shu. 2025. Ppoga: Predictive plan-on-graph with action for knowledge graph question answering. *Preprint*, arXiv:2602.00007.

Bowen Jin, Hansi Zeng, Zhenrui Yue, Jinsung Yoon, Sercan Arik, Dong Wang, Hamed Zamani, and Jiawei Han. 2025. Search-r1: Training llms to reason and leverage search engines with reinforcement learning. *Preprint*, arXiv:2503.09516.

Jian Li, Yizhang Jin, Dongqi Liu, Hang Ding, Jiafu Wu, Dongsheng Chen, Yunhang Shen, Yulei Qin, Ying Tai, Chengjie Wang, Xiaotong Yuan, and Yabiao Wang. 2026a. Se-search: Self-evolving search agent via memory and dense reward. *Preprint*, arXiv:2603.03293.

Jiaoyang Li, Junhao Ruan, Shengwei Tang, Saihan Chen, Kaiyan Chang, Yuan Ge, Tong Xiao, and Jingbo Zhu. 2025a. Subqrag: Sub-question driven dynamic graph rag. *Preprint*, arXiv:2510.07718.

Mufei Li, Siqi Miao, and Pan Li. 2025b. Simple is effective: The roles of graphs and large language models in knowledge-graph-based retrieval-augmented generation. *Preprint*, arXiv:2410.20724.

Xiaoxi Li, Guanting Dong, Jiajie Jin, Yuyao Zhang, Yujia Zhou, Yutao Zhu, Peitian Zhang, and Zhicheng Dou. 2025c. Search-o1: Agentic search-enhanced large reasoning models. *Preprint*, arXiv:2501.05366.

Xinze Li, Zhenghao Liu, Haidong Xin, Yukun Yan, Shuo Wang, Zheni Zeng, Sen Mei, Ge Yu, and Maosong Sun. 2026b. Structured knowledge representation through contextual pages for retrieval-augmented generation. *Preprint*, arXiv:2601.09402.

Hao Liu, Zhengren Wang, Xi Chen, Zhiyu Li, Feiyu Xiong, Qinhan Yu, and Wentao Zhang. 2025. Hoprag: Multi-hop reasoning for logic-aware retrieval-augmented generation. *Preprint*, arXiv:2502.12442.

Zhenghao Liu, Mingyan Wu, Xinze Li, Yukun Yan, Shuo Wang, Cheng Yang, Minghe Yu, Zheni Zeng, and Maosong Sun. 2026. Graph-anchored knowledge indexing for retrieval-augmented generation. *Preprint*, arXiv:2601.16462.

Haoran Luo, Haihong E, Yikai Guo, Qika Lin, Xiaobao Wu, Xinyu Mu, Wenhao Liu, Meina Song, Yifan Zhu, and Luu Anh Tuan. 2025. Kbqa-o1: Agentic knowledge base question answering with monte carlo tree search. *Preprint*, arXiv:2501.18922.

Linhao Luo, Yuan-Fang Li, Gholamreza Haffari, and Shirui Pan. 2024. Reasoning on graphs: Faithful and interpretable large language model reasoning. *Preprint*, arXiv:2310.01061.

Shengjie Ma, Chengjin Xu, Xuhui Jiang, Muzhi Li, Huaren Qu, Cehao Yang, Jiaxin Mao, and Jian Guo. 2025. Think-on-graph 2.0: Deep and faithful large language model reasoning with knowledge-guided retrieval augmented generation. *Preprint*, arXiv:2407.10805.

Yizhuo Ma, Shuang Liang, Rongzheng Wang, Jiakai, Qizhi Chen, Muquan Li, and Ke Qin. 2026. Mitigating kg quality issues: A robust multi-hop graphrag retrieval framework. *Preprint*, arXiv:2603.14828.

Costas Mavromatis and George Karypis. 2025. GNN-RAG: Graph neural retrieval for efficient large language model reasoning on knowledge graphs. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 16682–16699, Vienna, Austria. Association for Computational Linguistics.

Jinyoung Park, Sanghyeok Lee, Omar Zia Khan, Hyunwoo J. Kim, and Joo-Kyung Kim. 2026. Hypergraphpro: Progress-aware reinforcement learning for structure-guided hypergraph rag. *Preprint*, arXiv:2601.17755.

Ofir Press, Muru Zhang, Sewon Min, Ludwig Schmidt, Noah A. Smith, and Mike Lewis. 2023. Measuring and narrowing the compositionality gap in language models. *Preprint*, arXiv:2210.03350.

Zhenting Qi, Mingyuan Ma, Jiahang Xu, Li Lyna Zhang, Fan Yang, and Mao Yang. 2024. Mutual reasoning makes smaller llms stronger problem-solvers. *Preprint*, arXiv:2408.06195.

Qwen Team. 2026. Qwen3.5: Towards native multimodal agents.

Yuling Shi, Maolin Sun, Zijun Liu, Mo Yang, Yixiong Fang, Tianran Sun, and Xiaodong Gu. 2026. Reasoning in trees: Improving retrieval-augmented generation for multi-hop question answering. *Preprint*, arXiv:2601.11255.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, Yutian Chen, Timothy P. Lillicrap, Fan Hui, Laurent Sifre, George van den Driessche, Thore Graepel, and Demis Hassabis. 2017. Mastering the game of go without human knowledge. *Nature*, 550:354–359.

Aditi Singh, Abul Ehtesham, Saket Kumar, Tala Talaei Khoei, and Athanasios V. Vasilakos. 2026. Agentic retrieval-augmented generation: A survey on agentic rag. *Preprint*, arXiv:2501.09136.

Xiaozhuang Song, Shufei Zhang, and Tianshu Yu. 2025. ReKG-MCTS: Reinforcing LLM reasoning on knowledge graphs via training-free Monte Carlo tree search. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 9288–9306, Vienna, Austria. Association for Computational Linguistics.

Jiashuo Sun, Chengjin Xu, Lumingyuan Tang, Saizhuo Wang, Chen Lin, Yeyun Gong, Lionel M. Ni, Heung-Yeung Shum, and Jian Guo. 2024. Think-on-graph: Deep and responsible reasoning of large language model on knowledge graph. *Preprint*, arXiv:2307.07697.

Xin Sun, Zhongqi Chen, Xing Zheng, Qiang Liu, Shu Wu, Bowen Song, Zilei Wang, Weiqiang Wang, and Liang Wang. 2026. Kbqa-r1: Reinforcing large language models for knowledge base question answering. *Preprint*, arXiv:2512.10999.

Yushi Sun, Kai Sun, Yifan Ethan Xu, Xiao Yang, Xin Luna Dong, Nan Tang, and Lei Chen. 2025. Kerag: Knowledge-enhanced retrieval-augmented generation for advanced question answering. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 6194–6216.

Alon Talmor and Jonathan Berant. 2018. The web as a knowledge-base for answering complex questions. *Preprint*, arXiv:1803.06643.

Xingyu Tan, Xiaoyang Wang, Qing Liu, Xiwei Xu, Xin Yuan, and Wenjie Zhang. 2025. Paths-over-graph: Knowledge graph empowered large language model reasoning. *Preprint*, arXiv:2410.14211.

Qwen Team. 2025. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. 2022. MuSiQue: Multi-hop questions via single-hop question composition. *Transactions of the Association for Computational Linguistics*, 10:539–554.

Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. 2023. Interleaving retrieval with chain-of-thought reasoning for knowledge-intensive multi-step questions. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 10014–10037, Toronto, Canada. Association for Computational Linguistics.

Shuai Wang and Yinan Yu. 2025. iQUEST: An iterative question-guided framework for knowledge base question answering. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15616–15628, Vienna, Austria. Association for Computational Linguistics.

Yuxin Wang, Shicheng Fang, Bo Wang, Qi Luo, Xuanjing Huang, Yining Zheng, and Xipeng Qiu. 2026. Multi-hop reasoning via early knowledge alignment. *Preprint*, arXiv:2512.20144.

Ruofan Wu, Youngwon Lee, Fan Shu, Danmei Xu, Seung won Hwang, Zhewei Yao, Yuxiong He, and Feng Yan. 2025. Composerag: A modular and composable rag for corpus-grounded multi-hop question answering. *Preprint*, arXiv:2506.00232.

Tianle Xia, Ming Xu, Lingxiang Hu, Yiding Sun, Wenwei Li, Linfang Shang, Liqun Liu, Peng Shu, Huan Yu, and Jie Jiang. 2026. Search-p1: Path-centric reward shaping for stable and efficient agentic rag training. *Preprint*, arXiv:2602.22576.

Teng Xiao, Yige Yuan, Hamish Ivison, Huaisheng Zhu, Faeze Brahman, Nathan Lambert, Pradeep Dasigi, Noah A. Smith, and Hannaneh Hajishirzi. 2026. Meta-reinforcement learning with self-reflection for agentic search. *Preprint*, arXiv:2603.11327.

Guanming Xiong, Junwei Bao, and Wen Zhao. 2024. Interactive-KBQA: Multi-turn interactions for knowledge base question answering with large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 10561–10582, Bangkok, Thailand. Association for Computational Linguistics.

Guanming Xiong, Haochen Li, and Wen Zhao. 2025. Mcts-kbqa: Monte carlo tree search for knowledge base question answering. *Preprint*, arXiv:2502.13428.

Shuwen Xu, Yao Xu, Jiaxiang Liu, Chenhao Yuan, Wenshuo Peng, Jun Zhao, and Kang Liu. 2026. Graphwalker: Agentic knowledge graph question answering via synthetic trajectory curriculum. *Preprint*, arXiv:2603.28533.

Wujiang Xu, Zujie Liang, Kai Mei, Hang Gao, Juntao Tan, and Yongfeng Zhang. 2025. A-mem: Agentic memory for llm agents. *Preprint*, arXiv:2502.12110.

Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. 2018. HotpotQA: A dataset for diverse, explainable multi-hop question answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 2369–2380, Brussels, Belgium. Association for Computational Linguistics.

Wen-tau Yih, Matthew Richardson, Christopher Meek, Ming-Wei Chang, and Jina Suh. 2016. The value of semantic parse labeling for knowledge base question answering. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 201–206.

Sheng Zhang, Junyi Li, Yingyi Zhang, Pengyue Jia, Yichao Wang, Xiaowei Qian, Wenlin Zhang, Maolin Wang, Yong Liu, and Xiangyu Zhao. 2026. Memsearch-o1: Empowering large language models with reasoning-aligned memory growth in agentic search. *Preprint*, arXiv:2604.17265.

Yanzhao Zhang, Mingxin Li, Dingkun Long, Xin Zhang, Huan Lin, Baosong Yang, Pengjun Xie, An Yang, Dayiheng Liu, Junyang Lin, Fei Huang, and Jingren Zhou. 2025. Qwen3 embedding: Advancing text embedding and reranking through foundation models. *arXiv preprint arXiv:2506.05176*.

Penghao Zhao, Hailin Zhang, Qinhan Yu, Zhengren Wang, Yunteng Geng, Fangcheng Fu, Ling Yang, Wentao Zhang, Jie Jiang, and Bin Cui. 2024. Retrieval-augmented generation for ai-generated content: A survey. *Preprint*, arXiv:2402.19473.

Chulun Zhou, Chunkang Zhang, Guoxin Yu, Fandong Meng, Jie Zhou, Wai Lam, and Mo Yu. 2026a. Improving multi-step rag with hypergraph-based memory for long-context complex relational modeling. *Preprint*, arXiv:2512.23959.

Pengcheng Zhou, Haochen Li, Zhiqiang Nie, JiaLe Chen, Qing Gong, Weizhen Zhang, and Chun Yu. 2026b. Understand then memory: A cognitive gist-driven rag framework with global semantic diffusion. *Preprint*, arXiv:2602.15895.

A Full Baseline Results

Tables 6 and 7 provide the full baseline comparison used to construct the main result tables. We include each method's backbone, training setting, reported metric, and any supplementary semantic-accuracy score when available. The tables include both training-free and trained systems, with closed-source or substantially larger backbones retained as reference points rather than primary comparisons.

B Implementation Details

LLM inference runs on 4 NVIDIA A100 80GB GPUs. The Qwen3-8B reasoning backbone is served on 2 GPUs with SGLang model parallelism and thinking enabled, then exposed through a LiteLLM OpenAI-compatible proxy. Embedding and reranking models run on a separate GPU, while evaluation runs on a CPU server with 128 GB RAM and 32 cores. Dense retrieval uses an in-memory FAISS index over the Wiki23 corpus. SPARQL queries target either a local Virtuoso endpoint for KGQA or the public Wikidata endpoint for text-QA. Redis caches repeated calls during MCTS simulations.

B.1 Knowledge Base Setup

KGQA benchmarks (WebQSP, CWQ). We follow the standard topic-subgraph protocol: each question is paired with a pre-retrieved Freebase candidate subgraph centered on its topic entity, and graph retrieval is restricted to that subgraph. This reduces the full-KG search space but still leaves noisy and off-path relations for the system to filter. SPARQL queries target a local Virtuoso endpoint loaded with the per-question subgraphs. Entity linking maps surface mentions to Freebase MIDs using a dictionary derived from the benchmark training set; no new entities are added during evaluation. Corpus retrieval uses FAISS over the Wiki23 corpus with Qwen3-Embedding-4B.

Text-QA benchmarks (2WikiMultiHopQA, HotpotQA, MuSiQue, Bamboogle). We use full

Method	Backbone	Training	WebQSP	CWQ	Metric note
Learned/Subgraph KG-Retrieval KGQA					
SubgraphRAG (Li et al., 2025b)	GPT-4o-mini/ GPT-4o	Yes (MLP)	90.1 / 77.5	66.7 / 59.1	Hits@1 / F1
GNN-RAG (Mavromatis and Karypis, 2025)	LLaMA-2-7B	Yes (GNN)	85.7 / 71.3	66.8 / 60.4	Hits@1 / F1
iQUEST (Wang and Yu, 2025)	GPT-4o	Yes (GNN)	88.93	73.85	Hits@1
Live-KG KGQA					
ToG (Sun et al., 2024)	GPT-3.5-turbo	No	76.2	57.1	Hits@1
ToG 2.0 (Ma et al., 2025)	GPT-3.5-turbo	No	81.1	—	Hits@1
PoG (Tan et al., 2025)	GPT-3.5-turbo	No	93.9	74.7	Hits@1
PPoGA (Jeon et al., 2025)	GPT-3.5-turbo	No	83.1	64.5	Hits@1
Interactive-KBQA (Xiong et al., 2024)	GPT-4	No	72.47 / 71.20	59.17 / 49.07	Hits@1 / F1
ReKG-MCTS (Song et al., 2025)	LLaMA-3-8B	No	72.20	59.80	Hits@1
KBQA-o1 (Luo et al., 2025)	LLaMA-3.1-8B	No	68.3* / 59.8	57.8* / 43.1*	Hits@1 / F1
MCTS-KBQA (Xiong et al., 2025)	LLaMA-3.1-8B	No	73.5 / 72.5	72.1 / 64.9	Hits@1 / F1
KERAG (Sun et al., 2025)	LLaMA-3.1-70B	Yes (SFT)[+]	84.3	70.20	Hits@1
RoG (Luo et al., 2024)	LLaMA-2-7B	Yes (SFT)	85.7 / 70.8	62.6 / 56.2	Hits@1 / F1
KBQA-R1 (Sun et al., 2026)	LLaMA-3.1-8B	Yes (GRPO)	83.4	—	F1
Co-E (MCTS)	Qwen3-8B	No	85.5 / 94.55	74.9 / 89.85	Hits@1 / Acc
Co-E (CoT)	Qwen3-8B	No	85.3 / 92.7	70.1 / 87.78	Hits@1 / Acc

Table 6: Full KGQA baseline results. * denotes reproduced results. [+] KERAG trains an 8B model to summarize retrieved evidence.

Wikidata without pre-selection. Graph retrieval issues k-hop SPARQL queries against the public Wikidata endpoint and prunes candidates to the top 128 triples. Entity linking maps surface mentions to Wikidata QIDs; unlike the KGQA setting, the shared entity dictionary grows as new entities are discovered. Corpus retrieval again uses FAISS over the Wiki23 corpus.

Full-Wikidata KGQA. The Full-Wikidata evaluation in § 4.5 applies the text-QA protocol to WebQSP and CWQ: the same Wikidata endpoint, no pre-selected subgraph, and the same dual-stream retrieval stack. This setting tests robustness when the knowledge-base source is not benchmark-adapted.

C Inference Cost Analysis

Table 10 reports role-level inference cost on Bamboogle: average LLM calls per question, output (non-thinking) tokens per call, and total output tokens per question. These counts include every LLM invocation, both cache hits and misses; our implementation caches repeated LLM and retrieval calls, which reduces wall-clock latency but does not lower the totals reported here, since they reflect the underlying compute demand. Co-E (MCTS) uses 204.1 calls and 27.0K output tokens per question, compared with 58.0 calls and 7.8K tokens for Co-E (CoT), and 9.3 calls and 1.2K tokens for IR-CoT. In output tokens, MCTS is therefore about $3.5\times$ CoT and $22\times$ IR-CoT. The cost is concentrated in retrieval-side construction, not reasoning. Retrieval roles account for 57.1% of MCTS output

tokens and 68.7% of CoT output tokens. Within retrieval, the extractor is the largest contributor at 6.2K tokens per MCTS question and 2.7K per CoT question; within reasoning, answer generation contributes 8.0K and 2.1K tokens. MCTS further repeats this loop over alternative branches and adds verifier calls. The added cost is therefore tied to making intermediate evidence explicit, pruning noisy state, and exploring multiple reasoning paths.

To probe how much of Co-E's accuracy depends on the 8B backbone, we re-run both modes on Bamboogle using Qwen3.5-4B (Qwen Team, 2026) as the backbone for every role. Results are shown in Table 9. The smaller backbone loses 1.8 EM in MCTS mode and 3.3 EM in CoT mode. Co-E therefore degrades gracefully when the backbone is roughly halved, consistent with the design hypothesis that most of the gain comes from synchronized graph-text memory rather than from raw backbone capacity. This also provides direct evidence for the deployment argument below: in settings where 8B inference is too expensive, a 4B-class backbone preserves most of the accuracy at a fraction of the per-call compute.

This cost can be reduced without changing the training-free setup. We use Qwen3-8B for all roles because it is a relatively small, locally deployable backbone and keeps evaluation controlled. The Qwen3.5-4B result above shows that a roughly halved backbone preserves most of Co-E's Bamboogle accuracy, so the cheaper-backbone direc-

Method	Backbone	Training	HotpotQA	2WikiMultiHopQA	MuSiQue	Bamboogle	Metric note
Corpus-Based RAG							
HopRAG (GPT-3.5) (Liu et al., 2025)	GPT-3.5-turbo	No	61.3 / 78.3	61.6 / 68.9	39.1 / 53	—	EM / F1
HopRAG (GPT-4o) (Liu et al., 2025)	GPT-4o	No	62 / 76.1	61.1 / 68.3	42.2 / 54.9	—	EM / F1
ComposeRAG (Wu et al., 2025)	GPT-4o	No	58 / 73.2	80.8 / 82	34.2 / 38.8	62.4 / 72.8	EM / Acc
RT-RAG (GPT-4o-mini) (Shi et al., 2026)	GPT-4o-mini	No	52.50 / 65.26	63.00 / 75.08	41.50 / 54.42	—	EM / F1
RT-RAG (Qwen2.5-14B) (Shi et al., 2026)	Qwen2.5-14B	No	51.00 / 66.24	64.00 / 73.69	39.00 / 50.04	—	EM / F1
Search-o1 (Li et al., 2025c)	QwQ-32B	No	45.2 / 57.3	58.0 / 71.4	16.6 / 28.2	56.0 / 67.8	EM / F1
IRCoT (Trivedi et al., 2023)	Qwen3-8B	No	50.9 / 51.8	47.6 / 48.3	16.4 / 17.8	32.2 / 33.8	EM / Acc
Search-R1 (7B) (Jin et al., 2025)	Qwen2.5-7B	Yes (PPO)	43.30	38.20	19.6	43.2	EM
Search-R1 (14B) (Jin et al., 2025)	Qwen2.5-14B	Yes (PPO)	46.8	47	24.1	52.8	EM
Search-P1 (7B) (Xia et al., 2026)	Qwen2.5-7B	Yes (Dual-RL)	42.9	39.8	21.8	44	Acc
MR-Search (7B) (Xiao et al., 2026)	Qwen2.5-7B	Yes (Meta-RL)	46.8	43.6	22.1	45.2	EM
Graph-Augmented Retrieval							
HippoRAG 2 (Gutiérrez et al., 2025)	GPT-4o-mini	No	56.3 / 71.1	60.5 / 69.7	35.0 / 49.3	—	EM / F1
C2RAG (Ma et al., 2026)	GPT-4o-mini	No	55.3 / 72.8	65.9 / 73.9	33.2 / 46.1	—	EM / F1
PAGER (Li et al., 2026b)	Qwen3-32B	No	50.60	57.40	23.0	62.4	EM
GraphAnchor (Liu et al., 2026)	Qwen2.5-7B	No	53.8 / 66.0	52.2 / 61.6	21.2 / 32.6	24.8 / 34.3	EM / F1
EA-GraphRAG (Dong et al., 2026)	GPT-4o-mini	No	65.9 / 80.2	76.3 / 81.5	—	—	EM / Acc
Graph-R1 + EKA (Wang et al., 2026)	Qwen2.5-7B	Yes (GRPO)	59.38 / 66.14	60.94 / 68.26	40.63 / 51.63	—	EM / F1
ProGraph-R1 (3B) (Park et al., 2026)	Qwen2.5-3B	Yes (GRPO)	55.5 / 61.9	55.5 / 61.7	37.5 / 47.3	—	EM / F1
ProGraph-R1 (7B) (Park et al., 2026)	Qwen2.5-7B	Yes (GRPO)	60.9 / 67.6	59.4 / 69.8	39.8 / 49.5	—	EM / F1
Memory-Augmented							
SubQRAG (Li et al., 2025a)	GPT-4o-mini	No	56.00 / 64.30	61.90 / 64.30	29.70 / 38.14	—	EM / F1
MemSearch-o1 (Zhang et al., 2026)	Qwen2.5-72B-Instruct	No	59.71	65.95	44.11	—	F1
MemSearch-o1 (Zhang et al., 2026)	DeepSeek-V3.1	No	67.78	68.32	52.01	—	F1
SE-Search (Li et al., 2026a)	Qwen2.5-3B	Yes (GRPO)	45.0	36.10	18.3	42.4	EM
Co-E (MCTS)	Qwen3-8B	No	61.8 / 86.17	72.6 / 81.6	52.5 / 60.9	70.0 / 77.6	EM / Acc
Co-E (CoT)	Qwen3-8B	No	59.6 / 83.48	70.1 / 80.6	49.3 / 60.3	66.4 / 75.2	EM / Acc

Table 7: Full multi-hop text-QA baseline results.

Group	Parameter	Value
LLM Generation	Backbone	Qwen3-8B
	Temperature	1.0
	top-p	0.95
	top-k	20
	Presence penalty	1.5
	Thinking	enabled
Retrieval	Embedding model	Qwen3-Embedding-4B
	Reranker model	Qwen3-Reranker-4B
	Reranker top-k	10
	Web search top-k	5
	Graph hops (k)	2
	Entity candidates per mention	3
	Triple pruner top-k	128
MCTS	Max iterations	20
	Max tree depth	10
	Exploration weight (c)	2.5
	Max simulation depth	5
	Min iterations before early stop	5
	High-confidence threshold	0.9
	Convergence patience	5
	Semantic sufficiency count	5
MCTS node priors	Sub-question/Answer	0.60
	Self-Correction	0.50
	Synthesis	0.45
	Question Rephrasing	0.40
	Final Answer	0.30
CoT	Max chain depth	10
	Max sub-questions per step	3
Working Memory	Max textual memory tokens	8192

Table 8: Configuration hyperparameters applied across the Co-E framework.

Backbone	MCTS (EM / Acc)	CoT (EM / Acc)
Qwen3-8B	70.0 / 77.6	66.4 / 75.2
Qwen3.5-4B	68.2 / 74.9	63.1 / 69.5
Δ	−1.8 / −2.7	−3.3 / −5.7

Table 9: Bamboogle backbone-size sensitivity for Co-E.

can be significantly reduced because most computation is on the retrieval side. Caching can also reuse repeated entity-linking, SPARQL, extraction, verification, and LLM-call outputs. Finally, CoT provides the same graph-text memory mechanism at much lower cost, while MCTS can be reserved for ambiguous or long-chain questions.

D Failure Mode Analysis

Table 11 reports the full failure breakdown for Co-E (MCTS) on Bamboogle: 29 incorrect predictions out of 125 questions. Categories are assigned by manual inspection of the prediction, working memory, and retrieved evidence. *Retrieval gap* denotes cases where the system identifies the right entity but the corpus supports an incorrect fact. *Incomplete chain* covers failures where the needed evidence is present but the final chain is too short, too long, or off by one hop. *Wrong entity linking* covers scope-sensitive mentions resolved to the wrong entity. *Synthesis error* means the correct answer appears in memory but the final generator outputs a different answer. *Surface-form mismatch* captures

tion is empirically supported and not just hypothetical. In deployment, Co-E's role-based prompting makes model routing straightforward: retrieval-side roles such as NER, extraction, and pruning can use cheaper 2B-4B models or deterministic tools, while stronger models are reserved for harder reasoning roles such as question generation, verification, and consolidation. Thus, inference cost

Role	Category	MCTS calls/q	CoT calls/q	IR-CoT calls/q	Toks/call
ANSWER_GENERATOR	Reasoning	33.3	8.9	–	240.4
VERIFIER	Reasoning	14.8	–	–	79.4
SUBQUESTION_GENERATOR	Reasoning	8.4	1.4	–	203.7
SELF_CORRECTOR	Reasoning	3.7	–	–	118.3
FINAL_ANSWER_SYNTHESIZER	Reasoning	1.0	–	–	280.5
EXTRACTOR	Retrieval	43.8	19.4	–	140.6
TRIPLE_PRUNER (KB retrieval)	Retrieval	17.5	5.8	–	30.7
QUERY_GENERATOR	Retrieval	28.8	7.9	–	129.6
NER (entity linking)	Retrieval	28.8	7.9	–	61.1
MEMORY_CONSOLIDATOR	Retrieval	8.7	2.5	–	221.8
NER (memory sync)	Retrieval	5.1	1.4	–	56.2
RELATION_EXTRACTOR	Retrieval	5.1	1.4	–	177.3
TRIPLE_PRUNER (sync)	Retrieval	5.1	1.4	–	25.0
IR-CoT step (reasoning)	Reasoning	–	–	8.3	121.8
IR-CoT final answer	Reasoning	–	–	1.0	223.7
Total	–	**204.1**	**58.0**	**9.3**	–
Output tok/q	–	**27.0K**	**7.8K**	**1.2K**	–

Table 10: Bamboogle inference cost by LLM role. Call counts are averaged per question; the role-level token column reports tokens per call, and the final row reports total output tokens per question.

strict-EM artifacts where the prediction is semantically correct but formatted differently from the gold string.

E   Prompt Templates

This appendix reproduces the prompt templates used at each stage of Co-E. All LLM calls use JSON-mode structured output; each prompt's `Output Format` block gives the required schema. Prompts are shared across KGQA and text-QA benchmarks, with only runtime context variables changed (question, memory state, and retrieved evidence).

E.1   Request Generation

Used at the start of each reasoning step (§ 3.1, stage 1) to generate a focused sub-query $q^{(t)}$ from the current memory $\mathcal{M}^{(t)}$ and question q. In CoT mode, this prompt also decides whether the question is already answerable from memory. In MCTS mode, it serves as the **Sub-question/Answer** node type.

Request Generation Prompt

```
You are an expert assistant for multi-hop
    question answering and reasoning
decomposition. Decide whether the main
    question can already be answered from
    the
provided context. If not, generate strategic
    subquestions to advance the reasoning.

## Intermediate Answer
If `intermediate_answer` is provided, it is
    the resolved result of the PREVIOUS
```

```
hop. Use it as the anchor for the next
    subquestion, do NOT re-ask what was
already resolved.

## Core Principles
Each subquestion must:
- target a real knowledge gap not answerable
    from the provided context
- be atomic, self-contained, and
    understandable without the main question
- be non-redundant with other generated
    subquestions

**Sequential chains are allowed** when the
    main question explicitly links hops. In
these cases, generate subquestions in order,
    the first hop first, the next
anchored to its result. Sequential
    subquestions may depend on each other.

## Instructions
1. Analyze the main question: identify core
    intent, key entities, constraints,
    and required reasoning steps.
2. Check the context: if sufficient to
    answer, set `is_answerable` to true
    and stop.
3. Identify missing knowledge: only gaps
    that meaningfully advance reasoning
    toward the answer.
4. Generate subquestions:
   - For parallel gaps: each must be
     independently answerable.
   - For chained hops: generate in
     sequential order; use `
     intermediate_answer`
     to anchor step 2+.
   - If a subquestion is answerable with
     high confidence from common knowledge,
     include the answer inline.
5. Validate: remove subquestions answerable
    from context, redundant, or
```

Category	%	Representative example
Retrieval gap	44.8	"Oregon Trail/MECC (1971)" is the longest-running franchise; corpus attributed it to Super Mario/Nintendo
Incomplete chain	20.7	"Father of father of computer science" $\rightarrow$ Rev. John Robert Turing (correct: Julius Mathison Turing)
Wrong entity linking	13.8	"Third oldest surviving university" $\rightarrow$ Durham (correct: Cambridge; Durham is third in England only)
Synthesis error	13.8	"Habiba Akumu Nyanjango" in working memory; synthesizer output "Habiba Akumu Obama"
Surface-form mismatch	6.9	"2011" predicted (gold: "30 June 2011")

Table 11: Failure mode breakdown for Co-E (MCTS) on Bamboogle.

```
    low-value. Keep at most 3.

## Scope Consistency
Preserve the geographic or categorical scope
    of the main question. Do NOT
silently narrow a global scope to a specific
    region without justification.

## Output Format
Respond with a JSON object with exactly
    these keys:
- is_answerable: boolean
- subquestions: array of strings or null
```

E.2 Corpus Search

E.2.1 Query Generator

Rewrites the sub-query $q^{(t)}$ into search-optimized queries for web or dense-retrieval search (§ 3.4, Corpus Search).

Query Generator Prompt

```
You are a Reasoning Engine that deconstructs
    user input into precise,
self-contained search queries.

## Principles
1. Self-Contained: Each query understandable
    without original input.
2. Atomic: One single fact per query.
3. Essential & Non-Redundant: Every query
    necessary and unique.

## Instructions
1. Parse the Input: identify type (factual,
    comparative, causal, temporal),
   key entities, and required reasoning
    steps.
2. Generate Strategic Queries: formulate
    queries that collectively cover all
   necessary information to answer the input.

3. Ensure Self-Containment: each query must
    be independently answerable.
4. Review for Completeness and Non-
    Redundancy.
5. Temporal Grounding: if the input contains
    "current", "now", or a
   present-tense superlative, add "as of [
    current year]" to at least one query.
6. Fallback Queries: add 1-2 fallback
    queries using common aliases or
   alternative phrasings so that retrieval
    succeeds if the primary phrasing
```

```
    returns no results.

## Output Format
Respond with a JSON object with exactly
    these keys:
- queries: array of strings
```

E.2.2 Extractor

Filters each retrieved document into self-contained, question-relevant snippets that form $S^{(t)}$ (§ 3.4, Corpus Search). Raw documents never enter the working memory directly.

Extractor Prompt

```
You are a meticulous research analyst. Build
    a comprehensive dossier of
information from the provided text that
    could help answer the question.

Rules:
- Consider both direct and indirect relevant
    information. Information is
  relevant if it contains clues that could
  help answer the question (not
  necessarily directly answering it, but
    providing information that could
  help answer the question).
- Extracted information must be self-
    contained and clear, i.e.,
    understandable
  without any external context.

Instructions:
1. Question Deconstruction: identify primary
    subject, key entities, and
   specific information sought.
2. Candidate Identification: identify and
    quote ALL passages potentially
   related to concepts in the question. Be
    liberal and inclusive in this
   initial pass.
3. Relevance Evaluation: assess each quote
    against criteria (directly
   answering, contextual, supporting
   evidence, etc.).
4. Extraction: extract ALL relevant
    information. Add context for clarity but
   preserve original meaning. Each extracted
    item must be FULLY UNDERSTANDABLE
   on its own.
5. Final evaluation: examine each item for
    self-containment and relevance;
   rewrite or remove as needed.
```

```
## Output Format
Respond with a JSON object with exactly
    these keys:
- relevant_information: array of strings
```

E.3 Response Generation

Used in stage 3 of each reasoning iteration (§ 3.1) to produce an intermediate answer from the current memory augmented with newly retrieved evidence.

Response Generation Prompt

```
You are an expert assistant specializing in
    precise, well-reasoned question
answering. Deliver a direct, accurate answer
    with transparent, step-by-step
reasoning.

## Instructions
1. Analyze the question: identify core
    intent, key entities, and specific
    information sought.
2. Context priority: when context is
    provided, ground your answer exclusively
    in the context, do not introduce external
    facts. Only use your own
    knowledge when context is absent or
    clearly incomplete, and explicitly state
    when doing so.
3. Synthesize a clear, well-reasoned answer.
    State any assumptions clearly.

## Output Format
Respond with a JSON object with exactly
    these keys:
- answer: string
- concise_answer: string
- reasoning: string
- confidence_level: string
```

E.4 Memory Updating

E.4.1 Memory Consolidation

Runs twice per synchronization cycle (§ 3.3): once after evidence retrieval (primary consolidation) and once after graph-to-text injection (reconsolidation).

Memory Consolidation Prompt

```
You are an expert Memory Consolidation Agent.
    Process an input memory (a list
of information items) and consolidate it
    into a refined memory containing only
information relevant and useful for
    answering the given question.

## Instructions
1. Question Analysis: identify primary
    subject, key entities, and information
    sought.
2. Memory Atomization: atomize memory into
    atomic, self-contained items. No
```

```
    pronouns or references to external
    context.
3. Deduplication: if two items have the same
    content, keep one. If one item
    is completely contained in another,
    remove it.
4. Relevance Evaluation: keep items that
    contain ANY clue that could help
    answer the question.
4b. Provenance Audit: for each [System
    Prediction] item, check if any
    [Retrieval] item covers the same claim.
    If contradicted -> remove the
    [System Prediction] item. If supported
    -> upgrade provenance to "Retrieval".
4c. Hop Depth Filtering: items tagged [hop=N
    ] were retrieved at reasoning
    step N. If a lower-hop item fully
    answers the question, discard higher-hop
    items not needed. Strip [hop=N] prefixes
    from output `content`; record
    depth in `hop_depth`.
5. Irrelevant Information Removal.
6. Conflict Resolution: when a [Retrieval]
    item and a [System Prediction] item
    state conflicting specific facts, ALWAYS
    keep [Retrieval] and discard
    [System Prediction]. If two [Retrieval]
    items conflict, keep both and note
    the conflict.
7. Refinement: ensure each item is self-
    contained and clear.
8. Final check: verify every kept item is
    self-contained, non-redundant, and
    has correct provenance.

## Output Format
Respond with a JSON object with exactly
    these keys:
- consolidated_memory: array of objects;
    each object has:
  - content: string
  - provenance: string, exactly "System
    Prediction" or "Retrieval"
  - hop_depth: integer or null
```

E.4.2 Named Entity Recognition and Entity Linking

Identifies entities in the consolidated memory and links them to Wikidata QIDs for inclusion in the shared entity dictionary (§ 3.3, text-to-graph propagation).

NER and Entity Linking Prompt

```
You are an expert Named Entity Recognition
    specialist. Extract all named
entities from the text.

You may be given an optional list of KNOWN
    ENTITIES, each with:
- id: Wikidata QID
- name: official Wikidata label
- description: brief description for
    disambiguation
```

```
Wikidata linking rules (strict):
- If an extracted entity clearly matches a
      KNOWN ENTITY, set its id to that
  QID and use the KNOWN ENTITY's official
      name.
- If there is any ambiguity or you are not
      fully certain, set id to null.
- NEVER guess or invent a QID if it is not
      provided.

Instructions:
1. If text is a question, focus ONLY on
      entities which are main clues to
   answer the question.
2. Define precise boundaries (include
      modifiers).
3. Handle ambiguity using context.
4. Extract unique entities only once (
      deduplicate by real-world identity).

## Output Format
Respond with a JSON object with exactly
      these keys:
- entities: array of objects; each object
      has:
  - id: string or null
  - name: string
  - description: string or null
```

E.4.3 Relation Extraction

Extracts open-vocabulary (subject, relation, object) triples from the consolidated memory to extend the graph memory $\mathcal{G}$ (§ 3.3, text-to-graph propagation).

Relation Extraction Prompt

```
You are an expert Relation Extraction
      specialist. Extract all meaningful
relationships between entities. Each
      relationship must be self-contained.

You may be given an optional list of KNOWN
      ENTITIES (with Wikidata QIDs);
apply the same strict linking rules as NER.

Instructions:
1. Identify entity pairs with direct
      relationships.
2. Break down complex relationships into
      simpler ones.
3. Only extract explicitly stated or
      strongly implied relationships.
4. Use clear, concise, active-voice relation
       types.
5. Ensure relations are self-contained and
      non-duplicated.

## Canonical Relation Direction
Always use the ACTIVE form. Never use
      passive or inverse forms

Rules, convert to active form when a
      predicate:
1. ends in "_of"  -> invert: has_child,
      contains, has_capital
```

```
2. starts with "is_" -> invert to active
      form
3. ends in "_by" -> invert: precedes,
      directed, owns, succeeds

## Output Format
Respond with a JSON object with exactly
      these keys:
- relations: array of objects; each object
      has:
  - subject: string
  - subject_id: string or null
  - relation: string
  - object: string
  - object_id: string or null
  - context: string or null
```

E.4.4 Triple Pruner

Filters extracted and retrieved triples for question-relevance before they are merged into $\mathcal{G}$ (§ 3.3 and § 3.4). Applied as the LLM stage of the two-stage pruner (cross-encoder reranker followed by this LLM filter).

Triple Pruner Prompt

```
You are a Knowledge Graph Expert. Given a
      question and a list of triples,
keep only the triples that are genuinely
      useful for answering the question.

## Relevance Criteria
A triple (Subject, Relation, Object) is
      relevant ONLY if it meets one of:

1. Direct relevance: both subject AND object
       are directly related to the
  question, and the relation connects them
   in a way that helps answer it.
   - Example Q: "What is the capital of
   France?"
    Keep: (France, capital, Paris)
    Drop: (France, borders, Germany)

2. Chain relevance: the triple forms part of
       a reasoning chain with another
  kept triple. One entity of this triple
   must match an entity in another
  relevant triple, and together they help
   answer the question.
   - Example Q: "Who is the spouse of the
   president of France?"
    Keep: (France, president, Macron) + (
   Macron, spouse, Brigitte)

## Key Rule
Do NOT keep a triple just because one entity
       superficially matches a word in
the question. DO keep a triple if one entity
       is clearly relevant AND the other
could plausibly be an intermediate step or
      answer in the reasoning chain.

## Output Format
Respond with a JSON object with exactly
      these keys:
```

```
    - keep_indices: array of integers, 0-based
        indices of triples to retain
```

E.5 MCTS-Specific Prompts

These prompts are used exclusively in MCTS mode (§ 3.5). Each corresponds to one of the five MCTS node types.

E.5.1 Self-Correction Node

Self-Correction Prompt

```
You are an expert in answer verification and
    refinement. Given a question,
proposed answer, and context, verify
    correctness and provide a refined
    response.

## Instructions
1. Parse question requirements.
2. Extract relevant facts from context.
3. Evaluate proposed answer as: CORRECT /
    PARTIAL / INCORRECT / UNSUPPORTED.
4. Generate refined answer.

## Output Format
Respond with a JSON object with exactly
    these keys:
- status: string, one of: correct, partial,
    incorrect, unsupported
- refined_answer: string
- confidence_level: string
```

E.5.2 Question Rephrasing Node

Question Rephrasing Prompt

```
You are a Question Refiner that transforms
    unclear questions into precise,
clear questions. The rephrased question must
     be fully understandable on its
own without needing to refer back to the
    original.

## Principles
1. Clarity First: eliminate ambiguity and
    jargon.
2. Preserve Intent: do not alter the core
    inquiry.
3. Enhance Answerability: make specific and
    self-contained.

## Output Format
Respond with a JSON object with exactly
    these keys:
- rephrased_question: string
```

E.5.3 Synthesis Node

Synthesis Prompt

```
You are a specialized AI for multi-step
    reasoning. Perform a single, focused
reasoning step by analyzing context and
    producing a consolidated synthesis.
```

```
## Instructions
1. Analyze the main question objective.
2. Review all information in context.
3. If context is sufficient to directly
    answer, state this and formulate the
    definitive answer.
4. Otherwise, synthesize new thoughts that
    advance reasoning:
   - Causal or temporal links
   - Core relationship identification
   - Progress summary
   - Contradiction identification
   - Hypothesis formulation

## Critical Constraints
1. No External Information: do NOT introduce
    facts not in the context.
2. No New Questions: synthesize, do not
    query.

## Output Format
Respond with a JSON object with exactly
    these keys:
- is_answerable: boolean
- step_conclusion: string
- confidence_level: string
```

E.5.4 Final Answer Synthesis

Synthesizes the final answer from all candidate terminal nodes, weighted by their MCTS reward scores.

Final Answer Synthesis Prompt

```
You are an expert in argumentative synthesis.
     Construct a superior answer by
critically analyzing candidate answers and
    grounding your synthesis in
supporting evidence.

## Understanding your inputs
Candidate answers are MCTS outputs prefixed
    with [quality_score=X] where X in
[-1, 1]. Score >= 0.5: primary evidence.
    Score 0-0.5: supporting evidence.
Score < 0: treat skeptically.

supporting_evidence has two components:
- Textual facts tagged [Retrieval] (high
    reliability) or [System Prediction]
  (medium reliability).
- Knowledge graph triples (under **
    Information N** sections): structured
  entity-relationship facts. Use for
    verifying entity attributes; discard
  triples unrelated to the question.

## Synthesis Procedure
Phase I, Candidate Analysis: extract core
    claim, premises, reasoning chain
for each candidate. Weight by quality_score.

Phase II, Evidence Cross-Check & Conflict
    Resolution. Adjudication hierarchy:
1. High-score (>=0.5) + [Retrieval]
    corroboration
```

```
2. Convergent positive-score candidates
3. [Retrieval] facts regardless of candidate
     score
4. Logically sound reasoning consistent with
     graph triples
5. Majority agreement as last resort

Phase III, Synthesis & Self-Critique: verify
     every factual claim is traceable
to at least one reliable source. Revise if
     not.

## Output Format
Respond with a JSON object with exactly
     these keys:
- final_answer: string
- concise_answer: string
- reasoning: string
- confidence_level: string, one of: high,
     medium, low, uncertain
```

E.5.5 Verifier

The verifier runs three parallel calls conditioned on (i) no retrieved context, (ii) the textual memory $\mathcal{T}$, and (iii) the graph memory $\mathcal{G}$ serialized as triples; the normalized mean score becomes the MCTS reward $r \in [-1, 1]$.

Verifier Prompt

```
You are an expert verifier. Given a question
     and a candidate answer, evaluate
how well the answer is supported by the
     available evidence.

- If context is provided: use it as the
     primary source to verify the answer.
- If context is not provided: use your own
     knowledge to verify independently.

Rate from 0.0 to 10.0 how well the answer is
     correct/supported.

Scoring:
- 9.0-10.0: Fully verified / strongly
     supported
- 7.0-8.9:  Mostly supported, minor gaps
- 5.0-6.9:  Partially supported or uncertain
- 3.0-4.9:  Weakly supported, significant
     doubts
- 0.0-2.9:  Contradicted or completely
     unsupported

## Output Format
Respond with a JSON object with exactly
     these keys:
- rating: number, float from 0.0 to 10.0
- reasoning: string
```

E.6 LLM-Judged Accuracy (Acc)

Used offline to compute the supplementary Acc metric. This judge is not part of the Co-E inference pipeline.

LLM-Judged Accuracy Prompt

```
You are an expert evaluator. Rate the
     system_answer on a scale from 0.0 to
10.0 based on how effectively it addresses
     the user_question.

Evaluation Criteria:
1. Correctness (60%): Is the information
     factually accurate?
     - If correct_answer is provided and
     system_answer matches, award 10.0.
     - Otherwise, verify accuracy using your
     knowledge.
2. Helpfulness & Relevance (40%): Does it
     address the user's core need?

Scoring Guidelines:
- 9.0-10.0: Correct and comprehensive
- 7.0-8.9:  Mostly correct with minor issues
- 5.0-6.9:  Partially addresses or has
     accuracy concerns
- 3.0-4.9:  Significant correctness or
     relevance issues
- 0.0-2.9:  Incorrect or completely off-
     topic

Uncertainty rule: if you are not confident
     about the correct answer (obscure
facts, precise numbers, rare entities),
     assign 5.0 rather than a confident
high or low score.

## Output Format
Respond with a JSON object with exactly
     these keys:
- rating: number, float from 0.0 to 10.0
- reasoning: string
```