How To Design Stable Machine Learned Solvers For Scalar Hyperbolic PDEs

Abstract

Machine learned partial differential equation (PDE) solvers trade the robustness of classical numerical methods for potential gains in accuracy and/or speed. A key challenge for machine learned PDE solvers is to maintain physical constraints that will improve robustness while still retaining the flexibility that allows these methods to be accurate. In this paper, we show how to design solvers for scalar hyperbolic PDEs that are stable by construction. We call our technique 'global stabilization.' Unlike classical numerical methods, which guarantee stability by putting local constraints on the solver, global stabilization adjusts the time-derivative of the discrete solution to ensure that global invariants and stability conditions are satisfied. Although global stabilization can be used to ensure the stability of any scalar hyperbolic PDE solver that uses method of lines, it is designed to be used as an error-correcting algorithm for machine learned solvers.

1 Introduction

Scientists and engineers are interested in solving partial differential equations (PDEs). Many PDEs cannot be solved analytically, and must be approximated using discrete numerical algorithms. We refer to these discrete numerical algorithms as PDE solvers. The fundamental challenge for PDE solvers is to balance between two competing objectives: first, to find an accurate approximation to the solution of the equation, and second, to do so with as few computational resources as possible.

In recent years, scientists and engineers have attempted to use machine learning (ML) to design new and better PDE solvers [39, 2, 43, 29, 17, 42, 3, 40]. On certain problems, machine learned PDE solvers have achieved high accuracy at low computational cost [21, 37, 23, 14, 25]. However, these high-performing machine learned PDE solvers suffer from at least two major problems. First, they struggle to generalize to conditions outside of the training data. Second, they tend to have no guarantees of stability and as a result the solution sometimes blows up as $t \to \infty$. For examples of this second problem, see fig. 3a of [2] and fig. 9a of [43]. Consequently, [2] and [43] write that "figuring out how to guarantee stability" of machine learned PDE solvers is an "important topic for future work."

We consider scalar hyperbolic PDEs written in conservation form, given by

$$\frac{\partial u}{\partial t} + \boldsymbol{\nabla} \cdot \boldsymbol{f}(u) = 0. \tag{1}$$

For an introduction to the mathematical properties of, classical numerical methods for solving, and motivation for studying eq. (1), see [28]. If machine learned solvers for eq. (1) were somehow perfectly accurate, then stability (see section 2) would not be a concern because the solver would simply give the correct answer for all t. But, for a variety of reasons, machine learned solvers are not and will never be perfectly accurate. Some amount of error is inevitable, so the question becomes: how can we constrain the machine learned solver to give us the sorts of errors that we are willing

to tolerate? Although the answer to this question is problem dependent, we take the view that with machine learned numerical methods, as with well-designed classical numerical methods, the solution should be guaranteed not to blow up as $t \to \infty$ (see section 3).

The purpose of this paper is to demonstrate how to design machine learned solvers for eq. (1) that ensure stability (see sections 4 and 5) without degrading the accuracy of the solution. These solvers guarantee both mass conservation and stability as $t \to \infty$ for a subset of PDEs that are highly relevant in the physical sciences and engineering. We call our technique 'global stabilization'. In particular, the global stabilization technique can be used as a 'hard' constraint on the model architecture of so-called 'hybrid' machine learned solvers (see section 6). We present the global stabilization technique in 1D and 2D for rectangular grids with periodic boundary conditions, though it can easily be generalized to higher dimensional PDEs. We note that the method can also be used when the right hand side (RHS) of eq. (1) is nonzero (see section 6).

2 Stability of Scalar Hyperbolic PDEs

Conservation properties: eq. (1) implies that the scalar $\int u(\boldsymbol{x}, t) \, d\boldsymbol{x}$ is time-invariant, which we call 'conservation of mass'. In a 1D periodic system with $x \in [0, L]$, an integral over x makes the invariance apparent: $\frac{d}{dt} \int_0^L u(x, t) \, dx = \int_0^L \frac{\partial u}{\partial t} \, dx = -\int_0^L \frac{\partial f}{\partial x} \, dx = f(0) - f(L) = 0$. In words: the total rate of change of u is equal to the flux through the boundaries; for a periodic system this equals zero.

Stability properties: we begin with the entropy inequality [28, 36] given by

$$\frac{\partial S(u)}{\partial t} + \boldsymbol{\nabla} \cdot \boldsymbol{F}(u) \geq 0. \tag{2}$$

Equation (2) is satisfied for any concave entropy function $S(u)$, so long as the entropy flux $\boldsymbol{F}$ is defined as $\boldsymbol{F}(u) \coloneqq \int^u S'(u) \boldsymbol{f}'(u) \, du$. Integrating eq. (2) over x for a 1D periodic system where $x \in [0, L]$ shows that the total entropy is non-decreasing: $\frac{d}{dt} \int S(u) \, dx \geq F(0) - F(L) = 0$. By choosing $S(u) = -||u||_p$, where $||u||_p$ is defined as the ℓ_p-norm $||u||_p \coloneqq (\int |u|^p \, dx)^{1/p}$ for $1 \leq p < \infty$, we have the first stability property of eq. (1), which is that the ℓ_p-norm of u is non-increasing: $\frac{d}{dt}||u||_p \leq 0$ for $1 \leq p < \infty$. Taking the limit as $p \to \infty$ gives a second stability property, which is that the ℓ_∞-norm of u is non-increasing: $\frac{d}{dt}||u||_\infty \leq 0$. There is a third stability property, called the 'total variation diminishing' (TVD) property, which is derived in [28]. For continuous u, the TVD property is that $\frac{d}{dt} \int_0^L \left| \frac{\partial u}{\partial x} \right| dx \leq 0$.

3 Stability of Discrete Numerical Methods for Scalar Hyperbolic PDEs

[28] writes that "the central philosophy of numerical analysis is to devise numerical schemes that preserve stability properties of the underlying continuous problem." We now review how classical techniques preserve stability properties.

The standard approach of solving time-dependent PDEs is to discretize the PDE in space, which generates a system of ordinary differential equations (ODEs), then to integrate those ODEs in time. This approach is called method of lines (MOL). A very common approach for solving conservation-form PDEs is by using some type of finite-volume (FV) method. FV methods divide the spatial domain into a number of cells, then use a scalar value to represent the solution average within each cell. For example, on the 1D domain $x \in [0, L]$ with uniform cell width, a FV method divides the domain into N cells of width $\Delta x = L/N$ where the left and right boundaries of the jth cell for $j = 1, \ldots, N$ are $x_{j-1/2} = (j - 1)\Delta x$ and $x_{j+1/2} = j\Delta x$ respectively. FV methods also use a scalar value $u_j(t)$ to represent the solution average within each cell where $u_j(t) \coloneqq \int_{x_{j-1/2}}^{x_{j+1/2}} u(x, t) \, dx$. The standard FV equations for the time-derivative of u_j in 1D and $u_{i,j}$ in 2D are simply discrete versions of the continuity equation:

$$\frac{\partial u_j}{\partial t} + \frac{f_{j+\frac{1}{2}} - f_{j-\frac{1}{2}}}{\Delta x} = 0 \quad \text{(3a)} \qquad \frac{\partial u_{i,j}}{\partial t} + \frac{f^x_{i+\frac{1}{2},j} - f^x_{i-\frac{1}{2},j}}{\Delta x} + \frac{f^y_{i,j+\frac{1}{2}} - f^y_{i,j-\frac{1}{2}}}{\Delta y} = 0. \tag{3b}$$

where $f_{j+1/2}$ is the flux at the cell boundary $x_{j+1/2}$ and $f^x_{i+1/2,j}$ and $f^y_{i,j+1/2}$ are the average x-directed and y-directed fluxes through the right and top cell boundaries, e.g.,

79 $f_{i+1/2,j}^x := \frac{1}{\Delta y}\int_{y=y_{j-1/2}}^{y=y_{j+1/2}} \hat{\boldsymbol{x}} \cdot \boldsymbol{f}(x_{i+1/2},y)\,dy$. In 1D, eq. (3a) can be derived by applying the

80 integral $\int_{x_{j-1/2}}^{x_{j+1/2}}(...)\,dx$ to eq. (1) for all $j \in 1,\dots,N$; a similar calculation in 2D gives eq. (3b).

81 Equations (3a) and (3b) are exact. So long as the flux f across cell boundaries is exact for all t, then

82 the discrete solution u will be exact for all t. Thus, the key challenge for a FV scheme is to accurately

83 reconstruct the flux at cell boundaries.

84 For the rest of this paper, we consider solvers that use MOL and the FV method. We will also assume

85 that the ODE integration is stable; this can usually be done by using a strong stability preserving

86 Runge Kutta (SSPRK) ODE integration method [13, 12] and choosing the timestep to satisfy a CFL

87 condition. We also restrict ourselves to rectangular, periodic grids with uniform cell size. Our results

88 can easily be generalized to the case where the grid spacing is non-uniform.

89 **Conservation properties:** FV schemes conserve a discrete analogue $\sum_{j=1}^{N} u_j \Delta x$ of the continuous

90 invariant $\int u\,d\boldsymbol{x}$ by construction. In 1D, we can see this with a short proof: $d/dt \sum_{j=1}^{N} u_j \Delta x =$

91 $\Delta x \sum_{j=1}^{N} \partial u_j/\partial t = -\sum_{j=1}^{N}(f_{j+1/2} - f_{j-1/2}) = f_{N+1/2} - f_{1/2}$. The rate of change of the discrete

92 mass is equal to the flux of u through the boundaries; in a periodic system this equals 0.

93 **Stability properties:** Although FV schemes inherit a discrete analogue of conservation of mass by

94 construction, they do not automatically inherit discrete analogues of any of the stability properties

95 of the continuous system eq. (1). Instead, FV methods ensure stability through careful choice of

96 flux. The only known way of inheriting discrete analogues of all three stability properties of eq. (1)

97 (non-increasing ℓ_p-norm, non-increasing ℓ_∞-norm, and TVD) is to use a consistent monotone flux

98 function (see [28] for definitions of consistency and monotonicity). An example of a monotone flux

99 function for the linear advection equation $f = cu$ is the upwind flux; for non-linear $f(u)$ examples

100 of monotone flux functions include the Godunov flux and the Lax-Friedrichs flux. Unfortunately,

101 Godunov's famous theorem from 1959 implies that monotone schemes can be at most first-order

102 accurate [10]; this means that while monotone schemes are great at stability, they are usually not very

103 accurate. Fortunately, for a solver of eq. (1) to be stable it only has to inherit a discrete analogue

104 of *one* of the three stability properties of the continuous equation [8]. This was one of the insights

105 leading Van Leer's seminal paper introducing the MUSCL scheme [41]. MUSCL inherits a discrete

106 analogue of the TVD property (which guarantees stability and prevents spurious oscillations) while

107 retaining higher-order accuracy.

3.1   The Energy Method for Stability Analysis

109 As we learned in section 3, for a numerical method to be stable, it must inherit one or more of the

110 stability properties of eq. (1). The energy method is a technique that analyzes whether a numerical

111 method inherits a discrete analogue of the non-increasing ℓ_p-norm property. $p = 2$ is usually chosen.

112 Advantages of the energy method are that it can be used to analyze the stability of discrete methods

113 for solving eq. (1) even when $\boldsymbol{f}(u)$ is non-linear, when boundary conditions are non-periodic [8], and

114 with certain systems of hyperbolic PDEs [22, 19]. Using the energy method, in the time-continuous

115 limit a 1D discrete numerical algorithm for eq. (1) will be ℓ_2-norm stable if $\frac{d}{dt}\sum_{j=1}^{N}(u_j)^2 \Delta x \leq 0$

116 for all t. Some simple algebra gives $\frac{d}{dt}\Delta x \sum_{j=1}^{N} u_j^2/2 = \Delta x \sum_{j=1}^{N} u_j \frac{\partial u_j}{\partial t}$. Using eq. (3a), this

117 equals $-\sum_{j=1}^{N} u_j(f_{j+1/2} - f_{j-1/2})$. Performing summation by parts and ignoring boundary terms

118 that cancel in a periodic domain, this equals

$$\frac{d}{dt}\frac{\Delta x}{2}\sum_{j=1}^{N}(u_j)^2 = \sum_{j=1}^{N} f_{j+1/2}(u_{j+1} - u_j) \leq 0. \tag{4}$$

119 A discrete FV solver in 1D will be ℓ_2-norm stable if eq. (4) is satisfied for all t. For non-periodic

120 boundary conditions, eq. (4) is modified by replacing the RHS with a term which depends on the

121 flux through the boundaries.

4   Global Stabilization of Flux Predicting FV Schemes

123 We now introduce 'global stabilization,' a novel technique that guarantees the ℓ_2-stability of any FV

124 scheme given by eq. (3a) or (3b). In section 6, we will discuss how to use global stabilization as a

constraint on the model architecture of machine learned solvers. To derive this method in 1D with periodic boundary conditions, we begin with the energy method-based ℓ_2-norm stability condition eq. (4). Let us now define $d\ell_2^{\text{old}}/dt := \sum_{j=1}^{N} f_{j+\frac{1}{2}}(u_{j+1} - u_j)$ as the original rate of change of the discrete ℓ_2-norm, and $d\ell_2^{\text{new}}/dt$ as the desired rate of change of the discrete ℓ_2-norm. We also define $\boldsymbol{u}_j := \{u_j\}_{j=1}^{N}$ as a vector representation of the discrete solution. We can change the time-derivative of the discrete ℓ_2-norm from $d\ell_2^{\text{old}}/dt$ to $d\ell_2^{\text{new}}/dt$ by making the following transformation to $f_{j+1/2}$:

$$f_{j+\frac{1}{2}} \Rightarrow f_{j+\frac{1}{2}} + \frac{(d\ell_2^{\text{new}}/dt - d\ell_2^{\text{old}}/dt)G_{j+1/2}(\boldsymbol{u}_j)}{\sum_{k=1}^{N} G_{k+1/2}(\boldsymbol{u}_k)(u_{k+1} - u_k)} \tag{5}$$

for any scalar $d\ell_2^{\text{new}}/dt$ and any non-constant, finite function $G_{j+1/2}(\boldsymbol{u}_j)$ in which $\sum_{k=1}^{N} G_{k+1/2}(\boldsymbol{u}_k)(u_{k+1} - u_k) \neq 0$. As the reader can verify by plugging eq. (5) into eq. (4), eq. (5) modifies $f_{j+1/2}$ in a way that adds a constant $(d\ell_2^{\text{new}}/dt - d\ell_2^{\text{old}}/dt)$ to eq. (4) via cancellation of the denominator. Note that $G_{j+1/2}(\boldsymbol{u}_j)$ is a hyper parameter that determines how each $f_{j+1/2}$ is modified and $d\ell_2^{\text{new}}/dt$ is a user-defined quantity which sets the rate of change of the discrete ℓ_2-norm. We want $d\ell_2^{\text{new}}/dt \leq 0$ for stability. A similar calculation in 2D reveals that the rate of change of the discrete ℓ_2-norm is given by

$$\frac{d}{dt} \sum_{i,j} \frac{u_{i,j}^2}{2} \Delta x \Delta y = \Delta y \sum_{i,j} f_{i+\frac{1}{2},j}^x (u_{i+1,j} - u_{i,j}) + \Delta x \sum_{i,j} f_{i,j+\frac{1}{2}}^y (u_{i,j+1} - u_{i,j}) \leq 0. \tag{6}$$

We define $d\ell_2^{\text{old},x}/dt := \Delta y \sum_{i,j} f_{i+\frac{1}{2},j}^x (u_{i+1,j} - u_{i,j})$ and $d\ell_2^{\text{old},y}/dt := \Delta x \sum_{i,j} f_{i,j+\frac{1}{2}}^y (u_{i,j+1} - u_{i,j})$. Equation (6) will be satisfied if the following transformations are made to $f_{i+\frac{1}{2},j}^x$ and $f_{i,j+\frac{1}{2}}^y$:

$$f_{i+\frac{1}{2},j}^x \Rightarrow f_{i+\frac{1}{2},j}^x + \frac{(d\ell_2^{\text{new},x}/dt - d\ell_2^{\text{old},x}/dt)G_{i+1/2,j}^x(\boldsymbol{u}_{ij})}{\Delta y \sum_{k,l} G_{k+1/2,l}^x(\boldsymbol{u}_{kl})(u_{k+1,l} - u_{k,l})} \tag{7a}$$

$$f_{i,j+\frac{1}{2}}^y \Rightarrow f_{i,j+\frac{1}{2}}^y + \frac{(d\ell_2^{\text{new},y}/dt - d\ell_2^{\text{old},y}/dt)G_{i,j+1/2}^y(\boldsymbol{u}_{ij})}{\Delta x \sum_{k,l} G_{k,l+1/2}^y(\boldsymbol{u}_{kl})(u_{k,l+1} - u_{k,l})} \tag{7b}$$

for any scalars $d\ell_2^{\text{new},x}/dt$ and $d\ell_2^{\text{new},y}/dt$ where $d\ell_2^{\text{new},x}/dt + d\ell_2^{\text{new},y}/dt \leq 0$ and any non-constant, finite functions $G_{i+1/2,j}^x(\boldsymbol{u}_{ij})$ and $G_{i,j+1/2}^y(\boldsymbol{u}_{ij})$ for which $\sum_{k,l} G_{k+1/2,l}^x(\boldsymbol{u}_{kl})(u_{k+1,l} - u_{k,l}) \neq 0$ and $\sum_{k,l} G_{k,l+1/2}^y(\boldsymbol{u}_{kl})(u_{k,l+1} - u_{k,l}) \neq 0$. Equations (5), (7a) and (7b) are the main results of section 4; for scalar conservation form PDEs in 1D and 2D they ensure that the discrete ℓ_2-norm will be non-increasing in the time-continuous limit.

In our experiments we set $G_{j+1/2}(\boldsymbol{u}_j) = (u_{j+1} - u_j)$, $G_{i+1/2,j}^x(\boldsymbol{u}_{ij}) = (u_{i+1,j} - u_{i,j})$, and $G_{i,j+1/2}^y(\boldsymbol{u}_{ij}) = (u_{i,j+1} - u_{i,j})$. These choices have a simple physical interpretation: they correspond to the addition of a spatially constant diffusion coefficient everywhere in space [26]. Possible alternatives include setting $G_{j+1/2}(\boldsymbol{u}_j) = (u_{j+1} - u_j)^\beta$ for $\beta > 1$ or $G_{j+1/2}(\boldsymbol{u}_j) = \alpha_{j+1/2}(u_{j+1} - u_j)$ for $\alpha_{j+1/2} \in \mathbb{R}$. Choosing large β increases the amount of numerical diffusion added at discontinuities and decreases the amount of diffusion added in smooth regions, while $\alpha_{j+1/2}$ is a spatially dependent scalar which determines a spatially varying distribution of added numerical diffusion.

Global stabilization allows the user to control the rate of change of the ℓ_2-norm (i.e., the rate of numerical diffusion). We now show how this technique can be used to stabilize an unstable numerical method and to reduce or eliminate numerical damping from a stable numerical method.

Figure 1 demonstrates how global stabilization can stabilize an unstable scheme. On the inviscid Burgers equation the centered flux $f_{j+1/2} = (u_j^2 + u_{j+1}^2)/4$, shown in red, is unstable. We apply global stabilization to the centered flux with $d\ell_2^{\text{new}}/dt = 0$, shown in blue. This leads to exact conservation of the ℓ_2-norm and a stable numerical method. Our initial condition is $u(x) = \sin x$.

Note that the globally stabilized centered flux solution in fig. 1 conserves both the discrete mass and the discrete ℓ_2-norm, but does not maintain a discrete analogue of the total variation diminishing (TVD) property [8] of the scalar Burgers equation. As a result, the globally stable solution develops high-k oscillations; these spurious oscillations tend to be seen in ℓ_2-norm conserving schemes that do not have enough diffusion to damp high-k modes that develop near steep gradients [34].

Figure 1: Global stabilization turns an unstable solver into a stable solver. While centered flux $f_{j+1/2} = (u_j^2 + u_{j+1}^2)/4$ is an unstable choice of flux (red) on the inviscid Burgers equation and blows up by $t = 0.5$, global stabilization (blue) ensures that the discrete ℓ_2-norm is conserved.

(a)   (b)

Figure 2: Applying global stabilization to a stable FV scheme can reduce or eliminate numerical diffusion, but at the cost of introducing spurious high-k oscillations. (a) Images of the vorticity χ evolving under the incompressible Euler equations. The first and second columns show the baseline MUSCL scheme at high and low resolution. The third and fourth columns show the baseline MUSCL scheme with global stabilization (GS), either with no numerical damping or with numerical damping reduced by 75%. (b) Energy, enstrophy, and vorticity correlation over time. We use vorticity correlation as a benchmark measure of accuracy.

Figure 2 demonstrates how global stabilization can reduce or eliminate numerical damping from a stable scheme. We solve the 2D incompressible Euler equations in vorticity form, given by

$$\frac{\partial \chi}{\partial t} + \boldsymbol{\nabla} \cdot (\boldsymbol{u}\chi) = 0, \qquad \boldsymbol{u} = \boldsymbol{\nabla}\psi \times \hat{e}_z, \qquad -\boldsymbol{\nabla}^2\psi = \chi. \qquad (8)$$

Our baseline choice of flux is the second-order TVD MUSCL scheme with monotonized central (MC) slope limiters [38, 41]. We use a linear finite element (FE) solver for the poisson equation [1] and a strong stability preserving RK3 ODE integrator [13]. Note that eq. (8) exactly conserves both the energy $\frac{1}{2} \int \boldsymbol{u}^2 \, dx \, dy$ and the enstrophy $\int \chi^2 \, dx \, dy$ [35].

In each column of fig. 2a, we see the time-evolution of the vorticity χ according to one of four schemes. The baseline MUSCL schemes in the first and second columns decay the discrete ℓ_2-norm, while the MUSCL schemes with global stabilization (GS) in the third and fourth columns either exactly conserve ℓ_2-norm by setting $d\ell_2^{\text{new},x}/dt = d\ell_2^{\text{new},y}/dt = 0$ (no damping) or reduce the rate of numerical diffusion by 75% by setting $d\ell_2^{\text{new},x}/dt = \frac{1}{4}d\ell_2^{\text{old},x}/dt$ and $d\ell_2^{\text{new},y}/dt = \frac{1}{4}d\ell_2^{\text{old},y}/dt$ (reduced damping). In the third column, we again find that globally ensuring ℓ_2-norm conservation introduces spurious high-k oscillations.

In fig. 2b, bottom row, we plot the vorticity correlation between the high resolution baseline scheme and each of the four schemes shown in figure 2a. Vorticity correlation has been used previously as a benchmark measure of accuracy for these equations [21]. We find that applying global stabilization

with no damping underperforms relative to the baseline scheme at the same resolution, while global
stabilization with reduced damping performs similarly to the baseline scheme at the same resolution.
In fig. 2b, middle and top rows, we plot the discrete enstrophy $\sum_{i,j} \int \chi_{i,j}^2 \Delta x \Delta y$ and discrete energy
$\frac{1}{2} \sum_{i,j} \int (\boldsymbol{u}_{ij})^2 \Delta x \Delta y$ for each of the four schemes shown in figure 2a. The baseline schemes decay
energy and enstrophy, while the globally stabilized scheme with no damping exactly conserves
enstrophy and increases energy. The globally stabilized scheme with reduced damping decays
enstrophy and displays a non-monotonic increase in energy.

5 Global Stabilization of MOL Schemes with Arbitrary Time-Derivative

In section 4, we considered schemes that predict the flux f at cell boundaries. Using the energy
method, we found that we could adjust the flux prediction to ensure global stability. However, some
machine learned PDE solvers may use an alternative form for the time-derivative which does not
involve predicting the flux at cell boundaries. Thus, we now consider the more general problem of
how to stabilize MOL-based solvers for eq. (1) with arbitrary time-derivative. Suppose that the rate
of change of the cell average u_j in 1D or $u_{i,j}$ in 2D is given by

$$\frac{\partial u_j}{\partial t} = N_j(\boldsymbol{u}_j) \quad\quad (9\text{a}) \quad\quad\quad \frac{\partial u_{i,j}}{\partial t} = N_{i,j}(\boldsymbol{u}_{ij}) \quad\quad (9\text{b})$$

where $N_j(\boldsymbol{u}_j)$ and $N_{i,j}(\boldsymbol{u}_{ij})$ are arbitrary functions and $\boldsymbol{u}_j$ and $\boldsymbol{u}_{ij}$ are again vector representations of
the discrete solution. Note that eqs. (9a) and (9b) do not guarantee mass conservation by construction.
Ensuring stability therefore requires modifying N_j and $N_{i,j}$ to ensure both mass conservation and
a non-increasing discrete ℓ_2-norm. In 1D, this can be written as $\Delta x \sum_{j=1}^{N} \frac{\partial u_j}{\partial t} = \Delta x \sum_j N_j = 0$
and $\Delta x \sum_{j=1}^{N} u_j \frac{\partial u_j}{\partial t} = \Delta x \sum_j u_j N_j \leq 0$ which implies that the discrete mass will be conserved
and the discrete ℓ_2-norm will decay if $\langle \boldsymbol{N}_j \rangle := \sum_{j=1}^{N} N_j = 0$ and $\langle \boldsymbol{u}_j | \boldsymbol{N}_j \rangle := \sum_{j=1}^{N} u_j N_j \leq 0$.
The bracket notation $\langle \dots \rangle$ denotes the mean value over the domain while the inner product notation
$\langle \dots | \dots \rangle$ denotes a sum over all domain cells. These conditions will be satisfied if the following
transformation is applied to N_j:

$$\boldsymbol{U}_j := \boldsymbol{u}_j - \langle \boldsymbol{u}_j \rangle \quad\quad \boldsymbol{M}_j := \boldsymbol{N}_j - \langle \boldsymbol{N}_j \rangle \quad\quad \boldsymbol{N}_j \Rightarrow \boldsymbol{M}_j + \frac{\frac{d\ell_2^{\text{new}}}{dt} \boldsymbol{G}_j(\boldsymbol{M}_j)}{\langle \boldsymbol{U}_j | \boldsymbol{G}_j(\boldsymbol{M}_j) \rangle} - \frac{\langle \boldsymbol{U}_j | \boldsymbol{M}_j \rangle}{\langle \boldsymbol{U}_j | \boldsymbol{U}_j \rangle} \boldsymbol{U}_j \quad (10)$$

for any $d\ell_2^{\text{new}}/dt \leq 0$ and any smooth function $\boldsymbol{G}_j(\boldsymbol{M}_j)$ where $\langle \boldsymbol{G}_j(\boldsymbol{M}_j) \rangle = 0$ and $\langle \boldsymbol{G}_j(\boldsymbol{M}_j) | \boldsymbol{U}_j \rangle \neq 0$.
A simple choice is $\boldsymbol{G}_j(\boldsymbol{M}_j) = \boldsymbol{M}_j$. Equation (10) is the main result of section 5.

6 Stable Machine Learned PDE Solvers

The purpose of this paper is to demonstrate how to design stable *machine learned solvers*. Global
stabilization can be applied to (a) so-called 'hybrid' machine learned PDE solvers (b) that use ML to
approximate the divergence term $\boldsymbol{\nabla} \cdot \boldsymbol{f}(u)$ in eq. (1) in the time-continuous limit (c) even when the
RHS of eq. (1) is non-zero.

Regarding (a), the defining feature of a hybrid machine learned solver is that it inherits one or more
of the properties of classical numerical methods. See section 7 for examples of papers that use hybrid
solvers. Usually, this involves discretizing the domain into a number of grid cells, and using some
sort of time-stepping procedure or ODE integration to advance the solution (i.e., method of lines).

Regarding (b), approximating the divergence term is usually the most difficult element of a numerical
method, so it is fairly common to replace this term with a machine-learned approximation. Some
hybrid solvers may use the FV method and use ML to approximate the flux across cell boundaries
$f_{j+1/2}$. Other hybrid solvers may use the more general time-derivative function eq. (9a).

Regarding (c), when the RHS of eq. (1) is non-zero, global stabilization can be applied by treating
the right hand side terms using classical techniques and applying global stabilization only to the
divergence term. As we explain in appendix A, this works because the divergence term is typically
the cause of numerical instability while the RHS terms are usually straightforward to approximate
and do not contribute to numerical instability.

Recall that the global stabilization technique requires setting the value of $d\ell_2^{\text{new}}/dt$. According to eq. (4), for stability we want the discrete ℓ_2-norm of the exact solution to be non-increasing for all t. Thus, in algorithm 1 we propose a practical method for choosing $d\ell_2^{\text{new}}/dt$ when applying global stabilization to machine learned PDE solvers that satisfy the conditions (a), (b), and (c). Algorithm 1 can be used to ensure stability of machine learned solvers that predict $f_{j+1/2}$ in eq. (3a) or to ensure mass conservation and stability of solvers that use equation eq. (9a). Algorithm 1 does not change the output of the machine learned PDE solver if the solver tries to decay the discrete ℓ_2-norm, but sets $d\ell_2^{\text{new}}/dt = 0$ if the solver tries to increase the discrete ℓ_2-norm. Intuitively, algorithm 1 is an error correcting algorithms that adjusts the output of the machine learned solver if that output moves the solution towards instability. As a result, the method is stable according to the criterion in eq. (4). Algorithm 1 is the main result of section 6.

Algorithm 1 A stable machine learned MOL-based PDE solver in 1D

1: **Inputs**: Initial condition $\{u_j(t_0)\}_{j=1}^{N_x}$, ODE integrator, ML predictor for $f_{j+\frac{1}{2}}$ or N_j
2: **while** $t < T_f$ **do**
3:     Choose Δt, compute $\{f_{j+\frac{1}{2}}\}_{j=1}^{N_x}$ or $\{N_j\}_{j=1}^{N_x}$ using ML predictor
4:     **if** using eq. (3a) **then**
5:        **if** $d\ell_2^{\text{old}}/dt = \sum_j f_{j+\frac{1}{2}}(u_{j+1} - u_j) > 0$ **then**
6:           Set $\{f_{j+\frac{1}{2}}\}_{j=1}^{N_x}$ according to eq. (5) with $d\ell_2^{\text{new}}/dt = 0$
7:     **else if** using eq. (9a) **then**
8:        **if** $\langle M | u \rangle \le 0$ **then**
9:           Set $N = M$
10:        **else**
11:           Set N according to eq. (10) with $d\ell_2^{\text{new}}/dt = 0$
12:     Advance time t by Δt and state $\{u_{j+\frac{1}{2}}\}_{j=1}^{N_x}$ according to ODE integrator
13: **Output:** $\{u_j(T_f)\}_{j=1}^{N_x}$

6.1 Towards a Deeper Understanding of Global Stabilization

Readers familiar with classical numerical methods, which ensure stability via locally-derived constraints on the flux $f_{j+1/2}$, might be concerned by the global stabilization technique. It does, after all, violate the physical property that for hyperbolic PDEs information propagates at finite speed along characteristics. Why not just put local constraints on $f_{j+1/2}$?

It is of course *possible* to guarantee stability of machine learned numerical methods by putting local constraints on the flux. One could, for example, develop a TVD method by applying a flux limiter to a machine learned solver that predicts $f_{j+1/2}$. The problem with doing this is that (a) the goal of machine learned solvers is to use fewer computational resources than classical numerical methods, which requires solving the equations at coarser resolution, i.e., larger Δx (see the discussion of LES models in section 7), (b) at coarse resolution a high proportion of grid cells are either extremum or have sharp gradients, (c) local constraints like flux limiters add numerical diffusion to extremum and sharp gradients, and (d) the magnitude of numerical diffusion goes like $(\Delta x)^2$ [26]. The implication of (a), (b), (c), and (d) is that TVD-stable machine learned numerical methods operating at coarser resolution than classical solvers will add large amounts of numerical diffusion to many of the grid cells which will rapidly degrade the accuracy of the solution. Improving accuracy at coarse resolution requires finding a way to ensure stability while adding less numerical diffusion.

The whole point of the global stabilization method is that it can guarantee the stability of a solver *without* degrading the accuracy of an already-accurate solver. Global stabilization adds the minimum amount of numerical diffusion necessary to ensure ℓ_2-norm stability. This is only possible because we compute the *global* rate of change of the discrete ℓ_2-norm. See section 9 for further discussion.

Finally, we highlight a subtle point related to algorithm 1. Algorithm 1 proposes ensuring that the rate of change of the discrete ℓ_2-norm is non-increasing. However, in eq. (8), the ℓ_2-norm of the continuous solution is constant. Naively, for eq. (8) wouldn't we want algorithm 1 to set $d\ell_2^{\text{new}}/dt = 0$? No. As explained in appendix B, even for eq. (8) we want to ensure that $d\ell_2^{\text{new}}/dt \le 0$.

7 Related Work

LES models and backscattering: The objective of large eddy simulation (LES) is identical to that of many machine learned numerical solvers: both attempt to find an accurate approximation to the solution of the PDE with fewer computational resources than classical numerical methods. Both also attempt to do so without resolving the smallest scales of the problem, relying on either an explicit or implicit subgrid model to do so [2, 43, 21, 37, 40, 24, 32, 15, 16, 27, 3, 42, 30]. Of particular relevance to the stability of subgrid models (both in LES and ML) are the concepts of 'forward-scatter' and 'backscatter'. In 2D LES turbulence, forward-scattering involves the transfer of enstrophy from resolved to unresolved scales, while backscattering involves the transfer of enstrophy from unresolved to resolved scales. Analysis across a wide range of flows demonstrates two important facts [33]. First, to be accurate a subgrid model must allow both forward-scatter and backscatter. In the context of scalar hyperbolic PDEs, this means that to be accurate a subgrid model must allow a discrete analogue of the entropy inequality in eq. (2) to be locally violated. Second, averaged over the entire domain there is always more forward-scatter than backscatter. If on average there were more backscatter than forward-scatter, then the subgrid model would be unstable [15]. Global stabilization can thus be interpreted as a way of constraining a subgrid model to ensure that on average there is always at least as much forward-scatter as backscatter.

Machine learned finite volume solvers: [2, 43, 21] use machine learned finite volume solvers to solve a variety of 1D and 2D PDEs. Almost all of these PDEs can be written in conservation form with added diffusion and forcing terms. These 'hybrid' solvers conserve mass by construction but not the discrete ℓ_2-norm and therefore do not guarantee stability; instead, they promote stability by unrolling the loss function over multiple timesteps. [21] trains a hybrid solver for the 2D incompressible Euler equations that "remains stable during long simulations." This impressive result is likely facilitated by the addition of physical diffusion to the PDE, which decays the ℓ_2-norm at each timestep.

Other machine learned solvers: [24, 40, 32, 21] use convolutional neural networks to correct errors in low-resolution simulations; these hybrid solvers promote stability and improve accuracy by unrolling the loss function over multiple timesteps. [37] solves 2D and 3D hyperbolic PDEs using the 'fully learned' update equation $u_{i,j}(t + \Delta t) = u_{i,j}(t) + N_{i,j}(u_{i,j}(t), \Delta t))$ where $N_{i,j}$ is a the output of a convolutional neural network; this update equation is similar to eq. (9b) except with a discrete-time update instead of continuous-time ODE integration. [37] attempts to ensure stability by adding noise to the training distribution and by using very large timesteps. For scalar conservation form PDEs, this fully learned update equation will be stable if $\langle N \rangle = 0$ and $\langle u|N \rangle + \langle N|N \rangle \le 0$. [4] argues that instability in machine learned iterative numerical algorithms arises due to a *distribution shift* where the distribution of training data differs from the outputs of the solver during inference due to small errors that accumulate over time. [4] uses the update equation $u_{i,j}(t + \ell\Delta t) = u_{i,j}(t) + \ell\Delta t N_{i,j}^\ell$ for $1 \le \ell \le K$ where $N_{i,j}^\ell$ is the output of a message passing graph neural network that predicts the next K timesteps. [4] attempts to ensure stability by modifying the loss function, adding random noise, and by predicting multiple timesteps into the future. A variety of papers have attempted to promote stability of dynamical systems that result from data-driven reduced order models, including by adding sparsity-promoting priors to a loss function [20, 9] and by constraining the eigenvalues of a learned Koopman operator [31].

KEP schemes: Kinetic energy preserving (KEP) and entropy preserving (EP) schemes can be used in the numerical study of hyperbolic equations. Like global stabilization, KEP and EP schemes rely on the energy method for stability analysis and use summation by parts [18, 19, 6]. Unlike global stabilization, these schemes construct locally conservative algorithms which add just enough numerical damping at shocks to eliminate spurious oscillations.

8 Limitations

There are four main limitations of our work. First, we only consider rectangular grids, periodic boundary conditions, and *scalar* hyperbolic PDEs in conservation form. In particular, we do not consider *systems* of hyperbolic PDEs. Although many physically relevant equations can be written as scalar hyperbolic PDEs – including Hamiltonian systems, the incompressible Euler equations, and the Vlasov-Poisson equation – many more are systems of hyperbolic PDEs – including the compressible Euler equations, the magnetohydrodynamic (MHD) equations, the Einstein field equations, the shallow-water equations, the Navier-Stokes equations, and the Vlasov-Maxwell equations.

Fortunately, the energy method can be extended to non-periodic boundary conditions [8] and certain systems of PDEs [22, 19]. Furthermore, it is standard practice in the numerical methods community to first use the scalar conservation law eq. (1) to introduce a new method before later extending the method to systems of PDEs [7]. We anticipate that our method could be extended to many physically relevant systems of hyperbolic PDEs in a manner similar to KEP and EP schemes [18, 19].

Second, our method works with MOL in the continuous-time limit. The timestep Δt must be chosen to satisfy a CFL condition and be small enough to ensure accuracy of the ODE integration. Some machine learned solvers use large Δt or predict multiple timesteps at once or don't use MOL; algorithm 1 cannot be used to stabilize these solvers.

Third, while global stabilization is designed to solve the problem of ensuring stability of machine learned solvers for eq. (1) without degrading accuracy, it does not solve the problem of *finding* accurate machine learned solvers for eq. (1). Algorithm 1 prevents instability by adjusting the time-derivative if the solver makes an ℓ_2-norm increasing violation, but a solver which frequently commits such violations is likely to perform poorly. Alternatively, a solver could make no ℓ_2-norm increasing violations but decay the ℓ_2-norm too quickly. Or, it could decay the ℓ_2-norm at the correct rate but give inaccurate results. Building accurate, fast, and robust machine learned PDE solvers will require not only well-designed numerical methods but also well-engineered learning systems which consistently make accurate predictions about the time evolution of the solution.

Fourth, for some scalar hyperbolic PDEs a solver might be stable according to the definition in section 2 but not result in a physically meaningful solution as $t \to \infty$ unless additional physical constraints are satisfied. In appendix C, we give an example of this issue and illustrate how this forth limitation might be addressed by demonstrating that for some equations it may be possible to develop global stabilization schemes that enforce additional conservation laws.

9 Conclusion

Stability is a very desirable property of a PDE solver. Machine learned PDE solvers have tried a variety of techniques to encourage stability (see section 7). To some extent, these techniques have been successful, as high-performing solvers have demonstrated the ability to give stable and accurate predictions for hundreds or thousands of timesteps. However, none of these techniques are capable of *guaranteeing* stability.

In this paper, we show how to design machine learned PDE solvers for scalar hyperbolic PDEs that are stable by construction. The main result of our paper is the 'global stabilization' technique. This can be used as an error-correcting algorithm to guarantee both mass conservation and ℓ_2-norm stability of hybrid machine learned PDE solvers (see section 6), even when the time-derivative is an arbitrary function (see section 5).

As we have seen, it is impossible to design highly accurate numerical methods that inherit all of the properties of eq. (1); this is implied by Godunov's theorem (see section 3). We have also seen that it is often not even *desirable* for a numerical method to inherit the properties of the continuous equation, as doing so can significantly degrade the quality of the solution (see the discussion of backscattering in section 7 as well as appendices B and C). The lesson is that designers of numerical methods must determine which properties of the continuous system should be preserved by the discrete system and which properties either cannot be preserved or degrade the accuracy of the discrete system.

The whole point of the global stabilization technique is that it can be used to stabilize machine learned PDE solvers without degrading the accuracy of an already-accurate solver. This is possible because numerical diffusion is only added if the machine learned solver violates the non-increasing ℓ_2-norm property of the solution (see algorithm 1). A highly accurate machine learned solver is unlikely to frequently violate this property within its training distribution, but even if it does so the additional numerical diffusion is the minimum required to correct the violation. In other words, for a well-engineered machine learned PDE solver, we can expect the effects of global stabilization to be infrequent, small, and applied only when necessary.

We believe that for machine learned PDE solvers to have real-world impact, they must be sufficiently robust and reliable to be trusted. Stability is one critical feature of robust and reliable PDE solvers. We therefore believe that global stabilization is a step towards the development of machine learned PDE solvers which could have real-world impact.

References

[1] L. Agbezuge. Finite element solution of the poisson equation with dirichlet boundary conditions in a rectangular domain. *Rochester Institute of Technology, Rochester, NY*, 2006. 5

[2] Y. Bar-Sinai, S. Hoyer, J. Hickey, and M. P. Brenner. Learning data-driven discretizations for partial differential equations. *Proceedings of the National Academy of Sciences*, 116(31): 15344–15349, 2019. doi: 10.1073/pnas.1814058116. URL https://www.pnas.org/doi/abs/10.1073/pnas.1814058116. 1, 8

[3] A. Beck, D. Flad, and C.-D. Munz. Deep neural networks for data-driven les closure models. *Journal of Computational Physics*, 398:108910, 2019. ISSN 0021-9991. doi: https://doi.org/10.1016/j.jcp.2019.108910. URL https://www.sciencedirect.com/science/article/pii/S0021999119306151. 1, 8

[4] J. Brandstetter, D. Worrall, and M. Welling. Message passing neural pde solvers, 2022. URL https://arxiv.org/abs/2202.03376. 8

[5] C. Cercignani. The boltzmann equation. In *The Boltzmann equation and its applications*, pages 40–103. Springer, 1988. 14

[6] P. Chandrashekar. Kinetic energy preserving and entropy stable finite volume schemes for compressible euler and navier-stokes equations. *Communications in Computational Physics*, 14 (5):1252–1286, 2013. 8

[7] B. Cockburn and C.-W. Shu. Tvb runge-kutta local projection discontinuous galerkin finite element method for conservation laws. ii. general framework. *Mathematics of computation*, 52 (186):411–435, 1989. 9

[8] D. R. Durran. *Numerical methods for wave equations in geophysical fluid dynamics*. Texts in applied mathematics. Springer, New York, 1999. ISBN 0387983767. 3, 4, 9

[9] N. B. Erichson, M. Muehlebach, and M. W. Mahoney. Physics-informed autoencoders for lyapunov-stable fluid flow prediction, 2019. URL https://arxiv.org/abs/1905.10866. 8

[10] S. Godunov and I. Bohachevsky. Finite difference method for numerical computation of discontinuous solutions of the equations of fluid dynamics. *Matematičeskij sbornik*, 47(3): 271–306, 1959. 3

[11] A. N. Gorban. Basic types of coarse-graining. In *Model Reduction and Coarse-Graining Approaches for Multiscale Phenomena*, pages 117–176. Springer, 2006. 14

[12] S. Gottlieb. On high order strong stability preserving runge-kutta and multi step time discretizations. *Journal of scientific computing*, 25(1):105–128, 2005. 3

[13] S. Gottlieb, C.-W. Shu, and E. Tadmor. Strong stability-preserving high-order time discretization methods. *SIAM Review*, 43(1):89–112, 2001. doi: 10.1137/S003614450036757X. URL https://doi.org/10.1137/S003614450036757X. 3, 5

[14] D. Greenfeld, M. Galun, R. Basri, I. Yavneh, and R. Kimmel. Learning to optimize multigrid PDE solvers. In K. Chaudhuri and R. Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 2415–2423. PMLR, 09–15 Jun 2019. URL https://proceedings.mlr.press/v97/greenfeld19a.html. 1

[15] Y. Guan, A. Chattopadhyay, A. Subel, and P. Hassanzadeh. Stable a posteriori LES of 2d turbulence using convolutional neural networks: Backscattering analysis and generalization to higher re via transfer learning. *Journal of Computational Physics*, 458:111090, jun 2022. doi: 10.1016/j.jcp.2022.111090. URL https://doi.org/10.1016%2Fj.jcp.2022.111090. 8

[16] Y. Guan, A. Subel, A. Chattopadhyay, and P. Hassanzadeh. Learning physics-constrained subgrid-scale closures in the small-data regime for stable and accurate les, 2022. URL https://arxiv.org/abs/2201.07347. 8

[17] J.-T. Hsieh, S. Zhao, S. Eismann, L. Mirabella, and S. Ermon. Learning neural pde solvers with convergence guarantees, 2019. URL https://arxiv.org/abs/1906.01200. 1

[18] A. Jameson. The construction of discretely conservative finite volume schemes that also globally conserve energy or entropy. *Journal of Scientific Computing*, 34(2):152–187, 2008. 8, 9

[19] A. Jameson. Formulation of kinetic energy preserving conservative schemes for gas dynamics and direct numerical simulation of one-dimensional viscous compressible flow in a shock tube using entropy and kinetic energy preserving schemes. *Journal of Scientific Computing*, 34(2): 188–208, 2008. 3, 8, 9

[20] A. A. Kaptanoglu, J. L. Callaham, A. Aravkin, C. J. Hansen, and S. L. Brunton. Promoting global stability in data-driven models of quadratic nonlinear dynamics. *Physical Review Fluids*, 6(9), sep 2021. doi: 10.1103/physrevfluids.6.094401. URL https://doi.org/10.1103%2Fphysrevfluids.6.094401. 8

[21] D. Kochkov, J. A. Smith, A. Alieva, Q. Wang, M. P. Brenner, and S. Hoyer. Machine learning accelerated computational fluid dynamics. *Proceedings of the National Academy of Sciences*, 118(21):e2101784118, 2021. doi: 10.1073/pnas.2101784118. URL https://www.pnas.org/doi/abs/10.1073/pnas.2101784118. 1, 5, 8

[22] L. Lehner, D. Neilsen, O. Reula, and M. Tiglio. The discrete energy method in numerical relativity: towards long-term stability. *Classical and Quantum Gravity*, 21(24):5819, 2004. 3, 9

[23] Z. Li, N. Kovachki, K. Azizzadenesheli, B. Liu, K. Bhattacharya, A. Stuart, and A. Anandkumar. Fourier neural operator for parametric partial differential equations, 2020. URL https://arxiv.org/abs/2010.08895. 1

[24] B. List, L.-W. Chen, and N. Thuerey. Learned turbulence modelling with differentiable fluid solvers, 2022. URL https://arxiv.org/abs/2202.06988. 8

[25] I. Luz, M. Galun, H. Maron, R. Basri, and I. Yavneh. Learning algebraic multigrid using graph neural networks, 2020. URL https://arxiv.org/abs/2003.05744. 1

[26] L. G. Margolin and N. M. Lloyd-Ronning. Artificial viscosity – then and now, 2022. URL https://arxiv.org/abs/2202.11084. 4, 7

[27] R. Maulik, O. San, A. Rasheed, and P. Vedula. Subgrid modelling for two-dimensional turbulence using neural networks. *Journal of Fluid Mechanics*, 858:122–144, 2019. doi: 10.1017/jfm.2018.770. 8

[28] S. Mishra, U. Fjordholm, and R. Abgrall. Numerical methods for conservation laws and related equations. *Lecture notes for Numerical Methods for Partial Differential Equations, ETH*, 57:58, 2019. 1, 2, 3

[29] A. T. Mohan, N. Lubbers, D. Livescu, and M. Chertkov. Embedding hard physical constraints in neural network coarse-graining of 3d turbulence, 2020. URL https://arxiv.org/abs/2002.00021. 1

[30] N. Nguyen-Fotiadis, M. McKerns, and A. Sornborger. Machine learning changes the rules for flux limiters, 2021. URL https://arxiv.org/abs/2108.11864. 8

[31] S. Pan and K. Duraisamy. Physics-informed probabilistic learning of linear embeddings of nonlinear dynamics with guaranteed stability. *SIAM Journal on Applied Dynamical Systems*, 19(1):480–509, jan 2020. doi: 10.1137/19m1267246. URL https://doi.org/10.1137%2F19m1267246. 8

[32] J. Pathak, M. Mustafa, K. Kashinath, E. Motheau, T. Kurth, and M. Day. Using machine learning to augment coarse-grid computational fluid dynamics simulations, 2020. URL https://arxiv.org/abs/2010.00072. 8

[33] U. Piomelli, W. H. Cabot, P. Moin, and S. Lee. Subgrid-scale backscatter in turbulent and transitional flows. *Physics of Fluids A: Fluid Dynamics*, 3(7):1766–1771, 1991. doi: 10.1063/1.857956. URL https://doi.org/10.1063/1.857956. 8

[34] S. Premasuthan, C. Liang, and A. Jameson. Computation of flows with shocks using the spectral difference method with artificial viscosity, i: Basic formulation and application. *Computers & Fluids*, 98:111–121, 2014. ISSN 0045-7930. doi: https://doi.org/10.1016/j.compfluid.2013.12.013. URL `https://www.sciencedirect.com/science/article/pii/S0045793013004933`. 4

[35] T. G. Shepherd. Symmetries, conservation laws, and hamiltonian structure in geophysical fluid dynamics. In *Advances in Geophysics*, volume 32, pages 287–338. Elsevier, 1990. 5

[36] C.-W. Shu. Discontinuous galerkin methods: general approach and stability. *Numerical solutions of partial differential equations*, 201, 2009. 2

[37] K. Stachenfeld, D. B. Fielding, D. Kochkov, M. Cranmer, T. Pfaff, J. Godwin, C. Cui, S. Ho, P. Battaglia, and A. Sanchez-Gonzalez. Learned coarse models for efficient turbulence simulation, 2021. URL `https://arxiv.org/abs/2112.15275`. 1, 8

[38] P. K. Sweby. High resolution schemes using flux limiters for hyperbolic conservation laws. *SIAM Journal on Numerical Analysis*, 21(5):995–1011, 1984. doi: 10.1137/0721062. URL `https://doi.org/10.1137/0721062`. 5

[39] J. Tompson, K. Schlachter, P. Sprechmann, and K. Perlin. Accelerating eulerian fluid simulation with convolutional networks. In D. Precup and Y. W. Teh, editors, *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 3424–3433. PMLR, 06–11 Aug 2017. URL `https://proceedings.mlr.press/v70/tompson17a.html`. 1

[40] K. Um, R. Brand, Y. Fei, P. Holl, and N. Thuerey. Solver-in-the-loop: Learning from differentiable physics to interact with iterative pde-solvers, 2020. URL `https://arxiv.org/abs/2007.00016`. 1, 8

[41] B. van Leer. Towards the ultimate conservative difference scheme. v. a second-order sequel to godunov's method. *Journal of Computational Physics*, 32(1):101–136, 1979. ISSN 0021-9991. doi: https://doi.org/10.1016/0021-9991(79)90145-1. URL `https://www.sciencedirect.com/science/article/pii/0021999179901451`. 3, 5

[42] R. Wang, K. Kashinath, M. Mustafa, A. Albert, and R. Yu. Towards physics-informed deep learning for turbulent flow prediction, 2019. URL `https://arxiv.org/abs/1911.08655`. 1, 8

[43] J. Zhuang, D. Kochkov, Y. Bar-Sinai, M. P. Brenner, and S. Hoyer. Learned discretizations for passive scalar advection in a two-dimensional turbulent flow. *Phys. Rev. Fluids*, 6:064605, Jun 2021. doi: 10.1103/PhysRevFluids.6.064605. URL `https://link.aps.org/doi/10.1103/PhysRevFluids.6.064605`. 1, 8

A   Conservation Form PDEs with Nonzero Right Hand Side

Suppose we have the model equation $\partial u/\partial t + \boldsymbol{\nabla} \cdot \boldsymbol{f}(u) = D\boldsymbol{\nabla}^2 u + \boldsymbol{F}(\boldsymbol{x}, t)$ where $D \in \mathbb{R}$ is a non-negative diffusion coefficient and $\boldsymbol{F}(\boldsymbol{x}, t)$ is a forcing function. We can approximate the diffusion term using a standard approximation of the laplacian operator, we know that this can only decrease the ℓ_2-norm. Likewise, we can approximate the forcing term using a quadrature; this forcing term can contribute to *physical* instability but will not contribute to *numerical* instability. The only term which contributes to numerical instability is the divergence term; we can apply global stabilization to the approximation of this term.

B Enstrophy and Coarse Graining

The incompressible Euler equations in vorticity form exactly conserve the ℓ_2-norm of the solution, called the enstrophy. Naively, we might expect that a good PDE solver would conserve enstrophy as well. Yet algorithms that exactly conserve enstrophy on eq. (8), such as the centered flux (not shown) or the global stabilization flux with no damping (shown in fig. 2), perform significantly worse than schemes that allow enstrophy to decay.

To understand this puzzling result, we consider the relationship between the continuous enstrophy $\int \chi^2 \, dx \, dy$ and the discrete enstrophy $\sum_{i,j} \int \chi_{i,j}^2 \Delta x \Delta y$. Suppose that $\chi^{\text{exact}} = \chi(x, y, t)$ is the exact solution to eq. (8). As we know, χ^{exact} has constant enstrophy. Now suppose that we coarse grain χ^{exact}, such that $\chi_{i,j}^{\text{exact}} = \int_{i,j} \chi^{\text{exact}} \, dx \, dy$. It turns out that, with very high probability, the discrete enstrophy of $\chi_{i,j}^{\text{exact}}$ will decay in time [11]. This happens because χ^{exact} tends to develop structures on a scale smaller than the grid size. These structures cannot be represented by $\chi_{i,j}^{\text{exact}}$ and are replaced via coarse graining by a low-dimensional representation of the solution with lower enstrophy. The conclusion is as follows:

> Although the continuous equations for χ^{exact} maintain constant enstrophy, the discrete equations for $\chi_{i,j}^{\text{exact}}$ decay enstrophy.

Because machine learned PDE solvers solve discrete equations that are designed to approximate $\chi_{i,j}^{\text{exact}}$, then machine learned PDE solvers should inherit the properties of the discrete equations for $\chi_{i,j}^{\text{exact}}$, not the properties of the continuous equations for χ^{exact}. This means that solvers of eq. (1) should guarantee that enstrophy is non-increasing, not that enstrophy is constant.

C Energy-Conserving Global Stabilization

Consider the Boltzmann equation $\frac{\partial f}{\partial t} + \frac{\boldsymbol{p}}{m} \cdot \boldsymbol{\nabla} f = \left(\frac{\partial f}{\partial t}\right)_{\text{coll}}$ from kinetic physics which describes the evolution of the particle distribution function f in phase space $(\boldsymbol{x}, \boldsymbol{p})$ due to collisions with other particles [5]. Because f conserves particles $\int f \, d\boldsymbol{x} \, d\boldsymbol{p}$, momentum $\int f \boldsymbol{p} \, d\boldsymbol{x} \, d\boldsymbol{p}$, and energy $\frac{1}{2m} \int f \, \boldsymbol{p}^2 \, d\boldsymbol{x} \, d\boldsymbol{p}$ while maintaining $f \geq 0$ and increasing the entropy $-\int f \log f \, d\boldsymbol{x} \, d\boldsymbol{p}$, then as $t \to \infty$ f must evolve towards a Gaussian distribution. Yet if global stabilization were applied naively to a Boltzmann equation solver without preserving the right combination of these invariants, then f could evolve towards a flat distribution function or some other physically incorrect state. Thus, while global stabilization may be useful, it is not by itself always going to be sufficient to ensure that the solution evolves to the correct state as $t \to \infty$.

To demonstrate how additional conservation laws might be enforced, we again consider the incompressible euler equations in eq. (8) but now attempt to enforce an additional conservation law: conservation of energy. Recall that in fig. 2b, energy was not conserved by any of the schemes considered. Energy will be conserved if $\int \boldsymbol{u} \cdot \frac{\partial \boldsymbol{u}}{\partial t} \, dx \, dy = \int \psi \frac{\partial \chi}{\partial t} \, dx \, dy = \sum_{i,j} \bar{\psi}_{i,j} N_{i,j} \Delta x \Delta y = 0$ and is expressed most simply as $\langle \bar{\psi}_{i,j} | \boldsymbol{N}_{i,j} \rangle = 0$ where $\bar{\psi}_{i,j}$ is the cell average of ψ and $N_{i,j}$ is the time-derivative in the ith, jth cell. Conservation of mass, conservation of energy, and ℓ_2-stability will therefore all be guaranteed for eq. (8) if the following transformation is applied to $\boldsymbol{N}_{i,j}$:

$$\boldsymbol{U}_{i,j} = \boldsymbol{\chi} - \langle \boldsymbol{\chi}_{i,j} \rangle \qquad \boldsymbol{M}_{i,j} = \boldsymbol{N}_{i,j} - \langle \boldsymbol{N}_{i,j} \rangle \qquad \bar{\boldsymbol{\phi}}_{i,j} = \bar{\boldsymbol{\psi}}_{i,j} - \langle \bar{\boldsymbol{\psi}}_{i,j} \rangle$$

$$\boldsymbol{W}_{i,j} = \boldsymbol{U}_{i,j} - \frac{\langle \boldsymbol{U}_{i,j} | \bar{\boldsymbol{\phi}}_{i,j} \rangle}{\langle \bar{\boldsymbol{\phi}}_{i,j} | \bar{\boldsymbol{\phi}}_{i,j} \rangle} \bar{\boldsymbol{\phi}}_{i,j} \qquad \boldsymbol{P}_{i,j} = \boldsymbol{M}_{i,j} - \frac{\langle \boldsymbol{M}_{i,j} | \bar{\boldsymbol{\phi}}_{i,j} \rangle}{\langle \bar{\boldsymbol{\phi}}_{i,j} | \bar{\boldsymbol{\phi}}_{i,j} \rangle} \bar{\boldsymbol{\phi}}_{i,j}$$

$$\boldsymbol{N}_{i,j} \Rightarrow \left(1 + \frac{d\ell_2^{\text{new}}/dt}{\langle \boldsymbol{W}_{i,j} | \boldsymbol{P}_{i,j} \rangle}\right) \boldsymbol{P}_{i,j} - \frac{\langle \boldsymbol{W}_{i,j} | \boldsymbol{P}_{i,j} \rangle}{\langle \boldsymbol{W}_{i,j} | \boldsymbol{W}_{i,j} \rangle} \boldsymbol{W}_{i,j} \tag{11}$$

for any $d\ell_2^{\text{new}}/dt \leq 0$.

In fig. 3, we examine how the energy conserving global stabilization (GS EC) scheme in eq. (11) affects the baseline MUSCL scheme. The third column and fourth columns of fig. 3a set $d\ell_2^{\text{new}}/dt = 0$ (no damping) and $d\ell_2^{\text{new}}/dt = \langle \boldsymbol{\chi}_{i,j} | \boldsymbol{N}_{i,j} \rangle$ (normal damping). At small t the 'normal damping' solution has an large time-derivative, violating the CFL condition. This transient CFL violation causes an initial spike in enstrophy and energy in fig. 3b; afterwards the enstrophy decays and the energy is

(a) (b)

Figure 3: Global stabilization can be modified to enforce energy conservation as well as stability for the incompressible Euler equations. (a) Images of the vorticity χ at three different times. The first and second columns show the baseline MUSCL scheme at high and low resolution. The third and fourth columns show the baseline MUSCL scheme with energy conserving global stabilization (GS EC), either with no numerical damping or with the normal (baseline) rate of damping. (b) Energy, enstrophy, and vorticity correlation over time. For a brief period soon after $t = 0$ the CFL condition is violated for the 'normal damping' solution, causing a transient increase in enstrophy and energy.

conserved as eq. (11) would predict in the time-continuous limit. As we can see in both figs. 3a and 3b, the accuracy of the energy conserving global stabilization scheme is much worse than the standard MUSCL scheme.

Should energy be conserved by machine learned solvers of eq. (8)? Probably not, but it depends. Although χ^{exact} conserves energy exactly, and a high-resolution classical solver will either conserve the discrete energy exactly or decay the discrete energy slowly, it turns out that the discrete energy of $\chi_{i,j}^{\text{exact}}$ fluctuates around a fixed value, with the magnitude of the deviations depending on the coarse graining resolution. In other words, solvers of eq. (8) *must* violate energy conservation in order to predict $\chi_{i,j}^{\text{exact}}$ with perfect accuracy (see appendix B). In some cases energy conservation might increase the robustness of a machine learned solver, while in other cases enforcing energy conservation might too dramatically decrease the accuracy of a machine learned solver.