Understanding and Adopting Rational Behavior by Bellman Score Estimation

Abstract

We are interested in solving a class of problems that seek to understand and adopt rational behavior from demonstrations. We may broadly classify these problems into four categories of reward identification, counterfactual analysis, behavior imitation, and behavior transfer. In this work, we make a key observation that knowing how changes in the underlying rewards affect the optimal behavior allows one to solve a variety of aforementioned problems. To a local approximation, this quantity is precisely captured by what we term the *Bellman score*, i.e gradient of log probabilities of the optimal policy with respect to the reward. We introduce the Bellman score operator which provably converges to the gradient of the infinite-horizon optimal Q-values with respect to the reward which can then be used to directly estimate the score. Guided by our theory, we derive a practical *score-learning* algorithm which can be used for score estimation in high-dimensional state-actions spaces. We show that score-learning can be used to reliably identify rewards, perform counterfactual predictions, achieve state-of-the-art behavior imitation, and transfer policies across environments.

1 Introduction

A hallmark of intelligence is the ability to achieve goals with rational behavior. For sequential decision making problems, rational behavior is often formalized as a policy that is optimal with respect to a Markov Decision Process (MDP). In other words, intelligent agents are postulated to learn rational behavior for reaching goals by maximizing the reward of an underlying MDP (Doya, 2007; Neftci & Averbeck, 2019; Niv, 2009). The reward captures the goal while the remainder of the MDP characterizes the interplay between the agent's decisions and the environment.

In this work, we are interested in solving a class of problems that seek to understand and adopt rational (i.e optimal) behavior from demonstrations of sequential decisions. We may broadly classify them into categories of reward identification, counterfactual analysis, behavior imitation, and behavior transfer. These four problems of understanding and adopting rationality arise across a wide spectrum of science fields. For example, in econometrics, the field of Dynamic Discrete Choice (DDC) seeks algorithms for fitting reward functions to human decision making behavior observed in labor (Keane & Wolpin, 1994; 1997) or financial markets (Arcidiacono & Miller, 2011; Arcidiacono et al., 2016). The identified utilities are leveraged to garner deeper insight into people's decision strategies (Arcidiacono & Miller, 2020), make counterfactual predictions about how their choices will change in response to market interventions that alter the reward function (Keane & Wolpin, 1994; 1997), and train machine learning models that can make rational decisions like humans (Kalouptsidi et al., 2015; Christensen & Connault, 2019). In animal psychology and neuroscience, practitioners model the decision strategies of animals by fitting reward models to their observed behavior. The fitted reward is analyzed and then used to train AI models that simulate animal movements (Yamaguchi et al., 2018; Schafer et al., 2020) in order to gain a better understanding of ecologically and evolutionarily significant phenomena such as habitat selection and migration (Hirakawa et al., 2018). In robot learning, Inverse Reinforcement Learning (IRL) is used to infer reward functions from teleoperated robots and the learned rewards are fed through a RL algorithm to teach a robot how to perform the same task without human controls (Fu et al., 2017; Finn et al., 2016a; Chan & van der Schaar, 2021). As rewards for a task are often invariant to perturbations in the environment, (e.g walking can be described by the same reward function which encourages forward velocity and stability regardless of whether the agent is walking on ice or grass) the same task can be learned in various environmental conditions by optimizing the same inferred reward (Fu et al., 2017; Zhang et al., 2018).

We make a key observation that knowing how changes in the underlying rewards affect the optimal behavior (policy) allows one to solve a variety of aforementioned problems. To a local approximation, this quantity is precisely captured by what we term the *Bellman score*, i.e *gradient of log probabilities of the optimal policy with respect to the reward*. Prior works which study related quantities to the Bellman score are scarce and relied on having full-knowledge of the environment dynamics or small discrete state-action spaces (Neu & Szepesvári, 2012; Vroman, 2014; Li et al., 2017b). We introduce the Bellman score operator that provably converges to the gradient of the infinite-horizon optimal Q-values with respect to the reward. This Q-gradient can then be used to estimate the score. We further show that the Q-gradient is equivalent to the conditional state-action visitation counts under the optimal policy. These results allow us to derive, for the first time, the gradient of the Maximum Entropy IRL (Ziebart et al., 2008; Finn et al., 2016b; Fu et al., 2017) objective in the fully general setting with stochastic dynamics case and non-linear reward models. Guided by theory, we propose a powerful score-learning algorithm that can be used for model-free score estimation in continuous high-dimensional state-action spaces and an effective IRL algorithm, named Gradient Actor-Critic (GAC). Our experiments demonstrate that score-learning can be used to reliably identify rewards, make counterfactual predictions, imitate behaviors, and transfer policies across environments.

2 PRELIMINARIES

A Markov Decision Process (MDP) $\mathcal{M} \in \Omega$, where Ω is the set of all MDPs, is a tuple $\mathcal{M} = (\mathcal{X}, \mathcal{A}, P, P_0, r_\theta, \gamma)$ where $\mathcal{X}$ is the discrete state space, $\mathcal{A}$ is the discrete action (decision) space, $P \in \mathbb{R}^{|\mathcal{X} \times \mathcal{A}| \times |\mathcal{X}|}$ is the transition probability matrix, $P_0 \in \mathbb{R}^{|\mathcal{X}|}$ is the initial state distribution, $r_\theta \in \mathbb{R}^{|\mathcal{X} \times \mathcal{A}|}$ is the (stationary) parametric reward with parameters $\theta \in \Theta$, and $\gamma \in [0, 1]$ is the discount factor. Θ is the parameter space, typically set to a finite-dimensional real vector space $\mathbb{R}^{\dim(\theta)}$. We will use $T \geq 0$ to denote the time horizon for finite-horizon problems. A domain d is an MDP without the reward $\mathcal{M} \setminus r$. Moving forward we will alternate between vector and function notation, e.g $P(x'|x, a), r_\theta(x, a)$ denote the value of vector r_θ at the dimension for the state-action (x, a) and the value of matrix P at the location for $((x, a), x')$. Furthermore, one-dimensional vectors are treated as row vectors, e.g $\mathbb{R}^{|\mathcal{X} \times \mathcal{A}|} = \mathbb{R}^{1 \times |\mathcal{X} \times \mathcal{A}|}$. A (stationary) policy is a vector $\pi \in \mathbb{R}^{|\mathcal{X} \times \mathcal{A}|}$ that represents distributions over actions, i.e $\sum_{a \in \mathcal{A}} \pi(a|x) = 1$ for all x. A non-stationary policy for time horizon T is a sequence of policies $\tilde{\pi} = (\pi_t)_{t=0}^T \in (\mathbb{R}^{|\mathcal{X} \times \mathcal{A}|})^{T+1}$ where π_t is the policy used when there are t environment steps remaining[1] and $\tilde{\pi}_{:k} = (\pi_t)_{t=0}^k$ for $k \leq T$ denotes a subsequence. When there is no confusion we will use π to denote to both stationary and non-stationary policies. Next, $P_\pi \in \mathbb{R}^{|\mathcal{X} \times \mathcal{A}| \times |\mathcal{X} \times \mathcal{A}|}$ denotes the transition matrix of the Markov chain on state-action pairs induced by policy π, i.e $P_\pi(x', a'|x, a) = P(x'|x, a)\pi(a'|x')$. Furthermore, P_π^n denotes powers of the transition matrix with $P_\pi^0 = I$ where $I \in \mathbb{R}^{|\mathcal{X} \times \mathcal{A}| \times |\mathcal{X} \times \mathcal{A}|}$ is the identity. For non-stationary policies, we define $P_{\tilde{\pi}}^n = P_{\pi_{T-1}} P_{\pi_{T-2}} ... P_{\pi_{T-n}}$ for $n \geq 1$ and $P_{\tilde{\pi}}^0 = I$.

Let $\mathbb{1}_{x,a} \in \mathbb{R}^{|\mathcal{X} \times \mathcal{A}|}$ denote the indicator vector which has value 1 at the dimension corresponding to (x, a) and 0 elsewhere. The conditional marginal distribution for both stationary and non-stationary policy π after n environment steps is $p_{\pi,n}(\cdot|x, a) = \mathbb{1}_{x,a} P_\pi^n \in \mathbb{R}^{|\mathcal{X} \times \mathcal{A}|}$. The (unnormalized) t-step[2] conditional occupancy measure of π is the discounted sum of conditional marginals:

$$\mu_{\pi,t}(\cdot|x, a) = \sum_{n=0}^t \gamma^n p_{\pi,n}(\cdot|x, a) = \sum_{n=0}^t \gamma^n \mathbb{1}_{x,a} P_\pi^n \tag{1}$$

Intuitively, $\mu_{\pi,t}(x', a'|x, a)$ quantifies the visitation frequency for (x', a') when an agent starts from (x, a) and runs π for t environment steps, with more weight on earlier visits. The infinite horizon conditional occupancy exists for $\gamma < 1$ and we will denote it by simply omitting the subscript t, i.e $\mu_\pi(\cdot|x, a) = \lim_{t \to \infty} \mu_{\pi,t}(\cdot|x, a)$. The (unconditional) occupancy measure can be recovered by $\rho_{\pi,t}(x', a') = \sum_{x,a} P_0(x)\pi_T(a|x)\mu_{\pi,t}(x', a'|x, a)$. The t-step Q-values $Q_{\pi,t} \in \mathbb{R}^{|\mathcal{X} \times \mathcal{A}|}$ for both stationary and non-stationary policy π are defined as $Q_{\pi,t}(x, a) = \mathbb{E}_{x',a' \sim \mu_{\pi,t}(\cdot|x,a)}[r_\theta(x', a')] = \mu_{\pi,t}(\cdot|x, a) \cdot r$, i.e the conditional expectation of discounted reward sums when there are t environment steps remaining. The theory in this section will be derived in the Maximum Entropy RL (MaxEntRL) setting (Haarnoja et al., 2017; Kostrikov et al., 2020) but similar results for the vanilla RL setting without entropy regularization can be found in the Appendix. Let us define the t-step discounted conditional entropy of a policy as $\mathcal{H}_{\pi,t}(x, a) = -\sum_{n=1}^t \gamma^n p_{\pi,n}(\cdot|x, a) \cdot \log \pi_{T-n}$. In MaxEntRL,

---

[1] Backwards indexing is standard in dynamic programming RL algorithms (Bertsekas & Tsitsiklis, 1995)
[2] *Step* refers to the number of environment transitions and not the number of decisions made

the the soft Q-values are defined as $Q_{\pi,t}^{\mathrm{soft}}(x,a) = Q_{\pi,t}(x,a) + \mathcal{H}_{\pi,t}(x,a)$, i.e the conditional expectation of discounted reward and policy entropy sums. The theory in the remaining sections will be derived in the MaxEntRL setting for readability. Similar results for the standard RL setting without entropy regularization can be found in the Appendix.

For reward r_θ, let $Q_{\theta,t}^{\mathrm{soft}} \in \mathbb{R}^{|\mathcal{X} \times \mathcal{A}|}$ denote the t-step optimal Q-values defined iteratively by the soft Bellman optimality operator $\mathcal{T}_\mathcal{H} : \mathbb{R}^{|\mathcal{X} \times \mathcal{A}|} \to \mathbb{R}^{|\mathcal{X} \times \mathcal{A}|}$ as:

$$Q_{\theta,t}^{\mathrm{soft}}(x,a) = (\mathcal{T}_\mathcal{H} Q_{\theta,t-1}^{\mathrm{soft}})(x,a) = r_\theta(x,a) + \gamma \mathbb{E}_{x' \sim P(\cdot|x,a)}[\log \sum_{a' \in \mathcal{A}} \exp Q_{\theta,t-1}^{\mathrm{soft}}(x',a')] \quad (2)$$

for all $t > 0$ and $Q_{r,0}^{\mathrm{soft}} = r$. Hence the optimal Q-values for a decision problem with horizon t can be obtained by sequentially computing the optimal Q-values for $1, ..., t-1$ step decision problems using dynamic programming (Bertsekas & Tsitsiklis, 1995), i.e value iteration. The operator $\mathcal{T}_\mathcal{H}$ is a contraction in the max-norm (Bertsekas & Tsitsiklis, 1995) whose unique fixed point is the infinite-horizon optimal Q-values $Q_{\theta,\infty}^{\mathrm{soft}}$ satisfying $Q_{\theta,\infty}^{\mathrm{soft}} = \mathcal{T}_\mathcal{H} Q_{\theta,\infty}^{\mathrm{soft}}$. For finite horizon problems, the (non-stationary) optimal policy $\pi_\theta^{\mathrm{soft}} = (\pi_{\theta,t}^{\mathrm{soft}})_{t=0}^T$ is derived by $\pi_{\theta,t}^{\mathrm{soft}}(a|x) = \mathrm{softmax}(Q_{\theta,t}^{\mathrm{soft}})(x,a) = e^{Q_{\theta,t}^{\mathrm{soft}}(x,a)} / \sum_a e^{Q_{\theta,t}^{\mathrm{soft}}(x,a)}$ and, similarly, the infinite-horizon (stationary) optimal policy is $\pi_{\theta,\infty}^{\mathrm{soft}} = \mathrm{softmax}(Q_{\theta,\infty}^{\mathrm{soft}})$. We may now define the key quantity of interest, the *Bellman score*.

Definition 1 *The finite-horizon **Bellman score** $s_\theta^{\mathrm{soft}} \in (\mathbb{R}^{|\mathcal{X} \times \mathcal{A}| \times |\mathcal{X} \times \mathcal{A}|})^{T+1}$ is the gradient of the log probabilities of the (non-stationary) optimal policy with respect to the reward,*

$$s_\theta^{\mathrm{soft}} = (s_{\theta,t}^{\mathrm{soft}})_{t=0}^T = (\nabla_\theta \log \pi_{\theta,t}^{\mathrm{soft}})_{t=0}^T$$

Similarly the infinite-horizon Bellman score $s_{\theta,\infty}^{\mathrm{soft}} \in \mathbb{R}^{|\mathcal{X} \times \mathcal{A}| \times |\mathcal{X} \times \mathcal{A}|}$ is

$$s_{\theta,\infty}^{\mathrm{soft}} = \nabla_\theta \log \pi_{\theta,\infty}^{\mathrm{soft}}$$

In words, the finite-horizon score $s_{\theta,t}^{\mathrm{soft}}$ is the jacobian of the log optimal policy vector with respect to the reward parameters, i.e $s_{\theta,t}^{\mathrm{soft}}(x,a) = \nabla_\theta \log \pi_{\theta,t}^{\mathrm{soft}}(a|x)$ is the direction in which the reward parameters θ should perturbed in order to increase the log probability of action a at state x under the optimal policy for time t. To a local linear approximation around θ, the score conveys how the optimal behavior changes as a function of the underlying reward parameters. Next, we will prove useful properties of the score as well as derive a dynamic programming algorithm to compute it.

3 SCORE ITERATION

Since $\pi_{\theta,t}^{\mathrm{soft}}(a|x) = \mathrm{softmax}(Q_{\theta,t}^{\mathrm{soft}})(x,a)$, the Bellman score can be written as a difference of the gradients of optimal Q-values with respect to the reward parameters:

$$s_{\theta,t}^{\mathrm{soft}}(x,a) = \nabla_\theta \log \pi_{\theta,t}^{\mathrm{soft}}(a|x) = \nabla_\theta Q_{\theta,t}^{\mathrm{soft}}(x,a) - \mathbb{E}_{a' \sim \pi_{\theta,t}^{\mathrm{soft}}(\cdot|x)}[\nabla_\theta Q_{\theta,t}^{\mathrm{soft}}(x,a')] \quad (3)$$

We will refer to $\nabla_\theta Q_{\theta,t}^{\mathrm{soft}}$ as the Q-gradient or value gradient. Eq. 3 shows that an unbiased sample estimate of the score can be obtained from the Q-gradient and the optimal policy. Thus, we will derive a dynamic programming algorithm termed *score iteration* which efficiently computes the Q-gradients. Similar to how value iteration proceeds by repeated application of the Bellman optimality operator (Eq. 2), score iteration will rely on the Bellman score operator which we define now.

Definition 2 *The **Bellman score operator** $\mathcal{G}_{\pi,\theta} : \mathbb{R}^{|\mathcal{X} \times \mathcal{A}| \times \dim(\theta)} \to \mathbb{R}^{|\mathcal{X} \times \mathcal{A}| \times \dim(\theta)}$ for a policy π and reward r_θ is defined on an input $J \in \mathbb{R}^{|\mathcal{X} \times \mathcal{A}| \times \dim(\theta)}$ as*

$$\mathcal{G}_{\pi,\theta} J = \nabla_\theta r_\theta + \gamma P_\pi J$$

To gain intuition about the score operator, consider the tabular reward $r_\theta(x,a) = \theta(x,a)$ where $\theta \in \mathbb{R}^{|\mathcal{X} \times \mathcal{A}|}$. In this setting, the score operator simply computes the conditional occupancies for π (Eq. 1) when applied to the identity matrix I. For example, the values of $\mathcal{G}_{\pi,\theta} I = \nabla_\theta r_\theta + \gamma P_\pi I = I + \gamma P_\pi I$ at the row for state-action (x,a) is $\mathbb{1}_{x,a} + \gamma P_\pi(\cdot|x,a)$ which corresponds to the one-step conditional occupancy $\mu_{\pi,1}(\cdot|x,a)$. While the score operator has a pleasantly simple form, Theorem 1 will show that the Q-gradients can be computed by its repeated application and, as a result, that the Q-gradient is the conditional occupancy measure of the optimal policy for the underlying reward.

Algorithm 1 Score Iteration: Computes the infinite-horizon Bellman score via dynamic programming

$\mathcal{M} = (\mathcal{X}, \mathcal{A}, P, P_0, r_\theta, \gamma)$: Markov Decision Process
g: randomly initialized Q-gradient vector
procedure SCOREITERATION($\mathcal{M}$)
    For $\mathcal{M}$, learn the optimal policy $\pi_{\theta,\infty}^{\mathrm{soft}}$
    while g is not converged **do**
        for $x \in \mathcal{X}, a \in \mathcal{A}$ **do**
            Update Q-gradient: $g(x, a) \leftarrow \nabla_\theta r_\theta(x, a) + \gamma \sum_{x', a' \in \mathcal{X} \times \mathcal{A}} P_{\pi_{\theta,\infty}^{\mathrm{soft}}}(x', a'|x, a) g(x, a)$
    for $x \in \mathcal{X}, a \in \mathcal{A}$ **do**
        Compute Bellman score: $s(x, a) \leftarrow g(x, a) - \sum_{a' \in \mathcal{A}} \pi_{\theta,\infty}^{\mathrm{soft}}(a'|x) g(x, a')$
    return $\pi_{\theta,\infty}^{\mathrm{soft}}, g, s$

Theorem 1 *For all $t = 0, ..., T$, and for any matrix $J \in \mathbb{R}^{|\mathcal{X} \times \mathcal{A}| \times \dim(\theta)}$*

$$\nabla_\theta Q_{\theta,t}^{\mathrm{soft}} = \mathcal{G}_{\pi_{\theta,t}^{\mathrm{soft}}, \theta} ... \mathcal{G}_{\pi_{\theta,0}^{\mathrm{soft}}, \theta}(\nabla_\theta r_\theta)$$

$$\nabla_\theta Q_{\theta,\infty}^{\mathrm{soft}} = \mathcal{G}_{\pi_{\theta,\infty}^{\mathrm{soft}}, \theta}(\nabla_\theta Q_{\theta,\infty}^{\mathrm{soft}}) = \lim_{k \to \infty} \mathcal{G}_{\pi_{\theta,\infty}^{\mathrm{soft}}, \theta}^k J$$

Furthermore, the Q-gradient satisfies:

$$\nabla_\theta Q_{\theta,t}^{\mathrm{soft}}(x, a) = \mathbb{E}_{x', a' \sim \mu_{\pi_{\theta,:t}^{\mathrm{soft}}, t}(\cdot|x,a)}[\nabla_\theta r_\theta(x', a')]$$

$$\nabla_\theta Q_{\theta,\infty}^{\mathrm{soft}}(x, a) = \mathbb{E}_{x', a' \sim \mu_{\pi_{\theta,\infty}^{\mathrm{soft}}}(\cdot|x,a)}[\nabla_\theta r_\theta(x', a')]$$

Theorem 1 shows that both finite and infinite horizon Q-gradients can be computed by repeatedly applying the score operator of the current reward r_θ and its optimal policy $\pi_\theta^{\mathrm{soft}}, \pi_{\theta,\infty}^{\mathrm{soft}}$. Similar to how the Bellman optimality operator (Eq. 2) converges any starting vector in $\mathbb{R}^{|\mathcal{X} \times \mathcal{A}|}$ to the infinite-horizon optimal Q-values (Bertsekas & Tsitsiklis, 1995), the Bellman score operator converges any starting matrix in $\mathbb{R}^{|\mathcal{X} \times \mathcal{A}| \times \dim(\theta)}$ to the infinite-horizon Q-gradient.

Furthermore, we see that the Q-gradient is in fact the expected reward gradient under the conditional occupancy measure. To gain more intuition, once again consider the tabular reward $r_\theta(x, a) = \theta(x, a)$. Then, $\nabla_\theta Q_{\theta,t}^{\mathrm{soft}}(x, a) = \mathbb{E}_{x', a' \sim \mu_{\pi_{\theta,:t}^{\mathrm{soft}}, t}(\cdot|x,a)}[\mathbb{1}_{x',a'}] = \mu_{\pi_{\theta,:t}^{\mathrm{soft}}, t}$. We see that the Q-gradient is in fact equivalent to the conditional occupancy of the optimal policy, which is consistent with our previous analysis of the score operator. Thus, in order to increase the optimal Q-values at (x, a) the rewards of state-actions (x', a') should be increased proportional to their discounted visitation frequencies when starting from (x, a) and following the optimal policy. As an alternative to the operator perspective, one may consider a Linear Programming (LP) interpretation. The optimal Q-values are the solution to an LP optimization problem over the set of conditional occupancies D that are feasible under the Markovian environment dynamics, i.e $Q_{\theta,t}^{\mathrm{soft}}(x, a) = \max_{\mu \in D} r_\theta \cdot \mu$. Loosely speaking, invoking the supremum rule (Boyd et al., 2003) allows one to show that the gradient of the LP solution, i.e $\nabla_{r_\theta} \max_{\mu \in D} r_\theta \cdot \mu$, is in fact the conditional occupancy that solves the LP.

The main practical contribution of Theorem 1 is that the operator convergence results enable designing a powerful dynamic programming method for score computation as shown in Algorithm 1. (We omit the finite-horizon version for brevity, but it is very similar to the infinite-horizon case) The algorithm computes the optimal policy $\pi_{\theta,\infty}^{\mathrm{soft}}$, then proceeds by repeatedly applying the score operator $\mathcal{G}_{\pi_{\theta,\infty}^{\mathrm{soft}}, \theta}$. While highly effective in countable state-action spaces, score iteration has limited applicability to continuous state-action spaces and requires full knowledge of the environment dynamics. Similar to how Q-learning is a model-free instantiation of the value iteration algorithm, we will proceed to propose score-learning which is a model-free instantiation of the score iteration algorithm.

4 SCALING UP SCORE ESTIMATION

In order to scale score estimation to the model-free settings with (potentially) high-dimensional continuous state-action spaces, we start by parameterizing the policy, Q-gradient network, and score network as neural networks $\pi_\phi : \mathcal{X} \times \mathcal{A} \to \mathbb{R}$, $g_\psi : \mathcal{X} \times \mathcal{A} \to \mathbb{R}^{\dim(\theta)}$, and $s_\omega : \mathcal{X} \times \mathcal{A} \to \mathbb{R}^{\dim(\theta)}$. Just as Q-learning (Silver et al., 2016) approximates an application of the Bellman optimality operator by learning a Q-network that minimizes a boot-strapped regression loss, score-learning approximates an application of the score operator by learning a Q-gradient network that minimizes the boot-strapped

---

Algorithm 2 Score-learning: model-free instantiation of SCOREITERATION

$(\theta, \phi, \psi, \omega)$: Weights for reward, policy, Q-gradient, and score network
$\mathcal{B}$: Buffer of transitions (can be either online or offline data)
N, N_ψ: Total number of algorithm iterations, number of Q-gradient update steps per policy update
η_ψ, η_ω: Q-gradient learning rate, score-learning rate
α_g: Target Q-gradient mixing rate
RLSTEP: One policy update step in the inner loop of an RL algorithm, e.g one policy gradient step in
Soft-Actor Critic (Haarnoja et al., 2018).
procedure SCORELEARNING($\theta, \phi, \psi, \omega, \mathcal{B}, N$)
    for $i \in \{1, \ldots, N\}$ **do**
        # Update policy π_ϕ
        if ψ `is not None` **then**
            Update policy to maximize reward r_θ: $\phi \leftarrow$ RLSTEP($\theta, \phi, \mathcal{B}$)
        # Update Q-gradient g_ψ
        for $j \in \{1, \ldots, N_\psi\}$ **do**
            Sample batch: $(x, a, x') \sim \mathcal{B}$
            if ψ `is not None` **then**
                Sample next action from current policy: $a' \sim \pi_\phi(\cdot|x')$
            else
                Sample next action from buffer $a' \sim \mathcal{B}$
            Update Q-gradient (Eq. 4): $\psi \leftarrow \psi - \eta_\psi \nabla_\psi (\nabla_\theta r_\theta(x, a) + \gamma \bar{g}_\psi(x', a') - g_\psi(x, a))^2$
            Update Target Q-gradient $\bar{g}_\psi$ with soft mixing rate α_ψ (Haarnoja et al., 2017)
        # Update Bellman score s_ω
        Sample batch and contrastive action: $(x, a) \sim \mathcal{B}, a' \sim \pi_\phi(\cdot|x)$
        Update score network (Eq. 5): $\omega \leftarrow \omega - \eta_s \nabla_\omega (g_\psi(x, a) - g_\psi(x, a') - s_\omega(x, a))^2$
    return ϕ, ψ, ω

Algorithm 3 Gradient Actor-Critic (GAC): Inverse RL via Q-gradient Estimation

---

$(\theta, \phi, \psi_L, \psi_E)$: Weights for reward, policy, learner Q-gradient, and expert Q-gradient network
$\mathcal{D}$: Demonstrations of expert behavior
M: Total number GAC iterations
N, N_θ: Number of score iteration steps per GAC iteration, Reward update interval
η_r: Reward learning rate
procedure GAC($\theta, \phi, \bar{\phi}, \psi, \mathcal{D}$)
    for $i \in \{1, \ldots, M\}$ **do**
        Take step in environment with π_ϕ, add transition (x, a, s') to buffer $\mathcal{B}$
        Update learner Q-gradient and learner policy:
            $\phi, \psi_L \leftarrow$ SCORELEARNING($\theta, \phi, \psi_L, \mathcal{B}, N$)
        Update expert Q-gradient:
            $\psi_E \leftarrow$ SCORELEARNING(θ, ϕ=`None`$, \psi_E, \mathcal{D}, N$)
        if $i \mod N_\theta == 0$ **then**
            Sample expert batch of initial state-actions $(x_0, a_0) \sim \mathcal{D}_{\text{demo}}$
            Sample learner batch of initial state-actions $\tilde{x}_0 \sim \mathcal{B}, \tilde{a}_0 \sim \pi_\phi(\cdot|\tilde{x}_0)$
            Update reward with Q-gradient: $\theta \leftarrow \theta + \eta_r (g_\psi(x_0, a_0) - g_\psi(\tilde{x}_0, \tilde{a}_0))$
    return θ, ϕ

---

regression loss in Eq. 4. The score network then minimizes the regression loss in Eq. 5 which directly follows by replacing the Q-gradient with our estimate g_ψ in Eq. 3.

$$L_\psi = (\nabla_\theta r_\theta(x, a) + \gamma \mathbb{E}_{x', a' \sim P_{\pi_\phi}(\cdot|x,a)}[\bar{g}_\psi(x', a')] - g_\psi(x, a))^2 \tag{4}$$

$$L_\omega = (g_\psi(x, a) - \mathbb{E}_{a' \sim \pi_\phi(\cdot|x)}[g_\psi(x, a')] - s_\omega(x, a))^2 \tag{5}$$

Note that $\bar{g}_\psi$ is a target Q-gradient network used for stabilizing optimization analogous to target Q-networks that are used in Q-learning (Haarnoja et al., 2017). Algorithm 2 shows the full execution flow of score-learning. Instead of sequentially learning each model until convergence, score-learning alternates between making small improvements to the policy (red), regressing to the Q-gradient with the current estimate of the optimal policy (blue), and updating the score (yellow) with the current estimate of the Q-gradient. This enables the algorithm to output approximate estimates of all three components when run for a few-steps, which will be useful for downstream algorithms that use approximate score-learning in the inner-loop. If the buffer $\mathcal{B}$ already contains samples from the optimal policy, simply not passing ϕ disables policy updates. Note that score-learning can operate with both online and offline data $\mathcal{B}$ depending on the choice of the RL algorithm used to update the policy. We now show how the score-learning algorithm can be used for a variety of downstream tasks.

4.1 MAXIMUM ENTROPY INVERSE REINFORCEMENT LEARNING WITH SCORE-LEARNING

In this section we will show how score-learning can be used for maximum entropy inverse reinforcement learning (MaxEntIRL). Let $\tau = (x_0, a_0, ..., x_T, a_T)$ denote a trajectory of state-actions, and $p_\theta(\tau) = \log P_0(x_0) \prod_{t=0}^{T} \pi_{\theta,t}^{\text{soft}}(a_t|x_t) \prod_{t=0}^{T-1} P(x_{t+1}|x_t, a_t)$ denote the trajectory distribution of the MaxEnt optimal policy π_θ^{soft} for reward r_θ and similarly let $p^*(\tau)$ be the trajectory distribution of the expert policy $\pi^* = (\pi_t^*)_{t=0}^{T}$ from which the demonstrations $\mathcal{D}$ are sampled from. The goal in MaxEntIRL is to find reward parameters θ that maximize the log-likelihood of the expert trajectories:

$$\max_\theta \mathbb{E}_{\tau \sim p^*}[\log p_\theta(\tau)] \tag{6}$$

Gradients of the objective in Eq. 6 is highly useful as it enables direct gradient ascent to solve the maximization. Previously, the MaxEntIRL gradient has been derived in either the limited setting of deterministic dynamics (Ziebart et al., 2008) or in the general stochastic dynamics setting for the special case of linear reward models (Ziebart et al., 2010). Here, we leverage Theorem 1 to derive the fully general MaxEntIRL gradient in the stochastic dynamics setting with non-linear rewards.

Theorem 2 *The gradient of the MaxEntIRL objective is:*

$$\nabla_\theta \mathbb{E}_{\tau \sim p^*}[\log p_\theta(\tau)] = \mathbb{E}_{x \sim P_0, a \sim \pi_T^*(\cdot|x), a' \sim \pi_{\theta,T}^{\text{soft}}(\cdot|x)}[\nabla_\theta Q_{\pi^*,T}(x,a) - \nabla_\theta Q_{\theta,T}(x,a')] \tag{7}$$

$$= \mathbb{E}_{x,a \sim \rho_{\pi^*,T}}[\nabla_\theta r_\theta(x,a)] - \mathbb{E}_{x',a' \sim \rho_{\pi_\theta^{\text{soft}},T}}[\nabla_\theta r_\theta(x',a')] \tag{8}$$

Theorem 2 shows that the reward should be updated to increase the Q-values of the expert and decrease the optimal Q-values for the learner (Eq. 7) which is equivalent to increasing the reward on state-actions sampled from the expert and decreasing the reward of state-actions sampled from the learner (Eq. 8). With deterministic dynamics, Eq. 8 simply reduces to the known contrastive divergence gradient (Finn et al., 2016b) for energy-based models. When r_θ is linear, Eq. 8 reduces to the expected feature gap derived in Ziebart et al. (2010). (see Appendix for extended discussion)

Many prior works in MaxEntIRL (Finn et al., 2016b; Fu et al., 2017) take Monte Carlo samples to estimate Eq. 8 and perform stochastic gradient updates on θ. The key challenges with this approach are the difficulty of reusing old samples $(x, a) \sim \pi_{\theta_{\text{old}}}^{\text{soft}}$ from policies for older rewards θ_{old} and the high variance of the Monte Carlo estimator. *The main practical significance of Theorem 2 comes from Eq. 7 which reveals that we may instead learn Q-gradient networks with score-learning to approximate the expectations in Eq. 8.* At the cost of introducing bias to the gradient estimates, this approach resolves the two aforementioned challenges; score-learning works with offline data, which enables old sample reuse, and the Q-gradient network outputs the mean reward gradient, which reduces variance. We name our algorithm Gradient Actor-Critic (GAC) (see Algorithm 3) which uses score-learning to estimate the expert Q-gradient $\nabla_\theta Q_{\pi^*,T}(x,a)$ and learner Q-gradient $\nabla_\theta Q_{\theta,T}(x,a)$ with parametric functions g_{ψ_E} and g_{ψ_L}. To reduce computational cost, GAC alternates between approximate Q-gradient estimation, i.e running score-learning for N steps, and using the rough gradients for reward updates. Our method is analogous to actor-critic methods (Haarnoja et al., 2017) that learn a Q-network to estimate mean policy returns which are then used for policy gradient updates. These methods similarly introduce bias into the policy gradients in exchange for the ability to reuse old policy data and perform lower variance gradient updates. Just as how actor-critic typically outperforms Monte-Carlo policy gradient methods, our experiments will demonstrate a similar usefulness in trading off bias for lower variance.

4.2 COUNTERFACTUAL PREDICTIONS WITH SCORE-LEARNING

Here we describe how score-learning can be used for counterfactual predictions. The goal is to predict how the optimal policy changes when the original reward r_θ is perturbed to a counterfactual reward $r_{\theta'}$. When one has access to an efficient environment simulator, one natural solution is to simply solve the RL problem for the new reward $r_{\theta'}$. However, this is difficult in many domains where solving the forward RL problem is computationally expensive, particularly when we wish to make many counterfacutal predictions for multiple reward alterations. Instead, we may use the score $s_{\theta,\infty}^{\text{soft}}$ for the original reward r_θ to estimate of the optimal policy at the new reward $r_{\theta'}$ by simply using the first order taylor approximation of the log optimal policy:

$$\log \pi_{\theta',\infty}^{\text{soft}}(x,a) \approx \log \pi_{\theta,\infty}^{\text{soft}}(x,a) + s_{\theta,\infty}^{\text{soft}}(x,a) \cdot (\theta' - \theta) \tag{9}$$

Eq. 9 shows that $\log \pi_{\theta',\infty}^{\text{soft}}(a|x)$ increases proportional to how well the direction of change in reward $(\theta' - \theta)$ aligns with the score $s_\theta(x,a)$. We use Algorithm 2 to estimate s_θ with g_ψ and apply Eq. 9.

Figure 1: **Counterfactual Prediction Performance** for two scenarios: education subsidy (top row) and military enrollment incentives (bottom row). "no sub" corresponds to the initial reward from which the scores are estimated, "true sub" shows the probability of actions under the MaxEnt optimal policy obtained by resolving the RL model for perturbed rewards, and "pred sub" shows the score-estimated optimal policy probabilities. $2000, 8000$ denote the magnitude of the perturbation to the reward parameters which corresponds to the amount of subsidy or incentives.

5 EXPERIMENTS

5.1 REWARD IDENTIFICATION AND COUNTERFACTUAL PREDICTIONS

Environment: We experiment with the Keane and Wolpin (KW) environment (Keane & Wolpin, 1994; 1997) which is a widely used benchmark in the DDC literature. The KW environment simulates a life-time of occupational decisions where at each time-step an agent selects among five actions: white collar work, blue collar work, military, school, and staying home. The state is a 25 dimensional vector consisting of various features about the agent such as the time spent in each occupation, and their current job. The dynamics captures how their current job decision alters the state. Agents are required to be forward looking and maximize the rewards summed over a life-time of occupational choices. The reward parameter θ is a 63 dimensional vector where each parameter dimension corresponds to either a cost or benefit, e.g the cost of attending college or the benefit of transitioning from a white collar job to the military. The specific structure of the reward is omitted for brevity, but full details about the environment can be found in (Keane & Wolpin, 1994; 1997).

Results: We solve the forward MaxEntRL problem in the KW environment and use the optimal policy to generate 100 trajectories of occupational choices for two different reward parameters: θ_{edu} and θ_{mil}. The first reward simulates a scenario with lower education costs and the latter captures a scenario with high benefits for military enrollment (Keane & Wolpin, 1994; 1997).

Table 1: **Reward Identification on KW dataset.** Mean squared error between true reward and IRL estimated reward evaluated on the demonstrations.

	GCL	MSM	GAC
θ_{edu}	12.1 ± 5.3	0.14 ± 0.4	0.16 ± 0.3
θ_{mil}	20.5 ± 6.8	0.14 ± 0.3	0.08 ± 0.2

We test the reward identification performance by computing the mean squared error between the ground truth reward $r_{\theta_{edu}}, r_{\theta_{mil}}$ and the estimated rewards on $r_{\hat{\theta}_{edu}}, r_{\hat{\theta}_{mil}}$ evaluated on the demonstrations. As rewards are only identifiable up to additive constant shifts (Kim et al., 2021), we search this equivalence class for the parameters that minimize the mean squared error. Table 1 shows that GAC is able to identify the rewards to similar precision as the Method of Simulated Moments (MSM) baseline which is the state-of-the-art method for identification in the DDC literature.

Next we test the counterfactual prediction performance using the method in section 4.2. We simulate two counterfactual scenarios where the government provides a subsidy for college tuition and military participation. The scenarios are simulated by reducing the cost parameters in the reward for attending college and joining the military. Figure 1 shows how our score-estimated counterfactual predictions of policy changes compare to fully re-solving the RL problem for the perturbed rewards. We are able to accurately estimate the increase in time spent in school and the military. Particularly, when the reward perturbations are smaller, the score-based counterfactual predictions are more accurate.

Table 2: **State Control Performance** when provided with *one* demonstration.

	BC	DAC	AIRL	GCL	GAC (OURS)
BALL IN CUP CATCH	39.2 ± 15.2	291.9 ± 29.1	124.3 ± 25.0	502.2 ± 104.2	949.9 ± 42.4
CARTPOLE SWING-UP	106.0 ± 50.1	709.0 ± 40.9	591.4 ± 134.2	320.1 ± 105.8	970.1 ± 26.1
FINGER SPIN	159.1 ± 60.1	203.5 ± 91.9	105.0 ± 22.8	304.1 ± 50.6	984.0 ± 18.4
FISH SWIM	205.9 ± 49.2	150.5 ± 10.8	10.5 ± 85.1	203.0 ± 89.4	946.8 ± 22.5
HOPPER STAND	10.6 ± 50.2	809.1 ± 98.4	592.2 ± 101.2	900.1 ± 150.2	917.1 ± 15.9
WALKER STAND	143.5 ± 22.8	406.5 ± 89.5	739.6 ± 63.5	194.4 ± 39.5	990.0 ± 49.0
WALKER WALK	40.1 ± 39.1	125.9 ± 78.1	495.1 ± 77.2	102.4 ± 30.0	943.1 ± 56.7
CHEETAH RUN	230.1 ± 99.8	206.10 ± 75.1	102.4 ± 29.5	169.1 ± 20.3	989.7 ± 17.5
QUADRUPED RUN	10.45 ± 91.9	316.3 ± 33.6	195.4 ± 91.5	33.5 ± 98.2	961.3 ± 50.1

Figure 2: **Visual Control Performance** when a varying number of demonstrations.

5.2 BEHAVIOR IMITATION

Environment and Baselines: We experiment with high-dimensional robotics control environments from the DeepMind Control Suite (DMC) (Tassa et al., 2018), which is a widely used benchmark for RL and Imitation Learning (IL). For state control problems the agent has access to its proprioceptive states. For visual control the agent sees three consecutive observation images of size $84 \times 84 \times 3$ and uses action-repeat following the standard DMC protocol for visual RL (Yarats et al., 2021). We compare GAC against Behavioral Cloning (BC) (Pomerleau, 1991), Adversarial IRL (AIRL) (Fu et al., 2017), Guided Cost Learning (GCL) (Finn et al., 2016b), and Discriminator Actor-Critic (DAC) (Kostrikov et al., 2018; Cohen et al., 2021). We report the mean performance and standard deviation across ten random seeds where performance of each seed is measured as the mean reward of twenty trajectories sampled from the final policy. (see Appendix B for experiment details)

Results: For state control, we experiment in the extreme low-data regime where only one demonstration trajectory (consisting of 1000 state-actions) is provided. The experts for all tasks obtain rewards near 1000. Table 2 shows that GAC outperforms all baselines while achieving expert level performance. In particular, we found that the IRL methods are incapable of performing well in the low-data regime. These results suggest that trading off bias for lower variance is beneficial in practice. While DAC achieve competitive performance on some tasks such as HOPPER STAND, it does not have the benefit of learning a reward. For visual control, Figure 2 shows that GAC outperforms baselines while achieving expert performance on many hard visual control tasks with just one demonstration. We found that it was crucial to share the reward encoder with the Q-gradient network which outperformed sharing the RL encoder as done for P-DAC (Cohen et al., 2021). Hyperparameter ablation studies as well as compute time comparisons are in Appendix C.

5.3 BEHAVIOR TRANSFER

Next we show that that learned rewards from GAC robustly transfer behaviors to perturbed environments (Fu et al., 2017). We create variations of the state-based DMC environments by altering the surface and joint frictions to simulate realistic scenarios for robot learning where we may want to learn a single reward that can teach robots of different joint mechanics to mobilize in different walking

Table 3: **Reward Transfer** when provided with *ten* demonstrations in the original environment

	DIRECT	AIRL	GCL	GAC (OURS)
SLIPPERY WALKER	302.5 ± 29.5	493.2 ± 49.3	201.9 ± 89.6	789.3 ± 93.3
STIFF WALKER	205.2 ± 98.3	455.2 ± 99.3	301.3 ± 89.4	668.9 ± 60.2
SLIPPERY CHEETAH	366.5 ± 29.3	591.9 ± 65.7	93.1 ± 60.1	803.9 ± 98.9
STIFF CHEETAH	363.2 ± 39.6	430.3 ± 68.2	325.0 ± 44.6	650.3 ± 92.3

surfaces. For example, the SLIPPERYWALKER environment has about 80% less friction on the walking surface while STIFFCHEETAH has roughly 150% higher friction on the robot joints. Rewards are first learned on the non-perturbed environments using 10 demonstrations, then re-optimized via RL on the perturbed environments. As a sanity check, we also include the DIRECT baseline which simply uses policy learned in the non-perturbed environment. Table 3 shows that GAC is able to outperform the baselines while achieving near expert performance.

6 RELATED WORKS

Inverse Reinforcement Learning and Dynamic Discrete Choice: The field of IRL was pioneered by (Ng et al., 2000) and has since accumulated a rich history starting with early works that rely on linear reward models and hand-crafted features (Abbeel & Ng, 2004; Ramachandran & Amir, 2007; Choi & Kim, 2011; Neu & Szepesvári, 2012). Since the introduction of the Maximum Entropy IRL (Ziebart et al., 2008; 2010) framework, the field has gravitated towards learning more flexible rewards parameterized by deep neural networks (Wulfmeier et al., 2015) paired with adversarial training (Fu et al., 2017; Ho & Ermon, 2016; Finn et al., 2016b;a) while some works attempt scale more classical methods such as Bayesian IRL (Chan & van der Schaar, 2021; Mandyam et al., 2021). Most related to our work is gradient-based apprenticeship learning (Neu & Szepesvári, 2012) which showed that the gradient of the infinite horizon Q-function in the standard RL setting satisfies a linear fixed point equation. Bellman gradient iteration (Li et al., 2017b;a) and maximum-likelihood IRL (Vroman, 2014) take a computational approach to estimating approximate Q-gradients. Unlike these prior works, we generalize results to the MaxEntRL setting where we prove new properties of the Bellman score, and derive a dynamic programming algorithm that provably converges to the infinite-horizon Q-gradient. Most significantly, we propose a model-free score estimation algorithm which scales to high-dimensional environments and apply it to various applications beyond IRL.

The field of econometrics has a rich body of work on identifying Dynamic Discrete Choice (DDC) (Rust, 1994; Arcidiacono & Miller, 2011; 2020; Abbring & Daljord, 2020) models which is equivalent to the problem of MaxEntIRL (Ziebart et al., 2008; 2010). DDC literature more so focuses on counter factual predictions (Kalouptsidi et al., 2015; Christensen & Connault, 2019; Keane & Wolpin, 1994; 1997) which has various application areas such as in labor markets (Keane & Wolpin, 1994; 1997), health care (Heckman & Navarro, 2007), and retail competition (Arcidiacono & Miller, 2011). **Imitation Learning** A related field of Imitation Learning (IL) seeks to directly learn policies from demonstrations (Pomerleau, 1991; Ho & Ermon, 2016; Kostrikov et al., 2019; Kim et al., 2020) which is a viable alternative when the sole goal is behavior adoption. In recent years, IL has shown superior results than IRL for policy performance particular in the visual IL space. (Samak et al., 2020; Young et al., 2020; Pari et al., 2021; Cohen et al., 2021; Cheng et al., 2021) In particular, techniques such as data augmentation, and encoder sharing that have boosted performance in visual RL (Laskin et al., 2020; Kostrikov et al., 2020; Yarats et al., 2021) has been combined with adversarial imitation learning methods to solve challenging control environments (Cohen et al., 2021; Cheng et al., 2021; Chan & van der Schaar, 2021).

7 CONCLUSION

We have studied the theoretical properties of the Bellman score which allowed us to derive a model-free algorithm, score-learning, for score-estimation. We showed that score-learning has various applications in IRL, behavior transfer, reward identification, and counterfactual analysis. We are looking forward to seeing future works that apply score-learning to other problems such as reward design (Hadfield-Menell et al., 2017) and explainable RL (Puiutta & Veith, 2020).

REFERENCES

Pieter Abbeel and Andrew Y Ng. Apprenticeship learning via inverse reinforcement learning. In *Proceedings of the twenty-first international conference on Machine learning*, pp. 1, 2004.

Jaap H Abbring and Øystein Daljord. Identifying the discount factor in dynamic discrete choice models. *Quantitative Economics*, 11(2):471–501, 2020.

Peter Arcidiacono and Robert A Miller. Conditional choice probability estimation of dynamic discrete choice models with unobserved heterogeneity. *Econometrica*, 79(6):1823–1867, 2011.

Peter Arcidiacono and Robert A Miller. Identifying dynamic discrete choice models off short panels. *Journal of Econometrics*, 215(2):473–485, 2020.

Peter Arcidiacono, Patrick Bayer, Jason R Blevins, and Paul B Ellickson. Estimation of dynamic discrete choice models in continuous time with an application to retail competition. *The Review of Economic Studies*, 83(3):889–931, 2016.

Shaojie Bai, J Zico Kolter, and Vladlen Koltun. Deep equilibrium models. *Advances in Neural Information Processing Systems*, 32, 2019.

Dimitri P Bertsekas and John N Tsitsiklis. Neuro-dynamic programming: an overview. In *Proceedings of 1995 34th IEEE conference on decision and control*, volume 1, pp. 560–564. IEEE, 1995.

Stephen Boyd, Lin Xiao, and Almir Mutapcic. Subgradient methods. *lecture notes of EE392o, Stanford University, Autumn Quarter*, 2004:2004–2005, 2003.

Alex J Chan and Mihaela van der Schaar. Scalable bayesian inverse reinforcement learning. *arXiv preprint arXiv:2102.06483*, 2021.

Zhihao Cheng, Li Shen, and Dacheng Tao. Off-policy imitation learning from visual inputs. *arXiv preprint arXiv:2111.04345*, 2021.

Jaedeug Choi and Kee-Eung Kim. Map inference for bayesian inverse reinforcement learning. *Advances in Neural Information Processing Systems*, 24, 2011.

Timothy Christensen and Benjamin Connault. Counterfactual sensitivity and robustness. *arXiv preprint arXiv:1904.00989*, 2019.

Samuel Cohen, Brandon Amos, Marc Peter Deisenroth, Mikael Henaff, Eugene Vinitsky, and Denis Yarats. Imitation learning from pixel observations for continuous control. In *Deep RL Workshop NeurIPS 2021*, 2021.

Kenji Doya. Reinforcement learning: Computational theory and biological mechanisms. *HFSP journal*, 1(1):30, 2007.

Chelsea Finn, Paul Christiano, Pieter Abbeel, and Sergey Levine. A connection between generative adversarial networks, inverse reinforcement learning, and energy-based models. *arXiv preprint arXiv:1611.03852*, 2016a.

Chelsea Finn, Sergey Levine, and Pieter Abbeel. Guided cost learning: Deep inverse optimal control via policy optimization. In *International Conference on Machine Learning*, pp. 49–58, June 2016b.

Justin Fu, Katie Luo, and Sergey Levine. Learning robust rewards with adversarial inverse reinforcement learning. *arXiv preprint arXiv:1710.11248*, 2017.

Tuomas Haarnoja, Haoran Tang, Pieter Abbeel, and Sergey Levine. Reinforcement learning with deep energy-based policies. *arXiv preprint arXiv:1702.08165*, 2017.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft Actor-Critic: Off-Policy maximum entropy deep reinforcement learning with a stochastic actor. *arXiv preprint arXiv:1801.01290*, January 2018.

Dylan Hadfield-Menell, Smitha Milli, Pieter Abbeel, Stuart J Russell, and Anca Dragan. Inverse reward design. *Advances in neural information processing systems*, 30, 2017.

James J Heckman and Salvador Navarro. Dynamic discrete choice and dynamic treatment effects. *Journal of Econometrics*, 136(2):341–396, 2007.

Tsubasa Hirakawa, Takayoshi Yamashita, Toru Tamaki, Hironobu Fujiyoshi, Yuta Umezu, Ichiro Takeuchi, Sakiko Matsumoto, and Ken Yoda. Can ai predict animal movements? filling gaps in animal trajectories using inverse reinforcement learning. *Ecosphere*, 9(10):e02447, 2018.

Jonathan Ho and Stefano Ermon. Generative adversarial imitation learning. In *Advances in Neural Information Processing Systems*, pp. 4565–4573, 2016.

Myrto Kalouptsidi, Paul T Scott, and Eduardo Souza-Rodrigues. Identification of counterfactuals in dynamic discrete choice models. Technical report, National Bureau of Economic Research, 2015.

Michael P Keane and Kenneth I Wolpin. The solution and estimation of discrete choice dynamic programming models by simulation and interpolation: Monte carlo evidence. *The review of economics and statistics*, pp. 648–672, 1994.

Michael P Keane and Kenneth I Wolpin. The career decisions of young men. *Journal of political Economy*, 105(3):473–522, 1997.

Kuno Kim, Yihong Gu, Jiaming Song, Shengjia Zhao, and Stefano Ermon. Domain adaptive imitation learning. In *International Conference on Machine Learning*, pp. 5286–5295. PMLR, 2020.

Kuno Kim, Shivam Garg, Kirankumar Shiragur, and Stefano Ermon. Reward identification in inverse reinforcement learning. In *International Conference on Machine Learning*, pp. 5496–5505. PMLR, 2021.

Ilya Kostrikov, Kumar Krishna Agrawal, Debidatta Dwibedi, Sergey Levine, and Jonathan Tompson. Discriminator-actor-critic: Addressing sample inefficiency and reward bias in adversarial imitation learning. *arXiv preprint arXiv:1809.02925*, 2018.

Ilya Kostrikov, Ofir Nachum, and Jonathan Tompson. Imitation learning via off-policy distribution matching. *arXiv preprint arXiv:1912.05032*, 2019.

Ilya Kostrikov, Denis Yarats, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. *arXiv preprint arXiv:2004.13649*, 2020.

Misha Laskin, Kimin Lee, Adam Stooke, Lerrel Pinto, Pieter Abbeel, and Aravind Srinivas. Reinforcement learning with augmented data. *Advances in Neural Information Processing Systems*, 33: 19884–19895, 2020.

Bai Li, Changyou Chen, Hao Liu, and Lawrence Carin. On connecting stochastic gradient MCMC and differential privacy. *arXiv preprint arXiv:1712.09097*, December 2017a.

Kun Li, Yanan Sui, and Joel W Burdick. Bellman gradient iteration for inverse reinforcement learning. *arXiv preprint arXiv:1707.07767*, 2017b.

Aishwarya Mandyam, Didong Li, Diana Cai, Andrew Jones, and Barbara Engelhardt. Efficient bayesian inverse reinforcement learning via conditional kernel density estimation. In *Fourth Symposium on Advances in Approximate Bayesian Inference*, 2021.

Emre O Neftci and Bruno B Averbeck. Reinforcement learning in artificial and biological systems. *Nature Machine Intelligence*, 1(3):133–143, 2019.

Gergely Neu and Csaba Szepesvári. Apprenticeship learning using inverse reinforcement learning and gradient methods. *arXiv preprint arXiv:1206.5264*, 2012.

Andrew Y Ng, Stuart J Russell, et al. Algorithms for inverse reinforcement learning. In *Icml*, pp. 663–670, 2000.

Yael Niv. Reinforcement learning in the brain. *Journal of Mathematical Psychology*, 53(3):139–154, 2009.

Jyothish Pari, Nur Muhammad, Sridhar Pandian Arunachalam, Lerrel Pinto, et al. The surprising effectiveness of representation learning for visual imitation. *arXiv preprint arXiv:2112.01511*, 2021.

Dean A Pomerleau. Efficient training of artificial neural networks for autonomous navigation. *Neural computation*, 3(1):88–97, 1991. ISSN 0899-7667.

Erika Puiutta and Eric Veith. Explainable reinforcement learning: A survey. In *International cross-domain conference for machine learning and knowledge extraction*, pp. 77–95. Springer, 2020.

Deepak Ramachandran and Eyal Amir. Bayesian inverse reinforcement learning. In *IJCAI*, volume 7, pp. 2586–2591, 2007.

John Rust. Structural estimation of markov decision processes. *Handbook of econometrics*, 4: 3081–3143, 1994.

Tanmay Vilas Samak, Chinmay Vilas Samak, and Sivanathan Kandhasamy. Robust behavioral cloning for autonomous vehicles using end-to-end imitation learning. *arXiv preprint arXiv:2010.04767*, 2020.

Toryn LJ Schafer, Christopher K Wikle, and Mevin B Hooten. Bayesian inverse reinforcement learning for collective animal movement. *arXiv preprint arXiv:2009.04003*, 2020.

David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of go with deep neural networks and tree search. *nature*, 529(7587):484, 2016.

Yuval Tassa, Yotam Doron, Alistair Muldal, Tom Erez, Yazhe Li, Diego de Las Casas, David Budden, Abbas Abdolmaleki, Josh Merel, Andrew Lefrancq, Timothy Lillicrap, and Martin Riedmiller. DeepMind control suite. *arXiv preprint arXiv:1801.00690*, January 2018.

Monica C Vroman. *Maximum likelihood inverse reinforcement learning*. Rutgers The State University of New Jersey-New Brunswick, 2014.

Markus Wulfmeier, Peter Ondruska, and Ingmar Posner. Maximum entropy deep inverse reinforcement learning. *arXiv preprint arXiv:1507.04888*, July 2015.

Shoichiro Yamaguchi, Honda Naoki, Muneki Ikeda, Yuki Tsukada, Shunji Nakano, Ikue Mori, and Shin Ishii. Identification of animal behavioral strategies by inverse reinforcement learning. *PLoS computational biology*, 14(5):e1006122, 2018.

Denis Yarats and Ilya Kostrikov. Soft actor-critic (sac) implementation in pytorch. https://github.com/denisyarats/pytorch_sac, 2020.

Denis Yarats, Rob Fergus, Alessandro Lazaric, and Lerrel Pinto. Mastering visual continuous control: Improved data-augmented reinforcement learning. *arXiv preprint arXiv:2107.09645*, 2021.

Sarah Young, Dhiraj Gandhi, Shubham Tulsiani, Abhinav Gupta, Pieter Abbeel, and Lerrel Pinto. Visual imitation made easy. *arXiv preprint arXiv:2008.04899*, 2020.

Amy Zhang, Harsh Satija, and Joelle Pineau. Decoupling dynamics and reward for transfer learning. *arXiv preprint arXiv:1804.10689*, 2018.

Brian D Ziebart, Andrew L Maas, J Andrew Bagnell, and Anind K Dey. Maximum entropy inverse reinforcement learning. In *AAAI*, volume 8, pp. 1433–1438, 2008.

Brian D Ziebart, J Andrew Bagnell, and Anind K Dey. Modeling interaction via the principle of maximum causal entropy. In *ICML*, 2010.