CONTINUAL VISION-LANGUAGE REPRESENTAION LEARNING WITH OFF-DIAGONAL INFORMATION

ABSTRACT

Multimodal pre-trained methods with a contrastive learning framework (like CLIP) have recently achieved consistent advantages on various cross-model downstream tasks. However, they usually require a large amount of image-text samples and a vast computing budget for training, which makes the re-training process expensive while the training data is collected continuously (the phenomenon is widespread in real scenarios). In this paper, we discuss the feasibility of continuously training CLIP models based on discrete streaming data. We find that the multimodal retrieval performance of the CLIP in a continual training setting is significantly lower than that in a joint training setting. We name this phenomenon **Cognitive Disorder(CD)**. By tracking the directional changes of the representation vectors in the continuously updated CLIP model, we explore and summarize the spatial variation of the modal encoders within the CLIP: **Intra-modal Rotation** and **Inter-modal Deviation**. Intra-modal Rotation means that the vision and language representation space in the CLIP is rotating greatly around the center of a high-dimensional unit sphere during continual training, accompanied by a relatively small change in the topology of the representation space. Inter-modal deviation happens when the vision and language's intra-modal rotation is unsynchronized. Moreover, we empirically and theoretically demonstrate how intra-modal rotation and inter-modal deviation lead to CD. In order to alleviate CD in continual CLIP training, we propose a new continual training framework **Mod-X**: **M**aintain **o**ff-**d**iagonal information-matri**X**. By selectively aligning the off-diagonal information distribution of contrastive matrixes, the Mod-X helps the model not only better fits the newly trained data domain but also maintains the multimodal cognitive ability on the old data domain during the continual large-scale training (Section 5).

1 INTRODUCTION

Recently, multimodal pre-trained models such as CLIP Radford et al. (2021) have attracted much attention. By utilizing these pre-trained models, many works have achieved new progress in downstream tasks such as classification Zhang et al. (2020); Wei et al. (2022); Lee et al. (2022), semantic segmentation Xie et al. (2021b); Wang et al. (2021b), object detection Xie et al. (2021a); Wang et al. (2022a), speech recognition Baevski et al. (2020), etc. Although the CLIP model has strong generalization in open-world data, as mentioned in CLIP paper Radford et al. (2021), the ability to match image-text samples that are not in its training data distribution is still weak. The natural idea to alleviate this problem is to scale the training data to cover different data domains. However, it is infeasible to train infinite data with limited hardware at once.

In this paper, trying to break this non-iterability, we explore the feasibility of continuously training the CLIP model through streaming data, a training paradigm that follows Continual Learning (CL) McCloskey & Cohen (1989). To simulate continual CLIP training, we randomly and evenly divide the training data (joint-dataset) into multiple sub-datasets and train the CLIP sequentially using these sub-datasets. For comparison with continual training, we train a CLIP additionally from scratch using the joint-dataset, which is named joint training, as the upper bound on the performance of the continuously trained model.

Traditional supervised continual learning has been proven to suffer from catastrophic forgetting Rebuffi et al. (2017); Kirkpatrick et al. (2017). The model's performance on old tasks drops significantly

as training phases rise. Recently, some work Ni et al. (2021b); Hu et al. (2021) has validated that self-supervised models like SimCLR Chen et al. (2020) and BarlowTwins Zbontar et al. (2021) do not suffer from severe catastrophic forgetting during continual training. Some works Madaan et al. (2021); Thai et al. (2021) conjecture that the reason is that the contrastive loss is not directly affected by the supervised signal, and the self-supervised framework does not have a SoftMax function to amplify the influence of labels.

However, the performance of CLIP with a continual training setting overturns this hypothesis. There is a significant degradation of multimodal retrieval results with continual training compared with joint training (in Section 3 and 5). We name this phenomenon **Cognitive Disorder(CD)**. Due to the vision and language encoders within the CLIP normalizing the representation to a unit vector through a dimension-based L_2 norm, which limits the diffusion of representation vectors length, we try to analyze the representation space variation of modal extractors from a spatial geometry perspective. By tracking the directional changes of the representation vectors in the continuously updated CLIP model (in Section 3), we explore and summarize the spatial variation of the modal encoders within the CLIP: the **Intra-modal Rotation** and **Inter-modal Deviation**. The intra-modal rotation refers to the representation space of the single-modal feature extractors (vision and language) within the CLIP that rotates around the center of the high-dimensional sphere, accompanied by a slow topology change during the continual CLIP training. The inter-modal deviation refers to the cognitive deviation of different modal extractors (vision and language) to the same entities during continuous training. Moreover, we empirically and theoretically demonstrate how intra-modal rotation and inter-modal deviation lead to cognitive disorder (in Section 3).

To alleviate this cognitive disorder in continual CLIP training, we propose a simple yet effective framework Mod-X: **M**aintain **o**ff-**d**iagonal information-matri**X**. Unlike contrastive loss Oord et al. (2018) only focuses on the proportion of positive and negative sample pairs. The Mod-X framework pays more attention to the distribution of off-diagonal information in the contrastive matrix. The similarity distribution on the off-diagonal illustrates the model's cognition of all entities on current data. By selectively aligning the off-diagonal information distribution of the contrastive matrixes constructed by the current and past models based on the recent training sample, Mod-X helps the model preserve the correct cognition of various old entities while fitting the current vision-language data during continual training. The evaluations in Experiments 5 with different scale and scope datasets show that our Mod-X framework helps the model not only better fits the newly trained data domain (in Section 5.3) but also maintains the multimodal cognitive ability between the current model and old model on the old data domain during the continual large-scale training (in Section 5.4). More technological details and evaluations have been shown in Section 4 and Section 5. In summary, our contributions are as follows:

- We discuss the feasibility of training the CLIP model continuously through streaming data. Empirical experiments demonstrate that continual CLIP training leads to persistent performance degrades on multimodal retrieval. We name this Cognitive Disorder.

- By introducing a series of tools to track the directional changes of the representation vectors in the continuously updated CLIP model, we explore and summarize the spatial variation of the modal encoders within the CLIP: 1) The Intra-modal Rotation 2) The Inter-modal Deviation. Furthermore, we empirically and theoretically demonstrate how intra-modal rotation and inter-modal deviation lead to cognitive disorder (in Section 3).

- We propose a simple yet effective continual CLIP training framework **Mod-X** that alleviates CLIP's cognitive disorder by selectively aligning off-diagonal information in contrastive matrixes between the past and current models in continual training.

2 RELATED WORK

Continual Learning. Continual learning (CL) Thrun (1995), or incremental learning, is mainly focused on supervised tasks. In addition to the vision-based tasks De Lange et al. (2021); Kj et al. (2021); Cha et al. (2021); Ahn et al. (2021), some works discussing language-based tasks Biesialska et al. (2020); Sun et al. (2019). We can summarize the existing continual learning methods into three categories: regularization Kirkpatrick et al. (2017); Ahn et al. (2019); Ni et al. (2021a), replay Rebuffi et al. (2017); Rolnick et al. (2019); Wang et al. (2021a), and architecture Thai et al. (2021); Ni et al. (2021b); Hu et al. (2021); Madaan et al. (2021). In unsupervised and self-supervised based on a

single modal, the latest work Thai et al. (2021); Ni et al. (2021b); Hu et al. (2021); Madaan et al. (2021) has drawn some conclusions different from those of supervised. However, only a few works Srinivasan et al. (2022); Fan et al. (2022) focus on incremental multimodal tasks learning. Because of the cooperation between different models, continual multimodal pre-training shows different performance and problems from single modal continual training.

Visual-Language Representational Learning. Vision-language representation learning based on contrastive loss Oord et al. (2018) such as CLIP Radford et al. (2021) has attracted a lot of attention in various fields Radford et al. (2021); Li et al. (2021); Andonian et al. (2022); Mahabadi et al. (2022). And the pre-trained model perform surprisingly well on downstream tasks Shu et al. (2022); Wang et al. (2022b); Chowdhury et al. (2022). At the same time, the large-scale image-text datasets e.g., Laion400M Schuhmann et al. (2021) and Conceptual Captions Sharma et al. (2018) has played a key role in multimodal pre-training. Although large-scale open-world datasets contain various samples, pre-trained model still cannot perfectly match image-text sample pairs that are not in its training data domain Radford et al. (2021).

3 COGNITIVE DISORDER IN CONTINUAL CLIP TRAINING

This section discuss the performance of the CLIP_{ct} model, which trains CLIP continually without other operations. We name the decline in CLIP_{ct} performance as **Cognitive Disorder**. At the same time, the spatial variation of the modal encoders within the CLIP_{ct} are explored and summarized: 1). Intra-modal Rotation 2). Inter-modal Deviation. Finally, we empirically and theoretically demonstrate how intra-modal rotation and inter-modal deviation lead to cognitive disorder.

Exploration Setup. To ensure the controllability of the exploration, we train a CLIP_0 model from scratch on the COCO dataset Lin et al. (2014) based on the OpenAI source code OpenAI and use it as the initial(start) of continual CLIP training. After that, we divide the Flickr30K dataset Young et al. (2014) into five sub-datasets $\{D_1, D_2, D_3, D_4, D_5\}$ uniformly and randomly to simulate streaming data. Then we train the CLIP_0 based on this sub-datasets sequentially, and no other data is used when training on each sub-dataset. After finishing five training phases, we obtain the model CLIP_5. For comparison with CLIP_5, we train a CLIP_{jt} from scratch using joint dataset COCO and Flickr30K as the upper bound of the CLIP_{ct}. The hyper-parameters for all training phases are kept the same, and detailed settings of CLIP can be seen in Appendix 7.2.

Figure 1: The multimodal retrieval $R@1$ results of CLIP_t ($0 \leq t \leq 5$) on test sets COCO (5K) and Flickr30k (1K). The two sub-figures on the left show the Image-Text retrieval $R@1$ performance of CLIP_t on the continual training phase t. The rights show the Text-Image $R@1$ results. The pentagon points (CLIP_{jt}) show the results of the CLIP under joint training, which is an upper bound for continual CLIP training (CLIP_{ct}).

3.1 THE PERFORMANCE OF CONTINUAL CLIP TRAINING

We show the $R@1$ retrieval results of CLIP_t ($0 \leq t \leq 5$) on the 5K test set of COCO (COCO(5K)) and 1K test set of Flickr30k (Flickr30K(1K)) in Figure 1. By comparing the multimodal retrieval

performances of the $CLIP_0$ (initial phase) and $CLIP_{jt}$ on Flickr30K(1K), we can find that the retrieval performance of $CLIP_{jt}$ is significantly better than that of $CLIP_0$, which is not trained on Flickr30k. This phenomenon shows that the performance of the CLIP model is affected by the training data domain, which is consistent with the results of the paper Radford et al. (2021). Besides this, it can be clearly seen that the multimodal retrieval performance of the $CLIP_{ct}$ on the COCO(5K) has continued to decline with the rise of training phases. The final Image-Text R@1 result of $CLIP_5$ on COCO(5K) plummeted from the initial 14.7% to 6.1%, and the Text-Image results dropped from 10.6% to 4.7%. The gap with $CLIP_{jt}$ reached 10.0% and 7.0%. On the other hand, $CLIP_{ct}$ exhibits a slow and erratic increase in multimodal retrieval R@1 results on the test set Flickr30K(1K). Although the results between $CLIP_{ct}$ and $CLIP_{jt}$ on the Image-Text R@1 has been narrowed from the original 13.2% to 9.5% while the Text-Image R@1 of $CLIP_{ct}$ has increased from 12.0% to 16.1%, the gap between $CLIP_5$ and $CLIP_{jt}$ is still great. We name this phenomenon **Cognitive Disorder (CD)**.

3.2 THE REASONS FOR COGNITIVE DISORDER

In CLIP, the vision and language encoders normalize the final representation vector to a unit vector of length 1 using a dimension-based L_2 norm. This design makes the representation space in vision and language encoders form a high-dimensional unit sphere. Based on this fact, we ignore the influence of the representation vectors' length and track their direction changes.

3.2.1 THE INTRA-MODAL ROTATION

Firstly, we analyze the directional changes of the representation vectors of vision and language extractors in continual CLIP training. Taking the visual representation space as an example, we use the visual encoder E_i^V in $CLIP_i$ to extract the image representations of the test set COCO(5K) and obtain the vision representation vectors sets $V_i = \{V_i^0, V_i^1, V_i^2, ..., V_i^N, ..., V_i^{5K}\}$, where $i = 0, ..., 5$. After that, we take the inner product of each pair of vectors $< V_i^a, V_i^b >$ in each vector set V_i and perform $arccos$ operation to obtain their **S**elf-**A**ngle relationship **M**atrix (SAM_i). The $SAM_i^{(a,b)} = arccos(< V_i^a, V_i^b >)$. Any element $SAM_i^{(a,b)}$ in the SAM_i matrix represents the included angle between the sample a and b in the vision encoder E_i^V. By counting the difference θ_{SAM} between the corresponding elements in two continual SAM matrix SAM_i and SAM_{i+1} as shown in Figure 2(a), we get the following included angle change distribution table 2(b).

$\theta_{SAM} \in$	$[0°, 5°]$	$(5°, 10°]$	$(10°, 15°]$	$(15°, 20°]$	$(20°, 180°]$
SAM_{0-1}	54.23%	31.64%	11.28%	2.48%	0.38%
SAM_{1-2}	61.18%	30.21%	7.54%	0.99%	0.07%
SAM_{2-3}	61.44%	30.00%	7.50%	0.98%	0.07%
SAM_{3-4}	55.33%	31.75%	10.57%	2.07%	0.28%
SAM_{4-5}	50.51%	32.14%	13.17%	3.50%	0.68%
SAM_{0-5}	42.94%	31.12%	16.73%	6.66%	2.55%

(a)   (b)

Figure 2: The sub-figure on the left shows a schematic diagram of computing θ_{SAM}. The table on the right shows the distribution of the change of the included angle between any two samples in different training phases' vision representation space. And $SAM_{i-j} = |SAM_i - SAM_j|$.

From the table 2(b), we can find that 80% of the angle changes between any two vision representation vectors in the vision representation space are between 0 and 10 degrees in the process of continual CLIP training, while only 20% are above 10 degrees. Moreover, less than 1% of the angle changes are above 20 degrees. Those angle changes between 15-20 degrees also only account for about 5% of all image pairs. Therefore, we can conclude that **the topology of the visual representation of the $CLIP_{ct}$ changes slowly during the continual CLIP training.** In Appendix 7.7, we discuss this conjecture by comparing the representation quality of vision encoders.

In addition to discussing the change in the included angle between sample pairs in the visual representation space, by taking the inner product of the same sample's vision representation vector from different training phases' vision encoder E_i^V, we use the $arccos$ operation to compute the rotation angles θ_{RAM} of each test sample in vision encoder E_i^V and E_j^V and get the **R**otation **A**ngle **M**atrix $RAM_{(i,j)}$. The $RAM_{(i,j)}^a = arccos(< V_i^a, V_j^a >)$, where the a is the label of sample. The

schematic diagram can be seen in 3(a). By counting the distribution of rotation angles, we get the following rotation angle distribution table 3(b).

$\theta_{RAM} \in$	$[0°, 15°]$	$(15°, 20°]$	$(20°, 25°]$	$(25°, 30°]$	$(30°, 180°]$
$RAM_{(0,1)}$	0.00%	0.20%	4.62%	22.68%	72.50%
$RAM_{(1,2)}$	0.00%	0.40%	8.30%	34.11%	57.20%
$RAM_{(2,3)}$	0.00%	0.30%	8.40%	34.29%	57.01%
$RAM_{(3,4)}$	0.00%	0.00%	1.89%	17.11%	81.00%
$RAM_{(4,5)}$	0.00%	0.00%	0.00%	3.20%	96.81%
$RAM_{(0,5)}$	0.00%	0.00%	0.00%	0.21%	99.80%

(a)   (b)

Figure 3: The sub-figure on the left shows a schematic diagram of computing θ_{RAM}. The table on the right shows the rotation angle distribution of the same samples in different training phases.

By observing the table 3(b), we can find that the direction of the same sample in the visual representation space of different training phases has changed greatly. Only less than 0.4% samples are rotated within 20 degrees in the continual CLIP training, while the samples rotated within 20-25 degrees are at most less than 9%, and the samples of 25 degrees and above account for more than 90%. We speculate that **the vision representation space of CLIP$_{ct}$ has undergone a large rotation around the high-dimensional sphere center during the continual training.** After analyzing the language representation space, we reach the same conclusion as the vision representation space. Detailed SAM and RAM distribution of language encoders can be viewed in Appendix 7.3.

According to our analysis of the geometric changes of the single-modal encoder's representation space during continual CLIP training, we conclude that: **During the continual CLIP training, the representation space in the CLIP$_{ct}$ is significantly rotated. The topological structure of the representation space is slightly rotated compared with the rotation of the whole representation space.** We name this phenomenon **Intra-modal Rotation**.

Figure 4: The comparison of the rotation distributions of the representation spaces of the vision and language extractors during continual CLIP training. CLIP$_{i-j}$ refers to the CLIP's continual training from training phase i to j.

3.2.2 THE INTER-MODAL DEVIATION

Although the topology of the single-modal representation space changes during continual training, this slight rotation should not be the main reason for the degradation of CLIP's multimodal retrieval performance. To this end, we conduct a thought experiment: it is known that the representation spaces of vision and language encoders exhibit significant spatial rotations during continual training. Now we assume that the topology of the single-modal representation space is completely fixed during continual training. Therefore, if the CLIP$_{ct}$'s performance on multimodal retrieval does not degrade during continual training, the rotations of the two encoders' representation spaces should be **synchronized**. However, the fact is the opposite. So we think **there is a deviation between the rotation of the vision and language representation spaces**. Based on this suppose, we compare the rotation distributions of vision encoder (Figure 3(b)) and language encoder (Table 7(b)) and draw the rotation distribution comparison diagram (Figure 4). The values under the same color

represent the proportion of test samples to total samples in each rotation angle interval of the same modality. Comparing the difference in the distribution of rotation angles of the vision and language encoders, we can see that the space rotations of the two encoders are very different in the continual training. The rotation of language representation space is mostly concentrated between 20-30 degrees, while the vision's rotations are mostly between 30-180 degrees. This shows that the rotation of the representation space of the two modal extractors within CLIP_{ct} is not synchronized during the continual training, which verifies our previous inference: **The unsynchronized rotation of the vision and language representation spaces leads to cognitive deviations between the CLIP's modal encoders (vision and language).** We name this phenomenon **Inter-modal Deviation**.

3.2.3 Intra-modal Rotation and Inter-modal Deviation lead to Cognitive Disorder

Based on the above exploration, we can conclude that intra-modal rotation and inter-modal deviation play a key role in CLIP_{ct}'s cognitive disorder. However, how do they cause the model to misalign the old sample's vision and language representation? We show a schematic here to illustrate this. As shown in Figure 5, the α is vision representation and β is language representation. The a,b denote different image-text samples. For the convenience of illustration, we set the unsynchronous rotation of the two modal spaces as the visual modal's static and the language's relative rotation. When intra-modal rotation happens 5(a), β_a in training phase $t+1$ is rotated to β'_a, the modal similarity between a and b shift from $(\beta_a^T \alpha_a > \beta_a^T \alpha_b)$ to $({\beta'}_a^T \alpha_a < {\beta'}_a^T \alpha_b)$, which break the alignment of the current model to old sample a. When inter-modal deviation happens 5(b), the relative rotation of the representation space breaks the original modal alignment of sample a which makes the $(\beta_a^T \alpha_b > \beta_a^T \alpha_a)$. Because of this, the performance of CLIP_{ct} drops significantly during continual training. Detailed mathematical derivations can be found in Appendix 7.1.

Figure 5: The Schematic illustration of cognitive disorder caused by intra-modal rotation and inter-modal deviation.

4 Alleviating Cognitive Disorder

4.1 General continual CLIP training Setting

Suppose we have used training dataset D_0 got a pre-trained model CLIP_0. And there is another vision-language dataset D. We split D into N sub-datasets $\{D_1, ..., D_N\}$, randomly and evenly, to simulate a stream of data and $D_t = \{(v_t^0, l_t^0), ..., (v_t^n, l_t^n)\}$ denotes the training data in the training phase t, where $t \in \{1, 2, ..., N\}$. Then training the model CLIP_0 using sub-datasets sequentially. The enocded l_2 normalized embeddings of vision and text is $V_t^i = E_V^t(v_t^i)$ and $L_t^i = E_L^t(l_t^i)$. When the model CLIP_t is trained during the training phase t using training data D_t, the previous sub-datasets $\{D_0, D_1, ..., D_{t-1}\}$ are no longer available. The joint training refers to training a CLIP_{jt} from scratch using all data $D_{jt} = D_0 \cup D$.

4.2 Mod-X: Maintain off-diagonal information-matrix

To alleviate cognitive disorder of the CLIP_{ct} model during continual training. We produce a simple but effective new training framework: Maintain off-diagonal information-matrix (Mod-X). It helps the current CLIP retain the cognition of past samples by aligning off-diagonal information in the similarity matrix constructed by the CLIP_{ct} before and after continual training based on the current training data. The entire training framework is shown in Figure 6. The Contrastive module in Figure

6 is a traditional InfoNCE loss Baevski et al. (2020) , which inherit from CLIP Radford et al. (2021). In there, we mainly introduce our Cognition Align module.

Figure 6: The Mod-X framework mainly consists of two subsections. Cognition Align helps the current model align the cognition of the old model based on current data. And Contrative helps the model fit the current training data domain.

4.3 COGNITION ALIGN

The diagonal elements in CLIP's contrastive matrix represent the similarity of the model's understanding of the visual and language information of the current sample. The off-diagonal elements represent the similarity between the vision and language representation of the current sample and other samples or vice versa. The distribution of off-diagonal elements in the contrastive matrix represents the current model's cognition about the current training objects. So we use Cognition Align to distill the old model's "world view" of current samples to help the current model maintain the cognitive ability on past entities. Firstly, we construct contrastive matrix M_{t-1} and M_t using the last and current model $CLIP_{t-1}$ and $CLIP_t$ based on current sub-dataset D_t.

$$M_{t-1}^{i,j} = CLIP_{t-1}(D_t) = s(E_V^{t-1}(v_t^i), E_L^{t-1}(l_t^j)) \tag{1}$$

$$M_t^{i,j} = CLIP_t(D_t) = s(E_V^t(v_t^i), E_L^t(l_t^j)) \tag{2}$$

Where the $s(a, b) = (a)^T b$ is the cosine similarity function. However, the last model's cognition for current data is not totally correct. For those misunderstood sample information (diagonal elements are not the largest in the current retrieval), we use the corresponding similarity information of the current model to replace them. Thereby removing their influence on the current model during distillation.

$$M_{t-1}^{(i,:)} = M_t^{(i,:)}; \quad if \quad max(M_{t-1}^i) \neq i \tag{3}$$

After that, we align the information matrix M^{t-1}, which is selected by Screening, using Kullback-Leibler Divergence Csiszár (1975).

$$L_{KL}^t(M^t, M^{t-1}) = -\sum M^{t-1} ln(\frac{M^t}{M^{t-1}}) \tag{4}$$

The final training loss can be joint in L_{Mod-X} and α is a hyper-parameter.

$$L_{Mod-X}^t = L_{InfoNCE}^t + \alpha L_{KL}^t \tag{5}$$

5 EXPERIMENTS

5.1 TRAINING DATASETS

In the experiments, we use three image-text datasets varying in scale and scope to simulate continual CLIP training. **MS COCO Captions** Lin et al. (2014): MS COCO Captions (COCO) is a widely used image caption dataset. It contains 80K training images, 30K validation images, and 5K testing images (COCO(5K)). Each image has 5 human-evaluated captions. **Flickr30K** Young et al. (2014): Flickr30K(F30K) contains 30K training images and 1K test samples (Flickr30K(1K)) collected from Flickr, together with 5 reference sentences provided by human annotators. **SBU-1M** Ordonez et al. (2011): The SBU-1M collects 1M images from Flickr with associated visually relevant captions which representing a wider variety of content styles. After downloading and preprocessing, we utilized about 0.8M image-text pairs in our experiments.

5.2 EXPERIMENTS SETTING

We apply our Mod-X framework to two experiment settings to illustrate that Mod-X helps the model not only better fits the newly trained data domain but also maintains the multimodal cognitive ability of the old data domain during the continual large-scale training. **Experiment A:** The Experiment A follows the setup of the exploratory experiments, pre-training the $CLIP_0$ model using the COCO dataset. And then splitting Flickr30K dataset randomly and evenly into five sub-datasets and sequentially training them to update $CLIP_0$ continually. **Experiment B:** Unlike Experiment A, which looks like fine-tuning, we try to simulate continual large-scale training in Experiment B. We train a CLIP from scratch using the joint data of COCO and Flickr30K (COCO+F30K) as the initial model $CLIP_0$ and continually train eight sub-datasets divided from the SBU-1M dataset, randomly and uniformly. Each sub-dataset contains 100K unique samples, an equal scale to the initial pre-training dataset (COCO+F30K). This experiment verifies that our framework can iterate under continual large-scale training and maintain or even improve the model's cognition of past entities. **Evaluation Details:** We use the test sets COCO(5K) and Flickr30K(1K) to evaluate the performance of model in continual training. And all the results in the tables and figures are the average of 3 runs with different seeds. Experiment details have been shown in Appendix 7.2.

5.3 PERFORMANCE OF MOD-X IN THE EXPERIMENT A

The Experiment A focuses on verifying that Mod-X can not only fit new data domains but also maintain a cognition of past data domains. This table shows the final multimodal retrieval performance of the different training strategies on COCO(5K) and Flickr30K(1K). The $CLIP_0$ is the initial pre-trained model based on the COCO dataset. The $CLIP_{ct}$ means training CLIP continually without any other operation. The $CLIP_{EWC}$ means using the EWC method Kirkpatrick et al. (2017), which is a typical regularization strategy in continual supervised learning. The $CLIP_{Mod-X}$ is the proposed Mod-X, and the $CLIP_{JT}$ is the joint training model using the joint datasets (COCO+F30K), which is an upper bound for continual CLIP training in Experiment A. The detailed performance of the different models at each training phase is shown in Appendix 7.4.

| Pretraining Dataset | Model | Image-Text Retrieval(%) | | | | | | Text-Image Retrieval(%) | | | | | |
| | | Flickr30k(1K) | | | COCO(5K) | | | Flickr30k(1K) | | | COCO(5K) | | |
		$R@1$	$R@5$	$R@10$	$R@1$	$R@5$	$R@10$	$R@1$	$R@5$	$R@10$	$R@1$	$R@5$	$R@10$
COCO	$CLIP_0$	16.9	37.0	46.2	14.7	34.2	47.0	12.0	30.0	41.0	10.6	29.6	41.0
	$CLIP_{ct}$	20.6	42.8	56.4	6.2	17.8	26.1	16.1	38.5	50.4	4.7	14.3	21.8
	$CLIP_{EWC}$	22.2	43.1	57.0	6.1	17.2	26.5	17.0	39.1	51.2	4.5	13.9	22.0
	$CLIP_{Mod-X}$	**27.9**	**53.4**	**64.4**	**14.5**	**34.0**	**46.1**	**20.2**	**45.0**	**57.2**	**10.1**	**26.38**	**37.4**
COCO+F30K	$CLIP_{jt}$	30.1	55.9	60.1	16.1	38.1	51.9	22.5	48.5	59.6	11.7	30.9	42.7

Table 1: The final multimoal retrieval performance of the different continual CLIP training strategies in the Experiment A.

From the results in the Table 1, it is clear that our method $CLIP_{Mod-X}$ maintains its multimodal retrieval results on COCO(5K) after completing continual training on Flickr30K. The gap between

$CLIP_0$ and $CLIP_{Mod-X}$ is just 0.2% points in image-text retrieval and 0.5% points in text-image retrieval on COCO(5K). At the same time, the retrieval results of the $CLIP_{Mod-X}$ on the test set Flickr30K(1K) are also affected by the training domain and have a significant increase. The $R@1$ performance of the $CLIP_{Mod-X}$ in image-text retrieval rise from 16.9% (in $CLIP_0$) to 27.9%. And the $R@1$ results in text-image retrieval increase from 12.0% (in $CLIP_0$) to 20.2%. The performance gap between $CLIP_{Mod-X}$ and $CLIP_{jt}$ on the Flickr30K is only at most 2.3% points. Conversely, due to the model's cognitive disorder in continual training, the performance of $CLIP_{ct}$ on COCO(5K) drops significantly. In addition, although the performance of $CLIP_{ct}$ on Flickr30K(1K) has improved, it is still far from the upper bound $CLIP_{jt}$. The EWC, as a typical regularization strategy in continual learning, selectively updates the model by evaluating the importance of each parameter of the model. From the above experimental results, although $CLIP_{EWC}$ improves the accuracy of continual CLIP training on Flickr30K(1K), it does not preserve the model's understanding in past samples (COCO(5K)). According to the above comparisons, we can conclude that our Mod-X framework can not only maintain the cognitive ability on past samples during continual CLIP learning but also improve the model's fitting ability to the current training data domain.

5.4 Performance of Mod-X in the Experiment B

Unlike Experiment A, which looks like fine-tuning, Experiment B focuses on verifying that our framework Mod-X can maintain or even improve the model's understanding of past entities when iterating under continual large-scale training. Table 2 shows the final multimodal retrieval performance of the different continual CLIP training strategies in Experiment B. The detailed $R@1$ results in each training phase can be seen in Appendix 7.5.

Pretraining Dataset	Model	Image-Text Retrieval(%)						Text-Image Retrieval(%)					
		Flickr30K(1K)			COCO(5K)			Flickr30K(1K)			COCO(5K)		
		$R@1$	$R@5$	$R@10$	$R@1$	$R@5$	$R@10$	$R@1$	$R@5$	$R@10$	$R@1$	$R@5$	$R@10$
COCO+F30K	$CLIP_0$	33.0	56.5	67.3	17.7	40.7	52.9	23.4	48.2	59.1	12.9	32.8	44.9
	$CLIP_{ct}$	5.4	16.0	23.3	3.0	9.0	14.0	3.6	12.0	18.6	2.3	7.3	11.4
	$CLIP_{EWC}$	6.1	18.2	33.5	3.1	11.7	18.2	3.3	10.4	16.2	2.1	5.4	10.0
	$CLIP_{Mod-X}$	**37.3**	**62.6**	**72.1**	**19.5**	**42.8**	**55.7**	**26.0**	**51.9**	**62.6**	**13.4**	**33.6**	**45.3**
Joint Datasets	$CLIP_{jt}$	39.3	71.5	81.1	25.1	51.6	64.3	27.8	54.9	66.5	15.9	38.6	51.3

Table 2: The final multimoal retrieval performance of the different continual CLIP training strategies in the Experiment B.

Compared to the initial pre-trained model $CLIP_0$, our $CLIP_{Mod-X}$ not only does not show a significantly drop such as $CLIP_{ct}$ in multimodal retrieval performance on COCO(5K) and Flickr30K(1K) but it also shows a slight improvement after continual training in SBU-1M. The image-text $R@1$ results on Flickr30K(1K) increase from 33.0% to 37.3% and the accuracy on COCO improved to 19.5% from 17.7%. The performance of text-image $R@1$ is the same as that of image-text. The accuracy increase from 23.4% to 26.0% on Flickr30K(1K) and 12.9% to 13.4% on COCO(5K). The gap between continual CLIP training and joint training has been somewhat narrowed. Conversely, the ability of cognitive alignment in $CLIP_{ct}$ and $CLIP_{EWC}$ are lost in the large-scale data. This results in verifying that our framework Mod-X can iterate under continual large-scale training and can maintain or even improve the model's cognitive ability of past entity concepts.

6 Conclusion

In this paper, We explore the feasibility of training the CLIP model continuously through streaming data and name its performance decline in multimodal retrieval as Cognitive Disorder(CD). Then, By tracking the directional changes of the representation vectors in the continuously updated CLIP model, we explore and summarize the spatial variation of the modal encoders within the CLIP: Intra-modal Rotation and Inter-modal Deviation. Moreover, we mathematically demonstrate how intra-modal rotation and inter-modal deviation lead to CD. To alleviate the cognitive disorder of the continual CLIP training, we propose a simple yet effective continual learning framework Mod-X: **M**aintain **o**ff-**d**iagonal information-matri**X**. The results in experiments (5.3 and 5.4) demonstrate the effectiveness of our framework.

REFERENCES

Hongjoon Ahn, Sungmin Cha, Donggyu Lee, and Taesup Moon. Uncertainty-based continual learning with adaptive regularization. *Advances in neural information processing systems*, 32, 2019.

Hongjoon Ahn, Jihwan Kwak, Subin Lim, Hyeonsu Bang, Hyojun Kim, and Taesup Moon. Ss-il: Separated softmax for incremental learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 844–853, 2021.

Alex Andonian, Shixing Chen, and Raffay Hamid. Robust cross-modal representation learning with progressive self-distillation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16430–16441, 2022.

Alexei Baevski, Yuhao Zhou, Abdelrahman Mohamed, and Michael Auli. wav2vec 2.0: A framework for self-supervised learning of speech representations. *Advances in Neural Information Processing Systems*, 33:12449–12460, 2020.

Magdalena Biesialska, Katarzyna Biesialska, and Marta R Costa-Jussa. Continual lifelong learning in natural language processing: A survey. *arXiv preprint arXiv:2012.09823*, 2020.

Sungmin Cha, YoungJoon Yoo, Taesup Moon, et al. Ssul: Semantic segmentation with unknown label for exemplar-based class-incremental learning. *Advances in Neural Information Processing Systems*, 34:10919–10930, 2021.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020.

Jishnu Ray Chowdhury, Yong Zhuang, and Shuyi Wang. Novelty controlled paraphrase generation with retrieval augmented conditional prompt tuning. *arXiv preprint arXiv:2202.00535*, 2022.

Imre Csiszár. I-divergence geometry of probability distributions and minimization problems. *The annals of probability*, pp. 146–158, 1975.

Matthias De Lange, Rahaf Aljundi, Marc Masana, Sarah Parisot, Xu Jia, Aleš Leonardis, Gregory Slabaugh, and Tinne Tuytelaars. A continual learning survey: Defying forgetting in classification tasks. *IEEE transactions on pattern analysis and machine intelligence*, 44(7):3366–3385, 2021.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Zhihao Fan, Zhongyu Wei, Jingjing Chen, Siyuan Wang, Zejun Li, Jiarong Xu, and Xuanjing Huang. A unified continuous learning framework for multi-modal knowledge discovery and pre-training. *arXiv preprint arXiv:2206.05555*, 2022.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 9729–9738, 2020.

Dapeng Hu, Shipeng Yan, Qizhengqiu Lu, HONG Lanqing, Hailin Hu, Yifan Zhang, Zhenguo Li, Xinchao Wang, and Jiashi Feng. How well does self-supervised pre-training perform with streaming data? In *International Conference on Learning Representations*, 2021.

James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, et al. Overcoming catastrophic forgetting in neural networks. *Proceedings of the national academy of sciences*, 114 (13):3521–3526, 2017.

Joseph Kj, Jathushan Rajasegaran, Salman Khan, Fahad Shahbaz Khan, and Vineeth N Balasubramanian. Incremental object detection via meta-learning. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2021.

Hyungtae Lee, Sungmin Eum, and Heesung Kwon. Exploring cross-domain pretrained model for hyperspectral image classification. *IEEE Transactions on Geoscience and Remote Sensing*, 60: 1–12, 2022.

Yangguang Li, Feng Liang, Lichen Zhao, Yufeng Cui, Wanli Ouyang, Jing Shao, Fengwei Yu, and Junjie Yan. Supervision exists everywhere: A data efficient contrastive language-image pre-training paradigm. *arXiv preprint arXiv:2110.05208*, 2021.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European conference on computer vision*, pp. 740–755. Springer, 2014.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*, 2017.

Divyam Madaan, Jaehong Yoon, Yuanchun Li, Yunxin Liu, and Sung Ju Hwang. Representational continuity for unsupervised continual learning. In *International Conference on Learning Representations*, 2021.

Rabeeh Karimi Mahabadi, Luke Zettlemoyer, James Henderson, Marzieh Saeidi, Lambert Mathias, Veselin Stoyanov, and Majid Yazdani. Perfect: Prompt-free and efficient few-shot learning with language models. *arXiv preprint arXiv:2204.01172*, 2022.

Michael McCloskey and Neal J Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. In *Psychology of learning and motivation*, volume 24, pp. 109–165. Elsevier, 1989.

Zixuan Ni, Haizhou Shi, Siliang Tang, Longhui Wei, Qi Tian, and Yueting Zhuang. Revisiting catastrophic forgetting in class incremental learning, 2021a.

Zixuan Ni, Siliang Tang, and Yueting Zhuang. Self-supervised class incremental learning. *arXiv preprint arXiv:2111.11208*, 2021b.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

OpenAI. Clip. `https://github.com/openai/CLIP`.

Vicente Ordonez, Girish Kulkarni, and Tamara Berg. Im2text: Describing images using 1 million captioned photographs. *Advances in neural information processing systems*, 24, 2011.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pp. 8748–8763. PMLR, 2021.

Sylvestre-Alvise Rebuffi, Alexander Kolesnikov, Georg Sperl, and Christoph H Lampert. icarl: Incremental classifier and representation learning. In *Proceedings of the IEEE conference on Computer Vision and Pattern Recognition*, pp. 2001–2010, 2017.

David Rolnick, Arun Ahuja, Jonathan Schwarz, Timothy Lillicrap, and Gregory Wayne. Experience replay for continual learning. *Advances in Neural Information Processing Systems*, 32, 2019.

Christoph Schuhmann, Richard Vencu, Romain Beaumont, Robert Kaczmarczyk, Clayton Mullis, Aarush Katta, Theo Coombes, Jenia Jitsev, and Aran Komatsuzaki. Laion-400m: Open dataset of clip-filtered 400 million image-text pairs. *arXiv preprint arXiv:2111.02114*, 2021.

Piyush Sharma, Nan Ding, Sebastian Goodman, and Radu Soricut. Conceptual captions: A cleaned, hypernymed, image alt-text dataset for automatic image captioning. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2556–2565, 2018.

Manli Shu, Weili Nie, De-An Huang, Zhiding Yu, Tom Goldstein, Anima Anandkumar, and Chaowei Xiao. Test-time prompt tuning for zero-shot generalization in vision-language models. *arXiv preprint arXiv:2209.07511*, 2022.

Tejas Srinivasan, Ting-Yun Chang, Leticia Leonor Pinto Alva, Georgios Chochlakis, Mohammad Rostami, and Jesse Thomason. Climb: A continual learning benchmark for vision-and-language tasks. *arXiv preprint arXiv:2206.09059*, 2022.

Fan-Keng Sun, Cheng-Hao Ho, and Hung-Yi Lee. Lamol: Language modeling for lifelong language learning. *arXiv preprint arXiv:1909.03329*, 2019.

Anh Thai, Stefan Stojanov, Isaac Rehg, and James M Rehg. Does continual learning= catastrophic forgetting? *arXiv preprint arXiv:2101.07295*, 2021.

Sebastian Thrun. A lifelong learning perspective for mobile robot control. In *Intelligent robots and systems*, pp. 201–214. Elsevier, 1995.

Liyuan Wang, Kuo Yang, Chongxuan Li, Lanqing Hong, Zhenguo Li, and Jun Zhu. Ordisco: Effective and efficient usage of incremental unlabeled data for semi-supervised continual learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 5383–5392, 2021a.

Renhao Wang, Hang Zhao, and Yang Gao. Cyborgs: Contrastively bootstrapping object representations by grounding in segmentation. *arXiv preprint arXiv:2203.09343*, 2022a.

Xinlong Wang, Rufeng Zhang, Chunhua Shen, Tao Kong, and Lei Li. Dense contrastive learning for self-supervised visual pre-training. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3024–3033, 2021b.

Zifeng Wang, Zizhao Zhang, Chen-Yu Lee, Han Zhang, Ruoxi Sun, Xiaoqi Ren, Guolong Su, Vincent Perot, Jennifer Dy, and Tomas Pfister. Learning to prompt for continual learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 139–149, 2022b.

Longhui Wei, Lingxi Xie, Wengang Zhou, Houqiang Li, and Qi Tian. Mvp: Multimodality-guided visual pre-training. *arXiv preprint arXiv:2203.05175*, 2022.

Enze Xie, Jian Ding, Wenhai Wang, Xiaohang Zhan, Hang Xu, Peize Sun, Zhenguo Li, and Ping Luo. Detco: Unsupervised contrastive learning for object detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 8392–8401, 2021a.

Zhenda Xie, Yutong Lin, Zheng Zhang, Yue Cao, Stephen Lin, and Han Hu. Propagate yourself: Exploring pixel-level consistency for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16684–16693, 2021b.

Peter Young, Alice Lai, Micah Hodosh, and Julia Hockenmaier. From image descriptions to visual denotations: New similarity metrics for semantic inference over event descriptions. *Transactions of the Association for Computational Linguistics*, 2:67–78, 2014.

Jure Zbontar, Li Jing, Ishan Misra, Yann LeCun, and Stéphane Deny. Barlow twins: Self-supervised learning via redundancy reduction. In *International Conference on Machine Learning*, pp. 12310–12320. PMLR, 2021.

Li Zhang, Dan Xu, Anurag Arnab, and Philip HS Torr. Dynamic graph message passing networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3726–3735, 2020.

7 APPENDIX

7.1 THE THEORETICAL DEMONSTRATE THAT INTER-MODAL DEVIATION AND INTRA-MODAL ROTATION LEAD TO COGNITIVE DISORDER

Inter-modal Deviation and Intra-modal Rotation can influence the CLIP's sample similarity matrix, but this does not necessarily lead to errors in multimodal retrieval results. Unless the similarity of the visual language representation of the model for the same sample is smaller than that between different samples. In there, we abstract this problem and give the theoretical conditions that the Intra-modal Rotation and Inter-modal Deviation leads to the cognitive disorder.

There has N image-text pairs $\{(\alpha_1,\beta_1),(\alpha_2,\beta_2),(\alpha_3,\beta_3),...,(\alpha_i,\beta_i),...,(\alpha_N,\beta_N)\} \in R^{W \times W}$. Through function $\mathcal{M}(\alpha)$ and $\mathcal{Q}(\beta)$, $\mathcal{M} \neq \mathcal{Q}$, the Euclidean space A and B of images and texts are formed.

$$
\begin{aligned}
A &= span\{\mathcal{M}(\alpha_1), \mathcal{M}(\alpha_2), \mathcal{M}(\alpha_2), ..., \mathcal{M}(\alpha_i), ..., \mathcal{M}(\alpha_N)\} \\
B &= span\{\mathcal{Q}(\beta_1), \mathcal{Q}(\beta_2), \mathcal{Q}(\beta_2), ..., \mathcal{Q}(\beta_i), ..., \mathcal{Q}(\beta_N)\}
\end{aligned}
\tag{6}
$$

The $\mathcal{M}(\alpha_i), \mathcal{Q}(\beta_j) \in R^D$ and $\|\mathcal{M}(\alpha_i)\| = 1$, $\|\mathcal{Q}(\beta_j)\| = 1$, $i, j = 1, 2, 3, ..., N$. $< \mathcal{M}(\alpha_i), \mathcal{Q}(\beta_j) >$ is the cosine between $\mathcal{M}(\alpha_i)$ and $\mathcal{Q}(\beta_j)$, $j = 1, 2, 3, ..., N$.

Suppose: $\exists (\alpha_a, \beta_a), (\alpha_b, \beta_b) \in \{(\alpha_i, \beta_j), i, j = 1, 2, 3, ..., N\}$ and $a \neq b$ makes:

$$
\begin{aligned}
< \mathcal{M}(\alpha_a), \mathcal{Q}(\beta_a) > &= \underset{\beta_i = \beta_a}{\arg\max} < \mathcal{M}(\alpha_a), \mathcal{Q}(\beta_i) > \\
< \mathcal{M}(\alpha_b), \mathcal{Q}(\beta_b) > &< \underset{\beta_j \neq \beta_b}{\arg\max} < \mathcal{M}(\alpha_b), \mathcal{Q}(\beta_j) >
\end{aligned}
\tag{7}
$$

7.1.1 INTER-MODAL DEVIATION LEADS TO COGNITIVE DISORDER

Prove: There is a rotation matrix pair $(\mathcal{A},\mathcal{B})$ that not only keeps the A and B topology unbiased and makes the

$$
\begin{aligned}
< \mathcal{M}'(\alpha_a), \mathcal{Q}'(\beta_a) > &< \underset{\beta_i \neq \beta_a}{\arg\max} < \mathcal{M}'(\alpha_a), \mathcal{Q}'(\beta_i) > \\
< \mathcal{M}'(\alpha_b), \mathcal{Q}'(\beta_b) > &= \underset{\beta_j = \beta_b}{\arg\max} < \mathcal{M}'(\alpha_b), \mathcal{Q}'(\beta_j) >
\end{aligned}
\tag{8}
$$

where the $\mathcal{M}' = \mathcal{A}(\mathcal{M})$ and $\mathcal{Q}' = \mathcal{B}(\mathcal{Q})$, $\mathcal{A} \neq \mathcal{B}$. And the space A and B can be written as A' and B':

$$
\begin{aligned}
A' &= \mathcal{A}(A) = span\{\mathcal{M}'(\alpha_1), \mathcal{M}'(\alpha_2), \mathcal{M}'(\alpha_2), ..., \mathcal{M}'(\alpha_i), ..., \mathcal{M}'(\alpha_N)\} \\
B' &= \mathcal{B}(B) = span\{\mathcal{Q}'(\beta_1), \mathcal{Q}'(\beta_2), \mathcal{Q}'(\beta_2), ..., \mathcal{Q}'(\beta_i), ..., \mathcal{Q}'(\beta_N)\}
\end{aligned}
\tag{9}
$$

Solution: the Equ.7 can be written as:

$$
\begin{aligned}
< \mathcal{M}(\alpha_a), \mathcal{Q}(\beta_a) > - < \mathcal{M}(\alpha_a), \mathcal{Q}(\beta_i) >> 0, \forall \beta_i \in \beta, i \neq a \\
< \mathcal{M}(\alpha_b), \mathcal{Q}(\beta_b) > - < \mathcal{M}(\alpha_b), \mathcal{Q}(\beta_j) >< 0, \exists \beta_j \in \beta, j \neq b
\end{aligned}
\tag{10}
$$

hence:

$$
\begin{aligned}
\mathcal{M}(\alpha_a)^T \mathcal{Q}(\beta_a) - \mathcal{M}(\alpha_a)^T \mathcal{Q}(\beta_i) > 0, \forall \beta_i \in \beta, i \neq a \\
\mathcal{M}(\alpha_b)^T \mathcal{Q}(\beta_j) - \mathcal{M}(\alpha_b)^T \mathcal{Q}(\beta_b) > 0, \exists \beta_j \in \beta, j \neq b
\end{aligned}
\tag{11}
$$

because the rotation matrix pair $(\mathcal{A},\mathcal{B})$ can be seen as a rotation matrix $\mathcal{R}(\theta^D)$, where the θ^D is a rotation angle between AB and $A'B'$. Hence, when applying this rotation matrix $\mathcal{R}(\theta^D)$, the Equ.11 can be written as:

$$\mathcal{M}(\alpha_a)^T \mathcal{R}(\theta^D) \mathcal{Q}(\beta_a) - \mathcal{M}(\alpha_a)^T \mathcal{R}(\theta^D) \mathcal{Q}(\beta_i) < 0, \exists \beta_i \in \beta, i \neq a$$
$$\mathcal{M}(\alpha_b)^T \mathcal{R}(\theta^D) \mathcal{Q}(\beta_j) - \mathcal{M}(\alpha_b)^T \mathcal{R}(\theta^D) \mathcal{Q}(\beta_b) < 0, \forall \beta_j \in \beta, j \neq b \tag{12}$$

Because the rotation matrix satisfies that the inner product of itself is 1. So, Equ 12 can be written as:

$$\mathcal{M}(\alpha_a)^T \mathcal{R}(\theta^D)(\mathcal{Q}(\beta_a) - \mathcal{Q}(\beta_i)) < 0, \exists \beta_i \in \beta, i \neq a, \mathcal{R}(\theta^D)^T \mathcal{R}(\theta^D) = \mathcal{I} \tag{13}$$
$$\mathcal{M}(\alpha_b)^T \mathcal{R}(\theta^D)(\mathcal{Q}(\beta_j) - \mathcal{Q}(\beta_b)) < 0, \forall \beta_j \in \beta, j \neq b, \mathcal{R}(\theta^D)^T \mathcal{R}(\theta^D) = \mathcal{I} \tag{14}$$

For example, when $\mathcal{R}(\theta^D) = -\mathcal{I}$, then $\mathcal{R}(\theta^D)^T \mathcal{M}(\alpha_a) = -\mathcal{M}(\alpha_a)$ the equ 15 and 16 will hold. So, rotation matrices $(\mathcal{A},\mathcal{B})$ that makes Equ.8 true exists.

7.1.2 Intra-modal Rotation leads To Cognitive Disorder

Since intra-modal rotation just requires the length of representation vectors after rotation is 1 and does not require that the intra-modal representation space is invariant, it is a more general case of inter-modal deviation. This means that all rotation matrixes that satisfy 7.1.1 can also satisfy Intra-modal Rotation. Different from intra-modal deviation, the inner product of the mapping matrix $\mathcal{P}$ does not require to be 1. So, we rewrite the Equ 15 and 16 to:

$$\mathcal{M}(\alpha_a)^T(\mathcal{Q}(\beta_a) - \mathcal{Q}(\beta_i))\mathcal{P} < 0, \exists \beta_i \in \beta, i \neq a, \tag{15}$$
$$\mathcal{M}(\alpha_b)^T(\mathcal{Q}(\beta_j) - \mathcal{Q}(\beta_b))\mathcal{P} < 0, \forall \beta_j \in \beta, j \neq b, \tag{16}$$

Any mapping matrix $\mathcal{P}$ that rotation the direction of $(\mathcal{Q}(\beta_j) - \mathcal{Q}(\beta_b))$ by more than 90 degrees.

7.2 Detailed Experiment Setting

In exploration experiments 3 and main experiments 5, we use RN50 He et al. (2016) as the vision encoder and language encoder is a transformer-based architecture which follows modification proposed in CLIP OpenAI. The input images are resized to 224×224 and the input texts are tokenized by WordPiece with a maximum length of 77. We utilize AdamW Loshchilov & Hutter (2017) optimizer and a cosine annealing learning rate schedule with warmup which is consistent with OpenAI. All of the experiments are conducted on 8 NVIDIA V100 GPUS. In exploration Experiment and Experiment A, we use the hyper-parameters as be shown in table 2(a). Since the size of training data in our exploration experiment and experiment A is relatively small compared to large-scale pre-training, we set a smaller batch size. And other hyper-parameters is consistent with CLIP OpenAI.

(a)		(b)	
Hyperparameter	**Value**	**Hyperparameter**	**Value**
Batch size	280	Batch size	800
Vocabulary size	49408	Vocabulary size	49408
Training epochs	35	Training epochs	35
Initial temperature τ	0.07	Initial temperature τ	0.07
α	20	α	20
Weight decay	0.2	Weight decay	0.2
Warm-up iterations (%)	20	Warm-up iterations (%)	20
Learning rate	$5e^{-4}$	Learning rate	$1e^{-3}$
Adam β_1	0.9	Adam β_1	0.9
Adam β_2	0.99	Adam β_2	0.99
Adam ϵ	$1e^{-8}$	Adam ϵ	$1e^{-8}$

Table 3: Table (a) is the hyperparameter in exploration experiment (Section 3) and Experiment A (Section 5.3). Table (b) is the hyperparameter in Experiment B (Section 5.4).

In Experiment B, due to the size of training data reaches to 1 million, we increase the batch size to 800 and increase the initial learning rate to $1e^{-3}$. And other hyper-parameters is consistent with Experiment A. The detailed hyper-parameters in table 2(b).

7.3 Detailed SAM and RAM Distribution of Language Encoders

The topological structure of the language representation space does not change significantly with the continual CLIP training. But the whole language representation space, like the vision representation space, has a large rotation around the center of the high-dimensional sphere during the continual training. The angle change distribution table 7(a) and rotation angle distribution table 7(b) are shown below.

$\theta_{SAM} \in$	$[0°, 5°]$	$(5°, 10°]$	$(10°, 15°]$	$(15°, 20°]$	$(20°, 180°]$
SAM_{0-1}	64.43%	28.49%	6.23%	0.78%	0.07%
SAM_{1-2}	71.54%	24.89%	3.35%	0.22%	0.01%
SAM_{2-3}	71.36%	25.01%	3.40%	0.22%	0.01%
SAM_{3-4}	67.30%	27.27%	4.93%	0.48%	0.03%
SAM_{4-5}	58.84%	30.70%	8.77%	1.50%	0.20%
SAM_{0-5}	55.39%	31.60%	10.52%	2.15%	0.33%

(a) The angle difference distribution in text representation space.

$\theta_{RAM} \in$	$[0°, 15°]$	$(15°, 20°]$	$(20°, 25°]$	$(25°, 30°]$	$(30°, 180°]$
$RAM_{(0,1)}$	0.00%	1.94%	28.38%	45.88%	23.80%
$RAM_{(1,2)}$	0.02%	8.90%	47.76%	34.94%	8.38%
$RAM_{(2,3)}$	0.04%	1.14%	49.86%	31.18%	7.52%
$RAM_{(3,4)}$	0.02%	2.84%	33.70%	43.76%	19.68%
$RAM_{(4,5)}$	0.00%	0.04%	3.28%	27.66%	69.02%
$RAM_{(0,5)}$	0.00%	0.00%	0.00%	1.12%	98.88%

(b) The rotation angle distribution in text representation space.

Figure 7: Detailed SAM and RAM Distribution of Language Encoders.

By observing the table in Table 7, we can find that more than 88% of the angle change between any two language representation vectors in the language representation space are between 0 and 10 degrees in the process of continual CLIP training, while only 20% are above 10 degrees. Moreover, less than 0.2% of the angle changes is above 20 degrees. Those angle change between 15-20 degrees also only account for about 1.5% of all images pairs. Similar to the visual representation space, the direction of the same sample in the language representation space of different training phases also has changed greatly. However, unlike most of the rotations in the vision representation space, which are distributed over 30 degrees, in the language space, the rotations in the representation space are mostly distributed between 20 and 30 degrees. Because of this difference, the alignment of the CLIP for different modalities of the same sample deviates during the continual training.

7.4 The detailed performance of the models at each training phase in Experiment A

In figure 8 , we show the effect of our framework Mod-X (CLIP_{Mod-X}) in each training phase and compare the performance with continual CLIP training strategies in Experiment A 5.3. From the results of multimodal retrieval at each training phase, we can find that our framework, Mod-X, still has a good performance on the past pre-training dataset COCO(5K) during the continual training on the Flickr30K dataset. At each training phase, the $R@1$ results of CLIP_{Mod-X} on COCO(5K) did not show a significant drop, and the gap with the initial accuracy (CLIP_0) remained at $\pm 1\%$. In addition to this, by comparing the retrieval performance of the CLIP_{ct} and CLIP_{Mod-X} on the current training data domain (Flickr30K), it can be found that the CLIP_{Mod-X} is also significantly better than CLIP_{ct} in continual fitting the current data domain. The low performance of traditional regularization methods EWC also shows that continual multimodal training is more complex than single-modal supervised training.

Figure 8: The performance of different training strategies in each training phase in Experiment A.

7.5 THE DETAILED PERFORMANCE OF THE MODELS AT EACH TRAINING PHASE IN EXPERIMENT B

In figure 9, we show the effect of our framework Mod-X (CLIP_{Mod-X}) in each training phase in large-scale continual training settings (the Experiment B 5.4).

Figure 9: The performance of different training strategies in each training phase in Experiment B.

Comparing the $R@1$ results of the three continual training strategies at each training phase, we can clearly see that our Mod-X framework performance in each training phase is stabilized. As the training phase continues to rise, the performance of the Mod-X improves relative to the initial pre-training results (initial). The Image-Text and Text-Image $R@1$ results on COCO(5K) had risen by 1.7% and 0.5% points, respectively. And the gap of Image-Text $R@1$ results on the Flickr30K(1K) between CLIP_{jt} and CLIP_{Mod-X} narrowed from 6.3% to 2.0%. The performance of Text-Image $R@1$ on Flickr30K(1K) also improved to 25.98% from 23.44%. Conversely, the ability of cognition alignment in CLIP_{ct} and CLIP_{EWC} are lost in the continual large-scale training. This results in verifying that our framework Mox-X can iterate under continual large-scale training and can maintain or even improve the model's cognitive ability of past entity concepts.

7.6 THE PERFORMANCE OF MOX-X IN "FINE-TUNING" THE OPENAI'S CLIP

In this subsection, we simulate continual CLIP training on the joint-dataset (COCO and Flickr30K) based on OpenAI's pre-trained model CLIP_{vit32} with ViT-32/B vision encoder. We set the CLIP_{vit32}

as the initial model in the continuous training process and divide the joint-dataset (COCO and Flickr30K) into five sub-datasets uniformly and randomly to simulate streaming data. Because the pre-training datasets of $CLIP_{vit32}$ are not available, we train $CLIP_{vit32}$ on the joint-dataset to get the model $CLIP_{ub}$ as an upper bound for the performance of continual training. We apply our framework Mod-X in this setting and compare the final multimodal retrieval results with $CLIP_{ct}$, which is just continual training without any other operations, in Table 4.

Model	Image-Text Retrieval(%)						Text-Image Retrieval(%)					
	Flickr30k(1K)			COCO(5K)			Flickr30k(1K)			COCO(5K)		
	$R@1$	$R@5$	$R@10$	$R@1$	$R@5$	$R@10$	$R@1$	$R@5$	$R@10$	$R@1$	$R@5$	$R@10$
$CLIP_{vit32}$	77.7	94.5	98.3	50.1	74.6	83.0	58.9	83.5	90.1	30.2	55.6	66.7
$CLIP_{ct}$	74.7	92.6	96.5	36.3	60.6	71.2	61.7	84.8	91.2	24.6	47.8	59.1
$CLIP_{Mod-X}$	**80.0**	**94.4**	**97.1**	**54.8**	**80.8**	**88.6**	**65.2**	**88.2**	**92.9**	**40.5**	**68.7**	**78.8**
$CLIP_{ub}$	77.9	93.0	96.4	53.3	80.2	87.9	63.2	86.4	91.9	38.7	66.9	77.7

Table 4: The final multimoal retrieval performance of the $CLIP_{ct}$ and $CLIP_{Mod-X}$ based on OpenAI's $CLIP_{vit32}$ with VIT-32/B vision encoder.

The performance of our framework Mod-X is still better than $CLIP_{ct}$ on all of the evaluation settings. Compare the $R@1$ results on the test set Flickr30K(1K). We can find that $CLIP_{Mod-X}$ not only surpasses the initial results, 2.3% points and 6.3% points higher than $CLIP_{vit32}$ but also shows higher accuracy than the upper bound $CLIP_{up}$, although this is not a strict upper bound. The results on COCO(5K) also illustrate that our framework not only resists the cognitive disorder of the model but also fits the new data domain better than $CLIP_{ct}$.

7.7 THE REPRESENTATION QUALITY OF VISION ENCODERS DURING CONTINUAL CLIP TRAINING

In Section 3, based on the distribution Table 2(b), we inference that the topology of the visual representation of the $CLIP_{ct}$ changes slowly during the continual CLIP training. Due to the topology of the representation space is correlated with the quality of the model's representation, so we use the linear evaluation method, commonly used in self-supervision Oord et al. (2018); He et al. (2020), to detect the quality of the model's vision encoders to verify our suppose.By fixing the vision encoder, retrain a single Linear layer, which is connected behind the vision encoder, based on the ImageNet Deng et al. (2009) training set and evaluate its top-1 accuracy on the ImageNet test set to represent the vision encoder's representation quality.

7.7.1 THE CHANGES IN THE REPRESENTATION QUALITY OF VISUAL ENCODERS IN EXPERIMENT A.

This section discusses the representation quality of the CLIP's visual encoders in Experiment A. As shown in Figure 10, we calculate the vision encoders' linear evaluation in different training phases.

Figure 10: The changes in the representation quality of visual encoders in Experiment A.

Observing the changing trends in the linear evaluation accuracy of each training phase, we can find that the representation quality of the vision encoder in $CLIP_{cl}$ gradually decreases as the training phase increases. The top-1 accuracy in the ImageNet test set dropped from 30.1% to 28.1%, which is consistent with our conjecture 3.2.1. Compared to the decline in multimodal retrieval, the decrease in the quality of visual representations appears to be negligible. In addition, by comparing the results of $CLIP_{Mod-X}$ and $CLIP_{jt}$, we can find that our Mod-X framework can not only help the model fit new image-text samples but also improve the representation quality of the modal encoders within the CLIP. The top-1 accuracy of the vision encoder in $CLIP_{Mod-X}$ improved from 30.1% to 32.0%. All of this also illustrates that the quality of the extractor representation is not precisely positively correlated with the cognitive ability of the model.

7.7.2 THE CHANGES IN THE REPRESENTATION QUALITY OF VISUAL ENCODERS IN EXPERIMENT B.

This section discusses the representation quality of the CLIP's visual encoders in Experiment B. As shown in Figure 11, we calculate the vision encoders' linear evaluation in different training phases.

Figure 11: The changes in the representation quality of visual encoders in Experiment B.

Due to the continual large-scale training, the representation quality in $CLIP_{ct}$ has fallen off a cliff. The trend is similar to its performance on multimodal retrieval. Although our Mod-X framework maintains the quality of the modal encoders and the top-1 accuracy of vision encoders increased to 36% from 34.25%, the gap between $CLIP_{jt}$ still has 4%. We think how to shorten this gap will become a question worth considering.