On the Global Convergence Rates of Decentralized Softmax Gradient Play in Markov Potential Games

Abstract

Softmax policy gradient is a popular algorithm for policy optimization in single-agent reinforcement learning, particularly since projection is not needed for each gradient update. However, in multi-agent systems, the lack of central coordination introduces significant additional difficulties in the convergence analysis. Even for a stochastic game with identical interest, there can be multiple Nash Equilibria (NEs), which disables proof techniques that rely on the existence of a unique global optimum. Moreover, the softmax parameterization introduces non-NE policies with zero gradient, making it difficult for gradient-based algorithms in seeking NEs. In this paper, we study the finite time convergence of decentralized softmax gradient play in a special form of game, Markov Potential Games (MPGs), which includes the identical interest game as a special case. We investigate both gradient play and natural gradient play, with and without $\log$-barrier regularization. The established convergence rates for the unregularized cases contain a trajectory dependent constant that can be *arbitrarily large*, whereas the $\log$-barrier regularization overcomes this drawback, with the cost of slightly worse dependence on other factors such as the action set size. An empirical study on an identical interest matrix game confirms the theoretical findings.

1 Introduction

Multi-agent systems encounter vast application in real world scenarios, such as network routing [33, 7], social and economic decision making [34, 28], and robotic swarms [21, 13]. In these problems, a system consists of a group of agents interacting in a shared environment. Given the recent success of reinforcement learning (RL), increasing attention has been drawn to the possibility of applying RL algorithms, such as policy gradient, to multi-agent systems. However, the theoretical foundations for multi-agent reinforcement learning (MARL) remain limited. Unlike single-agent RL, the actions of other agents affect the dynamics and the decision making outcome for each individual in the system, raising additional theoretical challenges when analyzing joint performance.

The stochastic game (SG) is a classical multi-agent model that has received extensive attention in recent MARL studies. In a stochastic game, the environment is represented by a state space that evolves based on the joint actions of agents. Each agent in a stochastic game tries to maximize its own total reward by making decisions *independently*, based on state information shared between agents. The stochastic game model was first introduced in [29], with a series of followup works proposing NE-seeking algorithms, particularly in the RL setting (e.g. [20, 4, 30, 5, 16, 36] and citations therein). Given recent progress in the underlying theory of RL, many recent works have investigated finite time iteration and sample complexity for learning NE or other general equilibria notions, such as correlated and coarse correlated equilibria (e.g. [31]).

There are different types of SGs, some with attributes that merit special attention; for example, two-player zero sum games [3, 8], which are widely used to model two player competitive games

such as GO. In this paper, we will focus on another type of SG, the Markov potential game (MPG) [22, 26, 37, 17], which includes the identical interest game as a special case. The structure of a MPG enables efficient learning through the use of gradient-based algorithms such as gradient play. Recent work [37, 17] has focused on the iteration and sample complexity of finding a NE in an MPG under the *direct* policy parameterization, which is not practical in most real world scenarios, given the cost of projecting back to the probability simplex on every iteration. This drawback has motivated consideration of the *softmax* parameterization, which bypasses the projection step in the gradient update, and is perhaps the most popular approach to parameterizing policies in practice. [10] have studied natural gradient play for MPG under softmax parameterization, but only address asymptotic behavior and leave finite time complexity open.

From the perspective of analysis and practical performance, the extension from the direct to the softmax parameterization in policies is nontrivial. Even in the single agent case, as shown by [2, 23], there are policies in the softmax parameterization that have near-zero gradient and yet are far from being globally optimal, which creates difficulty for a gradient-based algorithm to escape suboptimal points. A similar issue exists for MPGs: due to the more complex interaction between agents, there is even a greater set of policies that obtain small gradient norm but are far from a NE. Based on our analysis and numerical results, even for natural gradient play—which is known to enjoy dimension free convergence in single agent learning [2]—we find in the multiagent setting that it can still become stuck in these undesirable regions. Such evidence suggests that preconditioning according to the Fisher information matrix is not sufficient to ensure fast convergence in multi-agent learning. A stronger form of regularization is required, which motivates the introduction of $\log$-barrier regularization to avoid undesirable regions of policy space.

Algorithm	Single-agent MDP	Multi-agent MPG
Gradient play, direct parameterization	$O\left(\frac{|\mathcal{A}|M^2}{(1-\gamma)^4\epsilon^2}\right)$ [2]	$O\left(\frac{(\phi_{\max}-\phi_{\min})\sum_{i=1}^n|\mathcal{A}_i|M^2}{(1-\gamma)^4\epsilon^2}\right)$ [37, 17]
Gradient play, softmax parameterization	$O\left(\frac{M^2}{(1-\gamma)^4c^2\epsilon}\right)$ [23]	$\boldsymbol{O\left(\frac{n\max_i|\mathcal{A}_i|(\phi_{\max}-\phi_{\min})M^2}{(1-\gamma)^4c^2\epsilon^2}\right)}^{\boldsymbol{*}}$
Natural gradient play, softmax parameterization	$O\left(\frac{1}{(1-\gamma)^2\epsilon}\right)$ [2]	$\boldsymbol{O\left(\frac{n(\phi_{\max}-\phi_{\min})^2M}{(1-\gamma)^3c\epsilon^2}\right)}^{\boldsymbol{*}}$
Gradient play + $\log$-barrier reg., softmax parameterization	$O\left(\frac{|\mathcal{A}|^2M^2}{(1-\gamma)^4\epsilon^2}\right)$ [2]	$\boldsymbol{O\left(\frac{n\max|\mathcal{A}_i|^2(\phi_{\max}-\phi_{\min})M^2}{(1-\gamma)^4\epsilon^2}\right)}$
Natural gradient play + $\log$-barrier reg, softmax parameterization	Unknown	$\boldsymbol{O\left(\frac{n\max_i|\mathcal{A}_i|(\phi_{\max}-\phi_{\min})M^2}{(1-\gamma)^4\epsilon^2}\right)}$

Table 1: Summary of known convergence rate results for gradient based methods in Markov decision processes (MDPs) and MPGs respectively. The new results proved in this paper for MPGs are displayed in bold font. Complexity bounds with '*' depend on an additional assumption on the MPG (See Theorem 2 and 5). The definitions of variables M and c appearing in some bounds can be found in (5) and (11). Note that the definition of M is slightly different from the "distribution mismatch coefficient" D_∞ defined in [2] (see more details in descriptions that follows Assumption 1). To make the complexity results more comparable, we slightly modify and re-derive the results in [2, 23, 37, 17].

Our contribution: In this paper, we provide *finite time* iteration complexity results for gradient and natural gradient play under the softmax parameterization, considering both unregularized and $\log$-barrier regularized dynamics. To the best of our knowledge, these are the first such results for MPGs under the softmax parameterization. We summarize our new results and compare them to existing results for the direct parameterization and to the corresponding single agent cases in Table 1. These findings suggest that regularization is crucial for obtaining fast convergence to a NE under the softmax parameterization in a MPG. In Table 1, the results for the two unregularized algorithms in the multi-agent case rely on the assumption that the set of stationary policies is isolated (which is also assumed in [10] when establishing the asymptotical convergence for NPG), and the corresponding complexity bounds contain an initialization dependent factor c. By contrast, the $\log$-barrier regularized algorithms overcome both drawbacks, but as a tradeoff, their bounds incur a slightly worse dependence on $|\mathcal{A}_i|$ and M. We observe numerically that the $\log$-barrier regularized algorithms are indeed more robust against becoming trapped near undesirable non-NE stationary points. Our results also convey the following two additional messages. First, finding the NE of a multi-agent MPG is harder than finding the global optimum of a Markov decision process (MDP), because multi-agent learning suffers greater

75 risk of becoming trapped near undesirable stationary points. Our complexity bounds also indicate
76 that, for MPGs, gradient-based algorithms exhibit complexities that scale with $O(\frac{1}{\epsilon^2})$, which is worse
77 than $O(\frac{1}{\epsilon})$ [2] or even the exponential rate [15, 24, 6] obtainable in the single agent case. Second,
78 natural gradient play outperforms gradient play counterparts, suggesting that natural gradient play
79 captures useful information about the geometry of the parameter space that helps accelerate the
80 learning process.

2 Problem settings

82 We consider an infinite time horizon n-agent stochastic game (SG, [29]) $\mathcal{M} = (N, \mathcal{S}, \mathcal{A} = \mathcal{A}_1 \times$
83 $\ldots \times \mathcal{A}_n, P, r = (r_1, \ldots, r_n), \ \gamma, \rho)$ which is specified by an agent set $N = \{1, 2, \ldots, n\}$, a finite
84 state space $\mathcal{S}$, a finite action space $\mathcal{A}_i$ for each agent $i \in N$, a transition model P (such that
85 $P(s'|s, a) = P(s'|s, a_1, \ldots, a_n)$ is the probability of transitioning into state s' upon taking action
86 $a := (a_1, \ldots, a_n)$ in state s where $a_i \in \mathcal{A}_i$ is action of agent i), a reward function $r_i : \mathcal{S} \times \mathcal{A} \to [0, 1]$
87 for each agent i, a discount factor $\gamma \in [0, 1)$, and an initial state distribution ρ over $\mathcal{S}$. We use $s(t) \in \mathcal{S}$
88 to denote the state at time step t, and $a(t) = (a_1(t), \ldots, a_n(t)) \in \mathcal{A}$ to denote the total action.

89 A stochastic policy $\pi : \mathcal{S} \to \Delta(\mathcal{A})$ (where $\Delta(\mathcal{A})$ is the probability simplex over $\mathcal{A}$) specifies a
90 strategy, where agents choose their actions *jointly* based on the current state in a stochastic fashion; i.e.
91 $\Pr(a(t)|s(t)) = \pi(a(t)|s(t))$. A *decentralized* stochastic policy is a special subclass of stochastic
92 policies with $\pi = \pi_1 \times \ldots \times \pi_n$, such that $\pi_i : \mathcal{S} \to \Delta(\mathcal{A}_i)$, where π_i is agent i's own local
93 policy. For decentralized stochastic policies, each agent takes its action based on the current state s
94 *independently of* other agents' action choices; i.e.,

$$\Pr(a(t)|s(t)) = \pi(a(t)|s(t)) = \prod_{i=1}^{n} \pi_i(a_i(t)|s(t)).$$

95 For notation simplicity, we define $\pi_I(a_I|s) := \prod_{i \in I} \pi_i(a_i|s)$, where $I \subseteq N$ is an index set. Further,
96 we use the notation $-i$ to denote the index set $N \backslash \{i\}$. In this paper we focus on tabular softmax
97 parameterization for a policy, where policy $\pi_\theta = (\pi_{\theta_1}, \ldots, \pi_{\theta_n})$ is parameterized by a set of
98 parameters $\theta = (\theta_1, \ldots, \theta_n)$, with $\theta_i = \{\theta_{s,a_i}\}_{s \in \mathcal{S}, a_i \in \mathcal{A}_i}$, and where

$$\pi_{\theta_i}(a_i|s) = \frac{\exp(\theta_{s,a_i})}{\sum_{a_i'} \exp(\theta_{s,a_i'})}. \tag{1}$$

99 We denote agent i's total reward starting from initial states $s(0) \sim \rho$ as: $J_i(\theta) :=$
100 $\mathbb{E}_{s(0) \sim \rho} \left[\sum_{t=0}^{\infty} \gamma^t r_i(s(t), a(t)) \big| \pi_\theta, s(0) = s \right]$. Agent i's objective is to maximize its own total re-
101 ward J_i. A Nash equilibrium (NE) is often used to characterize the equilibrium (a joint policy) where
102 no agent has a unilateral incentive to deviate from it.

Definition 1. *(Nash equilibrium) A policy* $\theta^* = (\theta_1^*, \ldots, \theta_n^*)$ *is called a (Markov perfect) Nash*
104 *equilibrium (NE) if*
$$J_i(\theta_i^*, \theta_{-i}^*) \geq J_i(\theta_i', \theta_{-i}^*), \quad \forall \theta_i', \quad i \in N \tag{2}$$
105 *Further, we define the 'NE-gap' of a policy* θ *to be:*
$$\texttt{NE-gap}_i(\theta) := \sup_{\theta_i'} J_i(\theta_i', \theta_{-i}) - J_i(\theta_i, \theta_{-i}); \quad \texttt{NE-gap}(\theta) := \max_i \texttt{NE-gap}_i(\theta).$$

106 *A policy* θ *is an* ϵ*-Nash equilibrium if:* $\texttt{NE-gap}(\theta) \leq \epsilon$.

We define the value function with respect to stage cost r_i as:

$$V_i^\theta(s) := \mathbb{E}\left[\sum_{t=0}^{\infty} \gamma^t r_i(s(t), a(t)) \big| \pi_\theta, s(0) = s \right].$$

107 We define agent i's Q-function and advantage function $Q_i^\theta, A_i^\theta : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$,

$$Q_i^\theta(s, a) := \mathbb{E}\left[\sum_{t=0}^{\infty} \gamma^t r_i(s(t), a(t)) \big| \pi_\theta, s(0) = s, a(0) = a \right], \quad A_i^\theta(s, a) := Q_i^\theta(s, a) - V_i^\theta(s).$$

108 We further define agent i's *'averaged' Q-function* $\overline{Q_i^\theta} : \mathcal{S} \times \mathcal{A}_i \to \mathbb{R}$ and *'averaged' advantage-*
109 *function* $\overline{A_i^\theta} : \mathcal{S} \times \mathcal{A}_i \to \mathbb{R}$ as:

$$\overline{Q_i^\theta}(s, a_i) := \sum_{a_{-i}} \pi_{\theta_{-i}}(a_{-i}|s) Q_i^\theta(s, a_i, a_{-i}), \quad \overline{A_i^\theta}(s, a_i) := \sum_{a_{-i}} \pi_{\theta_{-i}}(a_{-i}|s) A_i^\theta(s, a_i, a_{-i}).$$

110 Finally, define the *discounted state visitation distribution* d_θ of a policy π_θ given an initial state
111 distribution ρ as:
$$d_\theta(s) := \mathbb{E}_{s(0) \sim \rho}(1 - \gamma) \sum_{t=0}^{\infty} \gamma^t \Pr^\theta(s(t) = s|s(0)), \tag{3}$$

where $\Pr^\theta(s(t) = s|s(0))$ is the state visitation probability that $s(t) = s$ when executing π_θ starting at state $s(0)$. From the policy gradient theorem [32], we have that (proof given in Appendix B):

$$\frac{\partial J_i(\theta)}{\partial \theta_{s,a_i}} = \frac{1}{1-\gamma} d_\theta(s) \pi_{\theta_i}(a_i|s) \overline{A_i^\theta}(s, a_i). \tag{4}$$

For the remainder of the paper, we make the following assumptions on the stochastic games we study.

Assumption 1. *The stochastic game $\mathcal{M}$ satisfies:* $\inf_\theta \min_{s \in \mathcal{S}} d_\theta(s) > 0$.

Assumption 1 requires that every state is visited with positive probability for any policy, which is a standard assumption for convergence proofs in the RL literature (e.g. [2, 23]). We will use M to denote the following quantity
$$M := \sup_\theta \max_s \frac{1}{d_\theta(s)}. \tag{5}$$

Note that M can be viewed as a measure of exploration sufficiency in the stochastic game, which is slightly different from the "distributional mismatch coefficient" introduced in [2] defined by $\sup_{\theta,\theta'} \max_s \frac{d_{\theta'}(s)}{d_\theta(s)}$; however, both can be upper bounded by $\max_s \frac{1}{(1-\gamma)\rho(s)}$.

We primarily focus on the following subclass of stochastic games in this paper:

Definition 2. *A stochastic game is called a Markov potential game (MPG, [35, 22, 37, 17, 25]) if there exists a potential function $\phi : \mathcal{S} \times \mathcal{A}_1 \times \cdots \times \mathcal{A}_n \to \mathbb{R}$ such that for any agent i and any pair of policy parameters $(\theta_i', \theta_{-i}), (\theta_i, \theta_{-i})$:*

$$\mathbb{E}\left[\sum_{t=0}^\infty \gamma^t r_i(s(t), a(t)) \big| \pi = (\theta_i', \theta_{-i}), s(0) = s\right] - \mathbb{E}\left[\sum_{t=0}^\infty \gamma^t r_i(s(t), a(t)) \big| \pi = (\theta_i, \theta_{-i}), s(0) = s\right]$$
$$= \mathbb{E}\left[\sum_{t=0}^\infty \gamma^t \phi(s(t), a(t)) \big| \pi = (\theta_i', \theta_{-i}), s(0) = s\right] - \mathbb{E}\left[\sum_{t=0}^\infty \gamma^t \phi(s(t), a(t)) \big| \pi = (\theta_i, \theta_{-i}), s(0) = s\right], \forall s. \tag{6}$$

Without loss of generality, we assume that $\phi_{\min} \leq \phi(s, a) \leq \phi_{\max}$ for all (s, a). The definition of MPG is a generalization of the notion potential game in the one-shot setting [27]. Note that identical reward game where agents share a same reward function naturally satisfies the above condition and serves as one important special case of MPG. For non-identical reward settings, [22, 11] found that continuous MPGs can model applications such as the great fish war [18], the stochastic lake game [9], medium access control [22] etc. For tablular MPGs, [37, 17] also discuss necessary/sufficient conditions that implies a MPG, as well as its application and counterexamples.

Given a MPG, we define the *total potential function* Φ as:

$$\Phi(\theta) := \mathbb{E}_{s(0) \sim \rho}\left[\sum_{t=0}^\infty \gamma^t \phi(s(t), a(t)) \big| \pi_\theta, s(0) = s\right].$$

Given the property in (6), it is straightforward to verify that the NE condition (2) is equivalent to $\Phi(\theta_i^*, \theta_{-i}^*) \geq \Phi(\theta_i', \theta_{-i}^*), \forall \theta_i', i \in N$ and that for the policy gradient, $\frac{\partial J_i(\theta)}{\partial \theta_{s,a_i}} = \frac{\partial \Phi(\theta)}{\partial \theta_{s,a_i}}$ for all i, s, a_i.

Remark 1 (**Differences between MPG and single-agent/centralized MDP**). Because of the existence of the total potential function Φ, it is natural to ask whether MPG renders the multi-agent policy gradient similar to single agent policy gradient and thus results and analysis tools developed for single agent policy gradient in e.g., [2, 23] would be easily extended to the multiagent case. Unfortunately, this is not the case. To illustrate how it differs from single-agent/centralized case, we can focus on the special type of MPGs where every agent has the same reward function, namely the identical interest case. In the single agent/centralized case, there is a unique global optimal solution which corresponds to the convergent stationary policy. However, in the multiagent case, even if the rewards are identical, because the policy is *decentralized*, i.e., agents taking *independent* policies $\pi := \pi_1 \times \ldots \times \pi_n$, we loose the connection between stationary policies and optimal policies. As we shown later, the convergent stationary policies are Nash equilibria, which are unfortunately non-unique even for the identical interest case. Moreover, a key condition that is used in establishing the convergence rate, Łojasiewicz condition (Lemma 3), is also much weaker for the multiagent case compared to single agent [23]: the left hand side is the *Nash gap* $\max_{i,\theta_i^*} \Phi(\theta_i^*, \theta_{-i}) - \Phi(\theta)$ instead of the *optimality gap* $\max_{\theta^*} \Phi(\theta^*) - \Phi(\theta)$). Note that zero Nash gap does not imply zero optimality gap, as there exists *many* NEs of *different* values. These differences disable many proof technique used for single agent case and make the analysis harder and lead to different performance results, as demonstrated in the rest of the paper.

3 Unregularized gradient play

We first investigate the convergence to NE for gradient and natural gradient play, respectively. Under the softmax parameterization, the two schemes are given by

$$\text{Gradient Play:} \quad \theta_i^{(t+1)} = \theta_i^{(t)} + \eta \nabla_{\theta_i} J_i(\theta_i^{(t)}) \tag{7}$$

$$\text{Natural Gradient Play:} \quad \theta_i^{(t+1)} = \theta_i^{(t)} + \eta F_i(\theta^{(t)})^\dagger \nabla_{\theta_i} J_i(\theta_i^{(t)}) \tag{8}$$

where $\dagger$ denotes the Moore-Penrose inverse and $F_i(\theta)$ is the Fisher information matrix for π_{θ_i}:

$$F_i(\theta) := \mathbb{E}_{s \sim d_\theta(\cdot)} \mathbb{E}_{a_i \sim \pi_{\theta_i}(\cdot|s)} \left[\nabla_{\theta_i} \log \pi_{\theta_i}(a_i|s) \nabla_{\theta_i} \log \pi_\theta(a_i|s)^\top \right].$$

For notational simplicity, we abbreviate the variables $d_{\theta^{(t)}}$, $A_i^{\theta^{(t)}}$ and $\overline{A_i^{\theta^{(t)}}}$ as $d^{(t)}$, $A_i^{(t)}$ and $\overline{A_i^{(t)}}$ respectively; and denote $\pi_{\theta^{(t)}}(a|s)$ and $\pi_{\theta_i^{(t)}}(a_i|s)$ as $\pi^{(t)}(a|s)$ and $\pi_i^{(t)}(a_i|s)$ respectively. For the softmax parameterization, we can establish the equivalence of natural gradient play and soft Q-learning [12], formally stated in the following lemma.

Lemma 1. *(Proof given in Appendix C) Natural gradient play is equivalent to*

$$\pi_i^{(t+1)}(a_i|s) \propto \pi_i^{(t)}(a_i|s) \exp\left(\eta \overline{A_i^{(t)}}(s, a_i)/(1-\gamma) \right) \tag{9}$$

3.1 Asymptotic convergence to Nash Equilibrium

We first establish asymptotic convergence to NE for gradient and natural gradient play. Compared to the direct parameterization (see, e.g. [37, 17]), the convergence analysis for the softmax parameterization is more challenging due to the existence of non-NE stationary policies; for example, any deterministic policy has zero gradient whether or not it is a NE. Meanwhile, compared to global convergence in the single agent setting [2], the coupling of the agent dynamics in the multi-agent setting introduces extra difficulty as discussed in Remark 1. Nevertheless, using similar techniques as [2], we prove the following the asymptotic convergence result.

Theorem 2. *(Proof given in Appendix D.1) Suppose Assumption 1 holds and that the stationary policies are isolated, gradient play (7) with $\eta \leq \frac{(1-\gamma)^3}{6n}$ guarantees that $\lim_{t \to +\infty} \theta^{(t)} = \theta^{(\infty)}$, where $\theta^{(\infty)}$ is a NE. The same argument also holds for natural gradient play (9) with $\eta \leq \frac{(1-\gamma)^2}{2n(\phi_{\max} - \phi_{\min})}$.*

The proof of Theorem 2 resembles the technique used in [2] for the single agent case, where the additional assumption on the isolated stationary policies is introduced due to some specific technical difficulties encountered in multi-agent learning (see more discussion in Appendix D.1, which is also introduced in [10] for establishing the asymptotic convergence of NPG. We believe it is a conservative condition for ensuring the asymptotic convergence. It remains an interesting open question to establish convergence without this assumption.

3.2 Convergence fate

We next consider a convergence rate analysis for gradient play and natural gradient play. Corresponding results for the single-agent setting can be found in [23] (for gradient play) and [2, 15, 24] (for natural gradient play). Some aspects of these analyses can be carried over to the multi-agent MPG setting; however, as will be discussed later, there are several fundamental differences that make the multi-agent case more challenging.

We begin by establishing a non-uniform Łojasiewicz condition (also known as gradient domination) for stochastic games.

Lemma 3. *(Non-uniform Łojasiewicz inequality; proof given in Appendix D.2) Define*

$$M(\theta) := \max_s \frac{1}{d_\theta(s)}, \quad c(\theta) := \min_s \sum_{a_i^* \in \operatorname{argmax}_{a_i} \overline{Q_i^\theta}(s, a_i)} \pi_{\theta_i}(a_i^*|s). \tag{10}$$

Then we have that

$$\text{NE-gap}_i(\theta) \leq \frac{\sqrt{|\mathcal{A}_i|} M(\theta)}{c(\theta)} \|\nabla_{\theta_i} J_i(\theta)\|_2.$$

The Łojasiewicz condition (gradient domination) implies that the NE-gap of a policy can be bounded by the norm of its gradient, whereas the term 'non-uniform' refers to the factor $\frac{\sqrt{|\mathcal{A}_i|}M(\theta)}{c(\theta)}$, which cannot be bounded uniformly for all θ. The counterpart of Lemma 3 for a single-agent MDP was first introduced in [23], where they derive a similar relationship between the global optimality gap and the gradient norm. They also point out that the non-uniform term can be arbitrarily large for certain θ (e.g. any θ that corresponds to a deterministic policy), which implies that a θ with gradient norm close to zero is not necessarily near a global optimum. Similarly, for multiagent MPG, a θ with gradient norm close to zero is not necessarily near a NE (see Figure 1(a)-(c)).

To establish a valid convergence rate, we leverage the asymptotic convergence in Theorem 2 to show that the non-uniform term can be upper-bounded by a constant that depends on the initialization. Firstly, we establish the following lemma.

Lemma 4. *For any θ^* that is a NE, $c(\theta^*) = 1$.*

Combining Theorem 2 and Lemma 4, we know that $c(\theta^{(t)})$ asymptotically converges to 1 for (natural) gradient play, and since $c(\theta^{(t)}) > 0$ for any softmax policy (because $\pi_{\theta_i}(a_i|s) > 0$), this gives

$$c := \inf_t c(\theta^{(t)}) > 0. \tag{11}$$

We are now ready to give formal convergence rates for gradient and natural gradient play respectively.

Theorem 5. *(Gradient play and natural gradient play; proof given in D.3, D.4) Suppose Assumption 1 holds and that the stationary policies are isolated, gradient play (7) with $\eta = \frac{(1-\gamma)^3}{6n}$ will guarantee that for all T,*

$$\frac{\sum_{t=0}^{T-1} \texttt{NE-gap}(\theta^{(t)})^2}{T} \lesssim O\left(\frac{n \max_i |\mathcal{A}_i|(\phi_{\max} - \phi_{\min})M^2}{(1-\gamma)^4 c^2 T}\right), \tag{12}$$

Natural gradient play (9) with $\eta = \frac{(1-\gamma)^2}{2n(\phi_{\max}-\phi_{\min})}$ will guarantee that for all T,

$$\frac{\sum_{t=0}^{T-1} \texttt{NE-gap}(\theta^{(t)})^2}{T} \lesssim O\left(\frac{n(\phi_{\max} - \phi_{\min})^2 M}{(1-\gamma)^3 c T}\right). \tag{13}$$

Here $O(\cdot)$ hides constant factors, M and c are defined as in (5) and (11), respectively.

Proof in a glance: We provide a brief proof sketch for the convergence of gradient play. The analysis consists of two parts. The first part is to apply standard smooth nonconvex optimization techniques to show that the average of squared gradient norms scales as $O(\frac{1}{T})$. The second part is to link the gradient norm with the NE-gap via the non-uniform Łojasiewicz condition. To bound the NE-gap by the gradient norm *uniformly* along the trajectory, we need to take the maximum of the Łojasiewicz constant along the trajectory, i.e. $\sup_{t \leq T} \frac{\sqrt{|\mathcal{A}_i|}M(\theta^{(t)})}{c(\theta^{(t)})}$, which explains why $\frac{1}{c}$ and M show up in the bound. Note that the bound is only valid given the prior asymptotic convergence guarantee, without which $c = \inf_{t \leq T} c(\theta^{(t)})$ could be zero.

Discussion on $\frac{1}{c}$: The complexity results in Theorem 5 both depend on $\frac{1}{c}$. However, this term can become arbitrarily large. In fact, [19] show that c can be exponentially small in terms of the number of states $|\mathcal{S}|$ for a general finite MDP, even under uniform initialization, hence convergence can be very slow. This conclusion is also confirmed by numerical evidence. As pointed out by [23], even for single agent settings, policy gradient can get stuck at regions with small gradient yet far from being global optimal. Similar or even worse phenomena can be observed for multi-agent MPG, as shown in Figure 1(a)-(c): even for a single state game ($|\mathcal{S}| = 1$) with uniform initialization, unregularized gradient based algorithms can still enter regions with a relatively large NE-gap while the gradient norm and $c(\theta)$ are close to zero. For comparison, under similar conditions in the single agent case, i.e. $|\mathcal{S}| = 1$ with uniform initialization, [23] have proved that c is lower-bounded by $\frac{1}{|\mathcal{A}|}$, while for the multi-agent case c can be much smaller than $\frac{1}{\max_i |\mathcal{A}_i|}$ (see Figure 1(c)), indicating that multi-agent learning is harder than single-agent case.

More comparison with learning for single-agent MDP: For gradient play, we have established an iteration complexity of $O\left(\frac{n \max_i |\mathcal{A}_i|(\phi_{\max}-\phi_{\min})M^2}{(1-\gamma)^4 c^2 \epsilon^2}\right)$ to find an ϵ-NE, whereas [23] show a

complexity of $O\left(\frac{(\phi_{\max}-\phi_{\min})M^2}{(1-\gamma)^4 c^2 \epsilon}\right)$ to reach an ϵ-global optimum for policy gradient in a single agent MDP. The dependence on $\frac{1}{\epsilon}$ is better in the single agent case because of the existence of a global optimal policy π^* and optimal total reward J^*, which justify the definition of optimality gap $\delta_t = J(\theta^{(t)}) - J^*$. This, combined with the non-uniform Łojasiewicz condition which bounds δ_t by the gradient norm, allows one to use techniques from convex smooth analysis to show that δ_t is on the scale of $\frac{1}{t}$. By contrast, for multi-agent learning, there can be multiple NEs with different values, hence δ_t is ill-defined. Further, note that the NE-gap is different from the optimality gap, hence gradient ascent no longer guarantees monotonic decreasing of NE-gap (Figure 1(a)), and we can only exploit non-convex optimization techniques that yield $O(\frac{1}{\epsilon^2})$ complexities.

For the same reason, the rate of convergence we obtain for natural gradient play is $O\left(\frac{n(\phi_{\max}-\phi_{\min})^2 M}{(1-\gamma)^3 c\epsilon^2}\right)$, which is worse than the dimension free convergence rate of $O\left(\frac{1}{(1-\gamma)^2 \epsilon}\right)$ given in [2] for single-agent MDPs. (A better exponential convergence rate for natural PG has also been proved in [15, 24] with the exponential factor being problem dependent.) Nevertheless, the dependence on $\frac{1}{c}$, $\frac{1}{1-\gamma}$ and M is better than with gradient play, suggesting that the preconditioning of natural gradient play at least partially captures the geometry of the parameter space. We also note that the quadratic dependence on $(\phi_{\max} - \phi_{\min})$ might be a proof artifact. It remains an open question whether this can be reduced to a linear dependence.

4   Gradient play with $\log$-barrier regularization

The previous section has shown that, for unregularized objectives, the convergence rate for gradient based algorithms depends on a factor $\frac{1}{c}$ that can be arbitrarily large for bad initializations. This motivates us to investigate regularization, in hopes of removing the dependence on $\frac{1}{c}$. For this purpose, we consider $\log$-barrier regularization:

$$\widetilde{J}_i(\theta) = J_i(\theta) + \lambda \sum_{s,a_i} \log \pi_{\theta_i}(a_i|s).$$

Define:
$$\widetilde{\Phi}(\theta) = \Phi(\theta) + \lambda \sum_{i=1}^{n} \sum_{s,a_i} \log \pi_{\theta_i}(a_i|s). \tag{14}$$

It is not hard to verify that the gradient with respect to J_i is:

$$\frac{\partial \widetilde{J}_i(\theta)}{\partial \theta_{s,a_i}} = \frac{\partial \widetilde{\Phi}(\theta)}{\partial \theta_{s,a_i}} = \frac{1}{1-\gamma} d_\theta(s) \pi_{\theta_i}(a_i|s) \overline{A_i^\theta}(s,a_i) + \lambda - \lambda|\mathcal{A}_i| \pi_{\theta_i}(a_i|s).$$

Before analyzing the resulting algorithm we first discuss the motivation for this regularizer. First, note that for each agent, the additional regularizer only depends on an agent's own local policy, which is desirable for multiagent RL. As an alternative, one might impose regularization by choosing

$$\widetilde{\Phi}(\theta) = \Phi(\theta) + \lambda \mathbb{E}_{s \sim d_\theta(\cdot)} \sum_{i=1}^{n} \sum_{a_i} \log \pi_{\theta_i}(a_i|s);$$

i.e., so that the regularization weight imposed on a state s depends on the state visitation probability $d_\theta(s)$. However, in this case the gradient of the i-th agent $\nabla_{\theta_i} \widetilde{\Phi}(\theta)$ will not only depend on its own policy parameter θ_i, but also on other parameters of the other agents' policies θ_{-i}. Thus, running gradient based algorithms with such a regularization scheme can no longer be executed in a fully decentralized manner using local policy information. Therefore, we prefer regularization (14) which does not depend on $d_\theta(s)$. Second, we adopt the $\log$-barrier instead of entropy regularization to penalize small $\pi_i(a_i|s)$ values more strongly, since this is where the geometry becomes close to singular. Intuitively, the $\log$-barrier regularized gradient field repels the trajectory from singular regions more strongly, which in turn encourages better convergence properties. Although entropy regularization achieves fast exponential convergence in single agent learning [6, 23], for multi-agent learning, we haven't been able to obtain results as strong as the $\log$-barrier regularization, so we focus on $\log$-barrier regularization in this paper. It remains future work to determine whether entropy regularization can achieve the same, or even better convergence rates.

4.1   Gradient play

We first consider gradient play algorithm, i.e.,

$$\theta_i^{(t+1)} = \theta_i^{(t)} + \eta \nabla_{\theta_i} \widetilde{J}_i(\theta^{(t)}). \tag{15}$$

We start with the following lemma:

Lemma 6. *Suppose θ is such that $\|\nabla_{\theta_i} \widetilde{J}_i(\theta)\|_2 \leq \lambda$, then $\texttt{NE-gap}_i(\theta) \leq \lambda M |\mathcal{A}_i|$, where M is defined as in Assumption 1.*

Lemma 6 implies that any policy with gradient norm smaller than λ is also a $\lambda M \max_i |\mathcal{A}_i|$-NE. Thus by properly choosing λ, agents can find a ϵ-NE by running gradient play.

Theorem 7. *(Proof given in Appendix E.1) Under Assumption 1, for $\eta = \frac{(1-\gamma)^3}{6n + 2\lambda \max_i |\mathcal{A}_i|(1-\gamma)^3}$, and $\lambda = \frac{\epsilon}{M \max_i |\mathcal{A}_i|}$, let $\theta^{(0)}$ be the uniform random policy, i.e., $\theta^{(0)} = \mathbf{0}$, then running gradient play (15) for T steps, where $T \gtrsim O\left(\frac{n \max_i |\mathcal{A}_i|^2 (\phi_{\max} - \phi_{\min}) M^2}{(1-\gamma)^4 \epsilon^2} \right)$ will guarantee that $\min_{0 \leq t \leq T-1} \texttt{NE-gap}(\theta^{(t)}) \leq \epsilon$.*

Note that compared to the unregularized case in Theorem 5, it only requires Assumption 1, while the convergence rate is accelerated by eliminating the dependence on $\frac{1}{c}$. However, as a (worthy) tradeoff, the dependence on the action space size $\max_i |\mathcal{A}_i|$ now becomes quadratic. The key reason for these differences is that $\log$-barrier regularization assures that any policy with sufficiently small gradient norm cannot be close to the boundary of the probability simplex where the non-uniform Łojasiewicz constant is large. As a tradeoff, a $\lambda \max_i |\mathcal{A}_i| M$ bias is introduced as suggested in Lemma 6, i.e., $\log$-barrier regularization can find a $\lambda \max_i |\mathcal{A}_i| M$-NE at best. Thus to recover a ϵ-NE, the regularization constant λ must be smaller than $\frac{\epsilon}{\max_i |\mathcal{A}_i| M}$, which results in the quadratic dependence on $\max_i |\mathcal{A}_i|$.

4.2 Natural gradient play

In the unregularized setting, we have seen that natural gradient play enjoys a better convergence rate than gradient play, which motivates us to consider whether a similar advantage still holds for the regularized case. In this section we consider natural gradient play

$$\theta_i^{(t+1)} = \theta_i^{(t)} + \eta F_i(\theta^{(t)})^\dagger \nabla_{\theta_i} \widetilde{J}_i(\theta_i^{(t)}), \tag{16}$$

which is equivalent to (see the proof in Appendix C)

$$\pi_i^{(t+1)}(a_i|s) \propto \pi_i^{(t)}(a_i|s) \exp\left(\frac{\eta}{1-\gamma} \overline{A_i^{(t)}}(s, a_i) + \frac{\eta \lambda}{d^{(t)}(s)\pi_i^{(t)}(a_i|s)} - \frac{\eta \lambda |\mathcal{A}_i|}{d^{(t)}(s)} \right). \tag{17}$$

Theorem 8. *(Proof given in Appendix E.2) Under Assumption 1, for*

$$\eta = \min\left\{ \frac{1}{15\left(\frac{1}{(1-\gamma)^2} + \lambda |\mathcal{A}_i| M \right)}, \frac{1}{4\left(4\lambda \max_i |\mathcal{A}_i| M^2 + \frac{4M}{(1-\gamma)^2} + \frac{3nM}{(1-\gamma)^3} \right)} \right\}, \text{ the NPG scheme (17) will guarantee that}$$

$$\frac{\sum_{t=0}^{T-1} \texttt{NE-gap}(\theta^{(t)})}{T} \leq \frac{9\left(\widetilde{\Phi}(\theta^{(T)}) - \widetilde{\Phi}(\theta^{(0)}) \right)}{\eta \lambda T} + \lambda \max_i |\mathcal{A}_i| M,$$

Further, by setting $\lambda = \frac{\epsilon}{2 \max_i |\mathcal{A}_i| M}$, $\theta^{(0)} = \mathbf{0}$, for $T \gtrsim O\left(\frac{n \max_i |\mathcal{A}_i|(\phi_{\max} - \phi_{\min}) M^2}{(1-\gamma)^4 \epsilon^2} \right)$, we have

$$\frac{\sum_{t=0}^{T-1} \texttt{NE-gap}(\theta^{(t)})}{T} \leq \epsilon.$$

Compared with gradient play, natural gradient play manages to reduce the time complexity by a $\max_i |\mathcal{A}_i|$ factor. Further, gradient play can only guarantee the minimal NE-gap is smaller than ϵ, while natural gradient play can guarantee the average NE-gap along the trajectory smaller than ϵ. The key step in the proof is that natural gradient play can implicitly guarantee that $\pi_i^{(t)}(a_i|s) \geq \frac{\lambda}{4\left(\lambda |\mathcal{A}_i| M + \frac{1}{(1-\gamma)^2} \right)}$, $\forall t$, hence the ascent value $\Phi(\theta^{(t+1)}) - \Phi(\theta^{(t)})$ can be bounded by $\texttt{NE-gap}(\theta^{(t)})$ plus a $\lambda \max_i |\mathcal{A}_i| M$ bias term. To the best of our knowledge, this is the best time complexity bound obtained for the softmax parameterization in a MPG.

5 An Illustrative example

This section aims to gain a better understanding of the four gradient play algorithms, (7), (9), (15), and (17). To better justify our theoretical results and provide additional insights, we choose a carefully designed simple two-player game so that our theoretical results can be easily revealed from the

		$a_2=1$	$a_2=2$
$a_1=1$		-1	0.14
$a_1=2$		0.16	0.15
$a_1=3$		0.2	-1

Reward table

Figure 1: We consider a two-player identical reward matrix game as shown in the reward table. We run gradient play and natural gradient play (with and without $\log$-barrier regularization) with initial policies being the uniform distribution (i.e., $\pi_1 = [\frac{1}{3}, \frac{1}{3}, \frac{1}{3}]$, $\pi_2 = [\frac{1}{2}, \frac{1}{2}]$). The subfigures (a)-(d) show how the NE-gap$(\theta^{(t)})$, $\|\nabla_\theta \Phi(\theta^{(t)})\|_2$, $c(\theta^{(t)})$ (defined in (10)) and $\Phi(\theta^{(t)})$ change with each iteration respectively. In Figure (c), we zoom in on the $\log_{10} c(\theta)$ factor for natural gradient play. In Figure (d), we also zoom out the trajectory for running gradient play to iteration 2×10^4. Here the step sizes were chosen to be $\eta = 5$ while the regularization weight λ was chosen to be $\lambda = 0.003$. In consideration of numerical stability issues, we truncate the update step of natural gradient play with $\log$-barrier regularization by a maximum absolute value of 1 for each entry. For more numerical results and corresponding analysis see Appendix A.

empirical observations. However the four algorithms also works for settings with more agents. [1] Due to space limits, we defer the simulation with more agents in Appendix A.

The reward table as well as the performance of the four algorithms are shown in Figure 1. Comparing the $\log$-barrier regularized algorithms to the unregularized counterparts, one can see that the regularized dynamics converge faster but with a bias induced by the regularizer. This finding corroborates the analyses given in Theorem 7 and 8. By contrast, the unregularized dynamics are able to find a policy with zero NE-gap asymptotically, but tend to get stuck in regions where $c(\theta^{(t)})$ is very close to zero, as illustrated in Fig 1(a)(b). Specifically unregularized natural gradient play gets stuck around iteration 100-400 in a region where the gradient norm and $c(\theta^{(t)})$ are both close to zero while the NE-gap is not. This corroborates the finding in Lemma 3. Similar behavior can be observed for gradient play if we keep running the algorithm. In comparing the natural gradient play to gradient play algorithms, natural gradient play generally converges faster, which matches with our complexity analysis. However, natural gradient play with $\log$-barrier regularization can suffer from numerical instability due to the $1/\pi_i^{(t)}(a_i|s)$ term in the exponential factor. In this case, the stepsize needs to be chosen carefully. To bypass the numerical instability, we truncate the update step of natural gradient play with $\log$-barrier regularization by a maximum absolute value of 1 for each entry.

6 Discussions and conclusions

We have established finite time iteration complexity bounds for gradient and natural gradient play under the softmax parameterization, considering both unregularized and $\log$-barrier regularized dynamics, in the Markov potential game setting. To our best knowledge, this is the first concrete finite time global convergence result under the setting of softmax parameterization for MPGs. However, our work suffers from the following limitations: firstly, the paper mainly focuses on MPG settings, which limits its application to general-sum Markov games; secondly, convergence results for the unregularized case relies on an extra assumption that the stationary points are isolated; thirdly, for the regularized case, we consider $\log$-barrier regularization, which is admittedly a stronger regularization compared with entropy regularization which is more frequently used in practice. Some limitations are due to technical challenges, some might be caused by the fundamental difficulties of multi-agent learning. It remains interesting open questions to sharpen the analysis, derive similar or better bounds for entropy regularization, and to develop more fundamental understandings of multi-agent learning.

---

[1]Code can be found in https://anonymous.4open.science/r/NeurIPS2022-softmax-MPG-756E

References

[1] P.-A. Absil, R. Mahony, and B. Andrews. Convergence of the iterates of descent methods for analytic cost functions. *SIAM Journal on Optimization*, 16(2):531–547, 2005.

[2] A. Agarwal, S. M. Kakade, J. D. Lee, and G. Mahajan. On the theory of policy gradient methods: Optimality, approximation, and distribution shift, 2020.

[3] Y. Bai and C. Jin. Provable self-play algorithms for competitive reinforcement learning. In *International Conference on Machine Learning*, pages 551–560. PMLR, 2020.

[4] M. Bowling and M. Veloso. An analysis of stochastic game theory for multiagent reinforcement learning. Technical report, Carnegie-Mellon Univ Pittsburgh Pa School of Computer Science, 2000.

[5] L. Buşoniu, R. Babuška, and B. De Schutter. Multi-agent reinforcement learning: An overview. *Innovations in multi-agent systems and applications-1*, pages 183–221, 2010.

[6] S. Cen, C. Cheng, Y. Chen, Y. Wei, and Y. Chi. Fast global convergence of natural policy gradient methods with entropy regularization. *Operations Research*, 2021.

[7] R. Claes, T. Holvoet, and D. Weyns. A decentralized approach for anticipatory vehicle routing using delegate multiagent systems. *IEEE Transactions on Intelligent Transportation Systems*, 12(2):364–373, 2011.

[8] C. Daskalakis, D. J. Foster, and N. Golowich. Independent policy gradient methods for competitive reinforcement learning. *arXiv preprint arXiv:2101.04233*, 2021.

[9] W. D. Dechert and S. O'Donnell. The stochastic lake game: A numerical solution. *Journal of Economic Dynamics and Control*, 30(9-10):1569–1587, 2006.

[10] R. Fox, S. McAleer, W. Overman, and I. Panageas. Independent natural policy gradient always converges in markov potential games. *CoRR*, abs/2110.10614, 2021.

[11] D. González-Sánchez and O. Hernández-Lerma. *Discrete–time stochastic control and dynamic potential games: the Euler–Equation approach*. Springer Science & Business Media, 2013.

[12] T. Haarnoja, H. Tang, P. Abbeel, and S. Levine. Reinforcement learning with deep energy-based policies. In *International Conference on Machine Learning*, pages 1352–1361. PMLR, 2017.

[13] P. Iñigo-Blasco, F. Diaz-del Rio, M. C. Romero-Ternero, D. Cagigas-Muñiz, and S. Vicente-Diaz. Robotics software frameworks for multi-agent robotic systems development. *Robotics and Autonomous Systems*, 60(6):803–821, 2012.

[14] S. M. Kakade and J. Langford. Approximately optimal approximate reinforcement learning. In C. Sammut and A. G. Hoffmann, editors, *Machine Learning, Proceedings of the Nineteenth International Conference (ICML 2002), University of New South Wales, Sydney, Australia, July 8-12, 2002*, pages 267–274. Morgan Kaufmann, 2002.

[15] S. Khodadadian, P. R. Jhunjhunwala, S. M. Varma, and S. T. Maguluri. On the linear convergence of natural policy gradient algorithm. *arXiv preprint arXiv:2105.01424*, 2021.

[16] M. Lanctot, V. Zambaldi, A. Gruslys, A. Lazaridou, K. Tuyls, J. Pérolat, D. Silver, and T. Graepel. A unified game-theoretic approach to multiagent reinforcement learning. *arXiv preprint arXiv:1711.00832*, 2017.

[17] S. Leonardos, W. Overman, I. Panageas, and G. Piliouras. Global convergence of multi-agent policy gradient in markov potential games. *arXiv preprint arXiv:2106.01969*, 2021.

[18] D. Levhari and L. Mirman. The great fish war: An example using a dynamic cournot-nash solution. *Bell Journal of Economics*, 11(1):322–334, 1980.

[19] G. Li, Y. Wei, Y. Chi, Y. Gu, and Y. Chen. Softmax policy gradient methods can take exponential time to converge. *CoRR*, abs/2102.11270, 2021.

[20] M. L. Littman. Markov games as a framework for multi-agent reinforcement learning. In *Machine learning proceedings 1994*, pages 157–163. Elsevier, 1994.

[21] J. Liu and J. Wu. *Multiagent robotic systems*. CRC press, 2018.

[22] S. V. Macua, J. Zazo, and S. Zazo. Learning parametric closed-loop policies for markov potential games. *CoRR*, abs/1802.00899, 2018.

[23] J. Mei, C. Xiao, C. Szepesvari, and D. Schuurmans. On the global convergence rates of softmax policy gradient methods. In H. D. III and A. Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 6820–6829. PMLR, 13–18 Jul 2020.

[24] J. Mei, B. Dai, C. Xiao, C. Szepesvari, and D. Schuurmans. Understanding the effect of stochasticity in policy optimization. *Advances in Neural Information Processing Systems*, 34, 2021.

[25] D. Mguni. Stochastic potential games. *arXiv preprint arXiv:2005.13527*, 2020.

[26] D. Mguni, Y. Wu, Y. Du, Y. Yang, Z. Wang, M. Li, Y. Wen, J. Jennings, and J. Wang. Learning in nonzero-sum stochastic games with potentials. *arXiv preprint arXiv:2103.09284*, 2021.

[27] D. Monderer and L. S. Shapley. Potential games. *Games and economic behavior*, 14(1): 124–143, 1996.

[28] M. Roscia, M. Longo, and G. C. Lazaroiu. Smart city by multi-agent systems. In *2013 International Conference on Renewable Energy Research and Applications (ICRERA)*, pages 371–376. IEEE, 2013.

[29] L. S. Shapley. Stochastic games. *Proceedings of the national academy of sciences*, 39(10): 1095–1100, 1953.

[30] Y. Shoham, R. Powers, and T. Grenager. Multi-agent reinforcement learning: a critical survey. Technical report, Technical report, Stanford University, 2003.

[31] Z. Song, S. Mei, and Y. Bai. When can we learn general-sum markov games with a large number of players sample-efficiently?, 2021.

[32] R. S. Sutton, D. A. McAllester, S. P. Singh, Y. Mansour, et al. Policy gradient methods for reinforcement learning with function approximation. In *NIPs*, volume 99, pages 1057–1063. Citeseer, 1999.

[33] N. Tao, J. Baxter, and L. Weaver. A multi-agent, policy-gradient approach to network routing. In *In: Proc. of the 18th Int. Conf. on Machine Learning*. Citeseer, 2001.

[34] A. G. Ventre, A. Maturo, Š. Hošková-Mayerová, and J. Kacprzyk. *Multicriteria and Multiagent Decision Making with Applications to Economics and Social Sciences*, volume 305. Springer, 2013.

[35] S. Zazo, S. V. Macua, M. Sánchez-Fernández, and J. Zazo. Dynamic potential games with constraints: Fundamentals and applications in communications. *IEEE Transactions on Signal Processing*, 64(14):3806–3821, 2016.

[36] K. Zhang, Z. Yang, and T. Başar. Multi-agent reinforcement learning: A selective overview of theories and algorithms. *arXiv preprint arXiv:1911.10635*, 2019.

[37] R. Zhang, Z. Ren, and N. Li. Gradient play in multi-agent markov stochastic games: stationary points, convergence, and sample complexity. *CoRR*, abs/2106.00198, 2021.