Self-Improving Semantic Perception
for Indoor Localisation

Abstract: We propose a novel robotic system that can improve its perception during deployment. Contrary to the established approach of learning semantics from large datasets and deploying fixed models, we propose a framework in which semantic models are continuously updated on the robot to adapt to the deployment environments. By combining continual learning with self-supervision, our robotic system learns online during deployment without external supervision. We conduct real-world experiments with robots localising in 3D floorplans. Our experiments show how the robot's semantic perception improves during deployment and how this translates into improved localisation, even across drastically different environments. We further study the risk of catastrophic forgetting that such a continuous learning setting poses. We find memory replay an effective measure to reduce forgetting and show how the robotic system can improve even when switching between different environments. On average, our system improves by 60% in segmentation and 10% in localisation accuracy compared to deployment of a fixed model, and it maintains this improvement while adapting to further environments.

Keywords: continual learning, self-supervised learning, online learning

1 Introduction

Learning-based systems enable robots to partially understand the environment through, e.g., object detection or semantic classification [1, 2]. Such understanding is a key requirement to enable many complex robotic applications such as autonomous driving or mobile manipulation [3, 4]. However, mobile robots are deployed in increasingly unstructured environments, where learning-based systems often fail [5, 6]. Anticipation of a wide variety of environmental conditions is required for safe operation, however difficult if not impossible. Thus, robotic actors with a high degree of autonomy are required to adapt to unexpected and changing conditions for robust operation. Yet, deployment of learning-based systems typically means training a model on a variety of data and then using this fixed model during deployment. Since it is unattainable for fixed datasets to model all environmental conditions and objects, robustness of current approaches to novel situations is severely limited.

In this work, we explore how learning can be used as a means to self-improve semantic perception during exploration of the environment. Enabling robots to adapt on-the-job poses three main challenges: (i) Models need to be efficiently (re)trained to incorporate new data (*incremental / continual learning*). (ii) Acquired knowledge should be kept while adapting to new tasks and environments (avert *forgetting*). (iii) Training signals are required during deployment, i.e. automatically harvested without manual human supervision in the loop (*self-supervision*). For the first two points, we build upon recent advancements in the field of *continual learning (CL)* [7, 8], also referred to as *incremental learning* [9, 10], and *lifelong learning* [11, 12, 13]. This learning paradigm deals with settings where tasks or classes are presented incrementally, or in which the data distribution changes over time [7].

Key to our proposed system is the combination of CL and self-supervision. In the literature, CL is usually evaluated by consecutively presenting a model with parts of existing datasets. However, in order to continually learn during deployment, robots require streams of training signals without humans in the loop. We make use of *self-supervised pseudo labels*, which can be generated from

Submitted to the 5th Conference on Robot Learning (CoRL 2021). Do not distribute.

multi-sensor [14] or multi-task systems [15]. Our results show that even noisy, imperfect pseudo labels generate useful training signals and – what has not been discovered before – also work well with CL methods that were developed for perfect labels.

To validate our approach, we conduct experiments on a real physical system. We deploy robots in diverse environments with existing 3D floorplans, in which the robot is required to localize. This application case is prevalent in building construction and service robotics. While the floorplan only represents static building structure (*background*), the actual environments contain large amounts of un-modelled objects and clutter (*foreground*), potentially obstructing localization performance [16]. As the robot adapts to the environment, it learns to tell apart *background* from *foreground* and improves its localisation in all environments. We further observe catastrophic forgetting when the robot switches between environments, and we identify CL methods that mitigate such forgetting. Finally, our experiments show positive knowledge transfer where the robot improves in novel environments based upon learning in earlier environments. In summary, our contributions are:

Figure 1: Our system on average improves semantic segmentation by 60% and median localisation error by 10% during deployment, compared to a fixed pretrained model. However, when moving to a different environment, these improvements can be lost due to *catastrophic forgetting*. We find that memory replay is an effective method against forgetting that can retain large improvements on past and current environments.

- A framework for self-improving perception;
- A pseudo label generation method for background-foreground-segmentation;
- Validation on a real-world robotic system;
- Evaluation of a range of methods to prevent forgetting;
- Evidence that CL with noisy pseudo labels yields significant improvements over fixed models.

2   Related Work

Self-improving robotic agents is a both old and underexplored idea. One framework in which agents are self-improving is reinforcement learning (RL). With RL, robots have been learning to walk [17], grasp objects [18], or fly [19]. All these systems indeed learn by self-improving over time, often failing in the beginning of the learning process. Usually these learned models are fixed once they acquire the necessary skills, unlike life-long learning. This is because they require supervision signals, e.g. from simulators that are not available during deployment. However, online adaptation of model-based RL has been shown for example in [20].
Self-improving robotic systems have also been described outside of RL. For example, [21] and [22] describe online parameter optimisations for model predictive control. The adaptive stereo vision of Tonioni et al. [23] has been a particular inspiration for this work. Very related is also Sofman et al. [24], who learn a probabilistic model for terrain traversability in an online and self-supervised fashion. Interestingly, the mentioned previous works often do not explicitly address the problem of forgetting, which is a more prevalent problem in our semantic domain adaptation.

In continual learning, models are trained from non-stationary data distributions over a series of different tasks [8]. The main objective of CL is to optimize for the performance on each task or domain with which the network is presented at any given time, while achieving positive knowledge transfer between the tasks, and preventing performance on the previous tasks from decreasing. This decrease on previous tasks is commonly referred to as *catastrophic* forgetting [25, 7]. Multiple techniques have been proposed to mitigate such forgetting, ranging from architectural modifications [26, 27] to regularization techniques [28, 29] and methods based on memories [30, 31, 32, 33] or generative models [34, 35]. A number of works have explored the use of CL techniques in the context of semantic segmentation [36, 37, 38, 39, 40]. They however experiment on a class-incremental setting, whereas we are interested in the scenario in which the deployment environment of the agent changes. In this sense, the problem we aim at tackling is also related to a line of works that focus on domain adaptation [41, 42, 43]. However, these works generally assume that both the source and target domain are known at training time, while we tackle the problem of adapting to any (unknown) environment on the fly.

Self-supervision is often used to learn useful image features in convolutional neural networks (CNNs). These techniques include learning to (re)color images [44], to (un)rotate images [45], or to relatively

position random crops [46]. However, these features require further (supervised) processing to relate them to e.g. classes. In mobile agents, egomotion was found to be a promising self-supervision signal for a range of tasks [47]. Photometric consistency between video frames can be used to jointly learn camera calibration, visual odometry, depth estimation, and optical flow [15].

A different line of works produces pseudolabels for segmentation by leveraging models trained on more available data. Class activation maps of image classifiers [48] can be used to identify object regions as a segmentation proxy [49, 50, 51]. Furthermore, segmentation predictions can be refined by optimizing over Mask R-CNN predictions, room layout estimation, and superpixels [52], by tracking and optical flow [53], or by aggregating predictions in 3D space and projecting them back onto images [14]. While there is no direct prior work for background-foreground-segmentation, our proposed method builds up on similar ideas to use observable characteristics of the environment to produce a learning signal for the target task.

3 Proposed System

We propose a self-improving perception system that interlinks localisation within a map and semantic segmentation of the scene. We define the semantics of the scene not as arbitrary class labels, but by the observable affordance that some parts of the scene are mapped (*background*) and some are not (*foreground*). Therefore, we create pseudo labels based on the localisation in the map to train the semantic segmentation, and we use the segmentation into *foreground* and *background* to inform the localisation. This creates a feedback loop that can yield improvements in both parts, as can be seen in Figure 2.

Figure 2: The proposed self-improving system. The segmentation still incorporates existing training data as a prior, but is not fixed during deployment, as would be the established approach. Instead, our segmentation is updated during deployment based on CL methods. The continual learning uses self-supervised pseudo labels, which are available during deployment without manual labelling. We mark signals from the deployment environment in orange and from the pretraining domain in green.

3.1 Semantically Informed Localisation

We localize the robot based on aligning 3D LiDAR scans with the given floorplan in the form of a 3D mesh as in [16]. Given the floorplan mesh M, a pointcloud of the LiDAR scan P, and an initial alignment $T_{\mathrm{mesh} \to \mathrm{lidar}}^{(t=0)}$, we find subsequent robot poses as

$$T_{\mathrm{mesh} \to \mathrm{lidar}}^{(t)} = \mathrm{ICP}(M, P^{(t)}, T_{\mathrm{mesh} \to \mathrm{lidar}}^{(t-1)}).$$

We use point-to-plane ICP [54] and filter out points of large distance and other criteria. Complete parameters are reported in Appendix A.5.

To further divide the scan P into *foreground* and *background* points, we use additional information from a camera system mounted on top of the LiDAR. Once camera images are semantically segmented, we filter $P_{\mathrm{background}} \subseteq P$ as those points $p \in P$ whose reprojected pixel in image frame is segmented as *background* and localise with $\mathrm{ICP}(M, P_{\mathrm{background}}^{(t)}, T_{\mathrm{mesh} \to \mathrm{lidar}}^{(t-1)})$.

3.2 Pseudolabel Generation

We generate pseudo labels for each camera based on the LiDAR pointcloud that is localised w.r.t. the floorplan. First, for each point of the localised LiDAR scan, we calculate the distance to the closest plane of the mesh using fast intersection and distance computation [55]. We then check if the distance surpasses a given threshold δ. If so, the point is assigned the *foreground* class, otherwise the *background* class. In the second stage, we project each point onto the respective camera frames and refine the projection using SLIC superpixels [56]. In particular, we first oversegment the image into a superpixel set S. A superpixel $s \in S$ is then assigned a class according to a majority voting of the contained projected labels. We further improve the segmentation by discarding superpixels whose depth variance surpasses a given threshold. An overview of the approach is depicted in Figure 3.

(a) Mesh and Pointcloud   (b) Projected Pointcloud   (c) Oversegmented Image   (d) Pseudo Labels

Figure 3: Generation of pseudo labels. After localising the LiDAR scan, points are labeled by comparing the distance to the floorplan with a threshold δ (red is foreground, green is background). They are then projected into the image and aggregated into superpixels.

(a) Multi-Sensor Setup   (b) Parking Garage   (c) Construction Site   (d) Office Environment

Figure 4: Overview of our experimental setup.

146 These pseudo labels are not optimal[1]. The goal however is not to generate perfect labels, but a useful
147 training signal that can be generated on-the-fly without requiring any external supervision. As our
148 experiments demonstrate, even this noisy learning signal substantially boosts performance.

3.3 Domain Adaptation with Continual Learning

150 To solve the task of background-foreground segmentation, we incrementally train a neural network
151 architecture on different data sources. We pre-train a CNN on the NYU-Depth v2 dataset [57], which
152 contains 1449 images extracted from video sequences of indoor scenes, each with per-pixel semantic
153 annotations. We map the classes *wall*, *ceiling*, and *floor* to background and regard everything else as
154 foreground. This (pre-)training step allows the model to acquire prior knowledge as an inductive bias
155 to perform the same segmentation task on subsequent environments that the agent is presented with.

156 During deployment, the network is then updated with self-supervision through the pseudolabels
157 generated on the current scene. With reference to the nomenclature often used in CL [8], we consider
158 each new environment a *task*, and we assume *task boundaries* to be known, since for each task, the
159 robot is given a different floorplan. Every time the robot is moved to a new environment, the same
160 scheme is applied, i.e., the network trained on the previous environments is updated by training on
161 the pseudolabels from the current environment.

162 To prevent forgetting of information learned on the previous
163 tasks, we adopt a method based on memory replay buffers.
164 When adapting to a new environment, each training batch is
165 filled with the frames collected in the current environment,
166 along with a small fraction of images collected in the previ-
167 ous environments. Therefore, the model jointly optimizes over
168 current and previous environments. However, storing all obser-
169 vations from past environments in memory would come at huge
170 costs. Instead, a memory buffer for each previous environment
171 only contains a random subset of all images and (pseudo-)labels.
172 Details of the buffer implementation and a comparison with
173 other CL frameworks are described in Section 4.4.

Algorithm 1: Memory Replay

---

memory_buffer = RandomChoice(
  10% out of previous_scene)
train_data = ShuffleTogether(
  current_scene, memory_buffer)
while *training not converged* **do**
  foreach *batch in train_data* **do**
    | randomly augment batch
    | train on batch
  end
  validate on 10% hold-out of
    current_scene
end

---

4 Experimental Evaluation

175 We test and verify the applicability of the proposed framework in different steps of increasing
176 complexity. We first validate that our robot can self-improve by deploying it into different unknown
177 environments and measure the gained improvement. We then evaluate the effects of forgetting and
178 knowledge transfer when switching deployment between different environments. Finally, we conduct
179 an experiment in which the robot learns online during the mission.

---

[1]For example, for any clutter object standing on the ground, all points below a height of δ may be labelled as
background in the pseudolabels, dependent on the boundaries of the superpixel.

environment	mean/median/std translation error [mm]			segmentation quality [% mIoU]	
	no segmentation	trained on NYU	self-improving	trained on NYU	self-improving
Garage	50 / 41 / 37	58 / 41 / 73	**43 / 35 / 31**	33.9	**62.8**
Construction	488 / 183 / 999*	126 / 78 / 129	**104 / 68 / 105**	27.6	**48.2**
Office	167 / 168 / 88[+]	196 / 145 / 202	**150 / 138 / 81**	46.5	**53.9**

Table 1: Deployment to a single novel environment. We observe that segmentation in general is advantageous and the CL on self-supervised pseudolabels improves in all environments compared to deploying a fixed model. * marks ICP failures. [+] uses adjusted parameters, see Appendix A.5.

For each experiment, we measure the localisation error in the x-y plane[2] in mean, median and standard deviation. We also measure the segmentation quality in mean Intersection over Union (mIoU).

Robotic Platform. We conduct all our experiments on a wheeled robotic ground vehicle [16] with the sensor setup shown in Figure 4a. We calibrate all cameras to an IMU that we attach to the sensor system and then align trajectories from visual-inertial odometry and LiDAR to find the extrinsic calibration between the LiDAR and the cameras. The tracking prism is used to gather ground-truth with a total station for our evaluation and is mounted on the sensor system to be aligned with the optical center of the LiDAR. For time synchronisation, we trigger all cameras simultaneously. From images captured at 20 Hz we then take those closest to the timestamp of the LiDAR scans, which are captured at 5Hz. Finally, we manually correct time-offsets between the total station and the robot.

Evaluation Environments. We deploy our proposed system into three different environments: a construction site, a parking garage, and an office floor. Architectural researchers provided us 3D meshes, constructed from dense 3D scans (Construction) and existing 2D floorplans supplemented with additional measurements (Garage and Office). Figure 4 shows these meshes together with the experimental setup. In each environment, we steer the robot through multiple independent trajectories of 2-3 min while tracking the robot with a total station. The coordinate system of the total station is always initialised to the origin of the building mesh, which we therefore set at corners visible to the total station. To evaluate the learned segmentation models, we sample and annotate around 30 ground-truth segmentations per environment. We then evaluate the segmentation predictions against ground-truth annotations within a static field-of-view (FoV) mask of the LiDAR[3].

Learning Setup. We use a lightweight architecture based on Fast-SCNN [58] that we train for background-foreground segmentation. We resize input images to a common size (480×640 pixels). We first train the model on the NYU dataset. Then, when we deploy the robot into a new environment (cf. Sec. 4.1), we fill a replay buffer with samples from NYU in addition to training on the pseudolabels from the current environment. When we evaluate the transfer from a first environment to a second one (cf. Sec. 4.2), we replay images from both NYU and the first environment. We set the replay fraction to 10%, but evaluate different replay regimes and strategies in Section 4.4. Before feeding images to the network, we augment them with left-right flipping and random perturbation of brightness and hue. In each experiment, we hold out 10% of the training samples for validation and train our model using Adam optimizer. See Appendix A.2 for all training parameters and Appendix A.1 for runtimes.

4.1 Deployment in a new environment

To test the effectiveness of the pseudolabel training and the localisation based on filtered pointclouds, we deploy the robot in a first new environment. There, the robot collects information in the form of pseudolabels, which are used to train the segmentation. Afterwards, we deploy the robot over a different trajectory in the same environment and measure the performance of both segmentation and localisation.

In Table 1 we compare the performance obtained from our self-supervised foreground-background segmentation with segmentation obtained from the network pre-trained on NYU, and with a baseline that does not semantically filter the pointcloud. We note that segmentation in general is important for good localisation and can prevent failure, as on the construction site. The results also confirm

---

[2]The ground truth from the total station only provides translation measurements and does not enable evaluation of correctly estimated orientation.

[3]The FoV mask has two reasons: Because we are primarily interested in good localisation, comparing segmentation quality in the region that can be reprojected to the LiDAR relates better to localisation performance. Additionally, pseudolabels are also only available in image regions where the LiDAR provides information, therefore we expect the segmentation to learn mostly the semantics of the scene visible in these regions.

environment source → target	method	mean/median/std translation error [mm] source	target	segmentation [% mIoU] source	target
Garage→ Construction	replay	41 / 33 / 30	98 / 66 / 98	**60.8**	48.6
	finetuning	40 / 33 / 29	87 / 67 / 77	55.1	49.4
Garage→ Office	replay	39 / 31 / 31	168 / 137 / 109	**62.6**	47.2
	finetuning	37 / 30 / 33	196 / 118 / 267	61.0	47.4
Construction→ Garage	replay	**105 / 68 / 108**	40 / 33 / 29	**49.3**	62.2
	finetuning	549 / 84 / 1500*	40 / 31 / 29	42.3	62.0
Construction→ Office	replay	**125 / 72 / 128**	158 / 137 / 93	**50.3**	47.6
	finetuning	514 / 191 / 914*	146 / 123 / 93	45.4	49.4
Office → Garage	replay	**153 / 131 / 95**	44 / 34 / 36	**47.8**	62.1
	finetuning	182 / 151 / 114	38 / 32 / 27	40.2	61.0
Office → Construction	replay	171 / 161 / **86**	91 / 66 / 85	**47.5**	49.9
	finetuning	**168 / 159** / 88	121 / 70 / 128	33.3	49.1

Table 2: Evaluation of forgetting and knowledge transfer when switching between deployment environments. The perception system is first trained on pseudolabels of the source environment, then on the target, and then evaluated on both. Bold marks cases where one method reduces forgetting compared to the other method. Underlined metrics are better than single-environment deployment from Table 1. Finetuning leads to two cases (marked with star) where forgetting causes ICP failures.

the effectiveness of the pseudolabels, as training on these yields improvements in both segmentation quality and localisation error in all metrics. We conclude that the self-improving setup is working as expected and that through the feedback loop indeed the localisation improves the segmentation, and the segmentation improves the localisation.

4.2 Transfer into a second environment

In a second stage of experiments, we evaluate the ability of our system to retain knowledge and still adapt to new domains when moved from a first environment to a second one. In particular, we first train on pseudolabels from a *source* environment and afterwards train the same model on pseudolabels from a *target* environment. For each of these source-to-target transfers, we evaluate the extent of forgetting on both the pretraining data (NYU) and the source environment, comparing our adopted method based on a replay buffer with simple fine-tuning.

As shown in Table 2 and summarised in Figure 1, using replay buffers improves the segmentation performance on the source tasks w.r.t. the case in which no replay is adopted. This indicates successful mitigation of forgetting and is even more prominent when measured on the pseudolabels and measuring forgetting on the NYU data, which we analyse in further detail in Table 5 in Appendix A.3. Table 2 further shows that the forgetting in the finetuned models can cause localisation failure on the source environment. Using replay prevents such failure successfully. In the CL literature, memory replay is usually studied in settings in which high-quality segmentation masks covering all pixels in the image are available [7]. Yet, from our observations we can conclude that memory replay is also effective when the replayed labels are noisy and imperfect.

We note that finetuning can result in better adaptation to the target environment, especially with regard to localisation. This is expected, since the learning process of finetuning is fully tailored to the new environment. This effect is known as *stability-plasticity dilemma* [59], i.e. old knowledge can inhibit learning of new knowledge, but increasing plasticity can in turn lead to forgetting. In our experiments, the relative improvements of finetuning over memory replay that we observe on the target environment are marginal, suggesting that the chosen 10% replay finds a good balance.

Table 2 also highlights cases in which deployment in two consecutive environments is better than improving only towards one specific environment (Section 4.1), both with and without memory replay. This indicates positive knowledge transfer between our evaluation environments. For a self-improving robotic system this is a promising finding, showing that the robot not only adapts to the target environment, but generally improves at its task with every new deployment.

Finally, we observe that segmentation quality and localisation error are sometimes inconsistent, where a drop in segmentation quality in the source environment does not necessarily transfer into worse localisation. This indicates potential for advanced methods which only keep in memory those observations that are important for the task at hand.

4.3 Online Learning

The previous experiments have been conducted in a multi-mission fashion, in which a first mission gathers data of the environment and the robot learns from it to improve in subsequent missions. Figure 5 now shows how the system can learn online during a mission by learning from the pseudolabels directly as they are generated. We observe that over time segmentation quality increases and localisation error decreases. Notably, already a few seconds of online learning increase the segmentation quality significantly. However, it takes longer until we measure a notable effect on the localisation. Due to the limited time until the end of the trajectory, we are therefore unable to see if there is a feedback effect where the improved localisation would create better pseudolabels that can in turn increase the segmentation quality further. For this, further investigation on longer deployments is necessary.

4.4 Ablation Studies

Since CL methods have not been explored in a

Figure 5: Online Learning on the construction site. We measure how the robot improves online (row 1), but also evaluate snapshots of the model on reference data (rows 2 and 3). Areas in green/red show changes (better/worse) with respect to a fixed model. We observe that segmentation quality increases over time and localisation error decreases.

real-world robotic context, and even less in combination with noisy pseudolabels as training signal, we perform an extensive ablation of different methods and parameters to validate our use of replay buffers.

We first evaluate two different strategies for memory replay. In the first strategy, which is the one that we adopt in the main experiments, on each source-to-target experiment (e.g., NYU→Garage), we fill the replay buffer with a fraction of samples from the source dataset(s) (NYU in the example), which we select randomly. We then fill training batches from the replay buffer and target dataset according to their relative sizes. In the second strategy, we fill the replay buffer with the full source dataset but fill training batches with a pre-defined target-source ratio. For instance, a ratio Garage : NYU = 4 : 1 with a batch size of 10 indicates that batches on average contain 8 images from Garage and 2 images from NYU. As shown in Table 3, milder replay regimes (larger target-source ratios, or smaller replay fractions) achieve higher performance on the target domain, but cause the amount of information retained from the source domain to drop. This forgetting phenomenon is particularly evident in the adaptation tasks in which the semantic gap between source and domain is larger. Indeed, for instance, in the NYU→Garage experiment we observe a drop of 31.9% in mIoU on the NYU labels between a replay strategy with a fraction of 10% and simple fine-tuning, while the same decrease in performance when the target domain is Office – semantically closer to the indoor dataset NYU – is 14.8%. At the same time, the segmentation quality on the pseudo-labels of the target dataset follows an inverse trend, generally increasing for smaller amounts of replay. This highlights the trade-off between the accuracy on the target and on the source domain.

We further compare regularization techniques from the continual-learning literature. In particular, we investigate the use of a distillation approach, in which a regularization term is added to the cross-entropy loss, to encourage the network to retain the knowledge from previous tasks. Similarly to [36], we apply this distillation either on the output logits produced by the network (*Output distillation*) or on the intermediate features (*Feature distillation*). Furthermore, we evaluate Elastic Weight Consolidation (EWC) [28]. We present further details in Appendix A.4.

As shown in Table 3, in our experiments replay buffers prove to be the most effective among the examined methods in minimizing the amount of forgetting on the NYU dataset, and generally allow attaining a good trade-off with the segmentation quality on the pseudo-labels from the target domain. We also note that, with limited exceptions, both regularization approaches fail to maintain a good performance on the source dataset NYU. We believe that for distillation methods this can be ascribed to the fact that, as opposed to related works that explored similar techniques in a class-incremental

		NYU→Garage			NYU→Construction			NYU→Office			
		NYU	Garage		NYU	Construction		NYU	Office		
			Pseudo	GT		Pseudo	GT		Pseudo	GT	
Finetuning		36.4	96.3	61.8	36.6	79.5	48.9	66.2	70.9	51.2	
Replay buffer with ratio target : NYU	1 : 1	**87.2**	86.5	61.5	**82.9**	66.6	46.1	**83.5**	57.8	49.9	memory replay
	3 : 1	81.1	91.7	60.7	79.8	73.1	47.8	81.4	68.1	52.2	
	4 : 1	79.8	92.4	62.3	78.7	73.1	48.8	82.0	65.8	51.7	
	10 : 1	73.4	94.7	61.3	75.3	75.6	47.6	77.7	71.2	52.1	
	20 : 1	67.5	95.3	62.0	72.4	76.3	48.3	76.0	69.1	52.0	
	200 : 1	53.9	96.1	61.6	53.2	77.2	48.7	74.8	68.7	50.9	
Replay buffer with fraction replay	10%	**68.3**	95.4	62.8	**78.6**	77.0	48.2	**81.0**	69.7	53.9	
	5%	65.0	95.9	62.0	76.2	76.9	48.5	79.9	69.3	51.5	
Feature distillation	$\lambda = 0.5$	35.4	96.1	61.9	33.2	77.1	50.3	**65.3**	71.1	50.7	regularisation methods
	$\lambda = 1$	34.8	95.9	61.2	30.6	76.9	50.8	58.6	78.9	49.1	
	$\lambda = 10$	**37.4**	94.2	61.6	**33.6**	72.1	48.3	48.7	72.2	48.0	
	$\lambda = 50$	33.6	92.7	61.1	32.6	63.1	46.5	44.0	64.5	46.8	
Output distillation	$\lambda = 0.5$	33.1	94.4	63.3	34.0	76.5	47.8	**62.9**	68.4	49.9	
	$\lambda = 1$	32.4	85.3	64.4	**38.2**	59.4	46.6	53.0	60.4	44.3	
	$\lambda = 10$	37.8	40.8	47.5	37.9	32.9	37.1	45.3	35.8	36.1	
	$\lambda = 50$	**39.0**	48.9	53.0	31.7	28.7	31.1	46.3	30.5	35.9	
EWC [28]	$\lambda = 0.5$	36.1	96.4	61.5	34.4	76.5	47.9	65.7	69.2	51.6	
	$\lambda = 1$	36.2	96.3	61.4	**37.0**	76.4	48.0	66.2	74.0	50.8	
	$\lambda = 10$	**37.9**	96.2	61.1	35.4	76.2	48.0	**70.6**	69.1	51.8	
	$\lambda = 50$	**37.9**	95.9	**61.5**	35.0	75.6	47.9	65.5	73.2	51.0	

Table 3: Ablation study over different CL methods. After adapting from the source domain (NYU) to the different deployment environments, we measure segmentation quality [% mIoU] on the source data as well as the self-supervised pseudolabels (Pseudo) and our ground-truth annotations (GT). Forgetting is therefore indicated by low performance in the gray columns. We compare the finetuning with memory replay and regularisation methods. We observe that memory replay is more successful than regularisation at preventing catastrophic forgetting in our application.

setting [36, 37], we conduct domain adaptation. More importantly, unlike [36, 37] our supervision signal does not consist of accurate ground-truth annotations available at all pixels, but of noisy pseudo-labels that often cover a limited region of the image. Finally, while similar considerations also apply for EWC, we believe that the limited effectiveness of this technique in our setting is also related to the method being designed for classification as opposed to image segmentation.

4.5 Limitations

Our system required some manual intervention in the sense that a few parameters were changed across environments (ICP and superpixels, see Appendix). While coming close, the system also did not run in real-time. We are confident that both points can be tackled with better software implementations.

This study is limited to binary segmentation. However, our framework itself is agnostic of the self-supervision method and can be directly extended to more classes based on multi-sensor [14] or multi-task systems [15], or temporal consistency [53]. Alternatively, more affordances can be observed through manipulating objects [60], or observing contexts and spatial co-occurence [61, 62].

5 Conclusion & Outlook

In this work we propose a framework for self-improving perception by combining CL with self-supervision. We study this on a real robotic system that localises in 3D floorplans. Our experiments validate the gains of the self-improving systems in diverse environments. In particular, we analyse the effects of knowledge transfer and forgetting when switching between environments. We find that memory replay is an effective solution that can mitigate forgetting, and observe that the system can even further improve as it transfers knowledge from previously seen, distinct environments.

The main finding from our evaluations of knowledge transfer and forgetting is that self-supervision and CL is an effective combination, even if the self-supervision is noisy. This opens up exciting questions for future research. Through the self-supervision approaches that we describe in Sections 2 and 4.5, the same framework can be transferred to other perception tasks such as more semantic classes or perception for manipulation. For some tasks, task boundaries may be less clear, and further research is necessary to lift this assumption. Finally, we identify long-term dynamics and stability of self-improving systems as an interesting direction for future research.

References

[1] J. McCormac, R. Clark, M. Bloesch, A. Davison, and S. Leutenegger. Fusion++: Volumetric Object-Level SLAM. In *Intl. Conf. on 3D Vision (3DV)*, pages 32–41. IEEE, 2018.

[2] A. Rosinol, M. Abate, Y. Chang, and L. Carlone. Kimera: an Open-Source Library for Real-Time Metric-Semantic Localization and Mapping. In *IEEE Intl. Conf. on Robotics and Automation (ICRA)*, pages 1689–1696. IEEE, 2020.

[3] L. Kunze, N. Hawes, T. Duckett, M. Hanheide, and T. Krajník. Artificial intelligence for Long-Term Robot Autonomy: A Survey. *IEEE Robotics and Automation Letters*, 3(4):4023–4030, 2018.

[4] E. Yurtsever, J. Lambert, A. Carballo, and K. Takeda. A Survey of Autonomous Driving: Common Practices and Emerging Technologies. *IEEE Access*, 8:58443–58469, 2020.

[5] H. Blum, P.-E. Sarlin, J. Nieto, R. Siegwart, and C. Cadena. The fishyscapes benchmark: Measuring blind spots in semantic segmentation. Apr. 2019.

[6] O. Zendel, K. Honauer, M. Murschitz, D. Steininger, and G. Fernandez Dominguez. Wilddash-creating hazard-aware benchmarks. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 402–416. openaccess.thecvf.com, 2018. doi:10.1007/978-3-030-01231-1_25.

[7] G. I. Parisi, R. Kemker, J. L. Part, C. Kanan, and S. Wermter. Continual lifelong learning with neural networks: A review. *Neural Networks*, 113:54–71, 2020.

[8] T. Lesort, V. Lomonaco, A. Stoian, D. Maltoni, D. Filliat, and N. Díaz-Rodríguez. Continual Learning for Robotics: Definition, Framework, Learning Strategies, Opportunities and Challenges. *Information Fusion*, 58:52–68, 2020.

[9] R. Camoriano, G. Pasquale, C. Ciliberto, L. Natale, L. Rosasco, and G. Metta. Incremental Robot Learning of New Objects with Fixed Update Time. In *IEEE Intl. Conf. on Robotics and Automation (ICRA)*, 2017.

[10] K. Shmelkov, C. Schmid, and K. Alahari. Incremental Learning of Object Detectors without Catastrophic Forgetting. In *Intl. Conf. on Computer Vision (ICCV)*, 2017.

[11] Z. Chen and B. Liu. Lifelong Machine Learning. *Synthesis Lectures on Artificial Intelligence and Machine Learning*, 12(3):1–207, 2018.

[12] S. Thrun and T. M. Mitchell. Lifelong robot learning. *Robotics and Autonomous Systems*, 15: 25–46, 1995.

[13] D. L. Silver, Q. Yang, and L. Li. Lifelong Machine Learning Systems: Beyond Learning Algorithms. In *AAAI Conf. on Artificial Intelligence (AAAI)*, 2013.

[14] W. Sun, J. Zhang, and N. Barnes. 3D Guided Weakly Supervised Semantic Segmentation. *CoRR*, abs/2012.00242, 2020.

[15] Y. Chen, C. Schmid, and C. Sminchisescu. Self-Supervised Learning With Geometric Constraints in Monocular Video: Connecting Flow, Depth, and Camera. In *Intl. Conf. on Computer Vision (ICCV)*, pages 7063–7072, 2019.

[16] anonymous authors. reference omitted for anonymous review.

[17] T. Haarnoja, S. Ha, A. Zhou, J. Tan, G. Tucker, and S. Levine. Learning to Walk via Deep Reinforcement Learning. *arXiv preprint arXiv:1812.11103*, 2018.

[18] M. Q. Mohammed, K. L. Chung, and C. S. Chyi. Review of Deep Reinforcement Learning-Based Object Grasping: Techniques, Open Challenges, and Recommendations. *IEEE Access*, 8: 178450–178481, 2020.

[19] J. Hwangbo, I. Sa, R. Siegwart, and M. Hutter. Control of a Quadrotor With Reinforcement Learning. *IEEE Robotics and Automation Letters*, 2(4):2096–2103, 2017.

[20] J. Fu, S. Levine, and P. Abbeel. One-shot learning of manipulation skills with online dynamics adaptation and neural network priors. In *IEEE/RSJ Intl. Conf. on Intelligent Robots and Systems (IROS)*, pages 4019–4026. IEEE, 2016.

[21] M. Lorenzen, M. Cannon, and F. Allgöwer. Robust MPC with recursive model update. *Automatica*, 103:461–471, 2019. ISSN 0005-1098.

[22] J. Kabzan, L. Hewing, A. Liniger, and M. N. Zeilinger. Learning-Based Model Predictive Control for Autonomous Racing. *IEEE Robotics and Automation Letters*, 4(4):3363–3370, 2019. doi:10.1109/LRA.2019.2926677.

[23] A. Tonioni, O. Rahnama, T. Joy, L. D. Stefano, T. Ajanthan, and P. H. S. Torr. Learning to Adapt for Stereo. In *IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, pages 9661–9670, 2019.

[24] B. Sofman, E. Lin, J. A. Bagnell, J. Cole, N. Vandapel, and A. Stentz. Improving robot navigation through self-supervised online learning. *Journal of Field Robotics*, 23(11-12): 1059–1075, 2006.

[25] R. M. French. Catastrophic forgetting in connectionist networks. *Trends in Cognitive Sciences*, 3(4):128–135, 1999.

[26] A. A. Rusu, N. C. Rabinowitz, G. Desjardins, H. Soyer, J. Kirkpatrick, K. Kavukcuoglu, R. Pascanu, and R. Hadsell. Progressive Neural Networks. *arXiv preprint arXiv:1606.04671*, 2016.

[27] J. Schwarz, W. Czarnecki, J. Luketina, A. Grabska-Barwinska, Y. W. Teh, R. Pascanu, and R. Hadsell. Progress & Compress: A scalable framework for continual learning. In *Intl. Conf. on Machine Learning (ICML)*, 2018.

[28] J. Kirkpatrick, R. Pascanu, N. Rabinowitz, J. Veness, G. Desjardins, A. A. Rusu, K. Milan, J. Quan, T. Ramalho, A. Grabska-Barwinska, D. Hassabis, C. Clopath, D. Kumaran, and R. Hadsell. Overcoming catastrophic forgetting in neural networks. *Proceedings of the National Academy of Sciences*, 114(13):3521–3526, 2017.

[29] Z. Li and D. Hoiem. Learning without Forgetting. *IEEE Trans. Pattern Anal. Machine Intell.*, 40(12):2935–2947, 2018.

[30] S.-A. Rebuffi, A. Kolesnikov, G. Sperl, and C. H. Lampert. iCaRL: Incremental Classifier and Representation Learning. In *IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2017.

[31] D. Lopez-Paz and M. Ranzato. Gradient Episodic Memory for Continual Learning. In *Conf. on Neural Information Processing Systems (NIPS)*, 2017.

[32] T. L. Hayes, N. D. Cahill, and C. Kanan. Memory Efficient Experience Replay for Streaming Learning. In *IEEE Intl. Conf. on Robotics and Automation (ICRA)*, 2019.

[33] S. Zhang and R. S. Sutton. A Deeper Look at Experience Replay. In *Conf. on Neural Information Processing Systems (NIPS) - Deep Reinforcement Learning Symposium*, 2017.

[34] H. Shin, J. K. Lee, J. Kim, and J. Kim. Continual Learning with Deep Generative Replay. In *Conf. on Neural Information Processing Systems (NIPS)*, 2017.

[35] C. Wu, L. Herranz, X. Liu, Y. Wang, J. v. d. Weijer, and B. Raducanu. Memory Replay GANs: Learning to Generate Images from New Categories without Forgetting. In *Conf. on Neural Information Processing Systems (NIPS)*, 2018.

[36] U. Michieli and P. Zanuttigh. Incremental Learning Techniques for Semantic Segmentation. In *Intl. Conf. on Computer Vision (ICCV), Workshop on Transferring and Adapting Source Knowledge in Computer Vision (TASK-CV)*, 2019.

[37] U. Michieli and P. Zanuttigh. Knowledge distillation for incremental learning in semantic segmentation. *Computer Vision and Image Understanding*, 205:103167, 2021.

[38] F. Cermelli, M. Mancini, S. Rota Bulò, E. Ricci, and B. Caputo. Modeling the Background for Incremental Learning in Semantic Segmentation. In *IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2020.

[39] A. Douillard, Y. Chen, A. Dapogny, and M. Cord. PLOP: Learning without Forgetting for Continual Semantic Segmentation. *CoRR abs/2011.11390*, 2020.

[40] L. Yu, X. Liu, and J. van de Weijer. Self-Training for Class-Incremental Semantic Segmentation. *CoRR abs/2012.03362*, 2020.

[41] Y. Zou, Z. Yu, B. V. K. Vijaya Kumar, and J. Wang. Unsupervised Domain Adaptation for Semantic Segmentation via Class-Balanced Self-training. In *European Conf. on Computer Vision (ECCV)*, 2018.

[42] A. Saporta, T.-H. Vu, M. Cord, and P. Pérez. ESL: Entropy-guided Self-supervised Learning for Domain Adaptation in Semantic Segmentation. In *IEEE Conf. on Computer Vision and Pattern Recognition (CVPR), Workshop on Scalability in Autonomous Driving*, 2020.

[43] Y. Li, L. Yuan, and N. Vasconcelos. ESL: Entropy-guided Self-supervised Learning for Domain Adaptation in Semantic Segmentation. In *IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2019.

[44] R. Zhang, P. Isola, and A. A. Efros. Colorful Image Colorization. In *European Conf. on Computer Vision (ECCV)*, pages 649–666. Springer, 2016.

[45] S. Gidaris, P. Singh, and N. Komodakis. Unsupervised representation learning by predicting image rotations. In *Intl. Conf. on Learning Representations (ICLR)*, 2018.

[46] C. Doersch, A. Gupta, and A. A. Efros. Unsupervised Visual Representation Learning by Context Prediction. In *Intl. Conf. on Computer Vision (ICCV)*, pages 1422–1430, 2015.

[47] P. Agrawal, J. Carreira, and J. Malik. Learning to See by Moving. In *Intl. Conf. on Computer Vision (ICCV)*, pages 37–45, 2015.

[48] B. Zhou, A. Khosla, À. Lapedriza, A. Oliva, and A. Torralba. Learning Deep Features for Discriminative Localization. *CoRR*, abs/1512.04150, 2015.

[49] Y.-T. Chang, Q. Wang, W.-C. Hung, R. Piramuthu, Y.-H. Tsai, and M.-H. Yang. Mixup-CAM: Weakly-supervised Semantic Segmentation via Uncertainty Regularization. *CoRR*, abs/2008.01201, 2020.

[50] J. Lee, E. Kim, S. Lee, J. Lee, and S. Yoon. FickleNet: Weakly and Semi-supervised Semantic Image Segmentation using Stochastic Inference. *CoRR*, abs/1902.10421, 2019.

[51] Z. Huang, X. Wang, J. Wang, W. Liu, and J. Wang. Weakly-Supervised Semantic Segmentation Network With Deep Seeded Region Growing. In *IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, June 2018.

[52] M. A. Reza, A. U. Naik, K. Chen, and D. J. Crandall. Automatic Annotation for Semantic Segmentation in Indoor Scenes. In *IEEE/RSJ Intl. Conf. on Intelligent Robots and Systems (IROS)*, pages 4970–4976. IEEE, 2019.

[53] L. Porzi, M. Hofinger, I. Ruiz, J. Serrat, S. R. Bulo, and P. Kontschieder. Learning Multi-Object Tracking and Segmentation From Automatic Annotations. In *IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2020.

[54] Y. Chen and G. Medioni. Object modelling by registration of multiple range images. *Image and Vision Computing*, 10(3):145–155, 1992.

[55] P. Alliez, S. Tayeb, and C. Wormser. 3D fast intersection and distance computation. In *CGAL User and Reference Manual*. CGAL Editorial Board, 5.2 edition, 2020. URL https://doc.cgal.org/5.2/Manual/packages.html#PkgAABBTree.

[56] R. Achanta, A. Shaji, K. Smith, A. Lucchi, P. Fua, and S. Süsstrunk. SLIC Superpixels Compared to State-of-the-Art Superpixel Methods. *IEEE Trans. Pattern Anal. Machine Intell.*, 34(11):2274–2282, 2012.

[57] N. Silberman, D. Hoiem, P. Kohli, and R. Fergus. Indoor Segmentation and Support Inference from RGBD Images. In *European Conf. on Computer Vision (ECCV)*, 2012.

[58] R. P. K. Poudel, S. Liwicki, and R. Cipolla. Fast-SCNN: Fast Semantic Segmentation Network. In *British Machine Vision Conf. (BMVC)*, 2019.

[59] M. Mermillod, A. Bugaiska, and P. Bonin. The stability-plasticity dilemma: investigating the continuum from catastrophic forgetting to age-limited learning effects. *Frontiers in Psychology*, 4:504, 2013.

[60] C. Castellini, T. Tommasi, N. Noceti, F. Odone, and B. Caputo. Using Object Affordances to Improve Object Recognition. *IEEE Trans. Autonomous Mental Development*, 3(3):207–215, 2011.

[61] J. Bachmann, K. Blomqvist, J. Förster, and R. Siegwart. Points2Vec: Unsupervised Object-level Feature Learning from Point Clouds. *CoRR abs/2102.04136*, 2021.

[62] C. Galleguillos, A. Rabinovich, and S. Belongie. Object categorization using co-occurrence, location and appearance. In *IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, pages 1–8, 2008.

[63] Y. Wu and K. He. Group Normalization. In *European Conf. on Computer Vision (ECCV)*, 2018.

[64] S. Ioffe and C. Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *Intl. Conf. on Machine Learning (ICML)*, 2015.

[65] R. Giraud, V. Ta, and N. Papadakis. SCALP: superpixels with contour adherence using linear path. *CoRR*, abs/1903.07149, 2019. URL http://arxiv.org/abs/1903.07149.