Toxicity Detection in Finnish Using Machine Translation

Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
email@domain

Anonymouser Author
Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
email@domain

Anonymousest Author
Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
email@domain

Abstract

Due to the popularity of social media platforms and the share amount of user-generated content online, the automatic detection of toxic language has become crucial in the creation of a friendly and safe digital space. Previous work has been mostly focusing on English leaving many lower-resource languages behind. In this paper, we present novel resources for toxicity detection in Finnish by introducing two new datasets, a machine translated toxicity dataset for Finnish based on the widely used English Jigsaw dataset and a smaller test set of Suomi24 discussion forum comments originally written in Finnish, manually annotated following the same guidelines that were used to annotate the Jigsaw dataset. We show that machine translating the training data to Finnish provides better toxicity detection results than using the original English training data and zero-shot cross-lingual transfer with XLM-R. Finally, we demonstrate that the model identifies toxic content also from the Suomi24 comments, although the change of the text source does present its challenges.

1 Introduction

Social media is filled with moderated and unmoderated content with foul language such as threats, insults, swears, and others. Due to the popularity of the platforms and the share amount of comments, posts and other user-generated content they include, moderation by human-raters is getting impossible. This makes automatic toxicity detection a requirement in the monitoring of social media platforms and other online settings in order to guarantee a safe and friendly digital space.

In recent years, many studies have tackled the detection of toxic language as well as other similar and relevant tasks, such as the detection of hate speech and offensive language (Davidson et al., 2017; MacAvaney et al., 2019). However, most datasets and thus most of the studies focus on English, leaving other languages with very scarce resources (Davidson et al., 2017; Androcec, 2020). At the same time, the development of the resources, in particular the creation of manually annotated training data, is very time-consuming. Cross-lingual transfer learning has offered a solution to this challenge by allowing the use of data in one language to predict examples in another one. This method has showed promising results in tasks such as register labeling (Rönnqvist et al., 2021; Repo et al., 2021) and offensive language detection (Pelicon et al., 2021). Additionally, recent advances in machine translation open up the question about using machine translation to do the language transfer and create novel resources for a language.

In this paper, we address the lack of resources for toxicity detection in languages other than English by benefiting from the recent advances in machine translation. Specifically, we present the first publicly available dataset for toxicity detection in Finnish that we develop by machine translating the English Jigsaw Toxicity Dataset that is claimed to be the biggest and most widely used toxicity dataset (Androcec, 2020). We show that machine translating the dataset to Finnish provides better results for toxicity detection than cross-lingual transfer learning, where a cross-lingual XLM-R model (Conneau et al., 2020) is fine-tuned using the original English Jigsaw training set and tested on the Finnish machine translated test set. Furthermore, to test how much machine translation modifies the content of the dataset and thus causes performance loss, we backtranslate the dataset from Finnish to English, demonstrating only a minimal decrease in performance. Fi-

nally, in order to examine how much toxic content the trained model identifies from another source than the Wikipedia edit comments included in Jigsaw, we create another test set for toxicity detection in Finnish by manually annotating altogether 2260 comments from the Finnish discussion forum Suomi24. The annotations follow the label description guidelines that were used to annotate the original English dataset. We show that while the model does identify toxic content also from the discussion forum comments, the change of text source does present challenges. Both the machine translated and the native Finnish datasets are openly available at `deleted-for-review`.

The Jigsaw dataset is composed of 223,549 comments from Wikipedia's talk pages, see Section 3.1. As machine translation systems, we test two systems to see whether there are major differences to our results: the DeepL machine translation service [1] and Opus-MT (Tiedemann and Thottingal, 2020), see Section 3.2. Additionally, in the toxicity detection, we apply monolingual and cross-lingual transfer learning, see Section 4.

2   Related Work

Toxicity, in terms of speech, text or behaviour, is an umbrella term that encompasses many kinds of language use, such as hate speech, abusive language, offensive language and harmful language. In this paper, we follow the definition adopted in the Jigsaw dataset and define toxicity as "rude, disrespectful, or unreasonable language that is likely to make someone leave a discussion" (jig). For other definitions of the term and related tasks, see Davidson et al. (2017), and Burtenshaw and Kestemont (2021).

Toxicity detection (van Aken et al., 2018; Pavlopoulos et al., 2020) is related to many other similar classification tasks such as hate speech detection (Davidson et al., 2017; MacAvaney et al., 2019) and offensive language classification (Davidson et al., 2017; Jahan and Oussalah, 2020). In all these tasks, the goal is to identify harmful text in, e.g., social media, where comments can be flagged for review or automatically deleted.

Toxicity datasets and datasets for other related tasks are mostly monolingual with English being the most popular—most studies have used the same Jigsaw dataset that we use (Androcec, 2020). For instance, Carta. et al. (2019) reported

ROC_AUC-scores of nearly 90% on this dataset. Additionally, datasets are available, e.g., for Spanish (Androcec, 2020), and a multilingual dataset has been developed as a part of the Kaggle competition on multilingual toxicity detection[2].

The available datasets represent various domains and text lengths, ranging from short Twitter posts (Davidson et al., 2017) to Wikipedia editor comments featured by the Jigsaw dataset we are using, see Section 3.1. Similarly, the annotation strategies vary from multi-label annotation where one instance can have several independently assigned labels to multi-class where one instance can be assigned just one label (Davidson et al., 2017) and even a binary setting where each instance is either clean or toxic (D'Sa et al., 2020). Due to these differences, combining several datasets to increase the number of examples in training data is difficult.

Similarly, the subjectivity entailed in toxicity creates a challenge for its automatic detection—as people interpret things differently, a single correct answer may not exist (see discussion in Ross et al. (2016)). In addition to model performance, the subjectivity can be noted in low inter-annotator agreements. For instance, Waseem (2016) reported a kappa of .57, which can be interpreted as *weak*.

Cross-lingual zero-shot transfer learning where the model is trained on one language and tested on another relies on multilingual language models that have been trained on massive amounts of multilingual data (Conneau et al., 2020; Devlin et al.). These have been used for the zero-shot cross-lingual transfer of hate speech detection and offensive/abusive language detection. For instance, Pelicon et al. (2021) report that a multilingual BERT-based classifier achieves results that are comparable to monolingual classifiers in offensive language detection and also Eronen et al. (2022) demonstrate that zero-shot cross-lingual transfer can achieve competitive results for abusive language detection. However, Nozza (2021) note also challenges—the zero-shot transfer of hate speech detection can be complicated by non-hateful, language-specific taboo interjections that are interpreted by the model as signals of hate speech, and also Leite et al. (2020) found that zero-shot transfer did not produce accurate results for toxicity detection in Brazilian Portuguese.

---

[1]https://www.deepl.com/translator

[2]https://www.kaggle.com/c/jigsaw-multilingual-toxic-comment-classification

Machine translation can be considered a mode of transfer learning that has become viable with the advances of natural language processing. In particular, the method has been used in toxic language detection to get more data by data augmentation (Rastogi et al., 2020) and by translating data to English to be able to use ready-made models (Kobellarz and Silva, 2022). Kobellarz and Silva (2022) found that comments that were analyzed as toxic in Portuguese were not as toxic when translated to English—however, the same behaviour may not apply for other language pairs. To our knowledge, no experiments comparing cross-lingual transfer by a multilingual model and by machine translation have been made previously.

3 Data and Translation

3.1 Jigsaw Toxicity Dataset

The data used in this paper is the Jigsaw dataset developed by Google (Carta. et al., 2019). The dataset is based on comments from Wikipedia's talk page edits and consists of 223,549 comments. The dataset collection was done by crowdsourcing. No specific information about the annotation process is given.

The annotation scheme is composed of six classes: *toxicity*, *severe toxicity*, *identity attack, insult, obscene* and *threat*. Toxicity is defined as "rude, disrespectful, or unreasonable language that is likely to make someone leave a discussion", and severe toxicity as "a very hateful, aggressive, disrespectful comment or otherwise very likely to make a user leave a discussion or give up on sharing their perspective". For other definitions, please see the annotation guidelines for Perspective API (Perspective API Training Data).

The annotation is set up as multi-label, where each comment annotated as toxic has one or more labels assigned to it. The label distribution of the dataset is presented in Table 1. In total, only 11% of the comments are annotated with at least one of the toxic labels, the rest being left without labels and considered as neutral or non-toxic. This means that the label distribution is highly unbalanced, which, however, comes from the data. More information about label co-occurrence is given in Figure 1, showing that in particular *obscene* and *insult* as well as *toxicity* and *insult* and *obscene* co-occur.

The dataset is split into train and test sets with stratified sampling (159571 and 63978 comments) following the original Kaggle release. Furthermore, a development set is split from the train set by doing stratified splitting and taking 20 % of the train set comments.

Figure 1: Correlation matrix of the labels of the original train dataset calculated with Pearson standard correlation coefficient. Small values close to zero indicate no correlation between the labels, while higher values closer to 1 suggest correlation and that the labels tend to appear together.

3.2 Jigsaw Toxicity Data in Finnish

We machine translated the original English Jigsaw dataset to Finnish using two translation tools: the DeepL machine translation service[3] and Opus-MT (Tiedemann and Thottingal, 2020). For DeepL, the dataset was converted to the required `.docx`-format for the translation and then back to `.jsonl` after the translation. The English-Finnish translation cost less than 100 dollars. None of the comments were lost during this process—a possibility that needs to be considered when transforming data from a format to another.

For Opus-MT, the texts needed to be sentence split, because the tool can only translate one sentence at a time. This was done using the Udpipe REST api[4]. The model used for translation was `Helsinki-NLP/opus-mt-tc-big-en-fi`[5].

---

[3]https://www.deepl.com/translator
[4]https://lindat.mff.cuni.cz/services/udpipe/api-reference.php
[5]https://huggingface.co/Helsinki-NLP/opus-mt-tc-big-en-fi

Some of the comments from the test set did not survive the translation, as they were not in English. These were edited to only include the notion "EMPTY".

Finally, to examine the loss of performance caused by the machine translation, we also **back-translated** the dataset translated with DeepL from Finnish back to English. This was done using the same method as the English-Finnish translations.

3.3 Native Finnish Toxicity Dataset

To examine how much toxic content the fine-tuned model can identify in comments featuring another text variety than the Wikipedia edit comments included in Jigsaw, we developed a new manually annotated test set sampled from Suomi24—the largest online discussion forum in Finland compiled into a giga-size corpus. As the label distribution is very skewed in the Jigsaw dataset with a large majority of comments not annotated for toxicity (see Section 3.1), the sampling was done in a specific manner to ensure a representative set of comments featuring varying degrees of toxicity and the six toxicity classes.

Specifically, we first classified 945 867 comments taken from Suomi24 using the best-performing classifier described in Section 5.1. Then, for each of the six toxicity labels, we binned the comments to ten bins based on the classifier score for that label (0.0-0.1, 0.1-0.2, … 0.9-1.0). The distribution of comments in these bins is presented in Appendix A, showing that the classifier is very certain about its decisions. In particular, the 0.0-0.1 bins are extremely large, while another set of peaks can be seen on the right end with high scores.

After the binning, we selected randomly 50 comments from each bin for annotation. This gave 500 comments of broadly varying degrees of predicted toxicity for each of the six toxicity labels. Each of the six batches of 500 comments were annotated for one toxicity label only. Thus, the annotations are multi-class instead of the original Jigsaw multi-label, although 23 individual comments were selected in two different batches due to the sampling for each label being independent.

The annotation was done independently by three annotators with borderline cases jointly resolved and documented in guidelines. Finally, cases that were initially unanimously agreed or resolved in subsequent discussion were used to

	Train	Test
Toxicity	15924	6090
Severe toxicity	1595	367
Threat	478	211
Obscene	8449	3691
Insult	7877	3427
Identity attack	1405	712
No label	143346	57735

Table 1: Label distribution in the Jigsaw Toxicity Dataset. As each comment may have up to six labels, the total number of labels exceeds the number of comments in the dataset.

	Label	No label
Toxicity	158	193
Severe toxicity	25	328
Threat	40	391
Obscene	170	239
Insult	145	219
Identity attack	131	221
Total	669	1591

Table 2: Label distribution in the native Finnish annotations.

form the final data. This process thus created a novel test set of 2260 comments natively written in Finnish, further described in Table 2. The guidelines and label descriptions created during the annotation are published together with the datasets at `deleted-for-review`.

4 Fine-tuning

We use both monolingual and multilingual state-of-the-art models in the detection experiments. Specifically, the monolingual models are the large and cased versions of the original BERT for English (Devlin et al.) and FinBERT for Finnish (Virtanen et al.). For the crosslingual experiments, we use XLM-RoBERTA (XLM-R) Large (Conneau et al., 2020) because it has been shown to provide better results than the multilingual BERT for many tasks (Repo et al., 2021; Rönnqvist et al., 2021).

All the experiments are done in a multi-label setting. However, when evaluating classifier performance on the native Finnish test set where the comments are only annotated for one toxicity label at a time, we ignore other labels than the one annotated in the batch. Furthermore, importantly, we made a custom loss function to the model, giving the labels weights in order to tackle the imbalanced label distribution in the data. The weights were calculated based on the labels' frequency in the training data. E.g., *threat* received a weight of 47.6901 due to it appearing in the data only 478

times and *toxicity* the weight 1.4905 due to appearing 15924 times in the data.

No pre-processing for the texts was done to get the best results since previous studies had found that with deep learning models pre-processing might make the results worse (Saeed et al., 2018).

For training, we used sequence length of 512 by truncating at the end and did hyperparameter optimization with grid search using learning rate (LR) of (1e-5..5e-5), batch size of (4, 8, 12), and epochs (10) with early stopping and evaluation every 2500 steps. All the hyperparameters were optimized on the development set. For the cross-lingual experiments with XLM-R, we optimized on the English development set and tested on the translated Finnish test set. The best hyperparameters can be found in Appendix B. Furthermore, 0.65 was selected as the label assignment threshold after threshold optimization.

As metrics in the evaluation, we use the standard precision and recall, micro-F1, macro-F1, hamming loss and ROC_AUC. Precision shows how many of the positive predictions are correct, and recall how many of all the positive cases in the data were found. F1-score is the balanced and harmonic mean of precision and recall. Micro-F1 specifically calculates metrics globally and macro-F1 for each label separately, finding their unweighted mean. Thus, macro-F1 does not take label imbalance into account.

ROC_AUC score is the Area Under the Receiver Operating Characteristic Curve. This metric was used for the scoring of the Kaggle competition held for the original dataset, although only done on the probabilities and 90% of the data as opposed to us using the thresholded label and the full test set. Hamming loss for multi-label predictions is defined as the fraction of incorrect labels in the total set of labels. It is better suited for multi-label classification as it takes into account predictions of the individual labels.

The codebase can found on Github at `deleted-for-review`.

5 Results

5.1 Translation and Transfer

The results of the toxicity detection experiments using the original English and the translated datasets are presented in Table 3. As a baseline, we can consider the results of the English BERT model, 0.69 F1-score (micro-avg.) and 0.89 ROC_AUC, trained and tested on the original English data. This is very similar to the results reported by Carta. et al. (2019) using the same Jigsaw dataset and BERT (see Section 2).

FinBERT trained and tested on the machine translated data performs numerically slightly worse than BERT on the English data: 0.66 F1-score with DeepL and 0.65 with OPUS-MT. The loss of performance is, however, very small. With this result, we decide to run the further experiments with the data translated with DeepL.

The multilingual XLM-R performs numerically very similarly to FinBERT with the Finnish DeepL-translated data: 0.65 F1-score. However, its performance is clearly lower when trained on English and only tested on Finnish: 0.57 F1-score. Thus, our results support those by Leite et al. (2020), who noted that zero-shot transfer from English to another language can be challenging.

Our results thus suggest that transferring the language barrier provides much better results with machine translation than with a cross-lingual model. The quality of the machine translations is further supported by the results on the backtranslated English dataset. By showing only a 2% loss in the F1-score, this experiment supports the quality of the translations.

Even combining the original English data and its DeepL-translations in the training set does not provide better results than training and testing on the DeepL-translated Finnish data alone, and the model trained and tested in English outperforms both of these settings. This can suggest that transfer, done either with a model or machine translation, can have some effect on the results.

Given the subjectivity associated with toxicity detection, and the IAA scores discussed in Section 2, the detection results are very close to what can be expected for this task. Additionally, for practical purposes, it is noteworthy that the recall is approximately 20% higher than the precision for all the experiments except for the cross-lingual one. When used for cleaning data or moderating a platform, false positives can be less dangerous than false negatives. This further consolidates the practical usability of the method.

5.2 Label-Specific Scores

Nozza (2021) showed that language-specific differences in, e.g., taboo expressions can challenge cross-lingual toxicity detection. These differences

Model	Train	Test	Precision	Recall	F1-micro	FI-macro	ROC_AUC	Hamming loss
BERT	En	En	0.59	0.81	0.69	0.61	0.89	0.028
FinBERT	Fi-DeepL	Fi-DeepL	0.58	0.76	0.66	0.57	0.87	0.031
FinBERT	Fi-Opus-MT	Fi-Opus-MT	0.57	0.77	0.65	0.57	0.88	0.03
XLM-R	Fi-DeepL	Fi-DeepL	0.56	0.76	0.65	0.57	0.87	0.031
XLM-R	En	Fi-DeepL	0.60	0.54	0.57	0.47	0.76	0.03
XLM-R	Fi-DeepL+En	Fi-DeepL	0.56	0.78	0.65	0.57	0.88	0.031
BERT	Backtr-En	En	0.59	0.77	0.67	0.60	0.87	0.029

Table 3: Results with different language pairs and models.

may lead to lower results in particular for some subtypes of toxicity. To ensure that the cross-lingual results we presented in Section 5.1 are not affected by these or similar issues, we inspect label-specific performance metrics. We focus on two models: the best-performing Finnish model trained using FinBERT and the DeepL-translated data, as well as the English model trained using BERT and the original English data.

Figure 2 presents the label-specific metrics obtained using the two models. First, we can see that while the global scores obtained by the English model are slightly higher, the difference remains similar across the labels. Thus, the language transfer does not seem to affect them unevenly.

However, the F1-scores do vary between the different labels. In particular, *severe toxicity* and *threat* receive lower detection scores than the other labels. *Threat* is a very infrequent label, which may also explain its lower detection rate. However, the size of *severe toxicity* is similar to *identity attack*, which nevertheless received better performance. This suggests that the label as such is more vague and less well-defined linguistically.

5.3 Error analysis

Figure 3 presents to which labels the most frequent labels and label combinations were predicted to using the best-performing FinBERT model trained on the DeepL-translated data, and Table 4 presents examples of misclassified comments[6].

The most frequent misclassification for many labels and their combinations is *no label*. In part, this is because of the frequency of comments without any label in the training. On the other hand, this can also reflect the gray zone between different kinds of toxic comments and the ones annotated without a label, prone to subjective interpretation. This can be seen in Example 2 in Table 4, annotated as *insult* and predicted without a label.

---
[6]The examples may be considered offensive. They do not reflect the views of the authors and exclusively serve to explain the linguistic characteristics of the comments.

Whether *hyödytön* 'useless' actually is an insult or not can be prone to subjective interpretations. Furthermore, the Perspective API annotation guidelines in fact note that insult should be targeted towards a person (att; tra).

Similarly, *toxicity* as a label is easily predicted as *no label*. For instance, *insult-obscene-toxicity* is frequently misclassified as *insult-obscene*, and *obscene-toxicity* as *obscene*. Example 1 illustrates this as well—*toxicity* is present in the annotations but not predicted. In this case, the error may be caused by the translation, as the Finnish translation is not as toxic as the original English comment and can even be used to communicate affection.

As we mentioned in Section 5.2, *severe toxicity* received relatively low class-specific scores. Figure 3 shows that it is frequently misclassified as simple *toxicity*. For instance, the label combinations *identity_attack-insult-severe_toxicity* and *insult-obscene-severe_toxicity* are frequently confused with the same labels co-occurring with *toxicity*. Examples 1 and 3 illustrate this as well, as *severe_toxicity* is erroneously not predicted for Example 1 and is predicted for Example 3, where the correct label would have been *toxicity*.

5.4 Native Finnish Dataset

We tested the best-performing model on the native Finnish annotations (see Section 3.3) in order to examine how much toxic content it identifies in texts featuring very different language use than the Wiki edits included in Jigsaw. The micro-averaged performance of the model was 15% precision and 54% recall, and the macro-average scores 15% and 45%. This shows that while the model does find toxic content from Suomi24 discussion comments, the performance leaves much to hope for. In particular, similar to the Jigsaw dataset, *severe toxicity* and *threat* received low class-specific scores[7].

A reason for the low metrics can be found in the way the Suomi24 comments were sampled

---
[7]For detailed metrics, see Appendix C.

Figure 2: Class-specific F1-scores.

Figure 3: Most frequent classes (rows) and their misclassifications (columns), as percentages of the total number of instances in the data. For the sake of simplicity, co-occurring labels have been fixed as multi-class.

(see Section 3.3). Because we took even samples from all the prediction score bins even though the large majority of the comments were included in the bins with 0-0.1 scores (see Appendix A), the vast majority of comments of which the classifier was certain about were disregarded. The metrics do not take into account this imbalance and thus, they can be interpreted rather as macro-average known to be display low results for skewed data. Table 5 shows examples from the native Finnish dataset. Example 4 presents a comment annotated as *no label*, derived from the bin 0.8-0.9 for *identity attack*. This illustrates the oversensitivity of the model and bias. The comment is originally predicted as a very certain *identity attack* and then labeled as *toxic*, the most likely because the model

ID	Text	True label(s)	Predicted label(s)
FI-1	*Senkin pikku paskiainen == Senkin pikku paskiainen*	insult, obscene	insult, obscene
EN-1	You little son of a bitch == You little son of a bitch	severe_toxicity, toxicity	
FI-2	*Wikipedia on täysin hyödytön*	insult	no label
EN-2	Wikipedia is completely useless		
FI-3	*Painu helvettiin, pedo. Nyljen sinut elävältä, kastelen sinut bensiinillä ja poltan sinut kuoliaaksi, kusipää. Syön vitun sydämesi, senkin pikku mulkku.*	insult, obscene toxicity, threat	insult, obscene severe_toxicity, threat
EN-3	Fuck off paedo. I am going to fucking skin you alive, douse you in petrol then fucking burn you to death, fucktard. I am going to eat your fucking heart you little prick.		

Table 4: Examples of misclassified and correctly predicted labels in the DeepL-translated data.

ID	Text	Bin	True label(s)	Pred. label(s)
FI-4	*Oletko mahdollisesti homoseksuaali?*	identity attack 0.8-0.9	no label	toxicity
EN-4	Are you possibly gay?			
FI-5	*jos nämä muslimit saavat räjäytellä pommejaan missä haluavat ympäri maailmaa niin miksemme me saa julkaista vitsikkäitä kuvia.*	identity attack 0.9-1	identity attack	toxicity
EN-5	if these Muslims can explode their bombs anywhere they want so why can't we publish funny pictures?			
FI-5	*Tästä tulee iso hitti!*	toxicity 0.0-0.1	no label	no label
EN-5	This is going to be a big hit!			

Table 5: Examples of misclassified labels in the native Finnish data.

simply associates 'gay' with toxicity. Example 5 shows a comment binned in very certain *identity attack*, annotated with the same label and then predicted as *toxicity*. Even if the predicted category is wrong, the prediction would be useful for flagging harmful content. Finally, Example 6 presents a comment annotated and predicted as *no label* from one of the 0-0.1 bins—the kind of comment of which the classifier is certain about and what is underrepresented in the native Finnish sample.

6 Conclusion

We have shown that machine translation is a viable option for transferring the language barrier in toxicity detection—FinBERT and the DeepL-translated data outperformed XLM-R trained on English and tested on Finnish clearly, and the quality of the translation was further confirmed with the backtranslation experiment, showing only a minimal loss in the original English performance. Thus, our results support previous findings by Isbister et al. (2021) and Kobellarz and Silva (2022). The use of machine translation is a cost-effective alternative for building resources when there is no annotated data available in the target language.

However, translation can also cause subtle changes in the meaning, which can result in misclassifications and wrong interpretations. Our analysis showed that the toxicity entailed in the original comment can change during the transla-

tion to a much less toxic meaning. Therefore, it is crucial that the effect of the translation is evaluated separately for each language and task.

Additionally, our study shows that more work is needed to adapt the model to new text varieties. While some comments and labels were correctly classified in the native Finnish test set sampled from the Suomi24 discussion forum and the output is without a doubt useful for moderation, in particular precision remains very low. Furthermore, we acknowledge that our model might feature some bias, as illustrated in Section 3.3. Jigsaw has also reported this—the models may learn to incorrectly associate toxicity with, e.g., identities frequently co-occurring with toxic content. This has led to the creation of a new dataset called "Jigsaw Unintended Bias in Toxicity Classification" [8].

In the future, we should further inspect the possible biases the models developed in this study may feature, as well as the model generalizability. Furthermore, multilingual toxicity detection involving code-switching would offer an interesting avenue for the future. Finally, considering the promising results achieved in this study, the use of machine translation for other tasks and language pairs should certainly be analyzed further.

---

[8]https://www.kaggle.com/c/jigsaw-unintended-bias-in-toxicity-classification

References

https://jigsaw.google.com/the-current/toxicity/ Jigsaw toxicity [online].

https://developers.perspectiveapi.com/s/about-the-api-attributes-and-languages?language=en_US Perspective api attributes and languages [online].

https://developers.perspectiveapi.com/s/about-the-api-training-data?language=en_US Perspective api training data [online].

Betty van Aken, Julian Risch, Ralf Krestel, and Alexander Löser. 2018. Challenges for toxic comment classification: An in-depth error analysis. In *Proceedings of the 2nd Workshop on Abusive Language Online (ALW2)*, pages 33–42, Brussels, Belgium. Association for Computational Linguistics.

Darko Androcec. 2020. https://doi.org/10.2478/ausi-2020-0012 Machine learning methods for toxic comment classification: a systematic review. *Acta Universitatis Sapientiae, Informatica*, 12:205–216.

Ben Burtenshaw and Mike Kestemont. 2021. https://aclanthology.org/2021.bucc-1.10 A Dutch dataset for cross-lingual multilabel toxicity detection. In *Proceedings of the 14th Workshop on Building and Using Comparable Corpora (BUCC 2021)*, pages 75–79, Online (Virtual Mode). INCOMA Ltd.

Salvatore Carta., Andrea Corriga., Riccardo Mulas., Diego Reforgiato Recupero., and Roberto Saia. 2019. https://doi.org/10.5220/0008110901050112 A supervised multi-class multi-label word embeddings approach for toxic comment classification. In *Proceedings of the 11th International Joint Conference on Knowledge Discovery, Knowledge Engineering and Knowledge Management - KDIR,*, pages 105–112. INSTICC, SciTePress.

Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2020. https://doi.org/10.18653/v1/2020.acl-main.747 Unsupervised cross-lingual representation learning at scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8440–8451, Online. Association for Computational Linguistics.

Thomas Davidson, Dana Warmsley, Michael Macy, and Ingmar Weber. 2017. Automated hate speech detection and the problem of offensive language. In *Proceedings of the 11th International AAAI Conference on Web and Social Media*, ICWSM '17, pages 512–515.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding.

Ashwin Geet D'Sa, Irina Illina, and Dominique Fohr. 2020. https://aclanthology.org/2020.trac-1.4 Towards non-toxic landscapes: Automatic toxic comment detection using DNN. In *Proceedings of the Second Workshop on Trolling, Aggression and Cyberbullying*, pages 21–25, Marseille, France. European Language Resources Association (ELRA).

Juuso Eronen, Michal Ptaszynski, Fumito Masui, Masaki Arata, Gniewosz Leliwa, and Michal Wroczynski. 2022. https://doi.org/10.1016/j.ipm.2022.102981 Transfer language selection for zero-shot cross-lingual abusive language detection. *Information Processing &amp Management*, 59(4):102981.

Tim Isbister, Fredrik Carlsson, and Magnus Sahlgren. 2021. https://aclanthology.org/2021.nodalida-main.42 Should we stop training more monolingual models, and simply use machine translation instead? In *Proceedings of the 23rd Nordic Conference on Computational Linguistics (NoDaLiDa)*, pages 385–390, Reykjavik, Iceland (Online). Linköping University Electronic Press, Sweden.

Md Saroar Jahan and Mourad Oussalah. 2020. Team oulu at SemEval-2020 task 12: Multilingual identification of offensive language, type and target of Twitter post using translated datasets. In *Proceedings of the Fourteenth Workshop on Semantic Evaluation*, pages 1628–1637. International Committee for Computational Linguistics.

Jordan K. Kobellarz and Thiago H. Silva. 2022. https://doi.org/10.1145/3539637.3556892 Should we translate? evaluating toxicity in online comments when translating from portuguese to english. In *Proceedings of the Brazilian Symposium on Multimedia and the Web*, WebMedia '22, page 89–98, New York, NY, USA. Association for Computing Machinery.

João Augusto Leite, Diego Silva, Kalina Bontcheva, and Carolina Scarton. 2020. https://aclanthology.org/2020.aacl-main.91 Toxic language detection in social media for Brazilian Portuguese: New dataset and multilingual analysis. In *Proceedings of the 1st Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics and the 10th International Joint Conference on Natural Language Processing*, pages 914–924, Suzhou, China. Association for Computational Linguistics.

Sean MacAvaney, Yao Hao-Ren, Eugene Yang, Katina Russell, Nazli Goharian, and Ophir Frieder. 2019. Hate speech detection: Challenges and solutions. *PLoS One*, 14(8).

Debora Nozza. 2021. https://doi.org/10.18653/v1/2021.acl-short.114 Exposing the limits of zero-shot cross-lingual hate speech detection. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference*

on *Natural Language Processing (Volume 2: Short Papers)*, pages 907–914, Online. Association for Computational Linguistics.

John Pavlopoulos, Jeffrey Sorensen, Lucas Dixon, Nithum Thain, and Ion Androutsopoulos. 2020. Toxicity detection: Does context really matter? In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4296–4305. Association for Computational Linguistics.

Andraž Pelicon, Ravi Shekhar, Matej Martinc, Blaž Škrlj, Matthew Purver, and Senja Pollak. 2021. https://aclanthology.org/2021.hackashop-1.5 Zero-shot cross-lingual content filtering: Offensive language and hate speech detection. In *Proceedings of the EACL Hackashop on News Media Content Analysis and Automated Report Generation*, pages 30–34, Online. Association for Computational Linguistics.

Chetanya Rastogi, Nikka Mofid, and Fang-I Hsiao. 2020. Can we achieve more with less? Exploring data augmentation for toxic comment classification.

Liina Repo, Valtteri Skantsi, Samuel Rönnqvist, Saara Hellström, Miika Oinonen, Anna Salmela, Douglas Biber, Jesse Egbert, Sampo Pyysalo, and Veronika Laippala. 2021. https://doi.org/10.18653/v1/2021.eacl-srw.24 Beyond the English web: Zero-shot cross-lingual and lightweight monolingual classification of registers. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Student Research Workshop*, pages 183–191, Online. Association for Computational Linguistics.

Samuel Rönnqvist, Valtteri Skantsi, Miika Oinonen, and Veronika Laippala. 2021. https://aclanthology.org/2021.nodalida-main.16 Multilingual and zero-shot is closing in on monolingual web register classification. In *Proceedings of the 23rd Nordic Conference on Computational Linguistics (NoDaLiDa)*, pages 157–165, Reykjavik, Iceland (Online). Linköping University Electronic Press, Sweden.

Björn Ross, Michael Rist, Guillermo Carbonell, Benjamin Cabrera, Nils Kurowsky, and Michael Wojatzki. 2016. https://doi.org/10.17185/duepublico/42132 Measuring the reliability of hate speech annotations: The case of the european refugee crisis.

Hafiz Hassaan Saeed, Khurram Shahzad, and Faisal Kamiran. 2018. https://doi.org/10.1109/ICDMW.2018.00193 Overlapping toxic sentiment classification using deep neural architectures. In *2018 IEEE International Conference on Data Mining Workshops (ICDMW)*, pages 1361–1366.

Jörg Tiedemann and Santhosh Thottingal. 2020. OPUS-MT — Building open translation services for the World. In *Proceedings of the 22nd Annual Conferenec of the European Association for Machine Translation (EAMT)*, Lisbon, Portugal.

Antti Virtanen, Jenna Kanerva, Rami Ilo, Jouni Luoma, Juhani Luotolahti, Tapio Salakoski, Filip Ginter, and Sampo Pyysalo. Multilingual is not enough: BERT for finnish.

Zeerak Waseem. 2016. Are you a racist or am I seeing things? annotator influence on hate speech detection on Twitter. In *Proceedings of the First Workshop on NLP and Computational Social Science*, pages 138–142, Austin, Texas. Association for Computational Linguistics.

Appendices

A The distribution of predicted scores for the Suomi24 data before sampling

Figure 4: Distribution of prediction scores by label for the Suomi24 data from which our native Finnish dataset examples were sampled for annotation.

B Best hyperparamaters for the trained models

Model	Train	Test	LR	Batch size
BERT	En	En	1e-5	12
FinBERT	Fi-DeepL	Fi-DeepL	2e-5	12
FinBERT	Fi-Opus-MT	Fi-Opus-MT	1e-5	12
XLM-R	Fi-DeepL	Fi-DeepL	1e-5	12
XLM-R	En	Fi-DeepL	1e-5	12
XLM-R	Fi-DeepL+En	Fi-DeepL	1e-5	12
BERT	Backtr-En	En	2e-5	12

Table 6: Best hyperparameters for each model. Constant parameters were epochs 10 and early stopping 5. Threshold for the labels varied due to threshold optimization during training and evaluation.

C Label specific precision and recall for the native Finnish dataset

Figure 5: Label-specific performance metrics for the native Finnish dataset. Global F1-score is 0.20 (both micro and macro avg.)