Out-of-Dynamics Imitation Learning from Multimodal Demonstrations

Abstract: Existing imitation learning works mainly assume that the demonstrator who collects demonstrations share the same dynamics as the imitator. However, the assumption limits the usage of imitation learning, especially when collecting demonstrations for the imitator is difficult. In this paper, we study out-of-dynamics imitation learning (OOD-IL), which relaxes the assumption to that the demonstrator and the imitator have the same state spaces but could have different action spaces and dynamics. OOD-IL enables imitation learning to utilize demonstrations from a wide range of demonstrators but introduces a new challenge: some demonstrations cannot be achieved by the imitator due to the different dynamics. Prior works try to filter out such demonstrations by feasibility measurements, but ignore the fact that the demonstrations exhibit a multimodal distribution since the different demonstrators may take different policies in different dynamics. We develop a better transferability measurement to tackle this newly-emerged challenge. We firstly design a novel sequence-based contrastive clustering algorithm to cluster demonstrations from the same mode to avoid the mutual interference of demonstrations from different modes, and then learn the transferability of each demonstration with an adversarial-learning based algorithm in each cluster. Experiment results on several MuJoCo environments, a driving environment, and a simulated robot environment show that the proposed transferability measurement more accurately finds and down-weights non-transferable demonstrations and outperforms prior works on the final imitation learning performance. We show the videos of our experiment results on our website.

Keywords: Imitation Learning, Out-of-Dynamics Imitation Learning

1   Introduction

Imitation learning is a widely-used policy learning paradigm to solve robotics and control tasks, which learns the policy from demonstrations [1, 2]. Standard imitation learning assumes that the demonstrator who collects the demonstrations shares the same dynamics with the imitator, which means that their state spaces, action spaces and the transition model are all the same [3, 4, 5]. However, such strict assumption limits the practical usage of imitation learning, especially when it is difficult to collect demonstrations in the imitator's environment.

In this paper, we relax the assumption to that the demonstrator and the imitator share the same state space but the dynamics could be different, i.e., their action spaces and the transition model could be different, and name the new imitation learning setting as out-of-dynamics imitation learning (OOD-IL). The new assumption poses fewer requirements on the demonstrator and enables imitation learning to utilize a broader range of demonstrations. For example, in autonomous driving, to learn the policy of an autonomous vehicle in a new city, we may use the database of driving behavior of human vehicles containing useful information instead of manually collecting demonstrations on the autonomous vehicle. But such a database cannot be used by standard imitation learning since the

Submitted to the 6th Conference on Robot Learning (CoRL 2022). Do not distribute.

(a) Problem setting and the general framework. (b) Multimodal distribution.

Figure 1: (a) We are given demonstrations collected from an unknown mixture of demonstrators, which exhibit a multimodal distribution since different demonstrators may take different policies. Some demonstrations (red) may not be achievable by the target agent while others are achievable. Learning from these unachievable demonstrations introduces unknown behaviors. We develop a transferability measurement to mitigates negative impact of these non-transferable demonstrations and learn from transferable ones. (b) A t-SNE visualization of demonstrations collected from 4 dynamics in MuJoCo environment.

vehicles have different dynamics and the city environments can be different. Furthermore, in real applications, it is often difficult and expensive to obtain enough data in a single source, thus it is beneficial to utilize data from a mixture of massive data sources for a better real-world performance.

As shown in Figure 1(a), OOD-IL introduces a challenge that the mixture of demonstrations collected in different dynamics may not be achievable by the imitator, and thus are non-transferable. The state-of-the-art work constructs feasibility measurement to down-weight the non-transferable demonstrations by learning a deterministic policy from a feasibility-MDP (f-MDP) [6]. However, as is shown Figure 1(b), we notice that the prior work overlooks an important fact: the demonstrations collected from different demonstrators exhibit a multimodal distribution since different demonstrators may take different policies. The multimodal demonstrations make it impossible to learn a deterministic policy from the f-MDP. Furthermore, f-MDP suffers from slow and inaccurate optimization difficulties due to a step-by-step optimization procedure.

In this paper, we address OOD-IL with the above challenges by developing a transferability measurement to determine how transferable each demonstration is for the imitator. *To fully remove the interference from multimodal distribution*, we design a sequence-based contrastive clustering algorithm to simultaneously learn a hidden space and cluster the trajectories in the hidden space, which ensures each cluster introduces a unimodal trajectory distribution. Then we learn the transferability for each cluster respectively by generative adversarial imitation learning (GAIL) [5], a much easier-to-optimize objective than f-MDP. The discriminator in GAIL distinguishes transitions from the demonstrators' distribution to the imitators' distribution, which serves as the transferability measurement to indicate the likelihood for a demonstration trajectory to be reproduced by the imitator. Experiment results on several MuJoCo environments, a driving environment and a simulated Franka Panda Arm environment show that by re-weighting demonstrations with the proposed transferability measurement, the final imitation learning policy outperforms all baselines and achieves the state-of-the-art performance.

2 Related Works

Standard Imitation Learning Standard Imitation Learning learns a policy to imitate the behavior in demonstrations. Existing algorithms can be roughly categorized into three types: Behavior Cloning (BC), Inverse Reinforcement Learning (IRL), and Generative Adversarial Imitation Learning (GAIL). BC utilizes supervised learning to directly learn the policy from state-action pairs [7]. Following works propose dataset aggregation [3] or policy aggregation [8, 9] to address the compounding errors problem in BC. Torabi *et al.* [10] try to learn from state sequences by first recovering the actions by an inverse dynamics model and then conducting behavior cloning. IRL first recovers the reward function

from demonstrations and then learns the policy using the learned reward [11, 12, 4, 13]. GAIL-based works matches the occupancy measure between the learned policy and the demonstrations through adversarial learning to seek the optimal policy [5, 14]. Also, GAIL is demonstrated to successfully imitate state sequences [15, 16, 17]. However, all the methods assume that the demonstrator and the imitator share the same dynamics, which violates the assumption of OOD-IL.

Out-of-dynamics Imitation Learning To address the OOD-IL problem, there are works learning a correspondence model [18] between the demonstrator and the imitator [19, 20, 21, 22, 23]. However, these methods assume that the strict correspondence, i.e. a one-to-one mapping between the state spaces and action spaces, exists between the demonstrator and the imitator. This assumption can be violated in real-world applications, e.g., a 7-DoF robot arm and a 3-DoF robot arm have no such correspondence since some behavior of the 7-DoF robot cannot be realized by the 3-DoF robot. Recent works relax the assumption to that the demonstrator and the imitator only share the state space [24, 25]. One line of work aims to maximally follow the demonstrations [24, 26, 27, 28], but following the non-transferable demonstrations is impossible.

Cao *et al.* [25] develop a feasibility measurement to down-weight non-transferable demonstrations by learning an inverse dynamics model, but the learned inverse dynamics may not generalize to all the demonstrations. To address this difficulty, the state-of-the-art work improves the feasibility by learning the optimal policy in f-MDP [6]. However, f-MDP suffers from two limitations. Firstly, f-MDP brutely enforces one deterministic policy to maximally imitate the demonstrations but the demonstrations with a multimodal distribution cannot be modeled by such a policy. We address the limitation by clustering the demonstrations with a sequence-based contrastive clustering algorithm. Secondly, at each time step, only when the policy is optimized in all the prior time steps can the policy be optimized to maximize the reward at the current time step. Such constraint makes it difficult and inefficient to learn the optimal policy of f-MDP. We instead adopt the discriminator in GAIL to learn the transferability measurement.

3 Out-of-dynamics Imitation Learning

In OOD-IL, we aim to learn a policy for the agent of interest (the imitator) from demonstrations collected from multiple demonstrators with different dynamics from the imitator. Formally, we model both the demonstrators and the imitator as a standard Markov decision process (MDP) $\mathcal{M} = \langle \mathcal{S}, \mathcal{A}, p, \mathcal{R}, \rho_0, \gamma \rangle$. Here $\mathcal{S}$ is the state space, $\mathcal{A}$ is the action spaces, $p : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to [0, 1]$ is the transition probability and $\mathcal{R} : \mathcal{S} \times \mathcal{S} \to \mathbb{R}$ is the reward function, which is solely defined on states and shared between the demonstrators and the imitator. Such design aims to satisfy the basic requirement of imitation learning that the demonstrators and the imitator should finish the same task [24, 25]. γ is the shared discount factor. The action spaces $\mathcal{A}$ and the transition probability p of different demonstrators and the imitator are different. In particular, we use $\mathcal{M}^i = \langle \mathcal{S}, \mathcal{A}^i, p^i, \mathcal{R}, \rho_0, \gamma \rangle$ to indicate the MDP of the imitator. A policy for the imitator $\pi^i : \mathcal{S} \times \mathcal{A}^i \to [0, 1]$ defines a probability distribution over the action space in a given state. The policy is evaluated by the expected return, which is defined by $\eta_{\pi^i} = \mathbb{E}_{s_0 \sim \rho_0, \pi^i} \left[\sum_{t=0}^{\infty} \gamma^t \mathcal{R}(s_t, s_{t+1}) \right]$, where t indicates the time step.

We formalize the policy learning as an imitation learning problem where the reward function $\mathcal{R}$ is unknown. We aim to learn the policy π^i from a set of demonstrations collected by different demonstrators $\Xi = \{\xi_1, \xi_2, \dots\}$ where each trajectory is a sequence of states $\xi = \{s_0^d, s_1^d, \dots, s_H^d\}$. Here we use state trajectories since different action space makes it impossible to imitate actions. Since we put no assumption on the dynamics of the demonstrators, there is no guarantee that an optimal policy could be learned, e.g., in the extreme case, all the demonstrations could be non-transferable and a random policy will be learned. Our goal is to learn a policy with as high return as possible.

Since the dynamics of the demonstrators and the imitator are different, the transitions (s_t^d, s_{t+1}^d) in the demonstrations may not be realizable by the imitator, i.e., no action a_t in the imitator's action space A^i could make $p^i(s_t^d, a_t^d, s_{t+1}^d) > 0$. Such demonstrations provide no useful information for the imitator and are non-transferable. However, given such a set of demonstrations from a mixture of demonstrators, it is non-trivial to directly test whether a trajectory is achievable by reproducing the trajectory in the target environment since there is no action in demonstrations. Furthermore, different

demonstrators may take different policies due to the different dynamics and may take different actions even at the same state. This multimodal distribution of the demonstrations makes prior works ineffective. In this paper, we simultaneously remove the interference from the multimodal distribution and learn transferability to mitigate negative impact of non-transferable demonstrations.

3.1 Sequence-based Contrastive Clustering

Since directly imitating from all mixture of demonstrations will make a deterministic policy suffer, we need to fully capture and decompose the intrinsic multimodal distribution of data collected from different demonstrators. Thus, we cluster demonstrations before learning their transferablity to make sure they belong to a unimodal distribution. The goal for clustering is a smaller distance for the data within the same mode and vice versa. Motivated by contrastive learning [29], we learn a sequence feature extractor and a distance metric in the sequence feature space by contrastive learning over carefully-designed positive and negative pairs. We construct positive pairs by randomly subsampling fixed-length sub-trajectories from the same demonstration and treat sub-trajectories of different demonstrations as negative pairs. Such a design satisfies our requirement since the positive pairs are from the same trajectory, and thus are from the same mode. At each batch, we first sample N trajectories from Ξ and for each trajectory ξ_i, we take two sub-trajectories ξ_{2i-1}^{sub} and ξ_{2i}^{sub}. We then derive the contrastive learning loss for this batch of $2N$ sub-trajectories as follows:

$$\mathcal{L}_{\text{contrast}} = -\frac{1}{N}\sum_{i=1}^{N} \log \frac{\exp(\langle F(\xi_{2i-1}^{\text{sub}}), F(\xi_{2i}^{\text{sub}})\rangle)}{\sum_{i' \neq 2i-1, i' \neq 2i} \exp(\langle F(\xi_{2i-1}^{\text{sub}}), F(\xi_{i'}^{\text{sub}})\rangle) + \exp(\langle F(\xi_{2i-1}^{\text{sub}}), F(\xi_{2i}^{\text{sub}})\rangle)}, \tag{1}$$

where F is the feature extractor modelled as an recurrent neural network and $\langle \cdot, \cdot \rangle$ indicates the cosine distance. The loss maximizes the cosine similarity of features between positive pairs.

We embed contrastive learning into clustering to simultaneously ensure that the positive pairs are close and the clustering structure is learned. We first initialize a matrix $\mathbf{C}$ of size $\dim(F) \times K$, where $\dim(F)$ is the dimension of the output of F and each column $\mathbf{c}_k$ of $\mathbf{C}$ represents the center of cluster k, with K clusters in total. For each input sub-trajectory ξ^{sub}, we assign a one-hot cluster label $\mathbf{y}_n \in \{0,1\}^K$ as follows:

$$y_{n,j} = \begin{cases} 1, & j = \arg\min_{k=1,\cdots,K} \|F(\xi_n^{\text{sub}}) - \mathbf{c}_k\|_2 \\ 0, & \text{otherwise} \end{cases}, \tag{2}$$

where we assign the cluster label with the nearest cluster center to a sub-trajectory. Then we introduce the clustering objective with the contrastive learning loss $\mathcal{L}_{\text{contrast}}$ embedded into it:

$$\mathcal{L}_{\text{cluster}} = \mathcal{L}_{\text{contrast}} + \frac{\lambda}{2}\|F(\xi_n^{\text{sub}}) - \mathbf{y}_n^T \mathbf{C}\|_2^2. \tag{3}$$

Every time we update the feature extractor F, we reassign the cluster label of each sub-trajectory by Eqn. (2) and update the cluster center by the following process:

$$\mathbf{c}_k \leftarrow (1-\beta)\mathbf{c}_k + \beta \sum_{n=1}^{2N} \mathbb{I}[y_{n,k}=1] F(\xi_n^{\text{sub}}), \tag{4}$$

where $\mathbb{I}$ is an indicator which takes 1 only when the condition is satisfied and takes 0 otherwise, and $\beta = \frac{1}{\sum_{n=1}^{2N} \mathbb{I}[y_{n,k}=1]}$ automatically controls the learning rate. We simultaneously optimize the contrastive learning objective and the clustering objective to encourage them to benefit from each other, where the cluster structure is learned to keep trajectories from the same mode to be in the same cluster. Our contrastive clustering algorithm derives K clusters of trajectories $\Xi_k|_{k=1}^K$, where Ξ_k contains trajectories with cluster label k. We show the algorithm procedure in Appendix.

3.2 Adversarial Transferability Measurement

The sequence-based contrastive clustering algorithm removes the mutual interference of demonstrations from different modes, we then learn the transferability within each cluster. We design a new

Figure 2: The outline of our whole algorithm, which can be divided into two phases. The first phase is sequence-based contrastive clustering where we simultaneously conduct contrastive learning and clustering. We create positive pairs by subsampling different sub-trajectories from the same trajectory and use sub-trajectories from different trajectories as negative pairs. The second phase is learning transferability where we conduct an adversarial-learning based algorithm in each cluster.

transferability measurement by an adversarial-learning algorithm based on generative adversarial imitation learning (GAIL) [5]. Our key insight is that the GAIL discriminator output indicates the likelihood for a state transition to either come from the demonstration distribution or the policy distribution. Here higher output for a demonstration means that the state transition is more likely to belong to the policy distribution, thus be more achievable by the imitator. Therefore, we train a GAIL policy π_k and a GAIL discriminator D_k for each cluster of trajectories. The loss is defined as follows:

$$\mathcal{L}_{\text{tran}} = \sum_{k=1}^{K} -\mathbb{E}_{(s_t^d, s^d)_{t+1} \sim \Xi_k} \log(1 - D_k(s_t^d, s_{t+1}^d)) - \mathbb{E}_{(s_t^{\pi_k}, s_{t+1}^{\pi_k}) \sim \pi_k} \log(D_k(s_t^{\pi_k}, s_{t+1}^{\pi_k})). \quad (5)$$

where π indicates the current policy in training and D indicates the discriminator. We use label 0 for the state transitions in the demonstrations and 1 for the state transitions collected from the policy.

After convergence, the discriminator for each mode outputs a value in $[0, 1]$ reflecting how likely an input transition is drawn from the state transition distribution derived by the imitator's policy. Thus for a state transition in the demonstrations, if it has a discriminator output close to 1, it is more possible to be drawn from the imitator's policy and achievable by the imitator. Thus, we derive the transferability for a state transition as follows:

$$w(s_t^d, s_{t+1}^d) = \sum_{k=1}^{K} \mathbb{I}\left[(s_t^d, s_{t+1}^d) \in \Xi_k\right] D_k(s_t^d, s_{t+1}^d). \quad (6)$$

Note that the discriminator is strengthened by the adversarial training paradigm and thus has a strong ability to discriminate whether a transition is from the demonstrations or the imitator's policy. The optimization of the discriminator is demonstrated to be efficient and effective [5], which requires no time-consuming step-by-step optimization in f-MDP [6].

Transferablity-sampling imitation learning. We finally embed the transferability in Eqn. (6) into imitation learning. We normalize the transferability of all the state transitions into a sampling distribution, where state transitions with larger transferability will be sampled more often:

$$p_w(s_t^d, s_{t+1}^d) = \frac{w(s_t^d, s_{t+1}^d)}{\sum_{(s_{t'}^d, s_{t'+1}^d) \in \Xi} w(s_{t'}^d, s_{t'+1}^d)}. \quad (7)$$

Using the sampling distribution p_w, we can embed our transferability into any imitation learning algorithm. We use GAIL [5] in this paper and derive the loss as follows:

$$\mathcal{L}_{\text{GAIL}} = -\mathbb{E}_{(s_t^d, s_{t+1}^d) \sim p_w} \log(1 - D(s_t^d, s_{t+1}^d)) - \mathbb{E}_{(s_t^\pi, s_{t+1}^\pi) \sim \pi} \log(D(s_t^\pi, s_{t+1}^\pi)). \quad (8)$$

4 Experiments

We experiment with three MuJoCo environments, a simulated Driving environment, and a simulated Franka Panda Arm environment. We compare our approach with a standard imitation learning algorithm: GAIL [5], imitation learning with a measure of feasibility: ID [25] and f-MDP [6]. The original ID learns the inverse dynamics model from random trajectories far from demonstrations and thus makes the learned inverse dynamics not work well on demonstrations. We create an advanced ID by learning a GAIL policy to generate trajectories as the data for inverse dynamic learning. Such trajectories are closer to demonstrations and make the inverse dynamics work better on demonstrations. We call the original ID as ID-Random and the advanced ID as ID-GAIL.

We further conduct analyses including an ablation study to verify the efficacy of each component and include a visualization of the learned transferability, the results for different compositions of demonstrations, and the performance gain when we are given a larger budget to collect demonstrations in the Appendix. The code implementation is included in the supplementary materials.

4.1 MuJoCo

Figure 3: The illustration of the varying dynamics for HalfCheetah, Hopper and Walker2d.

Environments. We illustrate the environments in Figure 3. The **HalfCheetah** is an agent with two legs and a body. We create different dynamics by discounting the force of the front leg and the back leg with two factors γ_f and γ_b respectively. We create a mixture of demonstrators by setting (γ_f, γ_b) as (i) $(1, 0.9)$, (ii) $(0.9, 1)$, (iii) $(1, 0.05)$, (iv) $(0.05, 1)$. The imitator has the original force: (γ_f, γ_b) as $(1, 1)$. The **Hopper** is an agent with one leg consists of 3 joints. We create different dynamics by varying the gravitational constant. We create a mixture of demonstrators by setting the gravitational constant as (i) 15.0, (ii) 9.8, (iii) 2.0, (iv) 1.0. For the imitator, we use a gravitational constant of 12.0. The **Walker2d** is an agent with two legs where each leg consisting of 3 joints. We create different dynamics by using different frictions for the feet, i.e., the link that touches the ground. We create a mixture of demonstrators by setting the friction as (i) 24.8, (ii) 9.9, (iii) 3.9, (iv) 1.1. For the imitator, we use a friction of 19.9. For all three MuJoCo environments, we follow prior works [6, 25] to collect fewer demonstrations from the more transferable environments. We collect $100, 100, 250, 250$ demonstrations respectively for four dynamics in HalfCheetah, $10, 10, 250, 250$ for Hopper and $25, 50, 50, 50$ for Walker2d with 1000 interaction steps per demonstration.

Results. We show the expected return with respect to the number of interaction steps for the three different environments in Figure 4. In all three environments, we observe that the proposed method

Figure 4: The imitation learning performance of different methods in the three MuJoCo environments.

achieved the highest return. The baselines even show lower performance than Naive GAIL under such multimodal distribution of source demonstrations because f-MDP may learn one unimodal policy from the multimodal trajectory distribution, which cannot reproduce the demonstration trajectories, while ID fails to learn an accurate inverse dynamics model from random trajectories. The results demonstrate the importance of clustering trajectories of the same mode due to the unimodal nature of the policy. By learning the transferability in each cluster, we can accurately filter out non-transferable demonstrations and learn from transferable demonstrations.

4.2 Driving

Environment. In the driving environment, we can easily decide whether the target car can reproduce the route in the demonstrations, so trajectories are more interpretable. As shown in Figure 5(a), we create a task where a car drives starting from anywhere at the bottom side and ends at the top side. Two obstacles are set with the center at $\frac{1}{4}$ width and $\frac{3}{4}$ width respectively. We create different dynamics by setting obstacles with different widths and setting different speeds for the car, which simulates a realistic scenario where different car models are driving at different places. The reward function is defined as -1 for each interaction step, $+1000$ for reaching the goal, and -1000 for hitting the obstacle. In this environment, the different lengths and paths of the demonstration trajectory introduce a clear multimodal distribution, which can demonstrate the importance of clustering trajectories into an accurate mode. We create three demonstrators by setting the obstacles width as $[0.1, 0.5]$, $[0.5, 0.25]$ and $[0.25, 0.25]$ and setting the speed as 1.0, 1.0 and 5.0 respectively. For the target environment, we set the obstacle width as $[0.4, 0.25]$ and the speed as 1.0. We collect 5×10^5, 2.5×10^6, and 2.5×10^6 interaction steps of demonstrations from each source dynamics.

(a) Illustration (b) Result

Figure 5: (a) The illustration the driving environment, where the left and right parts show expert trajectories collected in multiple source dynamics and the target environment. The green trajectory shows a transferable demonstration. (b) The results in the driving environment.

Results. As is shown in Figure 5(b), we observe that the proposed method outperforms all other baselines. Though ID performs well at the first few interaction steps but the performance drops much then, which can be explained by that the feasibility learned by ID could find good demonstrations in the first few batches of data but makes errors then. That means the ID can only learn partially correct feasibility. Instead, our method learns accurate transferability to filter out non-transferable demonstrations and converges stably to a high return. f-MDP, as the state-of-the-art method on filtering non-transferable demonstrations, could not work well on this multimodal distribution of demonstrations, which demonstrates the importance of clustering trajectories into the correct mode.

4.3 Simulated Franka Panda

Environment. The environment simulates the Franka Panda Robot arm[1] with 7 degrees of freedom (DoF), which is implemented in the PyBullet [30]. We create a task of moving a box from one side of the desk to the other and create different dynamics by disabling different joints of the Robot arm. As shown in Figure 6(a), we create three demonstrators by disabling the No. 1, 4, and 6 joint respectively while disabling the No. 1 and 3 joints for the target imitator. The environment aims to address a real problem to leverage history data on any robot to learn a policy for a new robot. Similar to the Mujoco environment, we import more demonstrations from the more dissimilar demonstrator, where

---
[1]https://www.franka.de/

the number of interaction steps is 1×10^6, 1×10^5, and 1×10^6 for the environment disabling No. 1, 4, and 6 respectively. The reward function is defined as the current distance to the starting point, and an extra $+1000$ for the box reaching the other side of the table and -1000 for the box dropping to the ground or the robot going past the box to the other side of the desk.

(a) Illustration   (b) Result

Figure 6: (a) The illustration of Simulated Franka Panda environment, where we create different demonstrators by disabling different single joint and disable two joints for the imitator. (b) The return of different methods in the Simulated Franka Panda environment.

Results. The expected return with respect to the number of interaction steps is shown in Figure 6(b). We observe that the proposed method outperforms all the baselines with a large margin. Directly applying GAIL introduces a low performance, which indicates that the demonstrations from other robots cannot be directly utilized to learn a new robot, while the proposed method filters out non-transferable demonstrations and makes the new robot learn from transferable demonstrations. The experiments show that the proposed method can serve as a data cleaning step to clean the dataset from other robots for a real-robot transfer learning problem.

4.4 Analysis

Ablation Study. To verify that both our contrastive clustering algorithm and the adversarial-learning based algorithm contribute to the final performance, we compare the performance of our method with its variants by removing the clustering step and learning the transferability directly from the whole set of demonstrations (Ours w/o Cluster), and removing both clustering and the transferability (Ours w/o Cluster, Tran), which directly performs imitation on the whole set of demonstrations. The results are shown in Figure 7. We observe that Ours outperforms Ours w/o Cluster, which demonstrates that clustering

Figure 7: The ablation study on variants of our method.

trajectories within the same mode is important and our contrastive clustering algorithm achieves this goal. Ours w/o Cluster outperforms Ours w/o Cluster, Tran, which demonstrates that transferability is important to filter out non-transferable demonstrations and learn from more transferable ones.

5 Conclusion

We propose a new approach to address out-of-dynamics imitation learning. Noticing that the demonstrations exhibit a multimodal distribution, we propose a sequence-based contrastive clustering algorithm to make trajectories from the same mode fall into the same cluster. We then propose an adversarial-learning based algorithm to learn the transferability of each cluster with the discriminator output. Experimental results on three MuJoCo environments, a driving environment, and a simulated robot environment show that the proposed method can learn a transferability to accurately filter out non-transferable demonstrations and learn from more transferable ones.

Limitation and future work. Although our work relaxes stringent assumptions placed on imitation learning, it is also limited since we assumed that collected demonstrations are optimal in the target environment, while it might not hold true in varying dynamics. In future, we plan to address this combined challenge of multimodal OOD-IL and learning from sub-optimal demonstrations [31].

References

[1] T. Zhang, Z. McCarthy, O. Jow, D. Lee, X. Chen, K. Goldberg, and P. Abbeel. Deep imitation learning for complex manipulation tasks from virtual reality teleoperation. In *ICRA*, 2018.

[2] F. Codevilla, M. Müller, A. López, V. Koltun, and A. Dosovitskiy. End-to-end driving via conditional imitation learning. In *ICRA*, 2018.

[3] S. Ross, G. Gordon, and D. Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *AISTATS*, 2011.

[4] B. D. Ziebart, A. L. Maas, J. A. Bagnell, and A. K. Dey. Maximum entropy inverse reinforcement learning. In *AAAI*, 2008.

[5] J. Ho and S. Ermon. Generative adversarial imitation learning. In *NeurIPS*, 2016.

[6] Z. Cao, Y. Hao, M. Li, and D. Sadigh. Learning feasibility to imitate demonstrators with different dynamics. In *CoRL*, 2021.

[7] M. Bain and C. Sammut. A framework for behavioural cloning. In *Machine Intelligence 15*, 1995.

[8] H. Daumé, J. Langford, and D. Marcu. Search-based structured prediction. *Machine learning*, 2009.

[9] S. Ross and D. Bagnell. Efficient reductions for imitation learning. In *AISTATS*, 2010.

[10] F. Torabi, G. Warnell, and P. Stone. Behavioral cloning from observation. In *IJCAI*, 2018.

[11] P. Abbeel and A. Y. Ng. Apprenticeship learning via inverse reinforcement learning. In *ICML*, 2004.

[12] A. Y. Ng, S. J. Russell, et al. Algorithms for inverse reinforcement learning. In *ICML*, 2000.

[13] C. Finn, S. Levine, and P. Abbeel. Guided cost learning: Deep inverse optimal control via policy optimization. In *ICML*, 2016.

[14] J. Fu, K. Luo, and S. Levine. Learning robust rewards with adverserial inverse reinforcement learning. In *ICLR*, 2018.

[15] Y. Schroecker and C. L. Isbell. State aware imitation learning. In *NeurIPS*, 2017.

[16] F. Torabi, G. Warnell, and P. Stone. Generative adversarial imitation from observation. In *ICML Workshop on Imitation, Intent, and Interaction (I3)*, 2019.

[17] W. Sun, A. Vemula, B. Boots, and D. Bagnell. Provably efficient imitation learning from observation alone. In *ICML*, 2019.

[18] C. L. Nehaniv, K. Dautenhahn, et al. The correspondence problem. *Imitation in animals and artifacts*, 41, 2002.

[19] P. Englert, A. Paraschos, J. Peters, and M. P. Deisenroth. Addressing the correspondence problem by model-based imitation learning. In *ICRA Workshop on Autonomous Learning*, 2013.

[20] S. Calinon, F. Guenter, and A. Billard. On learning, representing, and generalizing a task in a humanoid robot. *IEEE Transactions on Systems, Man, and Cybernetics*, 2007.

[21] C. Eppner, J. Sturm, M. Bennewitz, C. Stachniss, and W. Burgard. Imitation learning with generalized task descriptions. In *ICRA*, 2009.

[22] Q. Zhang, T. Xiao, A. A. Efros, L. Pinto, and X. Wang. Learning cross-domain correspondence for control with dynamics cycle-consistency. In *ICLR*, 2021.

[23] Z. Wang, Z. Cao, Y. Hao, and D. Sadigh. Weakly supervised correspondence learning. *arXiv preprint arXiv:2203.00904*, 2022.

[24] F. Liu, Z. Ling, T. Mu, and H. Su. State alignment-based imitation learning. In *ICLR*, 2019.

[25] Z. Cao and D. Sadigh. Learning from imperfect demonstrations from agents with varying dynamics. *IEEE Robotics and Automation Letters (RA-L)*, 2021.

[26] P. Sharma, L. Mohan, L. Pinto, and A. Gupta. Multiple interactions made easy (mime): Large scale demonstrations data for imitation. In *CoRL*, 2018.

[27] T. Gangwani and J. Peng. State-only imitation with transition dynamics mismatch. In *ICLR*, 2020.

[28] I. Radosavovic, X. Wang, L. Pinto, and J. Malik. State-only imitation learning for dexterous manipulation. *arXiv preprint arXiv:2004.04650*, 2020.

[29] T. Chen, S. Kornblith, M. Norouzi, and G. Hinton. A simple framework for contrastive learning of visual representations. In *ICML*, 2020.

[30] E. Coumans and Y. Bai. Pybullet, a python module for physics simulation for games, robotics and machine learning. 2016.

[31] Y.-H. Wu, N. Charoenphakdee, H. Bao, V. Tangkaratt, and M. Sugiyama. Imitation learning from imperfect demonstration. In *ICML*, 2019.