Heavy Ball Momentum for Conditional Gradient

Abstract

Conditional gradient, aka Frank Wolfe (FW) algorithms, have well-documented merits in machine learning and signal processing applications. Unlike projection-based methods, momentum ones cannot improve the convergence rate of FW, in general. This limitation motivates the present work, which deals with heavy ball momentum, and its impact to FW. Specifically, it is established that heavy ball offers a unifying perspective on the primal-dual (PD) convergence, and enjoys a tighter *per iteration* PD error rate, for multiple choices of step sizes, where PD error can serve as the stopping criterion in practice. In addition, it is asserted that restart, a scheme typically employed jointly with Nesterov's momentum, can further tighten this PD error bound. Numerical results demonstrate the usefulness of heavy ball momentum in FW iterations.

1 Introduction

This work studies momentum in Frank Wolfe (FW) methods [8, 9, 15, 20] for solving

$$\min_{\mathbf{x} \in \mathcal{X}} f(\mathbf{x}). \tag{1}$$

Here, f is a convex function with Lipschitz continuous gradients, and the constraint set $\mathcal{X} \subset \mathbb{R}^d$ is assumed convex and compact, where d is the dimension of variable $\mathbf{x}$. Throughout, we let $\mathbf{x}^* \in \mathcal{X}$ denote a minimizer of (1). FW and its variants are prevalent in various machine learning and signal processing applications, such as traffic assignment [11], structured SVM [18], video colocation [16], image reconstruction [14], particle filtering [19], electronic vehicle charging [33], recommender systems [10], optimal transport [25], and neural network pruning [32]. The popularity of FW is partially due to the elimination of projection compared with projected gradient descent (GD) [28], leading to computational efficiency especially when d is large. In particular, FW solves a subproblem with a linear loss, i.e., $\mathbf{v}_{k+1} \in \arg\min_{\mathbf{v} \in \mathcal{X}} \langle \nabla f(\mathbf{x}_k), \mathbf{v} \rangle$ at kth iteration, and then updates $\mathbf{x}_{k+1}$ as a convex combination of $\mathbf{x}_k$ and $\mathbf{v}_{k+1}$. When dealing with a structured $\mathcal{X}$, a closed-form or efficient solution for $\mathbf{v}_{k+1}$ is available [12, 15], which is preferable over projection.

Unlike projected based algorithms [13, 30] though, momentum does not perform well with FW. Indeed, the lower bound in [15, 20] demonstrates that at least $\mathcal{O}(\frac{1}{\epsilon})$ linear subproblems are required to ensure $f(\mathbf{x}_k) - f(\mathbf{x}^*) \leq \epsilon$, which does not guarantee that momentum is beneficial for FW, because even vanilla FW achieves this lower bound. In this work, we contend that momentum is evidently useful for FW. Specifically, we prove that the *heavy ball momentum* leads to tightened and efficiently computed primal-dual error bound and numerical improvement. To this end, we outline first the primal convergence.

Primal convergence. The primal error refers to $f(\mathbf{x}_k) - f(\mathbf{x}^*)$. It is guaranteed for FW that $f(\mathbf{x}_k) - f(\mathbf{x}^*) = \mathcal{O}(\frac{1}{k}), \forall k \geq 1$ [15, 22]. This rate is tight in general since it matches to the lower bound [15, 20]. Other FW variants also ensure the same order of primal error; see e.g., [20, 21].

Primal-dual convergence. The primal-dual (PD) error quantifies the difference between both the primal and the 'dual' functions from the optimal objective, hence it is an upper bound on the

Table 1: A comparison of HFW with relevant works. The "computation" in the third column is short for "the number of required FW subproblems to calculate the PD error per iteration."

reference	computation	PD conv. type	PD conv. rate
[15]	1 subproblem	Type I	$\frac{27LD^2}{4(K+1)}$
[17]	2 subproblems	Type II	$\frac{2LD^2}{\sqrt{k+1}}, \forall k$
[27]	2 subproblems	Type II	$\frac{4LD^2}{k+1}, \forall k$
This work (Alg. 2)	1 subproblem	Type II	$\frac{2LD^2}{k+1}, \forall k$
This work (Alg. 3)	2 subproblems	Type II	$\frac{2LD^2}{k+1+c}, \forall k$ with $c \geq 0$

primal error. When the PD error is shown to *converge*, it can be safely used as the stopping criterion: whenever the PD error is less than some prescribed $\epsilon > 0$, $f(\mathbf{x}_k) - f(\mathbf{x}^*) \leq \epsilon$ is ensured automatically. The PD error of FW is convenient to compute, hence FW is suitable for the requirement of "solving problems to some desirable accuracy;" see e.g., [31]. For pruning (two-layer) neural networks [32], the extra training loss incurred by removing neurons can be estimated via the PD error. However, due to technical difficulties, existing analyses on PD error are not satisfactory enough and lack of unification. It is established in [6, 9, 15] that the minimum PD error is sufficiently small, namely $\min_{k \in \{1, \ldots, K\}} \text{PDError}_k = \mathcal{O}\left(\frac{1}{K}\right)$, where K is the total number of iterations. We term such a bound for the minimum PD error as Type I guarantee. Another stronger guarantee, which directly implies Type I bound, emphasizes the per iteration convergence, e.g., $\text{PDError}_k \leq \mathcal{O}(\frac{1}{k}), \forall k$. We term such guarantees as Type II bound. A Type II bound is reported in [17, Theorem 2], but with an unsatisfactory k dependence. This is improved by [27] with the price of extra computational burden since it involves solving *two* FW subproblems per iteration for computing this PD error. Several related works such as [9] provide a weaker PD error compared with [27]; see a summary in Table 1.

In this work, we show that a computationally affordable Type II bound can be obtained by simply relying on heavy ball momentum. Interestingly, FW based on heavy ball momentum (HFW) also maintains FW's neat geometric interpretation. Through unified analysis, the resultant type II PD error improves over existing bounds; see Table 1. This PD error of HFW is further tightened using *restart*. Although restart is more popular in projection based methods together with Nesterov's momentum [29], we show that restart for FW is natural to adopt jointly with heavy ball. In succinct form, our contributions can be summarized as follows.

• We show through unified analysis that HFW enables a tighter type II guarantee for PD error for multiple choices of the step size. When used as stopping criterion, no extra subproblem is needed.

• The Type II bound can be further tightened by restart triggered through a comparison between two PD-error-related quantities.

• Numerical tests on benchmark datasets support the effectiveness of heavy ball momentum. As a byproduct, a simple yet efficient means of computing local Lipschitz constants becomes available to improve the numerical efficiency of smooth step sizes [12, 22].

Notation. Bold lowercase (capital) letters denote column vectors (matrices); $\|\mathbf{x}\|$ stands for a norm of a vector $\mathbf{x}$, whose dual norm is denoted by $\|\mathbf{x}\|_*$; and $\langle \mathbf{x}, \mathbf{y} \rangle$ is the inner product of $\mathbf{x}$ and $\mathbf{y}$.

2 Preliminaries

This section outlines FW, starting with standard assumptions that will be taken to hold true throughout.

Assumption 1. *(Lipschitz continuous gradient.) The objective function $f : \mathcal{X} \to \mathbb{R}$ has L-Lipschitz continuous gradients; i.e., $\|\nabla f(\mathbf{x}) - \nabla f(\mathbf{y})\|_* \leq L\|\mathbf{x} - \mathbf{y}\|, \forall \mathbf{x}, \mathbf{y} \in \mathcal{X}$.*

Assumption 2. *(Convexity.) The objective function $f : \mathcal{X} \to \mathbb{R}$ is convex; that is, $f(\mathbf{y}) - f(\mathbf{x}) \geq \langle \nabla f(\mathbf{x}), \mathbf{y} - \mathbf{x} \rangle, \forall \mathbf{x}, \mathbf{y} \in \mathcal{X}$.*

Assumption 3. *(Convex and compact constraint set.) The constraint set $\mathcal{X} \subset \mathbb{R}^d$ is convex and compact with diameter D, that is, $\|\mathbf{x} - \mathbf{y}\| \leq D, \forall \mathbf{x}, \mathbf{y} \in \mathcal{X}$.*

FW for solving (1) under Assumptions 1–3 is listed in Alg. 1. The subproblem in Line 3 can be visualized geometrically as minimizing a supporting hyperplane of $f(\mathbf{x})$ at $\mathbf{x}_k$, i.e.,

$$\mathbf{v}_{k+1} \in \arg\min_{\mathbf{v}\in\mathcal{X}} f(\mathbf{x}_k) + \langle \nabla f(\mathbf{x}_k), \mathbf{v} - \mathbf{x}_k \rangle. \quad (2)$$

Algorithm 1 FW [8]

1: **Initialize:** $\mathbf{x}_0 \in \mathcal{X}$
2: **for** $k = 0, 1, \ldots, K - 1$ **do**
3:      $\mathbf{v}_{k+1} = \arg\min_{\mathbf{v}\in\mathcal{X}} \langle \nabla f(\mathbf{x}_k), \mathbf{v} \rangle$
4:      $\mathbf{x}_{k+1} = (1 - \eta_k)\mathbf{x}_k + \eta_k \mathbf{v}_{k+1}$
5: **end for**
6: **Return:** $\mathbf{x}_K$

For many constraint sets, efficient implementation or a closed-form solution is available for $\mathbf{v}_{k+1}$; see e.g., [15] for a comprehensive summary. Upon minimizing the supporting hyperplane in (2), $\mathbf{x}_{k+1}$ is updated as a convex combination of $\mathbf{v}_{k+1}$ and $\mathbf{x}_k$ in Line 4 so that no projection is required. The choices on the step size $\eta_k \in [0, 1]$ will be discussed shortly.

The PD error of Alg. 1 is captured by the so-termed *FW gap*, formally defined as

$$\bar{\mathcal{G}}_k := \langle \nabla f(\mathbf{x}_k), \mathbf{x}_k - \mathbf{v}_{k+1} \rangle = \underbrace{f(\mathbf{x}_k) - f(\mathbf{x}^*)}_{\text{primal error}} + \underbrace{f(\mathbf{x}^*) - \min_{\mathbf{v}\in\mathcal{X}}\left[f(\mathbf{x}_k) + \langle \nabla f(\mathbf{x}_k), \mathbf{v} - \mathbf{x}_k \rangle \right]}_{\text{dual error}} \quad (3)$$

where the second equation is because of (2). By appealing to the convexity of f, it can be verified that both primal and dual errors marked in (3) are no less than 0. If $\bar{\mathcal{G}}_k$ converges, one can deduce that the primal error converges. For this reason, $\bar{\mathcal{G}}_k$ is typically used as a stopping criterion for Alg. 1. Next, we focus on the step sizes that ensure convergence.

Parameter-free step size. This type of step sizes does not rely on any problem dependent parameters such as L and D, and hence it is extremely simple to implement. The most commonly adopted step size is $\eta_k = \frac{2}{k+2}$, which ensures a converging primal error $f(\mathbf{x}_k) - f(\mathbf{x}^*) \leq \frac{2LD^2}{k+1}, \forall k \geq 1$, and a weaker claim on the PD error, $\min_{k \in \{1,\ldots,K\}} \bar{\mathcal{G}}_k = \frac{27LD^2}{4K}$ [15]. A variant of PD convergence has been established recently based on a modified FW gap [27]. Although Type II convergence is observed, the modified FW gap therein is inefficient to serve as stopping criterion because an additional FW subproblem has to be solved per iteration to compute its value.

Smooth step size. When the (estimate of) Lipschitz constant L is available, one can adopt the following step sizes in Alg. 1 [22]

$$\eta_k = \min\left\{ \frac{\langle \nabla f(\mathbf{x}_k), \mathbf{x}_k - \mathbf{v}_{k+1} \rangle}{L\|\mathbf{v}_{k+1} - \mathbf{x}_k\|^2}, 1 \right\}. \quad (4)$$

Despite the estimated L is typically too pessimistic to capture the local Lipschitz continuity, such a step size ensures $f(\mathbf{x}_{k+1}) \leq f(\mathbf{x}_k)$; see derivations in Appendix A.1. The PD convergence is studied in [10], where the result is slightly weaker than that of [27].

3 FW with heavy ball momentum

After a brief recap of vanilla FW, we focus on the benefits of heavy ball momentum for FW for multiple step size choices, with special emphasis on PD errors.

3.1 Prelude

HFW is summarized in Alg. 2. Similar to GD with heavy ball momentum [13, 30], Alg. 2 updates decision variables using a weighted average of gradients $\mathbf{g}_{k+1}$. Similar to GD and FW with heavy ball momentums, the update direction of Alg. 2 is no longer guaranteed to be a descent one. This is because in Alg. 2, $\langle \nabla f(\mathbf{x}_k), \mathbf{x}_k - \mathbf{v}_{k+1} \rangle$ can be negative. Although a stochastic version of heavy ball momentum was adopted in [26] and its variants, e.g., [34], to reduce the mean square error of the gradient estimate, heavy ball is introduced here for a totally different purpose, that is, to improve the PD error. The most significant difference comes at technical perspectives, which is discussed in Sec. 3.4. Next, we gain some intuition on why heavy ball can be beneficial.

Consider $\mathcal{X}$ as an ℓ_2-norm ball, that is, $\mathcal{X} = \{\mathbf{x} \| \|\mathbf{x}\|_2 \leq R\}$. In this case, we have $\mathbf{v}_{k+1} = -\frac{R}{\|\mathbf{g}_{k+1}\|_2}\mathbf{g}_{k+1}$ in Alg. 2. The momentum $\mathbf{g}_{k+1}$ can smooth out the changes of $\{\nabla f(\mathbf{x}_k)\}$, resulting

in a more concentrated sequence $\{\mathbf{v}_{k+1}\}$. Recall that the PD error is closely related to $\mathbf{v}_{k+1}$ [cf. 3]. We hope the "concentration" of $\{\mathbf{v}_{k+1}\}$ to be helpful in reducing the changes of PD error among consecutive iterations so that a Type II PD error bound is attainable.

A few concepts are necessary to obtain a tightened PD error of HFW. First, we introduce the generalized FW gap associated with Alg. 2 that captures the PD error.

Algorithm 2 FW with heavy ball momentum

1: **Initialize:** $\mathbf{x}_0 \in \mathcal{X}, \mathbf{g}_0 = \nabla f(\mathbf{x}_0)$
2: **for** $k = 0, 1, \ldots, K - 1$ **do**
3:     $\mathbf{g}_{k+1} = (1 - \delta_k)\mathbf{g}_k + \delta_k \nabla f(\mathbf{x}_k)$
4:     $\mathbf{v}_{k+1} = \arg\min_{\mathbf{v} \in \mathcal{X}} \langle \mathbf{g}_{k+1}, \mathbf{v} \rangle$
5:     $\mathbf{x}_{k+1} = (1 - \eta_k)\mathbf{x}_k + \eta_k \mathbf{v}_{k+1}$
6: **end for**
7: **Return:** $\mathbf{x}_K$

Write $\mathbf{g}_{k+1}$ explicitly as $\mathbf{g}_{k+1} = \sum_{\tau=0}^{k} w_k^\tau \nabla f(\mathbf{x}_\tau)$, where $w_k^\tau = \delta_\tau \prod_{j=\tau+1}^{k}(1 - \delta_j) > 0, \; \forall \tau \geq 1$, and $w_k^0 = \prod_{j=1}^{k}(1 - \delta_j) > 0$. Then, define a sequence of linear functions $\{\Phi_k(\mathbf{x})\}$ as

$$\Phi_{k+1}(\mathbf{x}) := \sum_{\tau=0}^{k} w_k^\tau \big[f(\mathbf{x}_\tau) + \langle \nabla f(\mathbf{x}_\tau), \mathbf{x} - \mathbf{x}_\tau \rangle \big], \; \forall k \geq 0. \tag{5}$$

It is clear that $\Phi_{k+1}(\mathbf{x})$ is a weighted average of the supporting hyperplanes of $f(\mathbf{x})$ at $\{\mathbf{x}_\tau\}_{\tau=0}^{k}$. The properties of $\Phi_{k+1}(\mathbf{x})$, and how they relate to Alg. 2 are summarized in the next lemma.

Lemma 1. *For the linear function $\Phi_{k+1}(\mathbf{x})$ in (5), it holds that: i) $\mathbf{v}_{k+1}$ minimizes $\Phi_{k+1}(\mathbf{x})$ over $\mathcal{X}$; and, ii) $f(\mathbf{x}) \geq \Phi_{k+1}(\mathbf{x}), \forall k \geq 0, \forall \mathbf{x} \in \mathcal{X}$.*

From the last lemma, one can see that $\mathbf{v}_k$ is obtained by minimizing $\Phi_k(\mathbf{x})$, which is an affine lower bound on $f(\mathbf{x})$. Hence, HFW admits a geometric interpretation similar to that of FW. In addition, based on $\Phi_k(\mathbf{x})$ we can define the generalized FW gap.

Definition 1. *(Generalized FW gap.) The generalized FW gap w.r.t. $\Phi_k(\mathbf{x})$ is*

$$\mathcal{G}_k := f(\mathbf{x}_k) - \min_{\mathbf{x} \in \mathcal{X}} \Phi_k(\mathbf{x}) = f(\mathbf{x}_k) - \Phi_k(\mathbf{v}_k). \tag{6}$$

In words, the generalized FW gap is defined as the difference between $f(\mathbf{x}_k)$ and the minimal value of $\Phi_k(\mathbf{x})$ over $\mathcal{X}$. The newly defined $\mathcal{G}_k$ also illustrates the PD error

$$\mathcal{G}_k = f(\mathbf{x}_k) - \Phi_k(\mathbf{v}_k) = \underbrace{f(\mathbf{x}_k) - f(\mathbf{x}^*)}_{\text{primal error}} + \underbrace{f(\mathbf{x}^*) - \Phi_k(\mathbf{v}_k)}_{\text{dual error}}. \tag{7}$$

For the dual error, we have $f(\mathbf{x}^*) - \Phi_k(\mathbf{v}_k) \geq \Phi_k(\mathbf{x}^*) - \Phi_k(\mathbf{v}_k) \geq 0$, where both inequalities follow from Lemma 1. Hence, $\mathcal{G}_k \geq 0$ automatically serves as an overestimate of both primal and dual errors. When establishing the convergence of $\mathcal{G}_k$, it can be adopted as the stopping criterion for Alg. 2. Related claims have been made for the generalized FW gap [20, 23, 27]. Lack of heavy ball momentum leads to inefficiency, because an additional FW subproblem is needed to compute this gap [27]. Works [20, 23] focus on Nesterov's momentum for FW, that incurs additional memory relative to HFW; see also Sec. 3.4 for additional elaboration. Having defined the generalized FW gap, we next pursue parameter choices that establish Type II convergence guarantees.

3.2 Parameter-free step size

We first consider a parameter-free choice for HFW to demonstrate the usefulness of heavy ball

$$\delta_k = \eta_k = \frac{2}{k + 2}, \; \forall k \geq 0. \tag{8}$$

Such a choice on δ_k puts more weight on recent gradients when calculating $\mathbf{g}_{k+1}$, since $w_k^\tau = \mathcal{O}(\frac{\tau}{k^2})$. The following theorem specifies the convergence of $\mathcal{G}_k$.

Theorem 1. *If Assumptions 1-3 hold, then choosing δ_k and η_k as in (8), Alg. 2 guarantees that*

$$\mathcal{G}_k = f(\mathbf{x}_k) - \Phi_k(\mathbf{v}_k) \leq \frac{2LD^2}{k + 1}, \; \forall k \geq 1.$$

Theorem 1 provides a much stronger PD guarantee for all k than vanilla FW [15, Theorem 2]. In addition to a readily computable generalized FW gap, our rate is tighter than [27], where the provided bound is $\frac{4LD^2}{k+1}$. In fact, the constants in our PD bound even match to the best known primal error of vanilla FW. A direct consequence of Theorem 1 is the convergence of both primal and dual errors.

Corollary 1. *Choosing the parameters as in Theorem 1, then $\forall k \geq 1$, Alg.2 guarantees that*

$$\text{primal conv.: } f(\mathbf{x}_k) - f(\mathbf{x}^*) \leq \frac{2LD^2}{k+1}; \quad \text{dual conv.: } f(\mathbf{x}^*) - \Phi_k(\mathbf{v}_k) \leq \frac{2LD^2}{k+1}.$$

Proof. Combine Theorem 1 with $f(\mathbf{x}_k) - f(\mathbf{x}^*) \leq \mathcal{G}_k$ and $f(\mathbf{x}^*) - \Phi_k(\mathbf{v}_k) \leq \mathcal{G}_k$ [cf. (7)]. □

3.3 Smooth step size

Next, we focus on HFW with a variant of the smooth step size

$$\delta_k = \frac{2}{k+2} \quad \text{and} \quad \eta_k = \max\left\{0, \min\left\{\frac{\langle \nabla f(\mathbf{x}_k), \mathbf{x}_k - \mathbf{v}_{k+1}\rangle}{L\|\mathbf{v}_{k+1} - \mathbf{x}_k\|^2}, 1\right\}\right\}. \tag{9}$$

Comparing with the smooth step size for vanilla FW in (4), it can be deduced that the choice on η_k in (9) has to be trimmed to $[0, 1]$ manually. This is because $\langle \nabla f(\mathbf{x}_k), \mathbf{x}_k - \mathbf{v}_{k+1}\rangle$ is no longer guaranteed to be positive. The smooth step size enables an adaptive means of adjusting the weight for $\nabla f(\mathbf{x}_k)$. To see this, note that when $\eta_k = 0$, we have $\mathbf{x}_{k+1} = \mathbf{x}_k$. As a result, $\mathbf{g}_{k+2} = (1 - \delta_{k+1})\mathbf{g}_{k+1} + \delta_{k+1}\nabla f(\mathbf{x}_{k+1}) = (1 - \delta_{k+1})\mathbf{g}_{k+1} + \delta_{k+1}\nabla f(\mathbf{x}_k)$, that is, the weight on $\nabla f(\mathbf{x}_k)$ is adaptively increased to $\delta_k(1 - \delta_{k+1}) + \delta_{k+1}$ if one further unpacks $\mathbf{g}_{k+1}$. Another analytical benefit of the step size in (9) is that it guarantees a non-increasing objective value; see Appendix A.2 for derivations. Convergence of the generalized FW gap is established next.

Theorem 2. *If Assumptions 1-3 hold, while η_k and δ_k are chosen as in (9), Alg. 2 guarantees that*

$$\mathcal{G}_k = f(\mathbf{x}_k) - \Phi_k(\mathbf{v}_k) \leq \frac{2LD^2}{k+1}, \; \forall k \geq 1.$$

The proof of Theorem 2 follows from that of Theorem 1 after modifying just one inequality. This considerably simplifies the analysis on the (modified) FW gap compared to vanilla FW with smooth step size [10]. The PD convergence clearly implies the convergence of both primal and dual errors. A similar result to Corollary 1 can be obtained, but we omit it for brevity. We further extend Theorem 2 in Appendix B.4 by showing that if a slightly more difficult subproblem can be solved, it is possible to ensure *per step descent on the PD error; i.e., $\mathcal{G}_{k+1} \leq \mathcal{G}_k$*.

Line search. When choosing $\delta_k = \frac{2}{k+2}$ and η_k via line search, HFW can guarantee a Type II PD error of $\frac{2LD^2}{k+1}$; please refer to Appendix B.5 due to space limitation. For completeness, an iterative manner to update $\mathcal{G}_k$ for using as stopping criterion is also described in Appendix C.

3.4 Further considerations

There are more choices of δ_k and η_k leading to (primal) convergence. For example, one can choose $\delta_k \equiv \delta \in (0, 1)$ and $\eta_k = \mathcal{O}\left(\frac{1}{k}\right)$ as an extension of [26].[1] A proof is provided in Appendix B.7 for completeness. This analysis framework in [26], however, has two shortcomings: i) the convergence can be only established using ℓ_2-norm (recall that in Assumption 1, we do not pose any requirement on the norm); and, ii) the final primal error (hence PD error) can only be worse than vanilla FW because their analysis treats $\mathbf{g}_{k+1}$ as $\nabla f(\mathbf{x}_k)$ with errors but not momentum, therefore, it is difficult to obtain the same tight PD bound as in Theorem 1. Our analytical techniques avoid these limitations.

When choosing $\delta_k = \eta_k = \frac{1}{k+1}$, we can recover Algorithm 3 in [1]. Notice that such a choice on δ_k makes $\mathbf{g}_{k+1}$ a uniform average of all gradients. A slower convergence rate $f(\mathbf{x}_k) - f(\mathbf{x}^*) = \mathcal{O}\left(\frac{LD^2 \ln k}{k}\right)$ was established in [1] through a sophisticated derivation using no-regret online learning. Through our simpler analytical framework, we can attain the same rate while providing more options for the step size.

Theorem 3. *Let Assumptions 1-3 hold, and select $\delta_k = \frac{1}{k+1}$ with η_k using one of the following options: i) $\eta_k = \frac{1}{k+1}$; ii) as in (9); or iii) line search as in (26b). The generalized FW gap of Alg. 2 then converges with rate*

$$\mathcal{G}_k = f(\mathbf{x}_k) - \Phi_k(\mathbf{v}_k) \leq \frac{LD^2 \ln(k+1)}{2k}, \; \forall k \geq 1.$$

---

[1]We are unable to derive even a primal error bound using the same analysis framework in [26] for step sizes listed in Theorem 1.

191 The rate in Theorem 3 has worse dependence on k relative to Theorems 1 and 2, partially because too
192 much weight is put on past gradients in $\mathbf{g}_{k+1}$, suggesting that large momentum may not be helpful.

193 **Heavy ball versus Nesterov's momentum.** A simple rule to compare these two momentums is
194 whether gradient is calculated at the converging sequence $\{\mathbf{x}_k\}$. Heavy ball momentum follows this
195 rule, while Nesterov's momentum computes the gradient at some extrapolation points that are not
196 used in Alg. 2. It is unclear how the original Nesterov's momentum benefits the PD error, but the
197 ∞-memory variant of Nesterov's momentum [20, 23], which can be viewed as a combination of
198 heavy ball and Nesterov's momentum, yields a Type II PD error. However, compared with HFW,
199 additional memory should be allocated. In sum, these observations suggest that heavy ball momentum
200 is essentially critical to improve the PD performance of FW. Nesterov's momentum, on the other
201 hand, does not influence PD error when used alone; however, it gives rise to faster (local) primal rates
202 under additional assumptions [20, 23].

3.5 A side result: Directional smooth step sizes

204 Common to both FW and HFW is that the estimated L might be too pessimistic for a local update. In
205 this subsection, a local Lipschitz constant is investigated to further improve the numerical efficiency
206 of smooth step sizes in (9). This easily computed local Lipschitz constant is another merit of (H)FW
207 over projection based approaches.

208 **Definition 2.** *(Directional Lipschitz continuous.) For two points $\mathbf{x}, \mathbf{y} \in \mathcal{X}$, the directional Lipschitz*
209 *constant $L(\mathbf{x}, \mathbf{y})$ ensures $\|\nabla f(\hat{\mathbf{x}}) - \nabla f(\hat{\mathbf{y}})\|_* \leq L(\mathbf{x}, \mathbf{y})\|\hat{\mathbf{x}} - \hat{\mathbf{y}}\|$ for any $\hat{\mathbf{x}} = (1 - \alpha)\mathbf{x} + \alpha\mathbf{y}, \hat{\mathbf{y}} =$*
210 *$(1 - \beta)\mathbf{x} + \beta\mathbf{y}$ with some $\alpha \in [0, 1]$ and $\beta \in [0, 1]$.*

211 In other words, the directional Lipschitz continuity depicts the local property on the segment between
212 points $\mathbf{x}$ and $\mathbf{y}$. It is clear that $L(\mathbf{x}, \mathbf{y}) \leq L$. Using logistic loss for binary classification as an
213 example, we have $L(\mathbf{x}, \mathbf{y}) \leq \frac{1}{4N} \sum_{i=1}^{N} \frac{\langle \mathbf{a}_i, \mathbf{x} - \mathbf{y} \rangle^2}{\|\mathbf{x} - \mathbf{y}\|_2^2}$, where N is the number of data, and $\mathbf{a}_i$ is the
214 feature of the ith datum. As a comparison, the global Lipschitz constant is $L \leq \frac{1}{4N} \sum_{i=1}^{N} \|\mathbf{a}_i\|_2^2$. We
215 show in Appendix E that at least for a class of functions, including widely used logistic loss and
216 quadratic loss, $L(\mathbf{x}, \mathbf{y})$ has an analytical form.

217 Simply replacing L in (9) with $L(\mathbf{x}_k, \mathbf{v}_{k+1})$, i.e.,

$$\eta_k = \max\left\{0, \min\left\{\frac{\langle \nabla f(\mathbf{x}_k), \mathbf{x}_k - \mathbf{v}_{k+1} \rangle}{L(\mathbf{x}_k, \mathbf{v}_{k+1})\|\mathbf{v}_{k+1} - \mathbf{x}_k\|^2}, 1\right\}\right\} \tag{10}$$

218 we can obtain what we term *directionally smooth step size*. By exploring the collinearity of $\mathbf{x}_k, \mathbf{x}_{k+1}$
219 and $\mathbf{v}_{k+1}$, a simple modification of Theorem 2 ensures the PD convergence.

220 **Corollary 2.** *Choosing $\delta_k = \frac{2}{k+2}$, and η_k via (10), Alg. 2 ensures*

$$\mathcal{G}_k = f(\mathbf{x}_k) - \Phi_k(\mathbf{v}_k) \leq \frac{2LD^2}{k+1}, \ \forall k \geq 1.$$

221 The directional Lipschitz constant can also replace the global one in other FW variants, such as [12, 22],
222 with theories therein still holding. Numerical tests in Appendix F.3 illustrate that directional smooth
223 step sizes outperform the vanilla one by an order of magnitude.

4 Restart further tightens the PD error

225 Up till now it is established that the heavy ball momentum enables a unified analysis for tighter
226 Type II PD bounds. In this section, we show that if the computational resources are sufficient for
227 solving two FW subproblems per iteration, the PD error can be further improved by restart when the
228 standard FW gap is smaller than generalized FW gap. Restart is typically employed by Nesterov's
229 momentum in projection based methods [29] to cope with the robustness to parameter estimates, and
230 to capture the local geometry of problem (1). However, it is natural to integrate restart with heavy
231 ball momentum in FW regime. In addition, restart provides an answer to the following question:
232 *which is smaller, the generalized FW gap or the vanilla one?* Previous works using the generalized
233 FW gap have not addressed this question [20, 23, 27].

FW with heavy ball momentum and restart is summarized under Alg. 3. For exposition clarity, when updating the counters such as k and s, we use notation '←'. Alg. 3 contains two loops. The inner loop is the same as Alg. 2 except for computing a standard FW gap (Line 12) in addition to the generalized one (Line 11). The variable K_s, depicting the iteration number of inner loop s, is of analysis purpose. Alg. 3 can be terminated immediately whenever $\min\{\mathcal{G}_k^s, \bar{\mathcal{G}}_k^s\} \leq \epsilon$ for a desirable $\epsilon > 0$. The restart happens when the standard FW gap is smaller than generalized FW gap. And after restart, $\mathbf{g}_{k+1}^s$ will be reset. For Alg. 3, the linear functions used for generalized FW gap are defined stage-wisely

---

Algorithm 3 FW with heavy ball momentum and restart

1: **Initialize:** $\mathbf{x}_0^0 \in \mathcal{X}, \mathbf{g}_0^0 = \nabla f(\mathbf{x}_0^0),\ s \leftarrow 0,\ C^0 = 0,$ $\mathcal{G}_0^0 = \bar{\mathcal{G}}_0^0$
2: **while** [not terminated] **do**
3:      $k \leftarrow 0, \mathbf{g}_0^s = \nabla f(\mathbf{x}_0^s)$
4:      **while** [$\mathcal{G}_k^s \leq \bar{\mathcal{G}}_k^s$ or $k = 0$] and [not terminated] **do**
5:          $\delta_k^s = \frac{2}{k+2+C^s}$
6:          $\mathbf{g}_{k+1}^s = (1-\delta_k^s)\mathbf{g}_k^s + \delta_k^s \nabla f(\mathbf{x}_k^s)$
7:          $\mathbf{v}_{k+1}^s = \arg\min_{\mathbf{x}\in\mathcal{X}} \langle \mathbf{g}_{k+1}^s, \mathbf{x}\rangle$
8:          $\mathbf{x}_{k+1}^s = (1-\eta_k^s)\mathbf{x}_k^s + \eta_k^s \mathbf{v}_{k+1}^s$
9:          $\bar{\mathbf{v}}_{k+1}^s = \arg\min_{\mathbf{x}\in\mathcal{X}} \langle \nabla f(\mathbf{x}_{k+1}^s), \mathbf{x}\rangle$
10:        $\mathcal{G}_{k+1}^s = f(\mathbf{x}_{k+1}^s) - \Phi_{k+1}^s(\mathbf{v}_{k+1}^s)$
11:        $\bar{\mathcal{G}}_{k+1}^s = \langle \nabla f(\mathbf{x}_k^s), \mathbf{x}_k^s - \bar{\mathbf{v}}_{k+1}^s\rangle$
12:        $k \leftarrow k+1$
13:      **end while**
14:      $K_s \leftarrow k, \mathbf{x}_0^{s+1} = \mathbf{x}_{K_s}^s, C^{s+1} = \frac{2LD^2}{\mathcal{G}_{K_s}^s}, s \leftarrow s+1$
15: **end while**

$$\Phi_0^s(\mathbf{x}) = f(\mathbf{x}_0^s) + \langle \nabla f(\mathbf{x}_0^s), \mathbf{x} - \mathbf{x}_0^s\rangle \tag{11a}$$

$$\Phi_{k+1}^s(\mathbf{x}) = (1-\delta_k^s)\Phi_k^s(\mathbf{x}) + \delta_k^s[f(\mathbf{x}_k^s) + \langle \nabla f(\mathbf{x}_k^s), \mathbf{x} - \mathbf{x}_k^s\rangle], \forall\, k \geq 0. \tag{11b}$$

It can be verified that $\mathbf{v}_{k+1}^s$ minimizes $\Phi_{k+1}^s(\mathbf{x})$ over $\mathcal{X}$ for any $k \geq 0$. In addition, we also have $f(\mathbf{x}_0^s) - \Phi_0^s(\mathbf{v}_0^s) = \bar{\mathcal{G}}_{K_{s-1}}^{s-1}$ where $\mathbf{v}_0^s = \arg\min_{\mathbf{x}\in\mathcal{X}} \Phi_0^s(\mathbf{x})$.

There are two tunable parameters η_k^s and δ_k^s. The choice on δ_k^s has been provided directly in Line 6, where it is adaptively decided using a variable C^s relating to the generalized FW gap. Three choices are readily available for η_k^s: i) $\eta_k^s = \delta_k^s$; ii) smooth step size:

$$\eta_k^s = \max\left\{0, \min\left\{\frac{\langle \nabla f(\mathbf{x}_k^s), \mathbf{x}_k^s - \mathbf{v}_{k+1}^s\rangle}{L\|\mathbf{v}_{k+1}^s - \mathbf{x}_k^s\|^2}, 1\right\}\right\}; \tag{12}$$

and, iii) line search

$$\eta_k^s = \arg\min_{\eta\in[0,1]} f\big((1-\eta)\mathbf{x}_k^s + \eta \mathbf{v}_{k+1}^s\big). \tag{13}$$

Note that the directionally smooth step size, i.e., replacing L with $L(\mathbf{x}_k^s, \mathbf{v}_{k+1}^s)$ in (12) is also valid for convergence. We omit it to reduce repetition. Next we show how restart improves the PD error.

Theorem 4. *Choose η_k^s via one of the three manners: i) $\eta_k^s = \delta_k^s$; ii) as in (12); or iii) as in (13). If there is no restart (e.g., $s = 0$ when terminating), then Alg. 3 guarantees that*

$$\mathcal{G}_k^0 = f(\mathbf{x}_k^0) - \Phi_k(\mathbf{v}_k^0) \leq \frac{2LD^2}{k+1}, \forall k \geq 1. \tag{14a}$$

If restart happens, in additional to (14a), we have

$$\mathcal{G}_k^s = f(\mathbf{x}_k^s) - \Phi_k(\mathbf{v}_k^s) < \frac{2LD^2}{k+C^s}, \forall k \geq 1, \forall s \geq 1,\ \ with\ C^s \geq 1 + \sum_{j=0}^{s-1} K_j. \tag{14b}$$

Besides the convergence of both primal and dual errors of Alg. 3, Theorem 4 implies that when no restart happens, the generalized FW gap is smaller than the standard one, demonstrating that the former is more suitable for the purpose of "stopping criterion". When restarted, Theorem 4 provides a strictly improved bound compared with Theorems 1, 2, and 6, since the denominator of the RHS in (14b) is no smaller than the total iteration number. An additional comparison with [27], where two subproblems are also required, once again confirms the power of heavy ball momentum to improve the constants in the PD error rate, especially with the aid of restart.

Figure 1: Performance of FW variants for binary classification with the constraint being an ℓ_2-norm ball (first row), an ℓ_1-norm ball (second row), and an n-support norm ball (third row) on datasets *w7a* (first column), *realsim* (second column), *mushroom* (thrid column), and *ijcnn1* (forth column).

5 Numerical tests

This section presents numerical tests to showcase the effectiveness of HFW on different machine learning problems. Since there are two parameters' choices for HFW in Theorems 1 and 3, we term them as weighted FW (WFW) and uniform FW (UFW), respectively, depending on the weight of $\{\nabla f(\mathbf{x}_k)\}$ in $\mathbf{g}_{k+1}$. When Using smooth step size, the corresponding algorithms are marked as WFW-s and UFW-s. For comparison, the benchmark algorithms include: FW with $\eta_k = \frac{2}{k+2}$ (FW); and, FW with smooth step size (FW-s) in (4). The performances of directionally smooth step sizes are detailed in Appendix.

5.1 Binary classification

We first test the performance of Alg. 2 on binary classification using logistic regression

$$f(\mathbf{x}) = \frac{1}{N} \sum_{i=1}^{N} \ln \left(1 + \exp(-b_i \langle \mathbf{a}_i, \mathbf{x} \rangle) \right). \tag{15}$$

Here $(\mathbf{a}_i, b_i)$ is the (feature, label) pair of datum i, and N is the number of data. Datasets from LIBSVM[2] are used in the numerical tests, where details of the datasets are deferred to Appendix F due to space limitation.

ℓ_2-**norm ball constraint.** We start with $\mathcal{X} = \{\mathbf{x} | \|\mathbf{x}\|_2 \le R\}$. The primal errors are plotted in the first row of Fig. 3. We use primal error mainly for a fair comparison. It can be seen that the parameter-free step sizes achieve better performance compared with the smooth step sizes mainly because the quality of L estimate. Such a problem can be relived through directional smooth step sizes as shown in additional tests in Appendix F.3. Among parameter-free step sizes, it can be seen that WFW consistently outperforms both UFW and FW on all tested datasets, while UFW converges faster than FW only on datasets *realsim* and *mushroom*. For smooth step sizes, the per step descent property is validated.

ℓ_1-**norm ball constraint.** Here $\mathcal{X} = \{\mathbf{x} | \|\mathbf{x}\|_1 \le R\}$ denotes the constraint set that promotes sparse solutions. In the simulation, R is tuned to for a solution with similar sparsity as the dataset itself. The results are showcased in the second row of Fig. 3. For smooth step sizes, FW-s, UFW-s, and WFW-s exhibit similar performances, and their curves are smooth. On the other hand, parameter-free step

[2]https://www.csie.ntu.edu.tw/~cjlin/libsvmtools/datasets/binary.html.

297 sizes eventually outperform smooth step sizes
298 though the curves zig-zag. (The curves on *re-*
299 *alsim* are smoothed to improve figure quality.)
300 UFW has similar performance on *w7a* and
301 *mushroom* with FW and faster convergence on
302 other datasets. Once again, WFW consistently
303 outperforms FW and UFW.

304 *n*-**support norm ball constraint.** The *n*-
305 support norm ball is a tighter relaxation of

Figure 2: FW variants for matrix completion. From left to right: primal error, and solution rank.

306 a sparsity enforcing ℓ_0-norm ball combined with an ℓ_2-norm penalty compared with ElasticNet [35].
307 It gives rise to $\mathcal{X} = \mathrm{conv}\{\mathbf{x}|\|\mathbf{x}\|_0 \leq n, \|\mathbf{x}\|_2 \leq R\}$, where $\mathrm{conv}\{\cdot\}$ denotes the convex hull [3]. The
308 closed-form solution of $\mathbf{v}_{k+1}$ is given in [24]. In the simulation, we choose $n = 2$ and tune R for
309 a solution whose sparsity is similar to the adopted dataset. The results are showcased in the third
310 row of Fig. 3. For smooth step sizes, FW-s and WFW-s exhibit similar performance, while UFW-s
311 converges slightly slower on *ijcnn1*. Regarding parameter-free step sizes, UFW does not offer faster
312 convergence compared with FW on the tested datasets, but WFW again has numerical merits.

313 In a nutshell, the numerical experiments suggest that heavy ball momentum is best use with parameter-
314 free step sizes, and the weight on momentum should be carefully adjusted. WFW is more recom-
315 mended because it achieves improved empirical performance compared with UFW and FW regardless
316 of the constraint sets. The smooth step sizes on the other hand, eliminate the zig-zag behavior at the
317 price of slower convergence due to the need of L.

5.2 Matrix completion

319 This subsection focuses on matrix completion problems for recommender systems. Consider a
320 matrix $\mathbf{A} \in \mathbb{R}^{m \times n}$ with partially observed entries, i.e., entries A_{ij} for $(i, j) \in \mathcal{K}$ are known, where
321 $\mathcal{K} \subset \{1, \ldots, m\} \times \{1, \ldots, n\}$. Based on the observed entries that can be contaminated by noise, the
322 goal is to predict the missing entries. Within the scope of recommender systems, a commonly adopted
323 empirical observation is that $\mathbf{A}$ is low rank [4,5,7], leading to the following problem formulation.

$$\min_{\mathbf{X}} \quad \frac{1}{2} \sum_{(i,j)\in\mathcal{K}} (X_{ij} - A_{ij})^2 \quad \text{s.t.} \ \|\mathbf{X}\|_{\mathrm{nuc}} \leq R. \tag{16}$$

324 Problem (16) is difficult to solve using GD because projection onto a nuclear norm ball requires an
325 SVD, which has complexity $\mathcal{O}(mn(m \wedge n))$. In contrast, FW and its variants are more suitable for
326 (16) since the FW subproblem has complexity less than $\mathcal{O}(mn)$ [2].

327 Heavy ball based FW are tested using dataset *MovieLens100K*[3]. Following the initialization of [10],
328 the numerical results can be found in Fig. 2. Subfigures (a) and (b), depict the optimality error and
329 rank versus k for $R = 3$. For parameter-free step sizes, WFW converges faster than FW while finding
330 solutions with lower rank. The low rank solution of UFW is partially because it does not converge
331 sufficiently. For smooth step sizes, UFW-s finds a solution with slightly larger objective value but
332 much lower rank compared with WFW-s and FW-s. Overall, when a small optimality error is the
333 priority, WFW is more attractive; while UFW-s is useful for finding low rank solutions.

6 Conclusions

335 This work demonstrated the merits of heavy ball momentum for FW. Multiple choices of the step
336 size ensured a tighter Type II primal-dual error bound, that can be efficiently computed when adopted
337 as stopping criterion. An even tighter PD error bound can be achieved by relying on both heavy ball
338 momentum and restart. A novel and general approach was developed to compute local Lipschitz
339 constants in FW type algorithms. Numerical tests in the paradigms of logistic regression and matrix
340 completion demonstrated the effectiveness of heavy ball momentum in FW.

---

[3]https://grouplens.org/datasets/movielens/100k/

References

[1] J. D. Abernethy and J.-K. Wang, "On Frank-Wolfe and equilibrium computation," in *Proc. Advances in Neural Info. Process. Syst.*, 2017, pp. 6584–6593.

[2] Z. Allen-Zhu, E. Hazan, W. Hu, and Y. Li, "Linear convergence of a Frank-Wolfe type algorithm over trace-norm balls," in *Proc. Advances in Neural Info. Process. Syst.*, 2017, pp. 6191–6200.

[3] A. Argyriou, R. Foygel, and N. Srebro, "Sparse prediction with the k-support norm," in *Proc. Advances in Neural Info. Process. Syst.*, 2012, pp. 1457–1465.

[4] R. M. Bell and Y. Koren, "Lessons from the Netflix prize challenge." *SiGKDD Explorations*, vol. 9, no. 2, pp. 75–79, 2007.

[5] J. Bennett, S. Lanning *et al.*, "The Netflix prize," in *Proc. KDD cup and workshop*, vol. 2007. New York, NY, USA., 2007, p. 35.

[6] K. L. Clarkson, "Coresets, sparse greedy approximation, and the Frank-Wolfe algorithm," *ACM Transactions on Algorithms (TALG)*, vol. 6, no. 4, p. 63, 2010.

[7] M. Fazel, "Matrix rank minimization with applications," 2002.

[8] M. Frank and P. Wolfe, "An algorithm for quadratic programming," *Naval research logistics quarterly*, vol. 3, no. 1-2, pp. 95–110, 1956.

[9] R. M. Freund and P. Grigas, "New analysis and results for the Frank–Wolfe method," *Mathematical Programming*, vol. 155, no. 1-2, pp. 199–230, 2016.

[10] R. M. Freund, P. Grigas, and R. Mazumder, "An extended Frank–Wolfe method with "in-face" directions, and its application to low-rank matrix completion," *SIAM Journal on Optimization*, vol. 27, no. 1, pp. 319–346, 2017.

[11] M. Fukushima, "A modified Frank-Wolfe algorithm for solving the traffic assignment problem," *Transportation Research Part B: Methodological*, vol. 18, no. 2, pp. 169–177, 1984.

[12] D. Garber and E. Hazan, "Faster rates for the Frank-Wolfe method over strongly-convex sets," in *Proc. Intl. Conf. on Machine Learning*, 2015.

[13] E. Ghadimi, H. R. Feyzmahdavian, and M. Johansson, "Global convergence of the heavy-ball method for convex optimization," in *Proc. of European control conference*, 2015, pp. 310–315.

[14] Z. Harchaoui, A. Juditsky, and A. Nemirovski, "Conditional gradient algorithms for norm-regularized smooth convex optimization," *Mathematical Programming*, vol. 152, no. 1-2, pp. 75–112, 2015.

[15] M. Jaggi, "Revisiting Frank-Wolfe: Projection-free sparse convex optimization." in *Proc. Intl. Conf. on Machine Learning*, 2013, pp. 427–435.

[16] A. Joulin, K. Tang, and L. Fei-Fei, "Efficient image and video co-localization with Frank-Wolfe algorithm," in *Proc. European Conf. on Computer Vision*. Springer, 2014, pp. 253–268.

[17] S. Lacoste-Julien and M. Jaggi, "On the global linear convergence of Frank-Wolfe optimization variants," in *Proc. Advances in Neural Info. Process. Syst.*, 2015, pp. 496–504.

[18] S. Lacoste-Julien, M. Jaggi, M. W. Schmidt, and P. Pletscher, "Block-coordinate Frank-Wolfe optimization for structural svms," in *Proc. Intl. Conf. on Machine Learning*, no. CONF, 2013, pp. 53–61.

[19] S. Lacoste-Julien, F. Lindsten, and F. Bach, "Sequential kernel herding: Frank-Wolfe optimization for particle filtering," in *Proc. Intl. Conf. on Artificial Intelligence and Statistics*, 2015, pp. 544–552.

[20] G. Lan, "The complexity of large-scale convex programming under a linear optimization oracle," *arXiv preprint arXiv:1309.5550*, 2013.

[21] G. Lan and Y. Zhou, "Conditional gradient sliding for convex optimization," *SIAM Journal on Optimization*, vol. 26, no. 2, pp. 1379–1409, 2016.

[22] E. S. Levitin and B. T. Polyak, "Constrained minimization methods," *USSR Computational mathematics and mathematical physics*, vol. 6, no. 5, pp. 1–50, 1966.

[23] B. Li, M. Coutino, G. B. Giannakis, and G. Leus, "How does momentum help Frank Wolfe?" *arXiv preprint arXiv:2006.11116*, 2020.

[24] B. Liu, X.-T. Yuan, S. Zhang, Q. Liu, and D. N. Metaxas, "Efficient k-support-norm regularized minimization via fully corrective Frank-Wolfe method." in *Proc. Intl. Joint Conf. on Artifical Intelligence*, 2016, pp. 1760–1766.

[25] G. Luise, S. Salzo, M. Pontil, and C. Ciliberto, "Sinkhorn barycenters with free support via Frank-Wolfe algorithm," in *Proc. Advances in Neural Info. Process. Syst.*, 2019, pp. 9318–9329.

[26] A. Mokhtari, H. Hassani, and A. Karbasi, "Stochastic conditional gradient methods: From convex minimization to submodular maximization," *arXiv preprint arXiv:1804.09554*, 2018.

[27] Y. Nesterov, "Complexity bounds for primal-dual methods minimizing the model of objective function," *Mathematical Programming*, vol. 171, no. 1-2, pp. 311–330, 2018.

[28] ——, *Introductory lectures on convex optimization: A basic course*. Springer Science & Business Media, 2004, vol. 87.

[29] B. O'donoghue and E. Candes, "Adaptive restart for accelerated gradient schemes," *Foundations of computational mathematics*, vol. 15, no. 3, pp. 715–732, 2015.

[30] B. T. Polyak, "Some methods of speeding up the convergence of iteration methods," *Ussr computational mathematics and mathematical physics*, vol. 4, no. 5, pp. 1–17, 1964.

[31] A. Schwing, T. Hazan, M. Pollefeys, and R. Urtasun, "Globally convergent parallel MAP LP relaxation solver using the Frank-Wolfe algorithm," in *Proc. Intl. Conf. on Machine Learning*, 2014, pp. 487–495.

[32] M. Ye, C. Gong, L. Nie, D. Zhou, A. Klivans, and Q. Liu, "Good subnetworks provably exist: Pruning via greedy forward selection," in *Proc. Intl. Conf. on Machine Learning*, 2020.

[33] L. Zhang, G. Wang, D. Romero, and G. B. Giannakis, "Randomized block Frank–Wolfe for convergent large-scale learning," *IEEE Transactions on Signal Processing*, vol. 65, no. 24, pp. 6448–6461, 2017.

[34] M. Zhang, Z. Shen, A. Mokhtari, H. Hassani, and A. Karbasi, "One sample stochastic Frank-Wolfe," in *Proc. Intl. Conf. on Artificial Intelligence and Statistics*. PMLR, 2020, pp. 4012–4023.

[35] H. Zou and T. Hastie, "Regularization and variable selection via the elastic net," *Journal of the royal statistical society: series B (statistical methodology)*, vol. 67, no. 2, pp. 301–320, 2005.