Improved Utility Analysis of Private CountSketch

Abstract

Sketching is an important tool for dealing with high-dimensional vectors that are sparse (or well-approximated by a sparse vector), especially useful in distributed, parallel, and streaming settings. It is known that sketches can be made differentially private by adding noise according to the sensitivity of the sketch, and this has been used in private analytics and federated learning settings. The post-processing property of differential privacy implies that *all* estimates computed from the sketch can be released within the given privacy budget.

In this paper we consider the classical CountSketch, made differentially private with the Gaussian mechanism, and give an improved analysis of its estimation error. Perhaps surprisingly, the privacy-utility trade-off is essentially the best one could hope for, independent of the number of repetitions in CountSketch: The error is almost identical to the error from non-private CountSketch plus the noise needed to make the vector private in the original, high-dimensional domain.

1 Introduction

CountSketch was introduced by Charikar, Chen, and Farach-Colton (2004) as a method for finding heavy hitters in data streams. In machine learning the same sketch was studied by Weinberger, Dasgupta, Langford, Smola, and Attenberg (2009) under the name *feature hashing*, or less formally the "hashing trick". The idea is to map a high-dimensional vector $x \in \mathbf{R}^d$ to a lower-dimensional representation $Ax \in \mathbf{R}^D$, using a certain random linear mapping A. From Ax it is possible to estimate entries x_i, with error that depends on D and the norm of x, and more generally to estimate inner products. It was shown in (Weinberger et al., 2009) that for $y \in \mathbf{R}^d$, $\langle Ax, Ay \rangle$ is well-concentrated around $\langle x, y \rangle$. Recent interest in sketching techniques is motivated by distributed applications such as *federated learning* (Kairouz et al., 2021), where many users contribute to creating a model on their combined data, without transferring data itself. In this context, sketching can be used to identify the large-magnitude entries in the sum of many high-dimensional vectors (one held by each user), using communication proportional to the number of such entries.

Perhaps the most basic property of CountSketch/feature hashing is the estimation error of estimators for a single coordinate x_i. The sketch directly provides independent, noisy estimators $X_1, \ldots, X_k$, each symmetric with mean x_i. Two main ways of combining these into a more reliable estimator for x_i have been studied: Taking the *median* estimator (Charikar et al., 2004), or taking the *average* of estimators (implicit in Weinberger et al. (2009)). Larsen, Pagh, and Tětek (2021) showed that using the median estimator with $k = 3$ makes the error decrease quadratically with the sketch size D.

In this paper we consider CountSketches that have been made differentially private using the *Gaussian mechanism*, which is perhaps the most widely used mechanism for making high-dimensional vectors differentially private. This sketch, which we will refer to as *Private Count Sketch*, works by adding i.i.d. Gaussian noise to each coordinate of the CountSketch, with variance scaled according to the (squared L_2) sensitivity k of the sketch.

We give additional evidence that the median estimator is preferable to the mean by showing that the estimation noise is independent of the number k of estimators. Previous applications of sketching techniques to differential privacy have had noise that grew (polynomially) with k. The failure probability of CountSketch decreases exponentially in k, so it is preferable to have k relatively large, and thus these methods faced a trade-off between the noise from the Gaussian mechanism and the error probability of the underlying CountSketch. We show that this trade-off is not needed: It is possible to *both* get a highly reliable CountSketch (by choosing k large enough) *and* achieve noise that depends only on the privacy parameters (independent of k).

2 Related work

The analysis of the Gaussian mechanism is attributed in Dwork, Roth, et al. (2014, Appendix A) to the the authors of the seminal paper on differential privacy (Dwork, McSherry, Nissim, and Smith, 2006). It has since been shown to have desirable properties related to keeping track of privacy loss under composition, see e.g. Bun & Steinke (2016); Mironov (2017).

Local differential privacy. A variant of CountSketch, the *Count Mean Sketch* has been used by Apple to privately collect information on heavy hitters, e.g. popular emoji in different countries (Apple Differential Privacy Team, 2017). This can be phrased in terms of summing n user vectors, each one a 1-hot vector with a single 1, and identifying the large entries. Their protocol works in the *local* model of differential privacy, which means that each report is differentially private. Lower bounds on local differential privacy (Chan, Shi, and Song, 2012) imply that the noise on estimates in this setting grow with $\Omega(\sqrt{n})$, where n is the number of users.

Independently, Bassily, Nissim, Stemmer, and Thakurta (2020) improved theoretical results of Bassily and Smith (2015) on heavy hitter estimation in the local model, providing practical methods for matching the lower bound of (Chan et al., 2012). They also base their method on CountSketch, though it is made private using a sampling technique combined with randomized response, not by adding noise to each coordinate. The noise from this step, rather than from CountSketch itself, dominates the error. Acharya, Sun, and Zhang (2019) showed that similar error can be achieved without any agreed-upon public randomness (describing a sketch matrix).

Huang, Qiu, Yi, and Cormode (2021) used CountSketch, made private with the geometric (aka. discrete Laplace) mechanism, to design protocols for frequency estimation under local differential privacy and multiparty differential privacy. They observe that the estimator in each repetition of CountSketch is symmetric (assuming fully random hashing), but unlike the present paper they do not demonstrate that the median estimator has noise that is *smaller* than the noise added to each estimator. Thus their estimation error grows with the number of repetitions of CountSketch. Recently, Zhou, Wang, Chan, Fanti, and Shi (2022) also used CountSketch as the basis for a mechanism that releases t-sparse vectors with differential privacy. We relate our result to theirs in Section 3.4.

Protocols based on cryptographic protocols. Motivated by privacy-preserving aggregation of distributed statistics, Melis, Danezis, and Cristofaro (2016) considered CountSketch (and the related Count-Min sketch) made ε-differentially private using the *Laplace mechanism* (Dwork et al., 2016). They empirically showed that the set of *heavy hitters*, i.e., large entries in the vector, could be identified with very little error on skewed distributions, but did not provide general bounds on estimation error. Their protocol can be implemented in a distributed setting in which each user has a 1-hot vector, and we want to sketch the sum of these vectors, using cryptographic protocols for secure aggregation. This bypasses lower bounds on local differential privacy, and yields much better privacy-utility trade-offs (but now assuming security of the aggregation protocols, rather than in an information-theoretic sense).

Another model of differential privacy, built on the cryptographic primitive of an *anonymous channel* (aka. mixnet), is the *shuffle model* (Cheu, Smith, Ullman, Zeber, and Zhilyaev, 2019; Erlingsson, Feldman, Mironov, Raghunathan, Talwar, and Thakurta, 2019). Ghazi, Golowich, Kumar, Pagh, and Velingker (2021) used Count-Min sketches in a protocol for frequency estimation (and heavy hitters) in this context. Our work suggests that better accuracy can be obtained by using CountSketch instead of Count-Min, especially for high-probability bounds.

Related results in the central model. Mir, Muthukrishnan, Nikolov, and Wright (2011) studied general mechanisms for making sketching algorithms differentially private, and in particular studied using the Count-Min sketch to identify heavy hitters. They observed that any mechanism that makes a linear sketch private by adding (oblivious) noise to the sketch vector implies a *pan-private* sketch that can be updated dynamically. Our work implies an improved pan-private sketch based on CountSketch.

Aumüller, Lebeda, and Pagh (2021) studied differentially private representations of sparse vectors, showing that it is possible to achieve space close to the number of non-zero entries while keeping noise comparable to a naïve application of the Laplace mechanism to the raw vectors. Our work implies that, up to a logarithmic factor in space, such a result is possible with a linear sketch, which enjoys many desirable properties.

Analysis of CountSketch. Finally, we mention that several authors have worked on improved analysis of the error of CountSketch in the non-private setting, including Minton and Price (2014) and Larsen, Pagh, and Tětek (2021). However, directly using these results to analyze private CountSketch gives weak results in terms of the number k of repetitions, since the sketch returns a single entry (possibly with the sign flipped), and the expected magnitude of the noise added to a given entry in the sketch is $\Omega(\sqrt{k})$.

3 Private CountSketch

In this section we provide the necessary background information on CountSketch, and present our improved analysis of Private Count Sketch.

We use $[k]$ to denote the set $\{1, \ldots, k\}$. Vectors are indexed by one or more integers, each from designated ranges. For example, a vector of dimension $D = kb$ may be indexed by (i, j) where $i \in [k]$ and $j \in [b]$. The ordering of vector entries is not important. For integer k, let $\text{tail}_k(x)$ denote the vector that is identical to x except that the k coordinates of largest magnitude are replaced with zeros. For a predicate P, we let $[P]$ denote the indicator that is 1 if P is true and 0 otherwise.

3.1 Background

CountSketch is a random linear mapping of a vector $x \in \mathbf{R}^d$ to $Ax \in \mathbf{R}^D$. For parameters k, b such that $D = kb$, the sketch $CS(x)$ is defined by two sequences of random, independent hash functions:

- $h_1, \ldots, h_k : [d] \to [b]$, and
- $s_1, \ldots, s_k : [d] \to \{-1, +1\}$.

CountSketch was originally presented with hash functions from a 2-wise independent families (Charikar et al., 2004), but in this paper we assume that all hash functions used are *fully random*. Full randomness is used in our analysis of error, but the privacy does not rely on this assumption. To simplify our exposition we will further assume that k is odd and that b is even.

If we index $CS(x) \in \mathbf{R}^D$ by $(i, j) \in [k] \times [b]$, then

$$CS(x)_{ij} = \sum_{\ell \in [d]} s_i(\ell) x_\ell [h_i(\ell) = j] \ .$$

That is, each vector entry x_ℓ is added, with sign $s_i(\ell)$, to entries indexed by $(i, h_i(\ell))$, for $i \in [k]$. We can see the sketch as a sequence of k hash tables, each of size b; thus we refer to k as the number of *repetitions* and to b as the *table size*. It is easy to see that

$$X_i = s_i(\ell) CS(x)_{i, h_i(\ell)}$$

is an unbiased estimator for x_ℓ for each $i \in [k]$. Furthermore, since s is fully random the distribution of X_i conditioned on $s_i(\ell) = -1$ is identical to the distribution of X_i conditioned on $s_i(\ell) = 1$, which means that X_i is symmetric around x_ℓ. We can combine these estimators into a more robust estimator:

$$\hat{x}_\ell = \text{median}\left(\{s_i(\ell) CS(x)_{i, h_i(\ell)} \mid i \in [k]\}\right) \ . \tag{1}$$

Charikar et al. (2004) bounded the error of $\hat{x}_\ell$, with a failure probability that is exponentially decreasing with k:

Theorem 3.1 (Charikar et al. (2004)). *For each $\ell \in [d]$, the estimation error of CountSketch with k repetitions and table size b satisfies*

$$\Pr\left[|\hat{x}_\ell - x_\ell| > 2\,||tail_{b/2}(x)||_2/\sqrt{b}\right] < \exp\left(-\Omega\left(k\right)\right) \ .$$

Note that $||\text{tail}_{b/2}(x)||_2 \leq ||x||_2$, but this "residual norm" can be much smaller for skewed distributions and even zero for sparse vectors. Choosing suitable $k = O(\log d)$ we get that *all* coordinates x_ℓ are estimated within this error bound with high probability.

3.2 Private CountSketch

Several approaches for releasing a CountSketch with differential privacy have been studied. These all require that the sketches of *neighboring* vectors x, x', denoted $x \sim x'$, have similar distributions. The neighboring relation that we (mainly) consider is that $x \sim x'$ if and only if these vectors differ in at most one entry, by at most 1, or equivalently that $x - x'$ has a single nonzero entry with a value in $[-1, +1]$. Since CountSketch is linear, $CS(x) - CS(x') = CS(x - x')$. From this it is easy to see that for $x \sim x'$, $||CS(x) - CS(x')||_2 \leq \sqrt{k}$. In other words, the *sensitivity* of the sketch is $\sqrt{k}$.

There are many ways to compute a differentially private version of a CountSketch $CS(x)$ (or any other function of x), but it is most common to consider *oblivious* methods that work by sampling a symmetric noise vector $\nu \in \mathbf{R}^D$ that is independent of $CS(x)$ and releasing the private CountSketch:

$$PCS(x) = CS(x) + \nu \ .$$

Since the noise is symmetric around zero, we have (similar to before) that $X_i = s_i(\ell)PCS(x)_{i,h_i(\ell)}$ is an unbiased estimator for x_ℓ, and therefore it makes sense to use the median estimator (1) also for private count sketch:

$$\bar{x}_\ell = \text{median}\left(\{s_i(\ell)PCS(x)_{i,h_i(\ell)} \mid i \in [k]\}\right) \ . \tag{2}$$

Note that except for the addition of ν, which can be considered an alternative initialization step, Private CountSketch works in *exactly the same way* as CountSketch: Updates are done in the same way, and estimators $\bar{x}_\ell$ are computed in the same way.

Properties of Private CountSketch. Since $PCS(x)$ is an affine transformation, it can be maintained under updates to x. Also, it is possible to add and subtract Private CountSketches (based on the same hash functions), e.g.:

$$PCS(x) + PCS(y) = CS(x + y) + \nu_1 + \nu_2,$$

where ν_1 and ν_2 are sampled according to the noise distribution.

The noise distribution we will consider in this paper is the standard D-dimensional *Gaussian* distribution $\mathcal{N}(0, \sigma^2)^D$ with mean zero and variance σ^2, and in the rest of this paper we refer to $PSC(x)$ with noise $\nu \sim \mathcal{N}(0, \sigma^2)^D$. Differential privacy properties of $PCS(x)$ follows from general results on the Gaussian mechanism (see e.g. Dwork et al. (2014, Apendix A) and Bun & Steinke (2016)) — we state some of them for convenience here:

Lemma 3.2. *$PCS(x)$ is (ε, δ)-differentially private for ε, δ satisfying $\sigma^2 > 2k \ln(1.25/\delta)/\varepsilon^2$, and it is $(k/2\sigma^2)$-zero-concentrated differentially private.*

This tells us that to get good privacy parameters, we need to use Gaussian noise with variance $\Omega(k)$, i.e., standard deviation $\sigma > \Omega(\sqrt{k})$. The median estimator (2) returns, for some i,

$$s_i(\ell)PCS(x)_{i,h_i(\ell)} = s_i(\ell)\left(CS(x)_{i,h_i(\ell)} + \eta_{i,h_i(\ell)}\right)$$

i.e., a value that could be returned by CountSketch plus a noise term with standard deviation $\Omega(\sqrt{k})$. Thus, we might expect the magnitude of the noise to scale proportionally to $\sqrt{k}$. Our main result is that this does *not* happen, and in fact the noise can be bounded independently of k.

Theorem 3.3. *For $\ell \in [d]$, the estimation error of Private CountSketch (using fully random hashing) with k repetitions, table size b and noise from $\mathcal{N}(0, \sigma^2)^{kb}$ satisfies for $\gamma > 2\,||tail_{b/2}(x)||_2/\sqrt{b}$:*

$$\Pr[|\bar{x}_\ell - x_\ell| > \gamma] < 2\exp\left(-\Omega\left(k\,\min\left\{1, \gamma/\sigma\right\}^2\right)\right) \ .$$

Discussion. Theorem 3.3 generalizes the tail bound on CountSketch, since if we let $\sigma = \gamma$ we can recover Theorem 3.1 by taking the limit $\sigma \to 0$. If we choose suitable $\sigma = O(\sqrt{k \log(1/\delta)}/\varepsilon)$ the Private CountSketch satisfies (ε, δ)-differential privacy. For deviation $\gamma > \max\{\sigma, \|\mathrm{tail}_{b/2}(x)\|_2/\sqrt{b}\}$ we then get:

$$\Pr[|\bar{x}_\ell - x_\ell| > \gamma] < 2 \exp\left(-\Omega\left(\gamma^2 \varepsilon^2 / \ln(1/\delta)\right)\right) .$$

Up to the hidden constant in the order-notation this is *identical* to the tail bound for the noise of the Gaussian distribution applied directly to x.

3.3 Analysis of Private CountSketch

We start by showing the following lemma that bounds the error of the median of symmetric, unbiased estimators perturbed by Gaussian noise:

Lemma 3.4. *Given $\mu \in \mathbf{R}$ and $\Delta > 0$, suppose that $\mathcal{D}$ is a symmetric probability distribution with mean μ such that $\Pr_{x \sim \mathcal{D}}[x \in [\mu - \Delta, \mu + \Delta]] > \beta$, where $\beta > 0$ is a constant. For odd integer k and $\sigma > 0$, sample i.i.d. $x_1, \ldots, x_k \sim \mathcal{D}$ and $a_1, \ldots, a_k \sim N(0, \sigma^2)$, and consider the median X of $\{x_i + a_i \mid i \in \{1, \ldots, k\}\}$. Then for $\gamma > \Delta$,*

$$\Pr[X \notin [\mu - \gamma, \mu + \gamma]] < 2 \exp\left(-\Omega\left(k \min\{1, \gamma/\sigma\}^2\right)\right) .$$

Proof. Let $X_i = x_i + a_i$ for $i \in [k]$. These are i.i.d. random variables symmetric around the mean μ.

Medians of symmetric i.i.d. random variables. We first consider medians of *arbitrary* symmetric, i.i.d. random variables, ignoring Δ for now, and let X be their median. To bound the probability that $X \in [\mu - \gamma, \mu + \gamma]$, the critical quantity to study is

$$\alpha = \Pr[\mu - \gamma \le X_i \le \mu + \gamma] .$$

By symmetry, we know that

$$\Pr[X_i < \mu - \gamma] = \Pr[X_i > \mu + \gamma] = (1 - \alpha)/2 .$$

We now show some error bounds in terms of α. By definition of the median and since k is odd,

$$X < \mu - \gamma \iff \sum_{i=1}^{k}[X_i < \mu - \gamma] > k/2$$

However, $\mathrm{E}\left[\sum_{i=1}^{k}[X_i < \mu - \gamma]\right] = k(1 - \alpha)/2$, so by a Chernoff bound we get

$$\Pr[X < \mu - \gamma] = \exp(-\Omega(k\alpha^2)) .$$

By symmetry, we have the same bound on the probability that X is larger than $\mu + \gamma$, so we have:

$$\Pr[X \notin [\mu - \gamma, \mu + \gamma]] \le 2 \exp(-\Omega(k\alpha^2)) . \tag{3}$$

Bounding α. To prove the lemma we use the specific properties of the random variables X_i to show a lower bound on α. Defining $Y = X_i - \mu = x_i + a_i - \mu$, this is equivalent to bounding $\Pr[Y \in [-\gamma, \gamma]]$. Let Y_c denote the random variable Y conditioned on $x_i = \mu + c$ (this is well-defined whenever $\mu + c$ is in the support of $\mathcal{D}$). Note that $Y_c \sim N(c, \sigma^2)$, so the probability that $Y_c \in [-\gamma, \gamma]$ decreases with the absolute value of c. For a conservative analysis, we consider the case where $|x_i - \mu| \le \Delta$ (which by assumption happens with probability at least β), and ignore the contribution to the probability α if this condition does not hold. This gives us the lower bound

$$\begin{aligned}
\alpha &\ge \Pr[|x_i - \mu| \le \Delta \wedge Y_{x_i - \mu} \in [-\gamma, \gamma]] \\
&\ge \beta \cdot \Pr[Y_{x_i - \mu} \in [-\gamma, \gamma] \mid |x_i - \mu| \le \Delta] \\
&\ge \beta \cdot \Pr_{Z \sim \mathcal{N}(\Delta, \sigma^2)}[Z \in [-\gamma, \gamma]] .
\end{aligned}$$

We now have two cases. If $\gamma \le \sigma$, then since $\Delta < \gamma$ we have

$$\Pr_{Z \sim \mathcal{N}(\Delta, \sigma^2)}[Z \in [-\gamma, \gamma]] = \Theta(\gamma/\sigma) .$$

If $\gamma > \sigma$, then $\Pr_{Z \sim \mathcal{N}(\Delta, \sigma^2)}[Z \in [-\gamma, \gamma]] = \Theta(1)$. This means that we get the general bound:

$$\Pr_{Z \sim \mathcal{N}(\Delta, \sigma^2)}[Z \in [-\gamma, \gamma]] = \Theta(\min\{1, \gamma/\sigma\}),$$

and hence $\alpha = \Omega(\min\{1, \gamma/\sigma\})$. Plugging into (3) we get

$$\Pr[X \notin [\mu - \gamma, \mu + \gamma]] \leq 2\exp(-\Omega(k\min\{1, \gamma/\sigma\}^2)) \ .$$

This finishes the proof of the lemma. $\qquad\square$

Given Lemma 3.4 the proof of Theorem 3.3 follows the standard analysis of CountSketch. We sketch it for completeness here, and refer to (Charikar et al., 2004; Minton & Price, 2014) for details. To apply Lemma 3.4 we need to establish that for each choice of $\ell \in [d]$ and $i \in [k]$ the estimator $X_i = s_i(\ell)CS(x)_{i,h_i(\ell)}$ satisfies

$$\Pr[X_i] \in [x_\ell - \Delta, x_i + \Delta] > \beta,$$

for some constant $\beta > 0$ and for $\Delta = 2\,||\mathrm{tail}_{b/2}(x)||_2/\sqrt{b}$. Fix $\ell \in [d]$ and consider the vector x^* that is equal to x, except that $x_\ell^* = 0$. Defining $\mathrm{head}_{b/2}(x^*) = x^* - \mathrm{tail}_{b/2}(x^*)$, by linearity of CountSketch we have:

$$X_i = x_\ell + s_i(\ell)\,CS(\mathrm{tail}_{b/2}(x^*))_{i,h_i(\ell)} + s_i(\ell)\,CS(\mathrm{head}_{b/2}(x^*))_{i,h_i(\ell)} \ .$$

By a union bound, $\Pr[s_i(\ell)CS(\mathrm{head}_{b/2}(x^*))_{i,h_i(\ell)} \neq 0] \leq 1/2.$, so it suffices to show

$$\Pr[|CS(\mathrm{tail}_{b/2}(x^*))_{i,h_i(\ell)}| > \Delta] < 1/4 \ .$$

The conclusion now follows from Chebychev's inequality since

$$\mathrm{Var}[s_i(\ell)CS(\mathrm{tail}_{b/2}(x^*))_{i,h_i(\ell)}] \leq ||\mathrm{tail}_{b/2}(x^*)||_2^2/b \leq ||\mathrm{tail}_{b/2}(x)||_2/b \ .$$

Limitations. Our error analysis relies on the assumption that the sign hash functions used are fully random. This assumption may be expensive to realize in practice, though it is always possible by storing an explicit, random list of all hash values (as done in our experiments). Though CountSketch will be able to significantly compress sufficiently skewed or sparse input vectors, the size of a CountSketch can in general be larger than the size of the original vector.

3.4 Comparison to Other Private Sketches

It is instructive to compare Private CountSketch to other private sketches that have been studied in the literature, in particular Private Count-Min Sketch (Melis et al., 2016) and Count Mean Sketch (Apple Differential Privacy Team, 2017).

Private Count-Min Sketch. The Count-Min Sketch (Cormode & Muthukrishnan, 2005) is a well-known sketch that corresponds to CountSketch without the sign functions (or alternatively with constant $s_i(\ell) = 1$). Its estimator is similar to that of CountSketch except that it works by taking the *minimum* of the k independent estimates obtained from the sketch. The minimum estimator has a *one-sided* error guarantee (never underestimates x_ℓ) in terms of $||\mathrm{tail}_{b/2}(x)||_1$ for vectors x that have only nonnegative entries. Similar to count sketch its failure probability decreases exponentially with the number k of repetitions.

A private version of Count-Min Sketch was studied by Melis et al. (2016), and works by adding independent (Laplace) noise to each entry of the sketch. This of course breaks the one-sided error guarantee. Another variant, with a non-negative binomial noise distribution (for integer valued vectors), was studied by Ghazi et al. (2021). In both cases, however, the minimum estimator is biased and its variance grows with k. A third possibility would be Gaussian noise, but again the variance of the minimum estimator can be large (at least $O(k/\log k)$ for the minimum of k Gaussians with variance k).

Private Count-Mean Sketch. We use Count-Mean Sketch to refer to CountSketch, where the estimator is the *mean* rather than the median. This sketch was studied by Apple Differential Privacy Team (2017) in the *local* model, where it was only used on 1-hot vectors with a single 1. One can ask if the mean estimator is useful in other models of differential privacy, but unfortunately it lacks the robustness properties of CountSketch. In particular, it gives error bounds in terms of the norm $||x||_2$ rather than $||\mathrm{tail}_{b/2}(x)||_2$ which means that it is not robust against outliers or adversarial data.

Figure 1: *It is well-known that the median of k Gaussians with variance k is itself subgaussian, with variance independent of k. This illustrates a "best case" for Private CountSketch, in which estimators X_i (w/o noise) provide the exact answer.*

Figure 2: *Distribution of noise magnitude for Private CountSketch in the setting where estimators have zero variance. The magnitude is only slightly higher than a standard Gaussian, achieving the same level of privacy.*

Local differential privacy Zhou et al. (2022) consider differentially private encodings of t-sparse vectors with nonzero values in $[-1, 1]$. They use a CountSketch with a *single* repetition to encode a t-sparse vector, optionally apply a clipping step, and then add Laplace noise to ensure privacy. The main use case is the local differential privacy (LDP) model, where each noisy CountSketch is sent it to an aggrator that sums the estimates of n users.

Kane & Nelson (2014) have shown that the norm of a CountSketch, $||Ax||_2$, with $k = O_\gamma(\log(1/\delta))$ repetitions is within a factor $1 \pm \gamma$ from $\sqrt{k}||x||_2$ with probability at least $1 - \delta$. In particular, the CountSketch of a t-sparse vector x with nonzero values in $[-1, 1]$ has norm $||Ax||_2 < 2\sqrt{k}||x||_2 \le 2\sqrt{kt}$ with probability $1 - \delta$. Applying clipping to ensure norm at most $2\sqrt{kt}$ and scaling the Gaussian noise by $2\sqrt{kt}$ our results imply an alternative LDP encoding of t-sparse vectors in $[-1, 1]^d$ that differs from the protocol of Zhou et al. (2022) by offering smaller error (in fact matching their lower bound) at the expense of larger communication complexity.

4 Experiments

We have conducted a series of experiments to empirically investigate the properties of private CountSketch. Our main result ignores constant factors in the exponent of the bound on failure probability, but we see in experiments that these constants very reasonable. All experiments can be recreated by running a Python script available as supplementary material (runs in about 13 minutes on an M1 MacBook Pro). Density plots are smoothed using the Seaborn library's `kdeplot` function with default parameters.

Median of normals. As a warm-up we consider the setting in which a function $f(x)$ is released k times independently, $r_1, \ldots, r_k \sim \mathcal{N}(f(x), k)$, for some integer k. The magnitude of the noise is chosen such that the privacy is bounded independently of k, e.g., if $f(x)$ has sensitivity 1 then $(r_1, \ldots, r_k)$ satisfies $1/2$-zero-concentrated differentially privacy (different parameters can be achieved by scaling the magnitude of the noise). Each release has noise of expected magnitude $\Theta(\sqrt{k})$, but the median has noise that can be bounded independently of k, as illustrated in Figure 1. This gives a form of differentially private secret sharing, where i of k releases can be combined to yield an estimator with noise of magnitude $\Theta(\sqrt{k/i})$. We note that in this setting, simply taking the mean value also gives a low-variance estimator, but in contrast to medians, mean values are sensitive to outliers and are not robust to adversarially corrupted data.

The zero-variance CountSketch setting. Next, we consider the idealized setting in which Count-Sketch itself does not have any error. This corresponds to letting the table size b go to infinity, so we would hope to come close to the noise achieved by applying the Gaussian mechanism directly on

Figure 3: *Distribution of additional noise for Private CountSketch, relative to Count-Sketch, in the setting where estimators have a large variance (specifically, where the CountSketch error is uniform $\{-\Delta, l+\Delta\}$ for some $\Delta \gg \sigma$). This can be compared to making the output differentially private using a standard Gaussian, giving the same privacy guarantee. As can be seen, the CountSketch estimator reduces the noise in this case compared to standard CountSketch.*

the vector x. More generally, this is indicative of the situation in which the noise added to achieve differential privacy dominates the noise coming from randomness in CountSketch. Figure 2 shows the cumulative distribution function for the absolute value of the error obtained by Private CountSketch, for different values of k. (Of course, in this setting choosing $k = 1$ suffices to achieve a low failure probability, but a large value of k is needed in general to ensure few estimation failures.) As can be seen, the noise distributions are quite close to that the standard Gaussian mechanism operating directly on x. To achieve a desired level of privacy, the noise in both cases has to be scaled appropriately, e.g., to achieve (ε, δ)-differential privacy it suffices to multiply the noise by a factor $\sqrt{2\ln(1/\delta)}/\varepsilon$.

The high-variance CountSketch setting. Next, we illustrate what happens in another extreme setting where CountSketch always has an error in $\{-\Delta, +\Delta\}$, for some $\Delta \gg \sigma$, where CountSketch returns the median of estimators $X_i \in \{\mu - \Delta, \mu + \Delta\}$. This corresponds to a situation in which $h_i(\ell)$ collides with exactly one index $\ell_i \neq \ell$ with $x_{\ell_i} = \Delta$, such that $h_i(\ell) = h_i(\ell_i)$ for $i \in [k]$. This is indicative of the situation in which the noise added by CountSketch is significantly higher than the noise needed to obtain differential privacy. For simplicity we choose variance $\sigma^2 = k$, but the general case looks the same, the only difference being that the noise distribution is scaled by a factor determined by the privacy level. As can be seen, the additional error is mostly *negative*, that is, Private CountSketch returns estimates with *smaller* error than CountSketch itself! Of course, it is possible to find better estimators for CountSketch in this setting, for example a truncated mean, so there is no contradiction to the fact that privacy has a cost in terms of what accuracy is possible.

Sparse vectors. Next we investigate the error distribution on t-sparse vectors, where at most t entries are non-zero. It is well-known that a CountSketch with $k = O(\log d)$ repetitions each using space $b = O(t)$ is able to reconstruct t-sparse vectors without any error, with high probability. Thus we expect the error from Private CountSketch, with a sufficiently large number of repetitions, to be similar to the error obtained by applying the Gaussian mechanism to the raw vectors. Figure 4 shows the cumulative error distribution for a Private CountSketch representing a t-sparse vector in which every nonzero entry has a value of 10, using k repetitions with table size $b = t$. As can be seen, once the number of repetitions goes to 15 or more, the error distribution becomes comparable to that of the Gaussian mechanism applied directly to the sparse representation.

Figure 4: *Error distribution for Private CountSketch on sparse vectors for various number of repetitions, compared to making the output differentially private using a standard Gaussian, giving the same privacy guarantee.*

Figure 5: *Distribution of noise for Private CountSketch on the world cities dataset with table size $b = 10,000$ (left) and $b = 1000$ (right) for various number of repetitions k. The scale of the noise added for differential privacy is $\sigma = 10,000$ (left) and $\sigma = 100,000$ (right) so the sketch achieves strong group privacy. The Gaussian with standard deviation σ is included for comparison.*

Real-world example. To illustrate how Private CountSketch may be used on real-world data, we consider the noise of a sketch of population counts in about 40,000 cities[1]. We can consider this as a very sparse, high-dimensional data set indexed by the names of cities (among the set of all possible strings). In this way, the sketch does not need to contain any direct information on the set of cities whose population counts are stored, though we will be able to infer such membership from auxiliary information on population (if this number is sufficiently high).

We aim for *group privacy* for large sets of people (see (Dwork et al., 2014) for a formal definition) by setting the target noise magnitude on estimates high, from 10^4 to 10^5. Intuitively, this hides the contribution to the sketch from any not too large group of people. The table size b of the sketches is chosen to roughly balance the noise from the CountSketch itself and the Gaussian mechanism.

Figure 5 shows the figure with noise at scale 10^4 (left) and at scale 10^5 (right). As can be seen, the tails of the noise become noticably thinner as k increased (of course at the cost of a factor k in sketch size). Some of the sketches have size kb larger than the original data set (the sparsity of the vector indexed by city names) so the point of sketching is not compression per se, though one would expect to see compression for larger and more skewed data sets.

5 Conclusion

We have seen that CountSketch can be made differentially private at essentially the smallest conceivable cost: Coordinates of the sketched vector are estimated with error that is close to the maximum of the error from non-private CountSketch and the error necessary for differential privacy without sketching. Another open problem we leave is to obtain the same error bound with explicit classes of hash functions.

Since CountSketch can represent t-sparse vectors without error, for $k = O(\log d)$, this implies a new differentially private representation of such vectors that uses space $O(t \log d)$, is *dynamic* in the sense that the set of nonzero entries can be updated, and which keeps the level of noise close to the best possible in the non-sparse setting. This also implies that we can get good estimates of dot products between standard sparse vectors and vectors represented using Private CountSketch. Less clear is how to best estimate a dot product between two vectors given as CountSketches. This question is related to recent work of Stausholm (2021) on differentially private Euclidean distance estimation, though one could hope for error guarantees in terms of the norm of the tails of the two vectors.

Finally, we note that Cohen et al. (2022) recently used differential privacy techniques in connection with CountSketch in order to achieve robustness against adaptive adversaries that attempt to find elements that appear to be heavy hitters but are in fact not. It is worth investigating whether Private Countsketch has similar robustness properties.

---

[1]Retrieved 2020-01-27 from `https://simplemaps.com/data/world-cities`

References

Acharya, J., Sun, Z., and Zhang, H. Hadamard response: Estimating distributions privately, efficiently, and with little communication. In *Proceedings of International Conference on Artificial Intelligence and Statistics (AISTATS)*, pp. 1120–1129. PMLR, 2019.

Apple Differential Privacy Team. Learning with privacy at scale. *Apple Mach. Learn. J*, 1(8):1–25, 2017.

Aumüller, M., Lebeda, C. J., and Pagh, R. Differentially private sparse vectors with low error, optimal space, and fast access. In *Proceedings of Conference on Computer and Communications Security (CCS)*, pp. 1223–1236. ACM, 2021.

Bassily, R. and Smith, A. Local, private, efficient protocols for succinct histograms. In *Proceedings of ACM Symposium on Theory of Computing (STOC)*, pp. 127–135, 2015.

Bassily, R., Nissim, K., Stemmer, U., and Thakurta, A. Practical locally private heavy hitters. *Journal of Machine Learning Research*, 21(16):1–42, 2020.

Bun, M. and Steinke, T. Concentrated differential privacy: Simplifications, extensions, and lower bounds. In *Theory of Cryptography Conference (TCC)*, pp. 635–658. Springer, 2016.

Chan, T. H., Shi, E., and Song, D. Optimal lower bound for differentially private multi-party aggregation. In *Proceedings of European Symposium on Algorithms (ESA)*, pp. 277–288. Springer, 2012.

Charikar, M., Chen, K., and Farach-Colton, M. Finding frequent items in data streams. *Theoretical Computer Science*, 312(1):3–15, 2004.

Cheu, A., Smith, A., Ullman, J., Zeber, D., and Zhilyaev, M. Distributed differential privacy via shuffling. In *Proceedings of International Conference on the Theory and Applications of Cryptographic Techniques (Eurocrypt)*, pp. 375–403. Springer, 2019.

Cohen, E., Lyu, X., Nelson, J., Sarlós, T., Shechner, M., and Stemmer, U. On the robustness of countsketch to adaptive inputs. *CoRR*, abs/2202.13736, 2022. URL https://arxiv.org/abs/2202.13736. To appear in ICML 2022.

Cormode, G. and Muthukrishnan, S. An improved data stream summary: the count-min sketch and its applications. *Journal of Algorithms*, 55(1):58–75, 2005.

Dwork, C., McSherry, F., Nissim, K., and Smith, A. Calibrating noise to sensitivity in private data analysis. In *Theory of cryptography conference (TCC)*, pp. 265–284. Springer, 2006.

Dwork, C., Roth, A., et al. The algorithmic foundations of differential privacy. *Found. Trends Theor. Comput. Sci.*, 9(3-4):211–407, 2014.

Dwork, C., McSherry, F., Nissim, K., and Smith, A. Calibrating noise to sensitivity in private data analysis. *Journal of Privacy and Confidentiality*, 7(3):17–51, 2016.

Erlingsson, Ú., Feldman, V., Mironov, I., Raghunathan, A., Talwar, K., and Thakurta, A. Amplification by shuffling: From local to central differential privacy via anonymity. In *Proceedings of Symposium on Discrete Algorithms (SODA)*, pp. 2468–2479. SIAM, 2019.

Ghazi, B., Golowich, N., Kumar, R., Pagh, R., and Velingker, A. On the power of multiple anonymous messages: Frequency estimation and selection in the shuffle model of differential privacy. In *Proceedings of International Conference on the Theory and Applications of Cryptographic Techniques (Eurocrypt)*, pp. 463–488. Springer, 2021.

Huang, Z., Qiu, Y., Yi, K., and Cormode, G. Frequency estimation under multiparty differential privacy: One-shot and streaming. *CoRR*, abs/2104.01808, 2021.

Kairouz, P., McMahan, H. B., Avent, B., Bellet, A., Bennis, M., Bhagoji, A. N., Bonawitz, K. A., Charles, Z., Cormode, G., Cummings, R., D'Oliveira, R. G. L., Eichner, H., Rouayheb, S. E., Evans, D., Gardner, J., Garrett, Z., Gascón, A., Ghazi, B., Gibbons, P. B., Gruteser, M., Harchaoui, Z., He, C., He, L., Huo, Z., Hutchinson, B., Hsu, J., Jaggi, M., Javidi, T., Joshi, G., Khodak, M., Konečný, J., Korolova, A., Koushanfar, F., Koyejo, S., Lepoint, T., Liu, Y., Mittal, P., Mohri, M., Nock, R., Özgür, A., Pagh, R., Qi, H., Ramage, D., Raskar, R., Raykova, M., Song, D., Song, W., Stich, S. U., Sun, Z., Suresh, A. T., Tramèr, F., Vepakomma, P., Wang, J., Xiong, L., Xu, Z., Yang, Q., Yu, F. X., Yu, H., and Zhao, S. Advances and open problems in federated learning. *Found. Trends Mach. Learn.*, 14(1-2):1–210, 2021.

Kane, D. M. and Nelson, J. Sparser Johnson-Lindenstrauss transforms. *Journal of the ACM*, 61(1), January 2014. ISSN 0004-5411.

Larsen, K. G., Pagh, R., and Tětek, J. Countsketches, feature hashing and the median of three. In *Proceedings of International Conference on Machine Learning (ICML)*, volume 139 of *Proceedings of Machine Learning Research*, pp. 6011–6020. PMLR, 2021.

Melis, L., Danezis, G., and Cristofaro, E. D. Efficient private statistics with succinct sketches. In *Annual Network and Distributed System Security Symposium (NDSS)*. The Internet Society, 2016.

Minton, G. T. and Price, E. Improved concentration bounds for count-sketch. In *Proceedings of Symposium on Discrete Algorithms (SODA)*, pp. 669–686, 2014.

Mir, D., Muthukrishnan, S., Nikolov, A., and Wright, R. N. Pan-private algorithms via statistics on sketches. In *Proceedings of Symposium on Principles of database systems (PODS)*, pp. 37–48, 2011.

Mironov, I. Rényi differential privacy. In *Proceedings of Computer Security Foundations Symposium (CSF)*, pp. 263–275. IEEE, 2017.

Stausholm, N. M. Improved differentially private euclidean distance approximation. In *Proceedings of Symposium on Principles of Database Systems (PODS)*, pp. 42–56, 2021.

Weinberger, K., Dasgupta, A., Langford, J., Smola, A., and Attenberg, J. Feature hashing for large scale multitask learning. In *Proceedings of International Conference on Machine Learning (ICML)*, pp. 1113–1120, 2009.

Zhou, M., Wang, T., Chan, H., Fanti, G., and Shi, E. Locally differentially private sparse vector aggregation. In *Symposium on Security and Privacy (SP)*. IEEE, 2022. Preprint in CoRR, abs/2112.03449.