Global Convergence of Online Optimization for Nonlinear Model Predictive Control

Abstract

We study a real-time iteration (RTI) scheme for solving online optimization problem appeared in nonlinear optimal control. The proposed RTI scheme modifies the existing RTI-based model predictive control (MPC) algorithm, by selecting the stepsize of each Newton step at each sampling time using a differentiable exact augmented Lagrangian. The scheme can adaptively select the penalty parameters of the augmented Lagrangian on the fly, which are shown to be stabilized after certain time periods. We prove that, by involving stepsize selection instead of always using a full Newton step (like most of the existing RTIs do), the scheme converges globally: for *any* initial point, the KKT residuals of the subproblems converge to zero. A key step is to show that the augmented Lagrangian keeps decreasing as horizon moves forward. We demonstrate the global convergence behavior of the proposed RTI scheme in a numerical experiment.

1 Introduction

We consider the following time-varying nonlinear optimal control problem

$$\mathcal{P}(\bar{\boldsymbol{x}}_0): \min_{\boldsymbol{x},\boldsymbol{u}} \ \sum_{k=0}^{N-1} g_k(\boldsymbol{x}_k, \boldsymbol{u}_k) + g_N(\boldsymbol{x}_N),$$
$$\text{s.t.} \ \ \boldsymbol{x}_{k+1} = f_k(\boldsymbol{x}_k, \boldsymbol{u}_k), \ \ k \in [N-1], \tag{1}$$
$$\boldsymbol{x}_0 = \bar{\boldsymbol{x}}_0,$$

where $\boldsymbol{x}_k \in \mathbb{R}^{n_x}$ are the state variables, $\boldsymbol{u}_k \in \mathbb{R}^{n_u}$ are the control variables, $g_k : \mathbb{R}^{n_x} \times \mathbb{R}^{n_u} \to \mathbb{R}_+$ ($g_N : \mathbb{R}^{n_x} \to \mathbb{R}_+$) are the nonnegative cost functions, $f_k : \mathbb{R}^{n_x} \times \mathbb{R}^{n_u} \to \mathbb{R}^{n_x}$ are the dynamical constraint functions, $\bar{\boldsymbol{x}}_0$ is the given initial state, and N is the horizon length. We suppose that g_k, f_k are twice continuously differentiable and, without loss of generality, that the origin is a steady state, i.e. $f_k(\boldsymbol{0}, \boldsymbol{0}) = \boldsymbol{0}$, and is also a stationary point with zero loss, i.e. $g_k(\boldsymbol{0}, \boldsymbol{0}) = 0$ and $\nabla g_k(\boldsymbol{0}, \boldsymbol{0}) = \boldsymbol{0}$. The well-known linear quadratic regulator (LQR) satisfies this setup and the same setup is commonly used in the literature [10]. Problem (1) is also called dynamic program in control community, which has a close connection to reinforcement learning (see [8]). The main difference is that the dynamic f_k in our paper is known, which is the case in many industrial applications and model-based RL study.

In modern applications such as energy and autonomous control, N tends to be extremely large or even infinity, which stimulates the interest of solving (1) in *real time*. Let $f_k(\boldsymbol{x}_k, \boldsymbol{u}_k) = f_k(\boldsymbol{x}_k, \boldsymbol{u}_k; \boldsymbol{d}_k)$ where $\boldsymbol{d}_k$ is data at stage k, then a more realistic setting is to collect $\boldsymbol{d}_k$ as a data stream. That is, instead of knowing f_0 all the way to f_{N-1} and solving (1) offline, we only know f_k sequentially and have to solve (1) online. Model predictive control (MPC), also known as receding horizon control, is an important feedback control technique that is used in online optimization of control problems. Given the current system state, MPC looks ahead multiple stages on the prediction horizon, solves

the subproblem on the prediction horizon to the *optimality*, and provides the first optimal control action to the system as the feedback. Then the system evolves to a new state based on the control action and the procedure is repeated. However, the classical nonlinear MPC is being regarded as a theoretical concept rather than a practical strategy. It is not as widely used as linear MPC, and is mostly investigated in slow dynamics. This is due to the intensive computations of solving the control subproblems when we have nonlinear models. Fortunately, the design of real-time iteration (RTI) and its predecessors [29, 40] have enabled RTI-based nonlinear MPC to be applied on fast dynamics and achieve good performance [56, 7, 17, 46, 18, 27, 21, 25, 20, 23, 19, 22, 47, 1].

Instead of using optimal feedback control, the RTI schemes compute a cheap approximation of the control and provide back to the system as fast as possible. The existing RTI schemes perform a single, full Newton step for each subproblem, and the output iterate of the previous subproblem is used to warmly initialize the current subproblem [10, 49, 50]. Thus, the RTI schemes significantly reduce the computations of each subproblem, which makes them succeed in modern industrial applications. The RTI schemes exploit the fact that two successive subproblems are closely related though different, so that the iteration can achieve the convergence "on the fly" (i.e. the error goes to zero as horizon moves forward). However, the RTI-based MPC is challenging to analyze. The main difficulty lies in the fact that the prediction horizon is shifted each time. Each subproblem is appended by a new stage that has never been scanned before and may introduce perturbation into the system. Different RTI-based MPC schemes have been studied [11, 15, 26], with an improved local analysis established in [35] recently.

Our paper complements the literature on RTI-based MPC by establishing its global convergence. We emphasize that by global convergence we mean *the convergence for any initialization*, instead of the convergence to global optimality. Our notion follows nonlinear optimization literature [37]. Instead of using a full Newton step, we design an adaptive scheme to involve the stepsize selection procedure. In fact, the stepsize selection has been suggested as a way to improve the global behavior of RTI in shrinking (not moving) horizons in an old paper [28]. The authors implemented a ℓ_1 penalized merit function[1] with a watchdog line search. However, the global convergence theory remains open. Different from the suggestion of [28], we use a *differentiable exact augmented Lagrangian* as the merit function. This function has two advantages over the ℓ_1 penalized merit function: (i) it depends on both primal and dual variables, so that dual variables are updated using the same stepsize as the primal variables (ℓ_1 merit function only updates the primal variables); (ii) a simple backtracking line search can effectively overcome Maratos effect [32] and accept the unit stepsize locally (ℓ_1 merit function requires a more time-consuming line search method such as watchdog or second-order correction). We conduct experiments to show clear advantages of the augmented Lagrangian, especially for time-varying problems. Moreover, our algorithm adaptively selects the penalty parameters of the augmented Lagrangian on the fly. When the unit stepsize is accepted, the algorithm simply boils down to the standard RTI-based MPC, and the existing local theories [10, 35] apply seamlessly.

Related work and contribution: Our work is closely related to a growing literature on online optimization via RTI. The theories of RTI have been investigated over the past decade. [12] and [10] established the local convergence of RTI in shrinking horizons and moving horizons, respectively. When we have different models, [4, 50, 52, 38, 39] all showed similar results. A different view of RTI-based MPC is via the parametric optimization, where subproblems are parameterized by a continuous time index and a single Newton step is performed at each time instant. Similar stability results in this setup are shown in [13, 53, 16]. Recently, [35] studied a lag-L RTI-based MPC (i.e. one shifts L stages each time), and proved that RTI iterates on each stage converge linearly with a rate decaying exponentially in the prediction horizon length. Their analyses rely on the sensitivity analysis of (1) in [34, 36]. An important consequence of convergence of online iteration is the dynamic regret analysis [55, 30, 9, 51]. For example, the convergence rate in [35] and the regret order in [30] are both exponentially in prediction horizon length. This is due to the widely-used Lipschitz continuity assumption on the objective.

However, all above theories are local results. The algorithms always take a full (Newton) step for each subproblem, without involving any stepsize selection procedure. Thus, the analyses require to have an initial point that is sufficiently close to the local solution, or require that the first Newton step is sufficiently small. Obviously, for Problem (1), when $\|\bar{x}_0\|$ is small enough, the origin is a

---

[1] The merit function refers to the function that is used in the line search.

good initial point and RTI iterates stably track the origin. However, if $\|\bar{x}_0\|$ is large or we may want
to track a nontrivial MPC policy, the origin is not a reasonable choice for the initial point. Based
on these considerations, the global convergence of RTI addressed in this paper complements the
aforementioned rich local analyses. Again, by global convergence we mean that the KKT residuals
of subproblems go to zero as horizon moves forward for *any* initialization.

The challenge of our analysis is that: *the problem varies with time instants and only a single Newton*
step is performed at each time instant. A key, technical step is to show that the *exact* augmented
Lagrangian merit function keeps decreasing as horizons shift. To our knowledge, this is the first paper
studying the global behavior of online iteration under RTI setting, via a tool of the exact augmented
Lagrangian. Another contribution to nonlinear MPC is that we consider time-varying dynamics,
while most of the literature considered time-invariant dynamics (e.g. [10, 24, 48]). The subproblems
of time-invariant dynamics only differ in the initial state, which results in a much simpler analysis.
We notice that [35] allowed time-varying dynamics, but required to use a larger lag when shifting the
horizon. We allow lag one instead.

Notations: For two vectors $\boldsymbol{a}, \boldsymbol{b}$, $(\boldsymbol{a}; \boldsymbol{b})$ denotes a long column vector that stacks $\boldsymbol{a}$ and $\boldsymbol{b}$ together.
For two scalars a, b, $a \vee b = \max(a, b)$. Without specification, $\|\cdot\|$ denotes the ℓ_2 norm for vectors
and operator norm for matrices. We also reserve the following notations. $\mathbf{0}$ denotes zero vector or
matrix, and I denotes the identity matrix. Their dimensions are clear from the context. M denotes the
prediction horizon length, t indexes the sampling time, and $\boldsymbol{z}_k = (\boldsymbol{x}_k; \boldsymbol{u}_k) \in \mathbb{R}^{n_z}$ with $n_z = n_x + n_u$
denotes the state-control pair at stage k.

2 Preliminaries

We introduce MPC subproblems formulation, the Newton step, and the merit function in this section.
At time t, the prediction horizon shifts to $[t, M_t]$ with $M_t = t + M$ denoting the last stage, and the
corresponding subproblem $\mathcal{P}^t(\bar{x}_t)$ is given by

$$\mathcal{P}^t(\bar{x}_t): \quad \min_{\substack{\boldsymbol{x}_{t:M_t} \\ \boldsymbol{u}_{t:M_t-1}}} \sum_{k=t}^{M_t-1} g_k(\boldsymbol{x}_k, \boldsymbol{u}_k) + g_{M_t}(\boldsymbol{x}_{M_t}, \mathbf{0}) + \frac{\mu}{2}\|\boldsymbol{x}_{M_t}\|^2,$$
$$\text{s.t.} \quad \boldsymbol{x}_{k+1} = f_k(\boldsymbol{x}_k, \boldsymbol{u}_k), \quad k \in [t, M_t - 1], \tag{2}$$
$$\boldsymbol{x}_t = \bar{\boldsymbol{x}}_t.$$

Here, μ is a quadratic penalty parameter independent from t; $\bar{x}_t$ is the current system state, which
is given and determined by the control feedback provided to the system before t. The formulation
(2) is used in [35] for local analysis, while a variety of subproblem formulations are available as
well [10, 26]. We prefer (2) since we will see later that μ connects to the penalty parameter of the
augmented Lagrangian.

Given subproblem (2), RTI schemes perform a single Newton step for $\mathcal{P}^t(\bar{x}_t)$ and move to the
next time instant. To ease notations, we let $\tilde{\boldsymbol{x}}_t = \boldsymbol{x}_{t:M_t}$ and $\tilde{\boldsymbol{u}}_t = \boldsymbol{u}_{t:M_t-1}$ denote the state and
control variables of the t-th subproblem, respectively. We also let $\tilde{\boldsymbol{z}}_t = \boldsymbol{z}_{t:M_t} = (\boldsymbol{z}_t; \ldots; \boldsymbol{z}_{M_t})$
denote the whole ordered state-control variables, with slightly abusing the notation of $\boldsymbol{z}_{M_t}$ to let
$\boldsymbol{z}_{M_t} = \boldsymbol{x}_{M_t}$. We sometimes also express $\tilde{\boldsymbol{z}}_t = (\tilde{\boldsymbol{x}}_t, \tilde{\boldsymbol{u}}_t)$ when we specify each component of $\tilde{\boldsymbol{z}}_t$.
Then, the Lagrangian function of (2) is

$$\mathcal{L}^t(\tilde{\boldsymbol{z}}_t, \tilde{\boldsymbol{\lambda}}_t; \bar{\boldsymbol{x}}_t) = \sum_{k=t}^{M_t-1} g_k(\boldsymbol{x}_k, \boldsymbol{u}_k) + g_{M_t}(\boldsymbol{x}_{M_t}, \mathbf{0}) + \frac{\mu}{2}\|\boldsymbol{x}_{M_t}\|^2 + \sum_{k=t}^{M_t-1} \boldsymbol{\lambda}_k^T(\boldsymbol{x}_{k+1} - f_k(\boldsymbol{x}_k, \boldsymbol{u}_k))$$
$$+ \boldsymbol{\lambda}_{t-1}^T(\boldsymbol{x}_t - \bar{\boldsymbol{x}}_t),$$

where $\tilde{\boldsymbol{\lambda}}_t = \boldsymbol{\lambda}_{t-1:M_t-1}$ is the dual vector. Here, $\boldsymbol{\lambda}_k \in \mathbb{R}^{n_x}$ is associated to the k-th constraint of (2)
for $k \in [t, M_t - 1]$, and $\boldsymbol{\lambda}_{t-1} \in \mathbb{R}^{n_x}$ is associated to the initial state constraint.

Given the input iterate $(\tilde{\boldsymbol{z}}_t^0, \tilde{\boldsymbol{\lambda}}_t^0)$, the Newton direction $(\Delta\tilde{\boldsymbol{z}}_t, \Delta\tilde{\boldsymbol{\lambda}}_t)$ is solved by the KKT system

$$\begin{pmatrix} B^t & (G^t)^T \\ G^t & \mathbf{0} \end{pmatrix} \begin{pmatrix} \Delta\tilde{\boldsymbol{z}}_t \\ \Delta\tilde{\boldsymbol{\lambda}}_t \end{pmatrix} = -\begin{pmatrix} \nabla_{\tilde{\boldsymbol{z}}_t}\mathcal{L}^t \\ \nabla_{\tilde{\boldsymbol{\lambda}}_t}\mathcal{L}^t \end{pmatrix}, \tag{3}$$

124 where B^t is an approximation of the Hessian $H^t = \nabla^2_{\tilde{z}_t}\mathcal{L}^t$; $G^t = \nabla_{\tilde{\lambda}_t\tilde{z}_t}\mathcal{L}^t$ is the Jacobian matrix;

125 and all matrices in (3) are evaluated at $(\tilde{z}^0_t, \tilde{\lambda}^0_t)$. The left hand side matrix is called the KKT matrix.

126 In what follows, H^t, B^t, G^t are always evaluated at the input iterate $(\tilde{z}^0_t, \tilde{\lambda}^0_t)$ if no evaluation point is

127 specified. Taking a closer look at (3) (cf. Appendix A), we note that the KKT matrix and $\nabla_{\tilde{z}_t}\mathcal{L}^t$ are

128 *independent* from the given initial state $\bar{x}_t$. This is a crucial observation. In reality, the realization of

129 the system state may lag behind the sampling time, since the system has to apply the feedback control

130 to evolve. Thus, $\bar{x}_t$ may not be known as soon as the input iterates $(\tilde{z}^0_t, \tilde{\lambda}^0_t)$. However, a promising

131 property of RTI is that most of computations of (3) can be prepared without knowing $\bar{x}_t$.

132 Given the Newton direction $(\Delta\tilde{z}_t, \Delta\tilde{\lambda}_t)$ from (3), we update the iterates by involving a stepsize α_t

$$\begin{pmatrix} \tilde{z}^1_t \\ \tilde{\lambda}^1_t \end{pmatrix} = \begin{pmatrix} \tilde{z}^0_t \\ \tilde{\lambda}^0_t \end{pmatrix} + \alpha_t \begin{pmatrix} \Delta\tilde{z}_t \\ \Delta\tilde{\lambda}_t \end{pmatrix}. \tag{4}$$

133 In our paper, α_t is selected by forcing *Armijo condition* hold on a differentiable exact augmented

134 Lagrangian, defined as

$$\mathcal{L}^t_\eta(\tilde{z}_t, \tilde{\lambda}_t; \bar{x}_t) = \mathcal{L}^t(\tilde{z}_t, \tilde{\lambda}_t; \bar{x}_t) + \frac{\eta_1}{2}\left\|\nabla_{\tilde{\lambda}_t}\mathcal{L}^t(\tilde{z}_t, \tilde{\lambda}_t; \bar{x}_t)\right\|^2 + \frac{\eta_2}{2}\left\|\nabla_{\tilde{z}_t}\mathcal{L}^t(\tilde{z}_t, \tilde{\lambda}_t; \bar{x}_t)\right\|^2. \tag{5}$$

135 Here $\eta = (\eta_1, \eta_2)$ are the penalty parameters of the quadratic penalties. It is called *exact* augmented

136 Lagrangian since one can show that, for sufficiently large η_1 and sufficiently small η_2, a strict local

137 minimizer of $\mathcal{L}^t_\eta(\cdot)$ is also a strict local minimizer of Problem (2) and vice versa. When $\eta_2 = 0$, $\mathcal{L}^t_\eta(\cdot)$

138 is the standard augmented Lagrangian, while it does not enjoy exactness property anymore, and may

139 cause issues when it is used as the merit function. For simplicity, we sometimes suppress "exact" and

140 call $\mathcal{L}^t_\eta(\cdot)$ the augmented Lagrangian. Based on (5), α_t is selected by making the following Armijo

141 condition,

$$\mathcal{L}^t_\eta(\tilde{z}^1_t, \tilde{\lambda}^1_t; \bar{x}_t) \leq \mathcal{L}^t_\eta(\tilde{z}^0_t, \tilde{\lambda}^0_t; \bar{x}_t) + \alpha_t\beta\begin{pmatrix}\nabla_{\tilde{z}_t}\mathcal{L}^t_\eta(\tilde{z}^0_t, \tilde{\lambda}^0_t; \bar{x}_t) \\ \nabla_{\tilde{\lambda}_t}\mathcal{L}^t_\eta(\tilde{z}^0_t, \tilde{\lambda}^0_t; \bar{x}_t)\end{pmatrix}^T\begin{pmatrix}\Delta\tilde{z}_t \\ \Delta\tilde{\lambda}_t\end{pmatrix}, \tag{6}$$

142 hold for a prespecified parameter $\beta \in (0, 1)$. Note that, by mean value theory, α_t can always be

143 found by backtracking line search provided the inner product in (6) is negative.

3 An Adaptive RTI-based MPC Scheme

145 We now set the stage to propose our algorithm. The algorithm inherits the flavor of RTI schemes:

146 it performs a single Newton step for each subproblem. Differently, it involves a stepsize selection

147 procedure based on $\mathcal{L}^t_\eta(\cdot)$ instead of using a full step (i.e. $\alpha_t = 1$).

148 The algorithm adaptively selects the parameter η on the fly (i.e. it automatically selects suitable η

149 for each subproblem). However, since μ is required in the problem formulation, the adaptivity on μ

150 may require to solve the KKT system multiple times for each subproblem. Thus, the gain from the

151 adaptivity on μ is limited. We hence prefer to tune μ manually in practice. Our experiments show

152 that our algorithm is robust in μ (see Figure 1).

153 Let us now illustrate how we transit from the triple $(\tilde{z}^0_t, \tilde{\lambda}^0_t; \bar{x}_t)$ to $(\tilde{z}^0_{t+1}, \tilde{\lambda}^0_{t+1}; \bar{x}_{t+1})$. To further

154 ease notations, we let $\mathcal{L}^{t,1}_\eta, \mathcal{L}^{t,0}_\eta, \mathcal{L}^{t,1}, \mathcal{L}^{t,0}$ denote the function values of $\mathcal{L}^t_\eta(\cdot)$ and $\mathcal{L}^t(\cdot)$ at the output

155 iterate $(\tilde{z}^1_t, \tilde{\lambda}^1_t)$ and the input iterate $(\tilde{z}^0_t, \tilde{\lambda}^0_t)$, respectively. In addition, when we specify the iterate

156 on each stage, we let $\tilde{x}^{\mathrm{Id}}_t = x^{\mathrm{Id}}_{t:M_{t,t}}$ for Id = 0 or 1 (similar for $\tilde{z}^{\mathrm{Id}}_t, \tilde{\lambda}^{\mathrm{Id}}_t, \Delta\tilde{z}_t$, and $\Delta\tilde{\lambda}_t$). For example,

157 $x^1_{t+1,t}$ denotes the output iterate of the t-th subproblem at the stage $t+1$.

158 Given the input iterate $(\tilde{z}^0_t, \tilde{\lambda}^0_t)$, we perform four steps:

159 **(1)** We compute B^t, G^t, and $\nabla_{\tilde{z}_t}\mathcal{L}^{t,0}$. After we observe $\bar{x}_t$, we compute $\nabla_{\tilde{\lambda}_t}\mathcal{L}^{t,0}$. Then, we compute

160 the Newton direction $(\Delta\tilde{z}_t, \Delta\tilde{\lambda}_t)$ by solving the KKT system (3).

161 **(2)** We select $\eta^t = (\eta^t_1, \eta^t_2)$ such that

$$\begin{pmatrix}\nabla_{\tilde{z}_t}\mathcal{L}^{t,0}_{\eta^t} \\ \nabla_{\tilde{\lambda}_t}\mathcal{L}^{t,0}_{\eta^t}\end{pmatrix}^T\begin{pmatrix}\Delta\tilde{z}_t \\ \Delta\tilde{\lambda}_t\end{pmatrix} \leq -\frac{\eta^t_2}{4}\left\|\begin{pmatrix}\nabla_{\tilde{z}_t}\mathcal{L}^{t,0} \\ \nabla_{\tilde{\lambda}_t}\mathcal{L}^{t,0}\end{pmatrix}\right\|^2. \tag{7}$$

Algorithm 1 An Adaptive RTI-based MPC Scheme

1: **Input:** Initial iterate $(\tilde{z}_0^0, \tilde{\lambda}_0^0)$, initial state $\bar{x}_0$, and parameters $\mu > 0$, $\rho > 1$, $\eta^0 = (\eta_1^0, \eta_2^0) = (\mu^2, 1)$, and $\beta \in (0, 1)$;

2: **for** $t = 0, 1, 2, \ldots$ **do**

3:      Compute B^t, G^t, $\nabla_{\tilde{z}_t} \mathcal{L}^{t,0}$, $\nabla_{\tilde{\lambda}_t} \mathcal{L}^{t,0}$, and solve the KKT system to obtain $(\Delta \tilde{z}_t, \Delta \tilde{\lambda}_t)$;

4:      **while** $\begin{pmatrix} \nabla_{\tilde{z}_t} \mathcal{L}_{\eta^t}^{t,0} \\ \nabla_{\tilde{\lambda}_t} \mathcal{L}_{\eta^t}^{t,0} \end{pmatrix}^T \begin{pmatrix} \Delta \tilde{z}_t \\ \Delta \tilde{\lambda}_t \end{pmatrix} > -\frac{\eta_2^t}{4} \left\| \begin{pmatrix} \nabla_{\tilde{z}_t} \mathcal{L}^{t,0} \\ \nabla_{\tilde{\lambda}_t} \mathcal{L}^{t,0} \end{pmatrix} \right\|^2$ **do**

5:          Let $\eta_1^t = \rho^2 \eta_1^t$, $\eta_2^t = \eta_2^t / \rho$;

6:      **end while**

7:      Select α_t by backtracking line search to make (6) hold, and update iterates by (4);

8:      Define $(\tilde{z}_{t+1}^0, \tilde{\lambda}_{t+1}^0)$ and $\bar{x}_{t+1}$ according to (8), and let $\eta^{t+1} = \eta^t$;

9: **end for**

As shown in Algorithm 1, we can use a While loop to increase η_1^t and decrease η_2^t until (7) is satisfied. **(3)** Using η^t from the last step, we select α_t by backtracking line search to make the Armijo condition (6) hold. We then obtain the output iterate $(\tilde{z}_t^1, \tilde{\lambda}_t^1)$ by (4). **(4)** We transit to the next horizon by letting

$$
\begin{aligned}
\tilde{x}_{t+1}^0 &= x_{t+1:M_{t+1},t+1}^0 := (x_{t+1,t}^1; x_{t+2,t}^1; \ldots; x_{M_t,t}^1; \mathbf{0}), \\
\tilde{u}_{t+1}^0 &= u_{t+1:M_{t+1}-1,t+1}^0 := (u_{t+1,t}^1; u_{t+2,t}^1; \ldots; u_{M_t-1,t}^1; \mathbf{0}), \\
\tilde{\lambda}_{t+1}^0 &= \lambda_{t:M_{t+1}-1,t+1}^0 := (\lambda_{t,t}^1; \lambda_{t+1,t}^1; \ldots; \lambda_{M_t-1,t}^1; \mathbf{0}), \\
\bar{x}_{t+1} &:= f_t(x_{t,t}^1, u_{t,t}^1).
\end{aligned}
\tag{8}
$$

The above four steps are displayed in Algorithm 1. If we remove Step (2) and use $\alpha_t = 1$ in Step (3), it reduces to the standard RTI scheme [10, 49, 50, 35]. However, as shown later, the difference that we select α_t based on the augmented Lagrangian $\mathcal{L}_{\eta^t}^t(\cdot)$ enables Algorithm 1 to converge globally.

Remark 3.1. We discuss the overhead of the algorithm. For each subproblem, the computational complexity is dominated by solving the KKT system. The KKT matrix is a square matrix with dimensions $2(M+1)n_x + Mn_u$. Directly inverting the matrix results in $O((M(n_x + n_u))^3)$ flops. Fortunately, we can exploit the sparse structure of the KKT matrix and apply sparse LDL^T factorization as did in Section C of [49], which results in $O(M(n_x + n_u)^3)$ flops instead. So the computations are linear in terms of the prediction horizon length M.

4 Global Convergence Analysis

We conduct the global convergence analysis for Algorithm 1. We show that, for *any* initial iterate $(\tilde{z}_0^0, \tilde{\lambda}_0^0)$, the KKT residual of the t-th subproblem, $\|\nabla \mathcal{L}^{t,0}\|$, converges to zero as t increases. The significance of the result is that we only perform a single Newton step for each time-varying subproblem, and our result complements the local results of RTI.

4.1 Assumptions

We require the following assumptions.

Assumption 4.1 (Compactness). We assume all iterates lie in a compact set that contains the origin. In particular, we assume there exist compact sets $\mathbf{0} \in \mathcal{Z} \subseteq \mathbb{R}^{n_x + n_u}$ and $\mathbf{0} \in \Lambda \subseteq \mathbb{R}^{n_x}$, such that $(z_{k,t}^0, \lambda_{k,t}^0) \in \mathcal{Z} \times \Lambda$ for any $t \geq 0$ and any stage k of the t-th subproblem.

Assumption 4.2 (Boundedness condition). We assume there exist absolute constants $\Upsilon, \delta, \gamma_{RH} > 0$ such that (i) For any $t \geq 0$, B^t satisfies $z^T B^t z \geq \gamma_{RH} \|z\|^2$, $\forall z \in \{z : G^t z = \mathbf{0}, z \neq \mathbf{0}\}$, and $\|B^t - H^t\| \leq \delta$. (ii) For any $k \geq 0$ and $z_k \in \mathcal{Z}$, we have

$$
\|\nabla_{x_k} f_k(z_k)\| \vee \|\nabla_{u_k} f_k(z_k)\| \vee \|\nabla_{z_k}^2 g_k(z_k)\| \vee \{\|\nabla_{z_k}^2 f_{k,l}(z_k)\|\}_{l=1}^{n_x} \leq \Upsilon, \tag{9}
$$

$$
\{\|\nabla_{z_k}^2 [\nabla_{z_k} g_k(z_k)]_i\|, \|\nabla_{z_k}^2 [\nabla_{z_k} f_{k,l}(z_k)]_i\|\}_{i=1,l=1}^{n_z,n_x} \leq \Upsilon. \tag{10}
$$

(iii) For any $t \geq 0$, $G^t (G^t)^T \succeq I / \Upsilon^2$.

Assumption 4.3. We assume there exist absolute constants $c, C > 0$ such that for any $t \geq 0$ (i) $\|\Delta \tilde{\boldsymbol{\lambda}}_{M_t-1,t}\| \leq c\|(\Delta \tilde{\boldsymbol{z}}_t; \Delta \tilde{\boldsymbol{\lambda}}_t)\|$ if $\boldsymbol{x}_{M_t,t}^1 \neq \boldsymbol{0}$. (ii) $\|\boldsymbol{\lambda}_{t-1,t}^1\| \leq C\|\boldsymbol{x}_{t,t}^1 - \bar{\boldsymbol{x}}_t\|$ if $\boldsymbol{x}_{t,t}^1 \neq \bar{\boldsymbol{x}}_t$.

A 4.1 and 4.2 are standard in the literature on Newton analysis [41, 42, 6, 44, 45, 37, 2]. We note that Jacobian G^t always has full row rank (see (13) in Appendix A), so the linear independence constraint qualification (LICQ) holds. Together with LICQ, A 4.2(i) implies the KKT matrix is nonsingular [37, Lemma 16.1]. In fact, we can simply let $B^t = \mu I$, which satisfies all conditions trivially; is sufficient for our global analysis; and is indeed used in our experiments. More generally, B^t can approximate the Hessian H^t using any methods in [37]. Different from existing analyses which only require the bounded Hessian, (10) requires one more derivative—the third derivative—to be bounded. This is standard when using augmented Lagrangian $\mathcal{L}_\eta^t(\cdot)$ in the algorithm [54, 2], because the Hessian of $\mathcal{L}_\eta^t(\cdot)$ requires the third derivatives of g_k, f_k. We mention that the third derivatives are only used in the analysis, and do not have to be computed in the implementation. (9) is directly implied by the compactness in A 4.1. A 4.2(iii) is also reasonable to hold since G^t has full row rank. For time-invariant problems where $g_k = g, f_k = f$, A 4.2(ii) and (iii) hold trivially.

A 4.3 is standard in the literature on MPC analysis [10]. At the first glance, it seems to be a restrictive assumption. Fortunately, it is guaranteed to hold when μ is sufficiently large (the threshold depends on problem parameters), and is easily checkable during the iteration. In particular, A 4.3(i) assumes that the last dual step $\Delta \tilde{\boldsymbol{\lambda}}_{M_t-1,t}$ is bounded by the full Newton step $(\Delta \tilde{\boldsymbol{z}}_t, \Delta \tilde{\boldsymbol{\lambda}}_t)$. It holds trivially for $c = 1$, however, we hope c is small. One can expect this condition to be satisfied for large enough μ, since $\Delta \tilde{\boldsymbol{\lambda}}_{M_t-1,t}$ measures the disturbance of $\boldsymbol{x}_{M_t,t}^1$ away from $\boldsymbol{x}_{M_t,t}^0 = \boldsymbol{0}$. When μ is large, we know from the quadratic penalty in (2) that $\boldsymbol{x}_{M_t,t}^1 \approx \boldsymbol{0}$. Hence, $\Delta \tilde{\boldsymbol{\lambda}}_{M_t-1,t}$ becomes arbitrarily small. See more discussions in [10, Assumption 3] for local analysis of MPC. A 4.3(ii) allows any constant C as long as $C \leq \mu$, so it holds as well for large enough μ. In addition, A 4.3(ii) is not required if $\alpha_t = 1$ is selected, which is always true when $(\tilde{\boldsymbol{z}}_t^0, \tilde{\boldsymbol{\lambda}}_t^0)$ is close to a stationary point of the subproblem[2]. This is because that, if $\alpha_t = 1$, then $\boldsymbol{x}_{t,t}^1 = \bar{\boldsymbol{x}}_t$ for any input iterate $\boldsymbol{x}_{t,t}^0$.

4.2 Global convergence

We first show that Algorithm 1 is well-posed, that is each iteration can be performed successfully. The compute of the Newton direction in Line 3 is guaranteed by the nonsingularity of the KKT matrix, implied by A 4.2 as discussed before. The backtracking line search in Line 7 is guaranteed by the mean value theorem. It hence suffices to show that the While loop in Line 4 terminates in finite time.

Theorem 4.4. Consider Algorithm 1 under Assumptions 4.1 and 4.2. Let us define thresholds $\tau_1, \tau_2, \tau_3 > 0$ by

$$\tau_1 = \frac{25\mu^2 \Upsilon^2}{\gamma_{RH}}, \quad \tau_2 = \frac{\gamma_{RH}}{2\delta^2}, \quad \tau_3 = \frac{32\mu^2 \Upsilon^2}{\gamma_{RH}^2}.$$

For any $t \geq 0$, if $\eta_1 \geq \tau_1, \eta_2 \leq \tau_2, \eta_1\eta_2 \geq \tau_3$, then

$$\begin{pmatrix} \nabla_{\tilde{\boldsymbol{z}}_t} \mathcal{L}_\eta^{t,0} \\ \nabla_{\tilde{\boldsymbol{\lambda}}_t} \mathcal{L}_\eta^{t,0} \end{pmatrix}^T \begin{pmatrix} \Delta \tilde{\boldsymbol{z}}_t \\ \Delta \tilde{\boldsymbol{\lambda}}_t \end{pmatrix} \leq -\frac{\eta_2}{4} \left\| \begin{pmatrix} \nabla_{\tilde{\boldsymbol{z}}_t} \mathcal{L}^{t,0} \\ \nabla_{\tilde{\boldsymbol{\lambda}}_t} \mathcal{L}^{t,0} \end{pmatrix} \right\|^2.$$

Further, there exist an integer $\tau > 0$ and positive constants $\bar{\eta} = (\bar{\eta}_1, \bar{\eta}_2)$ satisfying

$$\bar{\eta}_1 \leq \frac{32^2 \rho^2 \mu^2 \Upsilon^4}{\gamma_{RH}^4}, \quad \bar{\eta}_2 \geq \frac{\gamma_{RH}}{32\rho\Upsilon^2},$$

such that $\eta^t = \bar{\eta}, \forall t \geq \tau$.

Theorem 4.4 shows that the While loop indeed terminates in finite time, and more importantly, the penalty parameter η^t stabilizes after certain iterations. This result is critical for global convergence since, after τ subproblems, all the succeeding subproblems try to decrease a much similar merit function. We note that $\bar{\eta}_1$ depends on μ, so the penalty of the objective connects to the penalty of augmented Lagrangian. We mention that the constants in $\{\tau_i\}_{i=1}^3$ and $\bar{\eta}_1, \bar{\eta}_2$ can be significantly improved by a careful calculation. However, we leave it for future work since it's not main target here.

We now study how the merit function decreases from one subproblem to another.

---

[2][31] showed under certain conditions that the backtracking line search would always select a unit stepsize locally when using exact augmented Lagrangian as the merit function.

Theorem 4.5. Consider Algorithm 1 under Assumptions 4.1 and 4.2. There exists a constant $\bar{\alpha} > 0$ such that $\alpha_t \geq \bar{\alpha}, \forall t \geq \tau$ where τ is from Theorem 4.4. Moreover,

$$\mathcal{L}_{\bar{\eta}}^{t,1} \leq \mathcal{L}_{\bar{\eta}}^{t,0} - \frac{\bar{\eta}_2 \bar{\alpha} \beta}{4} \|\nabla \mathcal{L}^{t,0}\|^2.$$

Theorem 4.5 shows that the Armijo condition is satisfied for sufficiently small α_t, with the threshold independent from t. Moreover, after one Newton step, we can observe a sufficient decrease of the merit function. However, since we only perform one step Newton and transit to the next subproblem immediately, we cannot claim the decrease is sustained. This is indeed the main challenge of global analysis of RTI schemes. Different subproblems target different merit functions, even η is shared.

We show in the next lemma that, the transition between subproblems may increase the merit function, but not too much. Overall, the merit function $\mathcal{L}_{\bar{\eta}}^{t,0}$ keeps decreasing.

Lemma 4.6. Under Assumptions 4.1-4.3 and let $\kappa = \frac{\mu}{\gamma_{RH}}$ denote the condition number of the Hessian matrix. Suppose the constants c, C in Assumption 4.3 satisfies $c \lesssim 1/\kappa^3$ and $C \lesssim \mu$.[3] Then,

$$\mathcal{L}_{\bar{\eta}}^{t+1,0} \leq \mathcal{L}_{\bar{\eta}}^{t,1} + \frac{\bar{\eta}_2 \bar{\alpha} \beta}{8} \|\nabla \mathcal{L}^{t,0}\|^2.$$

Combining Lemma 4.6 with Theorem 4.5, we immediately have

$$\text{one-step error recursion:} \quad \mathcal{L}_{\bar{\eta}}^{t+1,0} \leq \mathcal{L}_{\bar{\eta}}^{t,0} - \frac{\bar{\eta}_2 \bar{\alpha} \beta}{8} \|\nabla \mathcal{L}^{t,0}\|^2. \tag{11}$$

Using (11), we sum over t and finally establish the global convergence in the next theorem.

Theorem 4.7. Consider Algorithm 1 under Assumptions 4.1-4.3. Suppose $c \lesssim 1/\kappa^3$ and $C \lesssim \mu$, then for any input iterate $(\tilde{z}_0^0, \tilde{\lambda}_0^0)$, we have $\|\nabla \mathcal{L}^{t,0}\| \to 0$ as $t \to \infty$.

5 Numerical Experiment

We apply Algorithm 1 on a dynamic program to demonstrate the global behavior of RTI-based MPC. We compare the augmented Lagrangian merit function with ℓ_1 penalized merit function, defined as

$$\bar{\mathcal{L}}_{\nu}^t(\tilde{z}_t; \bar{x}_t) = \sum_{k=t}^{M_t-1} g_k(x_k, u_k) + g_{M_t}(x_{M_t}, \mathbf{0}) + \frac{\mu}{2}\|x_{M_t}\|^2 + \nu \left(\sum_{k=t}^{M_t-1} \|x_{k+1} - f_k(x_k, u_k)\|_1 + \|x_t - \bar{x}_t\|_1 \right).$$

Using $\bar{\mathcal{L}}_{\nu}^t(\cdot)$ as the merit function, the Armijo condition is rewritten as $\bar{\mathcal{L}}_{\nu}^{t,1} \leq \bar{\mathcal{L}}_{\nu}^{t,0} + \alpha_t \beta \cdot D(\bar{\mathcal{L}}_{\nu}^{t,0}, \Delta \tilde{z}_t)$, where $D(\bar{\mathcal{L}}_{\nu}^{t,0}, \Delta \tilde{z}_t)$ is the directional derivative of $\bar{\mathcal{L}}_{\nu}^t(\cdot)$ at $\tilde{z}_t^0$ along the direction $\Delta \tilde{z}_t$, given by

$$D(\bar{\mathcal{L}}_{\nu}^{t,0}, \Delta \tilde{z}_t) = \sum_{k=t}^{M_t-1} \nabla^T g_k(z_{k,t}^0) \Delta z_{k,t} + \nabla_{x_{M_t}}^T g_{M_t}(x_{M_t,t}^0, \mathbf{0}) \Delta x_{M_t,t}$$

$$- \nu \left(\sum_{k=t}^{M_t-1} \|x_{k+1} - f_k(x_k, u_k)\|_1 + \|x_t - \bar{x}_t\|_1 \right) =: D_1 - \nu D_2.$$

To ensure $D(\bar{\mathcal{L}}_{\nu}^{t,0}, \Delta \tilde{z}_t)$ is negative, we let $\nu^t = \max(D_1/\{(\rho-1)D_2\}, \nu^{t-1})$ with $\rho \in (1, 2)$. Thus, the RTI-based MPC using ℓ_1 penalized merit function (called ℓ_1 MPC) is obtained by replacing Lines 4 and 7 of Algorithm 1 by the above corresponding steps.

Simulation setups. We consider 1D trigonometric perturbed LQR problem. In particular, we let $g_k(z_k) = a_k x_k^2 + b_k u_k^2 + c_k \sin^2(x_k)$ and $f_k = x_k + u_k + \sin(x_k)$. We study three cases summarized in Table 1. For each case, we perform 5 independent runs with randomly generalized initial iterate $(\tilde{z}_0^0, \tilde{\lambda}_0^0)$, by letting $(x_{k,0}^0, u_{k,0}^0, \lambda_{k,0}^0) \sim \mathcal{N}(0, 25I), \forall k$. We stop the iteration if either $t > N - M$ (i.e. attains the iteration threshold) or $\|\nabla \mathcal{L}^{t,0}\| \leq \epsilon = 10^{-8}$ (i.e. attains the error threshold). We let $B^t = \mu I, \forall t$. For each case, we try three prediction horizon lengths, $M = 5, 10, 15$. We also vary μ

---

[3] "$\lesssim$" means the inequality holds up to a problem-independent constant.

Table 1: Simulation Setups

CASE	N	M	(a_k, b_k, c_k)	μ	η_1	η_2	β	ν^0	ρ	$\bar{x}_0$	ϵ
CASE 1	100	$(5, 10, 15)$	$(1, 1, 1)$	5	25	1	0.4	1	1.5	10	10^{-8}
CASE 2	250	$(5, 10, 15)$	(k, k, k)	1	1	1	0.4	1	1.5	10	10^{-8}
CASE 3	250	$(5, 10, 15)$	(k^2, k^2, k^2)	10	100	1	0.4	1	1.5	10	10^{-8}

Table 2: Simulation Results

M	Case	log(Time) Aug	ℓ_1	# of Iter Aug	ℓ_1	Case	log(Time) Aug	ℓ_1	# of Iter Aug	ℓ_1	Case	log(Time) Aug	ℓ_1	# of Iter Aug	ℓ_1
5		-2	-3	20	20		-4	-4	62	**246**		-6	-4	57	**246**
10	Case 1	-5	-7	21	21	Case 2	-4	-4	96	**241**	Case 3	-4	-3	94	**241**
15		-6	-6	24	24		-4	-3	127	**236**		-4	-3	127	**236**

(the boldface number indicates the iteration stops by attaining the iteration threshold)

in different cases to test the robustness of Algorithm 1 on μ. For Case 1, we let $a_k = b_k = c_k = 1$, which results in a time-invariant problem. For Cases 2 and 3, we let $a_k = b_k = c_k = k$ or k^2, which results in time-varying problems. The linear and quadratic increase of coefficients bring significant challenges for solving subproblems online. The code is implemented in Julia 1.5.2.

Evaluation of results. For each case, we compare the average running time between two merit functions, and compare the maximum (over 5 independent runs) of the number of iterations. The comparisons are shown in Table 2. From Table 2, we see that two merit functions work equally well for the time-invariant problem in Case 1, while the augmented Lagrangian works significantly better than the ℓ_1 MPC for the time-varying problems in Cases 2 and 3. The latter fails to attain 10^{-8} KKT residuals within 250 iterations in both Case 2 and Case 3.

Moreover, we plot $\|\nabla \mathcal{L}^{t,0}\|$ v.s. t in log scale for all cases. The plots are shown in Figure 1. We see from Figure 1 (a)-(f) that both MPC schemes achieve global convergence within 25 iterations for the time-invariant problem in Case 1. Their (linear) convergence speed is comparable as well. However, for the time-varying problems in Cases 2 and 3, Figure 1 (g)-(r) suggest that augmented Lagrangian MPC performs much better than ℓ_1 MPC. Although both schemes decrease the KKT residuals as t increases, which validates our global convergence theory, augmented Lagrangian MPC decreases the residuals linearly in t, and below the threshold $\epsilon = 10^{-8}$ within a moderate number of iterations. As a comparison, ℓ_1 MPC decreases the residuals only to $[10^{-2}, 10^{-4}]$ using 250 iterations. Moreover, it is clear to see that ℓ_1 MPC has a slow convergence speed locally (because the tail of $\|\nabla \mathcal{L}^{t,0}\|$ is flat), which does not appear in augmented Lagrangian MPC. Therefore, for time-varying problems, the proposed augmented Lagrangian MPC is much preferable than ℓ_1 MPC.

We also take Case 2 as an example to show our algorithm is robust to μ. We vary $\mu = 1, 2, 3, 4, 5$ and randomly generate an initial point for each μ. We see from Figure 1 (s)-(x) that the performance of our algorithm is stable for different choices of μ.

6 Conclusion

We studied the global behavior of RTI-based nonlinear MPC algorithm. Different from the existing schemes, we imposed line search for each subproblem to select the stepsize, using a differentiable exact augmented Lagrangian as the merit function. We proved that the proposed algorithm enjoys global convergence: for any initial iterates, the KKT residuals of subproblems converge to zero. Our analysis complements the existing local analyses of RTI-based MPC, which require a sufficiently good initial point.

One extension is to replace the Newton step by the quasi-Newton step. This may leads to a slow local convergence, however, the global convergence should be preserved. Another important extension is to study stochastic dynamics, like [48]. We can evaluate the iteration by either regret [30] or $\mathbb{E}\|\nabla \mathcal{L}^{t,0}\|$. Then even the local stability property of RTI-based MPC is not well understood. Finally, our experiments show that RTI-based MPC converge globally even for moderate μ (e.g. $\mu = 1$), which in some sense suggests Assumption 4.3 is not necessary. How to remove Assumption 4.3 even in local analysis is worth studying.

Figure 1: KKT residual plot. Each panel corresponds to a combination of Case, M and the merit function. The figures (a)-(r) correspond to the settings in Table 1. In each panel, the five lines correspond to five different initial points that are randomly generalized. The figures (s)-(x) tests the robustness of μ using Case 2. In each panel, the five lines correspond to five μ varying from 1 to 5, with randomly generated initial point.

References

[1] Thivaharan Albin, Dennis Ritter, Dirk Abel, Norman Liberda, Rien Quirynen, and Moritz Diehl. Nonlinear mpc for a two-stage turbocharged gasoline engine airpath. In *2015 54th IEEE Conference on Decision and Control (CDC)*, pages 849–856. IEEE, 2015.

[2] Dimitri P Bertsekas. *Constrained optimization and Lagrange multiplier methods*. Academic press, 2014.

[3] Lorenz T Biegler and James Blake Rawlings. Optimization approaches to nonlinear model predictive control. Technical report, Argonne National Lab., IL (USA), 1991.

[4] H. G. Bock, M. Diehl, E. A. Kostina, and J. P. Schlöder. Constrained optimal feedback control of systems governed by large differential algebraic equations. In *Real-Time and Online PDE-Constrained Optimization*, pages 3–22. SIAM, 2007.

[5] Hans Georg Bock, Moritz Diehl, DB Leineweber, and JP Schlöder. Efficient direct multiple shooting in nonlinear model predictive control. *Scientific Computing in Chemical Engineering II*, 2:218–227, 1999.

[6] Paul T Boggs and Jon W Tolle. Sequential quadratic programming. *Acta numerica*, 4(1):1–51, 1995.

[7] J. Bonilla, R. D. Keyser, M. Diehl, and J. Espinosa. Fast NMPC of a DC-DC converter: An exact Newton real-time iteration approach. In *Nonlinear Control Systems*, 2007.

[8] Lucian Busoniu. *Reinforcement learning and dynamic programming using function approximators*. CRC Press, Boca Raton, FL, 2010.

[9] Ching-An Cheng, Jonathan Lee, Ken Goldberg, and Byron Boots. Online learning with continuous variations: Dynamic regret and reductions. In *International Conference on Artificial Intelligence and Statistics*, pages 2218–2228. PMLR, 2020.

[10] M. Diehl, R. Findeisen, H.G. Bock, F. Allgöwer, and J.P. Schlöder. Nominal stability of real-time iteration scheme for nonlinear model predictive control. *IEE Proceedings - Control Theory and Applications*, 152(3):296–308, may 2005.

[11] Moritz Diehl. *Real-time optimization for large scale nonlinear processes*. PhD thesis, 2001.

[12] Moritz Diehl, Hans Georg Bock, and Johannes P. Schlöder. A real-time iteration scheme for nonlinear optimization in optimal feedback control. *SIAM Journal on Control and Optimization*, 43(5):1714–1736, jan 2005.

[13] Moritz Diehl, H.Georg Bock, Johannes P. Schlöder, Rolf Findeisen, Zoltan Nagy, and Frank Allgöwer. Real-time optimization and nonlinear model predictive control of processes governed by differential-algebraic equations. *Journal of Process Control*, 12(4):577–585, jun 2002.

[14] Moritz Diehl, Hans Joachim Ferreau, and Niels Haverbeke. Efficient numerical methods for nonlinear MPC and moving horizon estimation. In *Nonlinear model predictive control*, pages 391–417. Springer, 2009.

[15] Moritz Diehl, Lalo Magni, and Giuseppe De Nicolao. Efficient nmpc of unstable periodic systems using approximate infinite horizon closed loop costing. *Annual Reviews in Control*, 28(1):37–45, 2004.

[16] Quoc Tran Dinh, Carlo Savorgnan, and Moritz Diehl. Adjoint-based predictor-corrector sequential convex programming for parametric nonlinear optimization. *SIAM J. Optim.*, 22(4):1258–1284, 2012.

[17] H. J. Ferreau, P. Ortner, P. Langthaler, L. del Re, and M. Diehl. Predictive control of a real-world diesel engine using an extended online active set strategy. *Annual Reviews in Control*, 31(2):293–301, 2007.

[18] Hans Joachim Ferreau, Boris Houska, Kurt Geebelen, and Moritz Diehl. Real-time control of a kite-model using an auto-generated nonlinear MPC algorithm. In *Proceedings of the 18th IFAC World Congress*, 2011.

[19] J. V. Frasch, A. J. Gray, M. Zanon, H. J. Ferreau, S. Sager, F. Borrelli, and M. Diehl. An auto-generated nonlinear MPC algorithm for real-time obstacle avoidance of ground vehicles. In *Proceedings of the European Control Conference (ECC)*, pages 4136–4141, 2013.

[20] S. Gros, M. Vukov, and M. Diehl. A real-time MHE and NMPC scheme for wind turbine control. In *Proceedings of the IEEE Conference on Decision and Control (CDC)*, 2013.

[21] Sébastien Gros, Rien Quirynen, and Moritz Diehl. Aircraft control based on fast non-linear mpc & multiple-shooting. In *2012 IEEE 51st IEEE Conference on Decision and Control (CDC)*, pages 1142–1147. IEEE, 2012.

[22] Sébastien Gros, Rien Quirynen, and Moritz Diehl. An improved real-time economic nmpc scheme for wind turbine control using spline-interpolated aerodynamic coefficients. In *53rd IEEE Conference on Decision and Control*, pages 935–940. IEEE, 2014.

[23] Sébastien Gros, Mario Zanon, and Moritz Diehl. Control of airborne wind energy systems based on nonlinear model predictive control & moving horizon estimation. In *2013 European Control Conference (ECC)*, pages 1017–1022. IEEE, 2013.

[24] Sébastien Gros, Mario Zanon, Rien Quirynen, Alberto Bemporad, and Moritz Diehl. From linear to nonlinear MPC: bridging the gap via the real-time iteration. *International Journal of Control*, 93(1):62–80, sep 2016.

[25] Sébastien Gros, Mario Zanon, Milan Vukov, and Moritz Diehl. Nonlinear mpc and mhe for mechanical multi-body systems with application to fast tethered airplanes. *IFAC Proceedings Volumes*, 45(17):86–93, 2012.

[26] Lars Grüne, Jürgen Pannek, Martin Seehafer, and Karl Worthmann. Analysis of unconstrained nonlinear mpc schemes with time varying control horizon. *SIAM Journal on Control and Optimization*, 48(8):4938–4962, 2010.

[27] Boris Houska, Hans Joachim Ferreau, and Moritz Diehl. An auto-generated real-time iteration algorithm for nonlinear MPC in the microsecond range. *Automatica*, 47(10):2279–2285, oct 2011.

[28] Daniel B Leineweber, Irene Bauer, Hans Georg Bock, and Johannes P Schlöder. An efficient multiple shooting based reduced sqp strategy for large-scale dynamic process optimization. part 1: theoretical aspects. *Computers & Chemical Engineering*, 27(2):157–166, 2003.

[29] Wei C Li and Lorenz T Biegler. A multistep, newton-type control strategy for constrained, nonlinear processes. In *1989 American Control Conference*, pages 1526–1527. IEEE, 1989.

[30] Yingying Li, Xin Chen, and Na Li. Online optimal control with linear dynamics and predictions: Algorithms and regret analysis. In *NeurIPS*, pages 14858–14870, 2019.

[31] S Lucidi. Recursive quadratic programming algorithm that uses an exact augmented lagrangian function. *Journal of Optimization Theory and Applications*, 67(2):227–245, 1990.

[32] Nicholas Maratos. Exact penalty function algorithms for finite dimensional and control optimization problems. 1978.

[33] A M'hamdi, A Helbig, O Abel, and W Marquardt. Newton-type receding horizon control and state estimation-a case study. *IFAC Proceedings Volumes*, 29(1):5917–5922, 1996.

[34] Sen Na and Mihai Anitescu. Exponential decay in the sensitivity analysis of nonlinear dynamic programming. *SIAM Journal on Optimization*, 30(2):1527–1554, jan 2020.

[35] Sen Na and Mihai Anitescu. Superconvergence of online optimization for model predictive control. *arXiv preprint arXiv:2001.03707*, 2020.

[36] Sen Na, Sungho Shin, Mihai Anitescu, and Victor M Zavala. Overlapping schwarz decomposition for nonlinear optimal control. *arXiv preprint arXiv:2005.06674*, 2020.

[37] Jorge Nocedal and Stephen J. Wright. *Numerical Optimization*. Springer Series in Operations Research and Financial Engineering. Springer New York, 2nd edition, 2006.

[38] Armin Nurkanovic, Andrea Zanelli, Sebastian Albrecht, and Moritz Diehl. The advanced step real time iteration for NMPC. In *2019 IEEE 58th Conference on Decision and Control (CDC)*, pages 5298–5305. IEEE, IEEE, dec 2019.

[39] Armin Nurkanović, Andrea Zanelli, Gianluca Frison, Sebastian Albrecht, and Moritz Diehl. Contraction properties of the advanced step real-time iteration. In *Proceedings of the IFAC World Congress*, volume 51, 2020.

[40] Toshiyuki Ohtsuka. A continuation/GMRES method for fast computation of nonlinear receding horizon control. *Automatica*, 40(4):563–574, apr 2004.

[41] Klaus Schittkowski. The nonlinear programming method of wilson, han, and powell with an augmented lagrangian type line search function. *Numerische Mathematik*, 38(1):83–114, 1982.

[42] Klaus Schittkowski. On the convergence of a sequential quadratic programming method with an augmented lagrangian line search function. *Mathematische Operationsforschung und Statistik. Series Optimization*, 14(2):197–216, 1983.

[43] Joelle Skaf, Stephen Boyd, and Assaf Zeevi. Shrinking-horizon dynamic programming. *International Journal of Robust and Nonlinear Control*, 20(17):1993–2002, 2010.

[44] Kouichi Taji and Masao Fukushima. A new merit function and a successive quadratic programming algorithm for variational inequality problems. *SIAM Journal on Optimization*, 6(3):704–713, 1996.

[45] Chun-Ming Tang and Jin-Bao Jian. A sequential quadratically constrained quadratic programming method with an augmented lagrangian line search function. *Journal of Computational and Applied Mathematics*, 220(1-2):525–547, 2008.

[46] Q. Tran-Dinh, C. Savorgnan, and M. Diehl. Real-time sequential convex programming for nonlinear model predictive control and application to a hydro-power plant. In *Proceedings of the IEEE Conference on Decision and Control and European Control Conference (CDC-ECC)*, pages 5905–5910, December 2011.

[47] Milan Vukov, S Gros, G Horn, Gianluca Frison, Kurt Geebelen, John Bagterp Jørgensen, Jan Swevers, and Moritz Diehl. Real-time nonlinear MPC and MHE for a large-scale mechatronic application. *Control Engineering Practice*, 45:64–78, 2015.

[48] Nolan Wagener, Ching-An Cheng, Jacob Sacks, and Byron Boots. An online learning approach to model predictive control. *arXiv preprint arXiv:1902.08967*, 2019.

[49] Yang Wang and Stephen Boyd. Fast model predictive control using online optimization. *IEEE Transactions on Control Systems Technology*, 18(2):267–278, 2010.

[50] Andrew Wynn, Milan Vukov, and Moritz Diehl. Convergence guarantees for moving horizon estimation based on the real-time iteration scheme. *IEEE Trans. Automat. Control*, 59(8):2215–2221, 2014.

[51] Jianjun Yuan and Andrew Lamperski. Trading-off static and dynamic regret in online least-squares and beyond. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 6712–6719, 2020.

[52] Andrea Zanelli, Rien Quirynen, Gianluca Frison, and Moritz Diehl. A partially tightened real-time iteration scheme for nonlinear model predictive control. In *2017 IEEE 56th Annual Conference on Decision and Control (CDC)*, pages 4388–4393. IEEE, IEEE, dec 2017.

[53] Victor M. Zavala and Mihai Anitescu. Real-time nonlinear optimization as a generalized equation. *SIAM J. Control Optim.*, 48(8):5444–5467, 2010.

[54] Victor M Zavala and Mihai Anitescu. Scalable nonlinear programming via exact differentiable penalty functions and trust-region newton methods. *SIAM Journal on Optimization*, 24(1):528–558, 2014.

[55] Lijun Zhang, Tianbao Yang, Zhi-Hua Zhou, et al. Dynamic regret of strongly adaptive methods. In *International conference on machine learning*, pages 5882–5891. PMLR, 2018.

[56] J. Zhao, M. Diehl, R. Longman, H.G. Bock, and J.P. Schlöder. Nonlinear model predictive control of robots using real-time optimization. In *Proceedings of the AIAA/AAS Astrodynamics Conference*, Providence, RI, August 2004.