Inference for Probabilistic Dependency Graphs

Abstract

Probabilistic dependency graphs (PDGs) are a flexible class of probabilistic graphical models, subsuming Bayesian Networks and Factor Graphs. They can also capture inconsistent beliefs, and provide a way of measuring the degree of this inconsistency. We present the first tractable inference algorithm for PDGs with discrete variables, making the asymptotic complexity of PDG inference similar that of the graphical models they generalize. The key components are: (1) the observation that PDG inference can be reduced to convex optimization with exponential cone constraints, (2) a construction that allows us to express these problems compactly for PDGs of boundeed treewidth, for which we needed to further develop the theory of PDGs, and (3) an appeal to interior point methods that can solve such problems in polynomial time. We verify the correctness and time complexity of our approach, and provide an implementation of it. We then evaluate our implementation, and demonstrate that it outperforms baselines approaches.

1 INTRODUCTION

Probabilistic dependency graphs (PDGs) [Richardson and Halpern, 2021], form a very general class of probabilistic graphical models, that includes not only Bayesian Networks (BNs) and Factor Graphs (FGs), but also other statistical models such as Variational Autoencoders (VAEs) [Kingma and Welling, 2014]. PDGs can also capture inconsistent beliefs, and moreover provide a useful quantification of the degree of this inconsistency; for a VAE, this is the loss function used in training. But up to now, there has been no practical way to do inference for PDGs—that is, to answer questions of the form "what is the probability of Y given X?" This paper presents the first algorithm to do so.

Before discussing our algorithm, we must discuss what it even means to do inference for a PDG. A BN or FG represents a unique distribution. Thus, for example, when we ask "what is the probability of Y given that $X{=}x$?" in a BN, we mean "what is $\mu(Y|X{=}x)$?" for the probability measure μ that the BN represents. But a PDG does not, in general, represent just one probability distribution.

Like a BN, a PDG encodes two types of information: "structural" information about the independence of causal mechanisms, and "observational" information about conditional probabilities. Unlike in a BN, the two can conflict in a PDG. Corresponding to these two types of information, a PDG has two loss functions, which quantify how far a distribution μ is from modeling the information of each type. Given a weight $\hat{\gamma} \in [0,1]$ indicating the relative importance of structure to observation, we take the $\hat{\gamma}$-*semantics* of a PDG to be the set of distributions that minimize the appropriate convex combination of losses. We also consider the 0^+-*semantics*: the limiting case that arises as $\hat{\gamma}$ goes to zero (and so focuses on the observational loss, using the structural loss only to break ties). This set can be shown to contain precisely one distribution for PDGs satisfying a mild regularity condition (required by definition in Richardson and Halpern); for now, we call such PDGs *proper*. This gives us a parameterized family of inference notions: to do $\hat{\gamma}$-inference, for $\hat{\gamma} \in [0,1] \cup \{0^+\}$, is to answer queries in a way that is true of all distributions in the $\hat{\gamma}$-semantics.

If there are distributions fully consistent with both the observational and the structural information in a PDG $\mathcal{M}$, then for $\hat{\gamma} \in (0,1) \cup \{0^+\}$, all notions of $\hat{\gamma}$-inference coincide. If $\mathcal{M}$ is also proper, this means there is a single distribution $\mu_{\mathcal{M}}$ that minimizes both loss functions, in which case we want to answer queries with respect to $\mu_{\mathcal{M}}$ no matter how we weight observational and structural information. Moreover, if $\mathcal{M}$ represents a BN, then $\mu_{\mathcal{M}}$ is the distribution represented by the BN. However, if there is no distribution that is consistent with both types of information, then the choice of $\hat{\gamma}$ matters.

Since PDGs subsume BNs, and inference for BNs is already

NP-hard, the same must be true of PDGs. At a high level, the best we could hope for would be tractability on the restricted class of models on which inference has traditionally been tractable—that is, a polynomial algorithm for models whose underlying structure has *bounded treewidth* (see Section 2 for formal definitions). That is indeed what we have. More precisely, we show that 0^+-inference and $\hat{\gamma}$-inference for small $\hat{\gamma}$ can be done for discrete PDGs of bounded treewidth containing N variables in $\tilde{O}(N^4)$ time.

Our algorithm is based on a line of recent work in convex programming that establishes polynomial-time for a class of optimization problems called *exponential conic programs* [Badenbroek and Dahl, 2021, Skajaa and Ye, 2015, Nesterov et al., 1999]. Our contribution is to show that the problem of inference in a PDG of bounded treewidth can be efficiently converted to a (sequence of) exponential conic program(s), at which point it can be solved with a commercial solver (e.g., ApS [2022]) in polynomial time. The direct appeal to a solver allows us to benefit from the speed and reliability of such highly optimized solvers, and also from future improvements in exponential conic optimization. Thus, our result is not only a theoretical one, but practical as well.

Beyond its role as a probabilistic model, a PDG is also of interest for its degree of inconsistency—that is, the minimium value of its loss function. As shown by Richardson [2022], many loss functions and statistical divergences can be viewed as measuring the inconsistency of a PDG that models the context appropriately. This makes calculating this minimum value of interest—but up to now, there has been no way to do so. There is a deep connection between this problem and PDG inference; for now, we remark that this number is a byproduct of our techniques.

Contributions. We provide the first algorithm for inference in a PDG; in addition, it calculates a PDG's degree of inconsistency. We prove that our algorithm is correct, and also fixed-parameter tractable: for PDGs of bounded treewidth, it runs in polynomial time. Our algorithm reduces inference in PDGs to exponential conic programming, in a way that can be offloaded to powerful existing solvers. We also provide an implementation of the conversion in a standard convex optimization framework, giving users an interface between such solvers and the standard PDG Python library. Finally, we perform a preliminary evaluation of our implementation which suggests that our method is faster and much more reliable than our simple baselines.

2 PRELIMINARIES & RELATED WORK

Vector Notation. For us, a vector is a map from a finite set S, called its *shape*, to the extended reals $\overline{\mathbb{R}} := \mathbb{R} \cup \{\infty\}$. We write $\mathbf{u} := [u_i]_{i \in S}$ to define a vector by its components. Vectors of the same shape can be added (+), partially ordered ($\leq$), or multiplied ($\odot$) pointwise as usual. $\mathbf{1}$ denotes an all-

ones vector, of a shape implied by context.

Probabilities. We write ΔS to denote the set of probability distributions over a finite set S. Every variable X can take on values from a finite set $\mathcal{V}X$ of possible values. We can regard sets of variables $\mathbf{X}$ as variables themselves, with $\mathcal{V}\mathbf{X} = \Pi_{X \in \mathbf{X}} \mathcal{V}X$. A conditional probability distribution (cpd) $p(Y|X)$ is a map p that assigns each $x \in \mathcal{V}X$ a probability distribution $p(Y|X{=}x) \in \Delta \mathcal{V}Y$. Given a joint distribution μ, we write $\mu(X)$ for its marginal on X, and $\mu(Y|X)$ for the cpd obtained by conditioning on X and marginalizing to Y. We also refer to μ's entropy $\mathrm{H}(\mu) := \mathbb{E}_\mu[\log \frac{1}{\mu}]$ and conditional entropy $\mathrm{H}_\mu(Y|X) := \mathbb{E}_\mu[\log 1/\mu(Y|X)]$.

Hypergraphs and Treewidth. A hypergraph $(V, \mathcal{E})$ is a set V of vertices and a set $\mathcal{E}$ of *hyperedges*, which correspond to subsets of V. An ordinary graph may be viewed as the special case in which every hyperedge contains two vertices.

Definition 1. A *directed hypergraph* $(N, \mathcal{A})$ is a set N of nodes, and a set $\mathcal{A}$ of *(hyper)arcs*, each $a \in \mathcal{A}$ is associated with a set $S_a \subseteq N$ of source nodes, and a set $T_a \subseteq N$ target nodes. We also write $S \xrightarrow{a} T \in \mathcal{A}$ to specify an arc a together with its sources $S = S_a$ and targets $T = T_a$. □

A directed hypergraph can be viewed as a hypergraph by joining each source and target set, thereby "forgetting" the direction of the arrow.

Many problems that are intractable for general graphs are tractable for trees, and some graphs are closer to being trees than others. A tree decomposition of a (hyper)graph $G = (V, \mathcal{E})$ is a tree $(\mathcal{C}, \mathcal{T})$ whose vertices $C \in \mathcal{C}$, called *clusters*, are subsets of V such that:

1. every vertex $v \in V$ and every hyperedge $E \in \mathcal{E}$ is contained in at least one cluster, and
2. every cluster D along the unique path from C_1 to C_2 in $\mathcal{T}$, contains $C_1 \cap C_2$.

The *width* of a tree decomposition is one less than the size of its largest cluster, and the *treewidth* of a (hyper)graph G is the smallest possible width of any tree decomposition of G. It is NP-hard to determine the tree-width of a graph, but if the tree-width is known to be bounded above, a tree decomposition may be constructed in linear time [Bodlaender, 1993]. For graphs of bounded tree-width, many problems (indeed, any problem expressible in a certain second-order logic [Courcelle, 1990]) can be solved in linear time. This is also true of inference in standard graphical models.

Graphical Models and Inference. A *graphical model structure* is a (directed) (hyper)graph whose vertices $\mathcal{X}$ are variables, and whose (hyper)edges somehow indicate local influences between variables. A *probabilistic graphical model*, or simply "graphical model", is a graphical model structure together with quantitative information about these local influences. Semantically, a graphical model $\mathcal{M}$ typically represents a joint probability distribution $\mathrm{Pr}_\mathcal{M} \in \Delta \mathcal{V}\mathcal{X}$ over

its variables. Inference for $\mathcal{M}$ is then the ability to calculate cpds $\mathrm{Pr}_{\mathcal{M}}(Y|X{=}x)$, where $X, Y \subset \mathcal{X}$ and $x \in \mathcal{V}X$.

Many inference algorithms (such as belief propagation), when applied to tree-like graphical models, run in linear time and are provably correct. If the same algorithms are naïvely applied to graphs with cycles (as in loopy belief propagation), then they may not converge, and even if they do, may give incorect (or even inconsistent) answers [Wainwright et al., 2008]. Nearly all exact inference algorithms (including variable elimination, clique-tree calibration, and message-passing with and without division), effectively construct a tree decomposition, and can be viewed as running on a tree [Koller and Friedman, 2009, §9-11]. Indeed, under widely believed assumptions, every class of graphical models for which inference is *not* NP-hard has bounded treewidth [Chandrasekaran et al., 2012]. Given a tree decomposition $(\mathcal{C}, \mathcal{T})$ of the underlying model structure, many of these algorithms use a data structure known as a *clique tree*, which is a collection $\boldsymbol{\mu} = \{\mu_C(C)\}_{C \in \mathcal{C}}$ of probabilities over the clusters [Koller and Friedman, 2009, §10].

A clique tree $\boldsymbol{\mu}$ is said to be *calibrated* if neighboring clusters' distributions agree on the variables they share. In this case, it determines a joint distribution by

$$\mathrm{Pr}_{\boldsymbol{\mu}}(\mathcal{X}) = \prod_{C \in \mathcal{C}} \mu_C(C) \Big/ \prod_{(C-D) \in \mathcal{T}} \mu_C(C \cap D), \quad (1)$$

which has the property that $\mathrm{Pr}_{\boldsymbol{\mu}}(C) = \mu_C$ for all $C \in \mathcal{C}$. A calibrated clique tree summarizes the answers to queries about $\mathrm{Pr}_{\boldsymbol{\mu}}$ [see Koller and Friedman, 2009, §10.3.3]. Therefore, to answer probabilistic queries with respect to a distribution μ, it suffices to find a calibrated clique tree $\boldsymbol{\mu}$ that represents μ, and appeal to standard algorithms.

Probabilistic Dependency Graphs. Our presentation of PDGs is slightly different from (but equivalent to) that of Richardson and Halpern [2021], which the reader is encouraged to consult for more details and intuition. At a high level, a PDG is a collection of cpds and causal assertions, weighted by confidence. More precisely:

Definition 2. A PDG $\mathcal{M} = (\mathcal{X}, \mathcal{A}, \mathbb{P}, \boldsymbol{\alpha}, \boldsymbol{\beta})$ is a directed hypergraph $(\mathcal{X}, \mathcal{A})$ whose nodes are variables, together with probabilities $\mathbb{P}$ and confidence vectors $\boldsymbol{\alpha} = [\alpha_a]_{a \in \mathcal{A}}, \boldsymbol{\beta} = [\beta_a]_{a \in \mathcal{A}}$, so that each $S \xrightarrow{a} T \in \mathcal{A}$ is associated with:

- a conditional probability distribution $\mathbb{P}_a(T|S)$, on the target variables given the values of the source variables,
- a weight $\beta_a \in \overline{\mathbb{R}}$ indicating the modeler's confidence in the cpd $\mathbb{P}_a(T|S)$, and
- a weight $\alpha_a \in \mathbb{R}$ indicating the modeler's confidence in the functional dependence of T on S expressed by a.

If $\boldsymbol{\beta} \geq \boldsymbol{0}$ and $\alpha_a > 0$ implies $\beta_a > 0$, we call $\mathcal{M}$ *proper*. $\quad\square$

As mentioned in the introduction, a PDG contains two types of information: "structural" information in the hypergraph structure $\mathcal{A}$ and weights $\boldsymbol{\alpha}$, and "observational" information, in the cpds $\mathbb{P}$ and weights $\boldsymbol{\beta}$. The semantics of PDGs are based on two scoring functions that quantify the discrepancy between each type of information and a joint distribution $\mu \in \Delta \mathcal{V} \mathcal{X}$ over its variables.

The *observational incompatibility* of μ with $\mathcal{M}$, which can be thought of as a "distance" between μ and the cpds of $\mathcal{M}$, is given by the weighted sum of relative entropies:

$$OInc_{\mathcal{M}}(\mu) := \sum_{S \xrightarrow{a} T \in \mathcal{A}} \beta_a \, \boldsymbol{D}\Big(\mu(T, S) \,\Big\|\, \mathbb{P}_a(T|S)\mu(S)\Big).$$

Under a standard interpretation of the relative entropy $\boldsymbol{D}(\mu \| p) = \mathbb{E}_{\mu}[\log \frac{\mu}{p}]$, $OInc_{\mathcal{M}}$ measures the excess cost of using codes optimized for the cpds of $\mathcal{M}$ (weighted by their confidences), when reality is distributed according to μ.

The second scoring function measures the extent to which μ is incompatible with a causal picture consisting of independent mechanisms along each hyperarc. This is captured by the *structural incompatibility* (of μ with $\mathcal{M}$), and given by

$$SInc_{\mathcal{M}}(\mu) := \Big(\sum_{S \xrightarrow{a} T \in \mathcal{A}} \alpha_a \, \mathrm{H}_{\mu}(T|S) \Big) - \mathrm{H}(\mu).$$

Note that it does not depend on the cpds of $\mathcal{M}$, nor the possible values of the variables; it is defined purely in terms of the weighted hypergraph structure $(\mathcal{A}, \boldsymbol{\alpha})$.

When the observational and structural information conflict, then the distribution(s) that best represent a PDG will depend on the relative importance of observation and structure. This is captured by a trade-off paramter $\hat{\gamma} \in [0, 1]$, which we can use to form the convex combination $(1-\hat{\gamma}) OInc + \hat{\gamma} SInc$. So as to simplify the math and match the notation in previous work (2021, 2022), we instead use a rescaled variant with different parameterization. Let $\gamma := \hat{\gamma}/(1-\hat{\gamma}) \in [0, \infty]$, which is almost identical to $\hat{\gamma}$ when $\hat{\gamma} \approx 0$. With it, define the combined scoring function:

$$\llbracket \mathcal{M} \rrbracket_{\gamma}(\mu) := OInc_{\mathcal{M}}(\mu) + \gamma \, SInc_{\mathcal{M}}(\mu) \quad (2)$$
$$= \frac{1}{1-\hat{\gamma}} \Big((1-\hat{\gamma}) OInc_{\mathcal{M}}(\mu) + \hat{\gamma} \, SInc_{\mathcal{M}}(\mu) \Big)$$
$$= \mathbb{E}_{\mu}\left[\sum_{S \xrightarrow{a} T \in \mathcal{A}} \log \frac{\mu(T|S)^{\beta_a - \gamma \alpha_a}}{\mathbb{P}_a(T|S)^{\beta_a}} \right] - \gamma \, \mathrm{H}(\mu).$$

Let $\llbracket \mathcal{M} \rrbracket_{\gamma}^* := \arg\min_{\mu} \llbracket \mathcal{M} \rrbracket_{\gamma}(\mu)$ denote the set of optimal distributions at a particular value γ. One natural conception of inference in PDGs is then parameterized by $\hat{\gamma}$: to do $\hat{\gamma}$-inference in $\mathcal{M}$ is to respond to probabilistic queries in a way that is sound with respect to every $\mu \in \llbracket \mathcal{M} \rrbracket_{\gamma}^*$. It is not too difficult to see that when $\boldsymbol{\beta} \geq \gamma \boldsymbol{\alpha}$, (2) is strictly convex, which ensures that $\llbracket \mathcal{M} \rrbracket_{\gamma}^*$ is a singleton. This paper demonstrates that $\hat{\gamma}$-inference is tractable for such PDGs.

The limiting behavior of the $\hat{\gamma}$-semantics as $\hat{\gamma} \to 0$, which we denote $\llbracket \mathcal{M} \rrbracket_{0+}^*$ and call the 0^+-*semantics*, has some special properties. If $\mathcal{M}$ is proper, then $\llbracket \mathcal{M} \rrbracket_{0+}^*$ contains

precisely one distribution. This distribution intuitively reflects an extreme empirical view: observational data trumps causal structure. Note that in the absence of a causal picture ($\boldsymbol{\alpha} = \mathbf{0}$), this corresponds to the well-established practice of selecting the maximum entropy distribution consistent with some observational constraints [Jaynes, 1957]. One should be careful to distinguish $[\![m]\!]_{0^+}^*$ from $[\![m]\!]_0^*$, the set of distributions that minimize $OInc_m$; the latter set includes $[\![m]\!]_{0^+}^*$ [Richardson and Halpern, 2021, Prop 3.4], but may also contain other distributions. This paper also shows how to efficiently answer queries with respect to the unique distribution in $[\![m]\!]_{0^+}^*$, which we call 0^+-*inference*.

Given a PDG m, the smallest possible value of its scoring function, $\langle\!\langle m \rangle\!\rangle_\gamma := \inf_\mu [\![m]\!]_\gamma(\mu)$, is known as its γ-inconsistency and is interesting in its own right: $\langle\!\langle \cdot \rangle\!\rangle_\gamma$ seems to be a "universal" loss function [Richardson, 2022].

Interior-Point Methods and Convex Optimization. Interior-point methods provide an iterative way of approximately solving linear programs in polynomial time [Karmarkar, 1984]. With the theory of "symmetric cones", these methods were extended in the 1990s to handle second-order cone programs (SOCPs) and semidefinite programs (SDPs), which allow more expressive constraints. But the constraints that these methods can handle are insufficient for our purposes. We need what have been called *exponential cone constraints*. The *exponential cone* is the convex set

$$K_{\exp} := \big\{(x_1, x_2, x_3) : x_1 \geq x_2 e^{x_3/x_2}, \, x_2 > 0\big\}$$
$$\cup \big\{(x_1, 0, x_3) : x_1 \geq 0, \, x_3 \leq 0\big\} \qquad \subset \bar{\mathbb{R}}^3.$$

Let $K := K_{\exp}^p \times [0, \infty]^q \subset \bar{\mathbb{R}}^n$ be a product of p exponential cones and $q = n - 3k$ non-negative orthants. An *exponential conic program* is then an optimization problem of the form

$$\underset{\mathbf{x}}{\text{minimize}} \quad \mathbf{c}^\top \mathbf{x} \quad \text{subject to} \quad A\mathbf{x} = \mathbf{b}, \, \mathbf{x} \in K, \quad (3)$$

where $\mathbf{c} \in \bar{\mathbb{R}}^n$ is some cost vector, the function $\mathbf{x} \mapsto \mathbf{c}^\top \mathbf{x}$ is called the *objective*, and $\mathbf{b} \in \bar{\mathbb{R}}^m$, $\mathbf{A} \in \bar{\mathbb{R}}^{m \times n}$ encode linear constraints. Nesterov, Todd, and Ye [1999] first established that such problems can be solved in polynomial time, but incur double the memory and eight times the time, compared to the symmetric counterparts. These drawbacks were eliminated in Skajaa and Ye [2015]. The algorithm that seems to display the best empirical performance [Dahl and Andersen, 2022], however, was only recently shown to run in polynomial time [Badenbroek and Dahl, 2021].

Disciplined Convex Programming [Grant, 2004] is a compositional approach to convex optimization that imposes certain restrictions on how problems can be formed; a program conforming to those rules is said to be dcp. The reason to do so is that a dcp program can be efficiently compiled to a standard form [Agrawal et al., 2018], which in our case is an exponential conic program. Only two rules are relevant to us: a constraint of the form $(x, y, z) \in K_{\exp}$ is dcp iff

x, y, and z are affine transformations of the variables being optimized, and a linear program augmented with dcp exponential conic constraints is dcp. Because all the optimiztation problems that we give are of this form, we can easily compile them to exponential conic programs even if they do not exactly conform to (3).

3 INFERENCE AS A CONVEX PROGRAM

Here is an obvious, if inefficient, way of calculating $\text{Pr}_\mathcal{M}(Y | X = x)$ in a probabilistic model $\mathcal{M}$. First compute an explicit representation of the joint distribution $\text{Pr}_\mathcal{M} \in \Delta\mathcal{VX}$, then marginalize to $\text{Pr}_\mathcal{M}(X, Y)$ and condition on $X = x$. For a factor graph or BN, each step is straightforward; the problem is the exponential time and space required to represent $\text{Pr}_\mathcal{M}(\mathcal{X})$ explicitly. A key feature of inference algorithms for BNs and FGs is that they do not represent joint distributions in this way. For PDGs, though, it is not obvious that we can calculate the $\hat{\gamma}$-semantics, even if we know it is unique, and we ignore the space required to represent it (as we do in this section). Note that $\hat{\gamma}$-inference is already an optimization problem by definition:

$$\underset{\mu}{\text{minimize}} \quad [\![m]\!]_\gamma(\mu) \quad \text{subject to} \quad \mu \in \Delta\mathcal{VX}.$$

For small enough γ, it is even convex. But can we solve it efficiently? With exponential cone constraints, the answer is yes, as we show in Section 3.2. Moreover, we can compute the 0^+-semantics with a sequence of two exponential conic programs (Section 3.3). To give a flavor of our constructions and ease into the more complicated ones, we begin by minimizing $OInc$, the simpler of the two scoring functions.

3.1 MINIMIZING INCOMPATIBILTY ($\gamma = 0$)

When $\gamma = 0$, we want to find minimizers of $OInc$, which is a weighted sum of conditional relative entropies. There is a straightforward connection between the exponential cone and relative entropy: if $\mathbf{m}, \mathbf{p} \in \Delta\{1, \ldots, n\} \subset \mathbb{R}^n$ are points on a probability simplex, then $(-\mathbf{u}, \mathbf{m}, \mathbf{p}) \in K_{\exp}^n$ if and only if $\mathbf{u}$ is an upper bound on $\mathbf{m} \log \frac{\mathbf{m}}{\mathbf{p}}$, the pointwise contribution to relative entropy at each outcome. Thus, perhaps unsurprisingly, we can use an exponential conic program to find minimizers of $OInc$. If all beliefs are unconditional and over the same space, the construction is standard; we review it here, so that we can build upon it.

Warm-up. Consider a PDG with only one variable X with $\mathcal{VX} = \{1, \ldots, n\}$. Suppose further that every arc $j \in \mathcal{A} = \{1, \ldots, k\}$ has $T_j = \{X\}$ and $S_j = \emptyset$. Then each $\mathbb{P}_j(X)$ can be identified with a vector $\mathbf{p}_j \in [0, 1]^n$, and all k of them can be conjoined to form a matrix $\mathbf{P} = [p_{ij}] \in [0, 1]^{n \times k}$. Similarly, a candidate distribution μ can be identified with $\mathbf{m} \in [0, 1]^n$. Now consider a matrix $\mathbf{U} = [u_{i,j}] \in \bar{\mathbb{R}}^{n \times k}$ that, intuitively, gives an upper bound on the contribution to

OInc due to each edge and value of X. Observe that

$$(-\mathbf{U}, [\mathbf{m}, \ldots, \mathbf{m}], \mathbf{P}) \in K_{\exp}^{n \times k}$$

$$\iff \quad \forall i, j. \ u_{ij} \geq m_i \log(m_i/p_{ij})$$

$$\implies \quad \forall j. \ \textstyle\sum_i u_{ij} \geq \mathbf{D}(\mu \parallel p_j)$$

$$\implies \quad \textstyle\sum_{i,j} \beta_j u_{ij} \geq \sum_j \beta_j \mathbf{D}(\mu \parallel p_j)$$

$$\iff \quad \mathbf{1}^\mathsf{T} \mathbf{U} \boldsymbol{\beta} \geq OInc(\mu). \qquad (4)$$

So now, if $(\mathbf{U}, \mathbf{m})$ is a solution to the convex program

$$\underset{\mathbf{m}, \mathbf{U}}{\text{minimize}} \ \ \mathbf{1}^\mathsf{T} \mathbf{U} \boldsymbol{\beta} \ \ \text{subject to} \ \ \mathbf{1}^\mathsf{T} \mathbf{m} = 1,$$
$$(-\mathbf{U}, [\mathbf{m}, \ldots, \mathbf{m}], \mathbf{P}) \in K_{\exp}^{n \times k},$$

then (a) the objective value $\mathbf{1}^\mathsf{T} \mathbf{U} \boldsymbol{\beta}$ equals the inconsistency $\langle\!\langle m \rangle\!\rangle_0$, and (b) $\mu \in [\![m]\!]_0^*$, meaning μ minimizes $OInc_m$.

The General Case. We now show how the same construction can be used to find a distribution $\mu \in [\![m]\!]_0^*$ for an arbitrary PDG $m = (\mathcal{X}, \mathcal{A}, \mathcal{P}, \boldsymbol{\alpha}, \boldsymbol{\beta})$. To further simplify the presentation, for each arc $a \in \mathcal{A}$, let $\mathcal{V}a := \mathcal{V}(S_a, T_a)$ denote all joint settings of a's source and target variables, and write $\mathcal{V}\mathcal{A} := \sqcup_{a \in A} \mathcal{V}a = \{(a, s, t) : a \in \mathcal{A}, (s, t) \in \mathcal{V}(S_a, T_a)\}$ for the set of all choices of an arc together with values of its source and target. For each $a \in \mathcal{A}$, we can regard $\mu(T_a, S_a)$ and $\mu(S_a)\mathbb{P}_a(T_a|S_a)$, both distributions over $\{S_a, T_a\}$, as vectors of shape $\mathcal{V}a$. As before, we introduce an optimization variable $\mathbf{u}$ that packages together all of the relevant pointwise upper bounds. To that end, consider a vector $\mathbf{u} = [u_{a,s,t}] \in \bar{\mathbb{R}}^{\mathcal{V}\mathcal{A}}$ in the optimization problem

$$\underset{\mu, \mathbf{u}}{\text{minimize}} \quad \sum_{(a,s,t) \in \mathcal{V}\mathcal{A}} \beta_a u_{a,s,t} \qquad (5)$$
$$\text{subject to} \quad \mu \in \Delta \mathcal{V}\mathcal{X},$$
$$\forall a \in \mathcal{A}. \ (-\mathbf{u}_a, \mu(T_a, S_a), \mathbb{P}_a(T_a|S_a)\mu(S_a)) \in K_{\exp}^{\mathcal{V}a}$$

where $\mathbf{u}_a = [u_{a,s,t}]_{(s,t) \in \mathcal{V}a}$ consists of those components of $\mathbf{u}$ associated with arc a. Note that the marginals $\mu(S_a, T_a)$ and $\mu(S_a)$ are affine transformations of μ, so (5) is dcp. A straightforward generalization of the logic in (4) gives us:

Proposition 1. *If $(\mu, \mathbf{u})$ is a solution to* (5)*, then $\mu \in [\![m]\!]_0^*$, and $\sum_{(a,s,t) \in \mathcal{V}\mathcal{A}} \beta_a u_{a,s,t} = \langle\!\langle m \rangle\!\rangle_0$.*

Thus, a solution to (5) encodes a distribution that minimizes *OInc*, and the (0-)inconsistency of m. This is a start, but to do 0^+-inference, among the minimizers of *OInc* we must find the unique distribution in $[\![m]\!]_{0^+}^*$, while for $\hat{\gamma}$-inference ($\hat{\gamma} > 0$), we need to find the optimizers of $[\![m]\!]_{\gamma}^*$. Either way, we must consider *SInc* in addition to *OInc*.

3.2 γ-INFERENCE FOR SMALL $\gamma > 0$

When $\gamma > 0$ is small enough, the scoring function (2) is not only convex, but admits a straightforward representation as an exponential conic program. To see this, note that (2) can

be rewritten [Richardson and Halpern, 2021, Prop 4.6] as:

$$[\![m]\!]_{\gamma}(\mu) = -\gamma \operatorname{H}(\mu) - \sum_{a \in \mathcal{A}} \beta_a \ \underset{\mu}{\mathbb{E}} \log \mathbb{P}_a(T_a|S_a)$$
$$+ \sum_{a \in \mathcal{A}} (\gamma \alpha_a - \beta_a) \operatorname{H}_\mu(T_a|S_a). \qquad (6)$$

The first term, $-\gamma \operatorname{H}(\mu)$, is strictly convex and has a well-known translation into an exponential cone constraint; the second one linear in μ. Now, if $0 < \gamma \leq \min_a \frac{\beta_a}{\alpha_a}$, then every summand of the last term is a negative conditional entropy, and can be captured by an exponential cone constraint. The only wrinkle is that it is possible for a user to specify that some $\mathbb{P}_a(t \mid s) = 0$, in which case the linear term is undefined. The result is a requirement that $\mu(s, t) = 0$ at such points, which we can instead encode directly with linear constraints. To do this formally, divide $\mathcal{V}\mathcal{A}$ into two parts: $\mathcal{V}\mathcal{A}^+ := \{(a, s, t) \in \mathcal{V}\mathcal{A} : \mathbb{P}_a(t|s) > 0\}$ and $\mathcal{V}\mathcal{A}^0 := \{(a, s, t) \in \mathcal{V}\mathcal{A} : \mathbb{P}_a(t|s) = 0\}$. Armed with this notation, consider upper bound vectors $\mathbf{u} = [u_{a,s,t}]_{(a,s,t) \in \mathcal{V}\mathcal{A}}$ and $\mathbf{v} = [v_w]_{w \in \mathcal{V}\mathcal{X}}$, in the following optimization problem:

$$\underset{\mu, \mathbf{u}, \mathbf{v}}{\text{minimize}} \quad \sum_{(a,s,t) \in \mathcal{V}\mathcal{A}} (\beta_a - \alpha_a \gamma) u_{a,s,t} \ + \gamma \sum_{w \in \mathcal{V}\mathcal{X}} v_w \qquad (7)$$
$$- \sum_{(a,s,t) \in \mathcal{V}\mathcal{A}^+} \alpha_a \gamma \, \mu(S_a{=}s, T_a{=}t) \log \mathbb{P}_a(t|s)$$

$$\text{subject to} \quad \mu \in \Delta \mathcal{V}\mathcal{X}, \quad (-\mathbf{v}, \mu, \mathbf{1}) \in K_{\exp}^{\mathcal{V}\mathcal{X}},$$
$$\forall a \in \mathcal{A}. \ (-\mathbf{u}_a, \mu(T_a, S_a), \mathbb{P}_a(T_a|S_a)\mu(S_a)) \in K_{\exp}^{\mathcal{V}a},$$
$$\forall (a, s, t) \in \mathcal{V}\mathcal{A}^0. \ \mu(S_a{=}s, T_a{=}t) = 0.$$

Proposition 2. *If $(\mu, \mathbf{u}, \mathbf{v})$ is a solution to* (7)*, and $\boldsymbol{\beta} \geq \gamma \boldsymbol{\alpha}$, then μ is the unique element of $[\![m]\!]_{\gamma}^*$, and $\langle\!\langle m \rangle\!\rangle_\gamma$ equals the objective of* (7) *evaluated at $(\mu, \mathbf{u}, \mathbf{v})$.*

3.3 CALCULATING THE 0^+-SEMANTICS ($\gamma \to 0$)

In Section 3.1 we saw a way to find a distribution that minimizes *OInc*, but to do 0^+-inference, we need to find the distribution that, uniquely among them, best minimizes *SInc*. It turns out that a solution to (5) can be used to construct a second optimization problem of a similar size, that also optimizes *SInc* subject to these constraints. To justify our approach, we need two more results. First, a characterization of the minimizers of $OInc_m$.

Proposition 3. *If m has arcs $\mathcal{A}$ and $\boldsymbol{\beta} \geq 0$, the minimizers of $OInc_m$ all have the same conditional marginals along $\mathcal{A}$. That is, for all $\mu_1, \mu_2 \in [\![m]\!]_0^*$ and all $S \xrightarrow{a} T \in \mathcal{A}$ with $\beta_a > 0$, we have $\mu_1(T, S)\mu_2(S) = \mu_2(T, S)\mu_1(S)$.[1]*

As a result, once we find one minimizer ν of $OInc_m$ (e.g., via (5)), it then suffices to constrain distributions that have

---

[1]Intuitively, this assserts $\mu_1(T|S) = \mu_2(T|S)$, but also handles cases where some $\mu_1(S{=}s)$ or $\mu_2(S{=}s)$ equals zero.

the same conditional marginals along the edges, and optimize $SInc$. But in attempting to do so, we run into a second issue: $SInc$ is typically not convex. Fortunately, it is if we constrain to distributions that minimize $OInc$. Moreover, on this restricted domain, it can be represented with dcp exponential cone constraints.

Proposition 4. *If $\mu \in [\![\mathcal{M}]\!]_0^*$, then*

$$SInc_m(\mu) = \sum_{w \in \mathcal{VX}} \mu(w) \log \left(\mu(w) \Big/ \prod_{a \in \mathcal{A}} \nu(T_a(w)|S_a(w))^{\alpha_a} \right), \quad (8)$$

where $\{\nu(T_a|S_a)\}_{a \in \mathcal{A}}$ consists of the conditional marginals along the arcs $\mathcal{A}$ shared by all distributions in $[\![\mathcal{M}]\!]_0^*$ (per Proposition 3), while $S_a(w)$ and $T_a(w)$ are the values of the variables S_a and T_a in w, respectively.

If we already know a distribution $\nu \in [\![\mathcal{M}]\!]_0^*$, perhaps by solving (5), then the denominator of (8) does not depend on μ and so is constant in our search for minimizers of $SInc$. For ease of exposition, aggregate these values into a vector

$$\mathbf{k} := \left[\prod_{a \in \mathcal{A}} \nu(T_a(w)|S_a(w))^{\alpha_a} \right]_{w \in \mathcal{VX}}. \quad (9)$$

We can now capture $[\![\mathcal{M}]\!]_{0+}^*$ with a convex program.

Proposition 5. *If $\nu \in [\![\mathcal{M}]\!]_0^*$ and $(\mu, \mathbf{u})$ solves the problem*

$$\underset{\mu, \mathbf{u}}{\text{minimize}} \quad \mathbf{1}^\mathsf{T} \mathbf{u} \quad (10)$$
$$\text{subject to} \quad (-\mathbf{u}, \mu, \mathbf{k}) \in K_{\exp}^{\mathcal{VX}}, \quad \mu \in \Delta\mathcal{VX},$$
$$\forall S \xrightarrow{a} T \in \mathcal{A}. \ \mu(S,T)\,\nu(S) = \mu(S)\,\nu(S,T),$$

then $[\![\mathcal{M}]\!]_{0+}^* = \{\mu\}$ and $\mathbf{1}^\mathsf{T}\mathbf{u} = SInc_m(\mu)$.

Running (10) through a convex solver gives rise to the first algorithm that can reliably find $[\![\mathcal{M}]\!]_{0+}^*$.

4 POLYNOMIAL-TIME INFERENCE UNDER BOUNDED TREEWIDTH

We have now seen how $\hat{\gamma}$-inference (for small $\hat{\gamma}$) can be reduced to convex optimization over joint distributions μ— but μ grows exponentially with the number of variables in the PDG, so we do not yet have a tractable inference algorithm. We now show how μ can be replaced with a clique tree over the PDG's structure. What makes this possible is a key independence property of traditional graphical models, which we now prove is true of PDGs as well.

Proposition 6 (Markov Property for PDGs). *If $\mathcal{M}_1$ and $\mathcal{M}_2$ are PDGs over the sets of variables $\mathcal{X}_1$ and $\mathcal{X}_2$, respectively, then $\mathcal{X}_1$ and $\mathcal{X}_2$ are conditionally independent given $\mathcal{X}_1 \cap \mathcal{X}_2$ in every $\mu \in [\![\mathcal{M}_1 + \mathcal{M}_2]\!]_\gamma^*$, for all $\gamma > 0$, and $\gamma = 0^+$.*

For the remainder of this section, fix a PDG $\mathcal{M}$ and a tree decomposition $(\mathcal{C}, \mathcal{T})$ of $\mathcal{M}$'s hypergraph. One significant consequence of Proposition 6 is that, in the search for optimizers of (2), we need consider only distributions that satisfy those independencies, all of which can be represented as a clique tree $\boldsymbol{\mu} = \{\mu_C \in \Delta\mathcal{V}(C)\}_{C \in \mathcal{C}}$ over $(\mathcal{C}, \mathcal{T})$.

Corollary 6.1. *If $\mathcal{M}$ is a PDG with arcs $\mathcal{A}$, $(\mathcal{C}, \mathcal{T})$ is a tree decomposition of $\mathcal{A}$, $\gamma > 0$, and $\mu \in [\![\mathcal{M}]\!]_\gamma^*$, then there exists a clique tree $\boldsymbol{\mu}$ over $(\mathcal{C}, \mathcal{T})$ such that $\Pr_{\boldsymbol{\mu}} = \mu$.*

For convenience, let $\mathcal{VC} := \{(C, c) : C \in \mathcal{C}, c \in \mathcal{V}(C)\}$ be the set of all choices of a cluster and a setting of its variables. We now optimize over possible clique trees $\boldsymbol{\mu}$ over $(\mathcal{C}, \mathcal{T})$, which we identify with vectors $\boldsymbol{\mu} \cong [\mu_C(C{=}c)]_{(C,c) \in \mathcal{VC}}$. Operationally, we need to know the conditional marginals of $\boldsymbol{\mu}$ along each edge in order to calculate $OInc_m(\Pr_{\boldsymbol{\mu}})$. Since $(\mathcal{C}, \mathcal{T})$ is a tree decomposition of $\mathcal{A}$, we are guaranteed that the source and target of every arc a lie entirely within at least one cluster. Fix such a cluster $C_a \in \mathcal{C}$ for each arc $a \in \mathcal{A}$. As before, let $\mathbf{u}$ range over $\bar{\mathbb{R}}^{\mathcal{VA}}$ in the problem

$$\underset{\boldsymbol{\mu}, \mathbf{u}}{\text{minimize}} \quad \sum_{(a,s,t) \in \mathcal{VA}} \beta_a\, u_{a,s,t} \quad (11)$$
$$\text{subject to} \quad \forall C \in \mathcal{C}. \ \mu_C \in \Delta\mathcal{V}(C),$$
$$\forall a \in \mathcal{A}. \ \left(-\mathbf{u}_a, \mu_{C_a}(S_a, T_a), \mu_{C_a}(S_a)\mathbb{P}_a(T_a|S_a) \right) \in K_{\exp}^{\mathcal{V}a}$$
$$\forall (C, D) \in \mathcal{T}. \ \mu_C(C \cap D) = \mu_D(C \cap D),$$

where again $\mathbf{u}_a$ is the restriction of $\mathbf{u}$ to components associated with a. Problem (11) is similar to (5), except that it has local marginal constraints to ensure consistency, since we have to restrict our search to *calibrated* clique trees. In some ways, it is analogous to the problem CTree-Optimize-KL from Koller and Friedman [2009, pg. 384].

Proposition 7. *If $(\boldsymbol{\mu}, \mathbf{u})$ is a solution to (11), then*
(a) $\boldsymbol{\mu}$ is a calibrated, with $\Pr_{\boldsymbol{\mu}} \in [\![\mathcal{M}]\!]_0^*$, and
(b) the objective of (11) evaluated at $\mathbf{u}$ equals $\langle\!\langle \mathcal{M} \rangle\!\rangle_0$.

We can now find a minimizer of $OInc$ and compute $\langle\!\langle \mathcal{M} \rangle\!\rangle_0$ without storing a joint distribution. But to do anything else, we must deviate from the template laid out in Section 3.

Dealing with Joint Entropy. In the construction of (11), we rely heavily on the fact that each term of $OInc_m$ depends only on local marginal distributions $\mu_{C_a}(T_a, S_a)$ and $\mu_{C_a}(S_a)$. The same is not true of $SInc$, which depends on the joint entropy $\mathrm{H}(\Pr_{\boldsymbol{\mu}})$ of the entire distribution. At this point we should point out an important reason to restrict our focus to trees: it allows the joint entropy to be expressed in terms of the cluster marginals [Wainwright et al., 2008], by

$$-\mathrm{H}(\Pr_{\boldsymbol{\mu}}) = -\sum_{C \in \mathcal{C}} \mathrm{H}(\mu_C) + \sum_{(C,D) \in \mathcal{T}} \mathrm{H}_{\boldsymbol{\mu}}(C \cap D). \quad (12)$$

Even so, it is not obvious that (12) can be captured with dcp exponential cone constraints. (Exponential conic programs

can minimize negative entropy, but not positive entropy, which is concave.) We now describe how this can be done.

Choose a root node C_0 of the tree decomposition $\mathcal{T}$, and orient each edge of $\mathcal{T}$ so that it points away from C_0. Now each cluster $C \in \mathcal{C}$, except for C_0, has a parent cluster Par_C; define $\mathrm{Par}_{C_0} := \emptyset$ to be an empty cluster, since C_0 has no parent. Finally, for each $C \in \mathcal{C}$, let $VCP_C := C \cap \mathrm{Par}_C$ denote the the set of **v**ariables that cluster C has in **c**ommon with its **p**arent cluster.[2] As $\mathcal{T}$ is now a directed tree, this definition allow us to express (12) in a more useful form:

$$
\begin{aligned}
-\mathrm{H}(\mathrm{Pr}_{\boldsymbol{\mu}}) &= -\mathrm{H}(\mu_{C_0}) - \sum_{(C \to D) \in \mathcal{T}} \mathrm{H}_{\mathrm{Pr}_{\boldsymbol{\mu}}}(D \mid C) \\
&= \sum_{C \in \mathcal{C}} \sum_{c \in \mathcal{V}(C)} \mu_C(C{=}c) \log \frac{\mu_C(C{=}c)}{\mu_C(VCP_C(c))}, \quad (13)
\end{aligned}
$$

where $VCP_C(c)$ is the restriction of the joint value $c \in \mathcal{V}(C)$ to the variables $VCP_C \subseteq C$. Crucially, the denominator of (13) is an affine transformation of μ_C. The upshot: we have now rewritten the joint entropy as sum of functions of the clusters, each of which can be captured with a dcp exponential cone constraint. This gives us analogues of the problems in Sections 3.2 and 3.3 that operate on clique-trees.

Finding clique trees for $\hat{\gamma}$-inference. The ability to decompose the joint entropy as in (13) allows us to adapt (7) to operate on calibrated clique trees, rather than joint distributions. Beyond the changes already present in (11), the key is to replace the exponential cone constraint $(-\mathbf{v}, \mu, \mathbf{1}) \in K_{\exp}^{\mathcal{VX}}$, which captures the entropy of μ, with

$$
\left(-\mathbf{v}, \; \boldsymbol{\mu}, \; [\mu_C(VCP_C(c))]_{(C,c) \in \mathcal{VC}} \right) \in K_{\exp}^{\mathcal{VC}},
$$

which captures the entropy of $\boldsymbol{\mu}$, by (13). This gives rise to an optimization problem over $\mathbf{v}, \boldsymbol{\mu} \in \bar{\mathbb{R}}^{\mathcal{VC}}$ and $\mathbf{u} \in \bar{\mathbb{R}}^{\mathcal{VA}}$, that we call (14). The rest of the details are less instructive, so we defer them to Appendix A for brevity.

Proposition 8. *If $(\boldsymbol{\mu}, \mathbf{u}, \mathbf{v})$ is a solution to (14), and $\boldsymbol{\beta} \geq \gamma\boldsymbol{\alpha}$, then $\mathrm{Pr}_{\boldsymbol{\mu}}$ is the unique element of $[\![\mathcal{M}]\!]_{\gamma}^*$, and the objective of (14) at $(\boldsymbol{\mu}, \mathbf{u}, \mathbf{v})$ equals $\langle\!\langle\mathcal{M}\rangle\!\rangle_{\gamma}$.*

A related use of (13) is to adapt problem (10) for clique-trees, resulting in an optimization problem that we call (15), whose details we defer to Appendix A as well.

Proposition 9. *If $(\boldsymbol{\mu}, \mathbf{u})$ is a solution to (15), then $\boldsymbol{\mu}$ is a calibrated clique tree and $[\![\mathcal{M}]\!]_{0^+}^* = \{\mathrm{Pr}_{\boldsymbol{\mu}}\}$.*

At this point, the standard algorithms that operate on clique trees can be used to answer probabilistic queries in polynomial time [Koller and Friedman, 2009, §10.3.3]. It therefore

---

[2]Different choices of C_0 yield different definitions of VCP, and ultimately optimization problems of different sizes; the optimal choice can be found with Edmund's Algorithm [Chu, 1965], which computes a directed analogue of the minimum spanning tree.

follows from Propositions 8 and 9 that $\hat{\gamma}$-inference (for small $\hat{\gamma}$, and for 0^+) can be reduced to a (pair of) convex optimization problem(s) with a polynomial number of variables and constraints. All that remains is to show that a problem of this form can be solved in polynomial time. For this, we turn to interior-point methods. Since (14) and (15) are dcp, they can be transformed via established methods [Agrawal et al., 2018] into a standard form that can be solved in polynomial time by commercial solvers [ApS, 2022, Domahidi et al., 2013]. Threading the details of our constructions through the analyses of Dahl and Andersen [2022], and Nesterov et al. [1999] results in our main theorem.

Theorem 10. *Let $\mathcal{M} = (\mathcal{X}, \mathcal{A}, \mathbb{P}, \boldsymbol{\alpha}, \boldsymbol{\beta})$ be a proper discrete PDG with $N = |\mathcal{X}|$ variables each taking at most V values, and $A = |\mathcal{A}|$ arcs forming a hypergraph of treewidth T. Then for all $\gamma \in \{0^+\} \cup (0, \max_{a \in \mathcal{A}} \frac{\beta_a}{\alpha_a}]$ and $\epsilon > 0$, we can do $\hat{\gamma}$-inference to precision ϵ in*

$$
O\Big((N{+}A)^4 V^{4T} \Big(T \log V + \log \frac{N{+}A}{\epsilon} + \log \frac{\beta^{\max}}{\beta^{\min}} \Big) \Big),
$$

time,[†] where $\beta^{\max} := \max_{a \in \mathcal{A}} \beta_a$ and

$$
\beta^{\min} := \begin{cases} \min_{a \in \mathcal{A}} \{\beta_a : \beta_a > 0\} & \text{if } \gamma = 0^+ \\ \gamma & \text{otherwise.} \end{cases}
$$

Our approach to inference computes $\langle\!\langle\mathcal{M}\rangle\!\rangle_{\gamma}$ as a side effect of finding distributions of interest. But suppose that we were interested in calculating only this inconsistency. Might there then be a more direct, asymptotically easier way to do so? In general, the answer is no.

Proposition 11. (a) *Determining if there exists a distribution μ that shares all cpds with $\mathcal{M}$ is NP-hard.*
(b) *Computing $\langle\!\langle\mathcal{M}\rangle\!\rangle_{\gamma}$ is #P-hard, for all $\gamma \geq 0$.*

Rather, the problems are intimately related; see **??**.

5 EXPERIMENTS

We have given the first algorithm to provably do inference in polynomial time, but that does not mean that it's the best way of answering queries in practice; it also makes sense to use black-box optimization tools such as Adam [Kingma and Ba, 2014] or L-BFGS [Fletcher, 2013] to find minimizers of $[\![\mathcal{M}]\!]_{\gamma}$. Indeed, this scoring function has several properties that make it highly amenable to such methods: it is infinitely differentiable, γ-strongly convex, and its derivatives have simple closed-form expressions. So it may seem surprising that $[\![\mathcal{M}]\!]_{\gamma}$ poses a challenge to

---

[†]At the cost of substantial overhead and engineering effort, the exponent 4 can be reduced to 2.872, by appeal to Skajaa and Ye [2015] and the current best matrix multiplication algorithm [Duan et al., 2022, $O(n^{2.372})$] to invert $n{\times}n$ linear systems.

Figure 1: Accuracy and resource costs for the methods in Section 3. Left: a scatter plot of several algorithms on random PDGs of ≈ 10 variables. The x-axis is the score $[\![\mathcal{M}]\!]_\gamma(\mu)$, where μ is the output of the algorithm (lower is better) relative to the best-performing variant for each PDG and value of γ, and the y axis is the time required to compute μ. Our methods are in gold (0^+-inference) and violet ($\hat{\gamma}$-inference); the baselines (black-box optimizers applied directly to (2)) are in green. The area of each circle is proportional to the size of the optimization problem, as measured by $|\mathcal{VX}|$. The points on the left have attained the best possible score. Right: the convex solvers maintain their edge in accuracy even as the problem grows.

standard optimization tools—but it does, even when we optimize directly over joint distributions.

Synthetic Experiment 1 (over joint distributions). First, we randomly generate a small PDG $\mathcal{M}$ containing at most 10 variables and 15 arcs. Then for $\gamma \in \{0, 0^+, \ldots, \min_a \frac{\beta_a}{\alpha_a}\}$, we optimize $[\![\mathcal{M}]\!]_\gamma(\mu)$ over joint distributions μ, either by using cvxpy [Diamond and Boyd, 2016] to feed (5), (7), or (10) to MOSEK ApS [2022], or by using a standard optimizer (Adam or L-BFGS) built into pytorch [Paszke et al., 2019], and choosing a learning rate and a representation of μ in terms of optimization variables $\theta \in \mathbb{R}^n$. We then run the optimizer until it converges (or hits a time limit), and throw out the result if another choice of learning rate achieves a smaller value of $[\![\mathcal{M}]\!]_\gamma(\mu)$. The results are shown in Figure 1. Observe that the convex solver (gold and violet) is significantly more accurate than the baselines, and also much faster for small PDGs (although it uses more memory and doesn't scale as well; see Figure 2 in Appendix C.1).

Synthetic Experiment 2 (over clique trees). For PDGs of bounded treewidth, Corollary 6.1 allows us to express these optimzation problems compactly not just for the convex solver, but for the black-box baseline approaches as well. For this setting, we adapt the previous experiment as follows: first randomly generate a maximal graph of treewidth k and a PDG $\mathcal{M}$ whose hyperarcs lie within cliques of T; this ensures that the maximal cliques of T form a tree-decomposition $(\mathcal{C}, \mathcal{T})$ of $\mathcal{M}$'s structure. Then optimize $[\![\mathcal{M}]\!]_\gamma(\mathrm{Pr}_\mu)$ over clique trees μ over $(\mathcal{C}, \mathcal{T})$. The issue is that the resulting clique trees μ may not be calibrated, because we cannot encode the calibration constraints; instead, common practice is to add a loss term to "encourage" calibration. Still, it is sometimes advantageous for the optimizer

to simply incur that loss and violate the constraint, allowing the optimizer to "cheat". Thus, for fairness, we must recalibrate the final output of the optimizer before evaluating it. The result is a much more significant advantage for the convex solver; see Appendix C.2.

Evaluation on BNs. We then applied the procedure of Synthetic Experiment 1 to the BNs in the `bnlearn` repository and found similar results (but there are many fewer data points). But in cases where the PDG is also a BN, it is possible to use belief propogation for inference, which is much faster and at least as accurate. Many more figures and details about all experiments can be found in Appendix C.

6   DISCUSSION

We have defined a family of inference notions for PDGs, given a fixed-parameter tractable algorithm for it, and shown it to out-perform baselines. Still, much remains to be said about inference in PDGs. Our implementation runs in time $\tilde{O}(N^4)$, and our analysis suggests one of time $\tilde{O}(N^{2.872})$. But under bounded tree-width, inference in other graphical models, and nearly all graph problems can be solved in $O(N^1)$ time. More importantly, we have shown how to do inference only in a small subset of cases: when the $\hat{\gamma}$-semantics is a singleton, because of a pointwise "observational dominance": either $\beta \geq \gamma\alpha$ or $\beta \gg \alpha$. Other cases are certainly of interest as well. When $\beta = 0$ and $(\mathcal{A}, \alpha)$ represents independencies of a BN, for instance, PDG inference amounts to *qualitative* inference. Can we do inference more efficiently, or for larger values of γ? Given the long history of improvements to Bayesian network inference algorithms, we are optimistic that we can.

ACKNOWLEDGEMENTS

References

Akshay Agrawal, Robin Verschueren, Steven Diamond, and Stephen Boyd. A rewriting system for convex optimization problems. *Journal of Control and Decision*, 5(1): 42–60, 2018.

MOSEK ApS. *MOSEK Optimizer API for Python 10.0.25*, 2022. URL https://docs.mosek.com/10.0/pythonapi/index.html.

Riley Badenbroek and Joachim Dahl. An algorithm for nonsymmetric conic optimization inspired by mosek. *Optimization Methods and Software*, pages 1–38, 2021.

Hans L Bodlaender. A linear time algorithm for finding tree-decompositions of small treewidth. In *Proceedings of the twenty-fifth annual ACM symposium on Theory of computing*, pages 226–234, 1993.

Venkat Chandrasekaran, Nathan Srebro, and Prahladh Harsha. Complexity of inference in graphical models. *arXiv preprint arXiv:1206.3240*, 2012.

Yoeng-Jin Chu. On the shortest arborescence of a directed graph. *Scientia Sinica*, 14:1396–1400, 1965.

Bruno Courcelle. The monadic second-order logic of graphs. i. recognizable sets of finite graphs. *Information and Computation*, 85(1):12–75, 1990. ISSN 0890-5401. doi: https://doi.org/10.1016/0890-5401(90)90043-H. URL https://www.sciencedirect.com/science/article/pii/089054019090043H.

Joachim Dahl and Erling D Andersen. A primal-dual interior-point algorithm for nonsymmetric exponential-cone optimization. *Mathematical Programming*, 194(1): 341–370, 2022.

Steven Diamond and Stephen Boyd. CVXPY: A Python-embedded modeling language for convex optimization. *Journal of Machine Learning Research*, 17(83):1–5, 2016.

Alexander Domahidi, Eric Chu, and Stephen Boyd. Ecos: An socp solver for embedded systems. In *2013 European Control Conference (ECC)*, pages 3071–3076, 2013. doi: 10.23919/ECC.2013.6669541.

Ran Duan, Hongxun Wu, and Renfei Zhou. Faster matrix multiplication via asymmetric hashing. *arXiv preprint*, 2022. doi: 10.48550/ARXIV.2210.10173. URL https://arxiv.org/abs/2210.10173.

Roger Fletcher. *Practical methods of optimization*. John Wiley & Sons, 2013.

Michael Charles Grant. *Disciplined Convex Programming*. PhD thesis, Stanfor University, December 2004. URL https://web.stanford.edu/~boyd/papers/pdf/mcg_thesis.pdf.

Joseph Y Halpern. *Reasoning About Uncertainty*. MIT press, 2017.

Edwin T Jaynes. Information theory and statistical mechanics. *Physical review*, 106(4):620, 1957.

Narendra Karmarkar. A new polynomial-time algorithm for linear programming. In *Proceedings of the Sixteenth Annual ACM Symposium on Theory of Computing*, pages 302–311, 1984.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *Proceedings of the International Conference on Learning Representations (ICLR)*, 2014.

Daphne Koller and Nir Friedman. *Probabilistic Graphical Models: Principles and Techniques*. MIT press, 2009.

David J. C. MacKay. *Information Theory, Inference and Learning Algorithms*. Cambridge University Press, 2003.

Yu E Nesterov, Michael J Todd, and Yinyu Ye. Infeasible-start primal-dual methods and infeasibility detectors for nonlinear programming problems. Technical report, 1999.

Yurii Nesterov and Arkadii Nemirovskii. *Interior-Point Polynomial Algorithms in Convex Programming*. SIAM, 1994.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Köpf, Edward Yang, Zach DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library, 2019. URL https://arxiv.org/abs/1912.01703.

Oliver E Richardson. Loss as the inconsistency of a probabilistic dependency graph: Choose your model, not your loss function. *AISTATS '22*, 151, 2022.

Oliver E Richardson and Joseph Y Halpern. Probabilistic dependency graphs. *AAAI '21*, 2021.

Anders Skajaa and Yinyu Ye. A homogeneous interior-point algorithm for nonsymmetric convex conic optimization. *Mathematical Programming*, 150(2):391–422, 2015.

Martin J Wainwright, Michael I Jordan, et al. Graphical models, exponential families, and variational inference. *Foundations and Trends in Machine Learning*, 1(1–2): 1–305, 2008.

Alan L Yuille and Anand Rangarajan. The concave-convex procedure. *Neural computation*, 15(4):915–936, 2003.