CROSS-TRAJECTORY REPRESENTATION LEARNING FOR ZERO-SHOT GENERALIZATION IN RL

ABSTRACT

A highly desirable property of a reinforcement learning (RL) agent – and a major difficulty for deep RL approaches – is the ability to generalize policies learned on a few tasks over a high-dimensional observation space to similar tasks not seen during training. Many promising approaches to this challenge consider RL as a process of training two functions simultaneously: a complex nonlinear *encoder* that maps high-dimensional observations to a latent *representation* space, and a simple linear *policy* over this space. We posit that a superior encoder for zero-shot generalization in RL can be trained by using solely an auxiliary SSL objective if the training process encourages the encoder to map *behaviorally similar* observations to similar representations, as reward-based signal can cause overfitting in the encoder Raileanu and Fergus (2021). We propose Cross Trajectory Representation Learning (CTRL), a method that runs within an RL agent and conditions its encoder to recognize behavioral similarity in observations by applying a novel SSL objective to pairs of trajectories from the agent's policies. CTRL can be viewed as having the same effect as inducing a pseudo-bisimulation metric but, crucially, avoids the use of rewards and associated overfitting risks. Our experiments ablate various components of CTRL and demonstrate that in combination with PPO it achieves better generalization performance on the challenging Procgen benchmark suite Cobbe et al. (2020a).

1 INTRODUCTION

Deep reinforcement learning (RL) has emerged as a powerful tool for building decision-making agents for domains with high-dimensional observation spaces, such as video games (Mnih et al., 2015), robotic manipulation (Levine et al., 2016), and autonomous driving Kendall et al. (2019). However, while deep RL agents may excel at the specific task variations they are trained on, learning behaviors that generalize across a large family of similar tasks, such as handling a variety of objects with a robotic manipulator, driving under a variety of conditions, or coping with different levels in a game, remains a challenge. This problem is especially acute in zero-shot generalization (ZSG) settings, where only a few sequential tasks are available to learn policies that are meant to perform well on different yet related tasks without further parameter adaptation. This problem setting highlights the fact that generalization often cannot be solved by more training, as it can be too expensive or impossible to instantiate all possible real-world deployment scenarios a-priori.

In this work, we aim to improve ZSG in RL by proposing a new way of training the agent's *representation*, a low-dimensional summary of information relevant to decision-making extracted from the agent's high-dimensional observations. Outside of RL, representation learning can help with ZSG, e.g. using unsupervised learning to obtain a representation that readily transfers to unseen classes in vision tasks (Bucher et al., 2017; Sylvain et al., 2020; Wu et al., 2020). In RL, unsupervised representation learning in the form of auxiliary objectives can be used to provide a richer learning signal over learning from reward alone, which helps the agent avoid overfitting on task-specific information (Raileanu and Fergus, 2021). However, to our knowledge, no unsupervised learning method used in this way in RL has thus far been shown to substantially improve performance in ZSG over end-to-end reward-based methods (e.g., Cobbe et al., 2020a).

We posit that using unsupervised (reward-free) learning to find representations that capture behavioral similarity across different trajectories will improve ZSG in RL. We note that the bisimulation

framework (Ferns et al., 2004) does this directly with rewards, optimizing an agent to treat states as behaviorally similar based on the expected reward, and this has been shown to help in visual generalization settings (Zhang et al., 2021). We expand on this framework to improve ZSG performance, using unsupervised learning to train an agent that recognizes behavior similarity in a reward-free fashion. To do so, we propose *Cross Trajectory Representation Learning (CTRL)*, which applies a novel self-supervised learning (SSL) objective to pairs of trajectories drawn from the agent's policies. For optimization, CTRL defines a prediction objective across trajectory representations from nearby partitions defined by an online clustering algorithm. The end result is an agent whose encoder maps behaviorally similar trajectories to similar representations without directly referencing reward, which we show improves ZSG performance over using pure RL or RL in conjunction with other unsupervised or SSL methods.

Our main contributions are as follows:

- We introduce Cross Trajectory Representation Learning (CTRL), a novel SSL algorithm for RL that defines an auxiliary objective across trajectories in order to capture the notion of *behavioral similarity* in the representations of the agent's belief states. CTRL's approach is two-fold: (i) it uses a clustering loss to group representations of behaviorally similar trajectories and (ii) boosts cross-predictivity between trajectory representations from nearby clusters.

- We empirically show that CTRL improves zero-shot generalization in the challenging Procgen benchmark suite (Cobbe et al., 2020a). Through a series of ablations, we highlight the importance of cross-trajectory views in boosting behavioral similarity.

- We connect CTRL to the class of bisimulation methods, and provide sufficient conditions under which both formalisms can be equivalent.

2 BACKGROUND, MOTIVATION, AND RELATED WORKS

There are a broad class of ZSG settings in RL, such as generalization across reward functions (Barreto et al., 2016; Touati and Ollivier, 2021; Misra et al., 2020), observation spaces (Zhang et al., 2021; Li et al., 2021; Raileanu and Fergus, 2021), or task dynamics (Rakelly et al., 2019). For each of these settings, there are a number of promising directions for improving ZSG performance: giving the agent better exploration policies (Van Roy and Wen, 2016; Misra et al., 2020; Agarwal et al., 2020), meta learning (Oh et al., 2017; Gupta et al., 2018; Rakelly et al., 2019), or planning (Sohn et al., 2018). In this work, we focus on directly improving the agent's *representations*. The agent's representations are high-level abstractions of observations or trajectories from the environment (e.g., the output of an encoder), and the desired property here is that one can easily learn a policy on top of that representation such that the combined model (i.e., the agent) generalizes to novel situations. The tasks are assumed to share a common high-level goal and are set in environments that have the same dynamics, but each task may need to be accomplished under different initial conditions and may differ visually. As the policy is built upon the agent's representations, this motivates the focus of this work for improving generalization: unless the agent's representations generalize well, one cannot expect its policy to readily do so.

Unsupervised representation learning has been shown to improve generalization across domains, including zero-shot in vision (Sylvain et al., 2020; Wu et al., 2020) and sample-efficiency in RL (Eysenbach et al., 2019; Schwarzer et al., 2021; Stooke et al., 2020). In RL, unsupervised objectives can be used as an *auxiliary objective* (or auxiliary task, Jaderberg et al., 2017), which provide an alternative signal to reward-based learning signal. Due to the potential role the RL loss may play in overfitting (Raileanu and Fergus, 2021), we believe that having a learning objective for agent's representation that is separate from that of its policy is crucial for good ZSG performance.

Self-supervised learning and reinforcement learning. A successful class of models that incorporate unsupervised objectives to improve RL use self-supervised learning (SSL) (Anand et al., 2019; Srinivas et al., 2020; Mazoure et al., 2020; Schwarzer et al., 2021; Stooke et al., 2020). SSL formulates objectives by generating different *views* of the data, which are essentially transformed versions of the data, e.g., generated by using data augmentation or by sampling patches. While successful in their own way, prior works that combine SSL with RL do so by applying known

SSL algorithms (e.g., from vision, Hjelm et al., 2018; van den Oord et al., 2019; Bachman et al., 2019; Chen et al., 2020; He et al., 2020; Grill et al., 2020) to RL in a nearly off-the-shelf manner, predicting state representations *within* a given trajectory, only potentially using other trajectories as counterexamples in a contrastive loss. As such, these models provide no guarantees on generalization across RL tasks, potentially limiting their utility to ZSG.

Bisimulation metrics in reinforcement learning. Our hypothesis is that ZSG is achievable if the agent recognizes behavioral similarity between trajectories based on their long-term evolution. Learning this sort of behavior similarity is a central characteristic of bisimulation metrics (Ferns et al., 2004), which assign a value of 0 to states which are behaviorally indistinguishable and have the same reward. Reward-based bisimulation metrics have been shown to learn representations that have a number of useful properties, e.g.: smoothness (Gelada et al., 2019), visual invariance (Zhang et al., 2021), action equivariance (van der Pol et al., 2020) and multi-task adaptation (Zhang et al., 2020). For ZSG however, encoding relational information based on reward may not actually help (Misra et al., 2020; Touati and Ollivier, 2021; Yang and Nachum, 2021; Agarwal et al., 2021), as the agent may overfit to spurious correlations between high-dimensional observations and the reward signal seen during training. HOMER (Misra et al., 2020) expands on the concept of bisimulation to learn behavioral similarity between states using unsupervised exploration at deployment. Among the existing methods, PSE's (Agarwal et al., 2021) reward-free notion of behavioral similarity is conceptually the closest to CTRL's, and we compare these algorithms empirically in Section 6. However, algorithmically and in terms of their modes of operation, CTRL and PSE are very different. PSE assumes the availability of expert policies for training tasks and learns a representation using trajectories from these experts and an action distance measure, which it also assumes to be provided. CTRL doesn't make these assumptions and learns a representation online from trajectories simultaneously generated by its substrate RL algorithm.

Mining views across unsupervised clusters. Given our hypothesis that a model that learns behavioral similarities using signal other than reward will perform well on ZSG, there are still many potential models available to learn said similarities in an unsupervised way. A simple and natural choice is to collect agent trajectories as examples of behaviors, then do clustering (online, similar to Asano et al., 2020; Caron et al., 2020) over trajectories. In RL, Proto-RL (Yarats et al., 2021) also uses clustering to obtain a pre-trained set of prototypical states, but for a different purpose – to estimate state visitation entropy in hard exploration problems. However, clustering alone may not be sufficient to recognize behaviors necessary for ZSG, as representations built on clustering only need to partition behaviors, which may bias the model towards similarities evident training experience. This would be counter-productive for our generalization goal. We therefore use a second objective built on top of the structure provided by clustering to learn a more diverse set of similarities. Drawing inspiration from Mine Your Own View (MYOW, Azabou et al., 2021), CTRL selects (*mines*) representational nearest neighbors from different, nearby clusters and applies a predictive SSL objective to them. This cross-cluster objective encourages CTRL to recognize a larger set of similarities than would be necessary to cluster on the training set, which we show improves ZSG performance.

3 PROBLEM STATEMENT AND PRELIMINARIES

Formally, we define our problem setting w.r.t. a discrete-time Markov decision process (MDP) $M \triangleq \langle \mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R} \rangle$, where $\mathcal{S}$ is a state space, $\mathcal{A}$ is an action space, $\mathcal{P} : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \rightarrow [0, 1]$ is a transition function characterizing environment dynamics, and $\mathcal{R} : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$ is a reward function. M's state and action spaces may be discrete or continuous, but in the rest of the paper we assume them to be discrete to simplify exposition. In practice, an agent usually receives observations but not the full information about the environment's current state. Consider an observation space $\mathcal{O}$ and an observation function $\mathcal{Z} : \mathcal{S} \times \mathcal{O} \rightarrow [0, 1]$ that define what observations an agent may receive and how these observations are generated (possibly stochastically) from M's states. We define a *task* T as a partially observable MDP (POMDP) $T = \langle \mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R}, \mathcal{O}, \mathcal{Z}, s_0 \rangle$, where $s_0 \in \mathcal{S}$ is an initial state. Although many RL agents make decisions in a POMDP based only on the current observation o_t or at most a few recent ones, in general this may require using information from the entire observation history $o_1, \dots, o_t$ so far. Denoting the space of such histories as $\mathcal{H}$, computing an agent's behavior for task T amounts to finding a policy $\pi : \mathcal{H} \times \mathcal{A} \rightarrow [0, 1]$ with the optimal or near-optimal expected return from the initial state $V_T^\pi \triangleq \mathbb{E}\left[\sum_{t=0}^{\infty} \gamma^t \mathcal{R}(S_t, \pi(H_t)) \mid S_0 = s_0\right]$, where

S_t and H_t are random variables for the POMDP's underlying state and agent's observation history at time step t, respectively, and γ is a discount factor. For an MDP $M = \langle \mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R} \rangle$, a set $\mathcal{O}$ of observation spaces, and a set $\mathcal{Z}$ of observation functions w.r.t. $\mathcal{S}$, let a *task family* be the POMDPs set $\mathcal{T}_{M,\mathcal{O},\mathcal{Z}} \triangleq \{\langle \mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R}, \mathcal{O}, \mathcal{Z}, s_0 \rangle\}_{\mathcal{O} \in \mathcal{O}, \mathcal{Z} \in \mathcal{Z}, s_0 \in \mathcal{S}}$. We assume that different observation spaces in $\mathcal{O}$ have the same mathematical form, e.g., pixel tensors representing possible camera images, but correspond to qualitatively distinct subspaces of this larger space, such as subspaces of images depicting brightly and dimly lit scenes.

Our training and evaluation protocol is formalized w.r.t. a *task distribution* $d(\mathcal{T}_{M,\mathcal{O},\mathcal{Z}}) \triangleq P(\mathcal{O}, \mathcal{Z}, \mathcal{S})$ *over task family* $\mathcal{T}_{M,\mathcal{O},\mathcal{Z}}$, where $P(\mathcal{O}, \mathcal{Z}, \mathcal{S})$ is a joint probability mass over observation spaces, observation functions, and initial states. In the rest of the paper, M, $\mathcal{O}$, and $\mathcal{Z}$ will be clear from context, and we will denote the task family as $\mathcal{T}$ and the task distribution as $d(\mathcal{T})$. For agent training, we choose N tasks from $\mathcal{T}$, and denote the distribution $d(\mathcal{T})$ restricted to these N tasks as $d(\mathcal{T}_N)$. During the training phase, the RL agent learns via a series of epochs (themselves composed of episodes), by sampling a task from $d(\mathcal{T})$ independently at the start of each episode, until the total number of time steps exceeds its training budget. In each epoch, an RL algorithm uses a batch of trajectories gathered from episodes in order to compute gradients of an RL objective and update the parameters of the agent's policy π. In representation learning-aided RL, a policy is viewed as a composition $\pi = \theta \circ \phi$ of an *encoder* $\phi : \mathcal{H} \to \mathcal{E}$ and a *policy head* $\theta : \mathcal{E} \times \mathcal{A} \to [0, 1]$, both of which are the outputs of the training phase. The training phase is followed by an evaluation phase, during which the policy is applied to tasks sampled from $d(\mathcal{T} \setminus \mathcal{T}_N)$, distribution d restricted to the set of tasks $\mathcal{T} \setminus \mathcal{T}_N$ not seen during training. *Our focus on generalization means that we seek a policy* π *whose encoder* ϕ *allows it to maximize* $\mathbb{E}_{T \sim d(\mathcal{T} \setminus \mathcal{T}_N)}[V_T^\pi]$ *despite being trained only on distribution* $d(\mathcal{T}_N)$.

4 ALGORITHM

CTRL's key conceptual insight is that capturing reward-agnostic behavioral similarity improves ZSG, because it enables ϕ to correctly associate previously unseen observation histories with those for which the agent's RL-trained behavior prescribes a good action. CTRL runs synchronously with an online RL algorithm, which is crucial to ensure that as the agent's policies improve, so does the notion of behavioral similarity induced by CTRL.

Like most online RL methods themselves, our algorithm operates in epochs, learning from a batch of trajectories in each epoch. CTRL assumes that all trajectories within each of its training batches come from the same policy. Before the RL algorithm updates the policy head in a given epoch, CTRL uses a trajectory batch from the current policy to update the encoder with gradients of a novel auxiliary loss $\mathcal{L}_{\text{CTRL}}$ that we describe in this section.

4.1 INTUITION AND HIGH-LEVEL DESCRIPTION

Algorithm overview. For each trajectory batch, CTRL performs 4 operations:

1. Apply the observation history (belief state) encoder ϕ to generate a low-dimensional reward-agnostic representation ("view") of each trajectory.

2. Group trajectories' views into C sets (C is a tunable hyperparameter) using an online clustering algorithm with loss $\mathcal{L}_{\text{clust}}$ (Equation (5), Section 4.2).

3. Using trajectory pairs selected from neighboring clusters, apply a predictive loss $\mathcal{L}_{\text{pred}}$ (Equation (7), Section 4.2) to encourage ϕ to capture cross-cluster behavioral similarities.

4. Update ϕ with gradients of the total loss:

$$\mathcal{L}_{\text{CTRL}} = \mathcal{L}_{\text{clust}} + \mathcal{L}_{\text{pred}} \tag{1}$$

The schema in Figure 1 provides a high-level outline of these steps' implementation and explains their interplay within CTRL, accompanied by an intuition for each step (below) a more detailed description in Section 4.2. We conduct ablations to show the effect of removing the clustering and predictive objectives of CTRL, with details in Appendix 7.3.

Figure 1: Schematic view of CTRL's key steps for every trajectory batch. **(i) Generating trajectory views** *(top left)*. For each trajectory in a batch, CTRL samples a subsequence of its time steps, computes belief-state/action embeddings u_{t_i} with encoder ϕ, and concatenates them into a trajectory representation (view) $\mathbf{u}$. **(ii) Clustering trajectory views** *(bottom right)*. CTRL uses the online Sinkhorn-Knopp clustering procedure (Caron et al., 2020): for each trajectory view u, it produces two new views $\mathbf{v}$ and $\mathbf{w}$ soft-clusters $\mathbf{v}$'s and $\mathbf{w}$'s, and uses a measure of consistency between these two clusterings as a loss $\mathcal{L}_{\text{clust}}$. **(iii) Encouraging cross-cluster behavioral similarity** *(bottom left)*. After computing trajectory view clusters, CTRL applies a variant of MYOW (Azabou et al., 2021) to them. Namely, it repeatedly samples a trajectory view $\mathbf{v}'$, computes a new view $\mathbf{w}'$ for it, and computes a loss $\mathcal{L}_{\text{pred}}$ that penalizes differences between $\mathbf{w}'$ and views $\mathbf{v}'_{\mathbf{c_i}}$ of randomly chosen trajectories from $\mathbf{v}'$'s neighboring clusters. Encoder ϕ and auxiliary predictors used by CTRL are then updated using $\mathcal{L}_{\text{CTRL}} = \mathcal{L}_{\text{clust}} + \mathcal{L}_{\text{pred}}$'s gradients. The RL loss's gradients are stopped from flowing through encoder ϕ and don't affect it *(top right)*.

Clustering. C clusters can be viewed as corresponding to C latent "situations" in which an RL agent may find itself. Each situation is essentially a group of belief states. CTRL's implicit hypothesis is that a given policy should behave roughly similarly across all belief states corresponding to the same "situation", i.e., generalize across similar belief states. Under this hypothesis, an agent's policy can be expected to produce C sets of roughly similar trajectories. CTRL's clustering step (#2 above) is an attempt to recover these trajectory sets. Since each trajectory consists of belief states, the purpose of $\mathcal{L}_{\text{clust}}$ is to force the encoder ϕ to compute belief state representations that make trajectories within each cluster look similar in the latent space.

Since we would like to evolve clustering online as new trajectory batches arrive, we employ a common online clustering algorithm, the Sinkhorn-Knopp procedure (Caron et al., 2020), which has been used as an auxiliary RL loss (e.g., Proto-RL, Yarats et al., 2021).

Cross-cluster prediction. Note, however, that the clustering loss emphasizes the recognition of behavioral similarities *within* clusters. This may hurt generalization, as the resulting centroids may not faithfully represent behaviors encountered at test time. Our hypothesis is that encouraging encoder ϕ to induce latent-space similarities between trajectories from *different but adjacent* clusters will increase its ability to recognize behaviors in unseen test trajectories.

While there are several ways to encourage cross-cluster representational similarity, using a mechanism similar to MYOW (Azabou et al., 2021) on trajectories drawn from neighboring clusters captures this idea particularly well. Namely, to get the cross-predictive loss $\mathcal{L}_{\text{pred}}$, we sample trajectory view pairs from neighboring clusters and apply the cosine-similarity loss to those pairs.

Using reward guidance without reward signal for representation learning. CTRL trains encoder ϕ only using the gradients of $\mathcal{L}_{\text{CTRL}}$; the RL algorithm's loss $\mathcal{L}_{\text{RL}}$ trains only the policy head. Thus, encoder ϕ is isolated from the previously observed dangers of overfitting to the reward function Raileanu and Fergus (2021) that shapes $\mathcal{L}_{\text{RL}}$. However, we emphasize that CTRL's representation learning is nonetheless very much guided by the reward function, although indirectly: the training

batches of belief state and action trajectories are still collected from policies learned by the policy head via $\mathcal{L}_{\text{RL}}$'s gradients, which are reward-dependent.

4.2 DETAILS

Below we describe the details of each of CTRL's steps, with CTRL's pseudocode presented in Algorithm 1 in Appendix 7.1. While in general the agent's belief state at step t of a trajectory is the entire observation history $h_t = (o_1, \ldots, o_t)$, in the rest of the section we will assume $h_t = (o_t)$ and, in a slight abuse of notation, use $\phi(o_t)$ instead of $\phi(h_t)$ to simplify explanations[1]. We emphasize, however, that CTRL equally applies in settings where the agent uses a much longer history of observations as its state.

We note that in our CTRL implementation, the high-level algorithmic choices for clustering and cross-cluster prediction – Sinkhorn-Knopp and MYOW, respectively, were borrowed from preexisting works.

Generating low-dimensional trajectory views with encoder ϕ. CTRL's input in each epoch is a trajectory batch $\{traj_i\}_{i=1}^{B}$ of size B. Assume all trajectories in the batch have the same length L. For an integer hyperparameter $T \leq L$, for each trajectory $traj_i = (o_0, a_0, r_0, \ldots o_{T_b}, a_L, r_L)$ we independently and uniformly sample a subset of its steps $\tau_i = t_1, \ldots, t_T$ to form a subtrajectory $(o_{t_1}, a_{t_1}, r_{t_1}, \ldots o_{t_T}, a_{t_T}, r_{t_T})$. We then encode this subtrajectory as

$$\boldsymbol{u}_i^{(\tau_i)} = (FiLM(\phi(o_{t_1}), a_{t_1}), .., FiLM(\phi(o_{t_T}), a_{t_T})), \tag{2}$$

where $FiLM(\phi(o_{t_j}), a_{t_j})$ is a common way of combining representations of different objects, akin to conditioning Perez et al. (2018), and the resulting vector $\boldsymbol{u}_i^{(\tau_i)}$ is in a low-dimensional space $\mathcal{U}$. Note two aspects of the process of generating these vectors: (1) it drops rewards from the original trajectory and (2) it critically relies on ϕ whose parameter values are learned from previous epochs. Vectors $\boldsymbol{u}_i^{(\tau_i)}$ produced in this way are the trajectory views that the next steps of CTRL operate on.

Clustering trajectory views. CTRL groups trajectories from the epoch's batch by clustering the set of their views $\{\boldsymbol{u}_i^{(\tau_i)}\}_{i=1}^{B}$. Since we would like to evolve clustering online as new trajectory batches arrive, we employ a common online clustering algorithm, the Sinkhorn-Knopp procedure (Caron et al., 2020), which has been used as an auxiliary RL loss (e.g., Proto-RL, Yarats et al., 2021). Since CTRL operates online, Sinkhorn-Knopp is better-suited for the task than other clustering methods.

The clustering branch computes two views of each input $\boldsymbol{u}_i^{(\tau_i)}$ in a cascading fashion: first by passing it through a clustering encoder $\psi_{\text{clust}} : \mathcal{U} \to \mathcal{V}$, e.g. an RNN, to obtain a lower-dimensional view $\boldsymbol{v}_i = \psi_{\text{clust}}(\boldsymbol{u}_i^{(\tau_i)})$, and then by passing $\boldsymbol{v}_i$ through yet another network, an MLP $\theta_{\text{clust}} : \mathcal{V} \to \mathcal{W}$, to produce view $\boldsymbol{w}_i = \theta_{\text{clust}}(\boldsymbol{v}_i)$. The parameters of ψ_{clust} and θ_{clust} are learned through the epochs jointly with ϕ's. Like $\boldsymbol{u}_i^{(\tau_i)}$, each $\boldsymbol{v}_i$ and $\boldsymbol{w}_i$ is a view of trajectory i; the approach then consists in projecting $\boldsymbol{v}_i$'s and $\boldsymbol{w}_i$'s onto centroids of C clusters in two different ways and then computes a clustering loss that enforces consistency between $\boldsymbol{v}_i$'s and $\boldsymbol{w}_i$'s cluster projections.

Specifically, we represent the centroid of each cluster c with a vector $\boldsymbol{e}_c \in \mathcal{V}$, which are stacked into a matrix $\mathbf{E}$. These vectors are additional parameters in the joint optimization problem CTRL solves. They can be regarded as views of C typical behaviors around which the trajectories' views are regrouped. To project trajectory i's $\boldsymbol{v}_i$ views onto behavioral centroids learned from previous trajectory batches, CTRL computes a vector of soft assignments of $\boldsymbol{v}_i$ to each centroid $\boldsymbol{e}_c$:

$$\mathbf{Q}_i = \underset{1 \leq c \leq C}{\text{Softmax}} \left(\frac{\boldsymbol{v}_i^\top \boldsymbol{e}_c}{||\boldsymbol{v}_i||_2 ||\boldsymbol{e}_c||_2} \right) \tag{3}$$

and forms a $B \times C$ matrix $\mathbf{Q}$ whose i-th row is the soft assignment of $\boldsymbol{v}_i$. The resulting assignments may be very unbalanced, with most probability mass assigned to only a few clusters. Applying the Sinkhorn-Knopp algorithm solves this issue by iteratively re-normalizing $\mathbf{Q}$ in order to obtain a more

---

[1]While, in theory, the Procgen suite is indeed a POMDP, most RL algorithms take the most recent observation as the belief state – a simplification which was shown not to hinder ZSG on Procgen (Cobbe et al., 2020a).

equal cluster membership (Cuturi, 2013), where the degree of re-normalization is controlled by a temperature parameter β. The output of this operation is a matrix $\tilde{\mathbf{Q}}$.

For each view $\boldsymbol{w}_i$, the projection of trajectory view $\boldsymbol{v}_i$, CTRL computes the logarithm of its soft cluster assignments:

$$\mathbf{P}_i = \log\left[\underset{1 \leq c \leq C}{\text{Softmax}}(\boldsymbol{w}_i^\top \boldsymbol{e}_c)\right], \tag{4}$$

and treats these vectors as rows of another $B \times C$ matrix $\mathbf{P}$.

Finally, we compute the cross entropy between $\tilde{\mathbf{Q}}$ and $\mathbf{P}$, which measures their inconsistency. This measure is taken as the clustering loss:

$$\mathcal{L}_{\text{clust}} = \text{CrossEntropy}(\tilde{\mathbf{Q}}, \mathbf{P}) \tag{5}$$

Encouraging cross-cluster behavioral similarity. Note, however, that the clustering loss in the above step emphasizes the recognition of behavioral similarities *within* clusters. This may hurt generalization, as the resulting centroids may not faithfully represent behaviors encountered at test time. Our hypothesis is that encouraging encoder ϕ to induce latent-space similarities between trajectories from *different but adjacent* clusters will increase its ability to recognize behaviors in unseen test trajectories.

While there are several ways to encourage cross-cluster representational similarity, using a mechanism similar to MYOW (Azabou et al., 2021) on trajectories drawn from neighboring clusters captures this idea particularly well. Namely, to get the cross-predictive loss $\mathcal{L}_{\text{pred}}$, we sample trajectory view pairs from neighboring clusters and apply the cosine-similarity loss to those pairs.

To implement this idea, we define a measure of cluster proximity via a matrix $\mathbf{D}$ of cosine similarities between cluster centroids: for clusters k and l, $\mathbf{D}_{kl} = ||\boldsymbol{e}_k - \boldsymbol{e}_l||_2^2$ (Grill et al., 2020). Recall that in the previous step, the clustering branch computed a matrix $\mathbf{Q}$ whose rows $\mathbf{Q}_i$ are soft assignments of trajectory i's view $\boldsymbol{v}_i$ to clusters. In this step, we convert these soft assignments to hard ones by associating a trajectory's view $\boldsymbol{v}_i$ with cluster $c_i = \text{argmax}_{1 \leq c' \leq C}\tilde{\mathbf{Q}}_i$ and treating a cluster c as consisting of trajectories with indices in the set $\mathbb{T}_c = \{i \mid c = \text{argmax}_{1 \leq c' \leq C}\tilde{\mathbf{Q}}_i\}$. To assess how predictive a trajectory embedding $\boldsymbol{u}_i$ is of a trajectory embedding $\boldsymbol{u}_j$, like in the clustering step we will use two special helper maps, $\psi_{\text{pred}} : \mathcal{U} \to \mathcal{V}$ to obtain a reduced-dimensionality view $\boldsymbol{v}' = \psi_{\text{pred}}(\boldsymbol{u})$ and θ_{pred} to further project $\boldsymbol{v}'$ to $\boldsymbol{w}' = \theta_{\text{pred}}(\boldsymbol{v}')$.

CTRL proceeds by repeatedly sampling trajectories, which we call *anchor trajectories*, from the batch, with their associated embeddings $\boldsymbol{u}$. For each anchor trajectory n, consider K clusters $c_1, \ldots, c_K$ nearest to n's cluster c_n, as defined by the indices of K largest values in row c_n of matrix $\mathbf{D}$ (we exclude c_n itself when determining c_n's nearest clusters). Borrowing ideas from the MYOW approach Azabou et al. (2021), CTRL mines a view for $\boldsymbol{u}_n$ by randomly choosing a trajectory with embedding $\boldsymbol{u}_{c_k}^{(n)}$ from each of the neighboring clusters and computing its view $\boldsymbol{v}'_{c_k} = \psi_{\text{pred}}(\boldsymbol{u}_{c_k}^{(n)})$. We call the neighbors' views $\boldsymbol{v}'_{c_1}, \ldots, \boldsymbol{v}'_{c_K}$ trajectory n's *mined views*.

For the final operation in this step, CTRL computes trajectory n's predictive view $\boldsymbol{w}'_n = \theta_{\text{pred}}(\psi_{\text{pred}}(\boldsymbol{u}_n))$ and measures the distance from it to trajectory n's mined views:

$$\mathcal{L}_{\text{pred}}^{(n)} = \sum_{k=1}^{K} ||\boldsymbol{w}'_n - \boldsymbol{v}'_{c_k}||_2^2 \tag{6}$$

N is the CTRL's hyperparameter that determines the number of anchor trajectories to be sampled, so the total prediction loss is

$$\mathcal{L}_{\text{pred}} = \sum_{n=1}^{N} \mathcal{L}_{\text{pred}}^{(n)} \tag{7}$$

Updating encoder ϕ using reward guidance without reward signal for representation learning. Note that CTRL's total loss $\mathcal{L}_{\text{CTRL}}$ (Equation (1)) depends on the parameters of encoder ϕ as well as

of clustering networks ϕ_{clust} and θ_{clust}, prediction networks ϕ_{clust} and θ_{clust}, and cluster centroids $\boldsymbol{e}_c$, $1 \leq c \leq C$. In each epoch, CTRL updates all these parameters to minimize $\mathcal{L}_{\text{CTRL}}$.

5 CONNECTION TO BISIMULATION

Deep bisimulation metrics are tightly connected to the underlying mechanism of mining behaviorally similar trajectories of CTRL. They operate on a latent-dimensional space and, as is the case for DeepMDP (Gelada et al., 2019) and DBC (Zhang et al., 2021), ensure that bisimilar states (i.e. behaviorally similar states with identical reward) are located close to each other in that latent space. In this section, we aim to highlight a functional similarity between bisimulation metrics and CTRL.

Definition 1 *A bisimulation relation $E \subseteq \mathcal{S} \times \mathcal{S}$ is a binary relation which satisfies, $\forall (s,t) \in E$:*

1. $\forall a \in \mathcal{A}, \mathcal{R}(s,a) = \mathcal{R}(t,a)$

2. $\forall a \in \mathcal{A}, \forall c \in \mathcal{S}, \sum_{s' \in c} \mathcal{P}(s,a)(s') = \sum_{s' \in c} \mathcal{P}(t,a)(s')$

In practice, rewards and transition probabilities rarely match exactly. For this reason, (Ferns et al., 2004) proposed a smooth alternative to bisimulation relations in the form of bisimulation metrics, which can be found by solving a recursive equation involving the Wasserstein-1 distance $\mathcal{W}_1$ between transition probabilities. W_1 can be found by solving the following linear programming (Villani, 2008), where we let $\Gamma = \{\boldsymbol{v} \in \mathbb{R}^{|\mathcal{V}|} : 0 \leq \boldsymbol{v}_i \leq 1 \, \forall 1 \leq i \leq |\mathcal{V}|\}$:

$$\mathcal{W}_1^d(P||Q) := \max_{\mu \in \Gamma} \sum_{s \in \mathcal{S}} (P(s) - Q(s))\mu(s) \quad \text{s.t. } \mu(s) - \mu(s') < d(s,s') \forall s,s' \in \mathcal{S}, \tag{8}$$

where μ is a vector whose elements are constrained between 0 and 1. In practice, bisimulation metrics are used to enforce a temporal continuity of the latent space by minimization of the $\mathcal{W}_1$ loss between training state-action pairs. Therefore, to show a connection of CTRL to (reward-free) bisimulation metrics, it is sufficient to show that two trajectories are mapped to the same partition *if* their induced $\mathcal{W}_1$ distance is arbitrarily small. In our (informal) argument that follows, we assume that CTRL samples two consecutive timesteps and encodes them into $\boldsymbol{v}$; the exact form of $\boldsymbol{v}$ dictates the nature of the behavioral similarity.

Proposition 1 *(Informal) Let M be an MDP where $\mathcal{R}(s,a) = 0$ for all $(s,a) \in \mathcal{S} \times \mathcal{A}$ and let $\boldsymbol{v}, \boldsymbol{v}' \in \mathcal{V}$ be two dynamics embeddings in M. The clustering operation between $\boldsymbol{v}, \boldsymbol{v}'$ induces a reward-free bisimilarity metric $\mathcal{W}_1(\mathbb{P}[\boldsymbol{v}], \mathbb{P}[\boldsymbol{v}'])$ between induced distributions $\mathbb{P}[\boldsymbol{v}]$ and $\mathbb{P}[\boldsymbol{v}']$.*

The proof can be found in Appendix 7.7.

6 EMPIRICAL EVALUATION

We compare CTRL against strong RL baselines: DAAC (Raileanu and Fergus, 2021) – the current state-of-the-art on the challenging generalization benchmark suite *Procgen* (Cobbe et al., 2020a), and PPO (Schulman et al., 2017). DAAC optimizes the PPO loss (Schulman et al., 2017) through decoupling the training of the policy and value functions, which updates the advantage function during the policy network updates. We then compare to several unsupervised and SSL auxiliary objectives used in conjunction with PPO. DIAYN (Eysenbach et al., 2019) is an unsupervised skill-based exploration method which we adapt to the online setting by uniformly sampling skills. Its notion of skills has some similarities to the notion of clusters in CTRL. We also compare with two SSL-based auxiliary objectives: CURL (Srinivas et al., 2020), a common SSL baseline which contrasts augmented instances of the same state, and Proto-RL (Yarats et al., 2021), which we adapt for this generalization setting. Finally, we provide a comparison against bisimulation-based algorithms: DBC (Zhang et al., 2021), which was shown to perform well on robotic control tasks with visual distractor features, and PSE (Agarwal et al., 2021). PSE assumes policies for training tasks to be given and, like Agarwal et al. (2021), we ran it both with random and high-quality policies pretrained with extra computation budget. See Appendix 7.2 for details.

The Procgen benchmark suite, which we use in our experiments, consists of 16 video games (see Table 1). Procgen procedurally generates distinct levels for each game. The number of levels for each

game is virtually unlimited. Levels within a game which share common game rules and objectives but differ in level design such as the number of projectiles, background colors, item placements throughout the level and other game assets. The dynamics and rewards from a given Procgen level are shared with all other levels, while its observation space and the initial underlying state s_0 (about which the agent has no direct knowledge) is distinct. Moreover, the subspaces of the underlying state space $\mathcal{S}$ that can be visited from s_0's of different levels are largely disjoint. All of this makes Procgen a suitable benchmark for zero-shot generalization. Using our notation from Section 3, for each of 16 games, we train on a uniform distribution $d(\mathcal{T}_N)$ over $N = 200$ "easy" levels of the game and evaluate on $d(\mathcal{T} \setminus \mathcal{T}_N)$, i.e., a uniform distribution over the game's "easy" levels not seen during training. Following (Mohanty et al., 2021), we report results after 8M steps of training.

6.1 MAIN RESULTS

	RL		RL+Bisim.			RL+Unsup.	RL+SSL		Ours
Env	PPO	DAAC	PPO+DBC	PPO+PSE (random)	PPO+PSE (pretrained)	PPO+DIAYN	Proto-RL	PPO+CURL	**CTRL**
bigfish	2.3±0.1	4.3±0.3	1.8±0.1	2.3 ± 0.1	1.8 ± 0.2	2.2±0.1	2.4±0.1	2.2±0.2	**4.7±0.2**
bossfight	5.2±0.3	1.7±0.7	5±0.1	0.9 ± 0.2	0.7 ± 0.1	1.1±0.2	6.1±0.5	4.6±0.8	**8.2±0.1**
caveflyer	4.4±0.3	4.3±0.1	3.6±0.1	2.6 ± 0.1	3.6 ± 0.3	1.0±1.9	**4.7±0.1**	4.6±0.3	**4.7±0.2**
chaser	7.2±0.2	7.1±0.1	4.8±0.1	**8.7 ± 0.5**	4.2 ± 0.2	5.6±0.5	7.6±0.2	7.2±0.2	7.1±0.2
climber	5.1±0.1	5.5±0.2	4.1±0.4	2.9 ± 0.1	3.9 ± 0.2	0.8±0.7	5.5±0.3	5.5±0.1	**5.9±0.2**
coinrun	8.3±0.2	8.1±0.1	7.9±0.1	5.5 ± 0.5	7.3 ± 0.2	6.4±2.6	8.2±0.1	8.1±0.1	**8.7±0.3**
dodgeball	1.3±0.1	**1.8±0.2**	1.0±0.3	1.6 ± 0.1	1.3 ± 0.1	1.4±0.2	1.6±0.1	1.4±0.1	**1.8±0.1**
fruitbot	12.4±0.2	11.5±0.3	7.6±0.2	1.0 ± 0.1	1.1 ± 0.2	7.2±3.0	12.3±0.4	12.3±0.2	**13.3±0.3**
heist	2.7±0.2	**3.4±0.2**	3.3±0.2	3.1 ± 0.3	2.9 ± 0.4	0.2±0.2	3.0±0.3	2.5±0.1	3.1±0.3
jumper	5.8±0.3	**6.3±0.1**	3.9±0.4	4.1 ± 0.3	5.3 ± 0.2	2.6±2.3	6.0±0.1	5.9±0.1	6.0±0.1
leaper	3.5±0.4	3.5±0.4	2.7±0.1	2.7 ± 0.2	2.6 ± 0.1	2.5±0.2	3.2±0.8	**3.6±0.5**	2.8±0.2
maze	5.4±0.2	5.6±0.2	5.0±0.1	5.4 ± 0.2	5.3 ± 0.1	1.6±1.2	5.5±0.3	5.4±0.1	**5.7±0.1**
miner	8.7±0.3	5.7±0.1	4.8±0.1	5.6 ± 0.1	4.3 ± 0.3	1.3±2.0	8.8±0.5	**8.6±0.2**	6.5±0.2
ninja	5.5±0.2	5.2±0.1	3.5±0.1	3.4 ± 0.2	3.5 ± 0.3	2.8±2.0	5.4±0.3	5.6±0.1	**5.8±0.1**
plunder	6.2±0.4	4.1±0.1	5.1±0.1	4.0 ± 0.1	4.1 ± 0.2	2.1±2.5	6.0±0.9	6.5±0.3	**6.6±0.3**
starpilot	4.7±0.2	4.1±0.2	2.8±0.1	3.2 ± 0.2	3.0 ± 0.1	5.8±0.6	5.2±0.2	5.0±0.1	**7.7±0.5**

Table 1: Average evaluation returns collected after 8M training frames, ± one standard deviation over 10 seeds.

As Table 1 shows, PPO+CTRL outperforms all other baselines, including DAAC, on most games. Notably, bisimulation-based approaches other than CTRL– DBC as well as PSE with both random and expert data-gathering policies – exhibit lower gains than others. While this can be surprising, recent work has seen similar results when applying DBC to tasks with unseen backgrounds (Li et al., 2021). PSE's inferior performance may be due to the policy similarity metric, which PSE requires as input and which we took from Agarwal et al. (2021), being poorly suited to Procgen. This highlights an important difference between CTRL and PSE: CTRL doesn't need a policy similarity metric, since it implicitly induces such a metric automatically based on trajectory "signatures".

Despite training static prototypes for 8M timesteps and adapting the RL head for 8M additional timesteps (see Appendix 7.2 for details), Proto-RL performs worse than CTRL. This suggests that the temporal aspect of clustering is key for ZSG, a hypothesis we explore further in Section 7.4. Likewise, PPO+DIAYN uses its pre-training phase to find a diverse set of skills, which can be useful in robotics domains, but does not help much in the ZSG setting of Procgen. DAAC also exhibits good generalization performance, but inherits from PPG (Cobbe et al., 2020b) the separation of the value and policy branches both parameter-wise and by introducing distinct training phases, an overhead which CTRL manages to avoid.

In addition, we present a toy example demonstrating how learning behavioral similarities captures local perceptual changes (), empirically show that slow clustering convergence leads to better generalization (Section 7.4), and describe a number of ablation studies (Section 7.3).

REPRODUCIBILITY STATEMENT

To ensure reproducibility of our work, we attach the source code to the submission, provide the proof of the theorem in the appendix.

REFERENCES

A. Agarwal, M. Henaff, S. Kakade, and W. Sun. Pc-pg: Policy cover directed exploration for provable policy gradient learning. In *NeurIPS*, 2020.

R. Agarwal, M. C. Machado, P. S. Castro, and M. G. Bellemare. Contrastive behavioral similarity embeddings for generalization in reinforcement learning. In *ICLR*, 2021.

A. Anand, E. Racah, S. Ozair, Y. Bengio, M.-A. Côté, and R. D. Hjelm. Unsupervised state representation learning in atari. In *NeurIPS*, 2019.

Y. M. Asano, C. Rupprecht, and A. Vedaldi. Self-labelling via simultaneous clustering and representation learning. *ICLR*, 2020.

M. Azabou, M. G. Azar, R. Liu, C.-H. Lin, E. C. Johnson, K. Bhaskaran-Nair, M. Dabagia, K. B. Hengen, W. Gray-Roncal, M. Valko, and E. L. Dyer. Mine your own view: Self-supervised learning through across-sample prediction, 2021.

P. Bachman, R. D. Hjelm, and W. Buchwalter. Learning representations by maximizing mutual information across views. In *NeurIPS*, 2019.

A. Barreto, W. Dabney, R. Munos, J. J. Hunt, T. Schaul, H. Van Hasselt, and D. Silver. Successor features for transfer in reinforcement learning. *arXiv preprint arXiv:1606.05312*, 2016.

M. Bucher, S. Herbin, and F. Jurie. Generating visual representations for zero-shot classification. In *Proceedings of the IEEE International Conference on Computer Vision Workshops*, pages 2666–2673, 2017.

M. Caron, I. Misra, J. Mairal, P. Goyal, P. Bojanowski, and A. Joulin. Unsupervised learning of visual features by contrasting cluster assignments. In *NeurIPS*, 2020.

T. Chen, S. Kornblith, M. Norouzi, and G. Hinton. A simple framework for contrastive learning of visual representations. In *ICML*, 2020.

K. Cobbe, C. Hesse, J. Hilton, and J. Schulman. Leveraging procedural generation to benchmark reinforcement learning. In *ICML*, 2020a.

K. Cobbe, J. Hilton, O. Klimov, and J. Schulman. Phasic policy gradient. *arXiv preprint arXiv:2009.04416*, 2020b.

M. Cuturi. Sinkhorn distances: Lightspeed computation of optimal transportation distances. In *NeurIPS*, 2013.

W. Dabney, A. Barreto, M. Rowland, R. Dadashi, J. Quan, M. G. Bellemare, and D. Silver. The value-improvement path: Towards better representations for reinforcement learning. In *AAAI*, 2021.

B. Eysenbach, A. Gupta, J. Ibarz, and S. Levine. Diversity is all you need: Learning skills without a reward function. In *ICLR*, 2019.

N. Ferns, P. Panangaden, and D. Precup. Metrics for finite markov decision processes. In *UAI*, volume 4, pages 162–169, 2004.

C. Gelada, S. Kumar, J. Buckman, O. Nachum, and M. G. Bellemare. Deepmdp: Learning continuous latent space models for representation learning. In *ICML*, pages 2170–2179. PMLR, 2019.

J.-B. Grill, F. Strub, F. Altché, C. Tallec, P. H. Richemond, E. Buchatskaya, C. Doersch, B. A. Pires, Z. D. Guo, M. G. Azar, B. Piot, K. Kavukcuoglu, R. Munos, and M. Valko. Bootstrap your own latent: A new approach to self-supervised learning. In *NeurIPS*, 2020.

A. Gupta, B. Eysenbach, C. Finn, and S. Levine. Unsupervised meta-learning for reinforcement learning. *arXiv preprint arXiv:1806.04640*, 2018.

K. He, H. Fan, Y. Wu, S. Xie, and R. Girshick. Momentum contrast for unsupervised visual representation learning. In *CVPR*, 2020.

R. D. Hjelm, A. Fedorov, S. Lavoie-Marchildon, K. Grewal, P. Bachman, A. Trischler, and Y. Bengio. Learning deep representations by mutual information estimation and maximization. In *ICLR*, 2018.

M. Jaderberg, V. Mnih, W. M. Czarnecki, T. Schaul, J. Z. Leibo, D. Silver, and K. Kavukcuoglu. Reinforcement learning with unsupervised auxiliary tasks. *ICLR*, 2017.

A. Kendall, J. Hawke, D. Janz, P. Mazur, D. Reda, J.-M. Allen, V.-D. Lam, A. Bewley, and A. Shah. Learning to drive in a day. In *ICRA*, 2019.

S. Levine, C. Finn, T. Darrell, and P. Abbeel. End-to-end training of deep visuomotor policies. *Journal of Machine Learning Research*, 17(39):1–40, 2016. URL http://jmlr.org/papers/v17/15-522.html.

B. Li, V. François-Lavet, T. Doan, and J. Pineau. Domain adversarial reinforcement learning. *arXiv preprint arXiv:2102.07097*, 2021.

B. Mazoure, R. T. des Combes, T. Doan, P. Bachman, and R. D. Hjelm. Deep reinforcement and infomax learning. In *NeurIPS*, 2020.

D. Misra, M. Henaff, A. Krishnamurthy, and J. Langford. Kinematic state abstraction and provably efficient rich-observation reinforcement learning. In *International conference on machine learning*, pages 6961–6971. PMLR, 2020.

V. Mnih, K. Kavukcuoglu, D. Silver, A. A. Rusu, J. Veness, M. G. Bellemare, A. Graves, M. Riedmiller, A. K. Fidjeland, G. Ostrovski, S. Petersen, C. Beattie, A. Sadik, I. Antonoglou, H. King, D. Kumaran, D. Wierstra, S. Legg, and D. Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, Feb. 2015. ISSN 00280836. URL http://dx.doi.org/10.1038/nature14236.

S. Mohanty, J. Poonganam, A. Gaidon, A. Kolobov, B. Wulfe, D. Chakraborty, G. Šemetulskis, J. Schapke, J. Kubilius, J. Pašukonis, et al. Measuring sample efficiency and generalization in reinforcement learning benchmarks: Neurips 2020 procgen benchmark. *arXiv preprint arXiv:2103.15332*, 2021.

J. Oh, S. Singh, H. Lee, and P. Kohli. Zero-shot task generalization with multi-task deep reinforcement learning. In *International Conference on Machine Learning*, pages 2661–2670. PMLR, 2017.

E. Perez, F. Strub, H. de Vries, V. Dumoulin, and A. Courville. Film: Visual reasoning with a general conditioning layer. In *AAAI*, 2018.

R. Raileanu and R. Fergus. Decoupling value and policy for generalization in reinforcement learning. In *ICML*, 2021.

K. Rakelly, A. Zhou, C. Finn, S. Levine, and D. Quillen. Efficient off-policy meta-reinforcement learning via probabilistic context variables. In *ICML*, pages 5331–5340. PMLR, 2019.

P. J. Rousseeuw. Silhouettes: a graphical aid to the interpretation and validation of cluster analysis. *Journal of computational and applied mathematics*, 20:53–65, 1987.

J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms, 2017.

M. Schwarzer, A. Anand, R. Goel, R. D. Hjelm, A. Courville, and P. Bachman. Data-efficient reinforcement learning with self-predictive representations. In *ICLR*, 2021.

S. Sohn, J. Oh, and H. Lee. Hierarchical reinforcement learning for zero-shot generalization with subtask dependencies. *arXiv preprint arXiv:1807.07665*, 2018.

A. Srinivas, M. Laskin, and P. Abbeel. Curl: Contrastive unsupervised representations for reinforcement learning. In *ICML*, 2020.

A. Stooke, K. Lee, P. Abbeel, and M. Laskin. Decoupling representation learning from reinforcement learning, 2020.

T. Sylvain, L. Petrini, and D. Hjelm. Locality and compositionality in zero-shot learning. In *ICLR*, 2020.

A. Touati and Y. Ollivier. Learning one representation to optimize all rewards. In *ICLR Self-supervision for Reinforcement Learning Workshop*, 2021.

A. van den Oord, Y. Li, and O. Vinyals. Representation learning with contrastive predictive coding, 2019.

E. van der Pol, T. Kipf, F. A. Oliehoek, and M. Welling. Plannable approximations to mdp homomorphisms: Equivariance under actions, 2020.

B. Van Roy and Z. Wen. Generalization and exploration via randomized value functions. In *ICML*, 2016.

C. Villani. *Optimal transport: old and new*, volume 338. Springer Science & Business Media, 2008.

J. Wu, T. Zhang, Z.-J. Zha, J. Luo, Y. Zhang, and F. Wu. Self-supervised domain-aware generative network for generalized zero-shot learning. In *CVPR*, pages 12767–12776, 2020.

M. Yang and O. Nachum. Representation matters: Offline pretraining for sequential decision making. In *ICLR*, 2021.

D. Yarats, R. Fergus, A. Lazaric, and L. Pinto. Reinforcement learning with prototypical representations. In *ICML*, 2021.

A. Zhang, S. Sodhani, K. Khetarpal, and J. Pineau. Learning robust state abstractions for hidden-parameter block mdps. In *ICLR*, 2020.

A. Zhang, R. McAllister, R. Calandra, Y. Gal, and S. Levine. Learning invariant representations for reinforcement learning without reconstruction. In *ICLR*, 2021.