Contrastive Fine-grained Class Clustering via Generative Adversarial Networks

Abstract

Unsupervisedly clustering fine-grained object images without ground truth annotation is practical yet challenging due to the difficulty of feature learning on subtle object details. We introduce C3-GAN, a method for unsupervised fine-grained class clustering that leverages the categorical inference power of InfoGAN with contrastive learning. We aim to learn feature representations that not only maximize the mutual information between the latent code and its observation, but also encourage the data to form distinct cluster boundaries in the embedding space. Our approach is to represent the auxiliary distribution based on the contrastive loss where the image-latent pairs that maximize mutual information are considered as positive pairs and the rest as negative pairs. With this formulation, C3-GAN directly prevents degenerated solutions by enforcing the cluster centroids to be uniformly distributed. Experiments show that C3-GAN achieved state-of-the-art clustering performances on four fine-grained benchmark datasets, while alleviating mode collapse phenomenon.

1 Introduction

Unsupervised fine-grained class clustering is to semantically group unlabeled images of very similar objects (Benny & Wolf, 2020). This fine-grained class clustering is practical and useful for real-world applications such as e-commerce and image retrieval (Guo et al., 2019; Sun et al., 2018). Compared to conventional clustering on coarse-grained object images, fine-grained class clustering is more challenging because distinction between each cluster is more ambiguous. As shown in Figure 1, the feature vectors of fine-grained object images are more similar to each other than the ones of coarse-grained objects. Fine-grained images are difficult to be large-scale and the subtle changes of color or shape that actually play an important role are considered as noisy factors in multiview-based SSL methods (He et al., 2020; Chen et al., 2020; Grill et al., 2020). Thus, fine-grained clustering is difficult to be benefited from recent SSL methods, which show promising reports in conventional coarse-grained class clustering (Van Gansbeke et al., 2020).

Generative adversarial networks (GAN) (Goodfellow et al., 2014) can be a solution as it is required to learn fine details to generate realistic images. The possible starting point can be InfoGAN (Chen et al., 2016), which has achieved unsupervised categorical inference on MNIST dataset (LeCun et al., 2010) by maximizing mutual information between the latent code and its observation. The only prior knowledge employed was the number of classes and the fact that the data is uniformly distributed over the classes. FineGAN (Singh et al., 2019) modifies InfoGAN to deal with the fine-grained image clustering by integrating the scene decomposition learning into the network architecture. Specifically, FineGAN generates images in a hierarchical manner, which means a background, a superclass object, and a subclass object images are sequentially generated with multiple generators by associating three separated latent codes with each image component. Although FineGAN suggests that the learnt latent codes can be used for clustering images into the fine-grained classes, it requires bounding box annotations and lacks the ability to infer the categories from real images due to the training instability and reduced sample diversity (Higgins et al., 2017).

In this paper, we propose **C**onstrastive fine-grained **C**lass **C**lustering **GAN** (C3-GAN) that deals with the aforementioned problem. Our intuition is that optimal clustering results can be achieved if image features are uniformly distributed on the unit hypersphere and each cluster can be linearly separable (Wang & Isola, 2020). With this idea in our mind, we formulate of the auxiliary probability

(a) Fine-grained Class Clustering   (b) Coarse-grained Class Clustering

Figure 1: **Fine-grained vs. Coarse-grained.** We compare two sets of 4 classes each selected from (a) CUB (Wah et al., 2011) and (b) STL (Coates et al., 2011) datasets. The graphs below photos are the t-SNE visualization of features extracted from ResNet-50 pretrained on ImageNet-1k via SimCLR (Chen et al., 2020).The color of each dot corresponds to an image class. The classes in (a) are much more indistinguishable than those of (b), both in the image-level and the feature-level.

$Q(c|x)$ with the contrastive loss (He et al., 2020). In specific, we define the latent code mapped into the unit hypersphere as the cluster centroid, and optimize the contrastive loss considering the image-latent pairs that maximize mutual information as positive pairs and the rest as negative pairs. In the process of finding the optimal solution, each cluster centroid would pushes the other ones (negative pairs) and pulls the image features that would optimize the information-theoretic regularization (positive pairs). This formulation is also helpful for image synthesis learning, as the generator is required to synthesize images of a certain number of object classes with distinct characteristics. We have conducted experiments on four fine-grained datasets including CUB, Oxford Flower, Stanford Cars and Stanford Dogs and show that C3-GAN achieves state-of-the-art clustering performance on all the datasets. In addition, the synthesized images also imply that the proposed method is effective in alleviating the issue of mode collapse.

Our main contributions are summarized as three folds:

- We propose the novel formulation of information-theoretic regularization using contrastive loss for unsupervised fine-grained feature learning. With the proposed formulation, we directly learn features of the cluster centroids that would lead the data to form discernable cluster boundaries in the embedding space without falling into a degenerated solution.

- By extracting foreground features via scene decomposition, our method achieves the state-of-the-art performance of unsupervised fine-grained class clustering without any human annotations.

- Our model can not only cluster fine-grained object images but also generate various new images with controllability while alleviating the mode collapse issue of GAN.

2   RELATED WORK

Unsupervised Clustering. Unsupervised clustering methods can be mainly categorized into information theory-based and Expectation–Maximization (EM)-based approaches. The first approach aims to maximize mutual information between groups of original images and augmented images in an end-to-end fashion (Ji et al., 2019; Zhong et al., 2020; Caron et al., 2020). IIC (Ji et al., 2019) uses an unlabeled large dataset to improve the quality of feature representations, and DRC (Zhong et al., 2020) reduces the intra-class feature variation by optimizing contrastive loss on logit features. However, these methods might be vulnerable to the biases inherent in data. EM-based methods decouple the cluster assigning process (E-step) and the feature representations learning process (M-step) to learn more robust feature representations. Specifically, the feature representations are learned by not only optimizing particular pretext tasks but also fitting the proto clustering results estimated in the expectation step. It can be inferred by k-means clustering (Xie et al., 2016; Caron et al., 2018; Liu et al., 2020; Li et al., 2021) or optimization of specific regularization terms (Dizaji et al., 2017). However, these methods suffer from the uneven estimation issues of k-means clustering, which could

result in a degenerate solution. SCAN (Van Gansbeke et al., 2020) proposes a novel objective function that doesn't require k-means clustering. It is based on the observation that K nearest neighbors in the embedding space learnt with instance-wise contrastive loss belong to the same ground-truth clusters with the high probability. By training a classifier that assigns identical clusters to all neighbors, SCAN significantly improved the clustering performance. In the prior works, the cluster centroids are not learnt in an end-to-end manner or not the subject of research. C3-GAN jointly learns the cluster centroids with other parts of the model by optimizing the information-theoretic regularization term.

Unsupervised Scene Decomposition. Heavy costs of annotating segmentation masks led to the appearance of many unsupervised scene decomposition methods. Some works address this task in the information-theoretic perspective such as IIC (Ji et al., 2019) and IEM (Savarese et al., 2021). Another line of works are based on GAN including ReDO and PerturbGAN (Chen et al., 2019; Bielski & Favaro, 2019), and they learn to infer a segmentation mask as a side task of learning to generate realistic images. Meanwhile, some works utilized pre-trained high quality GAN models such as StyleGAN (Karras et al., 2019; 2020) and BigGAN (Brock et al., 2019). Labels4Free (Abdal et al., 2021) trains a segmentation network on top of the pre-trained StyleGAN utilizing the fact that inputs of each layer of StyleGAN have different degrees of contribution to foreground synthesis. Voynov & Babenko (2020) and Melas-Kyriazi et al. (2021) explore the latent space of pre-trained GANs to find the perturbing directions that can be used to induce segmentation masks. Voynov & Babenko (2020) automatically finds a specific number of reversible perturbing directions in the latent space of BigGAN and manually defines the characteristics of each direction. With the direction that removes the background, they produce pseudo masks assigning white pixels as background region. Melas-Kyriazi et al. (2021) defines specific functions to find the direction that enhances brightness contrast between foreground and background without changing the object shape, and define a mask based on the difference of brightness between an original image and a perturbed image. All these works require an additional training of mask encoder using pairs of synthesized images and masks, or process of projecting real images into the latent space of a pre-trained GAN. C3-GAN focuses on learning the semantic features of objects in the foreground region employing the method of decomposing the scene into background and foreground parts in an unsupervised manner.

Fine-grained Feature Learning. Some GANs (Singh et al., 2019; Li et al., 2020; Benny & Wolf, 2020) learn the disentangled features of an image to generate an image in a hierarchical manner. In these works, fake image is a composite of background, superclass object, and subclass object images, which are sequentially generated. The networks are trained using information theory so that each image is associated with unsupervisedly found latent codes. To train each code individually, FineGAN (Singh et al., 2019) trains multiple pairs of generator and discriminator, and leverage prior knowledge to impose constraints on each code to have hierarchical relationships. MixNMatch (Li et al., 2020) and OneGAN (Benny & Wolf, 2020) extend FineGAN with an autoencoder structure to predict these codes from real images. In order to avoid a degenerate solution in which one generator is responsible for generating the entire image, which is derived by having an autoencoder structure, MixNMatch conducts adversarial learning on the joint distribution of latent code and image following BiGAN (Donahue et al., 2017), and OneGAN trains the model in two stages, learning the generator first and the encoder next. All of these works succeed in generating images in a hierarchical manner, and suggest further that the learned latent code can be used for clustering images into fine-grained classes. C3-GAN aims to improve the fine-grained class clustering performance by modifying the form of the information-theoretic regularization. By formulating the auxiliary probability with the contrastive loss, we aim to learn the feature representations on the unit hypersphere where clusters are uniformly distributed and linearly separable.

3 METHOD

Given a dataset $X = \{x_i\}_{i=1}^N$ consisting of single object images, we aim to distribute the set X into Y semantically fine-grained clusters. The cluster assignment is made in the feature space $\mathcal{H} \in \mathbb{R}^{d^h}$ of the discriminator D of C3-GAN. The cluster index for each image x_i is inferred based on the cosine distance between the image feature $h_i \in \mathbb{R}^{d^h}$ and the set of cluster centroid features $l \in \mathbb{R}^{Y \times d^h}$, which are the latent codes c mapped into the space. To rephrase it, the index of the closest centroid will be assigned to the query image x_i. C3-GAN is built upon FineGAN (Singh et al., 2019) to extract the object information ignoring the background part, and propose the formulation of the auxiliary

Figure 2: Overview of C-3GAN. The generator synthesizes a background image $\hat{x}^{bg}$ and a foreground image $\hat{x}^{fg}$ separately. The scene decomposition is triggered by perturbing the foreground image with random affine transformation matrix $\mathcal{T}_\theta$ right before the composition. The association between the latent code c and image $\hat{x}$ is found by maximizing mutual information between the two based on their feature distance in the embedding space of the discriminator D. The dotted line represents the point of the real image feature (●), and the cluster assignment is made based on the distance to the embedded latent features (♦) that are considered as the cluster centroids values.

probability $Q(c|x)$ based on contrastive loss with the goal of finding the ideal embedding space $\mathcal{H}$ where each cluster is uniformly distributed with distinctive boundaries.

3.1 PRELIMINARIES

The proposed C3-GAN is built from FineGAN (Singh et al., 2019), which is in turn based on InfoGAN (Chen et al., 2016). InfoGAN learns to associate a random latent code c with its observation $\hat{x}$ by approximating the posterior $P(c|\hat{x})$ that maximizes the mutual information $\mathrm{I}(c, \hat{x})$. The latent code c can take various forms depending on the prior knowledge of the factor to be inferred, and be defined as the uniform categorical distribution when the purpose is to make the categorical inference of the data. FineGAN generates images in a hierarchical manner by introducing multiple latent codes that correspond to a background class, a superclass of object, and a subclass of object. To facilitate this decomposition, FineGAN employs multiple pairs of generator and discriminator and utilizes an auxiliary background classifier trained using object bounding box labels. In addition to decomposed image generation, the approach can cluster images according to their fine-grained features by separately trained classifiers. The classifiers are trained on synthesized images pseudo-labeled with corresponding latent code values that are interpreted as cluster indices.

Our C3-GAN differs from FineGAN: i) C3-GAN employs the discriminator D for the classification without training of additional networks, and ii) learns only one latent code c that represents the fine-grained class of an object in the image x. Specifically, our generator G synthesizes background image $\hat{x}^{bg} \in \mathbb{R}^{3 \times H \times W}$, foreground mask $\hat{m} \in \mathbb{R}^{1 \times H \times W}$ and foreground appearance $\hat{t} \in \mathbb{R}^{3 \times H \times W}$ with two independent random variables, the noise value z and the latent code c. The noise $z \in \mathbb{R}^{d^z}$ is sampled from the normal distribution $\mathcal{N}(0, I)$. The latent code $c \in \mathbb{R}^Y$ is represented as 1-hot encoding where the index k such that $c_k = 1$ is sampled from the uniform categorical distribution $\mathcal{U}(0, Y-1)$. The noise value z is used for generating all image components making the layout of the scene, while the latent code c is used only for the foreground synthesis. To add some randomness, we augmented the 1-hot latent code c to latent variable $c' \in \mathbb{R}^{d^c}$ which is sampled from a gaussian distribution $N(\mu_c, \sigma_c)$ where values of the mean μ_c and the diagonal covariance matrix σ_c are conditioned on the original code c (Zhang et al., 2017). The final image $\hat{x} \in \mathbb{R}^{3 \times H \times W}$ is composited by applying the hadamard product to the generated components, as described in Fig. 2.

For achieving fully unsupervised learning, we remove the dependence on bounding box labels by adopting the method used in one of the unsupervised scene decomposition works, PerturbGAN (Bielski & Favaro, 2019). We also employ the regularization functions that enforce foreground mask $\hat{m}$ to be more like a hard mask and to take up the reasonable proportions of the scene,

$$\begin{aligned}
\mathcal{L}_G^{mask} = \ &\mathbb{E}_{hw}[-\hat{m} \log(\hat{m}) - (1 - \hat{m}) \log(1 - \hat{m})] \\
&+ \max(0, 0.1 - \mathbb{E}_{hw}[\hat{m}]) + \max(0, \mathbb{E}_{hw}[\hat{m}] - 0.9).
\end{aligned} \tag{1}$$

In PerturbGAN, scene decomposition is triggered by perturbing foreground components $\hat{m}$ and $\hat{t}$ with the affine transformation matrix $\mathcal{T}_\theta$ right before the final image composition. $\mathcal{T}_\theta$ is randomly generated with θ sampled from the uniform distributions with predefined value ranges of rotation

angle, scaling factor and translation distance. In mathematical, the generation process is described:

$$c' \sim N(\mu_c, \sigma_c), \quad \hat{x}^{bg}, \hat{m}, \hat{t} = G(z, c'),$$
$$\hat{m}', \hat{t}' = \mathcal{T}_\theta(\hat{m}, \hat{t}), \quad \hat{x} = \hat{x}^{bg} \odot (1 - \hat{m}') + \hat{t}' \odot \hat{m}'. \tag{2}$$

3.2 Contrastive Fine-grained Class Clustering

We assume that data are effectively clustered when i) the data explicitly form discernable cluster boundaries in the embedding space $\mathcal{H}$ and ii) each cluster centroid $l \in \mathbb{R}^{d^h}$ exhibits distinct semantic features. This is exactly the space that the discriminator of InfoGAN aims to approach when the latent code c is sampled from the uniform categorical distribution $\mathcal{U}(0, Y - 1)$ (Chen et al., 2016). However, while jointly optimizing an adversarial loss, the model has a possibility of falling into the mode collapse phenomenon where a generator G covers only a few confident modes (classes) to easily deceive the discriminator D. This is why InfoGAN cannot infer the classes of real images. To handle this problem, we propose a new form of the auxiliary probability $Q(c|x)$.

Let us describe the mathematical definition in details. The discriminator D aims to learn adversarial features $r \in \mathbb{R}$ for authenticity discrimination, and image features $h \in \mathbb{R}^{d^h}$ for optimizing the information-theoretic regularization. The features are encoded from separate branches ψ_x^r and ψ_x^h, which has split at the end of the base encoder of the discriminator D_{base}. The adversarial features r are learned with the hinge loss as shown in the equation below:

$$r, \hat{r} = \psi_x^r(D_{base}(x, \hat{x})),$$
$$\mathcal{L}_D^{adv} = \min(0, 1 - r) + \min(0, 1 + \hat{r}), \qquad \mathcal{L}_G^{adv} = -\hat{r}. \tag{3}$$

Here, the image features h can be considered as logits in a classification model. In a supervised learning setting where the ground-truth class is given, the data mapped into the embedding space gradually forms the cluster boundaries as the training proceeds, like the one in Fig. 1 (b). However, it is difficult to learn such space in an unsupervised setting simply by maximizing the mutual information between the latent code c and its observation $\hat{x}$, $\mathrm{I}(c; \hat{x})$, for the aforementioned problem.

Our solution is to employ contrastive representation learning where the image-latent pairs that maximize mutual information are considered as positive pairs and the rest as negative pairs. Here, the latent code is mapped into the space with simple linear layer ψ_c, and treated as trainable cluster centroids l. The proposed formulation of the auxiliary probability $Q(c|x)$ with aforementioned contrastive loss is as below:

$$Q(c_k = 1|\hat{x}) = q_k = \frac{\exp(\mathrm{sim}(\hat{h}, l_k)/\tau)}{\sum_{y=0}^{Y-1} \exp(\mathrm{sim}(\hat{h}, l_y)/\tau)} \quad s.t.$$
$$\hat{h} = \psi_x^h(D_{base}(\hat{x})), \qquad l = \psi_c(I_Y), \tag{4}$$

where $\mathrm{sim}(a, b)$ is the cosine distance between vectors a and b, y is the index of the cluster, and τ is a temperature of the softmax function. I_Y denotes the identity matrix with size Y.

With this formulation, we expect that the image features h would be pulled to k-th cluster, where k is the index of its corresponding latent code c such that $c_k = 1$, and each cluster centroid l_y would be pushing each other on the unit hypersphere. To assist the scene decomposition learning, we additionally maximize the mutual information between the latent code c and the masked foreground images $\hat{x}^{fg}$. So the information-theoretic objectives are defined as:

$$\mathcal{L}^{info} = -\log \frac{\exp(\mathrm{sim}(\hat{h}, l_k)/\tau)}{\sum_{y=0}^{Y-1} \exp(\mathrm{sim}(\hat{h}, l_y)/\tau)}, \quad \mathcal{L}^{info^{fg}} = -\log \frac{\exp(\mathrm{sim}(\hat{h}^{fg}, l_k)/\tau)}{\sum_{y=0}^{Y-1} \exp(\mathrm{sim}(\hat{h}^{fg}, l_y)/\tau)}. \tag{5}$$

Following the prior works (Ji et al., 2019; Van Gansbeke et al., 2020), we set Y as multiple times of actual number of classes so that the model can learn more expressive features. To further reduce the gap between real and fake images, we also regularize the prediction of real images $p \in \mathbb{R}^Y$. Specifically, we minimize the entropy of p, $H(p)$, to promote each data to be mapped to one cluster with high confidence and the KL divergence between the averaged prediction $\bar{\mathbf{p}}$ and the uniform distribution $\mathbf{u}$ to avoid a degenerated solution where few clusters are overly allocated. The

regularization function is as below:

$$\mathcal{L}_D^{entropy} = \mathbb{E}[H(p)] + D_{\text{KL}}(\bar{\mathbf{p}}\|\mathbf{u}) \quad s.t.$$

$$h = \psi_x^h(D_{base}(x)) \,, \qquad p_k = \frac{\exp(\text{sim}(h, l_k)/\tau)}{\sum_{y=0}^{Y-1} \exp(\text{sim}(h, l_y)/\tau)} \,, \qquad \bar{\mathbf{p}} = \mathbb{E}[p]. \tag{6}$$

In summary, our C3-GAN is trained by minimizing the $\mathcal{L}_D$ and $\mathcal{L}_G$ iteratively:

$$\mathcal{L}_D = \mathcal{L}_D^{adv} + \lambda_0 \mathcal{L}_D^{entropy} + \lambda_2 \mathcal{L}^{info} + \lambda_3 \mathcal{L}^{info^{fg}},$$

$$\mathcal{L}_G = \mathcal{L}_G^{adv} + \lambda_1 \mathcal{L}_G^{mask} + \lambda_2 \mathcal{L}^{info} + \lambda_3 \mathcal{L}^{info^{fg}}. \tag{7}$$

4 EXPERIMENTS

4.1 EXPERIMENTAL SETTING

Datasets. We tested our method on 4 datasets which contain single object images. **i) CUB** (Wah et al., 2011): 5,994 training and 5,794 test images of 200 bird species. **ii) Oxford Flower** (Nilsback & Zisserman, 2008): 2,040 training and 6,149 test images of 102 flower categories. **iii) Stanford Cars** (Krause et al., 2013): 8,144 training and 8,041 test images of 196 car models. **iv) Stanford Dogs** (Khosla et al., 2011): 12,000 training and 8,580 test images of 120 dog species. Since the CUB and Oxford Flower datasets have a small number of training images, all the experiments were conducted using the entire data as in prior works (Singh et al., 2019; Li et al., 2020; Benny & Wolf, 2020).

Implementation Details. The weights of loss terms $(\lambda_0, \lambda_1, \lambda_2, \lambda_3)$ are set as (0.1, 1, 5, 1), and the temperature τ is set as 0.1. The models are trained with Adam optimizer with learning rate of 0.0002 and momentum coefficients of (0.5, 0.999). Readers can find the parameter value ranges of the random affine transformation and the number of clusters Y in Appendix A.2. Please refer to Appendix A.1 for network architectures.

Baselines. We first compare C3-GAN to **IIC** (Ji et al., 2019) in order to emphasize the difference between coarse-grained and fine-grained class clustering tasks since it achieved decent clustering results with sobel filtered images where color and texture information is discarded. To check if optimizing instance discrimination task is enough for fine-grained feature representations learning, we also compare the results of **SimCLR+K-Means** (Chen et al., 2020). The work that showed remarkable result on the coarse-grained class clustering, **SCAN** (Van Gansbeke et al., 2020), were also included to evaluate their method of inducing consistent predictions between nearest neighbors on the fine-grained class clustering task. In addition to **InfoGAN** (Chen et al., 2016), the reported results of **FineGAN** (Singh et al., 2019), **MixNMatch** (Li et al., 2020) and **OneGAN** (Benny & Wolf, 2020) were compared to claim the efficacy of our proposed formulation of the auxiliary probability based on the contrastive loss. For the fair comparison, we especially compared with the results of the unsupervised version of FineGAN and MixNMatch, which are trained by pseudo-labeling the edges of real images as background regions.

4.2 FINE-GRAINED CLASS CLUSTERING RESULTS

Quantitative results. We evaluate the clustering performance with two metrics: Accuracy (Acc) and Normalized Mutual Information (NMI). The accuracy is calculated based on the optimal mapping between the cluster indices and the real classes inferred by the Hungarian algorithm (Kuhn & Yaw, 1955). The results are presented in Table 1. As shown in Table 1, our C3-GAN outperforms other methods with remarkable margins in terms of Acc on all four datasets. For NMI, our method presents better or comparable performances as well. The lowest results of IIC underlines that understanding only structural characteristic is not enough for fine-grained class clustering. It is difficult to decide which of the GAN-based methods or the SSL-based methods are better suited for fine-grained feature learning. Both approaches have similar range of scores on every metric and display globally entangled feature spaces as shown in Fig. 3 (a) and (b). From the results of SCAN (2nd rank) and MixNMatch (3rd rank), we conjecture that both circumventing the problem by requiring local disentanglement

	Acc ↑				NMI ↑			
	Bird	Car	Dog	Flower	Bird	Car	Dog	Flower
FineGAN[†] (Singh et al., 2019)	*12.6*	*7.8*	*7.9*	*-*	*0.40*	*0.35*	*0.23*	*-*
MixNMatch[†] (Li et al., 2020)	*13.6*	*7.9*	*8.9*	*-*	*0.42*	*0.36*	*0.32*	*-*
OneGAN[†] (Benny & Wolf, 2020)	*10.1*	*6.0*	*7.3*	*-*	*0.39*	*0.27*	*0.21*	*-*
Fully Unsupervised Setting								
IIC (Ji et al., 2019)	7.4	4.9	5.0	8.7	0.36	0.27	0.18	0.24
SimCLR (Chen et al., 2020) +k-Means	8.4	6.7	6.8	12.5	0.40	0.33	0.19	0.29
InfoGAN (Chen et al., 2016)	8.6	6.5	6.4	23.2	0.39	0.31	0.21	0.44
FineGAN w/o labels	6.9	6.8	6.0	8.10	0.37	0.33	0.22	0.24
MixNMatch w/o labels	10.2	7.3	10.3	39.0	0.41	0.34	0.30	0.57
SCAN (Van Gansbeke et al., 2020)	11.9	8.8	12.3	56.5	0.45	0.38	0.35	**0.77**
C3-GAN (Ours)	**27.6**	**14.1**	**17.9**	**67.8**	**0.53**	**0.41**	**0.36**	0.67

Table 1: Quantitative evaluation of the clustering performance. [†] denotes the results reported in the original papers, and the rest is reproduced by our implementation. Note that FineGAN, MixNMatch, and OneGAN utilize supervision for training unlike our C3-GAN.

(a) MixNMatch (Li et al., 2020)   (b) SCAN (Van Gansbeke et al., 2020)   (c) C3-GAN (Ours)

Figure 3: Visualization of the embedding space of MixNMatch, SCAN and C3-GAN trained on CUB dataset. Each point represents image features of 10 classes reduced into 2-dimensional space via t-SNE. The color represents its cluster index. Only C3-GAN has a embedding space where the cluster distinction is clear.

of the embedding space and extracting foreground features via scene decomposition are helpful for improving the fine-grained clustering performance. The state-of-the-art scores of C3-GAN not only benefit from the scene decomposition learning, but also can be attributed to the proposed formulation of $Q(c|x)$ that enforces the clusters to be uniformly distributed in the embedding space, as visualized in Fig. 3 (c).

Furthermore, we present multiple qualitative results on fine-grained clustering tasks in the Appendix A.3, which show the superiority of our method to SCAN and MixNMatch.

Ablation Study. We performed ablation study regarding three factors: i) Overclustering, ii) Perturbing foreground images via random affine transformation, and iii) Our formulation of the auxiliary probability $Q(c|x)$. We investigate the clustering performance by removing each factor as shown in Table 2. The largest performance degradation is induced by changing the formulation of the auxiliary probability $Q(c|x)$ to a trivial softmax function. This result implies that the embedding space where clusters are uniformly distributed via our contrastive loss have a strong agreement with clustering performance as suggested by (Wang & Isola, 2020). We observe that C3-GAN fails to decompose background and foreground images when the random perturbation $\mathcal{T}_\theta$ is not applied. The significant performance degradation suggests that the method of extracting only the foreground features has

	Acc ↑	NMI ↑
C3-GAN (Ours)	**27.6**	**0.53**
− Overclustering	22.7	0.50
− Perturbing foreground images via random affine transformation	16.6	0.47
− Contrastive loss based auxiliary probability $Q(c\|x)$	14.5	0.45

Table 2: Effects of each components of C3-GAN on model performances on CUB dataset.

(a) Images synthesized with the predicted cluster index of a given real image.

(b) Images synthesized by controlling latent code c and noise value z.

Figure 4: Qualitative image generation results of C3-GAN trained on CUB dataset. We show (a) the synthesized images with the predicted cluster indices of real images and (b) the synthesized images with randomly sampled input variables z and c.

a non-negligible amount of benefit in fine-grained clustering. We present more ablation results on overclustering in the Appendix A.2.

4.3 IMAGE GENERATION RESULTS

Qualitative Results. Fig. 4 presents images synthesized by our model for given diverse latent codes c and noise values z on CUB dataset. As shown in Fig. 4(a), given a bird image, C3-GAN generates new various images with the bird same as the given image on diverse backgrounds generated from noise values. Latent code c is predicted from the given images by the discriminator of C3-GAN. The results present our discriminator accurately predict the cluster of input objects and generate plausible fine-grained images. Also, we observe that different noise values can diversify the pose of the birds as well as background. For more investigating the effects of c and z, we fix one of two factors and diversify the other for image generation as presented in Fig. 4(b). When c is fixed, all the generated images contain the same bird corresponding to c while the bird poses and image backgrounds vary due to variable z. On the contrary, for variable c and fixed z, we can observe various bird species with the same pose and background. We present more results on other datasets in the appendix A.4.

We observe that C3-GAN effectively alleviates the mode collapse issue from Fig. 5. The images are synthesized with the cluster index corresponding to the class of real images. While C3-GAN presents *intra*-class color, shape, and layout variation for a given flower class, the results of other

Figure 5: Qualitative image generation results of C3-GAN trained on Oxford flower dataset. The fake images are synthesized with cluster indices predicted by each model's own method. Only C3-GAN generates images that reflect the *intra*-class color, shape, and layout variation of the real images.

	FID ↓				IS ↑				Reverse KL ↓			
	Bird	Car	Dog	Flower	Bird	Car	Dog	Flower	Bird	Car	Dog	Flower
InfoGAN (Chen et al., 2016)	35.71	70.91	59.07	78.37	8.20	3.25	6.91	13.39	0.56	0.73	0.40	0.42
FineGAN w/o labels	33.87	87.66	49.12	35.72	10.07	**4.20**	10.67	10.42	0.67	0.58	0.24	0.52
MixNMatch w/o labels	31.59	78.36	48.11	**32.03**	9.76	4.11	**10.70**	**16.48**	0.52	**0.57**	0.22	0.34
C3-GAN (Ours)	**19.37**	**67.36**	**45.40**	64.19	**14.52**	3.62	9.33	13.75	**0.29**	**0.57**	**0.18**	**0.25**

Table 3: Quantitative evaluation of the image synthesis performance.

baselines differ only in layout. We conjecture that this is because the learnt image feature space of the discriminator represents the real data distribution well, so the generator gets a strong signal for learning to synthesize realistic images in addition to the adversarial loss. Through the investigation of synthesized images, we also found that C3-GAN was the only one that succeeded in scene decomposition learning in an unsupervised way. FineGAN and MixNMatch trained without bounding box annotations fell into a degenerate solution where the entire image is synthesized from the background generator.

Quantitative Results. We evaluate image synthesis performance based on three metrics, Frechet Inception Distance (FID), Inception Score (IS) and reverse KL that measures the distance between the predicted class distribution of real and synthesized images. We compared only with GAN-based models trained in a fully unsupervised setting. The scores of IS and reverse KL were measured with Inception networks fine-tuned on each fine-grained dataset using the method of Cui et al. (2018)[1], and the results are displayed in Table 3. C3-GAN presents state-of-the-art or comparable performance in terms of FID and Reverse KL on the most datasets. With the qualitative results together, these results imply our C3-GAN has competitive capability for fine-grained object image generation.

5 CONCLUSION

In this study, we proposed a new GAN-based method, C3-GAN, for unsupervised fine-grained class clustering, which is more challenging and less explored than coarse-grained clustering tasks. To achieve fine-grained class clustering, we leverage the information-theoretic regularization term based on the contrastive loss. Also, a scene decomposition-based approach is introduced into our GAN model to enforce the model to learn representation focusing on the details of foreground images. Furthermore, we enhance the performance by employing foreground perturbation with random affine transformation and the overclustering approach. Extensive experiments show our C3-GAN not only outperforms previous fine-grained clustering methods but also synthesizes fine-grained object images with comparable quality while reducing mode collapse that previous state-of-the-art GAN methods suffer from. Since our main goal is unsupervised fine-grained clustering rather than image generation, C3-GAN still has room to be improved despite its comparable results.

---

[1]The accuracy of Inception Networks fine-tuned on the CUB/Oxford Flower/Stanford Dogs/Stanford Cars datasets are 0.87/0.94/0.86/0.47 respectively.

ETHICS STATEMENT

Remarkable advancement of generative models has played a crucial role as AI tools for text (Brown et al., 2020; Kim et al., 2021), image (Karras et al., 2020; Choi et al., 2020b), audio (Sisman et al., 2020), and multimodal content generation (Tian et al., 2021; Yan et al., 2021). However, as its side effect, many malicious applications have been reported as well, thus leading to severe societal problems, such as deepfake (Dolhansky et al., 2020), fake news (Lazer et al., 2018), and generation biased by training data (Gupta et al., 2021). Our work might be an extension of the harmful effects of generative models. On the contrary, generative models can be a solution to alleviate these side effects via data augmentation (Yang et al., 2019; Choi et al., 2020a). In particular, our method can contribute to alleviating data bias and fine-grained class imbalance. Therefore, many endless efforts are required to make these powerful generative models benefit humans.

REPRODUCIBILITY STATEMENT

We described the datasets and baselines compared with our method in detail in 4.1. The details of our model architecture and hyperparameter setup are also explained in A.1 and A.2. And we plan to open the source code of C3-GAN for reproducibility.

REFERENCES

Rameen Abdal, Peihao Zhu, Niloy J. Mitra, and Peter Wonka. Labels4free: Unsupervised segmentation using stylegan. In *ICCV*, 2021.

Yaniv Benny and Lior Wolf. Onegan: Simultaneous unsupervised learning of conditional image generation, foreground segmentation, and fine-grained clustering. In *ECCV*, 2020.

Adam Bielski and Paolo Favaro. Emergence of object segmentation in perturbed generative models. In *NeurIPS*, 2019.

Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale GAN training for high fidelity natural image synthesis. In *ICLR*, 2019.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. In *NeurIPS*, 2020.

Mathilde Caron, Piotr Bojanowski, Armand Joulin, and Matthijs Douze. Deep clustering for unsupervised learning of visual features. In *ECCV*, 2018.

Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. Unsupervised learning of visual features by contrasting cluster assignments. In *NeurIPS*, 2020.

Mickaël Chen, Thierry Artières, and Ludovic Denoyer. Unsupervised object segmentation by redrawing. In *NeurIPS*, 2019.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *ICML*, 2020.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In *NeurIPS*, 2016.

Kristy Choi, Aditya Grover, Trisha Singh, Rui Shu, and Stefano Ermon. Fair generative modeling via weak supervision. In *ICML*, 2020a.

Yunjey Choi, Youngjung Uh, Jaejun Yoo, and Jung-Woo Ha. Stargan v2: Diverse image synthesis for multiple domains. In *CVPR*, 2020b.

Adam Coates, Andrew Ng, and Honglak Lee. An analysis of single layer networks in unsupervised feature learning. In *AISTATS*, 2011.

Yin Cui, Yang Song, Chen Sun, Andrew Howard, and Belongie Serge. Large scale fine-grained categorization and domain-specific transfer learning. In *CVPR*, 2018.

Kamran Ghasedi Dizaji, Amirhossein Herandi, and Heng Huang. Deep clustering via joint convolutional autoencoder embedding and relative entropy minimization. In *NeurIPS*, 2017.

Brian Dolhansky, Joanna Bitton, Ben Pflaum, Jikuo Lu, Russ Howes, Menglin Wang, and Cristian Canton Ferrer. The deepfake detection challenge (dfdc) dataset. In *arXiv*, 2020.

Jeff Donahue, Philipp Krähenbühl, and Trevor Darrell. Adversarial feature learning. In *ICLR*, 2017.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *NeurIPS*, 2014.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre H. Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Daniel Guo, Mohammad Gheshlaghi Azar, Bilal Piot, Koray Kavukcuoglu, Rémi Munos, and Michal Valko. Bootstrap your own latent: A new approach to self-supervised learning. In *NeurIPS*, 2020.

Guibing Guo, Yuan Meng, Yongfeng Zhang, Chunyan Han, and Yanjie Li. Visual semantic image recommendation. In *IEEE*, 2019.

Aman Gupta, Deepak Bhatt, and Anubha Pandey. Transitioning from real to synthetic data: Quantifying the bias in model. In *Synthetic Data Generation Workshop at ICLR 2021*, 2021.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *CVPR*, 2020.

Irina Higgins, Loïc Matthey, Arka Pal, Christopher P. Burgess, Xavier Glorot, Matthew M. Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. In *ICLR*, 2017.

Xu Ji, João F Henriques, and Andrea Vedaldi. Invariant information clustering for unsupervised image classification and segmentation. In *ICCV*, 2019.

Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *CVPR*, 2019.

Tero Karras, Samuli Laine, Miika Aittala, Janne Hellsten, Jaakko Lehtinen, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *CVPR*, 2020.

Aditya Khosla, Nityananda Jayadevaprakash, Bangpeng Yao, and Li Fei-Fei. Novel dataset for fine-grained image categorization. In *First Workshop on Fine-Grained Visual Categorization*, 2011.

Boseop Kim, HyoungSeok Kim, Sang-Woo Lee, Gichang Lee, Donghyun Kwak, Dong Hyeon Jeon, Sunghyun Park, Sungju Kim, Seonhoon Kim, Dongpil Seo, et al. What changes can large-scale language models bring? intensive study on hyperclova: Billions-scale korean generative pretrained transformers. In *EMNLP*, 2021.

Jonathan Krause, Michael Stark, Jia Deng, and Li Fei-Fei. 3d object representations for fine-grained categorization. In *4th International IEEE Workshop on 3D Representation and Recognition*, 2013.

H. W. Kuhn and Bryn Yaw. The hungarian method for the assignment problem. In *Naval Research Logistics Quarterly*, 1955.

David MJ Lazer, Matthew A Baum, Yochai Benkler, Adam J Berinsky, Kelly M Greenhill, Filippo Menczer, Miriam J Metzger, Brendan Nyhan, Gordon Pennycook, David Rothschild, et al. The science of fake news. In *AAAS*, 2018.

Yann LeCun, Corinna Cortes, and CJ Burges. Mnist handwritten digit database. In *ATT Labs [Online]. Available: http://yann.lecun.com/exdb/mnist*, 2010.

Junnan Li, Pan Zhou, Caiming Xiong, and Steven C.H. Hoi. Prototypical contrastive learning of unsupervised representations. In *ICLR*, 2021.

Yuheng Li, Krishna Kumar Singh, Utkarsh Ojha, and Yong Jae Lee. Mixnmatch: Multifactor disentanglement and encoding for conditional image generation. In *CVPR*, 2020.

Steven Liu, Tongzhou Wang, David Bau, Jun-Yan Zhu, and Antonio Torralba. Diverse image generation via self-conditioned gans. In *CVPR*, 2020.

Luke Melas-Kyriazi, Christian Rupprecht, Iro Laina, and Andrea Vedaldi. Finding an unsupervised image segmenter in each of your deep generative models. In *arXiv*, 2021.

Maria-Elena Nilsback and Andrew Zisserman. Automated flower classification over a large number of classes. In *ICCVGIP*, 2008.

Pedro Savarese, Sunnie S. Y. Kim, Michael Maire, Greg Shakhnarovich, and David McAllester. Information-theoretic segmentation by inpainting error maximization. In *CVPR*, 2021.

Krishna Kumar Singh, Utkarsh Ojha, and Yong Jae Lee. Finegan: Unsupervised hierarchical disentanglement for fine-grained object generation and discovery. In *CVPR*, 2019.

Berrak Sisman, Junichi Yamagishi, Simon King, and Haizhou Li. An overview of voice conversion and its challenges: From statistical modeling to deep learning. In *TASLP*, 2020.

Qiule Sun, Qilong Wang, Jianxin Zhang, and Peihua Li. Hyperlayer bilinear pooling with application to fine-grained categorization and image retrieval. In *Neurocomputing*, 2018.

Yu Tian, Jian Ren, Menglei Chai, Kyle Olszewski, Xi Peng, Dimitris N Metaxas, and Sergey Tulyakov. A good image generator is what you need for high-resolution video synthesis. In *ICLR*, 2021.

Wouter Van Gansbeke, Simon Vandenhende, Stamatios Georgoulis, Marc Proesmans, and Luc Van Gool. Scan: Learning to classify images without labels. In *ECCV*, 2020.

Andrey Voynov and Artem Babenko. Unsupervised discovery of interpretable directions in the gan latent space. In *ICML*, 2020.

Catherine Wah, Steve Branson, Peter Welinder, Pietro Perona, and Serge Belongie. The caltech-ucsd birds-200-2011 dataset. In *California Institute of Technology*, 2011.

Tongzhou Wang and Phillip Isola. Understanding contrastive representation learning through alignment and uniformity on the hypersphere. In *ICML*, 2020.

Junyuan Xie, Ross B. Girshick, and Ali Farhadi. Unsupervised deep embedding for clustering analysis. In *ICML*, 2016.

Wilson Yan, Yunzhi Zhang, Pieter Abbeel, and Aravind Srinivas. Videogpt: Video generation using vq-vae and transformers. In *arXiv*, 2021.

Shuo Yang, Kai Shu, Suhang Wang, Renjie Gu, Fan Wu, and Huan Liu. Unsupervised fake news detection on social media: A generative approach. In *AAAI*, 2019.

Han Zhang, Tao Xu, Hongsheng Li, Shaoting Zhang, Xiaogang Wang, Xiaolei Huang, and Dimitris Metaxas. Stackgan: Text to photo-realistic image synthesis with stacked generative adversarial networks. In *ICCV*, 2017.

Huasong Zhong, Chong Chen, Zhongming Jin, and Xian-Sheng Hua. Deep robust clustering by contrastive learning. In *arXiv*, 2020.

A APPENDIX

A.1 NETWORK ARCHITECTURE

We present the detailed description of architecture of the generator and the discriminator for our C3-GAN in Table 4 and Table 5, respectively. The colored dots (●, ●, ●) indicate that outputs of the earlier layers are used as inputs for the later layers. The training is done with 2 NVIDIA-V100 GPUs, and we optimized the model until the convergence of the FID score.

Module	Layers	Input size	Output size
G_{bg}	Linear, BN, GLU, UnSqueeze	64 ($\mathbf{z}$)	512×4×4
	[Up, Conv(3,1), BN, GLU]×5	512×4×4	64×128×128
	[Conv(3,1), BN, GLU, Conv(3,1), BN]×3	64×128×128	64×128×128
	Conv(3,1), Tanh	64×128×128	3×128×128 ($\hat{\mathbf{x}}^{\mathbf{bg}}$)
$N(\mu_c, \sigma_c)$	Linear, BN, GLU	Y ($\mathbf{c}$)	8 ●
G_{fg}^{base}	Linear, BN, GLU, Reshape	64 ($\mathbf{z}$)	512×4×4
	[Up, Conv(3,1), BN, GLU]×5	(512+8 ●)×4×4	16×128×128
	[Conv(3,1), BN, GLU, Conv(3,1), BN]×3	16×128×128	16×128×128 ●
G_{fg}^{m}	Conv(3,1), BN, GLU	16×128×128 ●	64×128×128
	Conv(3,1), Sigm	64×128×128	1×128×128 ($\hat{\mathbf{m}}$)
G_{fg}^{t}	Conv(3,1), BN, GLU	(16● + Y ($\mathbf{c}$))×128×128	16×128×128
	[Conv(3,1), BN, GLU, Conv(3,1), BN]×2	16×128×128	16×128×128
	Conv(3,1), BN, GLU	16×128×128	16×128×128
	Conv(3,1), Tanh	16×128×128	3×128×128 ($\hat{\mathbf{t}}$)

Table 4: Architecture description of the generator of C3-GAN.

Module	Layers	Input size	Output size
D_{base}	Conv(4,2), LReLU	3×128×128 ($\mathbf{x}$)	64×64×64
	[Conv(4,2), BN, LReLU]×4	64×64×64	512×4×4
	Conv(3,1), BN, LReLU	512×4×4	512×4×4 ●
ψ_x^r	Conv(4,4), Squeeze	512×4×4 ●	1 ($\mathbf{r}$)
ψ_x^h	Conv(3,1), BN, LReLU	512×4×4 ●	512×4×4
	Conv(4,4), Squeeze	512×4×4	512 ($\mathbf{h}$)
ψ_c	Linear	Y ($\mathbf{c}$)	512 ($\mathbf{l}$)

Table 5: Architecture description of the discriminator of C3-GAN.

- Conv(*a*,*b*) : 2D Convolution layer with kernel size *a* and stride *b*
- GLU : Gated Linear Units

A.2 MORE ABLATION STUDY

Random affine transformation. We experimented with two types of purtubing policies such as weak and strong perturbation. Their detailed value ranges are presented in Table 6. The type of perturbation to use for each dataset was determined by manually checking the results of randomly perturbed real images. The strong perturbation was used for CUB dataset, and the rest datasets were trained with the weak perturbation.

Criteria	Scale	Rotation	Translation	Dataset
Weak perturbation	(0.9, 1.1)	(-2, 2)	(-0.08, 0,08)	Stanford Cars, Stanford Dogs, Oxford Flower
Strong perturbation	(0.8, 1.5)	(-15, 15)	(-0.15, 0,15)	CUB

Table 6: Details of random affine transformation

Cluster numbers for each dataset. We use four datasets for evaluation, including CUB, Oxford Flower, Standford Cars, and Stanford Dogs. As depicted in 3.2, we employ the overclustering approaches to improve the performances, which is to set the cluster number to be multiple times as the actual number of classes of the dataset. For finding optimal setting, we compared the results of C3-GAN by setting the number of clusters as 1, 2, and 3 times the actual number of classes. We found that performance tends to improve as the number of clusters increases. This implies that overclustering is indeed helpful for expressive feature learning. The cluster numbers for each dataset were determined based on the results in Table 7.

		Acc ↑	NMI ↑	FID ↓
CUB	× 1	22.7	0.50	18.75
	× 2	**27.6**	**0.53**	19.37
	× 3	26.3	0.51	**17.13**
Stanford Cars	× 1	8.3	0.33	**64.55**
	× 2	11.5	0.39	66.65
	× 3	**14.1**	**0.41**	67.36
Stanford Dogs	× 1	11.8	0.30	51.37
	× 2	15.8	0.35	54.82
	× 3	**17.9**	**0.36**	**45.40**
Oxford Flower	× 1	55.6	**0.72**	75.12
	× 2	61.7	0.67	74.59
	× 3	**67.8**	0.67	**64.19**

Table 7: Results of hyperparameter search for overclustering.

A.3 QUALITATIVE ANALYSIS OF CLUSTERING RESULTS

We present the clustered images by our C3-GAN on two classes for CUB and Oxford Flowers datasets, comparing the results of MixNMatch and SCAN in Figs. 6 and 7. From Fig. 6, our method presents better clustered results outperforming two comparable methods. It is worth noting that even the objects in images incorrectly clustered by C3-GAN look very similar to given object class while the cluster results of other two methods contain images of objects that seldom resemble the given class object. We can confirm the consistent results on the Flower dataset as shown in Fig. 7.

(a) C3-GAN (Ours)   (b) SCAN (Van Gansbeke et al., 2020)   (c) MixNMatch (Li et al., 2020)

Figure 6: Examples of clustering results on CUB dataset. The cluster indices of the first and the second rows are the ones mapped from real classes *Cerulean Warbler* and *le Conte Sparrow* via Hungarian Algorithm. Red boxes denote incorrectly clustered images.

(a) C3-GAN (Ours)   (b) SCAN (Van Gansbeke et al., 2020)   (c) MixNMatch (Li et al., 2020)

Figure 7: Examples of clustering results on Flower dataset. The cluster indices of the first and the second rows are the ones mapped from real classes *35* and *66* via Hungarian Algorithm. Red boxes denote incorrectly clustered images.

A.4 ADDITIONAL IMAGE GENERATION RESULTS

A.4.1 CUB

A.4.2 STANFORD CARS

A.4.3 STANFORD DOGS

A.4.4 OXFORD FLOWER