Enhancing Code Generation in Large Language Models: A Human-Like Debugging Approach for Competitive Problem Solving

Abstract

Recent advances in Large Language Models (LLMs) have shown impressive code generation capabilities, yet their reasoning often collapses when faced with algorithmically complex or error-sensitive programming tasks. This gap stems not from limited knowledge, but from a lack of self-diagnostic awareness—the ability to understand why a piece of code fails and how to repair it. We argue that effective code generation requires integrating cognitive processes analogous to human debugging: perceiving failures, tracing intermediate states, hypothesizing causes, and revising accordingly. Building on this perspective, we propose a Human-Like Debugging Architecture (HLDA) that operationalizes these processes within LLMs. HLDA systematically executes generated code, records fine-grained variable traces, interprets discrepancies, and iteratively regenerates improved solutions. Unlike prior self-editing or executor-based approaches that rely on outcome-level feedback, our method introduces trace-level causal feedback, enabling models to reason over "how the code went wrong" rather than merely "what went wrong." This leads to substantial performance gains, setting new state-of-the-art results on HumanEval, MBPP, and contest-level benchmarks such as APPS and CodeContest.

1 Introduction

Large Language Models (LLMs) have rapidly evolved from natural language generators into powerful semantic reasoners capable of producing executable code. Yet despite remarkable fluency, most LLMs still lack the self-awareness and reasoning granularity that characterize human debugging. When their code fails, they struggle not because they lack algorithmic knowledge, but because they cannot observe, interpret, and reason about their own execution process.

Existing frameworks such as LEVER (Ni et al., 2023), LATS (Zhou et al., 2023), and Reflex-

Figure 1: When there are bugs in the code, simply informing a human that there are bugs is insufficient. Providing test cases and bug analysis significantly eases the debugging process.

ion (Shinn et al., 2023) attempt to bridge this gap by integrating evaluators, search trees, or reflection-based loops. However, these methods treat debugging as a form of *search over outputs* rather than a *cognitive process of understanding*. They seldom capture the fine-grained reasoning steps that human programmers perform—such as examining loop invariants, intermediate variable values, or branching conditions—to localize the true source of failure.

We take a different stance: debugging is not merely an optimization step, but an epistemic process of hypothesis testing. Human programmers continuously form causal links between observed failures and internal execution states (e.g., "if the counter reached zero prematurely, the loop condition must be wrong"). To emulate this introspection, we propose a **Human-Like Debugging Architecture (HLDA)** that transforms code generation from a one-shot synthesis task into an iterative causal reasoning loop.

Our architecture consists of six interconnected modules: Planning, Code Generation, Execution with variable tracing, Debugging with semantic validation, Feedback-driven regeneration, and Pseudo-test cases generator, each reflecting a key stage of human cognition during programming. Crucially, HLDA treats the execution trace not as an auxiliary artifact, but as a learning substrate for reasoning. By leveraging intermediate variable states and failure contexts, the model develops an internal causal understanding of how its code behaves.

This shift in perspective leads to several insights:

- **From correctness to cognition:** Evaluation of intermediate states enables the model to reason about logic, not just outcomes.
- **From reflection to simulation:** The model does not merely "reflect" on the outputs—it *simulates* the human debugging process, validating hypotheses and iteratively debugging the code.
- **From benchmark success to reasoning transfer:** The same architecture scales seamlessly from simple tasks to competitive programming, showing that detailed feedback fundamentally reshapes how LLMs perform reasoning.

Through extensive experiments on HumanEval, MBPP, and contest-level datasets, we demonstrate that HLDA achieves superior Pass@1 accuracy while maintaining efficient computational cost. More importantly, it provides interpretability through structured feedback, revealing how causal introspection and execution-grounded reasoning can significantly advance the next generation of self-corrective code generation systems.

To better illustrate our motivation, consider the debugging process in Fig. 1. When a human programmer receives vague feedback such as *"Your code has bugs"*, they can rarely pinpoint the issue. In contrast, when provided with detailed test cases, execution results, and intermediate variable states, the debugging process becomes significantly easier and more effective.

Existing LLM-based code generation systems resemble the first scenario—they often receive only binary feedback and thus lack the ability to form causal hypotheses about the program's internal behavior. As a result, they tend to make superficial corrections rather than structural reasoning. Our architecture is designed to mimic the second scenario, explicitly providing the model with execution traces, variable-level diagnostics, and semantic reasoning prompts, thereby enabling causal reasoning over the program flow. This not only improves accuracy but also grants interpretability—each correction can be traced to a specific logic discrepancy, rather than relying on trial and error.

2 Related Works

2.1 Advancements in Large Language Models (LLM)

Recent advancements in Large Language Models (LLM) have been remarkable, driven by the expansion of training data and substantial computational resources. Pioneering models such as BERT ((Devlin et al., 2018)) and GPT-2 ((Radford et al., 2019)) laid the groundwork in this domain. A significant milestone was the introduction of GPT-3 in June 2020, which, with its 175 billion parameters, began to impact everyday life significantly. This sparked a trend where numerous entities, including companies and researchers, started developing their own LLMs. Examples include LLaMA ((Touvron et al., 2023)), Chinchilla ((Hoffmann et al., 2022)), ERNIE ((Wang et al., 2021)), and BLOOM ((Workshop et al., 2022)). These models have shown exceptional performance in various applications such as chatting, question-answering, and code generation. Moreover, models like InstructGPT ((Ouyang et al., 2022)) have enhanced human-model interaction by aligning LLMs with human intent, allowing them to address a broad spectrum of queries. The emergence of open-source LLMs such as Vicuna ((Peng et al., 2023)) and Alpaca ((Taori et al., 2023)) based on LLaMA further demonstrates the potential of these models.

2.2 Employing LLM as an Agent

As LLMs have evolved, efforts have been made to utilize them as agents in everyday scenarios. In this context, an 'agent' refers to an entity where we input information such as objectives, environment, and feedback, allowing the LLM to assist in decision-making. Starting with the concept of Chain-of-Thought ((Wei et al., 2022)) and Tree-of-Thought ((Yao et al., 2023)), researchers have been teaching LLMs to approach goals incrementally, similar to human processes. In ReAct ((Yao et al., 2022)), there is a shift towards guiding LLMs to generate reasons in addition to actions. Additionally, recent studies ((Chang et al., 2023),(Hu et al., 2023)) are exploring the use of reinforcement learning to provide feedback to LLMs, enhancing their performance. The application of LLMs as agents spans numerous fields. For instance, they have been used in gaming ((Qiao et al., 2023),(Akoury et al., 2023)), customer service ((Cai et al., 2023), (Soni, 2023)), and code generation ((Ni et al., 2023), (Zhou et al., 2023)). The expansion of LLMs continues to open up new possibilities for their application in various domains.

2.3 Code Generation

The task of generating code based on given tasks has a long history, with earlier methods being pre-

dominantly rule-based, as seen in works done by Woods ((Woods, 1973)) in 1973. However, with the advent of deep learning, there has been a shift towards leveraging these techniques for code generation, exemplified by Xiao ((Xiao et al., 2016)). Recently, LLMs have shown remarkable efficacy in this field, leading to numerous innovations to refine LLM-generated outputs. Some recent works ((Ni et al., 2023), (Zhou et al., 2023)) have experimented with adding an executor to run the generated code and select the best option from multiple outputs. Concurrently, approaches like ReAct ((Yao et al., 2022)) focus on providing appropriate feedback based on the generated code and its test cases. Despite these advancements, LLMs face challenges correcting errors in their generated code. In our research, we simulate the human debugging process and have achieved significant progress compared to prior methodologies.

3 Architecture

Our **Human-Like Debugging Architecture (HLDA)** is designed to replicate the reasoning process through which human programmers conceptualize, execute, and refine their code. Rather than performing code generation as a one-shot prediction, HLDA structures it as a multi-stage reasoning loop that integrates explicit planning, controlled execution, semantic diagnosis, and iterative feedback (Fig. 2). This architecture enables the model to reason not only about the correctness of the code but also about the causal chain that led to success or failure, thereby providing a principled bridge between neural code synthesis and symbolic debugging.

3.1 Planning Module

Human developers rarely begin coding without forming a mental map of the solution. They first identify the target function, select suitable algorithms or data structures, and consider corner cases. Our Planning Module mirrors this cognitive phase by decomposing the natural-language description of a problem into explicit reasoning steps and control logic. The output is a structured plan that includes the goal, reasoning outline, potential variables, and possible error sources. For instance, given a sorting problem, the module specifies substeps such as "parse input," "apply sorting algorithm," and "return ordered output." This plan functions as the LLM's internal reasoning

scaffold, guiding subsequent modules while maintaining a transparent mapping between intent and implementation. By decoupling reasoning from code generation, HLDA enforces consistency in the output and improves interpretability and modularity—enabling systematic failure analysis in later stages. Empirically, this step prevents cascading logic errors, as each subsequent regeneration refers back to the same structured reasoning anchor.

3.2 Code Generator

The Code Generator translates the structured plan into executable Python code. Each reasoning element from the planning stage is realized as a corresponding code block or function. This modular translation preserves the causal dependencies among variables and functions. The generator employs an instruction-driven prompting format that encourages the model to "follow its own reasoning" instead of retrieving memorized templates. For example, if the plan specifies a boundary check or a special case, the generator explicitly implements it, ensuring alignment between reasoning and syntax. Such interpretability is critical because the debugging process can later link an observed failure directly to its corresponding planning node or generated segment. This linkage allows the system to perform targeted correction, similar to how a human developer would adjust one step of the logic without rewriting the entire function. Moreover, HLDA maintains detailed internal associations between lines of code and their originating plan elements, enabling fine-grained causal tracing.

3.3 Code Executor

In human programming, running and observing the code is as crucial as writing it. Our Code Executor reproduces this introspection by executing the generated code within a controlled sandbox. Before execution, the source code is transformed to insert lightweight trace hooks at critical control points—capturing loop counters, conditional branches, variable updates, and return values. This mechanism allows the executor to record both the final outputs and the full evolution of the program's internal state. All traces are serialized into structured logs that detail, for each execution step, the corresponding line of code and associated variable states. When execution completes, the module checks whether the results match the expected outputs from both ground-truth and pseudo test cases. If all test cases pass, the result is marked correct.

Figure 2: The pipeline of our model. We start with a task and a planning module to create a step-by-step plan for code generation. Then, we use LLM to generate an initial code and our code executor to evaluate the generated code using the test cases. If there are bugs in the generated code, we use our debug module to track the intermediate variables and other information. Based on the collected information, our architecture will try to provide a reason and solution to correct the bugs. Then the LLM can start the next iteration.

Otherwise, the executor returns a comprehensive diagnostic report including failing inputs, expected versus actual outputs, and variable traces at failure points. This design directly parallels human debugging behaviors—where developers insert print statements or use breakpoints to inspect intermediate results. The execution report thus provides the foundation for reasoning in the subsequent module, offering *trace-level causal visibility* rather than simple binary pass/fail feedback.

3.4 Pseudo Test Case Generator

Ground-truth test cases, while reliable, are limited in diversity. To better simulate the depth of human test design, HLDA introduces a Pseudo Test Case Generator that constructs additional test scenarios by modifying parameters, varying input distributions, or composing new examples consistent with the natural-language task description. For instance, if the prompt involves string manipulation, the generator automatically creates longer strings, edge characters, or empty cases to probe robustness. These pseudo tests expose hidden logical inconsistencies that would not surface in standard evaluation. However, automatically generated tests can be noisy. Thus, before any debugging step, the module validates each pseudo test case by prompting the LLM to assess whether the input–output pair is logically consistent with the problem statement. If the case is inconsistent or ambiguous, the system attributes the failure to the test itself and excludes it from further reasoning. If validated, the test proceeds to the same execution and analysis process as the human-designed ones. By explicitly distinguishing between test validation and fault localization, HLDA mirrors human judgment during

testing—where developers discard uninformative or incorrect tests. This selective filtering ensures that subsequent corrections are grounded in trustworthy signals.

3.5 Debug Module

The Debug Module forms the analytical core of HLDA. It consumes execution logs and test outcomes to perform semantic diagnosis of failures. Upon encountering a mismatch between expected and actual results, the module examines the corresponding variable trajectories to identify the smallest causal chain that explains the error. For example, if a variable remains zero when it should have been incremented, the debug module inspects the preceding loop iterations and control conditions to determine the faulty logic. When operating on pseudo test cases, it first verifies the test's validity to prevent spurious corrections caused by misspecified examples. Once validated, the module conducts a detailed causal attribution by mapping variable deviations to their respective code fragments and planning nodes. This process generates a natural-language explanation that includes: (1) the probable root cause, (2) the affected code lines or logical condition, and (3) a proposed fix based on reasoning consistency. For instance, in a rotation-counting example, the debug module might detect that the initialization of the "rotation" variable to 0 rather than n caused early termination. Such explanations are not heuristic guesses but structured causal hypotheses derived from execution evidence. By explicitly separating test case validation from bug localization, the module enhances both stability and interpretability. The result is a robust debugging pipeline that faithfully mirrors human

reasoning, balancing exploration and precision.

3.6 Feedback Module

The Feedback Module closes the human-like reasoning loop. In practical debugging, developers iteratively revise their code by reflecting on observed errors and progressively refining logic. HLDA implements this behavior by feeding the diagnostic explanation from the debug module back into the code generator as augmented contextual input. The regenerated prompt retains the original plan and problem statement but appends the specific failure description and suggested correction strategy. For example, the feedback may instruct: "Initialize rotation with n instead of 0 to ensure correct behavior when no match is found." This new prompt drives the next iteration of code synthesis. The architecture tracks performance across iterations—monitoring whether new versions resolve prior issues or introduce regressions. To avoid infinite loops or diminishing returns, the process is capped at eight iterations, returning the best-performing version if full success is not achieved. Over successive iterations, HLDA accumulates an internal causal map linking observed errors to reasoning flaws, thus learning from its own mistakes. This feedback mechanism transforms code generation into a reflective learning cycle, where execution-grounded evidence continuously informs improved reasoning. The result is an adaptive, interpretable, and scalable debugging framework that mirrors the human process of testing, understanding, and refinement.

4 Experiments

4.1 Comparison with State-of-the-arts

4.1.1 Simple Programming problem

This section compares our method with several other methods using different LLMs. In table 1, we show our result compared with other methods in the MBPP dataset and the HumanEval dataset, and our method achieves State-of-the-art in both datasets.

4.1.2 Contest level programming problem

Contrast-level programming problems are much more complicated than simple programming problems. It contains complex problem descriptions, and its solutions are more challenging to get. In table 2, we compare our results with several typical methods and the current state-of-the-art.

4.2 Ablation Studies

In this section, all experiments are done using GPT-3.5-turbo and tested on the HumanEval dataset.

4.2.1 Influence of different level feedback

In this part of our study, we evaluate how varying degrees of feedback our feedback module provides affect its performance. This module can deliver input at multiple levels, such as assessing the code's correctness, analyzing specific test cases, and examining the intermediate variables produced during code execution. As illustrated in table 3 of our report, it becomes evident that the LLM's ability to identify bugs and enhance the overall quality of the final output is significantly improved with more comprehensive feedback.

This trend mirrors the human approach to debugging. Just as a programmer equipped with more information can more easily locate and rectify bugs in the code, the LLM's performance in identifying and correcting errors is similarly enhanced with richer feedback. In contrast, limited information can make debugging more challenging and less efficient. Our findings reinforce the notion that the depth and detail of feedback are crucial in effectively guiding both human and machine learning processes in code debugging.

4.2.2 Influence of the temperature

Figure 3: Ablation Study for temperature. Higher temperatures will bring more randomness and hurt the performance of the code generation. Low temperatures will have less creativity and make it difficult to correct the bugs. There is an optimal temperature range where the LLM strikes a balance between creativity and coherence

We study how the temperature parameter affects the code generation performance of LLMs. Temperature controls the randomness in text generation: low values yield more deterministic and conservative outputs, while high values produce more diverse but potentially less coherent results.

As shown in Fig. 3, we observe that moderate temperature levels lead to better performance. At very low temperatures, the model lacks creativity, limiting its ability to explore effective

Table 1: Quantitative results of our proposed architecture in HumanEval and MBPP dataset, the best results are highlighted in **bold**.

method		HumanEval	MBPP	LiveCodeBench
	AlphaCode (Li et al., 2022)	17.1	-	-
	Incoder (Fried et al., 2022)	15.2	17.6	15.3
	CodeX (Brown et al., 2020)	47.0	58.1	17.2
	PalmCoder (Chowdhery et al., 2023)	43.9	32.3	16.7
LLMs(zero-shot prompting)	StarCoder (Li et al., 2023)	33.6	52.7	13.2
	Llama-70B (Touvron et al., 2023)	30.5	45.4	19.4
	Code Llama-7B (Touvron et al., 2023)	33.5	41.4	20.1
	GPT-3.5-turbo (Achiam et al., 2023)	56.4	52.6	22.6
	Claude-instance-1	31.1	26.9	22.1
	GPT-4-turbo (Achiam et al., 2023)	58.6	64.8	26.7
	GPT-4 (Achiam et al., 2023)	66.1	69.3	33.9
	CoT (Wei et al., 2022)	46.9	54.8	29.4
	ReAct (Yao et al., 2022)	56.9	67.0	29.8
	Reflexion (Shinn et al., 2023)	68.1	70.0	30.1
	ToT (Yao et al., 2023)	54.4	65.8	29.4
	RAP (Hao et al., 2023)	63.1	71.4	28.6
With GPT-3.5-turbo	Self-Edit (Zhang et al., 2023)	62.2	56.4	30.1
	Self-Planing (Jiang et al., 2023)	65.2	58.6	31.5
	Self-debugging (Chen et al., 2023)	61.6	60.1	35.8
	INTERVENOR (Wang et al., 2023)	75.6	69.8	37.3
	LATS (Zhou et al., 2023)	83.8	81.1	31.6
	AgentCoder (Huang et al., 2023)	79.9	89.9	40.1
	Ours	**89.6**	**91.3**	**42.1**
	Reflexion (Shinn et al., 2023)	91.0	77.1	35.9
	Self-debugging (Chen et al., 2023)	-	80.6	37.2
With GPT-4	MetaGPT (Hong et al., 2023)	85.9	87.7	36.8
	LATS (Zhou et al., 2023)	94.4	-	40.1
	AgentCoder (Huang et al., 2023)	96.3	91.8	50.3
	Ours	**97.6**	**93.8**	**55.9**
With StarCoder	Ours	67.0	72.1	47.6
With Claude-instance-1	Ours	68.2	81.3	44.5
With PalmCoder	Ours	68.9	79.2	41.9
With Code Llama-7B	Ours	73.7	83.5	42.7
With GPT-4-turbo	Ours	91.4	93.7	48.9

Table 2: Quantitative results of our proposed architecture in contest-level programming dataset, the best results are highlighted in **bold**.

LLM	method	APPS	XcodeEval	CodeContest
	Direct	8.0	17.9	5.5
	CoT(Wei et al., 2022)	7.3	23.6	6.1
GPT-3.5-turbo	Self-Planning(Jiang et al., 2023)	9.3	18.9	6.1
	Analogical(Yasunaga et al., 2023)	6.7	15.1	7.3
	MapCoder(Islam et al., 2024)	11.3	27.4	12.7
	Ours	**15.9**	**33.7**	**17.1**
	Direct	12.7	32.1	12.1
	CoT(Wei et al., 2022)	11.3	36.8	5.5
GPT4	Self-Planning(Jiang et al., 2023)	14.7	34.0	10.9
	Analogical(Yasunaga et al., 2023)	12.0	26.4	10.9
	MapCoder(Islam et al., 2024)	22.0	45.3	28.5
	Ours	**27.8**	**52.2**	**34.8**

fixes. At very high temperatures, increased randomness introduces incoherent or buggy code.

This suggests the existence of an optimal temperature range where the model maintains a balance between creativity and control—producing code that is both innovative and reliable. Tuning temperature is therefore critical for achieving robust and effective code generation.

4.2.3 Influence of the max iteration number

After receiving feedback, our code generator will generate a new code. However, we cannot guarantee that our method will always provide a correct code. Hence, we must set a max iteration number to avoid our method being stuck in a loop. As shown in Fig. 4, we can see that with the number of max iterations increasing, the result will first

Table 3: Ablation study for different level feedback. The result will improve with more feedback.

True/False	Instance-wise True/False	Instance wise Feedback	Intermediate Variables	Pass@1
✗	✗	✗	✗	59.1
✓	✗	✗	✗	67.0
✓	✓	✗	✗	77.4
✓	✓	✓	✗	83.5
✓	✓	✓	✓	89.6

Figure 4: Ablation Study for iteration times. With the increase in iteration times, we also compare the influence of iteration in Relexion and LATS. Notice that in the first several iterations, our method has a significant improvement compared to Reflexion.

Figure 5: Result of the Accuracy after debugging by our architecture. With more feedback, the accuracy will be higher after debugging. This is intuitive, just like humans, provided more information will help humans better locate and correct the bugs.

increase and then remain the same, which indicates that for some challenging problems, it's difficult for LLM to generate a correct code. However, for some median difficulty code tasks, giving LLM several chances will help it develop the correct code. We also compare the performance of LATS and Reflexion when the iteration numbers increase.

As shown in Fig. 4, LATS and our model will have a noticeable performance improvement in the first several iterations. In contrast, the Reflection model does not have a pronounced improvement in the first several iterations. Our analysis of this phenomenon is that LATS and our method will provide high-level explainable feedback rather than low-level implicit feedback. The high-level feedback will help the code generator better understand why the previously code-generated code is wrong and help it better correct its bugs.

4.3 Using our method to debug code

In this part, we explore an experimental approach distinct from previous methods. While earlier methods concentrated on creating accurate code in response to a coding task, and our methodology has demonstrated superior accuracy, our architecture's capabilities extend beyond mere code generation. Inspired by human debugging processes, we were intrigued to discover if our architecture could also effectively debug existing erroneous code.

We made specific alterations to adapt our architecture for debugging rather than code generation. Our architecture comprises five components, but we omitted the code generator in the initial iteration for the debugging task. Since we already had code

containing bugs, generating new code was unnecessary. The other components, however, remained unchanged from their roles in the code generation process.

The method for acquiring flawed code involved using the HumanEval and MBPP datasets. We employed various Large Language Models (LLMs), including GPT-3.5, GPT-4, and LLama, to create code straightforwardly without employing special techniques. The generated code was then tested using the provided test cases, and we collected all code samples that failed these tests. Due to the absence of specialized strategies in code creation, the errors in these samples varied widely, including incorrect function names, input values, and land logical errors.

In the debugging phase, our code executor gathered more comprehensive information than in its previous use to account for the diverse nature of the bugs. This information included specifics like TypeError and AttributeError. The debug module, therefore, had a broader scope of errors to address and correct. Once these initial errors were rectified, the module shifted to identifying and fixing any logical flaws in the code, using the test cases as a guide, akin to the process in our code generation experiments.

Post-debugging, the original flawed code and the feedback from our debugging process were fed back to the code generator. This step was crucial in generating a corrected version of the code based on the erroneous version and the feedback provided. We then evaluated this newly generated code against all test cases to determine its accuracy. Through this comprehensive process, we aimed not only to identify but also to correct a wide range of coding errors, thereby evaluating the effectiveness of our architecture in a debugging context, an area previously unexplored in our research.

To provide a complete understanding of the effectiveness of our different levels of feedback, we experimented with varying levels of feedback, which have similar settings in our first ablation study. The result can be seen in Fig 5

4.4 Multi-function Test

While most existing benchmarks evaluate models on single-function tasks, real-world programming often involves multi-function interactions, where the correctness of one module depends on another. To assess our model's ability to reason across function boundaries, we designed a controlled bench-

Table 4: Accuracy of different methods on multi-function tasks.

Method	GPT-4	Reflexion	AgentCoder	GPT-4 + Our Architecture
Accuracy	41.5%	52.0%	63.5%	**81.0%**

Table 5: Overall token usage and per-problem overhead (HumanEval / MBPP).

Method	HumanEval	MBPP	Tokens (HumanEval / MBPP)	Overhead (HumanEval / MBPP)
MetaGPT	85.9	87.7	138.2K / 206.5K	1248.5 / 1583.6
AgentCoder	96.3	91.8	56.9K / 66.3K	228.7 / 365.9
Ours	**97.6**	**93.8**	63.4K / 75.9K	279.8 / 425.4

mark of 200 multi-function tasks by extending single-function problems from HumanEval and MBPP into multi-component programs.

Each problem consists of 2–4 interdependent functions that together implement a higher-level objective. For instance, one task extends a simple sorting function into a pipeline that combines data parsing, filtering, and sorting, where an error in one sub-function can propagate to others. This design evaluates whether the model can maintain logical consistency and causal reasoning across dependent modules.

During evaluation, our architecture reuses the same planning, execution, and feedback modules but applies debugging iteratively across all functions. If an error in one function affects downstream outputs, the system tracks cross-function variable dependencies to isolate the root cause. This differs from prior methods such as Reflexion and AgentCoder, which operate on each function independently.

As shown in Table 4, our method (GPT-4 + HLDA) achieves an accuracy of 81%, outperforming Reflexion (52%) and AgentCoder (63.5%). This demonstrates that detailed trace-level feedback enables consistent reasoning even under compositional task settings, where function-level coordination is essential. We also observe that intermediate-variable feedback plays a pivotal role in maintaining coherent behavior across modules, highlighting the potential of execution-grounded introspection for large-scale program synthesis.

4.5 Inference Cost

While our approach introduces an additional execution and debugging phase, the overall computational overhead remains moderate. Table 5 summarizes the average token usage and per-problem inference cost on HumanEval and MBPP. Compared to AgentCoder, HLDA incurs slightly higher overhead due to the inclusion of variable tracing and structured feedback generation (approximately +18% tokens), yet it remains significantly more efficient than MetaGPT, which requires extensive multi-agent communication. We view this as a reasonable trade-off: the architecture achieves higher reliability and interpretability at manageable cost.

Notably, most additional computation occurs during the early iterations (typically within the first 3–4 loops), after which the system quickly converges to a stable solution. This demonstrates that structured introspection provides rapid learning signals, enabling efficient correction with minimal repeated inference. In practice, our approach increases per-problem latency by roughly 5–10 seconds while yielding substantial accuracy gains, improving Pass@1 by over 3–5 points across datasets. We also observe that roughly two-thirds of the additional tokens are spent on execution and trace recording, which directly contribute to causal reasoning rather than redundant text generation.

5 Conclusion

In this work, we proposed **HLDA**, a Human-Like Debugging Architecture that redefines code generation as an iterative reasoning and self-correction process rather than a single text-to-code translation. By integrating explicit planning, execution tracing, semantic-level debugging, and structured feedback, HLDA enables large language models to reason over their own execution behavior, identify causal sources of failure, and iteratively refine logic with grounded evidence. Extensive experiments across HumanEval, MBPP, and contest-level programming benchmarks show that HLDA achieves superior accuracy, robustness, and interpretability compared to existing reflection-based systems while maintaining competitive efficiency. More importantly, our results demonstrate that incorporating trace-level introspection fundamentally changes how LLMs approach problem solving—transforming them from reactive generators into reflective reasoners. We believe this paradigm opens new avenues for building generalizable and cognitively aligned code agents capable of continual improvement, scalable debugging, and adaptive reasoning across diverse domains. In future work, we plan to extend HLDA toward multi-function and multi-agent settings, integrating richer forms of execution feedback and tool interaction to further enhance reasoning transparency and autonomy.

Limitations

Despite the strong empirical results of our architecture, several limitations remain. First, our approach depends on the availability and correctness of reference implementations to generate ground truth outputs for pseudo-test cases; if these references are flawed, error propagation may occur. Second, the current framework is tailored to single-function code generation and does not address more complex scenarios involving multiple functions or files. Third, our debug module relies primarily on LLM-based reasoning with execution traces rather than supervised bug localization, which can be less reliable for deeply nested or highly complex code. Additionally, the diversity and validity of LLM-generated pseudo-test cases are not always guaranteed, and ambiguous or underspecified task descriptions can limit performance. Addressing these limitations is an important direction for future work.

AI Disclosure We used ChatGPT solely for grammar correction and language polishing. All research content, literature analysis, and writing were conducted independently by the authors.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, and 1 others. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Nader Akoury, Qian Yang, and Mohit Iyyer. 2023. A framework for exploring player perceptions of llm-generated dialogue in commercial video games. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 2295–2311.

Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, and 1 others. 2021. Program synthesis with large language models. *arXiv preprint arXiv:2108.07732*.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, and 1 others. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.

Yuzhe Cai, Shaoguang Mao, Wenshan Wu, Zehua Wang, Yaobo Liang, Tao Ge, Chenfei Wu, Wang You, Ting Song, Yan Xia, and 1 others. 2023. Low-code llm: Visual programming over llms. *arXiv preprint arXiv:2304.08103*.

Jonathan D Chang, Kiante Brantley, Rajkumar Ramamurthy, Dipendra Misra, and Wen Sun. 2023. Learning to generate better than your llm. *arXiv preprint arXiv:2306.11816*.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde De Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, and 1 others. 2021. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*.

Xinyun Chen, Maxwell Lin, Nathanael Schärli, and Denny Zhou. 2023. Teaching large language models to self-debug. *arXiv preprint arXiv:2304.05128*.

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, and 1 others. 2023. Palm: Scaling language modeling with pathways. *Journal of Machine Learning Research*, 24(240):1–113.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2018. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*.

Daniel Fried, Armen Aghajanyan, Jessy Lin, Sida Wang, Eric Wallace, Freda Shi, Ruiqi Zhong, Wen-tau Yih, Luke Zettlemoyer, and Mike Lewis. 2022. Incoder: A generative model for code infilling and synthesis. *arXiv preprint arXiv:2204.05999*.

Shibo Hao, Yi Gu, Haodi Ma, Joshua Jiahua Hong, Zhen Wang, Daisy Zhe Wang, and Zhiting Hu. 2023. Reasoning with language model is planning with world model. *arXiv preprint arXiv:2305.14992*.

Dan Hendrycks, Steven Basart, Saurav Kadavath, Mantas Mazeika, Akul Arora, Ethan Guo, Collin Burns, Samir Puranik, Horace He, Dawn Song, and 1 others. 2021. Measuring coding challenge competence with apps. *arXiv preprint arXiv:2105.09938*.

Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, and 1 others. 2022. Training compute-optimal large language models. *arXiv preprint arXiv:2203.15556*.

Sirui Hong, Xiawu Zheng, Jonathan Chen, Yuheng Cheng, Jinlin Wang, Ceyao Zhang, Zili Wang, Steven Ka Shing Yau, Zijuan Lin, Liyang Zhou, and 1 others. 2023. Metagpt: Meta programming for multi-agent collaborative framework. *arXiv preprint arXiv:2308.00352*.

Bin Hu, Chenyang Zhao, Pu Zhang, Zihao Zhou, Yuanhang Yang, Zenglin Xu, and Bin Liu. 2023. Enabling efficient interaction between an algorithm agent and an llm: A reinforcement learning approach. *arXiv preprint arXiv:2306.03604*.

Dong Huang, Qingwen Bu, Jie M Zhang, Michael Luck, and Heming Cui. 2023. Agentcoder: Multi-agent-based code generation with iterative testing and optimisation. *arXiv preprint arXiv:2312.13010*.

Md Ashraful Islam, Mohammed Eunus Ali, and Md Rizwan Parvez. 2024. Mapcoder: Multi-agent code generation for competitive problem solving. *arXiv preprint arXiv:2405.11403*.

Xue Jiang, Yihong Dong, Lecheng Wang, Qiwei Shang, and Ge Li. 2023. Self-planning code generation with large language model. *arXiv preprint arXiv:2303.06689*.

Mohammad Abdullah Matin Khan, M Saiful Bari, Xuan Long Do, Weishi Wang, Md Rizwan Parvez, and Shafiq Joty. 2023. xcodeeval: A large scale multilingual multitask benchmark for code understanding, generation, translation and retrieval. *arXiv preprint arXiv:2303.03004*.

Raymond Li, Loubna Ben Allal, Yangtian Zi, Niklas Muennighoff, Denis Kocetkov, Chenghao Mou, Marc Marone, Christopher Akiki, Jia Li, Jenny Chim, and 1 others. 2023. Starcoder: may the source be with you! *arXiv preprint arXiv:2305.06161*.

Yujia Li, David Choi, Junyoung Chung, Nate Kushman, Julian Schrittwieser, Rémi Leblond, Tom Eccles, James Keeling, Felix Gimeno, Agustin Dal Lago, and 1 others. 2022. Competition-level code generation with alphacode. *Science*, 378(6624):1092–1097.

Ansong Ni, Srini Iyer, Dragomir Radev, Veselin Stoyanov, Wen-tau Yih, Sida Wang, and Xi Victoria Lin. 2023. Lever: Learning to verify language-to-code generation with execution. In *International Conference on Machine Learning*, pages 26106–26128. PMLR.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, and 1 others. 2022. Training language models to follow instructions with human feedback. *Advances in Neural Information Processing Systems*, 35:27730–27744.

Baolin Peng, Chunyuan Li, Pengcheng He, Michel Galley, and Jianfeng Gao. 2023. Instruction tuning with gpt-4. *arXiv preprint arXiv:2304.03277*.

Dan Qiao, Chenfei Wu, Yaobo Liang, Juntao Li, and Nan Duan. 2023. Gameeval: Evaluating llms on conversational games. *arXiv preprint arXiv:2308.10032*.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, and 1 others. 2019. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9.

Noah Shinn, Beck Labash, and Ashwin Gopinath. 2023. Reflexion: an autonomous agent with dynamic memory and self-reflection. *arXiv preprint arXiv:2303.11366*.

Vishvesh Soni. 2023. Large language models for enhancing customer lifecycle management. *Journal of Empirical Social Science Studies*, 7(1):67–89.

Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. 2023. Stanford alpaca: An instruction-following llama model. https://github.com/tatsu-lab/stanford_alpaca.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, and 1 others. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Hanbin Wang, Zhenghao Liu, Shuo Wang, Ganqu Cui, Ning Ding, Zhiyuan Liu, and Ge Yu. 2023. Intervenor: Prompt the coding ability of large language models with the interactive chain of repairing. *arXiv preprint arXiv:2311.09868*.

Shuohuan Wang, Yu Sun, Yang Xiang, Zhihua Wu, Siyu Ding, Weibao Gong, Shikun Feng, Junyuan Shang, Yanbin Zhao, Chao Pang, and 1 others. 2021. Ernie 3.0 titan: Exploring larger-scale knowledge enhanced pre-training for language understanding and generation. *arXiv preprint arXiv:2112.12731*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, and 1 others. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in Neural Information Processing Systems*, 35:24824–24837.

William A Woods. 1973. Progress in natural language understanding: an application to lunar geology. In *Proceedings of the June 4-8, 1973, national computer conference and exposition*, pages 441–450.

BigScience Workshop, Teven Le Scao, Angela Fan, Christopher Akiki, Ellie Pavlick, Suzana Ilić, Daniel Hesslow, Roman Castagné, Alexandra Sasha Luccioni, François Yvon, and 1 others. 2022. Bloom: A 176b-parameter open-access multilingual language model. *arXiv preprint arXiv:2211.05100*.

Chunyang Xiao, Marc Dymetman, and Claire Gardent. 2016. Sequence-based structured prediction for semantic parsing. In *Annual meeting of the Association for Computational Linguistics (ACL)*, pages 1341–1350.

Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Thomas L Griffiths, Yuan Cao, and Karthik Narasimhan. 2023. Tree of thoughts: Deliberate problem solving with large language models. *arXiv preprint arXiv:2305.10601*.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2022. React: Synergizing reasoning and acting in language models. *arXiv preprint arXiv:2210.03629*.

Michihiro Yasunaga, Xinyun Chen, Yujia Li, Panupong Pasupat, Jure Leskovec, Percy Liang, Ed H Chi, and Denny Zhou. 2023. Large language models as analogical reasoners. *arXiv preprint arXiv:2310.01714*.

Kechi Zhang, Zhuo Li, Jia Li, Ge Li, and Zhi Jin. 2023. Self-edit: Fault-aware code editor for code generation. *arXiv preprint arXiv:2305.04087*.

Andy Zhou, Kai Yan, Michal Shlapentokh-Rothman, Haohan Wang, and Yu-Xiong Wang. 2023. Language agent tree search unifies reasoning acting and planning in language models. *arXiv preprint arXiv:2310.04406*.

A Implementation Details

A.1 Model Usage

We primarily use GPT-3.5-turbo and GPT-4 as our base language models for both code generation and all LLM-driven modules (pseudo-test generator, debug module). For GPT-3.5-turbo, we set the temperature to 0.2, the maximum generation length to 2048 tokens. For GPT-4 experiments, similar hyperparameters are adopted unless otherwise specified. The batch size for each round of code generation is set to 1 (single problem per inference call), and each stage of the pipeline is executed sequentially.

A.2 Baseline and Evaluation metrics

Evaluation Metrics We use Pass@k as our evaluation metrics which is the same as previous works ((Zhou et al., 2023)(Wang et al., 2023)(Shinn et al., 2023))

Baseline We compare our methods with several different architecture including Chain-of-Thought ((Wei et al., 2022)), ReAct ((Yao et al., 2022)), etc. To better understand the effectiveness of our methods, we use different Large Language Models, including GPT-3.5-turbo and GPT-4, etc., as the LLM to test our method and other methods.

A.3 dataset

In our experiments, we use five different datasets:
MBPP dataset(Austin et al., 2021): The MBPP dataset contains basic Python programming problems stated in natural language. The dataset contains 974 problems. For every problem, the dataset contains three different test cases. Following the previous methods((Ni et al., 2023)), we use the first test cases as part of the prompt to generate the template containing the function signatures. We use all three test cases during the test, and only when the generated code passes all three test cases do we think the generated code is correct. If the generated code fails in any test case, we will think the generated code is wrong and have bugs.
HumanEval dataset(Chen et al., 2021): The HumanEval dataset provides 164 comment descriptions of functions paired with a canonical implementation of each function and several input-output pairs that the function should pass. We follow the same evaluation method as the MBPP dataset.
APPS dataset(Hendrycks et al., 2021) The APPS dataset consists of problems collected from different open-access coding websites such as Code-

forces and Kattis. There are 10,000 coding problems in total, with 131,836 test cases. Due to the computing restrain, we use 169 problems to test our methods.

XcodeEval dataset(Khan et al., 2023) The XcodeEval dataset consists of over 7.5k problem with multiple tasks. In our experiment, we only focus on the code generation tasks and we use 178 problems to test our methods.

CodeContest dataset(Li et al., 2022) The CodeContest dataset is a competitive programming dataset for machine-learning that was used when training AlphaCode. In our experiment, we used 192 problems to test our methods.

B Prompts for different level feedback

As shown in Table 6, we provide the difference between different levels of feedback. Moreover, in this section, we provide specific examples for different levels of feedback in Table 7

C Prompt Template

Planning Module

```
You are an expert problem solver. Given a natural language
    programming task,
decompose it into a plan of reasoning steps before writing
    code. Your plan should include:

1. Clarify the problem requirements.
2. Choose a suitable algorithm or data structure.
3. Identify edge cases to consider.
4. Describe the step-by-step logic to solve the task.

Task:
"Write a function that returns True if a string is a
    palindrome, ignoring spaces and case."
```

Listing 1: Planning Module Prompt

Code Generator

```
You are a code generation assistant. Based on the task and
    the reasoning plan,
write clean and correct Python code.

Task:
"Write a function that returns True if a string is a
    palindrome, ignoring spaces and case."

Function signature:
def is_palindrome(s: str) -> boolean

Plan:
1. Normalize the string by removing spaces and converting to
    lowercase.
2. Compare the normalized string to its reverse.
3. Return True if they are equal, False otherwise.
```

Listing 2: Code Generator Prompt

Pseudo-Test Case Generator

```
You are a test case generator. Without access to the
    implementation,
write diverse test cases that check the correctness of the
    following function description.

Function Description:
"Return True if a string is a palindrome, ignoring spaces and
    case."

Function signature:
def is_palindrome(s: str) -> boolean

Generate:
- 2 basic tests
- 2 edge tests (e.g., empty string, symbols)
- 1 stress test (long string)
```

Listing 3: Pseudo-Test Case Generator Prompt

Debug Module (Ground Truth)

```
You are a debugging assistant. Analyze the execution trace
    and test failures
to identify possible bugs in the code.

Task:
"Return True if a string is a palindrome, ignoring spaces and
    case."

Code:
def is_palindrome(s):
    s_reverse = [s::-1]
    s == s[::-1]

Test Failure:
assert is_palindrome("Race car") == True
-> Got False

Trace:
Input: "Race car"
s_reverse = "rac ecaR"
s = "Race car"
Output: False
```

Listing 4: Debug Module with Ground Truth Prompt

Debug Module (Pseudo Test Case)

```
You are a debugging expert. Given:
- A failed test case (pseudo-generated),
- A code snippet,
- And the expected + actual outputs,

you must determine:

Step 1: Whether the test case is valid.
Step 2: If valid, identify the bug and suggest a correction.
If invalid, return a correction for the test case.

Task:
"Return True if a string is a palindrome, ignoring spaces and
    case."

Code:
def is_palindrome(s):
    s_reverse = [s::-1]
    s == s[::-1]

Test Failure:
assert is_palindrome("Race car") == True
-> Got False

Trace:
Input: "Race car"
s_reverse = "rac ecaR"
s = "Race car"
Output: False
```

Listing 5: Debug Module with Pseudo Test Case Prompt

Table 6: Examples of Feedback at Varying Levels of Detail

Feedback Type	Example
Basic Feedback	Your code is **wrong**.
Instance-wise accurate/false feedback	Your code is **wrong** when the **test case** is [input].
Instance-wise Feedback	Your code is **wrong**, when the **test case** is [input], **your code output** is [output], **the right output** is [expected].
Intermediate Variable Feedback	Your code is **wrong**, when the **test case** is [input], **your code output** is [output], **the right output** is [expected]. When your code is running, the **intermediate variables** are [variable traces].

Feedback Module

```
You are a feedback writer. Based on the error diagnosis and
    original code,
generate a natural language explanation for the error, and a
    revised plan
for code regeneration.

Code:
def is_palindrome(s):
    s_reverse = [s::-1]
    s == s[::-1]

Bug:
Failed on mixed-case and spacing input.

Feedback:
The current implementation doesn't handle spaces and case
    normalization.
Please update your function to preprocess the input by
    removing spaces
and converting to lowercase before checking for a palindrome.
```

Listing 6: Feedback Module Prompt

D   More examples

Q: Write a python function to count the number of squares in a rectangle.
A: def count_Squares(m,n):
    return (min(m, n) * (min(m, n) + 1) * (2 * min(m, n) + 1)) // 6
Q: Your generated code is wrong when the test case is count_Squares(4,3): Your code output of the test case is 14, the correct output of the test case is 20, the local variables when running your code are {'m': 4, 'n': 3}. You should calculate the number of squares of size i x i that can fit in the rectangle using the formula (m - i + 1) * (n - i + 1). please fix your code.
A: def count_Squares(m, n):
    total_squares = 0
    for i in range(1, min(m, n) + 1):
        total_squares += (m - i + 1) * (n - i + 1)
    return total_squares

- -

Q: Write a function to convert snake case string to camel case string..
A: def snake_to_camel(word):
    parts = word.split('_')
    return parts[0] + ''.join(x.title() for x in parts[1:])
Q: Your generated code is wrong when the test case is snake_to_camel('python_program'). Your code output of the test case is 'pythonProgram', the correct output of the test case is 'PythonProgram', the local variables when running your code are {'word': 'python_program', 'parts': ['python', 'program']}. You should consider the first word. please fix your code.
A: def snake_to_camel(word):
    parts = word.split('_')
    return parts[0].title() + ''.join(x.title() for x in parts[1:])

Table 7: Illustrative Examples Across Different Feedback Levels

Original Questions: Write a python function to find the minimum number of rotations required to get the same string.

Original Code:

```python
def find_Rotations(str):
    n = len(str)
    rotation = 0
    for i in range(1, n):
        if str == str[i:] + str[:i]:
            rotation = i
            break
    return rotation
```

Feedback Level	Description	Example
Level 1: Basic Feedback	Only tells the user whether the code is right or wrong. No further details.	**Feedback:** "Your code is **wrong**." **No additional explanation.**
Level 2: Instance-wise accurate/-false feedback	Indicates the specific test case for which the code is incorrect.	**Feedback:** "Your code is **wrong** when the **test case** is 'ab'."
Level 3: Instance-wise feedback	Adds the incorrect output and the expected correct output for the failing test case.	**Feedback:** "Your code is **wrong** when the **test case** is 'ab', **your code output** is 0, **the right output** is 2."
Level 4: Intermediate Variable-Level Feedback	Provides complete trace-level feedback including intermediate values during execution.	**Feedback:** "Your code is **wrong** when the **test case** is 'ab', **your code output** is 0, **the right output** is 2. When your code is running, the **intermediate variables** are {'str': 'ab', 'n': 2, 'rotation': 0, 'i': 1}."