Pre-Trained Model Reusability Evaluation for Small-Data Transfer Learning

Abstract

We study *model reusability evaluation* (MRE) for source pre-trained models: evaluating their transfer learning performance to new target tasks. In special, we focus on the setting under which the target training datasets are small, making it difficult to produce reliable MRE scores using them. Under this situation, we propose *synergistic learning* for building the task-model metric, which can be realized by collecting a set of pre-trained models and asking a group of data providers to participate. We provide theoretical guarantees to show that the learned task-model metric distances can serve as trustworthy MRE scores, and propose synergistic learning algorithms and models for general learning tasks. Experiments show that the MRE models learned by synergistic learning can generate significantly more reliable MRE scores than existing approaches for small-data transfer learning.

1 Introduction

When selecting a model from a big model pool for doing model transfer, one has to do model reusability evaluation (MRE) first: evaluating the transfer learning performance of the models to the target task and identifying the best model. The role of MRE is crucial since no matter how good the transfer learning strategy is, incorrect MRE would still lead to the danger of negative transfer. MRE has received growing attention in recent years [Achille et al., 2019, Tran et al., 2019, Nguyen et al., 2020, Wu et al., 2020, Ding and Zhou, 2020, You et al., 2021]. But most existing studies focus on large-data MRE, under which the target dataset is sufficiently large.

In this work, we focus on small-data MRE, under which the target training datasets are small. Reusing pre-trained models is essential under the small-data scenario since learning from scratch is difficult. Unfortunately, large-data MRE approaches are usually invalid for small data since they usually focus more on simplicity and efficiency, but not generalization and robustness, which are essential for small-data MRE. It is indeed challenging to obtain reliable MRE results under the small-data scenario due to the fundamental burden set by the laws of statistics.

Our solution is based on two observations. First, model reusability usually depends on the task-model relationship other than the task-independent property of any specific small sample. We could grasp this relationship by meta-learning an MRE function among tasks and models. Second, this learning process is often realizable in practice, in special for large model zoo platforms where sufficient pre-trained models and data providers are available. Based on these observations, we conduct the following studies in this paper:

Problem formuation. We provide the formulation of small-data MRE and synergistic learning to learn the MRE function by metric learning. Synergisitc learning works for general learning scenarios beyond classification, on which most previous MRE approaches focus.

Theoretical analysis. We propose access risk analysis showing that the MRE model learned by synergistic learning guarantees to generate reliable MRE scores. The theory not only provides guarantee

Figure 1: The illustration of synergistic learning for MRE. The left part illustrates the synergistic learning process, which is the preparation stage for the MRE process illustrated on the right part.

even for using non-convex deep networks as the MRE model, but also motivates feature pre-training in synergistic learning.

Algorithm and model design. We propose synergistic learning algorithms and MRE model structures for general learning tasks, which have the auxiliary advantage of protecting data privacy. Meanwhile, we propose a more elaborate MRE model strucuture for classification.

Experimental verification. Experimental results show that synergistic learning can generate significantly more reliable MRE scores for small-data transfer learning than existing MRE approaches.

2 Problem Setup

In this section, we provide the formal definition of small-data MRE and synergistic learning.

2.1 Small-Data MRE

Denote by $\mathcal{Z} = \mathcal{X} \times \mathcal{Y}$ the observation space, in which $\mathcal{X}, \mathcal{Y}$ are the input and output spaces respectively. A target learning task μ can be represented by a probability measure[1] $\mu(x, y)$ over some $\mathcal{Z}_\mu \subseteq \mathcal{Z}$. Furthermore, we assume that all μ are drawn from the task environment $\mathcal{T}$, a probability measure over the space of all target tasks.

In small-data MRE, target tasks μ are drawn from $\mathcal{T}$. For each μ, the objective is to learn a prediction rule f_μ such that for any observation $(x, y) \sim \mu$, $f_\mu(x)$ is close to y. The learner of μ will be given a target training dataset S_μ, a set of pre-trained models H, a model transfer strategy π and an MRE function v_π. $S_\mu = \{z_k = (x_k, y_k)\}_{k=1}^K$ is a sample drawn from μ such that the sample size K is a small number. H is the pre-trained model set in which each model $h \in H$ is drawn from the model environment $\mathcal{M}$, a probability measure over the space of all pre-trained models. We assume that the models in H are sampled independently from μ while different H can be given for different μ. $\pi(S_\mu, h)$ is a transfer learning strategy which can be used to transfer a pre-trained model h into f_μ using S_μ. The MRE function $v_\pi(S_\mu, h)$ is a real-valued function taking S_μ and h as the inputs and outputing the transferability score[2]. Without loss of generality, among all possible v, we define v^* as the optimal MRE function such that for any $\mu, S_\mu, h_1, h_2, v^*(S_\mu, h_1) < v^*(S_\mu, h_2)$ if and only if h_1 has better transfer learning performance with S_μ than h_2[3]. As discussed in Section 1, we assume that *the ground-truth model transferability depends only on the target task μ but does not depend on the random draw of S_μ from μ*, i.e. $\forall S_\mu, S'_\mu \sim \mu, v^*(S_\mu) = v^*(S'_\mu)$. Thus we can use the notation $v^*(\mu, h)$ instead of $v^*(S_\mu, h)$ for any S_μ, h.

---

[1]We will use μ to denote both a task and its probability measure below when there is no ambiguity.

[2]We assume that π is fixed for any target task. Thus below we use v instead of v_π to simplify notations.

[3]For the convenience of analysis, we assume that the MRE score needs to be *monotonically decreasing* w.r.t. transfer performance, while many previous studies made the opposite assumption. Obviously, these two views can be made equivalent by multiplying -1 to the scores.

2.2 Synergistic Learning

Synergistic learning is the preparation stage for learning an MRE function $\hat{v}$ that accurately approximate v^* before any MRE problem defined in Section 2.1 starts. A synergistic learning process works with the following three prerequisites:

- A set of pre-trained models $H_{\text{SynLearn}} = \{h_k\}_{k=1}^{N_m}$ drawn from $\mathcal{M}$ are given. Note that the models in this set could be different from models given in any future MRE problems;

- A set of data providers $\mathcal{D} = \{\mathcal{Z}_d\}_{d=1}^{D}$ participate in learning, such that each data provider represents an observation subspace $\mathcal{Z}_d \subseteq \mathcal{Z}$. Furthermore, $\cup \mathcal{Z}_d = \mathcal{Z}$. We define the closure of any task $\mu \sim \mathcal{T}$ as $\bar{\mathcal{Z}}_\mu = \min_L \{\mathcal{Z}_{d_1}, \mathcal{Z}_{d_2}, \ldots \mathcal{Z}_{d_L}\}$ s.t. $\mathcal{Z}_\mu \subseteq \cup_{l=1}^{L} \mathcal{Z}_{d_l}$.

- A validation MRE function v_{valid} is provided for synergistic learning. v_{valid} is unbiased between any task and model[4]: $\forall \mu, h, v_{valid}(\mu, h) = \mathbb{E}_{S_\mu \sim \mu}[v_{valid}(S_\mu, h)] = v^*(\mu, h)$.

The basic idea of synergistic learning is to establish a metric $\hat{v}(S_\mu, h)$ between the target training datasets and the models so that the metric distance could be used as the MRE score. In Section 4, we will show that learning $\hat{v}$ only requires the data providers to answer two kinds of queries:

- SQUERY($\psi_s, \mathcal{Z}_d, \mu, M$): a *single* data provider $\mathcal{Z}_d$ is queried to sample M observations from a given probability measure μ over $\mathcal{Z}_d$, and return the output of $\psi_s(\{z_i\}_{i=1}^{M})$, a function of the observations.

- MQUERY($\psi_m, \{\mathcal{Z}_{d_i}\}_{i=1}^{Q}, \{\mu_i\}_{i=1}^{Q}, \{M_i\}_{i=1}^{Q}$): *multiple* data providers $\{\mathcal{Z}_{d_i}\}_{i=1}^{Q}$ are queried jointly. Each data provider $\mathcal{Z}_{d_i}$ sample M_i observations from a given probability measure μ_i over $\mathcal{Z}_{d_i}$. Aggregating the sampled observations from all data providers, the output of $\psi_m(\{z_{1,j}\}_{j=1}^{M_1}, \{z_{2,j}\}_{j=1}^{M_2}, \ldots, \{z_{Q,j}\}_{j=1}^{M_Q})$, a function of all observations, is returned. Furthermore, ψ_m cannot be realized by aggregating multiple SQUERY.

The main difference between these two queries lies in the scope of involved data providers, which is important when the data privacy is a sensitive factor. SQUERY is answered by a single data provider. How this kind of queries can be answered in privacy-guaranteed ways receives many studies in the literature [Konečný et al., 2016, Zinkevich et al., 2010]. In contrast, MQUERY needs to be answered by multiple data providers jointly. Protecting data privacy is much harder in this situation since their data need to be aggregated. For this reason, we set an auxiliary target of reducing the number of times to use MQUERY.

3 Theoretical Analysis

In this section, we discuss the theoretical foundation of synergistic learning. Recall that our goal is to learn $\hat{v}$ that approximates v^*. We assume that $\hat{v}$ consists of three modules: task representation module $g_\mu(S_\mu)$, model representation module $g_\mu(h)$ and metric module $d_\theta(c(S_\mu), c(h))$ in which $c(S_\mu)$ and $c(h)$ are outputs of $g_\mu(S_\mu)$ and $g_h(h)$ meanwhile θ is the learnable parameter of $d_\theta(c(S_\mu), c(h))$. The task and model representation modules transfer target training dataset S_μ and pre-trained model h into their representations $c(S_\mu)$ and $c(h)$. The metric module then calculates the metric distance between $c(S_\mu)$ and $c(h)$ as the MRE score. In this section, we assume that the two representation modules are fixed and focus on learning the metric module. Thus the learnable parameter for $\hat{v}$ is θ.

For metric-based synergistic learning, we assume that N_m pre-trained models $\{h_k\}_{k=1}^{N_m}$ sampled from $\mathcal{M}$, N_t tasks $\{\mu_i\}_{i=1}^{N_t}$ sampled from $\mathcal{T}$ and N_S target training datasets $\{S_{\mu_i,j}\}_{j=1}^{N_S}$ sampled from each task μ_i are used for training. We also assume that for any pair of h_i and $S_{\mu_j,k}$, the ground-truth MRE score $v^*(\mu_i, h_k)$ are given[5]. Define $r_{v^*}(S_\mu, S_{\mu'}, h, h'; \hat{v})$ as $\mathbf{I}[\Delta_{v^*}(\mu, \mu', h, h') < 0]\mathbf{I}[\Delta_{\hat{v}}(S_\mu, S_{\mu'}, h, h') \geq 0]$ in which $\Delta_{v^*}(\mu, \mu', h, h') = v^*(\mu, h) - v(\mu', h')$, $\Delta_{\hat{v}}(S_\mu, S_{\mu'}, h, h') = \hat{v}(S_\mu, h) - v(S_{\mu'}, h')$ and $\mathbf{I}$ is the indicator function. Since v^* is the ground-truth MRE function, a desirable $\hat{v}$ should minimize

$$R(\hat{v}) = \mathbb{E}\big[r_{v^*}(S_\mu, S_{\mu'}, h, h'; \hat{v})\big],$$

---

[4]Even though v_{valid} is unbiased, it may have high variance when S_μ is small. Thus v_{valid} can not be used directly for small-data MRE.

[5]We show how the tasks, models and training datasets are sampled, and how the ground-truth MRE scores v^* can be obtained by using SQUERY and MQUERY in Section 4.

where the expectation is taken over $S_\mu \sim \mu, S_{\mu'} \sim \mu', \mu, \mu' \sim \mathcal{T}, h, h' \sim \mathcal{M}$. While for the convenience of optimization and analysis, we define our objective using the triplet surrogate loss. Define $r_{v^*}^\gamma(S_\mu, S_{\mu'}, h, h'; \hat{v})$ as $\mathbf{I}[\Delta_{v^*}(\mu, \mu', h, h') < 0][\Delta_{\hat{v}}(S_\mu, S_{\mu'}, h, h') + \gamma]_+$ in which $[x]_+ = \max\{x, 0\}$ and $\gamma > 0$. When $\gamma > 1$, $r_{v^*}^\gamma$ upper bounds r_{v^*}. Meanwhile, $r_{v^*}^\gamma$ is consistent with r_{v^*} since $r_{v^*}^\gamma(S_\mu, S_{\mu'}, h, h'; \hat{v}) = 0$ indicates that $r_{v^*}(S_\mu, S_{\mu'}, h, h'; \hat{v}) = 0$. Therefore, we define our goal as minimizing the following expected risk

$$R^\gamma(\hat{v}) = \mathbb{E}\big[r_{v^*}^\gamma(S_\mu, S_{\mu'}, h, h'; \hat{v})\big]. \tag{1}$$

A possible way to achieve this goal is to minimize the following empirical risk

$$\hat{R}^\gamma(\hat{v}) = \frac{1}{(N_t N_S N_m)^2} \sum \big[r_{v^*}^\gamma(S_\mu, S_{\mu'}, h_k, h_{k'}; \hat{v})\big] \tag{2}$$

where the summation is taken over all models, tasks and datasets used for training. We want to know whether minimizing the empirical risk $\hat{R}^\gamma(\hat{v})$ indeed leads to the minimization of the expected risk $R^\gamma(\hat{v})$. Denote by Θ the parameter space for θ and use $\hat{v}_\theta$ to denote the $\hat{v}$ with learnable parameter θ. We provide an access risk bound showing the effectiveness of minimizing the above empirical risk. Use $\bar{G}_\theta(S_\mu, S_{\mu'}, h, h')$ to denote $[\Delta_{\hat{v}_\theta}(S_\mu, S_{\mu'}, h, h') + \gamma]_+$. Additionally, we assume that $\nabla[\bar{G}_\theta(S_\mu, S_{\mu'}, h, h')] = 0$ when $\bar{G}_\theta(S_\mu, S_{\mu'}, h, h') = 0$. Furthermore, let

$$\nabla[\hat{R}(\bar{G}_\theta)] = \frac{1}{(N_t N_S N_m)^2} \sum \|\nabla^-[S_\mu, S_{\mu'}, h, h']\|,$$

in which the summation is taken over all tasks, datasets and models used for training and we have $\nabla^-[S_\mu, S_{\mu'}, h, h'] = \mathbf{I}[\Delta_{v^*}(\mu, \mu', h, h') < 0]\nabla[\bar{G}_\theta(S_\mu, S_{\mu'}, h, h')]$. Meanwhile, we denote $V = \max_{i \in [N_t]} \mathbb{E}_{S_{\mu_i} \sim \mu_i}[c^2(S_{\mu_i})]$. Now we are ready to state the following theorem whose proof is provided in the appendix (Section A).

Theorem 3.1. *Under Assumption A.1, there exist optimal parameter $\theta^* \in \Theta$ and constant $\beta > 0$, $\forall \theta \in \Theta$, the following event*

$$R^\gamma(\hat{v}_\theta) - R^\gamma(\hat{v}_{\theta^*}) \leq \beta\big[\nabla[\hat{R}(\bar{G}_\theta)] + \Delta(N_t, N_m, N_S)\big]$$

holds with high probability, in which $\Delta(N_t, N_m, N_S) = \tilde{O}(1/\sqrt{N_t}, 1/\sqrt{N_m}, V/\sqrt{N_S}, 1/N_S)$.

Theorem 3.1 shows several interesting insights. First, $\nabla[\hat{R}(\bar{G}_\theta)]$ is the gradient norm of the metric distance gaps from the training data. The bound shows that the access risk will be small when the gradient norm tends to zero, even when the global minimum of the empirical risk has not been reached. This makes the bound informative when non-convex models, such as DNNs, are used. Second, the bound has the normal $O(1/\sqrt{N_t}), O(1/\sqrt{N_m})$ sample complexity dependence for both tasks and models. This is in agreement with our intuition such that lacking any of the tasks and models would lead to the failure of learning. Finally, the most interesting take-away is the sample complexity for target datasets in each task, which has a dependence of the feature variance V. If V is small, the order becomes $O(1/N_S)$ instead of $O(1/\sqrt{N_S})$, a significant drop for the number of the training datasets. In Section 4, we show that this result inspires us to include feature variance reduction in the synergistic learning process, which would significantly reduce using MQUERY.

4 Learning Method

In this section, we introduce the synergistic learning algorithm and the MRE model.

4.1 Synergistic Learning Algorithm

The realization of synergistic learning is illustrated in Algorithm 1. In this section, besides the step of learning $\hat{v}$ (Line 11) discussed in Section 3, we discuss other crucial steps below in general. We consider two general synergistic learning settings. One is named *isolated closure setting*, which indicates that any task closure includes a single data provider. Otherwise, we name it *grouped closure setting*, which indicates that there exist multi-data-provider task closures.

Task and model sampling (Line 8). To generate the training data for synergistic learning, tasks and models are needed be sampled. At this stage, no interaction to the data providers is needed.

Algorithm 1 Synergistic Learning

1: **Given**: model set H_{SynLearn}, data providers $\mathcal{D}$.
2: **if** *Feature Pre-Training* **then**
3:    **repeat**
4:       $L_{decom}(\mathcal{Z}_d) \leftarrow \texttt{SQUERY}(\mathcal{Z}_d), d = 1, \ldots, D; \texttt{UPDATE}(g_\mu; \sum_{d=1}^{D} L_{decom}(\mathcal{Z}_d));$
5:    **until** reach end.
6: **end if**
7: **repeat**
8:    *Task & Model Sampling*: $\mu_1, \mu_2 \ldots, \mu_t \sim \mathcal{T}, h_1, h_2 \ldots, h_m \sim \mathcal{M};$
9:    *Reusability Validation*: $g(\mu_i, \mathcal{Z}_d, h_k) \leftarrow \texttt{SQUERY}(\mathcal{Z}_d),$
      $v^*(\mu_i, h_k) \leftarrow \texttt{COMBINE}[\{\psi(\mu_i, \mathcal{Z}_d, h_k)\}_{d=1}^{|\bar{\mathcal{Z}}_{\mu_i}|}], i \in [t], k \in [m], d \in [\bar{\mathcal{Z}}_{\mu_i}];$
10:    *Target Dataset Generation*: $S_{\mu_i} \leftarrow \texttt{MQUERY}(\bar{\mathcal{Z}}_{\mu_i}), i = 1, \ldots, t;$
11:    $\texttt{UPDATE}(\hat{v}; \{S_{\mu_i}\}_{i=1}^{t}, \{h_k\}_{k=1}^{m}, \{v^*(\mu_i, h_k)\}_{i,k=1}^{t,m});$
12: **until** reach end.

Reusability validation (Line 9). The objective for reusability validation is to acquire value of v^* between any pairs of task and model that are sampled. In general, this can be done by sending models to the data providers and estimate v^* using v_{valid}. Under the isolated closure setting, only $\texttt{SQUERY}$ is needed obviously. We could ask the data providers to use sufficiently large data, making v_{valid} an accurate estimator. But the key challenge appears under the grouped closure setting since the statistics used for calculating v_{valid} should be obtained from multiple providers at the same time. To achieve this by $\texttt{SQUERY}$, we require v_{valid} to have a special structure. Specifically, for task μ, let $S_\mu(\mathcal{Z}_d)$ be a sample generated from the marginal distribution of μ over $\mathcal{Z}_d$, a member of its task closure. We require $v_{valid}(\mu, h) = \texttt{COMBINE}[\{\psi(\mu, \mathcal{Z}_d, h)\}_{d=1}^{|\bar{\mathcal{Z}}_\mu|}]$, in which $\psi(\mu, \mathcal{Z}_d, h) = \mathbb{E}_{S_\mu(\mathcal{Z}_d) \sim \mu(\mathcal{Z}_d)}[\psi(S_\mu(\mathcal{Z}_d), h)]$. In this construction, $\psi(S_\mu(\mathcal{Z}_d), h)$ is a function over single data providers and $\texttt{COMBINE}$ is an aggregation function decided by specific MRE function, thus only $\texttt{SQUERY}$ is needed for calculation.

Target dataset generation (Line 10). For isolated closure setting, this step can be done by sampling from a data provider using $\texttt{SQUERY}$. However, for grouped closure setting, $\texttt{MQUERY}$ is necessary for this step since the target datasets must include the raw data. This issue can be relieved by the insight brought from Theorem 3.1: For each task, the number of the target data needed is closely related to the data variance. A feature pre-training stage can be introduced to reduce using $\texttt{MQUERY}$.

Feature pre-training (Line 2-6). Feature pre-training is the preparation stage for synergistic learning. It is participated by all data providers, aiming at learning a feature extractor g_μ which could output low-variance features for the raw data. Once g_μ is learned, it would be integrated into the MRE model. As a result, in synergstic learning, the data providers only need to use much fewer data for answering $\texttt{MQUERY}$. On the other hand, the feature pre-training stage itself should be done by using only $\texttt{SQUERY}$. We argue that this can be realized by using learning objectives which are *decomposable w.r.t. the data providers*. More specifically, a decomposable objective is the summation of individual objectives, such that each individual objective L_{decom}^d only takes the data from a single data provider $\mathcal{Z}_d$ as its input. Then the purpose of the queries reduces to calculating each L_{decom}^d, which can be done by $\texttt{SQUERY}$ as expected.

Due to space limitation, we provide more details on how to implement the above synergistic learning steps to different learning scenarios in Section B.

4.2 MRE Model

First, we introduce the basic structure of the MRE model defined in Section 3, which is illustrated in (a) of Figure 2. For simplicity, we will use shorthand notations c_μ, c_h to take the places of $c(S_\mu), c(h)$ when there is no ambiguity. In this model, the target data is first processed by the task backbone to generate the feature c_μ. Afterwards, a task transform module is responsible to generate the task representation ϕ_μ which aggregates all the information from the target dataset. For isolated closure setting, the task transform module can be simply an instance-wise averaging operation. In correspondence, before the model feature backbone, a model specification generator is introduced which can be any function that transforms a model into a vector. The model feature c_h is

Figure 2: The models proposed for synergistic learning. (a) illustrates the basic model. (b) and (c) illustrate the task and model transform modules (TMs) used in classification. (d) illustrates the model ensembler. The components within the dashed box of the same color are the same.

then transformed into the model representation ϕ_h using the model transform module. For isolated closure setting, the model transform module can usually be omitted, i.e. $c_h = \phi_h$.

For many learning scenarios, using more elaborate MRE model structure is often useful. A typical example is classification. We provide the general formulation of small-data transfer learning for classification. A target task μ has L_T classes $\{y_l\}_{l=1}^{L_T}$ to distinguish, in which all the classes belong to the task class universe $\mathcal{Y}_T$. Meanwhile, for a L_M-way classification model h, we denote by $\{\hat{y}_{l'}\}_{l'=1}^{L_M}$ the classes that the models are trained on. We assume that all the model classes belong to the model class universe $\mathcal{Y}_M$, which could be different from $\mathcal{Y}_T$. To reuse a pre-trained classification model on a new classification task, We consider the popular transfer strategy of head retrain: the learner just fixes the feature backbone of the model and retrain the prediction heads using the target data. Head retrain is a more proper strategy than global fine-tuning for small-data transfer learning.

The overall structure of the MRE model for classification follows the basic model, but the task and model transform modules have more complex structures. For the task transform module ((b) of Figure 2), we take care of modeling the relationship among task classes. On one hand, instead of directly generating the feature representation of the whole task ϕ_μ, the module generates the features $\{\phi_\mu^l\}_{l=1}^{L_T}$ for all task classes first, and then aggregate them to form ϕ_μ. Any set-to-set transform module, such as Deep Sets [Zaheer et al., 2017] and Transformer [Vaswani et al., 2017, Ye et al., 2020], can be used. What is essential here is to generate the feature for one task class based on the context information from all other task classes.

More importantly, we propose an attention-based model transform module. This module is motivated by our observations during studying MRE: there is a close connection between $p(y_l, \hat{y}_{l'})$ and model reusability for classification, which is also pointed out by recent studies [Tran et al., 2019, Nguyen et al., 2020]. The module is illustrated in (c) of Figure 2. First, the module takes both the model and task class features $\{c_h^{l'}\}_{l'=1}^{L_M}, \{c_\mu^l\}_{l=1}^{L_T}$ as its inputs and transform them into the *model-attention-aware task class features* $\{\phi_h^l\}_{l=1}^{L_T}$. Subsequently, $\{\phi_h^l\}_{l=1}^{L_T}$ are aggregated to form the model feature ϕ_h. The core component of this module is the model ensembler ((d) of Figure 2). For a pair of model and task classes $y_l, \hat{y}_{l'}$, the model ensembler calculates the attention weight of y_l to $\hat{y}_{l'}$, which is $w_{l,l'}$, with the inner-product attention. And then, the model class features are linearly combined by the attention weights to form ϕ_h^l which represents the selected model class information on y_l. We require $w_{l,l'}$ to be closely related to $p(y_l, \hat{y}_{l'})$ to make it represent the correlation between y_l and $\hat{y}_{l'}$. Therefore, besides the metric loss defined in Equation 2, we introduce an additional *attention supervision loss* to supervise the learning of attention weights. For $w_{l,l'}$, we treat it as the output probability of a binary classifier. The training labels are generated from $p(y_l, \hat{y}_{l'})$. To be specific, we set the label to be one if $p(y_l|\hat{y}_{l'}) > \gamma_1, p(\hat{y}_{l'}|y_l) > \gamma_2$ and zero otherwise, in which γ_1, γ_2 are two thresholds. And then, the attention supervision loss is calculated from the logistic loss. Finally, the overall training loss is formulated as

$$L_{all} = L_{metric} + w_{att}L_{att}, \tag{3}$$

in which L_{metric} is the small-batch version of the metric loss defined in Equation 2, L_{att} is the attention supervision loss defined above, and w_{att} is the weight for L_{att}.

| (a) MNIST (full data) | (b) MNIST (part data) | (c) CIFAR-10 (full data) | (d) CIFAR-10 (part data) |

Figure 3: t-SNE visualization of the learned metric on MNIST and CIFAR-10. (a) and (c) show the results learned with full data. (b) and (d) show the results learned with feature pre-training and part data. The class names for the data clusters (dot markers) are annotated. The detection models (cross markers) have the same color to their corresponding classes (better view in color mode).

| (a) In-distribution domain 1 | (b) In-distribution domain 2 | (c) In-distribution domain 3 |
| (d) Out-distribution domain 1 | (e) Out-distribution domain 2 | (f) Out-distribution domain 3 |

Figure 4: Performance comparison on dSprites: the MRE score rank vs. the true performance rank for MSE (left subfigure) and synergistic learning (right subfigure). (a-c) show in-distribution results on three random domains, and (d-f) show out-distribution results accordingly. The subfigure titles are the indexes of the domain factors. Please refer to Section D for more results.

5 Experiments

In the experiments, we first do metric visualization to verify whether synergistic learning can learn meaningful metric space. Furthermore, we conduct experiments for both in-dataset and cross-dataset MRE to verify the performance of synergistic learning. All the experiments are conducted on servers with NVIDIA Tesla V100 GPUs. The code is implemented using Tensorflow [Abadi et al., 2016] under Apache License 2.0 and is available on http://xxx.xxx.xxx. More details of the experimental setups are discussed in Section C and more experimental results are included in Section D.

5.1 Metric Visualization

We adopt two ten-class datasets MNIST [LeCun et al., 1998] and CIFAR-10 [Krizhevsky, 2009] to visualize the task-model metric learned by synergistic learning. For each dataset, we randomly generated 20 five-class pre-trained models for synergistic learning and another 20 models for testing. We treat each model as five detectors for the corresponding classes and try to use synergistic learning to obtain the detector-data metric. We consider two settings of synergistic learning. The first is learning with full data: all training sets are used for metric learning and there is no feature pre-training stage. The second is learning with part data: 10% of the training set for each class is used for metric learning, and there is a feature pre-training stage involved using the full training set. Figure 3 illustrates the t-SNE [Maaten and Hinton, 2008] visualizations of the learned metric, which is calculated from the testing models and instances. We can see that meaningful metric distance spaces are learned for both learning with full and part data: synergistic learning makes the instances and detectors with the same classes closer. These results provide preliminary proofs for the effectiveness of synergistic learning.

Table 1: Results for the classification experiments. For CIFAR-100 → MiniImageNet, the input shape is $32 \times 32 \times 3$. For MiniImageNet → CIFAR-100, the input shape is $84 \times 84 \times 3$. τ and τ_w indicate the Kendall's τ-coefficient and its weighted version calculated from 100 randomly generated five-class target tasks. The results are mean±95% confidence interval calculated from five random seeds. K indicates the number of training instances per class for each of the testing tasks.

Setting	Method	$K = 5$		$K = 10$		$K = 15$		$K = 20$	
		τ	τ_w	τ	τ_w	τ	τ_w	τ	τ_w
CIFAR-100 → MiniImageNet	LogME	0.139±0.070	0.180±0.187	0.200±0.079	0.359±0.231	0.243±0.056	0.420±0.217	0.255±0.042	0.418±0.270
	NCE	0.197±0.020	0.393±0.129	0.300±0.015	0.568±0.097	0.365±0.015	0.645±0.076	0.397±0.008	0.661±0.057
	LEEP	0.282±0.032	0.532±0.096	0.367±0.016	0.649±0.064	0.417±0.017	0.700±0.051	0.441±0.011	0.703±0.046
	SynLearn	**0.459±0.022**	**0.714±0.032**	**0.482±0.018**	**0.735±0.016**	**0.497±0.018**	**0.740±0.016**	**0.502±0.011**	**0.750±0.021**
MiniImageNet → CIFAR-100	LogME	0.166±0.044	0.312±0.176	0.244±0.083	0.413±0.164	0.288±0.087	0.478±0.163	0.310±0.078	0.479±0.189
	NCE	0.173±0.009	0.382±0.105	0.257±0.020	0.496±0.054	0.306±0.014	0.556±0.081	0.345±0.017	0.585±0.076
	LEEP	0.235±0.009	0.471±0.065	0.323±0.023	0.559±0.066	0.362±0.019	0.619±0.063	0.394±0.022	0.631±0.076
	SynLearn	**0.419±0.033**	**0.620±0.102**	**0.426±0.027**	**0.642±0.102**	**0.428±0.019**	**0.638±0.076**	**0.431±0.022**	**0.639±0.073**

5.2 In-Dataset MRE

Next, we use the dSprites dataset [Matthey et al., 2017] for testing in-dataset MRE performance. dSprites consists of images generated from six latent factors. We select three factors, shape, scale, orientation, to form the task domains. Another two real-valued factors, position X and Y, are used as the prediction targets. Based on this configuration, there are 720 domains and 1024 instances under each domain in total. For each domain, we randomly select 800 instances to form the training set which are used for obtaining 720 pre-trained models. The remaining 224 instances are used as the testing set. We randomly select 503 domains to be the in-distribution domains and the remaining 217 domains are used as the out-distribution domains. For synergistic learning, we only use the training sets and models from the in-distribution domains. $v_{valid}(\mu, h)$ is set according to the mean squared error (MSE). We set training $K = 10$, but testing $K = 1$ for verifying the performance under the extremely challenging situation. During testing, we generate testing tasks using the testing sets from either the in-distribution domains or the out-distribution domains. For in-distribution domains, the models used for testing consist of only in-distribution models. The out-distribution domains follow the similar rule. Figure 4 shows the ranking performance comparison between using MSE directly on the target datasets and synergistic learning (SynLearn). It can be observed that the synergistic learning ourperforms the naive MSE prediction significantly: under the extreme situation where testing $K = 1$, MSE almost fails totally in generating useful rankings, while synergistic learning can still perform desirably.

5.3 Cross-Dataset MRE

Finally, we use CIFAR-100 [Krizhevsky, 2009] and MiniImageNet [Vinyals et al., 2016] for cross-dataset MRE experiments. Both CIFAR-100 and MiniImageNet are 100-class datasets with pre-defined training and testing sets. We consider two settings for experiments: Reuse CIFAR-100 pre-trained models on MiniImageNet target tasks and the opposite. For each setting, we pre-train 200 20-class models on the source dataset, in which 100 models are used for synergistic learning and the other 100 for testing. For the target dataset, its training set is used for synergistic learning and its testing set is used for testing. All training and testing tasks are fixed to be five-way classification. For synergistic learning, full training set is used for metric pre-training and 10% of the training set is used for metric learning. For each testing task, 50 instances are sampled from each class for calculating the testing accuracy. For performance evaluation, we use Kendall's τ-coefficient [Kendall, 1938] to measure the rank correlation between the MRE scores and the testing accuracy. For emphasizing the performance on top-performed models, we also employ the weighted version of Kendall's τ-coefficient, τ_w, for which an exchange between elements with rank r and s (starting from zero) has weight $1/(r + 1) + 1/(s + 1)$ [Vigna, 2015]. We compare the performance of synergistic learning (SynLearn) with three state-of-the-art MRE methods: NCE [Tran et al., 2019], LEEP [Nguyen et al., 2020] and LogME [You et al., 2021]. The results are illustrated in Table 1. It can be observed that synergistic learning significantly outperforms other methods for small-data MRE. Note that for results in Table 1, we fix $K = 10$ during synergistic learning, while we observe significantly more robust performance of SynLearn over other approaches when the testing K varies. We conduct ablation studies to verify the effectiveness of the attention supervision, the feature pre-training, and the choice of the training K. which are provided in Section D. We also provide more experimental results for cross-dataset MRE in this section.

6 Related Work

Direct approaches for MRE. The direct approaches are based on the statistics calculated on the target training datasets as the MRE scores. The direct approaches involve only simple statistics calculation, meanwhile no auxiliary information is used, thus are usually quite simple and efficient. The representative studies of the direct approaches are [Tran et al., 2019, Nguyen et al., 2020]. In [Tran et al., 2019], the negative conditional entropy (NCE) score is proposed, which is an information-theoretic quantity measuring the entropy for $p(y|\hat{y})$. In [Nguyen et al., 2020], the log expected empirical prediction (LEEP) score is proposed, which can be regarded as an improvement of NCE. The LEEP score also closely related to $p(y|\hat{y})$. But it uses the *soft* prediction probability in calculation, to take the place of the *hard* label assignment calculation in NCE. Thus LEEP uses more information of prediction uncertainty. However, as shown in our experiments, both NCE and LEEP suffer from significant performance degeneration for small-data MRE. This is not surprising since the statistics calculated from small data usually have higher variance.

Specification-based approaches for MRE. The specification-based approaches use side information of the models, the *model specifications*, to identify model reusability [Wu et al., 2020, Ding and Zhou, 2020]. Wu et al. [2020] proposes the RKME specifications, which are data prototypes generated by kernel mean embedding. The RKME specifications reflect the density of the training domains for the pre-trained models, which can be used to calculate the distance between source and target domains. In [Ding and Zhou, 2020], the reusability indicator specification is proposed, which can be used to detect in-task-domain instances. The model specifications are designed to take auxiliary information for MRE, which can not be extracted from the model and the target data directly. Thus the specification-based approaches could benefit from the additional side information. However, the existing specification-based approaches are designed for the transductive learning setting, under which the testing data of the target task are given during MRE. This is different from the inductive learning setting studied in this paper.

Learning-based approaches for MRE. The learning-based approaches conducts learning *during* the MRE process. This is similar to the transductive setting considered by the specification-based approaches, since the learning-based approaches need to use the testing-stage models and tasks for learning. In comparison, synergistic learning is only the preparation stage for testing-stage MRE. No testing tasks and models are necessary for synergistic learning. The representative approaches are [You et al., 2021, Achille et al., 2019]. In [You et al., 2021], the logarithm of maximum evidence (LogME) approach is proposed. Different from NCE and LEEP which aim at finding the correlation between the source model predictions and the target outputs, LogME builds the correlation between source model features and the target outputs. Training using target data is necessary for LogME. The advantage of LogME is its wide applicability for different learning problems. While its performance degenerates more significantly than NCE and LEEP under the small-data scenario. This is likely caused by the necessity of learning on the target data which would lead to stronger over-fitting. In [Achille et al., 2019], the Model2Vec approach is proposed. Model2Vec uses metric learning to build task-model metric, which is similar to synergistic learning. But Model2Vec focuses on generating the metric distances for a fixed set of models, thus is a learning-based approach for MRE. In comparison, synergistic learning generates the task-model metric for future MRE problems in which the models are unseen during synergistic learning.

Few-shot learning. In few-shot learning (FSL) [Vinyals et al., 2016, Ha et al., 2017, Snell et al., 2017, Finn et al., 2017], a meta-model is learned to solve future small-data learning tasks. Usually, FSL does not assume to use pre-trained models except for a few cases [Chowdhury et al., 2021]. For MRE, its relationship to FSL is similar to that to transfer learning: MRE can serve as a good preparation step for any FSL task that is allowed to use a pool of pre-trained models.

7 Limitations and Future Work

In this work, we proposed the synergistic learning approach for the small-data model reusability evaluation (MRE) problem. This approach is based on the assumption that the model transferability has little relationship with the task-independent properties of the small sample. But in real problems, *bad samples* indeed exist whose task-independent properties affect transfer performance. We believe that fundamental limits exist for dealing with these samples. Deeper understandings of these limits and effective ways to tackle them will be important future research topics.

References

Martín Abadi, Paul Barham, Jianmin Chen, Zhifeng Chen, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Geoffrey Irving, Michael Isard, et al. {TensorFlow}: A system for {Large-Scale} machine learning. In *12th USENIX symposium on operating systems design and implementation (OSDI 16)*, pages 265–283, 2016.

Alessandro Achille, Michael Lam, Rahul Tewari, Avinash Ravichandran, Subhransu Maji, Charless C Fowlkes, Stefano Soatto, and Pietro Perona. Task2vec: Task embedding for meta-learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 6430–6439, 2019.

Nicolo Cesa-Bianchi and Gábor Lugosi. *Prediction, learning, and games*. Cambridge university press, 2006.

Arkabandhu Chowdhury, Mingchao Jiang, Swarat Chaudhuri, and Chris Jermaine. Few-shot image classification: Just use a library of pre-trained feature extractors and a simple classifier. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9445–9454, 2021.

Stéphan Clémençon, Gábor Lugosi, Nicolas Vayatis, et al. Ranking and empirical minimization of u-statistics. *The annals of statistics*, 36(2):844–874, 2008.

Yao-Xiang Ding and Zhi-Hua Zhou. Boosting-based reliable model reuse. In Sinno Jialin Pan and Masashi Sugiyama, editors, *Proceedings of the Asian Conference on Machine Learning (ACML)*, volume 129 of *Proceedings of Machine Learning Research*, pages 145–160, Bangkok, Thailand, 18–20 Nov 2020. PMLR.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *Proceedings of the international conference on machine learning (ICML)*, pages 1126–1135, 2017.

Dylan J Foster, Ayush Sekhari, and Karthik Sridharan. Uniform convergence of gradients for non-convex learning and optimization. In *Advances in neural information processing systems 31 (NeurIPS)*, pages 8745–8756, 2018.

Xiand Gao, Xiaobo Li, and Shuzhong Zhang. Online learning with non-convex losses and non-stationary regret. In *International Conference on Artificial Intelligence and Statistics*, pages 235–243, 2018.

David Ha, Andrew Dai, and Quoc V Le. Hypernetworks. In *International conference on learning representations (ICLR)*, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

Maurice G Kendall. A new measure of rank correlation. *Biometrika*, 30(1/2):81–93, 1938.

Jakub Konečný, H Brendan McMahan, Felix X Yu, Peter Richtárik, Ananda Theertha Suresh, and Dave Bacon. Federated learning: Strategies for improving communication efficiency. *arXiv preprint arXiv:1610.05492*, 2016.

Alex Krizhevsky. Learning multiple layers of features from tiny images. Technical report, 2009.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(Nov):2579–2605, 2008.

Loic Matthey, Irina Higgins, Demis Hassabis, and Alexander Lerchner. dsprites: Disentanglement testing sprites dataset. https://github.com/deepmind/dsprites-dataset/, 2017.

Colin McDiarmid. On the method of bounded differences. *Surveys in combinatorics*, 141(1):148–188, 1989.

Yurii Nesterov and Boris T Polyak. Cubic regularization of newton method and its global performance. *Mathematical programming*, 108(1):177–205, 2006.

Cuong Nguyen, Tal Hassner, Matthias Seeger, and Cedric Archambeau. Leep: A new measure to evaluate transferability of learned representations. In *International Conference on Machine Learning*, pages 7294–7305. PMLR, 2020.

Boris Oreshkin, Pau Rodríguez López, and Alexandre Lacoste. Tadam: Task dependent adaptive metric for improved few-shot learning. *Advances in neural information processing systems*, 31, 2018.

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In *Advances in Neural Information Processing Systems 30 (NIPS)*, pages 4080–4090, 2017.

Anh T Tran, Cuong V Nguyen, and Tal Hassner. Transferability and hardness of supervised classification tasks. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1395–1405, 2019.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Sebastiano Vigna. A weighted correlation index for rankings with ties. In *Proceedings of the 24th international conference on World Wide Web*, pages 1166–1176, 2015.

Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Daan Wierstra, et al. Matching networks for one shot learning. In *Advances in neural information processing systems 29 (NIPS)*, pages 3630–3638, 2016.

Xi-Zhu Wu, Wenkai Xu, Song Liu, and Zhi-Hua Zhou. Model reuse with reduced kernel mean embedding specification. *arXiv preprint arXiv:2001.07135*, 2020.

Han-Jia Ye, Hexiang Hu, De-Chuan Zhan, and Fei Sha. Few-shot learning via embedding adaptation with set-to-set functions. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8808–8817, 2020.

Kaichao You, Yong Liu, Jianmin Wang, and Mingsheng Long. Logme: Practical assessment of pre-trained models for transfer learning. In *International Conference on Machine Learning*, pages 12133–12143. PMLR, 2021.

Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabas Poczos, Russ R Salakhutdinov, and Alexander J Smola. Deep sets. *Advances in neural information processing systems*, 30, 2017.

Martin Zinkevich, Markus Weimer, Lihong Li, and Alex J Smola. Parallelized stochastic gradient descent. In *Advances in neural information processing systems 23 (NIPS)*, pages 2595–2603, 2010.