On the Universality of Graph Neural Networks in the Large Random Graph Limit

Abstract

We study the approximation power of Graph Neural Networks (GNNs) on latent position random graphs. In the large graph limit, GNNs are known to converge to certain "continuous" models known as c-GNNs, which enables a study of the universality of such architectures on random graph models. However, in the absence of input node features, GNNs are famously limited on regular graphs, and the same phenomenon happens for c-GNNs on random graphs with constant degree functions. Instead, we consider recently proposed architectures that augment GNNs with unique node identifiers, sometimes referred to as Graph Wavelets Neural Networks (GWNNs). We study the convergence of GWNNs to their continuous counterpart (c-GWNNs) in the large random graph limit. We then show that these are strictly more powerful than c-GNNs in the continuous limit, and prove their universality on several random graph models of interest, including most Stochastic Block Models and a large class of random geometric graphs. Our results cover both permutation-invariant and permutation-equivariant architectures.

1   Introduction

GNNs are deep architectures defined over graph data that have garnered a lot of attention in recent years. They represent the state-of-the-art in many graph Machine Learning (graph ML) problems, and have been successfully applied to e.g. node clustering [5], semi-supervised learning [21], quantum chemistry [14], and so on. See [3, 38, 15, 18] for reviews.

As the universality of Multi-Layers Perceptrons (MLP) is one of the foundational theorems in deep learning – that is, any continuous function can be approximated arbitrarily well by an MLP – in the last few years the approximation power of GNNs has been a topic of great interest. In the absence of special node features, when one has only access to the graph structure, the crux of the problem has been proven to be the capacity of GNNs to solve the *graph isomorphism problem*, that is, deciding when two graphs are permutations of each other or not (a difficult problem for which no polynomial algorithm is known [2]). Indeed, this property is directly linked to the approximation power of GNNs [6, 1]. In this light, the landmark paper [40] proves that classical GNNs are at best as powerful as the famous Weisfeiler-Lehman (WL) test [37] for graph isomorphism. Since then, several works [40, 28, 6] have derived new architectures, for instance involving high-order tensors [28], with improved discriminative power equivalent to "higher-order" variants of the WL test. In another line of works, several recent papers have advocated the use of *unique node identifiers* [25, 24], with strategies to preserve the permutation-equivariance/invariance of GNNs [39, 35] (see Sec. 2.3). These models are coined Graph Wavelet NNs (GWNNs) in [39]. GWNNs have been proved to be

strictly more powerful than the WL test in [35], and even *universal* on graphs with bounded degrees, however for powerful layers that cannot be implemented in practice. To our knowledge, the exact approximation power of GWNNs is still open.

When the size of the graphs grows, the notion of graph isomorphism becomes somewhat moot: large graphs might share properties (number of well-connected communities, and so on) but are never isomorphic to each other. GNNs have nevertheless proven successful in identifying their large-scale structures, e.g. for node clustering [5]. Several papers have therefore used tools from random graph theory and graphons to study the behavior of GNNs *in the large-graph limit*. In [19, 33], GNNs are shown to converge to limiting "continuous" architectures (coined c-GNNs in [19]). A few works have studied the discriminative power of c-GNNs on graphons [27], however, analogously to how the WL test will fail on regular graphs, c-GNNs are severely limited on graph models with almost-constant degree function (Fig. 1), and the question is still largely open.

Contribution and outline. In this paper, we study the convergence of GWNNs on large random graphs towards "c-GWNNs", and analyze the approximation power of c-GNNs and c-GWNNs. After some preliminary results in Sec. 2, we study the convergence of GWNNs in Sec 3. In Sec. 4 and 5, we show that c-GWNNs are strictly more powerful than c-GNNs in both permutation-invariant and equivariant case. We then prove the universality of c-GWNNs on several popular models of random graphs, including Stochastic Block Models (SBMs) and radial kernels. For instance, we show in Sec. 5.3 that permutation-equivariant c-GWNNs are universal on most SBMs, including some for which any c-GNN provably fails (Fig. 1).

Figure 1: Illustration of Prop. 7 (Sec. 5.3). On an SBM with constant degree function, a GNN (top) might overfit the training set, but converges to a constant c-GNN. On the contrary, there exists a c-GWNN (bottom) that perfectly separates the communities. Details can be found in App. E.

Related work. The approximation power of GNNs (on finite graphs) has been a topic of great interest in recent years, and we do not attempt to make an exhaustive list of all results here. The landmark paper [40] showed that permutation-invariant GNNs were at best as powerful as the WL test, and later models [28, 6, 13] were constructed to be as powerful as higher-order WL tests. The link between the graph isomorphism problem and function approximation was made in [6, 20] and extended in [1]. Some architectures where proven to be universal [29, 20] but involve tensors of unbounded order. When graphs are equipped with unique node identifiers, the approximation power of GNNs can be significantly improved if relaxing permutation-invariance/equivariance [25, 24]. Recent works have proposed methods to restore these properties [39, 35]. As mentioned above, the resulting GWNNs are indeed more powerful than the WL test [35].

Much less results can be found in the large-graph limit. Beyond the graph-isomorphism paradigm, authors have studied the capacity of GNNs to count graph substructures [4, 10] or identify various graph properties [12, 41]. Several works have studied the large-graphs limit of GNNs [33, 27, 23, 19], assuming random graph or graphon models. The degree function has been proven to be a crucial element for the discriminative power of c-GNNs, and they will not be able to distinguish graphons with close degree functions [27]. Here we show how c-GWNNs allow to overcome these limitations. Finally, universal architectures exist on measures [8, 43], which can be seen as limits of *point clouds*, but, similar to the discrete case [42, 29, 20], the graph case may be significantly harder to study.

2 Preliminaries

In this section, we group notations on random graphs and GNNs, present the convergence result of [19] slightly adapted to our context, and introduce the GWNNs of [39, 35]. An undirected graph

G with n nodes is represented by a symmetric adjacency matrix $A \in \mathbb{R}^{n \times n}$. It is isomorphic to all graphs with adjacency matrices $\sigma A \sigma^\top$, for any permutation matrix $\sigma \in \{0,1\}^{n \times n}$. Matrix rows (resp. columns) are denoted by $A_{i,:}$ (resp. $A_{:,i}$). The norm $\|\cdot\|$ is the operator norm for matrices and Euclidean norm for vectors. For a compact metric space $\mathcal{X}$, we denote by $\mathcal{C}(\mathcal{X}, \mathbb{R})$ the bounded continuous functions $\mathcal{X} \to \mathbb{R}$, equipped with $\|f\|_\infty = \sup_x |f(x)|$. For a multivariate function $\mathcal{C}(\mathcal{X}, \mathbb{R}^d)$, f_i denotes its ith coordinate, and $\|f\|_\infty = (\sum_i \|f_i\|_\infty^2)^{1/2}$.

2.1 Random graph model

We consider "latent position" random graphs, which include several popular models such as SBMs or graphons. The nodes are associated with unobserved latent random variables x_i drawn iid. For the edges, we will examine two cases: an "ideal" case with deterministic weighted edges, and a more "realistic" case where the edges are randomly drawn independently. In the literature, the deterministic case is often considered as an idealized framework to study the behavior of various algorithms [36].

Let $(\mathcal{X}, m_{\mathcal{X}})$ be a compact metric space that is not a singleton, and assume that the ε-covering numbers[1] of $\mathcal{X}$ scale as $\mathcal{O}\left(\varepsilon^{-d_{\mathcal{X}}}\right)$ for some dimension $d_{\mathcal{X}}$. We denote by $\mathcal{W}$ the set of symmetric bivariate functions in $\mathcal{C}(\mathcal{X} \times \mathcal{X}, [0,1])$ that are L_W-Lipschitz in each variable, and by $\mathcal{P}$ the set of probability distributions over $\mathcal{X}$ equipped with the total variation norm $\|\cdot\|_{\mathrm{TV}}$. A graph with n nodes is generated according to a random graph model $(W, P) \in \mathcal{W} \times \mathcal{P}$ as follows:

$$x_1, \ldots, x_n \overset{iid}{\sim} P, \qquad a_{ij} = \begin{cases} W(x_i, x_j) & \text{deterministic edges case} \\ \alpha_n^{-1}\mathrm{Bernoulli}(\alpha_n W(x_i, x_j)) & \text{random edges case} \end{cases} \tag{1}$$

where α_n is the *sparsity level* of the graph in the random edges case, which we assume to be known for simplicity. When $\alpha_n \sim 1$, the graph is said to be *dense*, when $\alpha_n \sim \frac{1}{n}$ the graph is *sparse*, and when $\alpha \sim \frac{\log n}{n}$ the graph is *relatively sparse*. Note that, for simplicity, we have normalized the Bernoulli edges by $1/\alpha_n$ such that $\mathbb{E}a_{ij} = W(x_i, x_j)$ conditionally on x_i, x_j. When $\mathcal{X}$ is finite, all the conditions above are automatically satisfied, and the model is called an SBM (see Sec. 4.3).

Like finite graphs, random graph models can be isomorphic to one another [19, 26]. In this paper, similar to [19] we consider that, for any bijection $\varphi : \mathcal{X} \to \mathcal{X}$, the model (W, P) is isomorphic to $(W_\varphi, \varphi_\sharp^{-1} P)$, where $W_\varphi(x, y) = W(\varphi(x), \varphi(y))$ and $f_\sharp P$ is the pushforward of P (the distribution of $f(X)$). Indeed, it is easy to see that both produce exactly the same distribution over graphs.

2.2 Graph Neural Networks

Following [19, 9], in this paper we consider the so-called "spectral" version of GNNs, which include several message-passing models for certain aggregation functions. We consider polynomial filters h defined as $h(A) = \sum_k \beta_k A^k$ for a matrix or operator A. In practice, the order of the filters is always finite, but our results are valid for infinite-order filters (assuming that the sum always converges for simplicity). We consider an activation function $\rho : \mathbb{R} \to \mathbb{R}$ which satisfies $\rho(0) = 0$ and $|\rho(x) - \rho(y)| \leqslant |x - y|$ for which the universality theorem of MLPs applies [31], e.g. ReLU.

Spectral GNNs are defined by successive filtering of a graph signal. Given an input signal $Z^{(0)} \in \mathbb{R}^{n \times d_0}$, at each layer $\ell = 0, \ldots, M-1$:

$$Z_{:,j}^{(\ell+1)} = \rho\left(\sum_{i=1}^{d_\ell} h_{ij}^{(\ell)}\left(\tfrac{1}{n}A\right) Z_{:,i}^{(\ell)} + b_j^{(\ell)} 1_n\right) \in \mathbb{R}^n \qquad j = 1, \ldots, d_{\ell+1}, \tag{2}$$

where $h_{ij}^{(\ell)}(A) = \sum_k \beta_{ijk}^{(\ell)} A^k$ are trainable graph filters, $b_j^{(\ell)} \in \mathbb{R}$ are trainable additive biases and ρ is applied pointwise. We note the normalization A/n that will be necessary for convergence. GNNs exist in two main versions: so-called "permutation-invariant" GNNs $\bar{\Phi}$ output a single vector for the entire graph, while "permutation-equivariant" GNNs Φ output a graph signal:

$$\Phi_A(Z^{(0)}) = g\left(Z^{(M)}\right) \in \mathbb{R}^{n \times d_{out}} \qquad \bar{\Phi}_A(Z^{(0)}) = g\left(\tfrac{1}{n}\sum_{i=1}^n Z_{i,:}^{(M)}\right) \in \mathbb{R}^{d_{out}}, \tag{3}$$

---

[1]the number of balls of radius ε required to cover $\mathcal{X}$

where $g : \mathbb{R}^{d_M} \to \mathbb{R}^{d_{out}}$ is an MLP applied row-wise in the equivariant case. By construction, such GNNs are indeed equivariant or invariant to node permutation: for all permutation matrices σ, we have $\Phi_{\sigma A \sigma^\top}(\sigma Z^{(0)}) = \sigma \Phi_A(Z^{(0)})$ and $\bar{\Phi}_{\sigma A \sigma^\top}(\sigma Z^{(0)}) = \bar{\Phi}_A(Z^{(0)})$.

Continuous GNNs. In [19], the authors show that, in the large random graphs limit, GNNs converge to the following "continuous" models (coined c-GNNs), which propagate **functions over the latent space** $f^{(\ell)} \in \mathcal{C}(\mathcal{X}, \mathbb{R}^{d_\ell})$ instead of graph signals. Given an input function $f^{(0)} \in \mathcal{C}(\mathcal{X}, \mathbb{R}^{d_0})$:

$$f_j^{(\ell+1)} = \rho \left(\sum_{i=1}^{d_\ell} h_{ij}^{(\ell)}(T_{W,P}) f_i^{(\ell)} + b_j^{(\ell)} \right), \tag{4}$$

where $T_{W,P}$ is the operator $T_{W,P} f = \int W(\cdot, x) f(x) dP(x)$. Then similar to (3) the permutation-equivariant/invariant versions of c-GNNs are defined as:

$$\Phi_{W,P}(f^{(0)}) = g \circ f^{(M)}, \qquad \bar{\Phi}_{W,P}(f^{(0)}) = g \left(\int f^{(M)}(x) dP(x) \right). \tag{5}$$

Remark that $\Phi_{W,P}(f^{(0)})$ is itself a *function* in $\mathcal{C}(\mathcal{X}, \mathbb{R}^{d_{out}})$ while $\bar{\Phi}_{W,P}(f^{(0)}) \in \mathbb{R}^{d_{out}}$ is a vector. Moreover, by virtue of the polynomial filters, the four architectures $\Phi_A, \bar{\Phi}_A, \Phi_{W,P}, \bar{\Phi}_{W,P}$ have the exact same set of parameters. Like in the discrete case, one can prove that c-GNN are equivariant or invariant to isomorphisms of random graph models [19]: for all bijection $\varphi : \mathcal{X} \to \mathcal{X}$, we have $\Phi_{W_\varphi, \varphi_\sharp^{-1} P}(f \circ \varphi) = \Phi_{W,P}(f) \circ \varphi$ and $\bar{\Phi}_{W_\varphi, \varphi_\sharp^{-1} P}(f \circ \varphi) = \bar{\Phi}_{W,P}(f)$.

Let us now turn to convergence of GNNs to c-GNNs. The following result is adapted[2] from [19]. For a graph signal $Z \in \mathbb{R}^{n \times d}$, a function $f : \mathcal{X} \to \mathbb{R}^d$ and $X = \{x_i\}_{i=1}^n$, we define the (square root of the) mean-square error as $\mathrm{MSE}_X(Z, f) = (\frac{1}{n} \sum_{i=1}^n \|Z_i - f(x_i)\|_2^2)^{1/2}$. The proof of Theorem 1 with all multiplicative constants is given in App. A.1. Recall that $d_\mathcal{X}$ is the "dimension" of $\mathcal{X}$.

Theorem 1. *Assume G is drawn from (W, P) and has latent variables X. Fix $\rho, \nu > 0$.*

- **In the deterministic edges case:** *with probability $1 - \rho$, for all $Z^{(0)}$:*

$$\mathrm{MSE}_X(\Phi_A(Z^{(0)}), \Phi_{W,P}(f^{(0)})) \leqslant C \cdot \mathrm{MSE}_X(Z^{(0)}, f^{(0)}) + R_1(n) \tag{6}$$

  for some constant C and $R_1(n) = \mathcal{O}\left(\sqrt{(d_\mathcal{X} + \log(1/\rho))/n} \right)$.

- **In the random edges case:** *assume that the sparsity level is $\alpha_n \gtrsim n^{-1} \log n$. There is a constant C_ν such that, with probability $1 - \rho - n^{-\nu}$, for all $Z^{(0)}$:*

$$\mathrm{MSE}_X(\Phi_A(Z^{(0)}), \Phi_{W,P}(f^{(0)})) \leqslant C \cdot \mathrm{MSE}_X(Z^{(0)}, f^{(0)}) + R_1(n) + R_2(n) \tag{7}$$

  where $R_2(n) = \mathcal{O}\left(C_\nu / \sqrt{\alpha_n n} \right)$.

- **In the permutation-invariant case:** *The exact same results hold for $\left\| \bar{\Phi}_A(Z^{(0)}) - \bar{\Phi}_{W,P}(f^{(0)}) \right\|$ instead of the MSE, with an added error term $R_3(n) = \mathcal{O}\left(\sqrt{\log(1/\rho)/n} \right)$.*

By the theorem above, a GNN converges to its continuous counterpart if $Z^{(0)}$ is (close to) a sampling of a function $f^{(0)}$ at the latent variables. This is directly assumed in [19]. In the present paper however, we do not suppose that input node features are available. While several strategies have been proposed in the literature, a popular baseline is to simply take constant input $Z^{(0)} = 1_n$ (which is also equivalent to taking the degrees as in [5] for instance). In this case, there is convergence to a c-GNN with $f^{(0)} = 1$. For simplicity in the rest of the paper we drop the notation "(1)" and write $\Phi_A = \Phi_A(1_n)$, $\Phi_{W,P} = \Phi_{W,P}(1)$, and so on. It is known that GNNs are limited on regular graphs: for permutation-invariant GNNs, the WL test cannot distinguish regular graphs of the same order, and for permutation-equivariant GNNs, $\Phi_A(1_n)$ is *constant over the nodes*. Similarly for c-GNN, the degree function $\int W(\cdot, x) dP(x)$ is key in the discriminative power of c-GNNs [27], and if it is constant, then $\Phi_{W,P}(1)$ is a constant function. See Fig. 1 for a concrete example of failure.

---

[2]The authors in [19] proved this for the normalized Laplacian, which allows bypassing the knowledge of α_n. Here we use the adjacency matrix, for our later results on approximation power.

2.3 GWNN: GNN with unique node identifiers

To remedy the absence of input node features, in [35] and [39], the authors propose an architecture with *unique node identifiers* while still respecting permutation invariance/equivariance. More precisely, they first choose an *arbitrary* ordering of the nodes $q = 1, \ldots, n$, apply a GNN to each *one-hot vector* $e_q = [0, \ldots, 1, \ldots, 0]$, and restore equivariance to permutation by a final pooling. For later purpose of convergence, we generalize this strategy to any collection $E_q(A) \in \mathbb{R}^{n \times d_0}$ that satisfies:

$$E_q(\sigma A \sigma^\top) = \sigma E_{\sigma^{-1}(q)}(A). \tag{8}$$

where by an abuse of notation $\sigma(q)$ designates the permutation function applied to index q. For instance, it can be any filtering of one-hot vector $E_q(A) = h(A)e_q$. After the GNN Φ_A, a pooling is applied to restore equivariance, then a second GNN Φ'_A that is either invariant or equivariant:

$$\Psi_A = \Phi'_A \left(\tfrac{1}{n} \sum_q \Phi_A \left(E_q(A) \right) \right) \in \mathbb{R}^{n \times d'_{out}}, \qquad \bar{\Psi}_A = \bar{\Phi}'_A \left(\tfrac{1}{n} \sum_q \Phi_A \left(E_q(A) \right) \right) \in \mathbb{R}^{d'_{out}} \tag{9}$$

Following [39], we refer to these architectures as GWNN. In [35], these architectures are interpreted as doing message-passing over matrices, and can use more general pooling and aggregation functions. It is not difficult to see that GWNNs satisfy: $\Psi_{\sigma A \sigma^\top} = \sigma \Psi_A$ and $\bar{\Psi}_{\sigma A \sigma^\top} = \bar{\Psi}_A$.

3 Convergence of GWNNs on large random graphs

In this section, we extend Theorem 1 to GWNNs. To define continuous GWNNs, we consider a *bivariate* input function $\eta_{W,P} : \mathcal{X} \times \mathcal{X} \to \mathbb{R}^{d_0}$ such that: the mapping $(W, P) \mapsto \eta_{W,P}$ is continuous[3], for any (W, P), $\eta_{W,P}$ is C_η-bounded and L_η-Lipschitz in each variable, and similar to (8):

$$\eta_{W_\varphi, \varphi_\sharp^{-1} P}(x, y) = \eta_{W,P}(\varphi(x), \varphi(y)), \tag{10}$$

for all bijections $\varphi : \mathcal{X} \to \mathcal{X}$. For instance, $\eta_{W,P} = W$ or any filter $\eta_{W,P}(x,y) = [h(T_{W,P})W(\cdot, y)](x)$ satisfy these conditions. A c-GWNN is then defined as:

$$\Psi_{W,P} = \Phi'_{W,P} \left(\int \Phi_{W,P}(\eta_{W,P}(\cdot, x)) dP(x) \right), \tag{11}$$

for the equivariant case, or similarly $\bar{\Psi}_{W,P} = \bar{\Phi}'_{W,P} \left(\int \Phi_{W,P}(\eta_{W,P}(\cdot, x)) dP(x) \right)$ for the invariant case. Again, using the properties of c-GNNs, it is easy to see that c-GWNNs satisfy: $\Psi_{W_\varphi, \varphi_\sharp^{-1} P} = \Psi_{W,P} \circ \varphi$ and $\bar{\Psi}_{W_\varphi, \varphi_\sharp^{-1} P} = \bar{\Psi}_{W,P}$. We are now ready to extend Theorem 1. The proof and multiplicative constants are in App. A.2.

Theorem 2. *Assume G is drawn from (W, P) with latent variables X. Fix $\rho, \nu > 0$.*

- ***In the deterministic edges case:*** *with probability $1 - \rho$, for all $Z^{(0)}$:*

$$\mathrm{MSE}_X(\Psi_A, \Psi_{W,P}) \leqslant C' \cdot \sup_q \mathrm{MSE}_X(E_q(A), \eta(\cdot, x_q)) + R'_1(n) \tag{12}$$

  for some constant C' and $R'_1(n) = \mathcal{O}\left(\sqrt{(d_\mathcal{X} + \log(1/\rho))/n} \right)$.

- ***In the random edges case:*** *assume that the sparsity level is $\alpha_n \gtrsim n^{-1} \log n$. There is a constant C_ν such that, with probability $1 - \rho - n^{-\nu}$, for all $Z^{(0)}$:*

$$\mathrm{MSE}_X(\Psi_A, \Psi_{W,P}) \leqslant C' \cdot \sup_q \mathrm{MSE}_X(E_q(A), \eta(\cdot, x_q)) + R'_1(n) + R'_2(n) \tag{13}$$

  where $R'_2(n) = \mathcal{O}\left(C_\nu/\sqrt{\alpha_n n} \right)$.

- ***In the permutation-invariant case:*** *The exact same results hold for $\left\| \bar{\Psi}_A - \bar{\Psi}_{W,P} \right\|$ instead of the MSE, with an added error term $R'_3(n) = \mathcal{O}\left(\sqrt{\log(1/\rho)/n} \right)$.*

Hence we see convergence when $E_q(A)$ is close to being a sampling of $\eta_{W,P}$ at x_q. The choice of input signal/function is therefore crucial. Let us examine a few strategies.

---

[3]for the norm $\|\cdot\|_\infty + \|\cdot\|_{\mathrm{TV}}$ on $\mathcal{W} \times \mathcal{P}$

One-hot vectors. If one chooses one-hot vectors $E_q = e_q$ as in [35, 39], then we can see that the GWNN converges to the continuous architecture with input $\eta_{W,P} = 0$, since $\mathrm{MSE}_X(e_q, 0) \to 0$. Since $\Psi_{W,P}$ is nothing more than a traditional c-GNN $\Phi_{W,P}$ with constant input in that case, this is not a satisfying choice in terms of approximation power.

One-hop filtering. If we choose to "filter" e_q once and take $E_q(A) = Ae_q$, the natural continuous equivalent is $\eta_{W,P} = W$. Such a strategy only works for deterministic edges: indeed,

$$\mathrm{MSE}_X(Ae_q, W(\cdot, x_q)) = \left(n^{-1} \sum_{i=1}^{n} (a_{iq} - W(x_i, x_q))^2\right)^{1/2}$$

$$\begin{cases} = 0 & \text{with deterministic edges} \\ \approx \sqrt{n^{-1} \sum_i Var(a_{iq})} \sim \alpha^{-1} & \text{with random edges, w.h.p.} \end{cases}$$

where the last line comes from a simple application of Hoeffding's inequality. Hence, in the case of random edges, the MSE does not vanish and typically diverges for non-dense graphs (Fig. 2).

Two-hop filtering. We can therefore choose to filter *twice* and consider $\eta_{W,P}(x, y) = T_{W,P}[W(\cdot, y)](x)$, that is, $E_q(A) = A^2 e_q / n$. We have the following result.

Proposition 1. *In the random edges case, with probability* $1 - \rho$, *we have for all q:*

$$\mathrm{MSE}_X\left(\frac{A^2 e_q}{n}, T_{W,P}[W(\cdot, x_q)](\cdot)\right) \lesssim \mathcal{O}\left(\frac{\sqrt{\log(n/\rho)}}{\alpha\sqrt{n}}\right).$$

In the deterministic edges case, the rate is $\mathcal{O}\left(1/\sqrt{n}\right)$.

Convergence is guaranteed when $\sqrt{\log n}/(\alpha_n\sqrt{n}) \to 0$, which is stronger than relative sparsity. The difference between one-hop and two-hop filtering is illustrated in Fig. 2. Other strategies may also be examined, and we leave this for future work. For instance, based on Theorem 5 in App. D, a strategy based on the eigenvectors of A could lead to convergence even in the relatively sparse case. In the rest of the paper, we explicitly write when our results are valid for one- or two-hop filtering.

Figure 2: Difference between the outputs of some $\bar{\Psi}_A$ in the random edges case with $\alpha_n \sim n^{-1/3}$ and in the deterministic edges case, which converges to $\bar{\Psi}_{W,P}$. Convergence is observed for two-hop filtering only. The theoretical rate of Prop. 1 is slightly pessimistic. Details can be found in App. E.

4 Approximation power: permutation-invariant case

In this section, we study the approximation power of continuous architectures in the permutation-invariant case. We seek to characterize the functions $\mathcal{W} \times \mathcal{P} \to \mathbb{R}$ that can be well-approximated by a c-GNN or c-GWNN. We derive a generic criterion for universality arising from the Stone-Weierstrass theorem, before proving that c-GWNNs are indeed strictly more powerful than c-GNNs. Finally, we give several examples of models for which c-GWNNs are universal.

4.1 Generic result with Stone-Weierstrass theorem

A classical tool to prove universality of neural nets in the literature is the Stone-Weierstrass theorem [17, 20], which states that an algebra of functions that separates points on a compact space is dense in the set of continuous functions. Although NNs are typically not an algebra since they are not closed by multiplication, one of the original proofs of universality for MLPs solves this by a clever trick [17] which we recall in Lemma 1 in App. D. A direct application results in the following proposition.

Proposition 2. *Let $\mathcal{M} \subset \mathcal{W} \times \mathcal{P}$ be a **compact** subset of $\mathcal{W} \times \mathcal{P}$. c-GWNNs (resp. c-GNNs) are dense in $\mathcal{C}(\mathcal{M}, \mathbb{R})$ if and only if: for all $(W, P) \neq (W', P') \in \mathcal{M}$, there is a c-GWNN (resp. a c-GNN) such that $\bar{\Psi}_{W,P} \neq \bar{\Psi}_{W',P'}$ (resp. $\bar{\Phi}_{W,P} \neq \bar{\Phi}_{W',P'}$).*

Note that, by construction of the permutation-invariant c-G(W)NNs, universality is only possible when $\mathcal{M}$ does *not* contain two isomorphic versions of the same random graph model. Equivalently, $\mathcal{M}$ may be a larger set *quotiented* by random graph isomorphism.

4.2 c-GWNNs are more powerful than c-GNNs

GWNNs were proven to be strictly more powerful than the WL test, and therefore than GNNs, in [35]. In the theorem below, we check that this strict inclusion holds for their continuous limits.

Theorem 3. *The set of functions of the form* $(W, P) \rightarrow \bar{\Phi}_{W,P}$ *is **strictly** included in the set of functions* $(W, P) \rightarrow \bar{\Psi}_{W,P}$*, for both one- and two-hop filtering.*

This theorem is proven by constructing two models that are distinguished by a c-GWNN but not by any c-GNN. We note that there might be subsets $\mathcal{M} \subset \mathcal{W} \times \mathcal{P}$ that do not contain such models, and therefore on which c-GNNs and c-GWNNs have the same approximation power.

4.3 Examples

While a generic universality theorem on random graphs seems to be out-of-reach for the moment, we examine several interesting examples, and pave the way for many future extensions. We focus on c-GWNNs, but, sometimes, may not conclude on the power of c-GNNs: we could not prove that they are universal, but were not able to find a counter-example either. For simplicity, we mostly focus on one-hop input filtering, and leave more generic notions of input signals for future work.

Stochastic Block Models. SBMs [16] are classical models to emulate graphs with communities. In our settings, SBMs with K communities can be obtained with a finite latent space $|\mathcal{X}| = K$, typically $\mathcal{X} = \{1, \ldots, K\}$. The kernel $W(k, k') = W_{kk'}$ can be represented as a matrix $W \in S_K$, where S_K is the set of symmetric matrices in $[0, 1]^{K \times K}$, and the distribution $P(k) = P_k$ as a vector $P \in \Delta^{K-1}$, where $\Delta^{K-1} = \{P \in [0, 1]^K, \sum_k P_k = 1\}$ is the $(K–1)$-dimensional simplex.

In the following proposition, we fix P and examine universality with respect to W. In this case, continuous GNNs are actually quite similar to discrete ones on matrices W, except that the probability vector P also intervenes in the computation. While GNNs on finite graphs can only be universal when using high-order tensors [29, 20] due to invariance to graph-isomorphism, here P can help to disambiguate this constraint. We will say that $P \in \Delta^{K-1}$ is **incoherent** if: for signs $s_i \in \{-1, 0, 1\}^k$, having $\sum_{k=1}^K s_k P_k = 0$ implies $s_k = 0$. That is, no probability is an exact sum or difference of the others. We note that a vector drawn uniformly on Δ^{K-1} is incoherent with probability 1. For incoherent probability vector, we can show universality of c-GWNNs. Moreover, this is actually a case where we *can* prove that c-GNNs are, in turn, *not* universal.

Proposition 3. *For one-hop filtering, if P is incoherent the space of functions $W \rightarrow \bar{\Psi}_{W,P}$ is dense in $\mathcal{C}(S_K, \mathbb{R})$. Moreover, there exists P incoherent and $W \neq W'$ such that, for any c-GNN, $\bar{\Phi}_{W,P} = \bar{\Phi}_{W',P}$.*

Additive kernel. Let us now fix W and examine universality with respect to P. A classical theorem on symmetric continuous functions [42] states that any W can be arbitrarily well approximated as $W(x, y) \approx u(v(x) + v(y))$ for some functions u, v. Inspired by this result, a kernel will be said to be **additive** if it can (exactly) be written as $W(x, y) = u(v(x) + v(y))$, and **injectively additive** if both u, v are *continuous and injective*. We prove universality in the unidimensional case below.

Proposition 4. *Let $\mathcal{X} \subset \mathbb{R}$, and $\tilde{\mathcal{P}}$ be any compact subset of $\mathcal{P}$. Assume W is injectively additive with $\text{Im}(v) \subset \mathbb{R}$. For one-hop filtering, the space of functions $P \rightarrow \bar{\Psi}_{W,P}$ is dense in $\mathcal{C}(\tilde{\mathcal{P}}, \mathbb{R})$.*

It is easy to see that injectively additive kernels include all SBMs for which $W_{ij} \neq W_{ij'}$ when $j \neq j'$, so Prop. 4 completes Prop. 3. However, unlike additive kernels, injectively additive kernels are *a priori* **not** universal approximators of symmetric continuous functions: this result [42] is only valid when $\text{Im}(v)$ can be multidimensional, but it is known for instance that there is no continuous injective map from $[0, 1]^2$ to $[0, 1]$, so if $\text{Im}(v) = [0, 1]^2$, u cannot be both continuous and injective.

Radial kernel. We conclude this section with an important class of kernels, *radial* kernels $W(x, y) = w(\|x - y\|)$ for some function $w : \mathbb{R}_+ \rightarrow [0, 1]$. They include the popular Gaussian kernel and so-called ε-graphs. Below, we give an example in one dimension, for which c-GWNNs are

universal on symmetric distributions. The case of non-symmetric distributions seems more involved and we leave it for future investigations.

Proposition 5. *Assume that $\mathcal{X} = [-1, 1]$ and $W(x, y) = w(|x - y|)$ where w is continuous and injective. Let $\tilde{\mathcal{P}} \subset \mathcal{P}$ be any compact set of **symmetric** distributions. For one-hop filtering, the space of functions $P \to \bar{\Psi}_{W,P}$ is dense in $\mathcal{C}(\tilde{P}, \mathbb{R})$.*

5 Approximation power: permutation-equivariant case

In the equivariant case, recall that the outputs of c-G(W)NNs are *functions* on $\mathcal{X}$. The "traditional" notion of universality is to evaluate the approximation power of mappings $(W, P) \to \mathcal{F}$, where $\mathcal{F}$ is some space of equivariant functions, as is done for the discrete case in [20, 1]. However, a potentially simpler and more relevant notion here is to *fix* (W, P), and directly examine the properties of the space of functions $\mathcal{X} \to \mathbb{R}$ represented by c-G(W)NNs, that is, the space of functions $\{\Psi_{W,P} : \mathcal{X} \to \mathbb{R}\}$ for all possible c-GWNNs $\Psi_{W,P}$ (and similar for $\Phi_{W,P}$). Indeed, this directly answers such questions as: given an SBM, does there exist a c-GNN that can labels the communities (Fig. 1)? Or: given the structure of a mesh, what functions can be computed on it, e.g. for segmentation?

5.1 Generic result with Stone-Weierstrass theorem

As in the invariant case, the Stone-Weierstrass theorem yields a generic separation condition.

Proposition 6. *Let (W, P) be fixed. Then c-GWNNs (resp. c-GNNs) are dense in $\mathcal{C}(\mathcal{X}, \mathbb{R})$ iff: for all $x \neq x' \in \mathcal{X}$, there is a c-GWNN (resp. a c-GNN) such that $\Psi_{W,P}(x) \neq \Psi_{W,P}(x')$ (resp. $\Phi_{W,P}(x) \neq \Phi_{W,P}(x')$).*

5.2 c-GWNNs are more powerful than c-GNNs

Using a proof similar to Theorem 3, we can then prove that c-GWNNs are indeed strictly more powerful than c-GNNs for some (W, P).

Theorem 4. *For both one- and two-hop filtering, the following holds. For any (W, P), the set of functions of the form $\Phi_{W,P}$ is included in the set of functions $\Psi_{W,P}$, and there exist (W, P) such that the inclusion is **strict**.*

5.3 Examples

We treat the same examples as before, with the addition of radial kernels on d-dimensional sphere.

SBM. Universality in the SBM case corresponds to being able to distinguish communities, that is, $\Psi_{W,P} : \mathcal{X} \to \mathbb{R}$ returns a different value for each element of the latent space $\mathcal{X}$. In the following result, we assume that W is invertible, and prove the result for *both* one- and two-hop filtering.

Proposition 7. *Let P be incoherent, and W be invertible. For **both** one- and two-hop filtering, c-GWNNs are dense in $\mathcal{C}(\mathcal{X}, \mathbb{R})$. Moreover, there exist (W, P) satisfying the conditions above such that any c-GNN $\Phi_{W,P}$ is a constant function.*

This proposition is illustrated in Fig. 1: on an SBM with constant degree function, any GNN converges to a c-GNN with constant output, while a GWNN with two-hop input filtering can be close to a c-GWNN that perfectly separates the communities.

Additive kernel. As in the invariant case, injectively additive kernels lead to universality.

Proposition 8. *Assume W is injectively additive, fix any P. Then, for one-hop filtering, c-GWNNs are dense in $\mathcal{C}(\mathcal{X}, \mathbb{R})$.*

Radial kernel. Unlike the invariant case (Prop. 5) which was limited to symmetric distributions, this time we treat of both symmetric and non-symmetric case: when P is symmetric, then so is $\Psi_{W,P}$

Figure 3: Illustration of Prop. 9 on Gaussian kernel, but with random edges and two-hop input filtering. The x-axis is the latent variables in $\mathcal{X} = [-1, 1]$. The y-axis is the output of a GWNN trained to approximate some function f (red curve). On the left, both distribution P and f are symmetric, c-GWNNs are universal in that case. In the center, P is symmetric but not f, and the training expectedly fails since the limit c-GWNN is symmetric. On the right, P and f are non-symmetric, and universality holds again. Details can be found in App. E.

(by permutation-equivariance), and we have universality among symmetric functions. When P is non-symmetric, we have universality among *all* functions. See Fig. 3 for an illustration.

Proposition 9. *Consider* $\mathcal{X} = [-1, 1]$, $W(x, y) = w(|x - y|)$ *a radial kernel with an invertible, continuous* w, *and* P *with a piecewise continuous density such that* $\mathbb{E}_P X = 0$. *Then, for one-hop filtering: if* P *is symmetric, c-GWNNs are dense in the space of* symmetric *functions in* $\mathcal{C}(\mathcal{X}, \mathbb{R})$, *and if* P *is not symmetric, c-GWNNs are dense in* $\mathcal{C}(\mathcal{X}, \mathbb{R})$.

Finally, we look at radial kernels on the d-dimensional sphere $\mathcal{X} = \mathbb{S}^{d-1} = \{x \in \mathbb{R}^d \mid \|x\| = 1\}$, an important example sometimes referred to as random geometric graphs [30]. In this case the kernel only depends on the dot product $W(x, y) = w(x^\top y)$. Denoting by $d\tau$ the uniform measure on $\mathbb{S}^{d-1}$, it is known [11, 7] that functions in $L^2(d\tau)$ can be uniquely decomposed as $f(x) = \sum_{k \geqslant 0} f_k(x) = \sum_{k \geqslant 0} \sum_{j=1}^{N(d,k)} a_{k,j} Y_{k,j}(x)$ where $Y_{k,j}$ are *spherical harmonics*, that is, homogeneous harmonic polynomials of degree k which form an orthonormal basis of $L^2(d\tau)$. We will say that such a function is **injectively decomposed** if the mapping $x \to [f_k(x)]_{k \geqslant 0}$ from $\mathbb{S}^{d-1}$ to $\ell_2(\mathbb{R})$ is injective. Note that generically this is verified if f_k is non-zero for more than $d - 1$ distinct values of $k > 0$, as this corresponds to solving an over-determined system of polynomial equations. Nevertheless, there may be degenerate situations where this is not enough.

Proposition 10. *Assume that* $\mathcal{X} = \mathbb{S}^{d-1}$, *that* $W(x, y) = w(x^\top y)$ *with continuous invertible* $w : [-1, 1] \to [0, 1]$, *and that* $P = f d\tau$ *has a density* f *which is injectively decomposed. Then for one-hop filtering c-GWNNs are dense in* $\mathcal{C}(\mathcal{X}, \mathbb{R})$.

6   Conclusion and outlooks

Just as permutation-invariant GNNs are known to fail to distinguish regular graphs of the same order, and permutation-equivariant GNNs return constant output on regular graphs, their continuous counterparts suffer from the same flaw on random graph with constant or almost-constant degree function [27]. However, we showed that the recently proposed GWNNs converge to continuous architectures which, like in the discrete world, are strictly more powerful than c-GNNs. Moreover, we proved that both permutation-invariant and permutation-equivariant c-GWNNs are universal on many random graph models of interest, including a large class of SBMs and random geometric graphs. Hence, it is for instance possible to exhibit a simple, well-separated SBM for which all c-GNNs will fail to distinguish communities while there exists a c-GWNN that perfectly separates them (Fig. 1).

We believe that our work opens many possibilities for future investigations. We examined very simple strategies for choosing the inputs $E_q(A)$ of the GWNN, but more complex, spectral-based choices could exhibit better convergence properties and approximation power. We showed universality in specific random graph models of interest, but deriving a more generic criterion is still an open question. Besides GWNNs, architectures that include high-order tensors [28] (sometimes called FGNN [1]) are known to be more powerful than the WL test. Conditions for their convergence on large graphs are still open, in particular since high-order tensors lead to high-order operators that may be difficult to manipulate. Finally, we remark that directly estimating the latent variables x_i is a classical task in statistics, for which conditions of success have been derived for various approaches, e.g. for Spectral Clustering [22]. Comparing them with GNNs is an important path for future work.

References

[1] Waïss Azizian and Marc Lelarge. Characterizing the expressive power of invariant and equivariant graph neural networks. In *International Conference on Learning Representations (ICLR)*, 2021.

[2] László Babai. Graph isomorphism in quasipolynomial time. *Proceedings of the Annual ACM Symposium on Theory of Computing*, 2016.

[3] Michael M. Bronstein, Joan Bruna, Yann Lecun, Arthur Szlam, and Pierre Vandergheynst. Geometric Deep Learning: Going beyond Euclidean data. *IEEE Signal Processing Magazine*, 34(4):18–42, 2017.

[4] Zhengdao Chen, Lei Chen, Soledad Villar, and Joan Bruna. Can graph neural networks count substructures? In *Advances in Neural Information and Processing Systems (NeurIPS)*, 2020.

[5] Zhengdao Chen, Lisha Li, and Joan Bruna. Supervised community detection with line graph neural networks. In *International Conference on Learning Representations (ICLR)*, 2019.

[6] Zhengdao Chen, Soledad Villar, Lei Chen, and Joan Bruna. On the equivalence between graph isomorphism testing and function approximation with GNNs. In *Advances in Neural Information Processing System (NeurIPS)*, pages 1–19, 2019.

[7] Feng Dai and Yuan Xu. *Approximation Theory and Harmonic Analysis on Spheres and Balls*. Springer, 2013.

[8] Gwendoline de Bie, Gabriel Peyré, and Marco Cuturi. Stochastic deep networks. In *International Conference on Machine Learning*, 2018.

[9] Michaël Defferrard, Xavier Bresson, and Pierre Vandergheynst. Convolutional Neural Networks on Graphs with Fast Localized Spectral Filtering. In *Advances in Neural Information and Processing Systems (NIPS)*, 2016.

[10] Nima Dehmamy, Albert-Làszlò Barabàsi, and Rose Yu. Understanding the representation power of graph neural networks in learning graph topology. In *Advances in Neural Information and Processing Systems (NeurIPS)*, 2019.

[11] Costas Efthimiou and Christopher Frye. *Spherical harmonics in p dimensions*. World Scientific, 2014.

[12] Vikas K. Garg, Stefanie Jegelka, and Tommi Jaakkola. Generalization and representational limits of graph neural networks. In *International Conference on Machine Learning (ICML)*, pages 1–22, 2020.

[13] Floris Geerts. The expressive power of kth-order invariant graph networks. *arXiv:2007.12035*, 2020.

[14] Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural Message Passing for Quantum Chemistry. In *International Conference on Machine Learning (ICML)*, pages 1–14, 2017.

[15] William L. Hamilton. *Graph Representation Learning*. Morgan & Claypool, 2020.

[16] Paul W Holland. Stochastic blockmodels: First steps. *Social Networks*, 5(2):109–137, 1983.

[17] Kurt Hornik, Maxwell Stinchcombe, and Halbert White. Multilayer Feedforward Networks are Universal Approximators. *Neural Networks*, 2:359–366, 1989.

[18] Weihua Hu, Matthias Fey, Marinka Zitnik, Yuxiao Dong, Hongyu Ren, Bowen Liu, Michele Catasta, and Jure Leskovec. Open Graph Benchmark: Datasets for Machine Learning on Graphs. *Neural Information Processing Systems (NeurIPS)*, 2020.

[19] Nicolas Keriven, Alberto Bietti, and Samuel Vaiter. Convergence and Stability of Graph Convolutional Networks on Large Random Graphs. In *Advances in Neural Information and Processing Systems (NeurIPS)*, pages 1–26, 2020.

[20] Nicolas Keriven and Gabriel Peyré. Universal Invariant and Equivariant Graph Neural Networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 1–19, 2019.

[21] Thomas N Kipf and Max Welling. Semi-Supervised Learning with Graph Convolutional Networks. In *International Conference on Learning Representations (ICLR)*, 2017.

[22] Jing Lei and Alessandro Rinaldo. Consistency of spectral clustering in stochastic block models. *Annals of Statistics*, 43(1):215–237, 2015.

[23] Ron Levie, Michael M. Bronstein, and Gitta Kutyniok. Transferability of spectral graph convolutional neural networks. *arXiv:1907.12972*, pages 1–41, 2019.

[24] Andreas Loukas. How hard is to distinguish graphs with graph neural networks? In *Advances in Neural Information and Processing Systems (NeurIPS)*, 2020.

[25] Andreas Loukas. What graph neural networks cannot learn: depth vs width. In *ICLR*, 2020.

[26] László Lovász. Large networks and graph limits. *Colloquium Publications*, 60, 2012.

[27] Abram Magner, Mayank Baranwal, and Alfred O. Hero. The Power of Graph Convolutional Networks to Distinguish Random Graph Models. *arXiv:1910.12954*, pages 1–27, 2019.

[28] Haggai Maron, Heli Ben-Hamu, Hadar Serviansky, and Yaron Lipman. Provably Powerful Graph Networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 1–12, 2019.

[29] Haggai Maron, Ethan Fetaya, Nimrod Segol, and Yaron Lipman. On the Universality of Invariant Networks. In *International Conference on Machine Learning (ICML)*, 2019.

[30] Mathew Penrose. *Random Geometric Graphs*. Oxford University Press, 2008.

[31] Allan Pinkus. Approximation theory of the MLP model in neural networks. *Acta Numerica*, 8(May):143–195, 1999.

[32] Ali Rahimi and Benjamin Recht. Weighted sums of random kitchen sinks: Replacing minimization with randomization in learning. In *Advances in Neural Information Processing Systems (NIPS)*, 2009.

[33] Luana Ruiz, Luiz F.O. Chamon, and Alejandro Ribeiro. Graphon neural networks and the transferability of graph neural networks. In *Advances in Neural Information and Processing Systems (NeurIPS)*, 2020.

[34] Roman Vershynin. *High-dimensional probability: An introduction with applications in data science*. Cambridge University Press, 2018.

[35] Clément Vignac, Andreas Loukas, and Pascal Frossard. Building powerful and equivariant graph neural networks with message-passing. In *Advances in Neural Information and Processing Systems (NeurIPS)*, 2020.

[36] Ulrike Von Luxburg, Mikhail Belkin, and Olivier Bousquet. Consistency of spectral clustering. *Annals of Statistics*, 36(2):555–586, 2008.

[37] B Yu Weisfeiler and A A Leman. The Reduction of a Graph to Canonical Form and the Algebra Which Appears Therein. *Nti*, 2(9):12–16, 1968.

[38] Zonghan Wu, Shirui Pan, Fengwen Chen, Guodong Long, Chengqi Zhang, and Philip S. Yu. A Comprehensive Survey on Graph Neural Networks. *IEEE Transactions on Neural Networks and Learning Systems*, pages 1–21, 2020.

[39] Bingbing Xu, Huawei Shen, Qi Cao, Yunqi Qiu, and Xueqi Cheng. Graph wavelet neural network. *International Conference on Learning Representations (ICLR)*, pages 1–13, 2019.

[40] Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How Powerful are Graph Neural Networks? In *ICLR*, pages 1–15, 2019.

[41] Gilad Yehudai, Ethan Fetaya, Eli Meirom, Gal Chechik, and Haggai Maron. On Size Generalization in Graph Neural Networks. *arXiv:2010.08853*, 2020.

[42] Manzil Zaheer, Satwik Kottur, Siamak Ravanbhakhsh, Barnabás Póczos, Ruslan Salakhutdinov, and Alexander J. Smola. Deep sets. *Advances in Neural Information Processing Systems (NeurIPS)*, 2017-December(ii):3392–3402, 2017.

[43] Aaron Zweig and Joan Bruna. A functional perspective on learning symmetric functions with neural networks. *arXiv*, pages 1–19, 2020.