High-probability bounds for Non-Convex Stochastic Optimization with Heavy Tails

Abstract

We consider non-convex stochastic optimization using first-order algorithms for which the gradient estimates may have heavy tails. We show that a combination of gradient clipping, momentum, and normalized gradient descent yields convergence to critical points in high-probability with best-known rates for smooth losses when the gradients only have bounded $\mathfrak{p}$th moments for some $\mathfrak{p} \in (1, 2]$. We then consider the case of second-order smooth losses, which to our knowledge have not been studied in this setting, and again obtain high-probability bounds for any $\mathfrak{p}$. Moreover, our results hold for arbitrary smooth norms, in contrast to the typical SGD analysis which requires a Hilbert space norm. Further, we show that after a suitable "burn-in" period, the objective value will monotonically decrease for every iteration until a critical point is identified, which provides intuition behind the popular practice of learning rate "warm-up" and also yields a last-iterate guarantee.

1 SGD and Heavy Tails

The standard algorithm for training large machine learning models today is stochastic gradient descent (SGD) and its myriad variants [13, 11, 19, 38, 28]. SGD enjoys many properties that help explain its empirical success: it can be implemented very easily, can efficiently process training data in a streaming manner, and even achieves the optimal convergence rate for finding critical points of smooth non-convex objectives [2]. In particular, SGD can be understood as optimizing the following stochastic optimization problem:

$$\min_{\vec{w}} F(\vec{w}) = \mathbb{E}_z[f(\vec{w}, z)]$$

where $f(\vec{w}, z)$ is some loss function taking model parameters $\vec{w}$ and a random example z, where z has some distribution P_z. Then SGD consists of the update:

$$\vec{w}_{t+1} = \vec{w}_t - \eta \nabla f(\vec{w}_t, z_t)$$

where $z_1, \ldots, z_T$ are i.i.d. random variables distributed according to P_z, and η is some real number called the learning rate. Assuming that F is L-smooth and that $\nabla f(\vec{w}, z)$ satisfies $\mathbb{E}[\|\nabla f(\vec{w}, z)\|^2] \leq G^2$ for some σ for all $\vec{w}$, SGD satisfies:

$$\frac{1}{T} \mathbb{E}\left[\sum_{t=1}^{T} \|\nabla F(\vec{w}_t)\|^2\right] \leq O\left(\frac{L\Delta}{T} + \frac{G^2}{\sqrt{T}}\right)$$

where $\Delta = F(\vec{w}_1) - \inf F(\vec{w})$. This implies that SGD takes $O(\epsilon^{-4})$ iterations to find an ϵ-critical point, which is a point $\vec{w}$ such that $\|\nabla F(\vec{w})\| \leq \epsilon$ [13]. When the stochastic gradients are further assumed to have light sub-gaussian tails, [21] shows that SGD with momentum can achieve this same result in high probability as well.

However, recent work [30, 31, 41, 40, 42] suggests that one or both of the assumptions on smoothness or bounded variance may be too optimistic in practical deep learning problems. In particular, Zhang et al. [42] provides empirical evidence that large NLP models based on attention and transformers [34, 10] have *heavy-tailed* gradients. In particular, the variance is extremely large (perhaps even infinite), but the $\mathfrak{p}th$ moment is bounded for some $\mathfrak{p} \in (1, 2]$. This setting is significantly more complicated, and SGD's convergence properties are difficult to characterize even when assuming slightly stronger tail bounds [29] or various versions of convexity [35].

A standard tool when working with heavy-tailed random variables is truncation, or *clipping*. Succinctly, if X is a random variable such that $\mathbb{E}[\|X\|^2] = \infty$, X itself may be poorly behaved due to the heavy tail, but a truncated value $X^{\text{clip}} = \frac{X}{|X|} \min(|X|, \tau)$ will be much more benign so long as τ is chosen in an appropriate manner [6, 23]. Fortuitously, gradient clipping has long been a standard technique to improve training of deep neural networks [26]. Recent analysis [42, 14] suggests that clipping allows SGD to deal with heavy-tailed stochastic gradients. Specifically, [42] shows that SGD combined with clipping can find an ϵ-critical point in expectation in $O\left(\epsilon^{-\frac{3\mathfrak{p}-2}{\mathfrak{p}-1}}\right)$ iterations.

We propose to improve upon this backdrop in three important ways. First, the prior analysis of [42] for non-convex convergence of SGD under heavy tails only provides an *in-expectation* analysis. In-expectation results are unsatisfying because the convergence rate itself is a random variable, and so might *also* have a heavy tail. In this case individual training runs could be quite poor. Since training modern networks is quite expensive [27, 5], it is important to be confident that each and every training run will produce a high-quality result. We provide a variant of the normalized SGD algorithm of Cutkosky & Mehta [9] that incorporates gradient clipping and show that the method finds an ϵ-critical point in $\tilde{O}\left(\epsilon^{-\frac{3\mathfrak{p}-2}{\mathfrak{p}-1}}\right)$ iterations with high probability.

Second, the vast majority of first-order optimization methods for stochastic non-convex optimization consider exclusively the standard L_2 or Hilbert-space norm. Such analyses can take advantage of the fact that $\mathbb{E}[\langle \vec{g}, \nabla F(x) \rangle] = \|\nabla F(x)\|^2$ when $\vec{g}$ is an unbiased estimate of $\nabla F(x)$. In contrast, our algorithms find critical points when the gradient is measured with any smooth norm (i.e. in a Banach space). This is another motivation for momentum: momentum-based updates typically *do not* rely on an unbiasedness argument, and so the techniques can be extended to more general norms.

Third, recent theoretical advances in non-convex optimization have produced a number of new algorithms that avoid the lower-bounds of [2] by assuming extra structure on the objective F, such as *second-order smoothness*. In this case, [32, 1, 12, 9, 3] provide algorithms that achieve faster convergence rates. In particular, the algorithms of [12, 9] can find an ϵ-critical point in $O(\epsilon^{3.5})$ iterations using a first-order stochastic oracle, which is the optimal rate [3]. To our knowledge, no analysis even in expectation exists for second-order smooth losses under heavy tails. We fill this gap, providing an algorithm that identifies an ϵ-critical point in $\tilde{O}\left(\epsilon^{-\frac{5\mathfrak{p}-3}{2\mathfrak{p}-2}}\right)$ iterations with high probability. Further, in both smooth and second-order smooth cases we provide a convergence guarantee for the *last iterate* of the optimization algorithm: with high probability, the objective value for the final iterate will be smaller than the objective value at some approximate critical point.

Finally, we discuss an intriguing connection to the popular *warm-up* learning rate schedule [16, 15, 10], in which the learning rate starts small and increases over the first iterations of training. We show that for normalized SGD with momentum, after a brief "burn-in" period, the objective value decreases monotonically until an approximate critical point is reached. This provides an alternative motivation for warm-up: it would be reasonable to keep the learning rate small during the "burn-in" period. There is a long line of empirical research in understanding the need for warm-up. Warm-up has been shown to be connected to the use of layer-normalization, and that improved use of layer-norm can enable warm-up free training of transformer models Chen et al. [7], Wang et al. [36], Nguyen & Salazar [25]. Huang et al. [18] further build on these insights and proposes a weight initialization scheme which removes the need for both layer normalization and warm-up while training transformer models. Finally, Liu et al. [22] demonstrate that the variance of the learning rate in optimizers like Adam is abnormally high in the early stages of the optimization process and further hypothesize that warm-up aids by reducing the variance in that stage.

Paper Organization: in Section 1.1 we provide our concrete assumptions and setup. In Sections 2 and 3, we provide our algorithms and high-probability convergence bounds. In Section 4, we provide some empirical observations on the effect of the burn-in phase in our analysis.

1.1 Setup and assumptions

We assume that the objective $F(\vec{w}) = \mathbb{E}[f(\vec{w}, z)]$ is a Frechet-differentiable function mapping a Banach space $\mathcal{B}$ to the reals $\mathbb{R}$. Let $\|\cdot\|$ be the norm in $\mathcal{B}$ and $\|\cdot\|_\star$ be the dual norm in the dual space $\mathcal{B}^\star$. To preserve analogy and notation from the Hilbert space setting, we will write $\langle v, w \rangle$ to indicate the application of a dual vector $v \in \mathcal{B}^\star$ to a vector $w \in \mathcal{B}$. We assume that $\|\cdot\|_\star^p$ is Frechet differentiable and satisfies for some p, C for all $x, y \in \mathcal{B}$:

$$\|x + y\|_\star^p \leq \|x\|_\star^p + \langle \nabla \|x\|_\star^p, y \rangle + C\|y\|_\star^p \tag{1}$$

Such a Banach space is called (p, C)-smooth. Note that if $\|\cdot\|$ is the standard p norm in $\mathbb{R}^n$ for $p \in (1, 2]$, then $\|\cdot\|$ is the corresponding q norm, and the dual space is $(2, \frac{1}{p-1})$-smooth. In the common case that $\mathcal{B}$ is a Hilbert space (e.g. $\mathbb{R}^n$ with the euclidean norm), then $\mathcal{B} = \mathcal{B}^\star$, $\|\cdot\| = \|\cdot\|_\star$ and $p = 2$ and $C = 1$. In this paper, we will exclusively consider the case $p = 2$ and $C \geq 1$. Finally, given any $v \in \mathcal{B}^\star$, we will write $d(v) \in \mathcal{B}$ to indicate a unit vector satisfying both $\|d(v)\| = 1$ and $\langle v, d(v) \rangle = \|v\|_\star$, which we assume exists for all v. For more background on Banach spaces, see Appendix D.

We assume F is L-smooth, which means that $\|\nabla F(\vec{w}) - \nabla F(\vec{x})\|_\star \leq L\|\vec{w} - \vec{z}\|_\star$. In Section 3, we will also assume that F is ρ-second-order smooth, which means that $\|(\nabla^2 F(\vec{w}) - \nabla^2 F(\vec{x}))v\|_\star \leq \rho\|\vec{w} - \vec{x}\|\|v\|$ for all $\vec{w}, \vec{x}, v \in \mathcal{B}$. We assume that $\nabla f(\vec{w}, z)$ satisfies $\mathbb{E}[\|\nabla f(\vec{w}, z) - \nabla F(\vec{w}, z)\|_\star^{\mathfrak{p}}] \leq G^{\mathfrak{p}}$ for some G and some $\mathfrak{p} \in (1, 2]$. We will design algorithms such that after T stochastic gradient evaluations, we can output a point $\vec{w}$ such that $\|\nabla F(\vec{w})\|_\star$ is small with high probability.

2 Normalized SGD with Momentum

In this section, we describe our algorithms for finding critical points with high probability in non-convex objectives. Our analysis makes use of gradient clipping, momentum, and normalized updates. Clipping is a standard technique for mitigating the effect of heavy tails, essentially by throwing out outlier data. Momentum is useful as it intuitively averages together many clipped gradients, resulting in a gradient estimate that concentrates about its mean with high probability. Normalizing the updates allows for significantly simplified analyses because the bias terms introduced by the moving average in momentum are now very precisely controlled by the learning rate, as originally analyzed for Hilbert spaces in [9]. In the Banac space case In order to analyze this algorithm, we need the following critical Lemma, which characterizes the effect of taking a norma

Lemma 1. *Suppose $F : \mathcal{B} \to \mathbb{R}$ be a Frechet-differentiable L-Smooth from a Banach space $\mathcal{B}$ to the reals. Let $w \in B$. Let $g^\star \in \mathcal{B}^\star$ and let $g \in \mathcal{B}$ be a unit-vector satisfying $\langle g^\star, g \rangle = \|g\|_\star$. Define $w' = w - \eta g$. Define $\epsilon = g^\star - \nabla F(w)$. Then:*

$$F(w') \leq F(w) - \eta\|\nabla F(w)\|_\star + 2\eta\|\epsilon\|_\star + \frac{L\eta^2}{2}$$

Algorithm 1 Normalized SGD with Clipping and Momentum

Input: Initial Point $\vec{w}_1$, learning rates η, momentum parameters α, clipping parameter τ, time horizon T:

Set $\vec{m}_1 = 0$.

for $t = 1 \ldots T$ **do**

   Sample $z_t \sim P_z$.

   Set $\vec{g}_t^{\text{clip}} = \frac{\nabla f(\vec{w}_t, z_t)}{\|\nabla f(\vec{w}_t, z_t)\|_\star} \min(\tau, \|\nabla f(\vec{w}_1, z_t)\|_\star)$.

   Set $\vec{m}_t = \beta \vec{m}_{t-1} + (1 - \beta)\vec{g}_t^{\text{clip}}$.

   Set $\vec{w}_{t+1} = \vec{x}_t - \eta d(\vec{m}_t)$.

end for

Theorem 2. *Suppose $\mathbb{E}_z[\|\nabla f(\vec{w}, z)\|_\star^{\mathfrak{p}}] \leq G^{\mathfrak{p}}$ for all $\vec{x}$ for some G. Suppose F is L-smooth. Set $\beta = 1 - \alpha$, $\alpha = \frac{b}{T^{\frac{\mathfrak{p}}{3\mathfrak{p}-2}}}$ and $\eta = \frac{s}{T^{\frac{2\mathfrak{p}-1}{3\mathfrak{p}-2}}}$ for arbitrary constant b and s satisfying $\alpha \leq 1$ and set $\tau = G/\alpha^{1/\mathfrak{p}}$. Then with probability at least $1 - \delta$:*

$$\frac{1}{T}\sum_{t=1}^{T} \|\nabla F(\vec{w}_t)\|_\star \leq O\left(\frac{\log(T/\delta)}{T^{\frac{\mathfrak{p}-1}{3\mathfrak{p}-2}}}\right)$$

117 *where the big-Oh hides constant that depend on L, G b, s, p, C and $F(\vec{w}_1) - F(\vec{w}_{T+1})$, but not T*
118 *or δ.*

119 This Theorem provides an analog of the standard in-expectation result for non-convex optimization,
120 but now the result holds with high-probability. Note that this matches the in-expectation convergence
121 rates from Zhang et al. [42]. The next Theorem takes this theme one step further: it shows that after a
122 brief "burn-in" period, the decrease in objective value will in fact be *monotonic* with high probability:

124 **Theorem 3.** *Under the assumptions of Theorem 2, define the constants:*

$$K = 10C \max(1, \log(3T/\delta)) + 4C^{1/2}\sqrt{\max(1, \log(3T/\delta))} + 1$$

$$Z = \frac{sL}{b} + GKb^{\frac{\mathfrak{p}-1}{\mathfrak{p}}}$$

125 *Then, with probability at least $1 - \delta$, if*

$$t \geq \mathcal{T} = \frac{T^{\frac{\mathfrak{p}}{3\mathfrak{p}-2}}}{b}\left(\frac{\mathfrak{p}-1}{3\mathfrak{p}-2}\log(T) + \log(G) - \log(Z)\right)$$

126 *Then we have*

$$\|\vec{m}_t - \nabla F(\vec{w}_t)\|_\star \leq \frac{2Z}{T^{\frac{\mathfrak{p}-1}{3\mathfrak{p}-2}}}$$

127 *And so long as*

$$\|\vec{m}_t\|_\star \geq 2\left(\frac{6Z}{T^{\frac{\mathfrak{p}-1}{3\mathfrak{p}-2}}} + \frac{Ls}{2T^{\frac{2\mathfrak{p}-1}{3\mathfrak{p}-2}}}\right) \tag{2}$$

128 *we have $F(\vec{w}_{t+1}) < F(\vec{w}_t) - \frac{\eta}{2}\|\vec{m}_t\|_\star$. Moreover, if (2) is ever not satisfied for some $t \geq \mathcal{T}$, we*
129 *must have*

$$\|\nabla F(\vec{w}_t)\|_\star \leq \frac{14Z}{T^{\frac{\mathfrak{p}-1}{3\mathfrak{p}-2}}} + \frac{Ls}{T^{\frac{2\mathfrak{p}-1}{3\mathfrak{p}-2}}}$$

130 *Finally, if t is the iteration with smallest value of $\|\vec{m}_t\|_\star$ such that $t \geq \mathcal{T}$, we have with probability at*
131 *least $1 - \delta$:*

$$\|\nabla F(\vec{w}_t)\|_\star \leq O\left(\frac{\log(T/\delta)}{T^{\frac{\mathfrak{p}-1}{3\mathfrak{p}-2}}}\right)$$

132 Theorem 3 shows that after a small burn-in period $\mathcal{T} = o(T)$, $\vec{m}_t$ is very likely to be an extremely
133 good estimate of the true gradient $\nabla F(\vec{x}_t)$. Moreover, we can empirically detect this event by
134 monitoring the norm of the exponentially weighted moving average $\vec{m}$. This burn-in period is
135 especially interesting given the success of learning rate schedules that incorporate a "warm-up"
136 component, in which the learning rate actually increases during the first iterations. Our result seems
137 to hint at a mechanism for this schedule: by keeping the learning rate small during the burn-in period,
138 we can limit any increase in the objective value until we reach the stage at which it begins to decrease
139 steadily.

140 Further, Theorem 3 provides a very concrete algorithm to find critical points: after the burn-in period
141 of $\tilde{O}(T^{\frac{\mathfrak{p}}{3\mathfrak{p}-2}})$ iterates, we can simply return the point $\vec{x}_t$ with the smallest value of $\|\vec{m}_t\|$. Intuitively,
142 this works because the objective value can only increase by a total of $O(T^{\frac{\mathfrak{p}}{3\mathfrak{p}-2}}\eta) = O(T^{\frac{1-\mathfrak{p}}{3\mathfrak{p}-2}}) = $
143 $O(1)$ during the burn-in period so even without a learning rate "warm-up", we should not expect the
144 burn-in period to have too significant an effect on the objective value. After the burnin-in period, $\vec{m}_t$
145 is always very close to $\nabla F(\vec{w}_t)$, so we make steady progress until a critical point is encountered.

146 *Proof of Theorem 2.* Define $\hat{\epsilon}_t = \vec{m}_t - \nabla F(\vec{w}_t)$. and $\epsilon_t = \vec{g}_t^{\text{clip}} - \nabla F(\vec{w}_t)$. Also, define $S(a, b) = $
147 $\nabla F(a) - \nabla F(b)$. By smoothness, we have $\|S(\vec{w}_t, \vec{w}_{t+1})\|_\star \leq L\|\vec{w}_t - \vec{w}_{t+1}\|_\star$

148 If we define $\vec{w}_0 = \vec{w}_1$, then we have the following recursive formulation for any $t \geq 0$:

$$\vec{m}_{t+1} = (1-\alpha)(\nabla F(\vec{w}_t) + \hat{\epsilon}_t) + \alpha \vec{g}_{t+1}^{\text{clip}}$$
$$= \nabla F(\vec{w}_{t+1}) + (1-\alpha)(S(\vec{w}_t, \vec{w}_{t+1}) + \hat{\epsilon}_t) + \alpha\epsilon_{t+1}$$
$$\hat{\epsilon}_{t+1} = (1-\alpha)S(\vec{w}_t, \vec{w}_{t+1}) + (1-\alpha)\hat{\epsilon}_t + \alpha\epsilon_{t+1}$$

149   Now, we unravel the recursion for $t + 1$ iterations:

$$\hat{\epsilon}_{t+1} = (1-\alpha)^t \hat{\epsilon}_0 + \alpha \sum_{t'=0}^{t} (1-\alpha)^{t'} \epsilon_{t+1-t'} + (1-\alpha) \sum_{t'=0}^{t} (1-\alpha)^{t'} S(\vec{w}_{t-t'}, \vec{w}_{t+1-t'})$$

150   Next, take the magnitude of both sides and use triangle inequality (using the fact that
151    $\|S(\vec{w}_a, \vec{w}_{t+1})\|_\star \le L\eta$):

$$\|\hat{\epsilon}_{t+1}\|_\star \le (1-\alpha)^t \|\hat{\epsilon}_0\|_\star + \alpha \left\| \sum_{t'=0}^{t} (1-\alpha)^{t'} \epsilon_{t+1-t'} \right\|_\star + (1-\alpha)\eta L \sum_{t'=0}^{t} (1-\alpha)^{t'}$$

$$\le (1-\alpha)^t G + \frac{(1-\alpha)\eta L}{\alpha} + \alpha \left\| \sum_{t'=0}^{t} (1-\alpha)^{t'} \epsilon_{t+1-t'} \right\|_\star$$

152   where in the second line we have used $\vec{m}_0 = 0$ and $\|\nabla F(\vec{w}_0)\|_\star \le G$, which follows since
153    $\|\nabla F(\vec{w}_0)\|_\star \le \mathbb{E}_z[\|\nabla f(\vec{w}_0, z)\|_\star^{\mathfrak{p}}]^{1/\mathfrak{p}} = G$.

154   Now, by Lemma 9, with probability at least $1 - \delta/T$:

$$\left\| \sum_{t'=0}^{t} (1-\alpha)^{t'} \epsilon_{t+1-t'} \right\|_\star \le 10C\tau \max(1, \log(3T/\delta)) + \sum_{t'=0}^{t} \frac{(1-\alpha)^{t'} G^{\mathfrak{p}}}{\tau^{\mathfrak{p}-1}}$$

$$+ 4 \left(C \sum_{t'=0}^{t} (1-\alpha)^{2t'} G^{\mathfrak{p}} \tau^{2-\mathfrak{p}} \right)^{1/2} \sqrt{\max(1, \log(3T/\delta))}$$

$$\le 10C\tau \max(1, \log(3T/\delta)) + \frac{G^{\mathfrak{p}}}{\alpha\tau^{\mathfrak{p}-1}} + \frac{4 \left(CG^{\mathfrak{p}} \tau^{2-\mathfrak{p}} \right)^{1/2} \sqrt{\max(1, \log(3T/\delta))}}{\alpha^{1/2}}$$

155   Therefore, with probability at least $1 - \delta/T$:

$$\|\hat{\epsilon}_{t+1}\|_\star \le (1-\alpha)^t G + \frac{(1-\alpha)\eta L}{\alpha} + 10C\alpha\tau \max(1, \log(3T/\delta))$$

$$+ 4 \left(\alpha CG^{\mathfrak{p}} \tau^{2-\mathfrak{p}} \right)^{1/2} \sqrt{\max(1, \log(3T/\delta))} + \frac{G^{\mathfrak{p}}}{\tau^{\mathfrak{p}-1}}$$

156   Now, with $\tau = \frac{G}{\alpha^{1/\mathfrak{p}}}$, and $D_\delta = \max(1, \log(3T/\delta))$ this becomes:

$$\le (1-\alpha)^t G + \frac{(1-\alpha)\eta L}{\alpha} + G\alpha^{1-1/\mathfrak{p}} \left[10CD_\delta + 4C^{1/p} \sqrt{D_\delta} + 1 \right]$$

$$= (1-\alpha)^t G + \frac{(1-\alpha)\eta L}{\alpha} + G\alpha^{1-1/\mathfrak{p}} K \tag{3}$$

157   where we define the constant $K = 10CD_\delta + 4C^{1/2}\sqrt{D_\delta} + 1$.

158   Now, we have from Lemma 1:

$$\sum_{t=1}^{T} \|\nabla F(\vec{w}_t)\|_\star \le \frac{F(\vec{w}_1) - F(\vec{w}_T)}{\eta} + \frac{LT\eta}{2} + 2 \sum_{t=1}^{T} \|\hat{\epsilon}_t\|_\star$$

159   so with probability at least $1 - \delta$:

$$\le \frac{F(\vec{w}_1) - F(\vec{w}_T)}{\eta} + \frac{LT\eta}{2} + 2 \sum_{t=1}^{T} (1-\alpha)^t G + \frac{(1-\alpha)\eta L}{\alpha} + G\alpha^{1-1/\mathfrak{p}} K$$

$$\le \frac{F(\vec{w}_1) - F(\vec{w}_T)}{\eta} + \frac{LT\eta}{2} + \frac{2G(1-\alpha)}{\alpha} + \frac{2(1-\alpha)\eta TL}{\alpha} + 2GT\alpha^{1-1/\mathfrak{p}} K$$

160   Now set $\alpha = \frac{b}{T^{\frac{\mathfrak{p}}{3\mathfrak{p}-2}}}$ and $\eta = \frac{s}{T^{\frac{2\mathfrak{p}-1}{3\mathfrak{p}-2}}}$. This yields:

$$\frac{1}{T} \sum_{t=1}^{T} \|\nabla F(\vec{w}_t)\| \le O\left(T^{\frac{1-\mathfrak{p}}{3\mathfrak{p}-2}} \log(T/\delta) \right)$$

161    $\square$

162 The proof of Theorem 3 follows essentially the same idea as that of Theorem 2. However, this time
163 we use the explicit bound on $\|\hat{\epsilon}_t\|_\star$ and observe that after the burn-in period, the contribution from
164 $\|\epsilon_1\|_\star$ has decreased exponentially to be insignificant, and so $\vec{m}_t$ will be a very high-quality estimate
165 of $\nabla F(\vec{x}_t)$ at every single iteration.

166 *Proof of Theorem 3.* Use the settings $\eta = \frac{c}{T^{\frac{2p-1}{3p-2}}}$ and $\alpha = \frac{b}{T^{\frac{p}{3p-2}}}$ and notice that from equation (3)
167 that with probability $1 - \delta$, for all t:

$$\|\hat{\epsilon}_{t+1}\|_\star \leq (1-\alpha)^t G + \frac{sL}{bT^{\frac{p-1}{3p-2}}} + \frac{GKb^{\frac{p-1}{p}}}{T^{\frac{p-1}{3p-2}}} = (1-\alpha)^t G + \frac{Z}{T^{\frac{p-1}{3p-2}}}$$

168 Further, we have

$$\log(1-\alpha) \leq -\alpha$$
$$\log\left(G(1-\alpha)^t\right) \leq -t\alpha + \log(G)$$

169 Therefore, if $t \geq \mathcal{T}$, then we have with probability at least $1 - \delta$:

$$\|\hat{\epsilon}_{t+1}\|_\star \leq \frac{2Z}{T^{\frac{p-1}{3p-2}}}$$

170 This implies the bound on $\|\nabla F(\vec{w}_t)\|_\star$ when $\|\vec{m}_t\|_\star$ is smaller than the threshold described in the
171 Theorem statement. Next, again from Lemma 1,

$$F(\vec{w}_{t+1}) \leq F(\vec{w}_t) - \eta\|\nabla F(\vec{w}_t)\|_\star + 2\eta\|\hat{\epsilon}_t\|_\star + \frac{L\eta^2}{2}$$
$$\leq F(\vec{w}_t) - \eta\|\vec{m}_t\|_\star + 3\eta\|\hat{\epsilon}_t\|_\star + \frac{L\eta^2}{2}$$
$$\leq F(\vec{w}_t) - \eta\|\vec{m}_t\|_\star + \eta\left(\frac{6Z}{T^{\frac{p-1}{3p-2}}} + \frac{Ls}{2T^{\frac{2p-1}{3p-2}}}\right)$$

172 from which we can conclude that if $\|\vec{m}_t\|_\star \geq 2\left(\frac{6Z}{T^{\frac{p-1}{3p-2}}} + \frac{Ls}{2T^{\frac{2p-1}{3p-2}}}\right)$, $F(\vec{w}_{t+1}) \leq F(\vec{w}_t) - \frac{\eta}{2}\|\vec{m}_t\|_\star$.

173 Now, for the final part of the Theorem, observe that since F is G-Lipschitz, we must have that

$$F(\vec{w}_\mathcal{T}) - F(\vec{w}_1) \leq G\mathcal{T}\eta = O(\log(T))$$

174 so that $F(\vec{w}_\mathcal{T}) - F(\vec{w}_{T+1}) \leq O(F(\vec{w}_1) - F(\vec{w}_{T+1}) + \log(T))$. Now consider two cases, either

$$\min_{t \geq \mathcal{T}} \|\vec{m}_t\|_\star \leq 2\left(\frac{6Z}{T^{\frac{p-1}{3p-2}}} + \frac{Ls}{2T^{\frac{2p-1}{3p-2}}}\right)$$

175 or not. In the first case, by our bound on $\|\hat{\epsilon}_t\|_\star$, the desired bound on $\|\nabla F(\vec{w}_t)\|_\star$ follows. In the
176 latter case, we have

$$F(\vec{w}_{T+1}) \leq F(\vec{w}_\mathcal{T}) - \frac{\eta}{2}\sum_{t=\mathcal{T}}^{T}\|\vec{m}_t\|_\star$$

177 So that

$$\min_{t \geq \mathcal{T}}\|\vec{m}_t\|_\star \leq O\left(\frac{F(\vec{w}_1) - F(\vec{w}_{T+1}) + \log(T)}{T\eta}\right) = \tilde{O}\left(\frac{1}{T^{\frac{2p-1}{3p-2}}}\right)$$

178 And so again the result follows from our bound on $\|\hat{\epsilon}_t\|_\star$. $\qquad\square$

179 In addition to providing a method for identifying critical points, Theorem 3 also provides an intuitively
180 desirable guarantee about the *last-iterate* of the algorithm $\vec{w}_T$. Specifically, one can easily check that
181 the following Corollary:

Corollary 4. *Under the notation and assumptions of Theorem 3, with probability at least $1 - \delta$, there exists some $\hat{w}$ such that both of the following inequalities hold:*

$$\|\nabla F(\hat{w})\|_\star \leq O\left(\frac{\log(T/\delta)}{T^{\frac{\mathrm{p}-1}{3\mathrm{p}-2}}}\right)$$

$$F(\vec{w}_T) \leq F(\hat{w})$$

where $\vec{w}_T$ is the last iterate of Algorithm 1

Proof. Set $\hat{w}$ to be the last iterate for which condition 2 does not hold. Then the result is immediately implied by Theorem 2. $\qquad\square$

In most applications we are not actually interested in finding critical points, but instead wish to actually minimize the objective F. This observation tells us that our objective value is at least never worse than it would have been if had indeed searched specifically for a critical point. Moreover, by providing a guarantee about $\vec{w}_T$, we have a closer match to practical use-cases: many of the theoretical analyses of non-convex stochastic gradient methods [13, 37, 20] only show that a *randomly selected iterate* has a small gradient norm. In contrast, Corollary 4 provides a non-asymptotic guarantee for the final iterate, which is the iterate most likely to be deployed after training in practice.

3   Second-Order Smooth Losses

In this section, we provide our extension to losses that are *second order smooth*. The overall method is very similar: we employ normalized SGD with momentum. However, in order to take advantage of the second-order smoothness, we will need to use a more advanced form of momentum. Specifically, we use implicit gradient transport [4], as implemented by Cutkosky & Mehta [9] in the NIGT algorithm. This algorithm replaces the standard momentum update with an extrapolation procedure:

$$\vec{m}_t = \beta\vec{m}_{t-1} + (1 - \beta)\nabla f\left(\vec{w}_t + \frac{\beta(\vec{w}_t - \vec{w}_{t-1})}{1 - \beta}, z_t\right)$$

By evaluating the gradient at the "shifted" point $\vec{w}_t + \frac{\beta(\vec{w}_t - \vec{w}_{t-1})}{1 - \beta}$ and performing a second-order Taylor expansion enabled by the second-order smoothness assumption, it is possible to show that $\vec{m}_t$ is a less-biased estimate of $\nabla F(\vec{w}_t)$ than it would be using the standard momentum update. We augment this procedure with gradient clipping in Algorithm 2 below, and provide its analysis in Theorems 5 and 6, which are directly analogous to Theorems 2 and 3.

Algorithm 2 NIGT with Clipping

Input: Initial Point $\vec{w}_1$, learning rates η, momentum parameters α, clipping parameter τ, time horizon T:
Set $\vec{m}_1 = 0$.
for $t = 1 \ldots T$ **do**
    Sample $z_t \sim P_z$.
    $\vec{x}_t = \vec{w}_t + \frac{\beta(\vec{w}_t - \vec{w}_{t-1})}{1-\beta}$
    Set $\vec{g}_t^{\text{clip}} = \frac{\nabla f(\vec{x}_t, z_t)}{\|\nabla f(\vec{x}_t, z_t)\|_\star} \min(\tau, \|\nabla f(\vec{x}_1, z_t)\|_\star)$.
    Set $\vec{m}_t = \beta\vec{m}_{t-1} + (1 - \beta)\vec{g}_t^{\text{clip}}$.
    Set $\vec{w}_{t+1} = \vec{w}_t - \eta d(\vec{m}_t)$.
end for

Theorem 5. *Suppose $\mathbb{E}_z[\|\nabla f(\vec{w}, z)\|^{\mathrm{p}}] \leq G^{\mathrm{p}}$ for all $\vec{x}$ for some G. Suppose F is L-smooth and ρ-second-order smooth. Set $\beta = 1 - \alpha$, $\alpha = \frac{b}{T^{\frac{2\mathrm{p}}{5\mathrm{p}-3}}}$ and $\eta = \frac{a}{T^{\frac{3\mathrm{p}-1}{5\mathrm{p}-3}}}$ for arbitrary constants b and c satisfying $\alpha \leq 1$, and set $\tau = \frac{G}{\alpha^{1/\mathrm{p}}}$. Then with probability at least $1 - \delta$:*

$$\frac{1}{T}\sum_{t=1}^T \|\nabla F(\vec{w}_t)\|_\star \leq O\left(\frac{\log(T/\delta)}{T^{\frac{2\mathrm{p}-2}{5\mathrm{p}-3}}}\right)$$

where the big-Oh hides constant that depend on L, ρ, G, b, a, C, and $F(\vec{w}_1) - F(\vec{w}_{T+1})$, but not T or δ.

We also have a direct analog of Theorem 3

Theorem 6. *Under the assumptions of Theorem 5, define the constants:*

$$K = 6\max(1, \log(3T/\delta)) + 3\max(1, \log(3T/\delta)) + 1$$

$$Z = \frac{\rho s^2}{b^2} + GKb^{\frac{\mathfrak{p}-1}{\mathfrak{p}}}$$

Then, with probability at least $1 - \delta$, if

$$t \geq \mathcal{T} = \frac{T^{\frac{\mathfrak{p}}{3\mathfrak{p}-2}}}{b}\left(\frac{\mathfrak{p}-1}{3\mathfrak{p}-2}\log(T) + \log(G) - \log(Z)\right)$$

Then we have

$$\|\vec{m}_t - \nabla F(\vec{x}_t)\| \leq \frac{2Z}{T^{\frac{\mathfrak{p}-1}{3\mathfrak{p}-2}}}$$

And so long as

$$\|\vec{m}_t\|_\star \geq 2\left(\frac{6Z}{T^{\frac{3\mathfrak{p}-1}{5\mathfrak{p}-3}}} + \frac{Lc}{2T^{\frac{3\mathfrak{p}-1}{5\mathfrak{p}-3}}}\right) \tag{4}$$

we have $F(\vec{w}_{t+1}) < F(\vec{w}_t) - \frac{\eta}{2}\|\vec{m}_t\|$. Moreover, if (4) is ever not satisfied, we must have

$$\|\nabla F(\vec{w}_t)\|_\star \leq \frac{14Z}{T^{\frac{3\mathfrak{p}-1}{3\mathfrak{p}-3}}} + \frac{Ls}{T^{\frac{3\mathfrak{p}-1}{5\mathfrak{p}-3}}}$$

Finally, if t is the iteration with smallest value of $\|\vec{m}_t\|$ such that $t \geq \mathcal{T}$, we have with probability at least $1 - \delta$:

$$\|\nabla F(\vec{w}_t)\|_\star \leq O\left(\frac{\log(T/\delta)}{T^{\frac{\mathfrak{p}-1}{3\mathfrak{p}-2}}}\right)$$

Finally, we note that we have a statement about the last iterate of Algorithm 2 that is directly analogous to Corollary 4:

Corollary 7. *Under the notation and assumptions of Theorem 6, with probability at least $1 - \delta$, there exists some $\hat{w}$ such that both of the following inequalities hold:*

$$\|\nabla F(\hat{w})\|_\star \leq O\left(\frac{\log(T/\delta)}{T^{\frac{3\mathfrak{p}-1}{5\mathfrak{p}-2}}}\right)$$

$$F(\vec{w}_T) \leq F(\hat{w})$$

where $\vec{w}_T$ is the last iterate of Algorithm 2

4 Experiments

Our theoretical analysis suggests that there is a short "burn-in" phase in our algorithms during which the momentum estimate $\vec{m}_t$ may be far from the true gradient $\nabla F(\vec{w}_t)$, and after this period, $\vec{m}_t$ will always be close to $\nabla F(\vec{w}_t)$. As a result, during the burn-in phase it is possible for the optimizer to make slow or even negative progress, while afterwards we should expect more steady improvement. This suggests that one might set the learning rate $\eta = 0$ throughout the burn-in phase and only begin taking steps after $\vec{m}_t$ has accumulated enough gradients to be come a good estimate. This procedure is reminiscent of the common practice of learning rate "warm-up", in which the learning rate starts at 0 and is linearly increased to some desired value during the initial phase of training, and then later decreased. Thus, we sought to answer how much of the success of the warm-up schedule can be attributed to burn-in.

To answer this question, we conducted an experimental study on the BERT pretraining task. We chose to experiment on BERT since it has been shown to have heavy tails empirically [42] and the

Figure 1: Comparison between warm-up and burn-in strategies on Masked language modeling BERT pre-training task. Plot (a) compares the accuracies on the eval set for BERT-Base model and plot (b) does the same for BERT-Large.

common practice is already to clip the gradients. Typically, BERT models are trained using Adam optimizer [10] but since our analysis relies on normalized updates, we instead base our experiments on LAMB optimizer, which includes normalization and is known to obtain state of the art results on BERT task [39]. Note that we also include experimental results using Algorithm 1 in the appendix. Fig 1 shows plots for two sizes of the model, BERT-Base and BERT-Large. All our experiments were conducted using the Tensorflow framework on TPUv3 architecture. For the baseline, we reproduce all the hyperparameters from You et al. [39]. Most importantly, we train all our models using the base learning rate η_0 of 6.25e-4 and batch size of 512. As shown in Fig 1, our baseline employs the standard practice of linear warm-up for 3125 steps [39] and polynomial decay of $\eta_t = \eta_0 * \left(1 - \frac{t}{T}\right)$ for the rest of the steps. For a fair comparison with the baseline, we start the polynomial decay after 3125 steps regardless of how many steps were used for burn-in. We set the learning rate to the constant base learning rate value of 6.25e-4 for steps in between burn-in and polynomial decay. For the models trained using burn-in, instead of linear warm-up, we set the base learning rate η_0 to zero for the amount of steps we run the burn-in for. Note that, even if the the model parameters are not being changed, the accumulators in LAMB optimizer are still being updated and their fidelity being improved with more samples. As shown in Fig 1, we perform a grid search across $[250, 500, 1000, 2000]$ steps for the initial burn-in period and compare their results. In BERT-Large, burn-in for some initial period appears to help the eval accuracy of the final model compared to not allowing special treatment for the learning rate during the burn-in phase. This lends empirical support to our theoretical intuition that the initial steps of the optimization may be unhelpful, or even hurtful. Note that for BERT-Large, warm-up baseline does considerably better than models where burn-in was employed. This suggests that the linear increase in the learning rate provided by warm-up adds some additional benefit to the optimization procedure compared to our naive pure burn-in strategy that remains to be explored.

5 Conclusion

We have provided algorithms based on normalized SGD with momentum and gradient clipping that provide high probability-rates for finding critical points of non-convex objectives with heavy-tailed gradients. We also show that as a by-product of our high-probability bounds, the algorithms provide a pleasing result for the *last iterate* of the optimization procedure. Specifically, the last iterate has function value smaller than the function value of a critical point.

Finally, we identify a critical "burn-in" phase early in optimization in which the optimizer may be making poor decisions. Empirically, we show that keeping the learning rate zero for the first iterations indeed does help training compared to simply running the optimizer with no special treatment during this phase. It is an interesting question to precisely identify what other advantages are provided by the increasing schedule used by warm-up during this phase.

References

[1] Allen-Zhu, Z. Natasha 2: Faster non-convex optimization than sgd. In *Advances in neural information processing systems*, pp. 2675–2686, 2018.

[2] Arjevani, Y., Carmon, Y., Duchi, J. C., Foster, D. J., Srebro, N., and Woodworth, B. Lower bounds for non-convex stochastic optimization. *arXiv preprint arXiv:1912.02365*, 2019.

[3] Arjevani, Y., Carmon, Y., Duchi, J. C., Foster, D. J., Sekhari, A., and Sridharan, K. Second-order information in non-convex stochastic optimization: Power and limitations. In *Conference on Learning Theory*, pp. 242–299, 2020.

[4] Arnold, S. M., Manzagol, P.-A., Babanezhad, R., Mitliagkas, I., and Roux, N. L. Reducing the variance in online optimization by transporting past gradients. *arXiv preprint arXiv:1906.03532*, 2019.

[5] Brown, T. B., Mann, B., Ryder, N., Subbiah, M., Kaplan, J., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., Agarwal, S., Herbert-Voss, A., Krueger, G., Henighan, T., Child, R., Ramesh, A., Ziegler, D. M., Wu, J., Winter, C., Hesse, C., Chen, M., Sigler, E., Litwin, M., Gray, S., Chess, B., Clark, J., Berner, C., McCandlish, S., Radford, A., Sutskever, I., and Amodei, D. Language models are few-shot learners, 2020.

[6] Bubeck, S., Cesa-Bianchi, N., and Lugosi, G. Bandits with heavy tail. *IEEE Transactions on Information Theory*, 59(11):7711–7717, 2013.

[7] Chen, M. X., Firat, O., Bapna, A., Johnson, M., Macherey, W., Foster, G., Jones, L., Schuster, M., Shazeer, N., Parmar, N., and et al. The best of both worlds: Combining recent advances in neural machine translation. *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2018. doi: 10.18653/v1/p18-1008. URL `http://dx.doi.org/10.18653/v1/P18-1008`.

[8] Cutkosky, A. *Algorithms and Lower Bounds for Parameter-free Online Learning*. PhD thesis, Stanford University, 2018.

[9] Cutkosky, A. and Mehta, H. Momentum improves normalized sgd. *arXiv preprint arXiv:2002.03305*, 2020.

[10] Devlin, J., Chang, M.-W., Lee, K., and Toutanova, K. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL `https://www.aclweb.org/anthology/N19-1423`.

[11] Duchi, J., Hazan, E., and Singer, Y. Adaptive subgradient methods for online learning and stochastic optimization. In *Conference on Learning Theory (COLT)*, 2010.

[12] Fang, C., Lin, Z., and Zhang, T. Sharp analysis for nonconvex sgd escaping from saddle points. In *Conference on Learning Theory*, pp. 1192–1234, 2019.

[13] Ghadimi, S. and Lan, G. Stochastic first-and zeroth-order methods for nonconvex stochastic programming. *SIAM Journal on Optimization*, 23(4):2341–2368, 2013.

[14] Gorbunov, E., Danilova, M., and Gasnikov, A. Stochastic optimization with heavy-tailed noise via accelerated gradient clipping. In *Neural Information Processing Systems*, 2020.

[15] Goyal, P., Dollár, P., Girshick, R., Noordhuis, P., Wesolowski, L., Kyrola, A., Tulloch, A., Jia, Y., and He, K. Accurate, large minibatch sgd: Training imagenet in 1 hour, 2017.

[16] He, K., Zhang, X., Ren, S., and Sun, J. Deep residual learning for image recognition. *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2015.

[17] Howard, S. R., Ramdas, A., McAuliffe, J., and Sekhon, J. Time-uniform, nonparametric, nonasymptotic confidence sequences. *arXiv preprint arXiv:1810.08240*, 2018.

[18] Huang, X. S., Perez, F., Ba, J., and Volkovs, M. Improving transformer optimization through better initialization. In III, H. D. and Singh, A. (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 4475–4483. PMLR, 13–18 Jul 2020. URL `http://proceedings.mlr.press/v119/huang20f.html`.

[19] Kingma, D. and Ba, J. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[20] Li, X. and Orabona, F. On the convergence of stochastic gradient descent with adaptive stepsizes. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pp. 983–992. PMLR, 2019.

[21] Li, X. and Orabona, F. A high probability analysis of adaptive sgd with momentum. *arXiv preprint arXiv:2007.14294*, 2020.

[22] Liu, L., Jiang, H., He, P., Chen, W., Liu, X., Gao, J., and Han, J. On the variance of the adaptive learning rate and beyond. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=rkgz2aEKDr`.

[23] Lugosi, G. and Mendelson, S. Mean estimation and regression under heavy-tailed distributions: A survey. *Foundations of Computational Mathematics*, 19(5):1145–1190, 2019.

[24] Minsker, S. On some extensions of bernstein's inequality for self-adjoint operators. *arXiv preprint arXiv:1112.5448*, 2011.

[25] Nguyen, T. Q. and Salazar, J. Transformers without tears: Improving the normalization of self-attention. *ArXiv*, abs/1910.05895, 2019.

[26] Pascanu, R., Mikolov, T., and Bengio, Y. Understanding the exploding gradient problem. *CoRR, abs/1211.5063*, 2(417):1, 2012.

[27] Raffel, C., Shazeer, N., Roberts, A., Lee, K., Narang, S., Matena, M., Zhou, Y., Li, W., and Liu, P. J. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 21(140):1–67, 2020. URL `http://jmlr.org/papers/v21/20-074.html`.

[28] Reddi, S. J., Kale, S., and Kumar, S. On the convergence of adam and beyond. In *International Conference on Learning Representations*, 2018.

[29] Scaman, K. and Malherbe, C. Robustness analysis of non-convex stochastic gradient descent using biased expectations. *Advances in Neural Information Processing Systems*, 33, 2020.

[30] Şimşekli, U., Gürbüzbalaban, M., Nguyen, T. H., Richard, G., and Sagun, L. On the heavy-tailed theory of stochastic gradient descent for deep neural networks. *arXiv preprint arXiv:1912.00018*, 2019.

[31] Simsekli, U., Sagun, L., and Gurbuzbalaban, M. A tail-index analysis of stochastic gradient noise in deep neural networks. In *International Conference on Machine Learning*, pp. 5827–5837. PMLR, 2019.

[32] Tripuraneni, N., Stern, M., Jin, C., Regier, J., and Jordan, M. I. Stochastic cubic regularization for fast nonconvex optimization. In *Advances in neural information processing systems*, pp. 2899–2908, 2018.

[33] Tropp, J. A. An introduction to matrix concentration inequalities. *arXiv preprint arXiv:1501.01571*, 2015.

[34] Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I. Attention is all you need. *Advances in Neural Information Processing Systems*, 30:5998–6008, 2017.

[35] Wang, H., Gürbüzbalaban, M., Zhu, L., Şimşekli, U., and Erdogdu, M. A. Convergence rates of stochastic gradient descent under infinite noise variance. *arXiv preprint arXiv:2102.10346*, 2021.

[36] Wang, Q., Li, B., Xiao, T., Zhu, J., Li, C., Wong, D. F., and Chao, L. S. Learning deep transformer models for machine translation. *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, 2019. doi: 10.18653/v1/p19-1176. URL `http://dx.doi.org/10.18653/v1/P19-1176`.

[37] Ward, R., Wu, X., and Bottou, L. Adagrad stepsizes: Sharp convergence over nonconvex landscapes. In *International Conference on Machine Learning*, pp. 6677–6686. PMLR, 2019.

[38] You, Y., Gitman, I., and Ginsburg, B. Large batch training of convolutional networks. *arXiv preprint arXiv:1708.03888*, 2017.

[39] You, Y., Li, J., Reddi, S., Hseu, J., Kumar, S., Bhojanapalli, S., Song, X., Demmel, J., Keutzer, K., and Hsieh, C.-J. Large batch optimization for deep learning: Training bert in 76 minutes. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=Syx4wnEtvH`.

[40] Zhang, B., Jin, J., Fang, C., and Wang, L. Improved analysis of clipping algorithms for non-convex optimization. *arXiv preprint arXiv:2010.02519*, 2020.

[41] Zhang, J., He, T., Sra, S., and Jadbabaie, A. Why gradient clipping accelerates training: A theoretical justification for adaptivity. In *International Conference on Learning Representations*, 2019.

[42] Zhang, J., Karimireddy, S. P., Veit, A., Kim, S., Reddi, S., Kumar, S., and Sra, S. Why are adaptive methods good for attention models? *Advances in Neural Information Processing Systems*, 33, 2020.