# On Reinforcement Learning and Distribution Matching for Fine-Tuning Language Models with no Catastrophic Forgetting

## Abstract

The availability of large pre-trained models is changing the landscape of Machine Learning research and practice, moving from a "training from scratch" to a "fine-tuning" paradigm. While in some applications the goal is to "nudge" the pre-trained distribution towards preferred outputs, in others it is to steer it towards a different distribution over the sample space. Two main paradigms have emerged to tackle this challenge: Reward Maximization (RM) and, more recently, Distribution Matching (DM). RM applies standard Reinforcement Learning (RL) techniques, such as Policy Gradients, to gradually increase the reward signal. DM prescribes to first make explicit the target distribution that the model is fine-tuned to approximate. Here we explore the theoretical connections between the two paradigms, and show that methods such as KL-control developed for RM can also be construed as belonging to DM. We further observe that while DM differs from RM, it can suffer from similar training difficulties, such as high gradient variance. We leverage connections between the two paradigms to import the concept of *baseline* into DM methods. We empirically validate the benefits of adding a baseline on an array of controllable language generation tasks such as constraining topic, sentiment, and gender distributions in texts sampled from a language model. We observe superior performance in terms of constraint satisfaction, stability and sample efficiency.

## 1 Introduction

Pre-trained language models (Devlin et al., 2019; Radford et al., 2019) are changing the landscape of Machine Learning research and practice. Due to their strong generative capabilities many studies have found it sufficient to "nudge" these models to conform to global preferences defined over the generated sequences instead of training from scratch using annotated data. These preferences could include topic and sentiment (Dathathri et al., 2020), valid musical notes and molecular structures (Jaques et al., 2017a), code compilability (Korbak et al., 2021),

Figure 1: In this study we make connection between two popular paradigms for fine-tuning sequence generation models according to preferences *Reward Maximization* (RM) and *Distribution Matching* (DM).

balancing gender bias (Khalifa et al., 2021), evaluation metrics for Machine Translation and Summarization (Ranzato et al., 2016; Bahdanau et al., 2016), or direct human feedback (Ziegler et al., 2019; Stiennon et al., 2020). This large body of studies is driven by two different paradigms: *Reward Maximization* (RM) and *Distribution Matching* (DM).

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

**Reward Maximization**  RM exploits the intuitive notion that we can nudge pre-trained models towards some preferences by providing global sequence-level rewards when the model generates outputs that satisfy desired features. For instance, if the model is producing toxic content, we can apply Reinforcement Learning (RL) techniques to discourage it from producing similar content again in the future. However, the risk of naively applying RL is that the model can undergo *catastrophic forgetting* of its original distribution. For example, it can degenerate into producing a single nonsensical but at least nontoxic sequence. Although several studies have considered hand-crafting general rewards to ensure desirable features like fluency (Liu et al., 2016a; Tambwekar et al., 2019), coming up with rewards that are not incomplete or imperfect is highly non-trivial (Wu et al., 2016; Vedantam et al., 2015). These challenges have sparked a wide discussion on the overall effectiveness of RM for some tasks such as Neural Machine Translation (Choshen et al., 2020; Kiegeland & Kreutzer, 2021).

**Reward Maximization with KL-Control**  To tackle the aforementioned issues of "catastrophic forgetting", several studies, still under an RM paradigm, have considered incorporating a distributional term inside the reward to be maximized. In particular Jaques et al. (2017b, 2019); Ziegler et al. (2019) and Stiennon et al. (2020) have applied variations of KL-control (Todorov, 2007; Kappen et al., 2012) which adds a penalty term to the reward term so that the resulting policy does not deviate too much from the original one in terms of KL-divergence. The overall objective with the KL-penalty is maximized using an RL algorithm of choice including: PPO (Schulman et al., 2017a) as in Ziegler et al. (2019) or Q-learning (Mnih et al., 2013) as in Jaques et al. (2017b). Adding this *distributional* KL-penalty to the reward raises some important questions: What effect does it have on the shape of the optimal policy? Does this new objective have any interpretation from a distributional perspective?

**Distribution Matching**  A different recent paradigm for fine-tuning language models to satisfy downstream preferences formulates the problem as Distribution Matching (DM). This paradigm consists of two steps: first a target distribution incorporating the desired preferences is defined as an Energy-Based Model (LeCun et al., 2006). Then the forward KL divergence is minimized between this target distribution and an auto-regressive policy using a family of algorithms referred to as Distributional Policy Gradients (DPG) (Parshakova et al., 2019b; Khalifa et al., 2021; Korbak et al., 2021). This approach capitalizes on the flexibility of EBMs in specifying the target distribution. For example, the EBM can be defined so that it conforms to all downstream preferences while its corresponding normalized distribution has a minimal KL divergence from the original, pre-trained language model, therefore tackling the problem of "catastrophic forgetting" (Khalifa et al., 2021). Interestingly, this DM paradigm can also deal with *distributional* preferences, for instance, for de-biasing language models by specifying that the generated sequences should be gender-balanced, i.e. that 50% of generations contain female mentions. Such distributional constraints cannot be defined in the RM paradigm where a reward is calculated for a single sequence.

Contrasting these two paradigms for fine-tuning language models, we can notice the promises and limitations of each.[1] RM approaches are equipped with a large arsenal of RL algorithms and optimization techniques that can be efficient in reward maximization, however they lack the distributional perspective that is necessary for avoiding catastrophic forgetting and imposing distributional preferences over LMs. DM approaches are better suited to tackle those limitations, however, the family of DPG algorithms currently used is not as rich as its RL counterpart. So far, the connections between these two seemingly distinct paradigms have not been thoroughly explored. By establishing such connections we might import ideas from one approach to the other. This is our goal in this paper, detailing the nuanced connections and applying them to a case-study in variance reduction. Overall, our contributions are the following:

- We reveal connections between the RM and DM paradigms through a detailed comparison between the family of DPG algorithms with Policy Gradients (Table 1).

- We introduce an interpretation of KL-control techniques from a distribution matching perspective, placing such techniques at an intermediate place between RM and DM (Theorem 1).

- We show how these connections can enable cross-pollination between the two perspectives by applying *baselines* — a variance reduction technique from RL — to DPG and derive a particular choice of a baseline (Facts 1 and 2). On an array of controllable language generation experiments, we show that adding baselines leads to superior performance on constraint satisfaction (Figure 3), stability on small batch sizes, and sample efficiency (Figure 4).

---

[1]See Appendix B for an extended discussion of related work.

## 2   Background

**Standard Policy Gradients**   One popular method for adapting the behaviour of language models to certain preferences has been that of assigning a "reward" score $R(x)$ for sequences $x$ sampled from an autoregressive language model (policy) $\pi_\theta$. Then, the simplest policy gradient algorithm in reinforcement learning, namely, REINFORCE (Williams, 1992a), aims to find the policy $\pi_\theta(x)$ that maximizes the average reward $\mathbb{E}_{x \sim \pi_\theta} R(x)$, and this leads, via the so-called "log derivative trick", to a gradient ascent algorithm that iteratively samples $x$ from $\pi_\theta$ and update parameters by increments proportional to $R(x) \nabla_\theta \log \pi_\theta(x)$ via the following identity:

$$\nabla_\theta \mathbb{E}_{x \sim \pi_\theta} R(x) = \mathbb{E}_{x \sim \pi_\theta} R(x) \nabla_\theta \log \pi_\theta(x). \tag{1}$$

**KL-control**   (Todorov, 2007; Kappen et al., 2012), was leveraged by Jaques et al. (2017b, 2019) and Ziegler et al. (2019) to include a KL penalty term in the reward function to penalize large deviations from the original pretrained model $a(x)$, weighted by a free hyperparameter $\beta$ to control the trade-off between the two goals. That is, they maximize the expectation $\mathbb{E}_{x \sim \pi_\theta} R_\theta^z(x)$, where:

$$R_\theta^z(x) \doteq r(x) - \beta \log \frac{\pi_\theta(x)}{a(x)}. \tag{2}$$

**Distributional Policy Gradients**   (DPG) (Parshakova et al., 2019b) is a recent approach used to fit an autoregressive policy $\pi_\theta$ to the distribution $p(x) = P(x)/Z$ induced by the EBM $P(x)$, where $Z = \sum_x P(x)$ is the normalization constant (partition function). Given an arbitrary EBM $P(x)$, DPG optimizes the loss function $D_{\mathrm{KL}}(p, \pi_\theta)$ with respect to the parameters $\theta$ of an autoregressive model $\pi_\theta$, a loss which is minimized for $\pi_\theta = p$. The KL-divergence minimization objective leads to a gradient estimate of the form:

$$\nabla_\theta D_{\mathrm{KL}}(p, \pi_\theta) = - \nabla_\theta \mathbb{E}_{x \sim p} \log \pi_\theta(x) \tag{3}$$

$$= - \sum_x p(x) \nabla_\theta \log \pi_\theta(x) = -\frac{1}{Z} \sum_x P(x) \nabla_\theta \log \pi_\theta(x) \tag{4}$$

$$= -\frac{1}{Z} \; \mathbb{E}_{x \sim \pi_\theta} \frac{P(x)}{\pi_\theta(x)} \nabla_\theta \log \pi_\theta(x). \tag{5}$$

## 3   Reward Maximization vs Distribution Matching

In the previous section, we have summarized three approaches that have been suggested for fine-tuning language models. Two of them can be characterized as "Reward Maximization" (RM): Standard Policy Gradients (PG) and KL-control. On the other hand, DPG clearly belongs to the realm of "Distribution Matching" (DM) as it first defines the target distribution and then optimizes a policy to match it. In the rest of this section, we will explore connections between these two seemingly distinct concepts and, in the following section, we will exploit them to improve DM-based methods.

### 3.1   Standard vs. Parametric Rewards

Let us start with distinguishing between a "parametric reward" $R_\theta$ which depends on $\theta$ and a standard reward $R$, which does not. If we wished to maximize the expected parametric reward, $\mathbb{E}_{\pi_\theta} R_\theta(x)$, we would follow its gradient, leading to the identities:

$$\nabla_\theta \mathbb{E}_{x \sim \pi_\theta} R_\theta(x) = \nabla_\theta \sum_x \pi_\theta(x) R_\theta(x) = \sum_x \pi_\theta(x) \nabla_\theta R_\theta(x) + \sum_x R_\theta(x) \nabla_\theta \pi_\theta(x) \tag{6}$$

$$= \sum_x \pi_\theta(x) \nabla_\theta R_\theta(x) + \sum_x \pi_\theta(x) R_\theta(x) \nabla_\theta \log \pi_\theta(x) \tag{7}$$

$$= \underbrace{\mathbb{E}_{x \sim \pi_\theta} \nabla_\theta R_\theta(x)}_{\text{RG-term}} + \underbrace{\mathbb{E}_{x \sim \pi_\theta} R_\theta(x) \nabla_\theta \log \pi_\theta(x)}_{\text{PG-term}}. \tag{8}$$

Equation (8) is the sum of two terms: the first one, the "RG-term" (Reward Gradient term), involves the gradient of the reward. The second one, the "PG-term" (Policy Gradient term), was obtained

121 using the "log derivative trick" and involves the gradient of the policy *stricto sensu*. In standard RL,
122 where the reward does *not* depend on $\theta$, the RG-term disappears and the gradient of expected reward
123 consists solely of the PG-term. However, when $R_\theta$ depends on $\theta$, the gradients are distinct (apart
124 from specific cases where the RG-term evaluates to 0, as we will see below).

## 3.2 KL-control as Distribution Matching

126 Adding a KL-penalty term to the reward (as in the case of KL-control) leads to a parametric reward.
127 However, due to the particular form of its objective, the RG-term actually *vanishes*,[2] leaving only
128 the PG-term $\mathbb{E}_{x \sim \pi_\theta} R_\theta^z(x) \nabla_\theta \log \pi_\theta(x)$ and simplifying the tuning procedure to a standard Policy
129 Gradient. While this algorithm falls under the RM paradigm, here we argue that is it multifaceted, and
130 explore deeper connections with the DM paradigm. More precisely, the maximization of the reward
131 with the KL penalty term is equivalent to a distributional matching with an underlying emergent
132 sequential EBM, a remark that already reveals some similarities with DPG.[3]

133 **Theorem 1.** *Consider the following EBM:*

$$P_z(x) = a(x)e^{r(x)/\beta} \tag{9}$$

134 *and let $p_z$ be the normalized distribution $p_z(x) = \frac{1}{Z} P_z(x)$, with $Z = \sum_x P_z(x)$. Then:*

135     *(i) $\arg\max_{\pi_\theta} \mathbb{E}_{x \sim \pi_\theta} R_\theta^z(x) = \arg\min_{\pi_\theta} D_{\mathrm{KL}}(\pi_\theta, p_z)$;*

136     *(ii) $\arg\max_{\pi \in \mathcal{D}(X)} \mathbb{E}_{x \sim \pi} R_\pi^z(x) = p_z$, where $\mathcal{D}(X)$ is the family of all distributions over $X$,*

137         *and $R_\pi^z(x) \doteq r(x) - \beta \log \frac{\pi(x)}{a(x)}$.*

138 *Proof.* A simple way to prove this is to notice that the expectation of the reward $R_\theta^z$ has a monotoni-
139 cally decreasing relationship with the *reverse* KL divergence between $\pi_\theta$ and $p_z$:

$$D_{\mathrm{KL}}(\pi_\theta, p_z) = \mathbb{E}_{x \sim \pi_\theta} \log \frac{\pi_\theta(x)}{p_z(x)} = \mathbb{E}_{x \sim \pi_\theta} \left[ \log \pi_\theta(x) - \log \frac{1}{Z} a(x)e^{r(x)/\beta} \right]$$

$$= \log Z - \frac{1}{\beta} \mathbb{E}_{x \sim \pi_\theta} \left[ r(x) - \beta \log \frac{\pi_\theta(x)}{a(x)} \right] = \log Z - \frac{1}{\beta} \mathbb{E}_{x \sim \pi_\theta} R_\theta^z(x), \tag{10}$$

140 so that the $\arg\min_{\pi_\theta} D_{\mathrm{KL}}(\pi_\theta, p_z)$ coincides with the $\arg\max_{\pi_\theta} \mathbb{E}_{x \sim \pi_\theta} R_\theta^z(x)$, proving (i). On
141 the other hand, $\arg\min_{\pi \in \mathcal{D}(X)} D_{\mathrm{KL}}(\pi, p_z)$, which also corresponds to $\arg\max_{\pi \in \mathcal{D}(X)} \mathbb{E}_{x \sim \pi} R_\pi^z$
142 because of (i) applied to a family $\pi_{\theta'}$ covering $\mathcal{D}(X)$ in full, is just $p_z$, concluding the proof. $\quad\square$

143 Overall, we can conclude that the addition of the distributional term (KL-penalty) to the reward
144 does indeed provide a DM interpretation, namely in terms of minimizing the reverse KL divergence
145 with an emergent underlying distribution $p_z(x)$. We note that $p_z(x)$ does not correspond to a free
146 and explicit choice of EBM (e.g. one that balances the gender and topic distributions of a language
147 model). Instead equation (9) appears in a restrictive format, which is implicitly defined by the reward
148 $R_\theta^z$, along with a $\beta$ hyperparameter without a clear meaning. By contrast, the DPG algorithms
149 are designed to perform DM on any EBM specification, corresponding to an explicit distributional
150 objective.

## 3.3 Similarities and Differences between DPG and Policy Gradients

152 In the previous subsection, we have connected KL-control, a method designed under a RM paradigm,
153 to DM. Now, we turn to the converse question of whether DPG, a DM method, can be connected to
154 RM. We begin by noting that after defining $R_\theta = \frac{P(x)}{\pi_\theta(x)}$, the DPG gradient $\mathbb{E}_{x \sim \pi_\theta} \frac{P(x)}{\pi_\theta(x)} \nabla_\theta \log \pi_\theta(x)$
155 acquires the format of the PG-term $\mathbb{E}_{\pi_\theta} R_\theta \nabla_\theta \log \pi_\theta(x)$.

156 However, the DM objective of DPG *cannot* be considered as maximizing the average "reward"
157 $R_\theta(x) = \frac{P(x)}{\pi_\theta(x)}$, as this would require adding also the RG-term $\mathbb{E}_{\pi_\theta} \nabla_\theta \frac{P(x)}{\pi_\theta(x)}$ into the gradient, which
158 in this case does not vanish.

---

[2] This is because $\mathbb{E}_{\pi_\theta} \nabla_\theta R_\theta^z(x) = -\beta \mathbb{E}_{\pi_\theta} \nabla_\theta \log \pi_\theta(x) = 0$, via the identity $\mathbb{E}_{\pi_\theta} \nabla_\theta \log \pi_\theta(x) = \sum_x \pi_\theta(x) \nabla_\theta \log \pi_\theta(x) = \sum_x \nabla_\theta \pi_\theta(x) = \nabla_\theta \sum_x \pi_\theta(x) = 0$.

[3] The optimal policy $p_z$ is briefly mentioned in (Ziegler et al., 2019) without reference or derivation. The proof, which reveals a connection to the reverse KL divergence from $\pi_\theta$, is ours.

| | Policy Gradients | DPG |
|---|---|---|
| **Reward** | $R(x)$ | $R_\theta(x) = \frac{P(x)}{\pi_\theta(x)}$ |
| $\nabla_\theta$ | $\mathbb{E}_{x \sim \pi_\theta} R(x) \nabla_\theta \log \pi_\theta(x)$ | $\mathbb{E}_{x \sim \pi_\theta} \frac{P(x)}{\pi_\theta(x)} \nabla_\theta \log \pi_\theta(x)$ |
| **Baseline** | $\mathbb{E}_{x \sim \pi_\theta} R(x)$ | $Z$ |
| $\nabla_\theta$ **with Baseline** | $\mathbb{E}_{x \sim \pi_\theta} \left[ R(x) - \mathbb{E}_{x \sim \pi_\theta} R(x) \right] \nabla_\theta \log \pi_\theta(x)$ | $\mathbb{E}_{x \sim \pi_\theta} \left[ \frac{P(x)}{\pi_\theta(x)} - Z \right] \nabla_\theta \log \pi_\theta(x)$ |

Table 1: A comparison between Policy Gradients (Sutton et al., 1999) and Distributional Policy Gradients (Parshakova et al., 2019b) forms of Reward, Baseline, and Gradient of the loss function (the PG-term) before ($\nabla_\theta$) and after ($\nabla_\theta$ with Baseline) including a baseline for variance reduction .

Nonetheless, the analogy behind this gradient term is more fruitful than it first appears. As a matter of fact, DPG gradient estimates suffer from the same high-variance problems as with standard PG. While the objective of DPG (distribution matching) is different from that of Policy Gradients (reward maximization), DPG also needs to estimate the PG-term $\mathbb{E}_{\pi_\theta} R(x) \nabla_\theta \log \pi_\theta(x)$ at a *given* value of $\theta$, using a batch of samples $x$. For such a *fixed $\theta$*, we can define provisionally set $R(x) \doteq R_\theta$ and the problem of gradient estimation *for this fixed $\theta$* is identical to the estimation $\mathbb{E}_{x \sim \pi_\theta} R(x) \nabla_\theta \log \pi_\theta(x)$ based on a set of samples $x$ in standard RL. Therefore, the techniques that have been developed to reduce the variance of the gradients estimates in RL can be ported to DPG insofar as we are computing the gradient estimates *at a given $\theta$*.In Section 4, we show how one can import one such variance reduction technique to the DPG: baselines.

## 4 A Case Study on Variance Reduction

Baselines are a standard variance reduction technique in the context of Policy Gradients (Sutton & Barto, 2018). The idea is to subtract from the reward $R(x)$ a value $B$ that does not introduce bias to the gradients but may change variance. After the introduction of baseline, equation (1) then takes the following form:

$$\nabla_\theta \mathbb{E}_{\pi_\theta} R(x) = \mathbb{E}_{\pi_\theta} [R(x) - B] \nabla_\theta \log \pi_\theta(x). \tag{11}$$

In standard RL, the simplest form of baseline $B$ is just the average of the rewards for the policy:[4]

$$B^{\text{RL}} = \mathbb{E}_{x \sim \pi_\theta} R(x). \tag{12}$$

Figure 2: Values of reward, advantage and the baseline for first 1000 epochs of a pointwise constraint experiment.

Following the same methodology of taking the baseline as the expectation of the reward term, we can obtain a remarkably simple form of a baseline for DPG: [5]

$$B = \mathbb{E}_{x \sim \pi_\theta} \frac{P(x)}{\pi_\theta(x)} = \sum_x \pi_\theta(x) \frac{P(x)}{\pi_\theta(x)} = \sum_x P(x) = Z. \tag{13}$$

**Fact 1.** *Subtracting $B$ from $R_\theta(x)$ does not introduce bias into DPG gradient estimates.*

*Proof.* Let us rewrite the DPG gradient in (5) with the added baseline $B = Z$:

$$\mathbb{E}_{x \sim \pi_\theta} \left[ R_\theta(x) - Z \right] \nabla_\theta \log \pi_\theta(x) = \mathbb{E}_{x \sim \pi_\theta} R_\theta(x) \nabla_\theta \log \pi_\theta(x) - Z \mathbb{E}_{x \sim \pi_\theta} \nabla_\theta \log \pi_\theta(x)$$
$$= \mathbb{E}_{x \sim \pi_\theta} R_\theta(x) \nabla_\theta \log \pi_\theta(x) - Z \left[ \sum_x \nabla_\theta \pi_\theta(x) \right] \tag{14}$$

Here, the second term does not introduce bias because $Z \left[ \sum_x \nabla_\theta \pi_\theta(x) \right] = 0$, leaving us with the exact same form of gradient as in the original DPG algorithm. $\qquad\square$

---

[4]While this choice of the baseline is not optimal (see Appendix C.1 for a proof), it is widely used in practice.

[5]In the scope of this paper, our focus is on importing to DPG simple constant baselines. The advantage is that this is a technique that is not impacted by the fact that $R_\theta$ depends on $\theta$: it can be applied "$\theta$-locally" to provide a more accurate estimate of $\mathbb{E}_{x \sim \pi_\theta} R_\theta(x) \nabla_\theta \log \pi_\theta(x)$ for a *fixed $\theta$*, irrespective of the values of $R_{\theta'}$ elsewhere, while variance reduction techniques that involve several $\theta' s$ simultaneously raise additional challenges for parametric rewards.

Note that since $B^{\mathrm{RL}}$ depends on $\theta$, it has to be be re-estimated after each gradient update. On the other hand, $B$ does *not* depend on $\theta$, which is an advantage because $B$ could be now estimated by averaging over samples from *all* the different $\theta$'s without introducing bias, leading to a more accurate estimation. See Table 1 for a comparison of these two forms of baselines.

The off-policy DPG version introduced in (Parshakova et al., 2019b) and its KL-adaptive variant (Khalifa et al., 2021) sample a proposal distribution $q$ instead of the policy $\pi_\theta$. Then, the baseline takes the form

$$B^{\mathrm{off}}(x) = Z \frac{\pi_\theta(x)}{q(x)}, \tag{15}$$

where the $\frac{\pi_\theta(x)}{q(x)}$ term is an importance weight correcting for the bias introduced by sampling from $q$. Similarly to the DPG case, we can prove the following (see Appendix C):

**Fact 2.** *Subtracting $B^{off}(x)$ from $R_\theta(x)$ does not introduce bias into off-policy DPG gradient estimates.*

In practice, as shown on Figure 2, adding a baseline to KL-adaptive DPG (Algorithm 1) centers the advantage (defined as $A \doteq \frac{P(x)}{q(x)} - Z\frac{\pi_\theta(x)}{q(x)}$) around 0 leading to better performance on: convergence (section 4.3), stability on small batch sizes (section 4.4), and variance reduction (section 4.5).

---

**Algorithm 1** KL-Adaptive DPG with baseline

**Require:** $P$, initial generative model $a$
1: $\pi_\theta \leftarrow a, q \leftarrow a$
2: **for** each iteration **do**
3:      **for** each episode **do**
4:          sample $x$ from $q(\cdot)$
5:          $\theta \leftarrow \theta + \alpha^{(\theta)} \left[ \frac{P(x)}{q(x)} - Z\frac{\pi_\theta(x)}{q(x)} \right] \nabla_\theta \log \pi_\theta(x)$
6:          **if** $D_{\mathrm{KL}}(p||\pi_\theta) < D_{\mathrm{KL}}(p||q)$ **then**
7:              $q \leftarrow \pi_\theta$
**Ensure:** $\pi_\theta$

---

## 4.1 Generation with Distributional Control

We investigate the benefits of adding a baseline to the DPG algorithm, on the Generation with Distributional Control (GDC) (Khalifa et al., 2021) framework. GDC makes use of DPG to control the properties of pre-trained language models to satisfy certain constraints. In our experiments, follow target distribution form of Parshakova et al. (2019a) and Khalifa et al. (2021), in which the EBM $P(x)$ is defined so that its normalized variant $p(x)$ matches a set of desired moments constraints on given features $\phi_i(x)$, while having a minimal KL divergence $D_{\mathrm{KL}}(p, a)$ from an original pretrained language model $a$, to avoid catastrophic forgetting.

These constraints are expressed as conditions $\bar{\mu}_i = \mathbb{E}_{x \sim p}\phi_i(x)$, for $i \in \{1, \ldots, n\}$, by which the moments (expectations) under the distribution $p$ of each feature $\phi_i(x)$ are required to take certain desired values $\bar{\mu}_i$. For instance, let $\phi_1(x) = 1$ iff the topic of $x$ is science and $\phi_2(x) = 1$ iff $x$ mentions a female person, then imposing moments $\bar{\mu}_1 = 1$ and $\bar{\mu}_2 = 0.5$ constrains the language model $p$ to only generate sequences about science, half of which mention females. $P(x)$ is uniquely determined by the following form:[6]

$$P(x) = a(x)e^{\sum_{i=1}^n \lambda_i \phi_i(x)}, \tag{16}$$

where $\lambda_i$ terms control the moments $\mu_i$ of the associated features, which can be estimated through self-normalized importance sampling (Owen, 2013); and then, to make the moments match the desired values, the $\lambda_i$ terms can be optimized through SGD (Parshakova et al., 2019a).

## 4.2 Experimental setup

We demonstrate the benefits of adding a baseline to the family of Distributional Policy Gradients algorithms on an array of controlled language generation tasks for English. For this, we modify the GDC framework Khalifa et al. (2021) namely its KL-DPG algorithm to include a baseline as shown in Algorithm 1. We refer to this method in all the following experiments as **GDC++**. In addition to comparing **GDC++** with **GDC**, for tasks for which the comparison is meaningful (i.e. for "pointwise constraints", see below), we compare with two reward maximization baselines: **Reinforce** (Williams, 1992b) and **Ziegler** (Ziegler et al., 2019). Reinforce tries to maximize the expected reward $\mathbb{E}_{x \sim \pi_\theta}R(x)$, where $R(x) = 1$ iff the pointwise constraints are met. Ziegler instantiates the KL-control approach: its objective includes a KL penalty term for departures from $a$.

---

[6] For a more precise formulation of this EBM, see (Khalifa et al., 2021).

**Tasks**    We evaluate GDC, GDC++ and the two baselines on **10 tasks**, which we construct through sets of moment constraints $\{\bar{\mu}_i\}$ for binary features $\{\phi_i\}$. These include 6 sets of purely pointwise constraints (for which $\bar{\mu}_i = 1$) and 4 sets including distributional constraints ($0 < \bar{\mu}_i < 1$). We consider the following constraint types:

   (a) Single-word constraints, where $\phi(x) = 1$ iff the a given word appears in the sequence $x$. We experiment both with frequent words (task 1: "amazing", original frequency: $10^{-4}$) and (task 2: "WikiLeaks", original frequency: $10^{-5}$) rare words,

   (b) Wordlist constraints, where $\phi(x) = 1$ iff $x$ contains at least one word from a given list. We consider lists of word associated with politics (task 3) and science (task 4) published by Dathathri et al. (2020),

   (c) Sentiment classifier constraints, where $\phi(x) = 1$ if $x$ is classified as positive (task 5), or negative (task 6) by a pre-trained classifier published by Dathathri et al. (2020).

   (d) A single distributional constraint where $\phi(x) = 1$ iff $x$ contains a female figure mention, and $\bar{\mu} = 0.5$ (task 8),

   (e) A set of four distributional constraints: $\phi_i(x) = 1$ iff $x$ contains at least one of the words in the "science", "art", "sports" and "business" wordlists (compiled by Dathathri et al. (2020)), respectively. For each $i$, $\bar{\mu}_i = 0.25$ (task 8),

   (f) Hybrid constraints where $\phi_1(x) = 1$ iff $x$ contains more female than male pronouns, $\bar{\mu}_1 = 0.5$ and $\phi_2(x) = 1$ iff $x$ contains at least one of the words from the "sports" wordlist (task 9) or "politics" wordlist, $\bar{\mu}_2(x) = 1$ (task 10).

Following (Khalifa et al., 2021), for hybrid and distributional constraints (tasks 8-10) we compare only GDC and GDC++ because the RM objective of Ziegler and Reinforce is not equipped to handle distributional constraints.

**Metrics**    We report the following metrics evaluated over batches of samples from $\pi_\theta$ at each validation step:

   1. $\mathbb{E}_{x \sim \pi_\theta} \phi_i(x)$, measuring the ability to reach the target moment of the $i$-th feature.

   2. $D_{\mathrm{KL}}(p, \pi_\theta)$, the forward KL divergence from the optimal target distribution $p$,[7]

   3. $D_{\mathrm{KL}}(\pi_\theta, a)$, the reverse KL divergence from the original pretrained language model $a$.

   4. Distinct-n score, a measure of text diversity in terms of the frequency of repetitions within a single sample $x$, proposed by (Li et al., 2016a).

   5. Self-BLEU-n, a measure of text diversity on a distributional level *across* samples proposed by (Zhu et al., 2018), ensuring that policies don't converge into limited number of sequences that satisfy the imposed constraints Caccia et al. (2020).

**Training details**    For tasks 1-6, we use a pre-trained GPT-2 small with 117M parameters (Radford et al., 2019) as the original language model $a$. For tasks 7-10, $a$ is the same pre-trained model additionally fine-tuned on the WikiBio (Lebret et al., 2016) dataset. See Appendix E for more details.

### 4.3    Results

We present the evolution of our metrics through training epochs in Figure 3 (aggregated over tasks 1-6) and Figure 6 in the Appendix (aggregated over tasks 7-10). Results for each task are presented separately on Figures 7-10 in the Appendix.

Consistent with prior work (Khalifa et al., 2021), we observe that Reinforce is able to quickly achieve high levels of constraint satisfaction, but at the cost of large deviations from $a$, which translates into significantly decreased diversity of generated samples (in terms of Self-BLEU-5 and Distinct-1). The KL penalty term in Ziegler imposes an upper bound on deviation from $a$ but the deviation is still significant enough to result in a drop in diversity. Moreover, we have observed Ziegler's objective to result in very unstable training.

GDC and GDC++ are the only fine-tuning methods that address constraint satisfaction based on a clear formal objective, i.e. reducing the divergence from $p$. The approach translates into significantly smaller deviations from $a$ and maintaining diversity within and across samples. The addition of a baseline indeed reduces the variance. We analyze that extensively in Appendix 4.5 while here focusing on the downstream effects of variance reduction. One is that $\pi_\theta$ is now able to compound

---

[7]See Appendix D for a detailed description of how $D_{\mathrm{KL}}(p, \pi_\theta)$ is computed.

Figure 3: Evaluation metrics: $D_{\mathrm{KL}}(p, \pi_\theta)$ ($\downarrow$ better), $\mathbb{E}_{\pi_\theta}\phi(x)$ ($\uparrow$ better), $D_{\mathrm{KL}}(\pi_\theta, a)$ ($\downarrow$ better), Self-BLEU-5 ($\downarrow$ better), and Distinct-1 ($\uparrow$ better) aggregated over 6 pointwise constraints experiments (tasks 1-6) for policies obtained from GDC++, GDC, Ziegler and Reinforce. See Figure 6 for aggregated distributional constraints experiments. In the Appendix Figures 7-10 and Table 4 contain individual view and final results of each run.

(a) Task 1: a pointwise constraint      (b) Task 8: a set of distributional constraints; $\bar{\mu}_i = 0.25$

Figure 4: $\mathbb{E}_{\pi_\theta}\phi(x)$ or $\hat{\mu}$ per constraint ($\uparrow$ better) and $D_{\mathrm{KL}}(p, \pi_\theta)$ ($\downarrow$ better) as a function of the number of samples reported for task 1 (a) and task 8 (b). We report the number of samples (i.e. the number of epochs times the batch size) for a fair comparison of convergence speed. *GDC++ is consistently superior across all batch sizes in terms of convergence and constraint satisfaction.* The effect is more conspicuous with small batch sizes. Batch sizes 512 and 2014 are greyed out for clarity.

staying closer to $p$ and $a$ *at the same time*, while achieving slightly better constraint satisfaction. We have also observed that baseline stabilizes training, leading to smoother curves.[8]

## 4.4 The effect of baseline across batch sizes

We expect that reducing variance in the gradient estimates can allow to train the models with lower batch sizes, performing gradient updates on estimates based on smaller batch sizes can increase the sample efficiency. To test this hypothesis, we rerun tasks 1 (a pointwise constraint on the word "amazing") and 8 (a set of distributional constraints on topics) with four batch sizes (256, 512, 1024, 2048). We present the results on Figures 4a and 4b. The benefits of adding a baseline — higher constraint satisfaction, lower divergence from $p$, more stable training — are especially evident with lower batch sizes. For instance, with batch size 256, GDC++ obtains a significantly higher constraint satisfaction rate and lower divergence from $p$.

Furthermore, stable training with smaller batch sizes translates into better sample efficiency. For instance, in task 1 (Figure 4a), GDC++ with batch size 256 needs 1M samples to achieve $\mathbb{E}_{x\sim\pi_\theta}\phi(x) = 0.5$ while GDC++ with batch size 2048 needs 4M. In contrast, GDC with batch size 256 does not achieve $\mathbb{E}_{x\sim\pi_\theta}\phi(x) = 0.5$ at all, confirming the importance of adding the baseline.

## 4.5 Empirical Evaluation of Variance Reduction

Next, we evaluate empirically the effect of the baseline for variance reduction. We select two tasks: task 1 (a pointwise constraint) and task 7 (distributional constraints) described in Section 4.2, each with 3 different seeds, while monitoring the following variance measures:

**Gradient Variance** The gradient estimate is defined as: $G_\theta(x) \doteq A(x)\nabla_\theta \log \pi_\theta(x)$, where $G_\theta(x) \in \mathbb{R}^{|\theta|}$ is an unbiased estimate of the gradient of the forward KL loss $\nabla_\theta D_{\mathrm{KL}}(p, \pi_\theta)$ with

---

[8]The interested reader can compare the large fluctuations of the Ziegler objective to more stable training curves of GDC , and even more of GDC++ , in the disaggregated curves in Figures 7-10 of the Appendix.

respect to the parameters $\theta$. We then have, with $\mu(G_\theta) \doteq \mathbb{E}_{x \sim q} G_\theta(x)$:

$$\text{Var}(G_\theta) \doteq \mathbb{E}_{x \sim q} \|G_\theta(x) - \mu(G_\theta)\|_2^2 = \mathbb{E}_{x \sim q} \|G_\theta(x)\|_2^2 - \|\mu(G_\theta)\|_2^2. \tag{17}$$

**Variance of the advantage** This is defined by:

$$\text{Var}(A) \doteq \mathbb{E}_{x \sim q} \left\| A(x) - \mu^A \right\|_2^2 \tag{18}$$

where, $\mu^A \equiv \mathbb{E}_{x \sim q} A(x)$ is the mean of the advantage, which we showed above to be null after the addition of the baseline.

**Expected absolute value of the advantage** This metric is defined as:

$$\mu^{|A|} \doteq \mathbb{E}_{x \sim q} |A(x)|. \tag{19}$$

It directly provides a standard measure of distributional discrepancy between $p$ and $\pi_\theta$, in terms of TVD (Total Variation Distance). Indeed we have:

$$\mathbb{E}_{x \sim q} \left| \frac{p(x)}{q(x)} - \frac{\pi_\theta(x)}{q(x)} \right| = 2 \, \text{TVD}(p, \pi_\theta). \tag{20}$$

**Results** Figure 5 shows that GDC++ obtains lower variance in the gradient estimates $\text{Var}(G_\theta)$ and the variance of the advantage $\text{Var}(A)$ in both pointwise and distributional experiments compared to its non-baseline counterpart GDC. We further observe a decreasing trend in the mean absolute value of the advantage $\mu^{|A|}$ which is correlated with a decreasing trend in the TVD distance between the trained

Figure 5: Comparison between GDC and GDC++ using a set of Variance diagnosis metrics on two experiments for pointwise and distributional constraints.

policy $\pi_\theta$ and the optimal distribution $p$. Overall, these results shows that adding a baseline to DPG reduces the variance during training and yields better convergence towards the optimal distribution $p$.

# 5 Conclusion

In this paper, we analyzed the nuanced relation between RM and DM approaches to fine-tuning language models: we demonstrated that KL-control can be seen as a form of DM and showed that while DPG and PG have different goals, some similarities (similar forms of gradient estimates despite different objectives) can be exploited. We used these insights to inform an extension of DPG, consisting in adding a baseline to reduce the variance of gradient estimates.

The connections we established suggest that despite fundamental differences between DPG and RL, at least some of the theoretical results and algorithmic techniques from RL can be adapted to a DM framework without losing their formal guarantees. In this paper, we have focused on variance reduction using baselines, but the space of possible enhancements is vast. Promising candidates include further reducing the variance using a learned value function (Konda & Tsitsiklis, 2000) and preventing detrimentally large policy updates by maintaining a trust region in the policy space – akin to techniques such as trust-region policy optimisation (Schulman et al., 2015) and proximal policy optimisation (Schulman et al., 2017b). Another future direction could consist in analyzing the relation between explicit EBMs in DPG and implicit EBMs arising in KL-control and characterizing the space of EBMs that could be reached through KL-control.

## References

Daniel Andor, Chris Alberti, David Weiss, Aliaksei Severyn, Alessandro Presta, Kuzman Ganchev, Slav Petrov, and Michael Collins. Globally Normalized Transition-Based Neural Networks. 2016. doi: 10.18653/v1/P16-1231.

Dzmitry Bahdanau, Philemon Brakel, Kelvin Xu, Anirudh Goyal, Ryan Lowe, Joelle Pineau, Aaron Courville, and Yoshua Bengio. An Actor-Critic Algorithm for Sequence Prediction. (2015):1–17, 2016. URL `http://arxiv.org/abs/1607.07086`.

Dzmitry Bahdanau, Philemon Brakel, Kelvin Xu, Anirudh Goyal, Ryan Lowe, Joelle Pineau, Aaron C. Courville, and Yoshua Bengio. An actor-critic algorithm for sequence prediction. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. URL `https://openreview.net/forum?id=SJDaqqveg`.

A. Bakhtin, Y. Deng, S. Gross, Myle Ott, Marc'Aurelio Ranzato, and Arthur Szlam. Energy-based models for text. *ArXiv*, abs/2004.10188, 2020.

David Belanger and Andrew McCallum. Structured prediction energy networks. In *Proceedings of the 33rd International Conference on International Conference on Machine Learning - Volume 48*, ICML'16, pp. 983–992. JMLR.org, 2016. URL `http://dl.acm.org/citation.cfm?id=3045390.3045495`.

Emily M. Bender, Timnit Gebru, Angelina McMillan-Major, and Shmargaret Shmitchell. On the dangers of stochastic parrots: Can language models be too big? In *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '21, pp. 610–623, New York, NY, USA, 2021. Association for Computing Machinery. ISBN 9781450383097. doi: 10.1145/3442188.3445922. URL `https://doi.org/10.1145/3442188.3445922`.

Su Lin Blodgett, Solon Barocas, Hal Daumé III, and Hanna Wallach. Language (technology) is power: A critical survey of "bias" in NLP. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 5454–5476, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.485. URL `https://www.aclweb.org/anthology/2020.acl-main.485`.

Christopher L. Buckley, Chang Sub Kim, Simon McGregor, and Anil K. Seth. The free energy principle for action and perception: A mathematical review. *Journal of Mathematical Psychology*, 81:55–79, 2017. ISSN 0022-2496. doi: https://doi.org/10.1016/j.jmp.2017.09.004. URL `https://www.sciencedirect.com/science/article/pii/S0022249617300962`.

Massimo Caccia, Lucas Caccia, William Fedus, Hugo Larochelle, Joelle Pineau, and Laurent Charlin. Language gans falling short. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=BJgza6VtPB`.

Leshem Choshen, Lior Fox, Zohar Aizenbud, and Omri Abend. On the weaknesses of reinforcement learning for neural machine translation. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL `https://openreview.net/forum?id=H1eCw3EKvH`.

Kevin Clark, Minh-Thang Luong, Quoc V. Le, and Christopher D. Manning. Pre-training transformers as energy-based cloze models. In Bonnie Webber, Trevor Cohn, Yulan He, and Yang Liu (eds.), *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing, EMNLP 2020, Online, November 16-20, 2020*, pp. 285–294. Association for Computational Linguistics, 2020. doi: 10.18653/v1/2020.emnlp-main.20. URL `https://doi.org/10.18653/v1/2020.emnlp-main.20`.

Sumanth Dathathri, Andrea Madotto, Janice Lan, Jane Hung, Eric Frank, Piero Molino, Jason Yosinski, and Rosanne Liu. Plug and play language models: A simple approach to controlled text generation. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL `https://openreview.net/forum?id=H1edEyBKDS`.

Peter Dayan. Reinforcement comparison. In *Proceedings of the 1990 Connectionist Models Summer School*, pp. 45–51. Morgan Kaufmann, San Mateo, CA, 1990.

Yuntian Deng, Anton Bakhtin, Myle Ott, Arthur Szlam, and Marc'Aurelio Ranzato. Residual energy-based models for text generation. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL `https://openreview.net/forum?id=B1l4SgHKDH`.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL `https://www.aclweb.org/anthology/N19-1423`.

Karl J Friston, Jean Daunizeau, James Kilner, and Stefan J Kiebel. Action and behavior: a free-energy formulation. *Biological cybernetics*, 102(3):227–260, 2010.

Evan Greensmith, Peter L. Bartlett, and Jonathan Baxter. Variance reduction techniques for gradient estimates in reinforcement learning. *J. Mach. Learn. Res.*, 5:1471–1530, December 2004. ISSN 1532-4435.

Michael Gutmann and Aapo Hyvärinen. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models. In Yee Whye Teh and Mike Titterington (eds.), *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, volume 9 of *Proceedings of Machine Learning Research*, pp. 297–304, Chia Laguna Resort, Sardinia, Italy, 13–15 May 2010. PMLR. URL `http://proceedings.mlr.press/v9/gutmann10a.html`.

Tuomas Haarnoja, Haoran Tang, Pieter Abbeel, and Sergey Levine. Reinforcement learning with deep energy-based policies. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 1352–1361. PMLR, 06–11 Aug 2017. URL `https://proceedings.mlr.press/v70/haarnoja17a.html`.

Danijar Hafner, Pedro A. Ortega, Jimmy Ba, Thomas Parr, Karl Friston, and Nicolas Heess. Action and perception as divergence minimization, 2020.

Tianxing He, Bryan McCann, Caiming Xiong, and Ehsan Hosseini-Asl. Joint energy-based model training for better calibrated natural language understanding models. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pp. 1754–1761, Online, April 2021. Association for Computational Linguistics. URL `https://www.aclweb.org/anthology/2021.eacl-main.151`.

Geoffrey E. Hinton. Training products of experts by minimizing contrastive divergence. *Neural Comput.*, 14(8):1771–1800, 2002. doi: 10.1162/089976602760128018. URL `https://doi.org/10.1162/089976602760128018`.

Natasha Jaques, Shixiang Gu, Dzmitry Bahdanau, José Miguel Hernández-Lobato, Richard E. Turner, and Douglas Eck. Sequence tutor: Conservative fine-tuning of sequence generation models with kl-control. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, volume 70 of *Proceedings of Machine Learning Research*, pp. 1645–1654. PMLR, 2017a. URL `http://proceedings.mlr.press/v70/jaques17a.html`.

Natasha Jaques, Shixiang Gu, Dzmitry Bahdanau, Jose Miguel Hernandez Lobato, Richard E. Turner, and Doug Eck. Tuning recurrent neural networks with reinforcement learning. 2017b. URL `https://openreview.net/pdf?id=Syyv2e-Kx`.

Natasha Jaques, Asma Ghandeharioun, Judy Hanwen Shen, Craig Ferguson, Àgata Lapedriza, Noah Jones, Shixiang Gu, and Rosalind W. Picard. Way off-policy batch deep reinforcement learning of implicit human preferences in dialog. *CoRR*, abs/1907.00456, 2019. URL `http://arxiv.org/abs/1907.00456`.

Hilbert J Kappen, Vicenç Gómez, and Manfred Opper. Optimal control as a graphical model inference problem. *Machine learning*, 87(2):159–182, 2012.

Muhammad Khalifa, Hady Elsahar, and Marc Dymetman. A distributional approach to controlled text generation. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=jWkw45-9AbL`.

Samuel Kiegeland and Julia Kreutzer. Revisiting the weaknesses of reinforcement learning for neural machine translation. In Kristina Toutanova, Anna Rumshisky, Luke Zettlemoyer, Dilek Hakkani-Tür, Iz Beltagy, Steven Bethard, Ryan Cotterell, Tanmoy Chakraborty, and Yichao Zhou (eds.), *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2021, Online, June 6-11, 2021*, pp. 1673–1681. Association for Computational Linguistics, 2021. doi: 10.18653/v1/2021. naacl-main.133. URL `https://doi.org/10.18653/v1/2021.naacl-main.133`.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

A.S. Klyubin, D. Polani, and C.L. Nehaniv. Empowerment: a universal agent-centric measure of control. In *2005 IEEE Congress on Evolutionary Computation*, volume 1, pp. 128–135 Vol.1, 2005. doi: 10.1109/CEC.2005.1554676.

Vijay Konda and John Tsitsiklis. Actor-critic algorithms. In S. Solla, T. Leen, and K. Müller (eds.), *Advances in Neural Information Processing Systems*, volume 12. MIT Press, 2000. URL `https://proceedings.neurips.cc/paper/1999/file/6449f44a102fde848669bdd9eb6b76fa-Paper.pdf`.

Tomasz Korbak, Hady Elsahar, Marc Dymetman, and Germán Kruszewski. Energy-based models for code generation under compilability constraints. *CoRR*, abs/2106.04985, 2021. URL `https://arxiv.org/abs/2106.04985`.

Rémi Lebret, David Grangier, and Michael Auli. Neural text generation from structured data with application to the biography domain. In Jian Su, Xavier Carreras, and Kevin Duh (eds.), *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing, EMNLP 2016, Austin, Texas, USA, November 1-4, 2016*, pp. 1203–1213. The Association for Computational Linguistics, 2016. doi: 10.18653/v1/d16-1128. URL `https://doi.org/10.18653/v1/d16-1128`.

Yann LeCun, Sumit Chopra, Raia Hadsell, Marc'Aurelio Ranzato, and Fu Jie Huang. A Tutorial on Energy-Based Learning. In *Predicting Structured Data*. MIT Press, 2006.

Sergey Levine. Reinforcement learning and control as probabilistic inference: Tutorial and review, 2018.

Jiwei Li, Michel Galley, Chris Brockett, Jianfeng Gao, and Bill Dolan. A diversity-promoting objective function for neural conversation models. In *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 110–119, San Diego, California, June 2016a. Association for Computational Linguistics. doi: 10.18653/v1/N16-1014. URL `https://www.aclweb.org/anthology/N16-1014`.

Jiwei Li, Will Monroe, Alan Ritter, Dan Jurafsky, Michel Galley, and Jianfeng Gao. Deep reinforcement learning for dialogue generation. In Jian Su, Xavier Carreras, and Kevin Duh (eds.), *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing, EMNLP 2016, Austin, Texas, USA, November 1-4, 2016*, pp. 1192–1202. The Association for Computational Linguistics, 2016b. doi: 10.18653/v1/d16-1127. URL `https://doi.org/10.18653/v1/d16-1127`.

Paul Pu Liang, Chiyu Wu, Louis-Philippe Morency, and Ruslan Salakhutdinov. Towards understanding and mitigating social biases in language models, 2021.

Chia-Wei Liu, Ryan Lowe, Iulian Serban, Michael Noseworthy, Laurent Charlin, and Joelle Pineau. How NOT to evaluate your dialogue system: An empirical study of unsupervised evaluation metrics for dialogue response generation. In Jian Su, Xavier Carreras, and Kevin Duh (eds.), *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing, EMNLP 2016, Austin, Texas, USA, November 1-4, 2016*, pp. 2122–2132. The Association for Computational Linguistics, 2016a. doi: 10.18653/v1/d16-1230. URL `https://doi.org/10.18653/v1/d16-1230`.

Siqi Liu, Zhenhai Zhu, Ning Ye, Sergio Guadarrama, and Kevin Murphy. Optimization of image description metrics using policy gradient methods. *CoRR*, abs/1612.00370, 2016b. URL `http://arxiv.org/abs/1612.00370`.

Beren Millidge, Alexander Tschantz, Anil Seth, and Christopher Buckley. Understanding the origin of information-seeking exploration in probabilistic objectives for control, 2021.

Andriy Mnih and Karol Gregor. Neural variational inference and learning in belief networks. In Eric P. Xing and Tony Jebara (eds.), *Proceedings of the 31st International Conference on Machine Learning*, volume 32 of *Proceedings of Machine Learning Research*, pp. 1791–1799, Bejing, China, 22–24 Jun 2014. PMLR. URL `http://proceedings.mlr.press/v32/mnih14.html`.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin A. Riedmiller. Playing atari with deep reinforcement learning. *CoRR*, abs/1312.5602, 2013. URL `http://arxiv.org/abs/1312.5602`.

Subhajit Naskar, Pedram Rooshenas, Simeng Sun, Mohit Iyyer, and A. McCallum. Energy-based reranking: Improving neural machine translation using energy-based models. *ArXiv*, abs/2009.13267, 2020.

Art B. Owen. Importance Sampling. In *Monte Carlo theory, methods and examples*, chapter 9. 2013. URL `https://statweb.stanford.edu/~owen/mc/Ch-var-is.pdf`.

Tetiana Parshakova, Jean-Marc Andreoli, and Marc Dymetman. Global Autoregressive Models for Data-Efficient Sequence Learning. In *Proceedings of the 23rd Conference on Computational Natural Language Learning (CoNLL)*, pp. 900–909, Hong Kong, China, November 2019a. Association for Computational Linguistics. doi: 10.18653/v1/K19-1084. URL `https://www.aclweb.org/anthology/K19-1084`.

Tetiana Parshakova, Jean-Marc Andreoli, and Marc Dymetman. Distributional Reinforcement Learning For Energy-Based Sequential Models. *CoRR*, 2019b. URL `https://arxiv.org/abs/1912.08517`.

Ramakanth Pasunuru and Mohit Bansal. Reinforced video captioning with entailment rewards. In Martha Palmer, Rebecca Hwa, and Sebastian Riedel (eds.), *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing, EMNLP 2017, Copenhagen, Denmark, September 9-11, 2017*, pp. 979–985. Association for Computational Linguistics, 2017. doi: 10.18653/v1/d17-1103. URL `https://doi.org/10.18653/v1/d17-1103`.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019. URL `http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf`.

Romain Paulus, Caiming Xiong, and Richard Socher. A deep reinforced model for abstractive summarization. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL `https://openreview.net/forum?id=HkAClQgA-`.

Jan Peters and Stefan Schaal. Reinforcement learning of motor skills with policy gradients. *Neural Networks*, 21(4):682–697, 2008. ISSN 0893-6080. doi: https://doi.org/10.1016/j.neunet.2008.02.003. URL `https://www.sciencedirect.com/science/article/pii/S0893608008000701`. Robotics and Neuroscience.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. *OpenAI Blog*, 1(8):9, 2019.

Marc'Aurelio Ranzato, Y-Lan Boureau, Sumit Chopra, and Yann LeCun. A unified energy-based framework for unsupervised learning. In Marina Meila and Xiaotong Shen (eds.), *Proceedings of the Eleventh International Conference on Artificial Intelligence and Statistics, AISTATS 2007, San Juan, Puerto Rico, March 21-24, 2007*, volume 2 of *JMLR Proceedings*, pp. 371–379. JMLR.org, 2007. URL `http://proceedings.mlr.press/v2/ranzato07a.html`.

Marc'Aurelio Ranzato, Sumit Chopra, Michael Auli, and Wojciech Zaremba. Sequence level training with recurrent neural networks. In Yoshua Bengio and Yann LeCun (eds.), *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*, 2016. URL `http://arxiv.org/abs/1511.06732`.

John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In *International conference on machine learning*, pp. 1889–1897, 2015.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *CoRR*, abs/1707.06347, 2017a. URL `http://arxiv.org/abs/1707.06347`.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint: 1707.06347*, 2017b.

Emily Sheng, Kai-Wei Chang, Premkumar Natarajan, and Nanyun Peng. The woman worked as a babysitter: On biases in language generation. In Kentaro Inui, Jing Jiang, Vincent Ng, and Xiaojun Wan (eds.), *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing, EMNLP-IJCNLP 2019, Hong Kong, China, November 3-7, 2019*, pp. 3405–3410. Association for Computational Linguistics, 2019. doi: 10.18653/v1/D19-1339. URL `https://doi.org/10.18653/v1/D19-1339`.

David Silver, Satinder Singh, Doina Precup, and Richard S. Sutton. Reward is enough. *Artificial Intelligence*, 299:103535, 2021. ISSN 0004-3702. doi: https://doi.org/10.1016/j.artint.2021.103535. URL `https://www.sciencedirect.com/science/article/pii/S0004370221000862`.

Nisan Stiennon, Long Ouyang, Jeff Wu, Daniel M. Ziegler, Ryan Lowe, Chelsea Voss, Alec Radford, Dario Amodei, and Paul F. Christiano. Learning to summarize from human feedback. *CoRR*, abs/2009.01325, 2020. URL `https://arxiv.org/abs/2009.01325`.

Richard S. Sutton. *Temporal credit assignment in reinforcement learning*. PhD thesis, University of Massachusetts, 1984.

Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. The MIT Press, second edition, 2018. URL `http://incompleteideas.net/book/the-book-2nd.html`.

Richard S. Sutton, David McAllester, Satinder Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. In *Proceedings of the 12th International Conference on Neural Information Processing Systems*, NIPS'99, pp. 1057–1063, Cambridge, MA, USA, 1999. MIT Press.

Pradyumna Tambwekar, Murtaza Dhuliawala, Lara J. Martin, Animesh Mehta, Brent Harrison, and Mark O. Riedl. Controllable neural story plot generation via reward shaping. In Sarit Kraus (ed.), *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI 2019, Macao, China, August 10-16, 2019*, pp. 5982–5988. ijcai.org, 2019. doi: 10.24963/ijcai.2019/829. URL `https://doi.org/10.24963/ijcai.2019/829`.

Emanuel Todorov. Linearly-solvable markov decision problems. In B. Schölkopf, J. Platt, and T. Hoffman (eds.), *Advances in Neural Information Processing Systems*, volume 19. MIT Press, 2007. URL `https://proceedings.neurips.cc/paper/2006/file/d806ca13ca3449af72a1ea5aedbed26a-Paper.pdf`.

Lifu Tu, Richard Yuanzhe Pang, Sam Wiseman, and Kevin Gimpel. Engine: Energy-based inference networks for non-autoregressive machine translation. *ArXiv*, abs/2005.00850, 2020.

Ramakrishna Vedantam, C. Lawrence Zitnick, and Devi Parikh. Cider: Consensus-based image description evaluation. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2015, Boston, MA, USA, June 7-12, 2015*, pp. 4566–4575. IEEE Computer Society, 2015. doi: 10.1109/CVPR.2015.7299087. URL https://doi.org/10.1109/CVPR.2015.7299087.

Lex Weaver and Nigel Tao. The optimal reward baseline for gradient-based reinforcement learning. In *Proceedings of the Seventeenth Conference on Uncertainty in Artificial Intelligence*, UAI'01, pp. 538–545, San Francisco, CA, USA, 2001. Morgan Kaufmann Publishers Inc. ISBN 1558608001.

Ronald J. Williams. Reinforcement-learning connectionist systems. Technical report, Northeastern University, 1987. Technical Report NU-CCS-87-3.

Ronald J. Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Mach. Learn.*, 8:229–256, 1992a. doi: 10.1007/BF00992696. URL https://doi.org/10.1007/BF00992696.

Ronald J. Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. In *Machine Learning*, pp. 229–256, 1992b.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, and Jamie Brew. Huggingface's transformers: State-of-the-art natural language processing. *CoRR*, abs/1910.03771, 2019. URL http://arxiv.org/abs/1910.03771.

Yonghui Wu, Mike Schuster, Zhifeng Chen, Quoc V. Le, Mohammad Norouzi, Wolfgang Macherey, Maxim Krikun, Yuan Cao, Qin Gao, Klaus Macherey, Jeff Klingner, Apurva Shah, Melvin Johnson, Xiaobing Liu, Lukasz Kaiser, Stephan Gouws, Yoshikiyo Kato, Taku Kudo, Hideto Kazawa, Keith Stevens, George Kurian, Nishant Patil, Wei Wang, Cliff Young, Jason Smith, Jason Riesa, Alex Rudnick, Oriol Vinyals, Greg Corrado, Macduff Hughes, and Jeffrey Dean. Google's neural machine translation system: Bridging the gap between human and machine translation. *CoRR*, abs/1609.08144, 2016. URL http://arxiv.org/abs/1609.08144.

Yaoming Zhu, Sidi Lu, Lei Zheng, Jiaxian Guo, Weinan Zhang, Jun Wang, and Yong Yu. Texygen: A benchmarking platform for text generation models. In Kevyn Collins-Thompson, Qiaozhu Mei, Brian D. Davison, Yiqun Liu, and Emine Yilmaz (eds.), *The 41st International ACM SIGIR Conference on Research & Development in Information Retrieval, SIGIR 2018, Ann Arbor, MI, USA, July 08-12, 2018*, pp. 1097–1100. ACM, 2018. doi: 10.1145/3209978.3210080. URL https://doi.org/10.1145/3209978.3210080.

Daniel M. Ziegler, Nisan Stiennon, Jeffrey Wu, Tom B. Brown, Alec Radford, Dario Amodei, Paul Christiano, and Geoffrey Irving. Fine-tuning language models from human preferences. *CoRR*, abs/1909.08593, 2019. URL http://arxiv.org/abs/1909.08593.